Forces between magnets and multipole arrays of magnets: A Matlab implementation

Will Robertson

December 24, 2009

Abstract

This is the user guide and documented implementation of a set of Matlab functions for calculating the forces (and stiffnesses) between cuboid permanent magnets and between multipole arrays of the same.

This document is still evolving. The documentation for the source code, especially, is rather unclear/non-existent at present. The user guide, however, should contain the bulk of the information needed to use this code.

Contents

1	User guide				
	1.1 Forces between magnets				
	1.2 Forces between multipole arrays of magnets				
2	Meta-information				
3 Implementation					

1 User guide

(See Section 2 for installation instructions.)

1.1 Forces between magnets

The function magnetforces is used to calculate both forces and stiffnesses between magnets. The syntax is as follows:

```
forces = magnetforces(magnet_fixed, magnet_float, displ);
stiffnesses = magnetforces( ... , 'stiffness');
    [f s] = magnetforces( ... , 'force', 'stiffness');
```

magnetforces takes three mandatory inputs to specify the position and magnetisation of the first and second magnets and the displacement between them. Optional arguments appended indicate whether to calculate force or stiffness or both; the output arguments must match to reflect this choice. The force¹ is calculated as that imposed on the second magnet; for this reason, I often call the first magnet the 'fixed' magnet and the second 'floating'. If you wish to calculate the force on the first magnet instead, simply reverse the sign of the output.

Inputs and outputs The first two inputs are structures containing the following fields:

```
magnet.dim A (3 \times 1) vector of the side-lengths of the magnet.
```

magnet.magn The magnetisation magnitude of the magnet.

magnet.magdir A vector representing the direction of the magnetisation. This may be either a (3×1) vector in cartesian coordinates or a (2×1) vector in spherical coordinates.

In cartesian coordinates, the vector is interpreted as a unit vector; it is only used to calculate the direction of the magnetisation. In other words, writing [1;0;0] is the same as [2;0;0], and so on. In spherical coordinates (θ,ϕ) , θ is the vertical projection of the angle around the x-y plane $(\theta=0)$ coincident with the x-axis), and ϕ is the angle from the x-y plane towards the z-axis. In other words, the following unit vectors are equivalent:

```
(1,0,0)_{\text{cartesian}} \equiv (0,0)_{\text{spherical}}

(0,1,0)_{\text{cartesian}} \equiv (90,0)_{\text{spherical}}

(0,0,1)_{\text{cartesian}} \equiv (0,90)_{\text{spherical}}
```

N.B. θ and ϕ must be input in degrees, not radians. This seemingly odd decision was made in order to calculate quantities such as $\cos(\pi/2) = 0$ exactly rather than to machine precision.

 $^{^1{\}rm From}$ now I will omit most mention of calculating stiffnesses; assume whenever I say 'force' I mean 'force and stiffness'

The third mandatory input is displ, which is a matrix of displacement vectors between the two magnets. displ should be a $(3 \times D)$ matrix, where D is the number of displacements over which to calculate the forces. The size of displ dictates the size of the output force matrix; forces (etc.) will be also of size $(3 \times D)$.

Example Using magnetforces is rather simple. A magnet is set up as a simple structure like

```
magnet_fixed = struct(...
  'dim' , [0.02 0.012 0.006], ...
  'magn' , 0.38, ...
  'magdir', [0 0 1] ...
);
```

with something similar for magnet_float. The displacement matrix is then built up as a list of (3×1) displacement vectors, such as

```
displ = [0; 0; 1]*linspace(0.01,0.03);
```

And that's about it. For a complete example, see 'examples/magnetforces_example.m'.

1.2 Forces between multipole arrays of magnets

Because multipole arrays of magnets are more complex structures than single magnets, calculating the forces between them requires more setup as well. The syntax for calculating forces between multipole arrays follows the same style as for single magnets:

```
forces = multipoleforces(array_fixed, array_float, displ);
stiffnesses = multipoleforces( ... , 'stiffness');
    [f s] = multipoleforces( ... , 'force', 'stiffness');
```

Because multipole arrays can be defined in various ways, there are several overlapping methods for specifying the structures defining an array. Please escuse a certain amount of dryness in the information to follow; more inspiration for better documentation will come with feedback from those reading this document!

Linear arrays A minimal set of variables to define a linear multipole array are:

```
array.type Either 'linear-x', 'linear-y', or 'linear-z' to align the array with an axis.
```

array.face One of '+x', '+y', '+z', '-x', '-y', or '-z' to specify which direction the 'strong' side of the array faces.

array.msize A (3×1) vector defining the size of each magnet in the array.

array. Nmag The number of magnets composing the array.

array.magn The magnetisation magnitude of each magnet.

array.magdir_rotate The amount of rotation, in degrees, between successive magnets.

Notes:

- The array must face in a direction orthogonal to its alignment.
- 'up' and 'down' are defined as synonyms for facing '+z' and '-z', respectively, and 'linear' for array type 'linear-x'.
- Singleton input to msize assumes a cube-shaped magnet.

The variables above are the minimum set required to specify a multipole array. In addition, the following array variables may be used instead of or as well as to specify the information in a different way:

- array.magdir_first This is the angle of magnetisation in degrees around the direction of magnetisation rotation for the first magnet. It defaults to ±90° depending on the facing direction of the array.
- array.length The total length of the magnet array in the alignment direction of the array. If this variable is used then width and height (see below) must be as well.
- array.width The dimension of the array orthogonal to the alignment and facing directions.
- array.height The height of the array in the facing direction.
- array.wavelength The wavelength of magnetisation. Must be an integer number of magnet lengths.
- array. Nwaves The number of wavelengths of magnetisation in the array, which is probably always going to be an integer.
- array.Nmag_per_wave The number of magnets per wavelength of magnetisation (e.g., Nmag_per_wave of four is equivalent to magdir_rotate of 90°).
- array.gap Air-gap between successive magnet faces in the array. Defaults to zero.

Notes:

- array.mlength+array.width+array.height may be used as a synonymic replacement for array.msize.
- When using Nwaves, an additional magnet is placed on the end for symmetry.
- Setting gap does not affect length or mlength! That is, when gap is used, length refers to the total length of magnetic material placed end-to-end, not the total length of the array including the gaps.

Planar arrays Most of the information above follows for planar arrays, which can be thought of as a superposition of two orthogonal linear arrays.

array.type Either 'planar-xy', 'planar-yz', or 'planar-xz' to align the array with a plane.

array.width This is now the 'length' in the second spanning direction of the planar array. E.g., for the array 'planar-xy', 'length' refers to the x-direction and 'width' refers to the y-direction. (And 'height' is z.) array.mwidth Ditto, etc.

All other variables for linear arrays hold analogously for planar arrays; if desired, two-element input can be given to specify different properties in different directions.

Arbitrary arrays Until now we have assumed that magnet arrays are composed of magnets with identical sizes and regularly-varying magnetisation directions. Some facilities are provided to generate more general/arbitrary—shaped arrays.

array.type Should be 'generic' but may be omitted.

array.mcount The number of magnets in each direction, say (X, Y, Z).

array.msize_array An (X, Y, Z, 3)-length matrix defining the magnet sizes for each magnet of the array.

array.magdir_fn An anonymous function that takes three input variables (i, j, k) to calculate the magnetisation for the (i, j, k)-th magnet in the (x, y, z)-directions respectively.

array.magn At present this still must be singleton-valued. This will be amended
 at some stage to allow magn_array input to be analogous with msize and
 msize_array.

This approach for generating magnet arrays has been little-tested. Please inform me of associated problems if found.

2 Meta-information

Obtaining The latest version of this package may be obtained from the GitHub repository http://github.com/wspr/magcode with the following command:

git clone git://github.com/wspr/magcode.git

Installing It may be installed in Matlab simply by adding the 'matlab/' subdirectory to the Matlab path; e.g., adding the following to your startup.m file: (if that's where you cloned the repository)

addpath ~/magcode/matlab

Licensing This work may be freely modified and distributed under the terms and conditions of the Apache License v2.0.² This work is Copyright 2009–2010 by Will Robertson.

Contributing and feedback Please report problems and suggestions at the GitHub issue tracker.³

The Matlab source code is written using Matlabweb.⁴ After it is installed, use mtangle magnetforces to extract the Matlab files magnetforces.m and multipoleforces.m, as well as extracting the test suite (such as it is, for now). Running the Makefile with no targets (i.e., make) will perform this step as well as compiling the documentation you are currently reading.

3 Implementation

magnetforces

	Section	Page
Calculating forces between magnets	3	7
Variables and data structures	5	9
Wrangling user input and output	7	11
The actual mechanics	9	12
Functions for calculating forces and stiffnesses	16	15
Setup code	27	21
Test files	35	24
Force testing	37	24
Forces between (multipole) magnet arrays	56	34
Actual calculation of the forces	59	36
From user input to array generation	61	38
Test files for multipole arrays	70	49

 $^{^2}$ http://www.apache.org/licenses/LICENSE-2.0

³http://github.com/wspr/magnetocode/issues

⁴http://www.ctan.org/tex-archive/web/matlabweb/

1. About this file. This is a 'literate programming' approach to writing Matlab code using Matlabes⁵. To be honest I don't know if it's any better than simply using the Matlab programming language directly. The big advantage for me is that you have access to the entire IATEX document environment, which gives you access to vastly better tools for cross-referencing, maths typesetting, structured formatting, bibliography generation, and so on.

The downside is obviously that you miss out on Matlab's IDE with its integrated M-Lint program, debugger, profiler, and so on. Depending on one's work habits, this may be more or less of limiting factor to using literate programming in this way.

2. This work consists of the source file magnetforces.web and its associated derived files. It is released under the Apache License v2.0.⁶

This means, in essense, that you may freely modify and distribute this code provided that you acknowledge your changes to the work and retain my copyright. See the License text for the specific language governing permissions and limitations under the License.

Copyright © 2009 Will Robertson.

3. Calculating forces between magnets. This is the source of some code to calculate the forces and/or stiffnesses between two cuboid-shaped magnets with arbitary displacements and magnetisation direction. (A cuboid is like a three dimensional rectangle; its faces are all orthogonal but may have different side lengths.)

⁵http://tug.ctan.org/pkg/matlabweb

⁶http://www.apache.org/licenses/LICENSE-2.0

4. The main function is magnetforces, which takes three mandatory arguments: magnet_fixed, magnet_float, and displ. These will be described in more detail below.

Optional string arguments may be any combination of 'force', and/or 'stiffness' to indicate which calculations should be output. If no calculation is specified, 'force' is the default.

Inputs:	magnet_fixed	structure describing first magnet
	magnet_float	structure describing the second magnet
	displ	displacement between the magnets
	$[what\ to\ calculate]$	'force' and/or 'stiffness'
Outputs:	forces	forces on the second magnet
	stiffnesses	stiffnesses on the second magnet
Magnet properties:	dim	size of each magnet
	magn	magnetisation magnitude
	magdir	magnetisation direction

5. Variables and data structures. First of all, address the data structures required for the input and output. Because displacement of a single magnet has three components, plus sizes of the faces another three, plus magnetisation strength and direction (two) makes nine in total, we use one of Matlab's structures to pass the information into the function. Otherwise we'd have an overwhelming number of input arguments.

The input variables *magnet.dim* should be the entire side lengths of the magnets; these dimensions are halved when performing all of the calculations. (Because that's just how the maths is.)

We use spherical coordinates to represent magnetisation angle, where *phi* is the angle from the horizontal plane $(-\pi/2 \le \phi \le \pi/2)$ and θ is the angle around the horizontal plane $(0 \le \theta \le 2\pi)$. This follows Matlab's definition; other conventions are commonly used as well. Remember:

```
(1,0,0)_{\text{cartesian}} \equiv (0,0,1)_{\text{spherical}}

(0,1,0)_{\text{cartesian}} \equiv (\pi/2,0,1)_{\text{spherical}}

(0,0,1)_{\text{cartesian}} \equiv (0,\pi/2,1)_{\text{spherical}}
```

Cartesian components can also be used as input as well, in which case they are made into a unit vector before multiplying it by the magnetisation magnitude. Either way (between spherical or cartesian input), J1 and J2 are made into the magnetisation vectors in cartesian coordinates.

```
⟨Initialise main variables 5⟩ ≡
size1 = reshape(magnet_fixed.dim/2, [3 1]);
size2 = reshape(magnet_float.dim/2, [3 1]);
J1 = resolve_magnetisations(magnet_fixed.magn, magnet_fixed.magdir);
J2 = resolve_magnetisations(magnet_float.magn, magnet_float.magdir);
See also section 25.
```

This code is used in section 4.

6. Gotta check the displacement input for both functions. After sorting that out, we can initialise the output variables now we know how big they need to me.

```
\langle Organise input displacements _{6}\rangle \equiv
  if size(displ, 1) \equiv 3
          % all good
  elseif size(displ, 2) \equiv 3
     displ = transpose(displ);
  else
     error(['Displacements\_matrix\_should\_be\_of\_size\_(3,\_D)', \dots
          'where \square D \sqcup is \sqcup the \sqcup number \sqcup of \sqcup displacements.']
  end
  Ndispl = size(displ, 2);
  if \ \textit{calc\_force\_bool}
     forces\_out = repmat(NaN, [3 Ndispl]);
  end
  if calc_stiffness_bool
     stiffnesses\_out = repmat(NaN, [3 Ndispl]);
  end
```

7. Wrangling user input and output. We now have a choice of calculations to take based on the user input. This chunk and the next are used in both magnetforces.m and multipoleforces.m.

```
\langle \text{ Parse calculation args } 7 \rangle \equiv
  debug\_disp = @(str) disp([]);
  calc\_force\_bool = false;
  calc\_stiffness\_bool = false;
  for ii = 1: length (varargin)
     switch varargin{ii}
     case 'debug'
        debug\_disp = @(str) disp(str);
     case 'force'
        calc\_force\_bool = true;
     case 'stiffness'
        calc\_stiffness\_bool = true;
     otherwise
        error(['Unknown_{\square}calculation_{\square}option_{\square}''', varargin\{ii\}, ''''])
     end
  end
  if \  \, \texttt{NOT} \,\, \textit{calc\_force\_bool} \,\, \land \,\, \texttt{NOT} \,\, \textit{calc\_stiffness\_bool}
  calc\_force\_bool = true;
  end
```

This code is used in sections 4 and 56.

8. After all of the calculations have occured, they're placed back into varargout. (This happens at the very end, obviously.)

```
⟨Return all results 8⟩ ≡

varargout{1} = forces_out;
for ii = 1: length (varargin)
    switch varargin{ii}
    case 'force'
     varargout{ii} = forces_out;
    case 'stiffness'
     varargout{ii} = stiffnesses_out;
    end
end
```

This code is used in sections 4 and 56.

9. The actual mechanics. The idea is that a multitude of displacements can be passed to the function and we iterate to generate a matrix of vector outputs.

```
\langle Calculate for each displacement |9\rangle \equiv
  if calc_force_bool
     for ii = 1: Ndispl
       forces\_out(:, ii) = single\_magnet\_force(displ(:, ii));
     end
  end
  if calc_stiffness_bool
     for ii = 1: Ndispl
       stiffnesses\_out(:, ii) = single\_magnet\_stiffness(displ(:, ii));
     end
  end
This code is used in section 4.
       And this is what does the calculations.
\langle Function for single force calculation 10 \rangle \equiv
  function force_out = single_magnet_force(displ)
       force_components = repmat(NaN, [9 3]);
        ⟨ Precompute displacement rotations 30 ⟩
        (Print diagnostics 33)
        \langle \text{ Calculate } x \text{ force } 13 \rangle
        \langle \text{ Calculate } y \text{ force } 14 \rangle
        \langle \text{ Calculate } z \text{ force } 12 \rangle
       force_out = sum(force_components);
       end
This code is used in section 4.
11.
       And this is what does the calculations for stiffness.
\langle Function for single stiffness calculation | | |
  function \ stiffness\_out = single\_magnet\_stiffness(displ)
       stiffness\_components = repmat(NaN, [9 3]);
        ⟨ Precompute displacement rotations 30 ⟩
        (Print diagnostics 33)
        \langle Calculate stiffnesses 15\rangle
       stiffness_out = sum(stiffness_components);
       end
This code is used in section 4.
```

12. The easy one first, where our magnetisation components align with the direction expected by the force functions.

```
 \begin{split} &\langle \text{Calculate } z \text{ force } \underline{12} \rangle \equiv \\ & \text{ } debug\_disp(\texttt{'z-z_lforce:'}) \\ & \text{ } force\_components(9,:) = forces\_calc\_z\_z(size1, size2, displ, J1, J2); \\ & \text{ } debug\_disp(\texttt{'z-y_lforce:'}) \\ & \text{ } force\_components(8,:) = forces\_calc\_z\_y(size1, size2, displ, J1, J2); \\ & \text{ } debug\_disp(\texttt{'z-x_lforce:'}) \\ & \text{ } force\_components(7,:) = forces\_calc\_z\_x(size1, size2, displ, J1, J2); \\ & \text{ } This code is used in section 10. \end{split}
```

13. The other forces (i.e., x and y components) require a rotation to get the magnetisations correctly aligned. In the case of the magnet sizes, the lengths are just flipped rather than rotated (in rotation, sign is important). After the forces are calculated, rotate them back to the original coordinate system.

```
 \begin{split} &\langle \text{Calculate } x \text{ force } \textbf{13} \rangle \equiv \\ & \text{ } debug\_disp(\text{`Forces}\_x-x:\text{'}) \\ & \text{ } force\_components(1,:) = \dots \\ & \text{ } rotate\_z\_to\_x(\text{forces}\_calc\_z\_z(\text{size1}\_x, \text{size2}\_x, d\_x, J1\_x, J2\_x)); \\ & \text{ } debug\_disp(\text{`Forces}\_x-y:\text{'}) \\ & \text{ } force\_components(2,:) = \dots \\ & \text{ } rotate\_z\_to\_x(\text{forces}\_calc\_z\_y(\text{size1}\_x, \text{size2}\_x, d\_x, J1\_x, J2\_x)); \\ & \text{ } debug\_disp(\text{`Forces}\_x-z:\text{'}) \\ & \text{ } force\_components(3,:) = \dots \\ & \text{ } rotate\_z\_to\_x(\text{forces}\_calc\_z\_x(\text{size1}\_x, \text{size2}\_x, d\_x, J1\_x, J2\_x)); \\ \end{split}  This code is used in section 10.
```

14. Same again, this time making y the 'up' direction.

```
 \begin{split} &\langle \text{Calculate } y \text{ force } \underline{14} \rangle \equiv \\ & \text{ } debug\_disp(\text{`Forces}_{\square}y-x:\text{'}) \\ & \text{ } force\_components(4,:) = \dots \\ & \text{ } rotate\_z\_to\_y(\text{forces}\_calc\_z\_x(\text{size1}\_y, \text{size2}\_y, d\_y, J1\_y, J2\_y)); \\ & \text{ } debug\_disp(\text{`Forces}_{\square}y-y:\text{'}) \\ & \text{ } force\_components(5,:) = \dots \\ & \text{ } rotate\_z\_to\_y(\text{forces}\_calc\_z\_z(\text{size1}\_y, \text{size2}\_y, d\_y, J1\_y, J2\_y)); \\ & \text{ } debug\_disp(\text{`Forces}_{\square}y-z:\text{'}) \\ & \text{ } force\_components(6,:) = \dots \\ & \text{ } rotate\_z\_to\_y(\text{forces}\_calc\_z\_y(\text{size1}\_y, \text{size2}\_y, d\_y, J1\_y, J2\_y)); \\ \end{aligned}
```

This code is used in section 10.

15. Same as all the above. Except not really. Because stiffness isn't the same sort of vector quantity (if at all, really) as force, we simply 'flip' the directions around between different coordinate systems rather than rotate them.

```
\langle \text{ Calculate stiffnesses } 15 \rangle \equiv
 debug_disp('x-x_stiffness:')
 stiffness\_components(1, :) = ...
 swap_x_z(stiffnesses_calc_z_z(size1_x, size2_x, d_x, J1_x, J2_x));
 debug disp('x-y_stiffness:')
 stiffness\_components(2, :) = \dots
 swap_x_z(stiffnesses_calc_z_y(size1_x, size2_x, d_x, J1_x, J2_x));
 debug_disp('x-z_stiffness:')
 stiffness\_components(3, :) = \dots
 swap x z(stiffnesses calc z x(size1 x, size2 x, d x, J1 x, J2 x));
 debug_disp('y-x_stiffness:')
 stiffness\_components(4, :) = \dots
 swap\_y\_z(stiffnesses\_calc\_z\_x(size1\_y, size2\_y, d\_y, J1\_y, J2\_y));
 debug_disp('y-y_stiffness:')
 stiffness\_components(5, :) = \dots
 swap_y_z(stiffnesses_calc_z_z(size1_y, size2_y, d_y, J1_y, J2_y));
 debug_disp('y-z_stiffness:')
 stiffness\_components(6,:) = \dots
 swap_y_z(stiffnesses_calc_z_y(size1_y, size2_y, d_y, J1_y, J2_y));
 debug_disp('z-x_stiffness:')
 stiffness components (7, :) = \dots
 stiffnesses_calc_z_x(size1, size2, displ, J1, J2);
 debug_disp('z-y_stiffness:')
 stiffness components (8, :) = \dots
 stiffnesses_calc_z_y(size1, size2, displ, J1, J2);
 debug disp('z-z_|stiffness:')
 stiffness components (9, :) = \dots
 stiffnesses_calc_z_z(size1, size2, displ, J1, J2);
```

This code is used in section 11.

16. Functions for calculating forces and stiffnesses. The calculations for forces between differently-oriented cuboid magnets are all directly from the literature. The stiffnesses have been derived by differentiating the force expressions, but that's the easy part.

```
\langle \mbox{ Functions for calculating forces and stiffnesses } \mbox{ $16$} \rangle \equiv \\ \langle \mbox{ Parallel magnets force calculation } \mbox{ $17$} \rangle \\ \langle \mbox{ Orthogonal magnets force calculation } \mbox{ $18$} \rangle \\ \langle \mbox{ Parallel magnets stiffness calculation } \mbox{ $21$} \rangle \\ \langle \mbox{ Orthogonal magnets stiffness calculation } \mbox{ $22$} \rangle \\ \langle \mbox{ Helper functions } \mbox{ $31$} \rangle \\ \mbox{ This code is used in section $4$}.
```

17. The expressions here follow directly from Akoun and Yonnet [1].

```
Inputs:
            size1 = (a, b, c)
                                          the half dimensions of the fixed magnet
            size2 = (A, B, C)
                                          the half dimensions of the floating magnet
            displ=(dx, dy, dz)
                                          distance between magnet centres
                                          magnetisations of the magnet in the z-direction
            (J, J2)
 Outputs:
            forces\_xyz=(Fx, Fy, Fz)
                                          Forces of the second magnet
\langle \text{ Parallel magnets force calculation } 17 \rangle \equiv
 function calc out = forces calc z z(size1, size2, offset, J1, J2)
      J1 = J1(3);
      J2 = J2(3);
      ⟨Initialise subfunction variables 24⟩
      component\_x = \dots
      +multiply_x_log_y(0.5*(v.^2 - w.^2), r - u)...
      +multiply_x_log_y(u \cdot * v, r - v)...
      +v * w * atan1(u * v, r * w)...
      +0.5*r.*u;
      component_y = \dots
      +multiply x log y(0.5*(u.^2 - w.^2), r - v)...
      +multiply_x_log_y(u \cdot * v, r - u)...
      +u * w * atan1(u * v, r * w)...
      +0.5*r.*v;
      component\_z = \dots
      -multiply_x_log_y(u \cdot * w, r - u)...
      -multiply_x_log_y(v \cdot * w, r - v)...
      +u .* v .* atan1(u .* v, r .* w)...
      -r \cdot *w;
      ⟨Finish up 26⟩
```

18. Orthogonal magnets forces given by Yonnet and Allag [2]. \langle Orthogonal magnets force calculation $|18\rangle \equiv$ function calc_out = forces_calc_z_y(size1, size2, offset, J1, J2) J1 = J1(3);J2 = J2(2);⟨Initialise subfunction variables 24⟩ $component_x = \dots$ $-multiply_x_log_y(v.*w, r-u)...$ +multiply_x_log_y($v \cdot * u, r + w$)... +multiply_x_log_y($u \cdot * w, r + v$)... $-0.5*u.^2.*$ atan1(v.*w, u.*r)... $-0.5*v.^2.*$ atan1 (u.*w, v.*r)... $-0.5*w.^2.*atan1(u.*v, w.*r);$ $component_y = \dots$ 0.5*multiply_x_log_y($u \cdot ^2 - v \cdot ^2, r + w$)... -multiply_x_log_y($u \cdot * w, r - u$)... $-u * v * atan1(u * w, v * r) \dots$ -0.5*w.*r; $component_z = \dots$ $0.5*multiply_x_log_y(u.^2 - w.^2, r + v)...$ -multiply_x_log_y($u \cdot * v, r - u$)... -u .* w .* atan1(u .* v, w .* r) ...-0.5*v.*r;allag correction = -1; component_x = allag_correction*component_x; $component_y = allag_correction*component_y;$ component_z = allag_correction*component_z; $\langle \text{Finish up } 26 \rangle$

See also section 20.

This code is used in section 16.

19. This is the same calculation with Janssen's equations instead. By default this code never runs, but if you like it can be enabled to prove that the equations are consistent.

```
\langle Test against Janssen results | 19\rangle \equiv
 S = u:
 T = v:
 U=w:
 R = r;
 component_x_{ii} = \dots
 (0.5*atan1(U, S) + 0.5*atan1(T .* U, S .* R)) .* S .^ 2 ...
 +T.*S-3/2*U.*S-multiply_x_log_y(S.*T, U+R)-T.^2.*atan1(S, T)
      T)\dots
 +U .* (U .* (...
      0.5*\mathtt{atan1}(S,U) + 0.5*\mathtt{atan1}(S.*T,U.*R)\dots
    -multiply_x_log_y(T, S+R) + multiply_x_log_y(S, R-T) \dots
 +0.5*T.^2.*atan1(S.*U, T.*R)...
 component\_y\_ii = \dots
 0.5*U.*(R-2*S)+...
 multiply_x_log_y(0.5*(T . ^2 - S . ^2), U + R) + . . .
 S .* T .* (atan1(U, T) + atan1(S .* U, T .* R)) + ...
 multiply_x_log_y(S .* U, R - S) ...
 component\_z\_ii = \dots
 0.5*T .* (R - 2*S) + ...
 \verb|multiply_x_log_y(0.5*(U.^2-S.^2),T+R)+...|
 S .* U .* (atan1(T, U) + atan1(S .* T, U .* R)) + ...
 multiply_x_log_y(S * T, R - S) \dots
 xx = index\_sum .* component\_x;
 xx_ii = index_sum .* component_x_ii;
 assert(abs(sum(xx(:)) - sum(xx_ii(:))) < 1 \cdot 10^{-8})
 yy = index_sum .* component_y;
 yy_ii = index_sum .* component_y_ii;
 assert(abs(sum(yy(:)) - sum(yy_ii(:))) < 1 \cdot 10^{-8})
 zz = index_sum .* component_z;
 zz_ii = index_sum .* component_z_ii;
 assert(abs(sum(zz(:)) - sum(zz_ii(:))) < 1 \cdot 10^{-8})
 component\_x = component\_x\_ii;
 component_y = component_y_ii;
 component_z = component_z_{ii};
```

20. The improvement in processing time between typing in the actual equals compared to just transforming the z-y case isn't worth the tedium of actually doing it.

doing it. $\langle \text{Orthogonal magnets force calculation } 18 \rangle +\equiv$

```
\begin{split} & \textbf{function} \ \ \textit{calc\_out} = \textit{forces\_calc\_z\_x}(\textit{size1}, \textit{size2}, \textit{offset}, \textit{J1}, \textit{J2}) \\ & \textit{forces\_xyz} = \textit{forces\_calc\_z\_y}(\dots \\ & \textit{swap\_x\_y}(\textit{size1}), \textit{swap\_x\_y}(\textit{size2}), \textit{rotate\_x\_to\_y}(\textit{offset}), \dots \\ & \textit{J1}, \textit{rotate\_x\_to\_y}(\textit{J2})); \\ & \textit{calc\_out} = \textit{rotate\_y\_to\_x}(\textit{forces\_xyz}); \\ & \textbf{end} \end{split}
```

21. Stiffness calculations are simply differentiated (in Mathematica) from the forces.

```
\langle Parallel magnets stiffness calculation |21\rangle \equiv
```

```
function calc_out = stiffnesses_calc_z_z(size1, size2, offset, J1, J2) J1 = J1(3);
J2 = J2(3);
\langle \text{Initialise subfunction variables } 24 \rangle
component_x = \dots
-r \dots
-(u ^2 \cdot v) \cdot / (u ^2 + w ^2) \dots
-v \cdot * \log(r - v);
component_y = \dots
-r \dots
-(v ^2 \cdot v) \cdot / (v ^2 + w ^2) \dots
-u \cdot * \log(r - u);
component_z = -component_x - component_y;
\langle \text{Finish up } 26 \rangle
```

This code is used in section 16.

22. Orthogonal magnets stiffnesses derived from Yonnet and Allag [2]. First the z-y magnetisation.

```
the z-y magnetisation.

\langle Orthogonal magnets stiffness calculation 22\rangle \equiv

function calc_out = stiffnesses_calc_z_y(size1, size2, offset, J1, J2)
```

J2 = J2(2); (Initialise subfunction variables 24)

```
 \begin{array}{l} {\rm component\_x} = ((u.^2.*v)./(u.^2+v.^2)) + (u.^2.*w)./(u.^2+w.^2) \ldots \\ -u.* \\ {\rm atan1} (v.*w, r.*u) + \\ {\rm multiply\_x\_log\_y}(w, r+v) + \ldots \\ + \\ {\rm multiply\_x\_log\_y}(v, r+w); \\ {\rm component\_y} = -v/2 + (u.^2.*v)./(u.^2+v.^2) - (u.*v.*w)./\\ (v.^2+w.^2) \ldots \\ -u.* \\ {\rm atan1} (u.*w, r.*v) - \\ {\rm multiply\_x\_log\_y}(v, r+w); \\ {\rm component\_z} = -\\ {\rm component\_x} - \\ {\rm component\_y}; \\ \end{array}
```

See also section 23.

This code is used in section 16.

 $\langle \text{Finish up } 26 \rangle$

J1 = J1(3);

23. Now the z-x magnetisation, which is z-y rotated.

 $\langle \text{Orthogonal magnets stiffness calculation } 22 \rangle + \equiv$

```
\begin{split} & \textbf{function} \ \ \textit{calc\_out} = \textit{stiffnesses\_calc\_z\_x}(\textit{size1}, \textit{size2}, \textit{offset}, \textit{J1}, \textit{J2}) \\ & \textit{stiffnesses\_xyz} = \textit{stiffnesses\_calc\_z\_y}(\dots \\ & \textit{swap\_x\_y}(\textit{size1}), \textit{swap\_x\_y}(\textit{size2}), \textit{rotate\_x\_to\_y}(\textit{offset}), \dots \\ & \textit{J1}, \textit{rotate\_x\_to\_y}(\textit{J2})); \\ & \textit{calc\_out} = \textit{swap\_x\_y}(\textit{stiffnesses\_xyz}); \\ & \textbf{end} \end{split}
```

24. Some shared setup code. First **return** early if either of the magnetisations are zero — that's the trivial solution. Assume that the magnetisation has already been rounded down to zero if necessary; i.e., that we don't need to check for J1 or J2 are less than $1 \cdot 10^{-12}$ or whatever.

This code is used in sections 17, 18, 21, and 22.

25. Here are some variables used above that only need to be computed once. The idea here is to vectorise instead of using **for** loops because it allows more convenient manipulation of the data later on.

```
\langle Initialise main variables 5\rangle +\equiv magconst = 1/(4*\pi*(4*\pi*1\cdot 10^{-7})); [index_i, index_j, index_k, index_l, index_p, index_q] = ndgrid([0 1]); index_sum = (-1).^(index_i + index_j + index_k + index_l + index_p + index_q);
```

26. And some shared finishing code.

```
\label{eq:component_x} \langle \operatorname{Finish\ up\ 26} \rangle \equiv \\ component\_x = \operatorname{index\_sum\ .*\ component\_x}; \\ component\_y = \operatorname{index\_sum\ .*\ component\_y}; \\ component\_z = \operatorname{index\_sum\ .*\ component\_z}; \\ calc\_out = J1*J2*magconst\ .*\ ..\ . \\ [\operatorname{sum\ (component\_x\ (:))}; \\ \operatorname{sum\ (component\_y\ (:))}; \\ \operatorname{sum\ (component\_z\ (:))}; \\ \operatorname{sum\ (component\_z\ (:))}; \\ \operatorname{debug\_disp\ (calc\_out')} \\ \operatorname{end} \\ \end{cases}
```

This code is used in sections 17, 18, 21, and 22.

27. Setup code.

28. Magnetisation directions are specified in either cartesian or spherical coordinates. Since this is shared code, it's sent to the end to belong in a nested function.

We don't use Matlab's sph2cart here, because it doesn't calculate zero accurately (because it uses radians and $\cos(\pi/2)$ can only be evaluated to machine precision of pi rather than symbolically).

 \langle Function for resolving magnetisations $|28\rangle \equiv$

```
function J = resolve\_magnetisations(magn, magdir)
    if length(magdir) \equiv 2
      J_r = magn;
      J_t = magdir(1);
      J_p = magdir(2);
      J = [J_r * cosd(J_p) * cosd(J_t); \dots
         J_r*cosd(J_p)*sind(J_t); \dots
         J_r*sind(J_p);
    else
      if all(magdir \equiv [0 \ 0 \ 0])
         J = [0; 0; 0];
      else
         J = magn*magdir/norm(magdir);
         J = reshape(J, [3\ 1]);
      end
    end
    end
```

This code is used in section 4.

29. Forces due to magnetisations in x and y are calculated by rotating the original expressions. The rotated magnet sizes and magnetisation vectors are calculated here once only.

The rotation matrices are precalculated to avoid performing the matrix multiplications each time.

```
\langle \text{ Precompute rotations } 29 \rangle \equiv
 swap_x_y = @(vec) vec([2 1 3]);
 swap x z = @(vec) vec([3\ 2\ 1]);
 swap\_y\_z = @(vec) \ vec([1\ 3\ 2]);
 rotate\_z\_to\_x = @(vec) [vec(3); vec(2); -vec(1)];
                                                                 % Ry(90)
 rotate_x_to_z = @(vec)[-vec(3); vec(2); vec(1)];
                                                                 % Ry(-90)
 rotate\_y\_to\_z = @(vec) [vec(1); -vec(3); vec(2)];
                                                                 % Rx(90)
 rotate\_z\_to\_y = @(vec) [vec(1); vec(3); -vec(2)];
                                                                 % Rx(-90)
 rotate_x_to_y = @(vec)[-vec(2); vec(1); vec(3)];
                                                                 % Rz(90)
 rotate\_y\_to\_x = @(vec) [vec(2); -vec(1); vec(3)];
                                                                 % Rz(-90)
 size1\_x = swap\_x\_z(size1);
 size2\_x = swap\_x\_z(size2);
  J1_x = rotate_x_to_z(J1);
 J2\_x = rotate\_x\_to\_z(J2);
 size1_y = swap_y_z(size1);
 size2_y = swap_y_z(size2);
 J1\_y = rotate\_y\_to\_z(J1);
  J2\underline{y} = rotate\underline{y}\underline{to}\underline{z}(J2);
```

This code is used in section 4.

30. And the rotated displacement vectors are calculated once per loop:

```
\langle Precompute displacement rotations 30 \rangle \equiv
```

```
d_x = rotate_x_to_z(displ);

d_y = rotate_y_to_z(displ);
```

This code is used in sections 10 and 11.

31. The equations contain two singularities. Specifically, the equations contain terms of the form $x \log(y)$, which becomes NaN when both x and y are zero since $\log(0)$ is negative infinity.

This function computes $x \log(y)$, special-casing the singularity to output zero, instead. (This is indeed the value of the limit.)

See also section 32.

This code is used in section 16.

32. Also, we're using atan instead of atan2 (otherwise the wrong results are calculated — I guess I don't totally understand that), which becomes a problem when trying to compute atan(0/0) since 0/0 is NaN.

This function computes atan but takes two arguments.

33. Let's print some information to the terminal to aid debugging. This is especially important (for me) when looking at the rotated coordinate systems.

```
⟨Print diagnostics 33⟩ ≡

debug_disp('⊔⊔')

debug_disp('CALCULATING⊔THINGS')

debug_disp('Displacement:')

debug_disp(displ')

debug_disp('Magnetisations:')

debug_disp(J1')

debug_disp(J2')

This code is used in sections 10 and 11.
```

34. When users type help magnetforces this is what they see.

```
\langle Matlab help text (forces) 34\,\rangle \equiv %% MAGNETFORCES Calculate forces between two cuboid magnets % % Finish this off later. %
```

This code is used in section 4.

35. Test files. The chunks that follow are designed to be saved into individual files and executed automatically to check for (a) correctness and (b) regression problems as the code evolves.

How do I know if the code produces the correct forces? Well, for many cases I can compare with published values in the literature. Beyond that, I'll be setting up some tests that I can logically infer should produce the same results (such as mirror-image displacements) and test that.

There are many Matlab unit test frameworks but I'll be using a fairly low-tech method. In time this test suite should be (somehow) useable for all implementations of magnetocode, not just Matlab. But I haven't thought about doing anything like that, yet.

36. Because I'm lazy, just run the tests manually for now. This script must be run twice if it updates itself.

```
⟨testall.m 36⟩ ≡
  clc;
  magforce_test001a
  magforce_test001b
  magforce_test001c
  magforce_test001d
See also section 70.
```

37. Force testing. This test checks that square magnets produce the same forces in the each direction when displaced in positive and negative x, y, and z directions, respectively. In other words, this tests the function forces_calc_z_y directly. Both positive and negative magnetisations are used.

```
\langle magforce\_test001a.m \quad 37 \rangle \equiv
  disp('======;')
  fprintf('TEST_001a:_'')
  magnet_fixed.dim = [0.04 \ 0.04 \ 0.04];
  magnet_float.dim = magnet_fixed.dim;
  magnet\_fixed.magn = 1.3;
  magnet\_float.magn = 1.3;
  offset = 0.1;
  \langle \text{ Test } z - z \text{ magnetisations } 38 \rangle
  (Assert magnetisations tests 46)
  \langle \text{ Test } x - x \text{ magnetisations } 39 \rangle
  (Assert magnetisations tests 46)
  \langle \text{ Test } y - y \text{ magnetisations } 40 \rangle
  (Assert magnetisations tests 46)
  fprintf('passed\n')
  disp('=======,')
```

```
38.
       Testing vertical forces.
\langle \text{ Test } z - z \text{ magnetisations } 38 \rangle \equiv
  f = [];
  for ii = [1, -1]
     magnet\_fixed.magdir = [0 ii*90];
                                                   % ±z
     for jj = [1, -1]
       magnet\_float.magdir = [0 jj*90];
       for kk = [1, -1]
          displ = kk*[0\ 0\ offset];
          f(:, end + 1) = magnetforces(magnet_fixed, magnet_float, displ);
       end
     end
  end
  dirforces = chop(f(3, :), 8);
  otherforces = f([1\ 2],:);
This code is used in section 37.
       Testing horizontal x forces.
\langle \text{ Test } x - x \text{ magnetisations } 39 \rangle \equiv
  f = [];
  for ii = [1, -1]
     magnet\_fixed.magdir = [90 + ii*90 0];
                                                         % ±x
     for jj = [1, -1]
       magnet\_float.magdir = [90 + jj*90 \ 0];
       for kk = [1, -1]
          displ = kk*[offset 0 0];
          f(:, end + 1) = magnetforces(magnet_fixed, magnet_float, displ);
       end
     end
  \quad \mathbf{end} \quad
  dirforces = chop(f(1, :), 8);
  otherforces = f([2\ 3],:);
This code is used in section 37.
```

```
40.
       Testing horizontal y forces.
\langle \text{Test } y - y \text{ magnetisations } 40 \rangle \equiv
  f = [];
  for ii = [1, -1]
                                                  % ±y
     magnet\_fixed.magdir = [ii*90\ 0];
     for jj = [1, -1]
       magnet\_float.magdir = [jj*90\ 0];
       for kk = [1, -1]
          displ = kk*[0 offset 0];
          f(:, end + 1) = magnetforces(magnet_fixed, magnet_float, displ);
       end
     end
  end
  dirforces = chop(f(2, :), 8);
  otherforces = f([1\ 3],:);
This code is used in section 37.
       This test does the same thing but for orthogonally magnetised magnets.
\langle magforce\_test001b.m | 41 \rangle \equiv
  disp('======;')
  fprintf('TEST_001b:_'')
  magnet_fixed.dim = [0.04 \ 0.04 \ 0.04];
  magnet_float.dim = magnet_fixed.dim;
  magnet\_fixed.magn = 1.3;
  magnet\_float.magn = 1.3;
  \langle \text{ Test ZYZ } 42 \rangle
  ⟨ Assert magnetisations tests 46⟩
  \langle \text{ Test ZXZ } 43 \rangle
  \langle Assert magnetisations tests 46\rangle
  \langle \text{ Test ZXX } 45 \rangle
  ⟨ Assert magnetisations tests 46⟩
  \langle \text{ Test ZYY } 44 \rangle
  (Assert magnetisations tests 46)
  fprintf('passed\n')
  disp('======;')
```

```
42.
       z-y magnetisations, z displacement.
\langle \text{ Test ZYZ } 42 \rangle \equiv
  fzyz = [];
  for ii = [1, -1]
    for jj = [1, -1]
       for kk = [1, -1]
         magnet\_fixed.magdir = ii*[0 90];
                                                     \% \pm z
         magnet\_float.magdir = jj*[90\ 0];
                                                     % ±y
         displ = kk*[0 \ 0 \ 0.1];
                                     % ±z
         fzyz(:, end + 1) = magnetforces(magnet_fixed, magnet_float,
       end
    end
  end
  dirforces = chop(fzyz(2, :), 8);
  otherforces = fzyz([1 \ 3], :);
This code is used in section 41.
43.
       z-x magnetisations, z displacement.
\langle \text{ Test ZXZ } 43 \rangle \equiv
  fzxz = [];
  for ii = [1, -1]
    for jj = [1, -1]
       for kk = [1, -1]
         magnet\_fixed.magdir = ii*[0 90];
         magnet\_float.magdir = [90 + jj*90 0];
                                                          % ±x
         displ = kk*[0.1 \ 0 \ 0];
         fzxz(:, end + 1) = magnetforces(magnet_fixed, magnet_float,
               displ);
       end
    end
  end
  dirforces = chop(fzxz(3, :), 8);
  otherforces = fzxz([1\ 2],:);
This code is used in section 41.
```

```
z-y magnetisations, y displacement.
\langle \text{ Test ZYY } 44 \rangle \equiv
  fzyy = [];
  for ii = [1, -1]
    for jj = [1, -1]
       for kk = [1, -1]
         magnet\_fixed.magdir = ii*[0 90];
                                                     \% \pm z
         magnet\_float.magdir = jj*[90\ 0];
                                                     % ±y
         displ = kk*[0 \ 0.1 \ 0];
                                     % ±y
         fzyy(:, end + 1) = magnetforces(magnet_fixed, magnet_float,
       end
    end
  end
  dirforces = chop(fzyy(3, :), 8);
  otherforces = fzyy([1\ 2],:);
This code is used in section 41.
45.
       z-x magnetisations, x displacement.
\langle \text{ Test ZXX } 45 \rangle \equiv
  fzxx = [];
  for ii = [1, -1]
    for jj = [1, -1]
       for kk = [1, -1]
         magnet\_fixed.magdir = ii*[0 90];
         magnet\_float.magdir = [90 + jj*90 0];
                                                          % ±x
         displ = kk*[0\ 0\ 0.1];
                                      \% \pm z
         fzxx(:, end + 1) = magnetforces(magnet_fixed, magnet_float,
              displ);
       end
    end
  end
  dirforces = chop(fzxx(1, :), 8);
  otherforces = fzxx([2\ 3],:);
This code is used in section 41.
```

```
46.
       The assertions, common between directions.
\langle Assert magnetisations tests 46 \rangle \equiv
  assert(...
     all(abs(otherforces(:)) < 1 \cdot 10^{-11}), \dots
     \verb|'Orthogonal| | forces | | should | | be | | zero' ... |
     )
  assert(...
     all(abs(dirforces) \equiv abs(dirforces(1))), \dots
     'Force_magnitudes_should_be_equal'...
  assert(...
     all(dirforces(1:4) \equiv -dirforces(5:8)), \dots
     \verb|'Forces_{\sqcup}should_{\sqcup}be_{\sqcup}opposite_{\sqcup}with_{\sqcup}reversed_{\sqcup}fixed_{\sqcup}magnet_{\sqcup}magnetisation'...
     )
  assert(...
     all(dirforces([1 \ 3 \ 5 \ 7]) \equiv -dirforces([2 \ 4 \ 6 \ 8])), \dots
     \verb|'Forces_{\sqcup} should_{\sqcup} be_{\sqcup} opposite_{\sqcup} with_{\sqcup} reversed_{\sqcup} float_{\sqcup} magnet_{\sqcup} magnetisation'...
This code is used in sections 37 and 41.
       Now try combinations of displacements.
\langle magforce\_test001c.m | 47 \rangle \equiv
  disp('======;')
  fprintf('TEST_001c:_')
  magnet_fixed.dim = [0.04 \ 0.04 \ 0.04];
  magnet\_float.dim = magnet\_fixed.dim;
  magnet_fixed.magn = 1.3;
  magnet\_float.magn = 1.3;
   ⟨ Test combinations ZZ 48⟩
   ⟨ Assert combinations tests 50⟩
   ⟨ Test combinations ZY 49⟩
   \langle Assert combinations tests 50\rangle
  fprintf('passed\n')
  disp('=======,')
```

```
48.
        Tests.
\langle Test combinations ZZ | 48\rangle \equiv
  f = [];
  for ii = [-1 \ 1]
     for jj = [-1 \ 1]
        for xx = 0.12*[-1, 1]
           for yy = 0.12*[-1, 1]
             for zz = 0.12*[-1, 1]
                magnet\_fixed.magdir = [0 ii*90];
                                                                 \% z
                magnet\_float.magdir = [0 jj*90];
                                                                % z
                displ = [xx yy zz];
                f(:, end + 1) = magnetforces(magnet_fixed, magnet_float,
                     displ);
             \mathbf{end}
           end
        end
     \quad \text{end} \quad
  \quad \mathbf{end} \quad
  f = \operatorname{chop}(f, 8);
  uniquedir = f(3, :);
  otherdir = f([1 \ 2], :);
This code is used in section 47.
```

```
49.
       Tests.
\langle Test combinations ZY | 49\rangle \equiv
  f = [];
  for ii = [-1 \ 1]
    for jj = [-1 \ 1]
       for xx = 0.12*[-1, 1]
          for yy = 0.12*[-1, 1]
            for zz = 0.12*[-1, 1]
               magnet\_fixed.magdir = [0 ii*90];
                                                            % ±z
               magnet\_float.magdir = [jj*90\ 0];
                                                            % ±y
               displ = [xx yy zz];
               f(:, end + 1) = magnetforces(magnet_fixed, magnet_float,
            end
          \mathbf{end}
       end
     end
  end
  f = \operatorname{chop}(f, 8);
  uniquedir = f(1, :);
  otherdir = f([2\ 3],:);
This code is used in section 47.
       Shared tests, again.
\langle Assert combinations tests 50 \rangle \equiv
  test1 = abs(diff(abs(f(1,:)))) < 1 · 10<sup>-10</sup>;
  test2 = abs(diff(abs(f(2,:)))) < 1 \cdot 10^{-10};
  test3 = abs(diff(abs(f(3,:)))) < 1 · 10<sup>-10</sup>;
  assert(all(test1) \land \land all(test2) \land \land all(test3), ...
     'All_forces_in_a_single_direction_should_be_equal')
  test = abs(diff(abs(otherdir))) < 1 \cdot 10^{-11};
  assert(all(test), 'Orthogonal forces should be equal')
  test1 = f(:, 1:8) \equiv f(:, 25:32);
  test2 = f(:, 9:16) \equiv f(:, 17:24);
  assert(all(test1(:)) \land \land all(test2(:)), ...
     'Reverse_magnetisation_shouldn''t_make_a_difference')
This code is used in section 47.
```

```
51.
      Now we want to try non-orthogonal magnetisation.
\langle magforce\_test001d.m 51 \rangle \equiv
  disp('======,')
  fprintf('TEST_001d:_')
  magnet_fixed.dim = [0.04 \ 0.04 \ 0.04];
  magnet_float.dim = magnet_fixed.dim;
       % Fixed parameters:
  magnet\_fixed.magn = 1.3;
  magnet\_float.magn = 1.3;
  magnet\_fixed.magdir = [0 \ 90];
                                         % z
  displ = 0.12*[1 \ 1 \ 1];
  ⟨ Test XY superposition 52⟩
  (Assert superposition 55)
  ⟨ Test XZ superposition 53⟩
  (Assert superposition 55)
  ⟨ Test planar superposition 54⟩
  (Assert superposition 55)
  fprintf('passed\n')
  disp('======;')
52.
      Test with a magnetisation unit vector of (1, 1, 0).
\langle \text{ Test XY superposition } 52 \rangle \equiv
  magnet\_float.magdir = [45 \ 0];
                                        \vec{e}_x + \vec{e}_y
  f1 = magnetforces(magnet\_fixed, magnet\_float, displ);
       % Components:
  magnet\_float.magdir = [0 \ 0];
                                       % \vec{e}_x
  fc1 = magnetforces(magnet_fixed, magnet_float, displ);
  magnet\_float.magdir = [90 \ 0];
  fc2 = magnetforces(magnet_fixed, magnet_float, displ);
  f2 = (fc1 + fc2)/sqrt(2);
This code is used in section 51.
```

```
53.
       Test with a magnetisation unit vector of (1,0,1).
\langle \text{ Test XZ superposition } 53 \rangle \equiv
  magnet\_float.magdir = [0 \ 45];
                                                \% \vec{e}_y + \vec{e}_z
  f1 = magnetforces(magnet_fixed, magnet_float, displ);
        % Components:
  magnet\_float.magdir = [0 \ 0];
                                              \% \vec{e}_x
  fc1 = magnetforces(magnet_fixed, magnet_float, displ);
  magnet\_float.magdir = [0 \ 90];
                                                \% \vec{e}_z
  fc2 = magnetforces(magnet_fixed, magnet_float, displ);
  f2 = (fc1 + fc2)/sqrt(2);
This code is used in section 51.
        Test with a magnetisation unit vector of (1, 1, 1). This is about as much
as I can be bothered testing for now. Things seem to be working.
\langle \text{ Test planar superposition } 54 \rangle \equiv
  [t \ p \ r] = \operatorname{cart2sph}(1/\operatorname{sqrt}(3), 1/\operatorname{sqrt}(3), 1/\operatorname{sqrt}(3));
  magnet_float.magdir = [t \ p]*180/\pi;
                                                      \% \vec{e}_y + \vec{e}_z + \vec{e}_z
  f1 = magnetforces(magnet_fixed, magnet_float, displ);
        % Components:
  magnet\_float.magdir = [0 \ 0];
                                              \% \vec{e}_x
  fc1 = magnetforces(magnet_fixed, magnet_float, displ);
  magnet\_float.magdir = [90 \ 0];
                                                \% \vec{e}_y
  fc2 = magnetforces(magnet_fixed, magnet_float, displ);
  magnet\_float.magdir = [0 \ 90];
                                                \% \vec{e}_z
  fc3 = magnetforces(magnet_fixed, magnet_float, displ);
  f2 = (fc1 + fc2 + fc3)/sqrt(3);
This code is used in section 51.
       The assertion is the same each time.
\langle Assert superposition 55 \rangle \equiv
  assert(...
     isequal(chop(f1, 4), chop(f2, 4)), \dots
     \verb|'Components_{\square}| should_{\square} sum_{\square} due_{\square} to_{\square} superposition'...
This code is used in section 51.
```

56. Forces between (multipole) magnet arrays. This function uses magnetforces.m to compute the forces between two multipole magnet arrays. As before, we can calculate either force and/or stiffness in all three directions.

The structure of the function itself should look fairly straightforward. Some of the code is repeated from *magnetforces* (an advantage of the literate programming approach) for parsing the inputs for which calculations to perform and return.

```
\langle \text{multipoleforces.m } 56 \rangle \equiv
  function [varargout] = multipoleforces(fixed_array, float_array, displ, varargin)
     ⟨Matlab help text (multipole) 69⟩
     ⟨ Parse calculation args 7⟩
     ⟨Organise input displacements 6⟩
     (Initialise multipole variables 60)
     (Calculate array forces 59)
     ⟨Return all results 8⟩
     (Multipole sub-functions 57)
     end
57.
       And sub-functions.
\langle Multipole sub-functions 57 \rangle \equiv
  ⟨ Create arrays from input variables 61⟩
  ⟨Extrapolate variables from input 68⟩
This code is used in section 56.
```

58. Although the input to these functions is described in the user guide, there's a quick summary in Tables 1 and 2.

Table 1: Description of multipoleforces data structures.

Inputs:	fixed_array float_array displ [what to calculate]	structure describing first magnet array structure describing the second magnet array displacement between first magnet of each array 'force' and/or 'stiffness'
Outputs:	forces stiffnesses	forces on the second array stiffnesses on the second array
Arrays:	type mcount msize mgap magn magdir_fn	See Table 2 $[i\ j\ k]$ magnets in each direction size of each magnet gap between successive magnets magnetisation magnitude function to calculate the magnetisation direction

Table 2: Possibilities for the type of a multipole array.

generic	Magnetisation directions &c. are defined manually
linear-x	Linear array aligned with x
linear-y	Linear array aligned with y
linear-z	Linear array aligned with z
planar-xy	Planar array aligned with $x-y$
planar-yz	Planar array aligned with $y-z$
planar-xz	Planar array aligned with $x-z$

59. Actual calculation of the forces. To calculate these forces, let's assume that we have two large arrays enumerating the positions and magnetisations of each individual magnet in each magnet array.

```
Required fields for each magnet array:
 total M total number of magnets in the array
   \dim (M \times 3) size of each magnet
magloc (M \times 3) location of each magnet from the local coordinate system of the
        array
  magn (M \times 1) magnetisation magnitude of each magnet
magdir (M \times 2) magnetisation direction of each magnet in spherical coordinates
  size (M \times 3) total actual dimensions of the array
   \langle \text{ Calculate array forces } 59 \rangle \equiv
     for ii = 1: fixed_array.total
       fixed magnet = struct(...
         'dim', fixed_array.dim(ii,:),...
         'magn', fixed_array.magn(ii), ...
         'magdir', fixed_array.magdir(ii, :)...
         );
       for jj = 1: float_array.total
         float\_magnet = struct(...
            'dim', float\_array.dim(jj, :), ...
            'magn', float_array.magn(jj), ...
            'magdir', float_array.magdir(jj,:)...
           );
         for dd = 1: Ndispl
           mag_displ = displ_from_array_corners(:, dd)...
            -fixed_array.magloc(ii, :)' + float_array.magloc(jj, :)';
           if calc force bool
              array\_forces(ii, jj, :, dd) = ...
              magnetforces(fixed_magnet, float_magnet, mag_displ,
                   'force');
            end
           if calc_stiffness_bool
              array\_stiffnesses(ii, jj, :, dd) = \dots
              magnetforces(fixed_magnet, float_magnet, mag_displ,
                   'stiffness');
            end
         end
       end
     end
     if calc_force_bool
       forces\_out = squeeze(sum(sum(array\_forces, 1), 2));
```

end

```
\label{eq:calc_stiffness_bool} \begin{split} & \textit{stiffnesss\_bool} \\ & \textit{stiffnesses\_out} = \texttt{squeeze}(\texttt{sum}(\texttt{sum}(\textit{array\_stiffnesses}, 1), 2)); \\ & \textbf{end} \end{split}
```

This code is used in section 56.

This code is used in section 56.

60. Don't forget about the necessary initialisation for the above. \langle Initialise multipole variables $|60\rangle \equiv$

```
\begin{aligned} & \text{part} = @(x,y) \ x(y); \\ & \text{fixed\_array} = & \text{complete\_array\_from\_input(fixed\_array)}; \\ & \text{float\_array} = & \text{complete\_array\_from\_input(float\_array)}; \\ & \text{if} \ & \text{calc\_force\_bool} \\ & \text{array\_forces} = & \text{repmat}(\text{NaN}, \\ & & & & \text{[fixed\_array.total float\_array.total 3 Ndispl])}; \\ & \text{end} \\ & \text{if} \ & \text{calc\_stiffness\_bool} \\ & & \text{array\_stiffnesses} = & \text{repmat}(\text{NaN}, \\ & & & & \text{[fixed\_array.total float\_array.total 3 Ndispl])}; \\ & \text{end} \\ & & \text{displ\_from\_array\_corners} = & \text{displ} \dots \\ & & + & \text{repmat}(\text{fixed\_array.size}/2, [1 \ Ndispl]) \dots \\ & & -& \text{repmat}(\text{float\_array.size}/2, [1 \ Ndispl]); \end{aligned}
```

61. From user input to array generation. We separate the force calculation from transforming the inputs into an intermediate form used for that purpose. This will hopefully allow us a little more flexibility.

As input variables for a linear multipole array, we want to use some combination of the following:

- w wavelength of magnetisation
- *l* length of the array without magnet gaps
- N number of wavelengths
- d magnet length
- T total number of magnets
- M number of magnets per wavelength
- ϕ rotation between successive magnets

These are related via the following equations of constraint:

$$w = Md$$
 $l = Td$ $N = T/M$ $M = 360^{\circ}/\phi$ (1)

Taking logarithms and writing in matrix form yields

$$\begin{bmatrix} 1 & 0 & 0 & -1 & 0 & -1 & 0 \\ 0 & 1 & 0 & -1 & -1 & 0 & 0 \\ 0 & 0 & 1 & 0 & -1 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 & 1 \end{bmatrix} \log \begin{bmatrix} w \\ l \\ N \\ d \\ T \\ M \\ \phi \end{bmatrix} = \begin{bmatrix} 0 \\ 0 \\ 0 \\ \log(360^{\circ}) \end{bmatrix}$$
 (2)

We can use this matrix to compute whichever variables we need given enough inputs.

However, we generally do not want an integer number of wavelengths of magnetisation in the magnet arrays; if T=MN then we get small lateral forces that are undesirable for stability. We prefer instead to have T=MN+1, but this cannot be represented by our linear (logarithmic) algebra above. Therefore, if the user requests a total number of wavelengths of magnetisation, we automatically add one end magnet to restore the symmetry of the forces.

More variables than can be set are:

- ϕ_0 magnetisation direction of the first magnet
- g additional gap between adjacent magnet faces (optional)
- e array height (or magnet height)
- f array width (or magnet width)

For both technical reasons and reasons of convenience, the length of the array l does not take into account any specified magnet gap g. In other words, l is actually the length of the possibly discontiguous magnetic material; the length of the array will be l + (N-1)g.

 \langle Create arrays from input variables $|61\rangle \equiv$

```
function array = complete_array_from_input(array)
    if NOT isfield(array, 'type')
      array.type = 'generic';
    end
    linear\_index = 0;
    planar\_index = [0 \ 0];
    switch array.type
    case 'generic'
    case 'linear', linear\_index = 1;
    case 'linear-x', linear_index = 1;
    case 'linear-y', linear_index = 2;
    case 'linear-z', linear index = 3;
    case 'planar', planar_index = [1 \ 2];
    case 'planar-xy', planar_index = [1 2];
    case 'planar-yz', planar_index = [2 \ 3];
    case 'planar-xz', planar_index = [1 3];
    otherwise
      error(['Unknown_array_type_''', array.type, '''.'])
    end
    switch array.face
    case \{'+x', '-x'\}, facing_index = 1;
    case \{'+y', '-y'\}, facing_index = 2;
    case {'up', 'down'}, facing_index = 3;
    case \{'+z', '-z'\}, facing_index = 3;
    end
    if linear_index \neq 0
      if linear\_index \equiv facing\_index
         error('Arrays, cannot, face, into, their, alignment, direction.')
      end
      (Infer linear array variables 63)
    elseif NOT isequal(planar_index, [0 0])
      if any(planar_index \equiv facing_index)
        error('Planaruarraysucanuonlyufaceuintoutheiruorthogonaludirection')
      (Infer planar array variables 64)
    end
    (Array sizes 65)
    ⟨Array magnetisation strengths 66⟩
    (Array magnetisation directions 67)
    \langle Fill in array structures 62 \rangle
    end
```

This code is used in section 57.

```
62.
      This is the important step.
\langle \text{ Fill in array structures } 62 \rangle \equiv
  array.magloc = repmat(NaN, [array.total 3]);
  array.magdir = array.magloc;
  arrat.magloc\_array = repmat(NaN,
      [array.mcount(1) array.mcount(2) array.mcount(3) 3]);
  nn = 0:
  for iii = 1: array.mcount (1)
    for jjj = 1: array.mcount (2)
      for kkk = 1: array.mcount (3)
        nn = nn + 1;
        array.magdir(nn, :) = array.magdir_fn(iii, jjj, kkk);
    end
  end
  magsep\_x = zeros(size(array.mcount(1)));
  magsep\_y = zeros(size(array.mcount(2)));
  magsep\_z = zeros(size(array.mcount(3)));
  magsep_x(1) = array.msize_array(1, 1, 1, 1)/2;
  magsep_y(1) = array.msize_array(1, 1, 1, 2)/2;
  magsep\_z(1) = array.msize\_array(1, 1, 1, 3)/2;
  for iii = 2: array.mcount (1)
    magsep_x(iii) = array.msize_array(iii - 1, 1, 1, 1)/2...
    +array.msize\_array(iii, 1, 1, 1)/2;
  end
  for jjj = 2: array.mcount (2)
    magsep\_y(jjj) = array.msize\_array(1, jjj - 1, 1, 2)/2...
    +array.msize\_array(1, jjj, 1, 2)/2;
  end
  for kkk = 2: array.mcount (3)
    magsep_z(kkk) = array.msize_array(1, 1, kkk - 1, 3)/2...
    +array.msize\_array(1, 1, kkk, 3)/2;
  end
  magloc\_x = cumsum(magsep\_x);
  magloc_y = cumsum(magsep_y);
  magloc\_z = cumsum(magsep\_z);
  for iii = 1: array.mcount (1)
    for jjj = 1: array.mcount (2)
      for kkk = 1: array.mcount (3)
        array.magloc\_array(iii, jjj, kkk, :) = ...
        [magloc\_x(iii); magloc\_y(jjj); magloc\_z(kkk)]...
        +[iii-1; jjj-1; kkk-1].* array.mgap;
      end
    end
```

```
end
  array.magloc = reshape(array.magloc_array, [array.total 3]);
  array.size = squeeze(\ array\ .\ magloc\_array(\ end\ ,\ end\ ,\ end\ ,\ :\ )\ \dots
    -array.magloc\_array(1, 1, 1, :)...
    +array.msize\_array(1, 1, 1, :)/2...
    +array . msize\_array(end, end, end, :) / 2);
  debug_disp('Magnetisation

directions')
  debug_disp(array.magdir)
  debug_disp('Magnet_locations:')
  debug_disp(array.magloc)
This code is used in section 61.
      Infer variables.
63.
\langle \text{Infer linear array variables } 63 \rangle \equiv
  array = extrapolate_variables(array);
  array.mcount = ones(1, 3);
  array.mcount(linear_index) = array.Nmag;
This code is used in section 61.
```

64. For now it's a bit more messy to do the planar array variables. 'length' and 'mlength' may either be of length two or one; in the latter case, 'width' and 'mwidth' must also be specified.

```
\langle \text{Infer planar array variables } 64 \rangle \equiv
  if isfield(array, 'length')
    if length(array.length) \equiv 1
      if isfield(array.width)
        array.length = [array.length array.width];
        array.length = [array.length array.length];
      end
    end
  end
  if isfield(array, 'mlength')
    if length(array.mlength) \equiv 1
      if isfield(array.mwidth)
        array.mlength = [array.mlength array.mwidth];
      else
        array.mlength = [array.mlength array.mlength];
      end
    end
  end
  var_names = { 'length', 'mlength', 'wavelength', 'Nwaves', ...
    'Nmag', 'Nmag_per_wave', 'magdir_rotate'};
  tmp_array1 = struct();
  tmp_array2 = struct();
  var_index = zeros(size(var_names));
  for iii = 1: length (var names)
    if isfield(array, var_names(iii))
      tmp\_array1.(var\_names\{iii\}) = array.(var\_names\{iii\}) (1);
      tmp_array2.(var_names{iii}) = array.(var_names{iii}) ( end );
      var\_index(iii) = 1;
      end
      end
      tmp_array1 = extrapolate_variables(tmp_array1);
      tmp\_array2 = extrapolate\_variables(tmp\_array2);
      for iii = find(var_index)
        array.(var_names{iii}) =
             [tmp_array1.(var_names{iii}) tmp_array2.(var_names{iii})];
      end
      array.width = array.length(2);
      array.length = array.length(1);
```

```
array.mwidth = array.mlength(2);
       array.mlength = array.mlength(1);
       array.mcount = ones(1, 3);
       array.mcount(planar\_index) = array.Nmag;
This code is used in section 61.
65.
      Sizes.
\langle \text{Array sizes } 65 \rangle \equiv
  array.total = prod(array.mcount);
  if NOT isfield(array, 'msize')
    array.msize = [NaN NaN NaN];
    if linear_index \neq 0
       array.msize(linear\_index) = array.mlength;
       array.msize(facing\_index) = array.height;
       array.msize(isnan(array.msize)) = array.width;
    elseif NOT isequal(planar_index, [0 0])
       array.msize(planar_index) = [array.mlength array.mwidth];
       array.msize(facing\_index) = array.height;
    else
       error(`The_{\sqcup}array_{\sqcup}property_{\sqcup}``msize'`_{\sqcup}is_{\sqcup}not_{\sqcup}defined_{\sqcup}and_{\sqcup}I_{\sqcup}have_{\sqcup}no_{\sqcup}way_{\sqcup}to_{\sqcup}infer_{\sqcup}it.')
    end
  elseif numel(array.msize) \equiv 1
    array.msize = repmat(array.msize, [3 1]);
  end
  if numel(array.msize) \equiv 3
    array.msize\_array = \dots
    repmat(reshape(array.msize, [1 1 1 3]), array.mcount);
  else
    error('Magnetusizeu'msize''mustuhaveuthreeuelementsu(oruoneuelementuforuaucubeumagnet).'
  end
  array.dim = reshape(array.msize_array, [array.total 3]);
  if NOT isfield(array, 'mgap')
    array.mgap = [0; 0; 0];
  elseif length(array.mgap) \equiv 1
    array.mgap = repmat(array.mgap, [3 1]);
  end
```

This code is used in section 61.

66. Magnetisation strength of each magnet.

```
\begin{split} \langle & \text{Array magnetisation strengths } & \textbf{66} \, \rangle \equiv \\ & \text{if length}(\textit{array}.\textit{magn}) \equiv 1 \\ & \textit{array}.\textit{magn} = \texttt{repmat}(\textit{array}.\textit{magn}, [\textit{array}.\textit{total} \ 1]); \\ & \text{else} \\ & \textit{error}(\texttt{'Magnetisation}_{\square}\texttt{magnitude}_{\square}\texttt{'magn''}_{\square}\texttt{must}_{\square}\texttt{be}_{\square}\texttt{a}_{\square}\texttt{single}_{\square}\texttt{value}.\texttt{'}) \\ & \text{end} \end{split}
```

This code is used in section 61.

```
67. Magnetisation direction of each magnet.
⟨ Array magnetisation directions 67⟩ ≡
if NOT isfield(array 'magdir fn')
```

```
if NOT isfield(array, 'magdir_fn')
  if NOT isfield(array, 'face')
    array.face = '+z';
  end
  switch array.face
  case {'up', '+z', '+y', '+x'}, magdir_rotate_sign = 1;
  case {'down', '-z', '-y', '-x'}, magdir\_rotate\_sign = -1;
  if NOT isfield(array, 'magdir_first')
    array.magdir\_first = magdir\_rotate\_sign*90;
  magdir\_fn\_comp\{1\} = @(ii, jj, kk) 0;
  magdir\_fn\_comp\{2\} = @(ii, jj, kk) 0;
  {\tt magdir\_fn\_comp}\{3\} = @({\tt ii},{\tt jj},{\tt kk}) \ 0;
  if linear_index \neq 0
    magdir\_theta = @(nn) \dots
    array.magdir\_first + magdir\_rotate\_sign*array.magdir\_rotate*(nn - magdir\_rotate)
    magdir\_fn\_comp\{linear\_index\} = @(ii, jj, kk) ...
    cosd(magdir_theta(part([ii, jj, kk], linear_index)));
    magdir\_fn\_comp\{facing\_index\} = @(ii, jj, kk) \dots
    sind(magdir_theta(part([ii, jj, kk], linear_index)));
  elseif NOT isequal(planar_index, [0 0])
    magdir\_theta = @(nn) \dots
    array.magdir first(1) +
         magdir\_rotate\_sign*array.magdir\_rotate(1)*(nn - 1);
    magdir phi = @ (nn) ...
    array . magdir_first( end ) +magdir_rotate_sign*array .
         magdir\_rotate(end) * (nn - 1);
    magdir_fn_comp\{planar_index(1)\} = @(ii, jj, kk) \dots
    cosd(magdir\_theta(part([ii, jj, kk], planar\_index(2))));
    magdir_fn_comp\{planar_index(2)\} = @(ii, jj, kk) \dots
    cosd(magdir_phi(part([ii, jj, kk], planar_index(1))));
    magdir\_fn\_comp\{facing\_index\} = @(ii, jj, kk) \dots
    sind(magdir_theta(part([ii, jj, kk], planar_index(1))))...
    +sind(magdir\_phi(part([ii, jj, kk], planar\_index(2))));
    else
    error('Array_property_''magdir_fn''unot_defined_and_I_have_no_way_to_infer_it.')
    end
    array.magdir fn = @(ii, jj, kk) \dots
```

```
 \begin{split} & [\mathit{magdir\_fn\_comp}\{1\} \; (\mathit{ii}, \mathit{jj}, \mathit{kk}) \; \dots \\ & \; \mathit{magdir\_fn\_comp}\{2\} \; (\mathit{ii}, \mathit{jj}, \mathit{kk}) \; \dots \\ & \; \mathit{magdir\_fn\_comp}\{3\} \; (\mathit{ii}, \mathit{jj}, \mathit{kk})]; \\ & \; \mathsf{end} \end{split}
```

This code is used in section 61.

68. Sub-functions.

```
\langle Extrapolate variables from input 68 \rangle \equiv
 function array_out = extrapolate_variables(array)
      var_names = {'wavelength', 'length', 'Nwaves', 'mlength', ...
        'Nmag', 'Nmag_per_wave', 'magdir_rotate'};
      mcount\_extra = 0;
      if isfield(array, 'Nwaves')
        mcount\_extra = 1;
      end
      variables = repmat(NaN, [7 1]);
      for iii = 1:length (var_names);
        if isfield(array, var_names(iii))
           variables(iii) = array.(var_names{iii});
        end
      end
      var\_matrix = \dots
      [1, 0, 0, -1, 0, -1, 0;
         0, 1, 0, -1, -1, 0, 0;
         0, 0, 1, 0, -1, 1, 0;
         0, 0, 0, 0, 0, 1, 1;
      var\_results = [0 \ 0 \ 0 \log(360)]';
      variables = log(variables);
      idx = NOT isnan(variables);
      var\_known = var\_matrix(:, idx)*variables(idx);
      var\_calc = var\_matrix(:, NOT idx) \setminus (var\_results - var\_known);
      variables(NOT idx) = var\_calc;
      variables = exp(variables);
      for iii = 1:length (var_names);
        array.(var\_names\{iii\}) = variables(iii);
      end
      array.Nmag = round(array.Nmag) + mcount_extra;
      array.Nmag_per_wave = round(array.Nmag_per_wave);
      array.mlength = array.mlength*(array.Nmag -
          mcount_extra)/array.Nmag;
      array_out = array;
      end
```

This code is used in section 57.

69. When users type help multipoleforces this is what they see.

```
\langle Matlab help text (multipole) ^{69}\rangle \equiv %% MULTIPOLEFORCES Calculate forces between two multipole arrays of magnets % % Finish this off later. %
```

This code is used in section 56.

 $\langle \text{testall.m } 36 \rangle + \equiv$ multiforce_test002a multiforce_test002b $multiforce_test002c$ $multiforce_test002d$ First test just to check the numbers aren't changing. $\langle multiforce_test002a.m \quad 71 \rangle \equiv$ disp('======;') fprintf('TEST_002a:_') $fixed_array = \dots$ struct(... 'type', 'linear-x', ... 'face', 'up', ... 'length', $0.01, \ldots$ 'width', 0.01, ...'height', 0.01, ...'Nmag_per_wave', $4, \ldots$ 'Nwaves', 1, ... 'magn', $1, \ldots$

f_total = multipoleforces(fixed_array, float_array, displ);

 $assert(chop(f_total(3), 5) \equiv 0.13909$, 'Regression_shouldn''t_fail');

Not much here yet.

Test files for multipole arrays.

 $\verb|'magdir_first'|, 90 \dots$

float_array = fixed_array; float_array.face = 'down'; float_array.magdir_first = -90;

 $displ = [0 \ 0 \ 0.02];$

fprintf('passed\n')

disp('======,')

);

70.

72. Test against single magnet.

```
\langle multiforce\_test002b.m \quad \frac{72}{} \rangle \equiv
 disp('======,')
 fprintf('TEST_002b:_'')
 fixed\_array = \dots
 struct(...
    'type', 'linear-x', ...
    'face', 'up', ...
    'length', 0.01, \ldots
    'width', 0.01, ...
    'height', 0.01, ...
    'Nmag_per_wave', 1, ...
    'Nwaves', 1, ...
    'magn', 1, \ldots
    'magdir_first', 90...
    );
 float_array = fixed_array;
 float_array.face = 'down';
 float\_array.magdir\_first = -90;
 displ = [0 \ 0 \ 0.02];
 f\_total = multipole forces(fixed\_array, float\_array, displ);
 fixed_mag = struct('dim', [0.01 0.01 0.01], 'magn', 1, 'magdir', [0 90]);
 float\_mag = struct('dim', [0.01 \ 0.01 \ 0.01], 'magn', 1, 'magdir', [0 - 90]);
 f_mag = magnetforces(fixed_mag, float_mag, displ);
 assert(chop(f\_total(3), 6) \equiv chop(f\_mag(3), 6));
 fprintf('passed\n')
 disp('=======,')
```

73. Test that linear arrays give consistent results regardless of orientation.

```
\langle multiforce\_test002c.m \quad 73 \rangle \equiv
 disp('======,')
 fprintf('TEST_002c:_'')
      % Fixed parameters
 fixed\_array = \dots
 struct(...
    'length', 0.10, ...
    'width', 0.01, ...
    'height', 0.01, \ldots
    'Nmag_per_wave', 4, \ldots
    'Nwaves', 1, ...
    'magn', 1, ...
    'magdir_first', 90...
    );
 float_array = fixed_array;
 float_array.magdir_first = -90;
 f = \text{repmat}(\text{NaN}, [3\ 0]);
      % The varying calculations
 fixed_array.type = 'linear-x';
 float_array.type = fixed_array.type;
 fixed_array.face = 'up';
 float_array.face = 'down';
 displ = [0 \ 0 \ 0.02];
 f(:, end +1) = multipoleforces(fixed_array, float_array, displ);
 fixed_array.type = 'linear-x';
 float_array.type = fixed_array.type;
 fixed_array.face = '+y';
 float_array.face = '-y';
 displ = [0 \ 0.02 \ 0];
 f(:, end +1) = multipoleforces(fixed_array, float_array, displ);
 fixed_array.type = 'linear-y';
 float_array.type = fixed_array.type;
 fixed_array.face = 'up';
 float_array.face = 'down';
 displ = [0 \ 0 \ 0.02];
 f(:, end +1) = multipoleforces(fixed_array, float_array, displ);
 fixed_array.type = 'linear-y';
 float_array.type = fixed_array.type;
 fixed_array.face = '+x';
 float_array.face = '-x';
  displ = [0.02 \ 0 \ 0];
  f(:, end +1) = multipoleforces(fixed_array, float_array, displ);
```

```
fixed_array.type = 'linear-z';
float_array.type = fixed_array.type;
fixed_array.face = '+x';
float_array.face = '-x';
displ = [0.02 \ 0 \ 0];
f(:, end +1) = multipoleforces(fixed_array, float_array, displ);
fixed_array.type = 'linear-z';
float_array.type = fixed_array.type;
fixed_array.face = '+y';
float_array.face = '-y';
displ = [0 \ 0.02 \ 0];
f(:, end +1) = multipoleforces(fixed_array, float_array, displ);
assert(all(chop(sum(f), 4) \equiv 37.31), \dots
  \verb|`Arrays_\square| a ligned_\square in_\square different_\square directions_\square should_\square produce_\square consistent_\square results.')|;
fprintf('passed\n')
disp('=======,')
```

74. Test that planar arrays give consistent results regardless of orientation.

```
\langle multiforce\_test002d.m 74 \rangle \equiv
  disp('======,')
  fprintf('TEST_002d:_'')
      % Fixed parameters
  fixed\_array = \dots
  struct(...
    'length', [0.10 \ 0.10], ...
    'width', 0.10, \ldots
    'height', 0.01, \ldots
    'Nmag_per_wave', [4 4], ...
    'Nwaves', [1 1], ...
    'magn', 1, ...
    'magdir_first', [90 \ 90] \dots
    );
  float_array = fixed_array;
  float_array.magdir_first = [-90 - 90];
  f = \text{repmat}(\text{NaN}, [3\ 0]);
      % The varying calculations
  fixed_array.type = 'planar-xy';
  float_array.type = fixed_array.type;
  fixed_array.face = 'up';
  float_array.face = 'down';
  displ = [0 \ 0 \ 0.02];
  f(:, end +1) = multipoleforces(fixed_array, float_array, displ);
  fixed_array.type = 'planar-yz';
  float_array.type = fixed_array.type;
  fixed_array.face = '+x';
  float_array.face = '-x';
  displ = [0.02 \ 0 \ 0];
  f(:, end +1) = multipoleforces(fixed_array, float_array, displ);
  fixed_array.type = 'planar-xz';
  float_array.type = fixed_array.type;
  fixed_array.face = '+y';
  float_array.face = '-y';
  displ = [0 \ 0.02 \ 0];
  f(:, end +1) = multipoleforces(fixed_array, float_array, displ);
  ind = [3 \ 4 \ 8];
  assert(all(round(f(ind)*100)/100 \equiv 589.05), \dots)
    \verb|`Arrays_\square| a ligned_\square in_\square different_\square directions_\square should_\square produce_\square consistent_\square results.')|;
  assert(all(f(NOT ind) < 1 \cdot 10^{-10}), \dots
    'These_forces_should_all_be_(essentially)_zero.');
```

```
fprintf('passed\n')
disp('======;)
```

75. These are MATLABWEB declarations to improve the formatting of this document. Ignore unless you're editing magnetforces.web.

define end \equiv end format *END* TeX

Index of magnetforces

```
abs: 19, 46, 50
                                     d_x: 13, 15, 30
all: 28, 46, 50, 73, 74
                                     d_y: 14, 15, 30
allag_correction: 18
                                     dd: 59
any: 61
                                     debug_disp: 7, 12, 13, 14, 15, 24,
arrat: 62
                                         26, 33, 62
array: 61, 62, 63, 64, 65, 66, 67, 68
                                     diff: 50
array_forces: 59, 60
                                     dim: 4, 5, 37, 41, 47, 51, 59, 65
array_out: 68
                                     dirforces: 38, 39, 40, 42, 43, 44,
array stiffnesses: 59,60
                                         45. 46
assert: 19, 46, 50, 55, 71, 72, 73, 74
                                     disp: 7, 37, 41, 47, 51, 71, 72, 73, 74
                                     displ: 4, 6, 9, 10, 11, 12, 15, 17,
atan: 32
atan1: 17, 18, 19, 22, 32
                                         30, 33, 38, 39, 40, 42, 43, 44,
atan2: 32
                                         45, 48, 49, 51, 52, 53, 54, 56, 58,
                                         60, 71, 72, 73, 74
calc_force_bool: 6, 7, 9, 59, 60
calc_out: 17, 18, 20, 21, 22, 23,
                                     displ_from_array_corners: 59,60
    24, 26
                                     dx: 17
                                     dy: 17
calc\_stiffness\_bool: 6, 7, 9, 59, 60
cart2sph: 54
                                     dz: 17
chop: 38, 39, 40, 42, 43, 44, 45, 48,
                                     end: 38, 39, 40, 42, 43, 44, 45,
    49, 55, 71, 72, 73
                                         48, 49, 75
clc: 36
                                     error: 6, 7, 61, 65, 66, 67
complete_array_from_input: 60,
                                     exp: 68
                                     extrapolate_variables: 63, 64, 68
                                     f_mag : 72
component_x: 17, 18, 19, 21,
    22, 26
                                     f_total: 71, 72
component_x_ii: 19
                                     face: 61, 67, 71, 72, 73, 74
component_y: 17, 18, 19, 21,
                                     facing_index : 61, 65, 67
                                     false: 7
    22, 26
component_y_ii: 19
                                     fc1: 52, 53, 54
                                     fc2: 52, 53, 54
component_z: 17, 18, 19, 21, 22, 26
component z ii: 19
                                     fc3:54
cos: 28
                                     find: 64
cosd : 28, 67
                                     fixed_array: 56, 58, 59, 60, 71,
cumsum: 62
                                         72, 73, 74
```

```
fixed_mag: 72
                                    jj: 38, 39, 40, 42, 43, 44, 45, 48,
                                        49, 59, 67
fixed_magnet: 59
                                    jjj : 62
float_array: 56, 58, 59, 60, 71,
    72, 73, 74
                                    J1: 5, 12, 15, 17, 18, 20, 21, 22,
float_mag: 72
                                        23, 24, 26, 29, 33
                                    J1_x: 13, 15, 29
float_magnet: 59
                                    J1_y: 14, 15, 29
force_components: 10, 12, 13, 14
                                    J2: 5, 12, 15, 17, 18, 20, 21, 22,
force_out: 10
                                        23, 24, 26, 29, 33
forces: 4, 58
                                    J2_x: 13, 15, 29
forces_calc_z_x: 12, 13, 14, 20
                                    J2_y: 14, 15, 29
forces_calc_z_y: 12, 13, 14, 18,
                                    kk: 38, 39, 40, 42, 43, 44, 45, 67
    20. 37
                                    kkk: 62
forces_calc_z_z: 12, 13, 14, 17
                                    length: 7, 8, 28, 64, 65, 66, 68
forces_out: 6, 8, 9, 59
                                    linear_index: 61, 63, 65, 67
forces_xyz : 17, 20
                                    log: 21, 31, 68
fprintf: 37, 41, 47, 51, 71, 72, 73, 74
                                    mag_displ: 59
Fx: 17
                                    magconst: 25, 26
Fy: 17
                                    magdir: 4, 5, 28, 38, 39, 40, 42,
Fz: 17
                                        43, 44, 45, 48, 49, 51, 52, 53,
fzxx: 45
                                        54, 59, 62
fzxz:43
                                    magdir_first: 67, 71, 72, 73, 74
fzyy: 44
                                    magdir_fn: 58, 62, 67
fzyz: 42
                                    magdir_fn_comp: 67
f1: 52, 53, 54, 55
                                    magdir_phi: 67
f2: 52, 53, 54, 55
                                    magdir_rotate: 67
height: 65
                                    magdir_rotate_sign: 67
idx: 68
                                    magdir_theta: 67
ii: 7, 8, 9, 38, 39, 40, 42, 43, 44,
                                    magforce_test001a:
    45, 48, 49, 59, 67
                                    magforce_test001b:
iii : 62, 64, 68
                                    magforce_test001c:
ind: 32, 74
                                    magforce_test001d: 36
index_i: 24, 25
                                    magloc: 59, 62
index_j: 24, 25
                                    magloc_array: 62
index_k: 24, 25
                                    magloc_x : 62
index_1: 24, 25
                                    magloc_y: 62
index_p: 24, 25
                                    magloc\_z : 62
index_q : 24, 25
                                    magn: \ 4,\ 5,\ 28,\ 37,\ 41,\ 47,\ 51,
index_sum : 19, 25, 26
                                        58, 59, 66
isequal: 55, 61, 65, 67
                                    magnet: 5
isfield: 61, 64, 65, 67, 68
                                    magnet_fixed: 4, 5, 37, 38, 39,
isfinite: 31
                                        40, 41, 42, 43, 44, 45, 47, 48,
isnan: 65, 68
                                        49, 51, 52, 53, 54
                                    magnet_float: 4, 5, 37, 38, 39, 40,
J_p : 28
                                        41, 42, 43, 44, 45, 47, 48, 49,
J_{r} : 28
J_t: 28
                                        51, 52, 53, 54
```

```
magnetforces: 4, 38, 39, 40, 42,
                                     rotate_y_to_x: 20, 29
    43, 44, 45, 48, 49, 52, 53, 54,
                                     rotate_y_to_z: 29, 30
    56, 59, 72
                                     rotate_z_to_x: 13, 29
magsep_x: 62
                                     rotate_z_to_y: 14, 29
magsep\_y: 62
                                     round: 68, 74
                                     sind: 28, 67
magsep\_z: 62
mcount: 58, 62, 63, 64, 65
                                     single_magnet_force: 9, 10
                                     single_magnet_stiffness: 9, 11
mcount_extra: 68
                                     size: 6, 32, 60, 62, 64
mgap: 58, 62, 65
                                     size1: 5, 12, 15, 17, 18, 20, 21,
mlength: 64, 65, 68
                                         22, 23, 24, 29
msize: 58, 65
                                     {\tt size1\_x} \; : \; \; 13, \; 15, \; 29
msize\_array: 62, 65
multiforce_test002a: 70
                                     size1_y: 14, 15, 29
multiforce test002b: 70
                                     size2: 5, 12, 15, 17, 18, 20, 21,
multiforce test002c: 70
                                         22, 23, 24, 29
multiforce test002d: 70
                                     size2_x: 13, 15, 29
multiply_x_log_y: 17, 18, 19,
                                     size2_y: 14, 15, 29
    22, 31
                                     sph2cart: 28
                                     sqrt: 24, 52, 53, 54
multipoleforces: 56, 71, 72, 73, 74
mwidth: \ 64,\ 65
                                     squeeze: 59, 62
\mathtt{NaN} \ : \quad 6, \ 10, \ 11, \ 31, \ 32, \ 60, \ 62,
                                     stiffness_components: 11, 15
    65, 68, 73, 74
                                     stiffness_out: 11
                                     stiffnesses: 4,58
ndgrid: 25
Ndispl: 6, 9, 59, 60
                                     stiffnesses\_calc\_z\_x: 15, 23
Nmag: 63, 64, 68
                                     stiffnesses\_calc\_z\_y: 15, 22, 23
Nmag_per_wave: 68
                                     stiffnesses\_calc\_z\_z: 15, 21
nn: 62, 67
                                     stiffnesses\_out: 6, 8, 9, 59
norm: 28
                                     stiffnesses_xyz: 23
numel: 65
                                     str : 7
offset: 17, 18, 20, 21, 22, 23, 24,
                                     struct: 59, 64, 71, 72, 73, 74
    37, 38, 39, 40
                                     sum: 10, 11, 19, 26, 59, 73
                                     swap_x_y : 20, 23, 29
ones: 63, 64
otherdir: 48, 49, 50
                                     swap x z : 15, 29
otherforces: 38, 39, 40, 42, 43,
                                     swap\_y\_z : 15, 29
    44, 45, 46
                                     test: 50
out: 31, 32
                                     test1:50
part: 60, 67
                                     test2:50
                                     test3:50
phi : 5
planar_index : 61, 64, 65, 67
                                     TeX: 75
prod : 65
                                     \theta: 5
repmat: 6, 10, 11, 60, 62, 65, 66,
                                     tmp_array1: 64
    68, 73, 74
                                     tmp\_array2: 64
reshape: 5, 28, 62, 65
                                     total: 59, 60, 62, 65, 66
resolve_magnetisations: 5, 28
                                     transpose: 6
rotate_x_to_y: 20, 23, 29
                                     true: 7
rotate_x_to_z: 29, 30
                                     type: 58, 61, 73, 74
```

```
uniquedir: 48, 49
                                   vec: 29
var_calc: 68
                                   width: 64, 65
var index: 64
                                  xx : 19, 48, 49
var_known: 68
                                  xx_ii : 19
var matrix: 68
                                  yy: 19, 48, 49
var_names : 64, 68
                                  yy_ii : 19
var_results: 68
                                  zeros: 32, 62, 64
varargin: 4, 7, 8, 56
                                  zz: 19, 48, 49
varargout : 4, 8, 56
variables: 68
                                  zz ii: 19
```

List of Refinements in magnetforces

```
\langle magforce\_test001a.m 37 \rangle
magforce_test001b.m 41 >
magforce_test001c.m 47
magforce_test001d.m \frac{51}{}
[magnetforces.m 4]
multiforce_test002a.m 71
multiforce_test002b.m 72 >
multiforce_test002c.m 73 >
multiforce_test002d.m 74 >
multipoleforces.m 56 >
testall.m 36, 70
(Array magnetisation directions 67) Used in section 61.
Array magnetisation strengths 66
                                       Used in section 61.
Array sizes 65 Used in section 61.
\langle Assert combinations tests 50 \rangle Used in section 47.
(Assert magnetisations tests 46) Used in sections 37 and 41.
Assert superposition 55 \ Used in section 51.
Calculate array forces 59 Used in section 56.
Calculate for each displacement 9 Used in section 4.
Calculate stiffnesses 15 Used in section 11.
Calculate x force 13 Used in section 10.
Calculate y force 14 \ Used in section 10.
Calculate z force 12 Used in section 10.
Create arrays from input variables 61 \ Used in section 57.
Extrapolate variables from input 68 \ Used in section 57.
(Fill in array structures 62) Used in section 61.
(Finish up 26) Used in sections 17, 18, 21, and 22.
Function for resolving magnetisations 28 Used in section 4.
Function for single force calculation 10 Used in section 4.
Function for single stiffness calculation 11 Used in section 4.
(Functions for calculating forces and stiffnesses 16) Used in section 4.
\langle Helper functions 31, 32\rangle Used in section 16.
```

```
(Infer linear array variables 63) Used in section 61.
\langle Infer planar array variables 64 \rangle Used in section 61.
\langle \text{Initialise main variables } 5, 25 \rangle Used in section 4.
(Initialise multipole variables 60) Used in section 56.
Initialise subfunction variables 24 Used in sections 17, 18, 21, and 22.
(Matlab help text (forces) 34) Used in section 4.
(Matlab help text (multipole) 69 Used in section 56.
 Multipole sub-functions 57 \ Used in section 56.
 Organise input displacements 6 \ Used in sections 4 and 56.
Orthogonal magnets force calculation 18, 20 Used in section 16.
Orthogonal magnets stiffness calculation 22, 23 Used in section 16.
 Parallel magnets force calculation 17 Used in section 16.
 Parallel magnets stiffness calculation 21 \rangle Used in section 16.
 Parse calculation args 7 Used in sections 4 and 56.
Precompute displacement rotations 30 \ Used in sections 10 and 11.
 Precompute rotations 29 \ Used in section 4.
Print diagnostics 33 \ Used in sections 10 and 11.
\langle \text{Return all results 8} \rangle Used in sections 4 and 56.
\langle \text{ Test } x - x \text{ magnetisations } 39 \rangle Used in section 37.
 Test y-y magnetisations 40 \rangle Used in section 37.
Test z-z magnetisations 38 Used in section 37.
(Test XY superposition 52) Used in section 51.
(Test XZ superposition 53) Used in section 51.
Test ZXX 45 Used in section 41.
\langle \text{Test ZXZ } 43 \rangle
                   Used in section 41.
⟨Test ZYY 44⟩
                   Used in section 41.
\langle \text{ Test ZYZ } 42 \rangle
                   Used in section 41.
Test against Janssen results 19
(Test combinations ZY 49) Used in section 47.
(Test combinations ZZ 48) Used in section 47.
\langle Test planar superposition 54 \rangle Used in section 51.
```

References

- [1] Gilles Akoun and Jean-Paul Yonnet. "3D analytical calculation of the forces exerted between two cuboidal magnets". In: *IEEE Transactions on Magnetics* MAG-20.5 (Sept. 1984), pp. 1962–1964. DOI: 10.1109/TMAG.1984. 1063554. See p. 15.
- [2] Jean-Paul Yonnet and Hicham Allag. "Analytical Calculation of CuboArdal Magnet Interactions in 3D". In: The 7th International Symposium on Linear Drives for Industry Application. 2009. See pp. 16, 19.