

Lesson 46 Practice: Firmware, BIOS, UEFI and Drivers

JKSSB Computer Awareness

October 10, 2026

Provenance: 19 items are original JKSSB-pattern questions (*[Original]*); 1 item is a real previous-year question (*[PYQ WO 2026 Q68, key:provisional]*).

Q1. *[Original]* Expand BIOS.

- A. Basic Input/Output System
- B. Binary Input/Output System
- C. Basic Internal Operating System
- D. Basic Input/Output Software

Q2. *[Original]* Expand UEFI.

- A. Universal Embedded Firmware Interface
- B. Unified Extensible Firmware Interface
- C. Unified External File Interface
- D. Universal Extensible Firmware Integration

Q3. *[Original]* Expand POST.

- A. Power-Off System Test
- B. Primary Operating System Test
- C. Power-On Self-Test
- D. Post-Operation Startup Task

Q4. *[PYQ WO 2026 Q68, key:provisional]* Which firmware initialises the hardware and loads the operating system when a computer is switched on?

- A. Device driver
- B. BIOS
- C. Application program
- D. Compiler

Q5. *[Original]* Firmware is best described as:

- A. temporary data stored in RAM while a program runs.
- B. software stored in non-volatile memory that gives a device its basic, low-level instructions.
- C. a program that the user opens from the desktop.

D. the physical circuits inside a processor.

Q6. *[Original]* Firmware is normally stored in:

- A. RAM
- B. a CPU register
- C. ROM or flash memory
- D. the cache

Q7. *[Original]* What does the POST do at startup?

- A. Loads the user's application programs
- B. Tests whether the basic hardware is present and working
- C. Formats the hard disk
- D. Installs device drivers

Q8. *[Original]* Which item comes FIRST in the power-on sequence?

- A. Application programs
- B. Device drivers
- C. Firmware (BIOS/UEFI)
- D. Operating system

Q9. *[Original]* A device driver is:

- A. hardware that plugs into the motherboard.
- B. software that lets the operating system communicate with a specific device.
- C. the same as the BIOS.
- D. a type of cache memory.

Q10. *[Original]* In which order does the computer normally start these layers?

- A. application → OS → driver → firmware
- B. firmware → OS → driver → application
- C. OS → firmware → application → driver
- D. driver → firmware → OS → application

Q11. *[Original]* Which of the following is **NOT** a function of the BIOS?

- A. Running the power-on self-test
- B. Initialising the basic hardware
- C. Finding and loading the operating system
- D. Compiling the user's source code

Q12. *[Original]* Which statement correctly contrasts BIOS and UEFI?

- A. BIOS is the modern firmware and UEFI is the legacy firmware.

- B. UEFI is the modern firmware; it boots faster, supports large GPT disks, and can provide Secure Boot.
- C. BIOS and UEFI are identical in every feature.
- D. UEFI is a device driver, while BIOS is firmware.

Q13. *[Original]* Which option is an advantage of UEFI over the legacy BIOS?

- A. It removes the need for any firmware.
- B. It supports very large disks using GPT and offers a graphical setup.
- C. It works only on 32-bit computers.
- D. It makes device drivers unnecessary.

Q14. *[Original]* A student claims that the program which initialises the hardware and starts the operating system is a device driver. Which is the correct term?

- A. Application software
- B. BIOS/UEFI firmware
- C. Compiler
- D. Device Manager

Q15. *[Original]* A firmware update is commonly called:

- A. flashing
- B. formatting
- C. partitioning
- D. compiling

Q16. *[Original]* What is the main risk during a firmware update?

- A. The screen resolution may change.
- B. Interrupting power during flashing can leave the device unusable.
- C. The mouse will stop working.
- D. The font size will change.

Q17. *[Original]* Evaluate the statements:

- I. Firmware is stored in non-volatile memory.
 - II. Device drivers are loaded by the operating system.
 - III. The POST runs after the operating system has started.
-
- A. I and II only
 - B. I and III only
 - C. II and III only
 - D. I, II, and III

Q18. *[Original]* BIOS settings such as boot order and system date/time are stored in:

- A. RAM
- B. the CMOS (battery-backed) chip
- C. the cache
- D. a device driver

Q19. *[Original]* Which of the following is software that runs before the operating system?

- A. A word processor
- B. Firmware (BIOS/UEFI)
- C. A web browser
- D. A device driver

Q20. *[Original]* Which pairing is correctly matched?

- A. BIOS — a device driver for printers
- B. UEFI — the legacy firmware with a text-only setup
- C. Firmware — permanent software stored in ROM/flash
- D. POST — the application that loads the OS

Q21. *[JKSSB FAA-pattern]* Which firmware initialises hardware and loads the OS at startup?

- A. BIOS/UEFI
- B. Compiler
- C. Assembler
- D. Media player

Q22. *[JKPSI-pattern]* UEFI is best described as:

- A. a modern replacement for legacy BIOS.
- B. a type of printer paper.
- C. a speaker cable.
- D. a keyboard cover.

Q23. *[SSC CGL-pattern]* A device driver is:

- A. software that lets the OS control a device.
- B. a hardware screwdriver.
- C. a printer paper tray.
- D. a monitor stand.

Q24. *[JKSSB-pattern]* (**MSQ: select ALL correct options.**) Which tasks happen during system boot?

- A. Power-on self-test (POST)
- B. Loading the operating system
- C. Initialising hardware devices

D. Printing a test novel

Q25. *[SSC CGL-pattern]* **(MSQ: select ALL correct options.)** Which statements about firmware and drivers are correct?

- A. BIOS/UEFI starts before the OS loads.
- B. Drivers translate OS commands for devices.
- C. UEFI supports larger disks than legacy BIOS.
- D. A compiler loads the operating system at startup.

Q26. *[PYQ-adapted: JKSSB FAA 2024, QCRIAS item 668; SRC-16/SRC-19]* Firmware is commonly stored in:

- A. Cache
- B. RAM
- C. External printer memory only
- D. ROM or flash memory

Q27. *[PYQ-adapted: JKSSB Website Operator 2026 Q68, provisional key; SRC-04/SRC-07]* Which firmware initializes hardware and begins the boot process on a traditional PC?

- A. BIOS
- B. Device driver
- C. Spreadsheet
- D. Web browser

Q28. *[Original]* UEFI is best described as:

- A. A modern firmware interface used during startup
- B. A type of spreadsheet formula
- C. A printer cable
- D. A file-compression format

Q29. *[Original]* A device driver primarily enables:

- A. The operating system to communicate with a hardware device
- B. A monitor to store files permanently
- C. A user to change the CPU clock by typing a document
- D. A network to replace the operating system

Q30. *[Original, MSQ drill]* **(MSQ: select ALL correct options.)** Which statements are correct?

- A. Firmware is low-level software associated with a device.
- B. ROM/flash can retain firmware without power.
- C. BIOS/UEFI participates in startup.
- D. A device driver is a physical circuit board.