

Lesson 46 Practice: Answers and Rationales

JKSSB Computer Awareness

October 10, 2026

Provenance: 19 items are original JKSSB-pattern questions (*[Original]*); 1 item is a real previous-year question (*[PYQ WO 2026 Q68, key:provisional]*).

- Q1. A.** BIOS stands for Basic Input/Output System. B, C, and D are not the correct expansion of the abbreviation.
- Q2. B.** UEFI stands for Unified Extensible Firmware Interface. A, C, and D are not the correct full forms.
- Q3. C.** POST stands for Power-On Self-Test. A, B, and D are not the correct expansions.
- Q4. B.** BIOS is the firmware that initialises the hardware and loads the operating system. A device driver (A) is loaded by the OS; an application (C) and a compiler (D) are higher-level software, not startup firmware.
- Q5. B.** Firmware is software stored in non-volatile memory that gives a device its basic low-level instructions. A describes RAM data; C describes ordinary application software; D describes hardware circuitry.
- Q6. C.** Firmware is normally stored in ROM or flash memory, which are non-volatile. RAM (A), a register (B), and cache (D) are all volatile and empty at power-on.
- Q7. B.** The POST tests whether the basic hardware is present and working. Loading applications (A), formatting a disk (C), and installing drivers (D) are not POST functions.
- Q8. C.** Firmware (BIOS/UEFI) runs first at power-on. The operating system (D), device drivers (B), and applications (A) each start later in the chain.
- Q9. B.** A device driver is software that lets the OS communicate with a specific device. A describes hardware; C is wrong because the BIOS is firmware, not a driver; D is wrong because a driver is not cache.
- Q10. B.** The correct order is firmware, then OS, then driver, then application. A, C, and D all place a later layer before an earlier one.
- Q11. D.** Compiling source code is done by a compiler after the OS and application are running, so it is not a BIOS function. Running POST (A), initialising hardware (B), and loading the OS (C) are all BIOS jobs.
- Q12. B.** UEFI is the modern firmware: it boots faster, supports large GPT disks, and can provide Secure Boot. A reverses the ages; C wrongly calls them identical; D wrongly calls UEFI a device driver.

- Q13. B.** UEFI supports very large disks using GPT and offers a graphical setup. It does not remove the need for firmware (A), is not limited to 32-bit systems (C), and does not remove device drivers (D).
- Q14. B.** The firmware that initialises hardware and starts the OS is the BIOS/UEFI. Application software (A), a compiler (C), and Device Manager (D) are not the startup firmware.
- Q15. A.** A firmware update is commonly called flashing. Formatting (B) prepares storage; partitioning (C) divides a disk; compiling (D) translates source code.
- Q16. B.** Interrupting power during flashing can leave the device unusable. Screen resolution (A), the mouse (C), and font size (D) are not the risk of a firmware update.
- Q17. A.** Statements I and II are correct: firmware is non-volatile, and drivers are loaded by the OS. III is false because POST runs before the OS, not after. B and C include false III; D includes false III.
- Q18. B.** BIOS settings are stored in the CMOS battery-backed chip. RAM (A) is volatile; the cache (C) holds recent data; a device driver (D) controls a device, not BIOS settings.
- Q19. B.** Firmware (BIOS/UEFI) runs before the operating system. A word processor (A), a web browser (C), and a device driver (D) all run after the OS has started.
- Q20. C.** Firmware is permanent software stored in ROM/flash, so this pairing is correct. A wrongly calls BIOS a printer driver; B calls UEFI the legacy text-only firmware; D calls POST the application that loads the OS.
- Q21. A.** BIOS/UEFI boots the machine. Compilers (B) and assemblers (C) translate code; D plays media.
- Q22. A.** UEFI succeeds legacy BIOS. B, C, and D are unrelated physical items.
- Q23. A.** Drivers are control software. B, C, and D are hardware objects.
- Q24. A, B, C.** POST, OS loading, and device init are boot steps. Printing (D) is not.
- Q25. A, B, C.** The boot order, driver role, and UEFI advantage are correct. D is false: firmware, not compilers, boots the OS.
- Q26. D.** Firmware must persist without power and is commonly stored in ROM/flash. Cache and RAM are volatile; printer memory is not the general answer.
- Q27. A.** BIOS firmware initializes hardware and starts booting. Drivers are loaded for device operation; spreadsheet/browser are applications. The cited key is provisional.
- Q28. A.** UEFI is firmware interface technology used to initialize the system and start the boot process. The other choices are unrelated.
- Q29. A.** Drivers let the OS control/communicate with hardware. The other options confuse storage, applications, and system software.
- Q30. A, B, C.** Firmware is software stored persistently; BIOS/UEFI participates in boot. A driver is software, not a circuit board.