

Lesson 16 Practice: Answers and Rationales

JKSSB Computer Awareness

October 10, 2026

Provenance: All 25 items are original exam-pattern questions (*[Original]* plus the *[JKSSB FAA-pattern]*, *[JKPSI-pattern]*, *[SSC CGL-pattern]*, and *[JKSSB-pattern]* extension items, including MSQs); none reproduces an official paper item.

- Q1. A.** USB stands for Universal Serial Bus. B, C, and D are not expansions of the abbreviation.
- Q2. A.** HDMI stands for High-Definition Multimedia Interface. B drops “Multimedia”; C changes “Definition” to “Digital”; D uses “Memory” instead of “Multimedia”.
- Q3. A.** VGA stands for Video Graphics Array. B, C, and D are not the correct full forms.
- Q4. A.** RJ-45 stands for Registered Jack 45. B, C, and D are not the correct expansion of “RJ”.
- Q5. A.** SATA stands for Serial Advanced Technology Attachment (Serial ATA). B, C, and D are not the correct expansion.
- Q6. D.** RJ-45 is the Ethernet network connector, not a video output port. HDMI (A), DisplayPort (B), and VGA (C) are all display ports.
- Q7. C.** USB Type-C is reversible and can be inserted either way up. Type-A (A), Type-B (B), and Micro-USB (D) are not orientation-independent.
- Q8. B.** HDMI is digital and carries audio, while VGA is analog and carries video only. A reverses the classification; C wrongly gives VGA audio; D swaps the two.
- Q9. B.** RJ-45 is the eight-pin connector for a wired Ethernet LAN. RJ-11 (A) is the smaller telephone jack; USB-C (C) and HDMI (D) are not network connectors.
- Q10. A.** Statements I and II are correct: USB supplies power and supports hot swapping. III is false because VGA carries video only. B includes false III; C includes false III and omits II; D includes false III.
- Q11. B.** A port number such as 80 or 443 is a logical (software) port that names a service. A wrongly calls it a physical socket; C confuses it with pin count; D confuses it with cable speed.
- Q12. B.** DisplayPort is designed mainly for computers and monitors and supports high refresh rates and multi-monitor setups. VGA (A) is an older analog port; RJ-45 (C) is networking; SATA (D) is storage.
- Q13. A.** VGA is the analog, video-only port now largely replaced by HDMI and DisplayPort. HDMI (B) and DisplayPort (C) are digital; USB-C (D) is a connector type, not the analog video port.

- Q14. B.** Hot swapping is the ability to attach or remove a device while the computer is running. Cold boot (A), fragmentation (C), and multiplexing (D) are unrelated.
- Q15. A.** SATA connects internal drives (HDD, SSD, optical drive) to the motherboard. HDMI (B) is video; RJ-45 (C) is networking; the 3.5 mm jack (D) is audio.
- Q16. B.** TRRS adds a microphone channel to stereo audio, while TRS (A) carries stereo audio only. RJ-45 (C) is networking; VGA (D) is video.
- Q17. B.** An Ethernet (RJ-45) port typically connects a wired network router, so this pairing is correct. A pairs HDMI with headphones (HDMI is for displays); C pairs VGA with a printer; D pairs SATA with a keyboard (SATA is for storage drives).
- Q18. B.** SATA is a storage interface for drives. USB (A), HDMI (C), and the audio jack (D) are general-purpose peripheral or display ports, not storage interfaces.
- Q19. A.** eSATA (external SATA) connects an external storage drive. B, C, and D describe monitor, microphone, and network connections, which use other ports.
- Q20. A.** This statement is precise: USB is the standard, USB-C is a connector type, and a USB port is the socket. B wrongly calls the connector the socket; C wrongly says port and connector are identical; D wrongly calls HDMI analog (it is digital).
- Q21. A.** USB is the standard printer interface. VGA (B) drives displays; C and D do not connect printers.
- Q22. A.** HDMI combines audio and video. B, C, and D name signals HDMI does not exclusively carry.
- Q23. A.** RJ-45 terminates Ethernet LAN cables. B, C, and D are other connectors.
- Q24. A, B, C.** USB, HDMI, and Ethernet are interfaces. A stapler slot (D) is not a computer port.
- Q25. A, B, C.** The USB, HDMI, and RJ-45 roles are correct. D is false: VGA carries analog video, not digital audio.
- Q26. A.** HDMI commonly carries digital audio and video. RJ-11 is associated with telephone wiring, PS/2 with legacy keyboard/mouse connections, and VGA carries analog video.
- Q27. A.** RJ-45 is commonly used for Ethernet. HDMI and VGA serve displays; a 3.5 mm jack serves analog audio.
- Q28. A.** USB Type-C is a reversible physical connector. It can carry different signals depending on implementation; the other options confuse it with unrelated interfaces.
- Q29. A.** TCP port 80 is a logical endpoint number. The others are physical connectors.
- Q30. A, B, C.** The first three pairings are standard uses. MICR, not VGA, reads magnetic-ink characters.