

Lesson 11 Practice: Answers and Rationales

JKSSB Computer Awareness

October 10, 2026

Provenance: All 20 items are *[Original]*; the answer key is the author's. No official JKSSB key is claimed.

- Q1. C.** A full backup copies all selected files and folders on every run. Incremental (A) and differential (B) copy only changes; an image (D) is a whole-system clone, a coverage type rather than the “copy everything each run” definition.
- Q2. B.** An incremental backup captures changes since the last backup of any type. A describes differential; C is not a backup rule; D is not a basis for change tracking.
- Q3. C.** A differential backup captures changes since the last full backup. A describes incremental; B is an arbitrary interval; D excludes modified files, which is wrong.
- Q4. B.** Incremental looks back to the immediately preceding backup of any type; differential always looks back to the last full backup. A swaps the two definitions; C wrongly makes them identical; D ignores that both back up user data, not just the OS.
- Q5. A.** An incremental restore needs the last full backup plus every incremental applied in sequence, because each holds only its own slice of changes. B and C would lose intermediate changes; D ignores the chain entirely.
- Q6. B.** A differential restore needs the last full backup plus only the most recent differential, which already contains all changes since that full backup. A overstates the requirement; C omits the full baseline; D names the wrong type.
- Q7. C.** A full backup repeats all selected data each run, so it is the largest and slowest to create. Incremental (A) is the smallest and fastest; differential (B) is in between.
- Q8. C.** The full backup is heaviest to create but fastest to restore, since one complete set suffices. Incremental (A) is fast to create but slow to restore; differential (B) is intermediate; file-level (D) does not imply a single complete restore set.
- Q9. B.** An image is a complete clone of a system, including OS, settings and data. A and D describe narrow copies; C describes a differential, not an image.
- Q10. B.** File-level backup copies selected files and folders rather than a whole system. A describes an image; C narrows it incorrectly; D confuses file-level backup with RAID.
- Q11. D.** Defragmentation reorganises file placement on a disk; it is not a backup type. Full, incremental and differential (A, B, C) are the three time-based backup types.

- Q12. A.** The 3-2-1 rule is 3 copies, 2 different media, 1 copy off-site. B swaps the roles of the numbers; C invents a frequency scheme; D confuses backup types with the rule.
- Q13. B.** In 3-2-1 the 2 stands for two different types of storage media. A misreads it as off-site copies (that is the “1”); C and D attach meanings the rule does not carry.
- Q14. A.** RAID expands to Redundant Array of Independent Disks, and it provides redundancy (uptime), not backup (recovery). B, C and D give wrong expansions and wrongly treat RAID as a backup mechanism.
- Q15. A.** Statements I and II are correct: full copies everything, and differential tracks changes since the last full backup. III is false — an incremental tracks changes since the last backup of any type, not specifically the last full. B and D wrongly include III; C omits I.
- Q16. A.** A backup is a recoverable copy, storage is the working primary copy, and an archive is old data kept for long-term retention. B collapses the three into one; C mistakes the live working file for a backup; D misidentifies an archive as a RAID disk.
- Q17. A.** Cloud backup stores copies on remote servers, supplying an off-site copy. B wrongly equates it with RAID; C describes a local copy, which is not off-site; D is a category error, since cloud is a location, not a backup type.
- Q18. A.** An offline backup is disconnected from the network, which limits ransomware spread across connected drives. B describes an online backup; C denies a backup exists; D describes volatile memory, not backup media.
- Q19. B.** Rotation keeps several dated backup sets so an older clean copy survives if corruption is found late. A is unrelated to CPU clocks; C confuses rotation with encryption; D wrongly substitutes RAID for a backup strategy.
- Q20. C.** An incremental backup is defined as changes since the last backup of any type. A assigns the differential definition to the wrong type; B assigns the differential’s “last full” rule to incremental; D describes file-level, not image.
- Q21. A.** Incremental backups capture changes since the previous backup. B copies everything; C and D are not backups.
- Q22. A.** Each incremental in the chain is needed after the full backup. B, C, and D omit required backup sets.
- Q23. A.** RAID gives redundancy/performance across disks. B, C, and D describe unrelated peripherals.
- Q24. A, B, C.** Full, incremental, and differential are backup types. Formatting (D) erases rather than backs up.
- Q25. A, B, C.** The three backup definitions are standard. D is false: sync mirrors current state while backup keeps restorable copies.
- Q26. A.** A full backup copies the entire selected set. Incremental copies changes since the latest backup; differential copies changes since the latest full backup.

- Q27. A.** Incremental backups record changes since the most recent backup. Differential backups use the last full backup as their reference point.
- Q28. A.** Each differential backup includes changes since the last full backup, so the set can grow. Incrementals reset their comparison after each backup.
- Q29. A.** The rule calls for three copies, two different media, and one off-site copy. The other choices do not provide this redundancy.
- Q30. A, B, C.** Off-site, tested, and isolated copies improve recoverability. RAID improves availability but does not protect against deletion, corruption, or every disaster.

Concepts That Click