MC 451 Inferencing Data in R rubric

100 points. Due Friday, December 4, 11:59 PM.

How this is scored. Add the points from each row; the total is out of 100. A first attempt is graded forgivingly: a part that is there but incomplete earns partial credit, and 0 is kept for a part that is missing. Submissions are unlimited before the deadline, so you can revise and submit again.

- Run all four tests: a chi-square test of independence with `v2v::run_chi_square()`; an independent t-test with `v2v::run_t_test()` (Welch's version); a one-way ANOVA with `aov()` and `summary()`; and a linear regression with `lm()` and `summary()`. You choose the variables; the variable types decide the test.
- Every script opens with a settings block: load the data, rename the variables you use to outcome, `group2`, `group3`, predictor, `cat_a`, and `cat_b`, and make the categorical ones factors. The code below the block uses only those names. This is what lets the same script run on your own data for the White Paper.
- How this loses points: reporting p and stopping. The effect sizes are worth twice the execution here, on purpose: a p-value says something happened, and only the effect size says whether it matters.
- What it feeds: your White Paper, which runs this same script on your own variables after you change its settings block. The Twitch results stay here; the paper reports only what your own data shows, and only the tests your questions call for.

Inferencing Data in R, 100 points

Criterion	Exemplary	Proficient	Developing	Beginning
Hypotheses 8 points	**8 points.** Four hypotheses in plain English, written before any code, one for each test, each naming its variables and the relationship you expect.	**6 to 7 points.** Four stated before the code, but one variable is vague, or one hypothesis is a topic instead of a relationship.	**4 to 5 points.** Fewer than four, or stated after the results.	**0 to 3 points.** Missing.
Test choice with its reason 12 points	**12 points.** Each hypothesis takes the test its variable types call for (two categorical: chi-square test of independence; a two-group category against a continuous variable: independent t-test; a category with three or more groups against a continuous variable: one-way ANOVA; a continuous outcome and a continuous predictor: linear regression), with one sentence on why that test and not another.	**9 to 11 points.** The right four tests, but a reason is missing or would fit any test.	**6 to 8 points.** A test that does not fit its hypothesis's variable types, with a reason given.	**0 to 5 points.** No tests chosen, or tests that do not fit with no reason.

Criterion	Exemplary	Proficient	Developing	Beginning
Execution, including the settings block 12 points	**12 points.** All four tests run in your script on your analysis dataset, the output shown is what the code produces, and the script opens with the settings block, with the code below it using only the names the block sets.	**9 to 11 points.** All four run, but the settings block is missing or the code below it names the Twitch columns directly, or one test runs on a different variable than its hypothesis names with no word on why.	**6 to 8 points.** The code stops with an error, or the output is pasted in instead of produced.	**0 to 5 points.** Not run.
APA reporting 20 points	**20 points.** Each of the four reported in APA format with the test statistic, the degrees of freedom, the p-value, and the n.	**15 to 19 points.** One of the four pieces is missing on one or more tests, most often the n or the degrees of freedom.	**10 to 14 points.** The statistic and p only, or numbers copied from the console without APA form.	**0 to 9 points.** Not reported.
Effect sizes 24 points	**24 points.** The right statistic for each test (Cramér's V, Cohen's d, eta-squared computed from the sums of squares, and R-squared with the slope in your outcome's units), each with what it means in the units of the data rather than only as a label such as "small".	**18 to 23 points.** All four reported with their labels, but one has no translation into what it means for the data.	**12 to 17 points.** Computed but not explained, or the wrong measure for a test.	**0 to 11 points.** Missing: reporting p and stopping. A p-value says something happened; only the effect size says whether it matters.
Interpretation 16 points	**16 points.** Two to three sentences in plain English after each test, saying what the result means for its hypothesis.	**12 to 15 points.** Plain English, but it restates the numbers without saying what they mean for the hypothesis.	**8 to 11 points.** One sentence each, which usually means the "so what" is missing, or a reading that treats a small p as a large effect.	**0 to 7 points.** None.

Criterion	Exemplary	Proficient	Developing	Beginning
What the results do not license 8 points	**8 points.** One paragraph: a significant test on this sample is not a claim about Twitch, and a variable that belongs to a channel (its game, its audience) varies across about fifty channels, not tens of thousands of messages.	**6 to 7 points.** A limit, but it covers only one of the two points.	**4 to 5 points.** A generic limit ("more research is needed"), or a limit of the data in general rather than of these results.	**0 to 3 points.** Missing.

Before you submit

Inferential Check recomputes a chi-square or a t test from your own table or group figures and returns the statistic, the degrees of freedom, p, the effect size, the assumptions your data may be breaking, and the APA sentence to compare against what you wrote. It is a second opinion on your R output, not a replacement for it. It does not grade, and nothing you enter leaves your machine. It does not cover ANOVA or regression, so check those two against the worked examples in Chapter 13.