```
MockActualCall
   + returnFunctionPointerValue

    returnFunctionPointerValue

   OrDefault
   + MockActualCall()
   + ~MockActualCall()
   + withName()
   + withCallOrder()
   + withParameter()
   + withParameter()
   + withParameter()
   + withParameter()
   + withParameter()
   + withParameter()
    그리고 40개 더...
     MockCheckedActualCall
+ returnFunctionPointerValue
+ returnFunctionPointerValue
OrDefault

    functionName

- callOrder
- reporter
- state
- matchingExpectation
- potentiallyMatchingExpectations
- allExpectations

    outputParameterExpectations

+ MockCheckedActualCall()
+ ~MockCheckedActualCall()
+ withName()
+ withCallOrder()
+ withBoolParameter()
+ withIntParameter()
+ withUnsignedIntParameter()
+ withLongIntParameter()
+ withUnsignedLongIntParameter()
+ withDoubleParameter()
 그리고 33개 더...
# setName()
# getName()
# getTest()
# callHasSucceeded()
# copyOutputParameters()
# completeCallWhenMatchIsFound()
# failTest()
# checkInputParameter()
# checkOutputParameter()
# callIsInProgress()
# setState()
```

- addOutputParameter()

cleanUpOutputParameterList()