

```
In [1]: n=eval(input())
```

```
python
```

```
-----  
-  
NameError                                Traceback (most recent call las  
t)  
Cell In[1], line 1  
----> 1 n=eval(input())  
  
File <string>:1  
  
NameError: name 'python' is not defined
```

```
In [ ]: if <condition>  
        elif <condtion>  
        else # No condition
```

```
In [2]: if a==10  
        print('hello')
```

```
Cell In[2], line 2  
    print('hello')  
    ^  
IndentationError: expected an indented block after 'if' statement on line  
1
```

```
In [4]: if a==10:  
        print('hello')
```

```
-----  
-  
NameError                                Traceback (most recent call las  
t)  
Cell In[4], line 1  
----> 1 if a==10:  
      2     print('hello')  
  
NameError: name 'a' is not defined
```

```
In [ ]: summ=10  
        max=25
```

Functions

- Reuse any part of code

With out arguments

```
In [6]: n1=10
n2=20
add=n1+n2
print("the addition of {} and {} is {}".format(n1,n2,add))
```

the addition of 10 and 20 is 30

```
In [ ]: def <function_name>():
# write your code here
```

```
In [20]: def addition():
n1=10
n2=20
add=n1+n2
print("the addition of {} and {} is {}".format(n1,n2,add))
```

```
In [21]: # The output will not display untill unless you call the function
```

```
In [22]: addition()
```

the addition of 10 and 20 is 30

```
In [23]: def hello():
n1=eval(input('enter number'))
print('hello')
print('im writing function')
```

```
In [24]: hello()
```

enter number50
hello
im writing function

```
In [ ]:
```

```
In [ ]: but how did python execute 2nd and not 1st function.
```

```
In [17]: a=100
a=200

# why a is not equal to 100
```

```
In [18]: print(a)
```

200

```
In [19]: a=1000
```

```
In [ ]: # python will latest value one
```

```
In [ ]: # In this particular cell : 500lines
```

```
In [ ]: # lin1
```

```
In [ ]: # lin2
```

```
In [ ]: # lin3
```

```
In [25]: n1=100
```

```
In [26]: n2=200
```

```
In [27]: print(n1+n2)
```

300

```
In [29]: def hello_world():  
         print('hello good morning')
```

```
hello_world()
```

hello good morning

```
In [ ]: # Take three numbers find the average  
# WAP ask the user enter 3 numbers  
# n1=eval(input())  
# n2=eval(input())  
# n3=eval(input())  
# avg=(n1+n2+n3)/3  
# First write normal code  
# Then implemnt the function
```

```
In [30]: num1=eval(input("enter number1:"))  
num2=eval(input("enter number2:"))  
num3=eval(input("enter number3:"))  
avg=(num1+num2+num3)/3  
print("the average of {},{} and {} is {}".format(num1,num2,num3,avg))
```

enter number1:20

enter number2:30

enter number3:40

the average of 20,30 and 40 is 30.0

```
In [37]: def avg():
          num1=eval(input("enter number1:"))
          num2=eval(input("enter number2:"))
          num3=eval(input("enter number3:"))
          avg=(num1+num2+num33333)/3
          print("the average of {},{} and {} is {}".format(num1,num2,num3,avg))
```

```
In [38]: avg()
```

```
enter number1:100
enter number2:100
enter number3:100
```

```
-----
-
NameError                                Traceback (most recent call last)
Cell In[38], line 1
----> 1 avg()

Cell In[37], line 5, in avg()
      3 num2=eval(input("enter number2:"))
      4 num3=eval(input("enter number3:"))
----> 5 avg=(num1+num2+num33333)/3
      6 print("the average of {},{} and {} is {}".format(num1,num2,num3,avg))
```

NameError: name 'num33333' is not defined

Note:

we are not sure , the function is defined correct or wrong

untill unless we call the function

```
In [39]: try:
          num1=eval(input("enter number1:"))
          num2=eval(input("enter number2:"))
          num3=eval(input("enter number3:"))
          avg=(num1+num2+num3)/3
          print("the average of {},{} and {} is {}".format(num1,num2,num3,avg))

          except Exception as e:
              print(e)
```

```
enter number1:20
enter number2:30
enter number3:40
the average of 20,30 and 40 is 30.0
```

```
In [41]: def avg1():
    try:
        num1=eval(input("enter number1:"))
        num2=eval(input("enter number2:"))
        num3=eval(input("enter number3:"))
        avg=(num1+num2+num3333)/3
        print("the average of {},{} and {} is {}".format(num1,num2,num3,avg))

    except Exception as e:
        print(e)

avg1()
```

```
enter number1:20
enter number2:30
enter number3:40
name 'num3333' is not defined
```

```
In [ ]: # WAP ask the user enter bill amount
#       ask the user enter tip amount
#       calculate total bill

# First write normal code
# Then implement the function
```

```
In [42]: def Bill():
    try:
        Bill_Amt= eval(input("Enter Bill amount"))
        Tip_Amt= eval(input("Enter Tip amount"))
        Total_Bill = Bill_Amt+Tip_Amt
        print("Total Bill is {}".format(Total_Bill))
    except exception as e:
        print(e)

Bill()
```

```
Enter Bill amount20
Enter Tip amount30
Total Bill is 50
```

```
In [ ]: #WAP ask the user get a random number between 1 to 100
# print it is even or odd number
# Implement using function
# import <package>
# num=<package>.<method_name>(1,100)
# if <condition>:
#     print("{} is an even number".format(num))
# else:
#     print("{} is an odd number".format(num))
```

```
In [44]: import random
num=random.randint(1,100)
if num%2==0:
    print("{} is an even number".format(num))
else:
    print("{} is an odd number".format(num))
```

54 is an even number

```
In [47]: import random
def even_odd1():
    print('we are implementing even odd function')
    print("take one number")
    num=random.randint(1,100)
    if num%2==0:
        print("the remainder is zero")
        print("{} is an even number".format(num))
    else:
        print("the remainder is not equal to zero")
        print("{} is an odd number".format(num))

even_odd1()
```

we are implementing even odd function
take one number
the remainder is zero
76 is an even number

```
In [48]: import random
def even_odd2():
    try:
        print('we are implementing even odd function')
        print("take one number")
        num=random.randint(1,100)
        if num%2==0:
            print("the remainder is zero")
            print("{} is an even number".format(num))
        else:
            print("the remainder is not equal to zero")
            print("{} is an odd number".format(num))

    except Exception as e:
        print(e)

even_odd2()
```

we are implementing even odd function
take one number
the remainder is zero
8 is an even number

```
In [49]: import random
print('hello')
print("python")
def even_odd2():
    try:
        print('we are implementing even odd function')
        print("take one number")
        num=random.randint(1,100)
        if num%2==0:
            print("the remainder is zero")
            print("{} is an even number".format(num))
        else:
            print("the remainder is not equal to zero")
            print("{} is an odd number".format(num))

    except Exception as e:
        print(e)

print('calling function')
even_odd2()
print("done!")
```

```
hello
python
calling function
we are implementing even odd function
take one number
the remainder is zero
50 is an even number
done!
```

```
In [ ]: def addition():
        n1=20
        n2=30
        print('addition:',n1+n2)

        print("mul function starts")
        def mul():
            n1=20
            n2=30
            print('mul:',n1*n2)
            print("mul is done")

        print("subtraction function starts")
        def sub():
            n1=20
            n2=30
            print('sub:',n1-n2)
            print("subtraction is done")

        print("anything remains")
        print("no")
        print("then call the function")

        sub()
        mul()
        addition()
```

```
In [ ]:
```

```
In [ ]: def addition():
        n1=10
        n2=20
        add=n1+n2
        print("the addition of {} and {} is {}".format(n1,n2,add))

        addition()
```

```
In [ ]: def Bill():
        try:
            Bill_Amt= eval(input("Enter Bill amount"))
            Tip_Amt= eval(input("Enter Tip amount"))
            Total_Bill = Bill_Amt+Tip_Amt
            print("Total Bill is {}".format(Total_Bill))
        except exception as e:
            print(e)

        Bill()
```

```
In [ ]: addition()
        Bill()
```

- if you are not mentioning any values inside the function bracket
- with out arguments or with out parmeters
- arguments or parameters

With arguments

```
In [ ]: def addition():
        n1=10
        n2=20
        add=n1+n2
        print("the addition of {} and {} is {}".format(n1,n2,add))

        addition()

        # 1Q) inside function how many variables are there
        #      3 variables are there
        # 2Q) how many user provided variables
        #      2 variables
```

```
In [53]: def addition(n1,n2): # arguments
        add=n1+n2
        print("the addition of {} and {} is {}".format(n1,n2,add))

        addition(100,200) # n1=100 n2=200

        the addition of 100 and 200 is 300
```

```
In [55]: def addition(n1,n2):
        add=n1+n2
        print("the addition of {} and {} is {}".format(n1,n2,add))

        addition(200)
```

```
-----
-
TypeError                                Traceback (most recent call last)
Cell In[55], line 6
      3     add=n1+n2
      4     print("the addition of {} and {} is {}".format(n1,n2,add))
----> 6 addition(200)

TypeError: addition() missing 1 required positional argument: 'n2'
```

```
In [57]: def addition11():
        add=n111+n222
        print("the addition of {} and {} is {}".format(n1,n2,add))

        addition11(200,300)    # what is the error
```

```
-----
-
TypeError                                Traceback (most recent call las
t)
Cell In[57], line 5
      2     add=n111+n222
      3     print("the addition of {} and {} is {}".format(n1,n2,add))
----> 5 addition11(200,300)

TypeError: addition11() takes 0 positional arguments but 2 were given
```

```
In [58]: # Implement below code using with arguments
def avg(num1,num2,num3):
    print("num1:",num1) # 20
    print("num2:",num2) #30
    print("num3:",num3) # 40
    avg=(num1+num2+num3)/3
    print("the average of {},{} and {} is {}".format(num1,num2,num3,avg))

avg(20,30,40)
```

```
num1: 20
num2: 30
num3: 40
the average of 20,30 and 40 is 30.0
```

```
In [67]: num=12345
v1=num%10      #5
v11=num//100
v11 # 1234

v2=v11%10     # 4
v2
v22=v11//10 # 123
v22

# 12345===== 1234=====4
# 54321
```

Out[67]: 12

```
In [69]: num=12345
v1=num%100
v1
```

Out[69]: 45

```
In [66]: v11=num//10
v11
```

Out[66]: 1234

```
In [64]: if a=10:
        print('h')
```

Cell In[64], line 1
if a=10:
 ^
SyntaxError: invalid syntax. Maybe you meant '==' or ':=' instead of '='?

```
In [ ]: 7260927090
```

```
In [ ]: 12345 ===== 54
```

```
In [70]: 12345%10
```

Out[70]: 5

```
In [ ]: 12345 ===== 4?
```

```
In [ ]: 1234?
```

```
In [71]: print(5,end='')
        print(4)
```

54

```
In [ ]: 12345%10=====> 5
```

```
In [73]: 12345//10
```

Out[73]: 1234

```
In [78]:
```

Out[78]: 2

```
In [79]: 180
        100
```

Out[79]: 100

```
In [ ]: 1100
        150
        310
```

```
In [ ]: def Bill():
        try:
            Bill_Amt= eval(input("Enter Bill amount"))
            Tip_Amt= eval(input("Enter Tip amount"))
            Total_Bill = Bill_Amt+Tip_Amt
            print("Total Bill is {}".format(Total_Bill))
        except exception as e:
            print(e)

Bill()

# First how many important(user) variables are there inside the function
# Bill_Amy, Tip_AMT
```

```
In [2]: def Bill(Bill_Amt,Tip_Amt):
        try:
            Total_Bill = Bill_Amt+Tip_Amt
            print("Total Bill is {}".format(Total_Bill))
        except exception as e:
            print(e)

Bill(1000,50)

# What error will come
# Name error: Bill_Amt not defined
```

Total Bill is 1050

```
In [ ]: # WAP ask the user enter number
        # and find the square of the number

        # M-1: Write in normal ways
        # M-2: write in function with out argument
        # M-3: Weite in function with argument
```

```
In [3]: number=eval(input("enter a number"))
        print("the square of {} is {}".format(number,number*number))
```

enter a number5
the square of 5 is 25

```
In [4]: def square(): # In side the bracket No arguments
        number=eval(input("enter a number"))
        print("the square of {} is {}".format(number,number*number))

square()
```

enter a number6
the square of 6 is 36

```
In [5]: def square(number):
        print("the square of {} is {}".format(number,number*number))

        square(7)

# How many variables are there inside the function: number

the square of 7 is 49
```

```
In [ ]: # WAP ask there user
# get one random number between 1 to 20
# enter a number
# compare these two number
# if both are same: print("you won")
# else: print(lost)

#M-1: Write in normal way
#M-2: Create a function with out argument
#M-3: Create a function with argument
```

```
In [7]: #M-1:
import random
random_num=random.randint(1,20)
num=eval(input("enter number:"))

if random_num==num:
    print("you won")
else:
    print("you lost")
```

```
enter number:7
you lost
```

```
In [9]: #M-2:
import random
def compare():
    random_num=random.randint(1,20)
    num=eval(input("enter number:"))

    if random_num==num:
        print("you won")
    else:
        print("you lost because the random number is:",random_num)

compare()
```

```
enter number:9
you lost because the random number is: 17
```

```
In [14]: #M-2:
import random
def compare(num):
    random_num=random.randint(1,20)
    if random_num==num:
        print("you won")
    else:
        print("you lost because the random number is:",random_num)

compare(eval(input("enter number"))) # keyboard pass
```

```
enter number20
you lost because the random number is: 13
```

```
In [13]: #M-2:
import random
def compare(num):
    random_num=random.randint(1,20)
    if random_num==num:
        print("you won")
    else:
        print("you lost because the random number is:",random_num)

compare(20) # direct pass
```

```
you lost because the random number is: 19
```

```
In [ ]: #M-2:
import random
def compare(num):
    random_num=random.randint(1,20)
    if random_num==num:
        print("you won")
    else:
        print("you lost because the random number is:",random_num)

value=20
compare(value) # direct pass
```

```
In [15]: #M-2:
import random
def compare(random_num,num):

    if random_num==num:
        print("you won")
    else:
        print("you lost because the random number is:",random_num)

value_random=random.randint(1,20)
value=eval(input("enter number"))

compare(value_random,value)

# Step-1: import random
# step-2: function will defin: not give
# step-3: value_random
# step-4: value
# step-5: calling the function=====> step-2
#                                     print won/loss
```

enter number7
you lost because the random number is: 18

```
In [16]: # Step-1: import random
# step-3: value_random
# step-4: value
# step-2: function will defin: not give
# step-5: calling the function=====> step-2
#                                     print won/loss
```

```
import random

value_random=random.randint(1,20)
value=eval(input("enter number"))

def compare(random_num,num):

    if random_num==num:
        print("you won")
    else:
        print("you lost because the random number is:",random_num)

compare(value_random,value)
```

enter number8
you lost because the random number is: 9

```
In [ ]: # Step-1: import random
# step-2: function will defin: not give
# step-5: calling the function=====> step-2
#                                     print won/loss
# step-3: value_random
# step-4: value
```

```
In [17]: import random
random.randint(1,20)
```

Out[17]: 3

```
In [18]: from random import randint
randint(1,20)
```

Out[18]: 16

```
In [25]: import random

#=====defined=====
def megha(random_num,num):

    if random_num==num:
        print("you won")
    else:
        print("you lost because the random number is:",random_num)

#=====calling=====
#
megha(20,10)
```

enter number9
you lost because the random number is: 2

```
In [ ]: # WAP ask the user enter salary
#       ask the user enter tax percentage
#       calulate total tax to pay
```

```
In [29]: import random
def compare(user_num,ran_num):
    try:
        if ran_num == user_num:
            print("You won")
        else:
            print("You are not a winner")
    except exception as e:
        print(e)

#user_num=eval(input("enter number"))
#ran_num=random.randint(1,20)
#compare(user_num,ran_num)

compare(eval(input("Enter a number:")),
        random.randint(1,20))
```

Enter a number:9
You are not a winner


```
In [31]: def tax_cal(salary,tax_per):
        total_tax=salary*tax_per/100
        print("The total tax is:",total_tax)

        tax_cal(10000,10)
```

The total tax is: 1000.0

```
In [ ]: # How do you pass the value
def tax_cal(salary,tax_per):
    total_tax=salary*tax_per/100
    print("The total tax is:",total_tax)

    tax_cal(10000,10)           # Direct pass
```

```
In [33]: # How do you pass the value
def tax_cal(salary,tax_per):
    total_tax=salary*tax_per/100
    print("The total tax is:",total_tax)

    val1=eval(input("enter salary:"))
    val2=eval(input("enter tax perc:"))
    tax_cal(val1,val2)          # keyboard pass
```

```
enter salary:10000
enter tax perc:10
The total tax is: 1000.0
```

default arguments

```
In [ ]: # tax percentage is always=20
        # fixed
        # default parameter
```

```
In [34]: # How do you pass the value
def tax_cal(salary,tax_per=20):
    total_tax=salary*tax_per/100
    print("The total tax is:",total_tax)

    tax_cal(10000)
```

The total tax is: 2000.0

```
In [36]: def avg(num1,num2,num3):
        add=(num1+num2+num3)
        avg=add/3
        print("the avg is:",avg)

        avg(20,30,40)
```

the avg is: 30.0

```
In [43]: def avg(num1,num2,num3=50):
          print("num1:",num1)           # 20
          print("num2:",num2)           # 20
          print("num3:",num3)           # 100
          add=(num1+num2+num3)
          avg=add/3
          print("the avg is:",avg)

avg(20,20,100)
```

```
num1: 20
num2: 20
num3: 100
the avg is: 46.666666666666664
```

```
In [45]: def avg(num1,num2=200,num3):
          print("num1:",num1)           #
          print("num2:",num2)           #
          print("num3:",num3)           #
          add=(num1+num2+num3)
          avg=add/3
          print("the avg is:",avg)

avg(200,300)
```

Cell In[45], line 1

```
def avg(num1,num2=200,num3):
    ^
```

SyntaxError: non-default argument follows default argument

```
In [46]: def avg(num1,num2,num3=50):
          print("num1:",num1)           # 20
          print("num2:",num2)           # 20
          print("num3:",num3)           # 100
          add=(num1+num2+num3)
          avg=add/3
          print("the avg is:",avg)

val1=20
val2=30
avg(val1,val2)
```

```
num1: 10000
num2: 30
num3: 50
the avg is: 3360.0
```

In []:

In []:

In []:

```
In [42]: num1,num2,num3=100
print(num1,num2,num3)
```

```
-----
-
TypeError                                Traceback (most recent call las
t)
Cell In[42], line 1
----> 1 num1,num2,num3=100
      2 print(num1,num2,num3)

TypeError: cannot unpack non-iterable int object
```

```
In [ ]: num1,num2,num3=300 ===== valid
num1,num2=200,num3 ===== not
num1=100,num2=200,num3 ===== not
num1=100,num2,num3 ===== not
num1,num2=500,num3=300 ===== valid
```

```
In [ ]: def avg(num1,num2,num3=50):
        print("num1:",num1)           # 20
        print("num2:",num2)           # 20
        print("num3:",num3)           # 100
        num3=800
        add=(num1+num2+num3)
        avg=add/3
        print("the avg is:",avg)

avg(200,300,600)

# while defining function: num3=50
# while you are calling function num3=600
# after enter inside the function num3=800
```

- with out arguments
- with arguments
- default arguments

```
In [50]: import random
random.randint() # a

# (<excpeting 2 arguments>)
```

```
-----
-
TypeError                                Traceback (most recent call las
t)
Cell In[50], line 2
----> 1 import random
      2 random.randint()

TypeError: Random.randint() missing 2 required positional arguments: 'a' a
nd 'b'
```

```
In [54]: complex(7) # not provide: default
```

```
Out[54]: (7+0j)
```

```
In [56]: from random import randint  
         randint(10,20)
```

```
Out[56]: 19
```

```
In [ ]:
```

```
In [ ]: # function = method
```

```
In [58]: def summ(a=0,b=0):  
         print(a*b)  
  
         summ(5,10)
```

```
50
```

```
In [ ]: 7260927090
```