```
/**
 1
 2
 3
        @copyright © 2010 - 2020, Fraunhofer-Gesellschaft zur Foerderung der
 4
      * angewandten Forschung e.V. All rights reserved.
 5
 6
      * BSD 3-Clause License
 7
      * Redistribution and use in source and binary forms, with or without
 8
      * modification, are permitted provided that the following conditions are met:
 9
      * 1. Redistributions of source code must retain the above copyright notice,
10
            this list of conditions and the following disclaimer.
11
       2. Redistributions in binary form must reproduce the above copyright
12
            notice, this list of conditions and the following disclaimer in the
13
            documentation and/or other materials provided with the distribution.
14
      * 3. Neither the name of the copyright holder nor the names of its
15
            contributors may be used to endorse or promote products derived from
16
            this software without specific prior written permission.
17
18
      * THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
19
      * AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
20
      * IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
21
      * ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE
22
      * LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
23
      * CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
24
      * SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
25
      * INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
26
      * CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
27
      * ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
28
      * POSSIBILITY OF SUCH DAMAGE.
29
30
      * We kindly request you to use one or more of the following phrases to refer
31
      * to foxBMS in your hardware, software, documentation or advertising
32
      * materials:
33
34
      * ″ This product uses parts of foxBMS&req; ″
35
36
      * ″ This product includes parts of foxBMS® ″
37
38
      * ″ This product is derived from foxBMS&req; ″
39
40
      */
41
     /**
42
43
      * @file
                database.c
44
      * @author foxBMS Team
45
      * @date
               18.08.2015 (date of creation)
      * @ingroup ENGINE
46
      * @prefix DATA
47
48
49
      * @brief Database module implementation
50
51
      * Implementation of database module
52
```

```
53
 54
     /*======= Includes =======*/
 55
     #include "database.h"
56
57
     #include "diag.h"
58
     #include <string.h>
59
 60
     /*====== Macros and Definitions ===============*/
 61
 62
      * Maximum queue timeout time in milliseconds
 63
 64
     #define DATA QUEUE TIMEOUT MS
 65
66
 67
      * @brief Length of data Queue
68
 69
     #define DATA OUEUE LENGTH
                                    (1u)
71
     /**
 72
      * @brief Size of data Queue item
73
74
     #define DATA QUEUE ITEM SIZE sizeof(DATA QUEUE MESSAGE s)
75
76
     /*======== Static Constant and Variable Definitions =======*/
77
     /* FIXME Some uninitialized variables */
                                                                           81 typedef struct {
78
     static DATA BLOCK ACCESS s data block access[DATA MAX BLOCK NR];
                                                                                void *RDptr;
                                                                           83
                                                                                 void *WRptr;
79
     QueueHandle t data queue;
                                                                               DATA_BLOCK_ACCESS_s;
80
81
     /**
 82
 83
      * @brief size of Oueue storage
 84
85
      * The array to use as the queue's storage area.
      * This must be at least #DATA QUEUE LENGTH * #DATA QUEUE ITEM SIZE
86
87
      * /
88
     static uint8_t dataQueueStorageArea[ DATA_QUEUE_LENGTH * DATA_QUEUE_ITEM_SIZE ];
     /**
90
91
      * @brief structure for static data queue
 92
 93
     static StaticQueue t dataQueueStructure;
94
95
      /*======= Extern Constant and Variable Definitions ========*/
96
                                foxbms_code_v1p6p4_c29s06_databaseH.pdf
97
     /*====== Static
                                 98
                                     const DATA_BASE_HEADER_DEV_s data_base_dev = {
99
      /*====== Static
                                 304
                                        .nr_of_blockheader = sizeof(data_base_header)/sizeof(DATA_BASE_HEADER_s), /* number of blocks (and block
100
                                        headers) */
                                        .blockheaderptr
                                                     = &data_base_header[0],
101
     /*===== Extern
102
     void DATA_Init(void) {
                                                      126 typedef struct {
103
         if (sizeof(data_base_dev) == 0) {
                                                      127
                                                             uint8_t nr_of_blockheader;
                                                                                      Total number of blockheaders (blocks
104
             /* todo fatal error! */
                                                      128
                                                             DATA_BASE_HEADER_s *blockheaderptr;
                                                                                      of data in the database)
                                                      129 } DATA_BASE_HEADER_DEV_s; You, a mo
```

```
105
               while (1) {
106
                   /* No database defined - this should not have happened! */
107
108
          }
109
                                     This number is the same as DATA MAX BLOCK NR
110
           /* Iterate over database and set respective read/write pointer for each database entry */
111
          for (uint16 t i = 0; i < data base dev.nr of blockheader; i++) {</pre>
               /* Set write pointer to database entry */
112
               data_block_access[i].WRptr = (void*)*(uint32_t*) (data_base_dev.blockheaderptr + i);
113
               /* Set read pointer: read = write pointer */
114
                                                                                 pointing to the ith pair of data base header,
                                                                                 which is the pointer of the ith data block.
115
               data_block_access[i].RDptr = data_block_access[i].WRptr;
116
               /* Initialize database entry with 0, set read and write pointer in case double
117
118
               * buffering is used for database entries */
              uint8 t * startDatabaseEntryWR = (uint8 t *)data block access[i].WRptr;
119
120
               uint8 t * startDatabaseEntryRD = (uint8 t *)data block access[i].RDptr;
121
122
               for (uint16_t j = 0; j < (data_base_dev.blockheaderptr + i) -> datalength; j++) {
123
                   /* Set write pointer database entry to 0 */
124
                   *startDatabaseEntryWR = 0;
125
                   startDatabaseEntryWR++;
126
127
                   /* Set read pointer database entry to 0 - identical to write pointer
128
                   * if database entry is SINGLE BUFFERED */
129
                   *startDatabaseEntryRD = 0;
130
                   startDatabaseEntryRD++;
131
              }
132
          }
133
134
          /* Create queue to transfer data to/from database */
135
136
          /* Create a queue capable of containing a pointer of type DATA OUEUE MESSAGE s
137
          Data of Messages are passed by pointer as they contain a lot of data. */
138
          data queue = xQueueCreateStatic (DATA QUEUE LENGTH, DATA QUEUE ITEM SIZE, dataQueueStorageArea,
          &dataQueueStructure);
139
140
          if (data_queue == NULL_PTR) {
              /* Failed to create the queue */
141
142
              /* @ TODO Error Handling */
143
              while (1) {
144
                   /* TODO: explain why infinite loop */
145
              }
146
          }
147
      }
                                                                                                typedef struct {
148
                                                                                               /* FIXME what is the intention of this u
149
                                                                                                   You, a month ago | 1 author (You)
                                                                                            68
                                                                                                   union {
150
      void DB WriteBlock(void *dataptrfromSender, DATA BLOCK ID TYPE e blockID) {
                                                                                            69
                                                                                                      uint32_t
                                                                                                                       u32value;
151
          /* dataptrfromSender is a pointer to data of caller function
                                                                                            70
                                                                                                      uint32 t
                                                                                                                       *u32ptr;
152
              dataptr_toptr_fromSender is a pointer to this pointer
                                                                                            71
                                                                                                     void
                                                                                                                       *voidptr;
153
              this is used for passing message variable by reference
                                                                                            72
                                                                                                   } value:
154
              note: xQueueSend() always takes message variable by value */
                                                                                            73
                                                                                                   DATA_BLOCK_ID_TYPE_e
                                                                                                                      blockID;
          DATA_QUEUE_MESSAGE_s data_send_msq;
155
                                                                                            74
                                                                                                   DATA_BLOCK_ACCESS_TYPE_e
                                                                                                                      accesstype;
                                                                                            75 } DATA_QUEUE_MESSAGE_s;
```

```
156
          TickType t queuetimeout;
157
158
          queuetimeout = DATA_QUEUE_TIMEOUT_MS / portTICK_RATE_MS;
159
          if (queuetimeout == 0) {
160
              queuetimeout = 1;
161
162
163
          /* prepare send message with attributes of data block */
          data send msq.blockID = blockID;
164
165
          data_send_msg.value.voidptr = dataptrfromSender;
166
          data_send_msg.accesstype = WRITE_ACCESS;
167
          /* Send a pointer to a message object and
             maximum block time: queuetimeout */
168
          xQueueSend(data_queue, (void *) &data_send_msg, queuetimeout); The actual data writing happens in DATA_Task()
169
170
      }
171
172
173
      void DATA_Task(void) {
174
          DATA QUEUE MESSAGE s receive msg;
                                                 Better to be called queue message
175
          void *srcdataptr;
                                    Better to be called queue dataptr
176
          void *dstdataptr;
177
          DATA BLOCK ID TYPE e blockID;
178
          DATA BLOCK ACCESS TYPE e
                                      accesstype; /* read or write access type */
179
          uint16_t datalength;
180
181
          if (data queue != NULL PTR) {
182
              if (xQueueReceive(data_queue, (&receive_msg), (TickType_t) 1)) { /* scan queue and wait for a message up to
              a maximum amount of 1ms (block time) */
183
                   /* ptrrcvmessage now points to message of sender which contains data pointer and data block ID */
                   blockID = receive msq.blockID;
184
185
                   srcdataptr = receive msg.value.voidptr;
186
                   accesstype = receive msg.accesstype;
187
                   if ((blockID < DATA MAX BLOCK NR) && (srcdataptr != NULL PTR)) { /* plausibility check */
188
                       /* get entries of blockheader and write pointer */
189
                       if (accesstype == WRITE_ACCESS) {
190
                           /* write access to data blocks */
                           datalength = (data_base_dev.blockheaderptr + blockID) ->datalength;
191
                     void * dstdataptr = data block access[blockID].WRptr;
192
193
194
                               uint32 t *previousTimestampptr = NULL PTR;
                                                                              The code block to the left is an example of bad code. For time
195
                               uint32 t *timestampptr = NULL PTR;
                                                                              update, which should be saved in the database only, we can use the
196
                                                                              following code, for better readability:
197
                               /* Set/timestamp pointer */
                                                                              dstdataptr->previous timestap = dstdataptr->timestamp;
198
                               timestampptr = (uint32 t *)dstdataptr;
                                                                              dstdataptr->timestamp = OS getOSSysTick();
199
                               /* Set previous timestampptr */
200
                               previousTimestampptr = (uint32 t *) srcdataptr;
201 Increment the pointer to point
202 to the previous time stamp.
                               previousTimestampptr++;
203
                               /* Write previous timestamp */
                               *previousTimestampptr = *timestampptr;
204
                               /* Write timestamp */
205
                               *(uint32 * *) srcdataptr = OS getOSSysTick();
206
```

```
207
                                                queue dataptr
208
                             memcpy(dstdataptr, srcdataptr, datalength);
209
210
                     } else if (accesstype == READ ACCESS) {
211
                         /* Read access to data blocks */
212
                         datalength = (data_base_dev.blockheaderptr + blockID) ->datalength;
213
                         dstdataptr = srcdataptr;
214
                    void * srcdataptr = data_block_access[blockID].RDptr;
215
216
                         if (srcdataptr != NULL_PTR) {
217
                            memcpy(dstdataptr, srcdataptr, datalength);
218
                                   queue dataptr,
                         }
219
                     } else {
220
                 /* TODO: explain why empty else */
                                                     Should report error and exit.
221
222
                 }
223
224
             DIAG_SysMonNotify(DIAG_SYSMON_DATABASE_ID, 0); /* task is running, state = ok */
225
         }
226
     }
227
228
229
     STD RETURN TYPE e DB ReadBlock (void *dataptrtoReceiver, DATA BLOCK ID TYPE e blockID) {
230
         DATA_QUEUE_MESSAGE_s data_send_msg;
                                                   should be data access msg
231
         TickType_t queuetimeout;
232
233
         queuetimeout = DATA QUEUE TIMEOUT MS / portTICK RATE MS;
234
         if (queuetimeout == 0) {
235
             queuetimeout = 1;
236
         }
237
238
         /* prepare send message with attributes of data block */
239
         data send msq.blockID = blockID;
240
         data send msg.value.voidptr = dataptrtoReceiver;
241
         data_send_msg.accesstype = READ_ACCESS;
242
243
         /* Send a pointer to a message object and */
244
         /* maximum block time: queuetimeout */
2.45
         xQueueSend(data_queue, (void *) &data_send_msq, queuetimeout);
246
247
         return E OK;
248
     }
249
250
     251
```

NOTE: There should be two versions of DB\_ReadBlock and DB\_WriteBolck. The first is the current one, and the second is a new one which can read/write directly without using the Queue which blocks the caller of the function. This is especially useful for those data blocks that are short.