```
/**
 1
 2
 3
        @copyright © 2010 - 2020, Fraunhofer-Gesellschaft zur Foerderung der
 4
      * angewandten Forschung e.V. All rights reserved.
 5
 6
      * BSD 3-Clause License
 7
      * Redistribution and use in source and binary forms, with or without
      * modification, are permitted provided that the following conditions are met:
 8
 9
      * 1. Redistributions of source code must retain the above copyright notice,
10
            this list of conditions and the following disclaimer.
11
      * 2. Redistributions in binary form must reproduce the above copyright
12
            notice, this list of conditions and the following disclaimer in the
13
            documentation and/or other materials provided with the distribution.
14
      * 3. Neither the name of the copyright holder nor the names of its
15
            contributors may be used to endorse or promote products derived from
16
            this software without specific prior written permission.
17
18
      * THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
19
      * AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
20
      * IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
21
      * ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE
22
      * LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
23
      * CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
24
      * SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
25
      * INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
26
      * CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
27
      * ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
28
      * POSSIBILITY OF SUCH DAMAGE.
29
30
      * We kindly request you to use one or more of the following phrases to refer
31
      * to foxBMS in your hardware, software, documentation or advertising
32
      * materials:
33
34
      * ″ This product uses parts of foxBMS&req; ″
35
36
      * ″ This product includes parts of foxBMS® ″
37
38
      * ″ This product is derived from foxBMS&req; ″
39
40
      */
41
     /**
42
43
      * @file
               diag cfg.c
44
      * @author foxBMS Team
      * @date 09.11.2015 (date of creation)
45
46
      * @ingroup ENGINE CONF
47
      * @prefix DIAG
48
49
      * @brief Diagnostic module configuration
50
51
      * The configuration of the different diagnosis events defined in diag_cfg.h is set in the array
      * diag ch cfg[], e.g. initialization errors or runtime errors.
52
```

```
53
 54
       * Every entry of the diag ch cfg[] array consists of
 55
       * - name of the diagnosis event (defined in diag_cfg.h)
 56
       * - type of diagnosis event
57
       * - diagnosis sensitivity (after how many occurrences event is counted as error)
 58
       * - enabling of the recording for diagnosis event
 59
       * - enabling of the diagnosis event
 60
       * - callback function for diagnosis event if wished, otherwise dummyfu
 61
 62
       * The system monitoring configuration defined in diag_cfg.h is set in the array
 63
       * diag_sysmon_ch_cfg[]. The system monitoring is at the moment only used for
 64
       * supervising the cyclic/periodic tasks.
 65
 66
       * Every entry of the diag_sysmon_ch_cfq[] consists of
 67
       * - enum of monitored object
 68
       * - type of monitored object (at the moment only DIAG SYSMON CYCLICTASK is supported)
 69
       * - maximum delay in [ms] in which the object needs to call the DIAG_SysMonNotify function defined in diag.c
 70
       * - enabling of the recording for system monitoring
71
       * - enabling of the system monitoring for the monitored object
 72
       * - callback function if system monitoring notices an error if wished, otherwise dummyfu2
 73
 74
 75
      /*======= Includes =======*/
 76
      #include "diag_cfg.h"
 77
 78
      #include "database.h"
     #include "rtc.h"
 79
 80
      /*----*/ Macros and Definitions ----*/
 81
 82
 83
      /*====== Static Constant and Variable Definitions ======*/
 84
      static DATA BLOCK ERRORSTATE s error flags = { 0 };
 85
      static DATA BLOCK MOL FLAG s mol flags = { 0 };
      static DATA BLOCK RSL FLAG s rsl flags = { 0 };
 87
      static DATA_BLOCK_MSL_FLAG_s msl_flags = { 0 };
                                                                            DIAG_CH_LOW_COIN_CELL_VOLTAGE, /* coin cell voltage */
                                                                    208
 88
                                                                    209
                                                                            DIAG_CH_CRIT_LOW_COIN_CELL_VOLTAGE, /* coin cell voltage */
 89
      /*========= Static Function Prototypes ======== 210
                                                                            DIAG_CH_OPEN_WIRE, /* open-wire check */
                                                                    211
                                                                            DIAG_CH_PLAUSIBILITY_CELL_VOLTAGE, /* plausibility checks */
 90
      /* dummy functions */
                                                                    212
                                                                            DIAG_CH_PLAUSIBILITY_CELL_TEMP, /* plausibility checks */
 91
      static void dummyfu (DIAG_CH_ID_e ch_id, DIAG_EVENT_e event);
                                                                   213
                                                                            DIAG_CH_PLAUSIBILITY_PACK_VOLTAGE, /* plausibility checks */
      static void dummyfu2(DIAG_SYSMON_MODULE_ID_e ch_id);
 92
                                                                    214
                                                                            DIAG_CH_DEEP_DISCHARGE_DETECTED, /* DoD was detected */
 93
                                                                    215
                                                                            DIAG_ID_MAX, /* MAX indicator - do not change */
                                                                    216 } DIAG_CH_ID_e;
 94
      /* functions for SOA related events */
 95
      static void DIAG_overvoltage (DIAG_CH_ID_e ch_id, DIAG_EVENT_e event);
                                                                                                /** diagnosis check res
                                                                                           218
 96
      static void DIAG_undervoltage(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event);
                                                                                           219
                                                                                                typedef enum {
      static void DIAG overtemperature charge (DIAG CH ID e ch id, DIAG EVENT e event);
 97
                                                                                           220
                                                                                                    DIAG_EVENT_OK, /*!<
 98
      static void DIAG_overtemperature_discharge(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event);
                                                                                           221
                                                                                                    DIAG_EVENT_NOK, /*!
99
      static void DIAG undertemperature charge (DIAG CH ID e ch id, DIAG EVENT e event);
                                                                                                    DIAG_EVENT_RESET, /
      static void DIAG_undertemperature_discharge(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event); 223 } DIAG_EVENT_e;
100
      static void DIAG_overcurrent_charge(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event);
101
      static void DIAG_overcurrent_discharge(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event);
102
103
104
      /* functions for system related events */
```

```
105
      static void DIAG error cantiming (DIAG CH ID e ch id, DIAG EVENT e event);
      static void DIAG error ltc(DIAG CH ID e ch id, DIAG EVENT e event);
106
107
      static void DIAG_error_cancurrentsensor(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event);
108
      static void DIAG cont feedback (DIAG CH ID e ch id, DIAG EVENT e event);
109
      static void DIAG error fuseState (DIAG CH ID e ch id, DIAG EVENT e event);
110
      static void DIAG_error_interlock (DIAG_CH_ID_e ch_id, DIAG_EVENT_e event);
111
      static void DIAG_error_insulation(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event);
112
      static void DIAG error openWire (DIAG CH ID e ch id, DIAG EVENT e event);
113
      static void DIAG error deep discharge detected (DIAG CH ID e ch id, DIAG EVENT e event);
      static void DIAG_error_MCUdieTemperature(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event);
114
115
      static void DIAG_error_coinCellVoltage(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event);
116
      /* functions for plausibility related events */
117
118
      static void DIAG error plausibility check (DIAG CH ID e ch id, DIAG EVENT e event);
119
120
      /*====== Extern Constant and Variable Definitions =======*/
121
122
       * Enable and Disable of Error Checks for Testing Purposes
123
124
       * Each Bit enables or disables the diagnosis (checking of) the corresponding failure code
125
       * FIXME struct isn't used anywhere in the code at the moment.
126
       * FIXME delete if not needed
                                                     305 typedef struct {
127
      * /
                                                     306
                                                          DIAG_CH_ID_e id;
                                                                                            /*!< diagnos
128
      DIAG_CODE_s diag_mask = {
                                                             uint8_t description[40];
                                                     308 uint16_t thresholds;
129
              .GENERALmsk = OxFFFFFFFF,
                                                                                            /*!< thresh
                                                             generating a notification in both direction (OK or N
130
              .CELLMONmsk = 0 \times FFFFFFFFF,
                                                     309
131
              .COMmsk = 0 \times FFFFFFFF,
                                                                                            1:reports t
132
              .ADCmsk = 0xFFFFFFFF,
                                                     310
                                                             DIAG_TYPE_RECORDING_e enablerecording; /*!< if enak
                                                     311
                                                             DIAG ENABLE STATE e state: /*!< if enak
133
      };
                                                             void (*callbackfunc) (DIAG_CH_ID_e, DIAG_EVENT_e);
134
                                                             (in both direction) with parameter DIAG_EVENT_e */
135
      DIAG_CH_CFG_s diag_ch_cfg[] = {
                                                     313 } DIAG_CH_CFG_s;
136
          /* OS-Framework and startup events */
137
          {DIAG CH FLASHCHECKSUM,
                                                               "FLASHCHECKSUM",
          DIAG ERROR SENSITIVITY HIGH,
                                                     DIAG RECORDING ENABLED, DIAG ENABLED, dummyfu],
138
                                                               "BKPDIAG",
          {DIAG_CH_BKPDIAG_FAILURE,
                                                     DIAG_RECORDING_ENABLED, DIAG_ENABLED, dummyfu},
          DIAG_ERROR_SENSITIVITY_HIGH,
139
          {DIAG CH WATCHDOGRESET FAILURE,
                                                               "WATCHDOGRESET",
          DIAG ERROR SENSITIVITY HIGH,
                                                     DIAG RECORDING ENABLED, DIAG ENABLED, dummyfu},
140
          {DIAG CH_POSTOSINIT_FAILURE,
                                                               "POSTOSINIT",
          DIAG ERROR SENSITIVITY HIGH,
                                                     DIAG RECORDING ENABLED, DIAG ENABLED, dummyfu},
141
          {DIAG CH CALIB EEPR FAILURE,
                                                               "CALIB EEPR".
          DIAG_ERROR_SENSITIVITY_HIGH,
                                                     DIAG_RECORDING_ENABLED, DIAG_ENABLED, dummyfu},
142
          {DIAG CH CAN INIT FAILURE,
                                                               "CAN INIT",
                                                     DIAG RECORDING ENABLED, DIAG ENABLED, dummyfu},
          DIAG ERROR SENSITIVITY HIGH,
143
          {DIAG CH VIC INIT FAILURE,
                                                               "VIC INIT".
          DIAG ERROR SENSITIVITY HIGH,
                                                     DIAG_RECORDING_ENABLED, DIAG_ENABLED, dummyfu},
144
145
          /* HW-/SW-Runtime events */
146
          {DIAG_CH_DIV_BY_ZERO_FAILURE,
                                                               "DIV_BY_ZERO",
          DIAG_ERROR_SENSITIVITY_HIGH,
                                                     DIAG_RECORDING_ENABLED, DIAG_ENABLED, dummyfu},
147
          {DIAG_CH_UNDEF_INSTRUCTION_FAILURE,
                                                               "UNDEF INSTRUCTION",
          DIAG ERROR SENSITIVITY HIGH,
                                                     DIAG RECORDING ENABLED, DIAG ENABLED, dummyfu},
```

```
148
          {DIAG CH DATA BUS FAILURE,
                                                               "DATA BUS FAILURE",
          DIAG ERROR SENSITIVITY HIGH,
                                                     DIAG RECORDING ENABLED, DIAG ENABLED, dummyfu},
149
                                                               "INSTRUCTION_BUS",
          {DIAG_CH_INSTRUCTION_BUS_FAILURE,
          DIAG ERROR SENSITIVITY HIGH,
                                                    DIAG_RECORDING_ENABLED, DIAG_ENABLED, dummyfu},
150
          {DIAG CH HARDFAULT NOTHANDLED,
                                                               "HARDFAULT NOTHANDLED",
          DIAG_ERROR_SENSITIVITY_HIGH,
                                                    DIAG_RECORDING_ENABLED, DIAG_ENABLED, dummyfu},
151
152
          {DIAG CH CONFIGASSERT,
                                                               "CONFIGASSERT",
          DIAG ERROR SENSITIVITY HIGH,
                                                    DIAG RECORDING ENABLED, DIAG ENABLED, dummyfu],
153
          {DIAG_CH_SYSTEMMONITORING_TIMEOUT,
                                                               "SYSTEMMONITORING_TIMEOUT",
          DIAG_ERROR_SENSITIVITY_HIGH,
                                                    DIAG_RECORDING_ENABLED, DIAG_ENABLED, dummyfu},
154
155
156
          /* Measurement events */
157
          {DIAG CH CANS MAX VALUE VIOLATE,
                                                               "CANS MAX VALUE VIOLATE",
          DIAG ERROR SENSITIVITY HIGH,
                                                    DIAG RECORDING ENABLED, DIAG ENABLED, dummyfu},
158
          {DIAG_CH_CANS_MIN_VALUE_VIOLATE,
                                                               "CANS_MIN_VALUE_VIOLATE",
          DIAG_ERROR_SENSITIVITY_HIGH,
                                                    DIAG_RECORDING_ENABLED, DIAG_ENABLED, dummyfu},
159
                                                               "CANS_CAN_MOD_FAILURE",
          {DIAG CH CANS CAN MOD FAILURE,
          DIAG ERROR SENSITIVITY HIGH,
                                                    DIAG RECORDING ENABLED, DIAG ENABLED, dummyfu},
160
161
      #if BUILD MODULE ENABLE ISOGUARD == 1
162
          {DIAG CH ISOMETER TIM ERROR,
                                                               "ISOMETER TIM ERROR",
          DIAG_ERROR_SENSITIVITY_MID,
                                                     DIAG_RECORDING_ENABLED, DIAG_ENABLED, dummyfu},
163
          {DIAG_CH_ISOMETER_GROUNDERROR,
                                                               "ISOMETER_GROUNDERROR",
                                                    DIAG RECORDING ENABLED, DIAG ENABLED, dummyfu},
          DIAG ERROR SENSITIVITY HIGH,
                                                               "ISOMETER_ERROR",
164
          {DIAG CH ISOMETER ERROR,
                                                    DIAG_RECORDING_ENABLED, DIAG_ENABLED, dummyfu},
          DIAG_ERROR_SENSITIVITY_MID,
165
                                                               "ISOMETER_MEAS_INVALID",
          {DIAG_CH_ISOMETER_MEAS_INVALID,
                                                    DIAG RECORDING ENABLED, DIAG ENABLED, dummyfu},
          DIAG ERROR SENSITIVITY HIGH,
166
          {DIAG_CH_INSULATION_ERROR,
                                                               "INSULATION_ERROR",
          DIAG_ERROR_INSULATION_SENSITIVITY,
                                                    DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_error_insulation},
167
      #else
168
                                                               "ISOMETER TIM ERROR",
          {DIAG CH ISOMETER TIM ERROR,
          DIAG_ERROR_SENSITIVITY_MID,
                                                    DIAG_RECORDING_DISABLED, DIAG_DISABLED, dummyfu},
169
          {DIAG_CH_ISOMETER_GROUNDERROR,
                                                               "ISOMETER_GROUNDERROR",
          DIAG_ERROR_SENSITIVITY_HIGH,
                                                    DIAG_RECORDING_DISABLED, DIAG_DISABLED, dummyfu},
170
          {DIAG CH ISOMETER ERROR,
                                                               "ISOMETER ERROR",
          DIAG_ERROR_SENSITIVITY_MID,
                                                    DIAG_RECORDING_DISABLED, DIAG_DISABLED, dummyfu},
171
          {DIAG_CH_ISOMETER_MEAS_INVALID,
                                                               "ISOMETER_MEAS_INVALID",
          DIAG ERROR SENSITIVITY HIGH,
                                                    DIAG_RECORDING_DISABLED, DIAG_DISABLED, dummyfu},
172
          {DIAG_CH_INSULATION_ERROR,
                                                               "INSULATION_ERROR",
          DIAG_ERROR_INSULATION_SENSITIVITY,
                                                    DIAG_RECORDING_DISABLED, DIAG_DISABLED, dummyfu},
173
      #endif
174
175
          /* Under and over temperature, voltage and current at cell level */
176
          {DIAG CH CELLVOLTAGE OVERVOLTAGE MSL,
                                                             "CELLVOLT OVERVOLT MSL",
          DIAG ERROR VOLTAGE SENSITIVITY MSL,
                                                       DIAG RECORDING ENABLED, DIAG ENABLED, DIAG overvoltage),
                                                             "CELLVOLT_OVERVOLT_RSL",
177
          {DIAG_CH_CELLVOLTAGE_OVERVOLTAGE_RSL,
          DIAG_ERROR_VOLTAGE_SENSITIVITY_RSL,
                                                       DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_overvoltage},
178
          {DIAG_CH_CELLVOLTAGE_OVERVOLTAGE_MOL,
                                                           "CELLVOLT_OVERVOLT_MOL",
          DIAG_ERROR_VOLTAGE_SENSITIVITY_MOL,
                                                       DIAG RECORDING ENABLED, DIAG ENABLED, DIAG overvoltage},
```

```
179
180
          {DIAG CH CELLVOLTAGE UNDERVOLTAGE MSL,
                                                             "CELLVOLT UNDERVOLT MSL",
          DIAG_ERROR_VOLTAGE_SENSITIVITY_MSL,
                                                        DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_undervoltage},
181
          {DIAG CH CELLVOLTAGE UNDERVOLTAGE RSL,
                                                             "CELLVOLT UNDERVOLT RSL",
          DIAG ERROR VOLTAGE SENSITIVITY RSL,
                                                        DIAG RECORDING ENABLED, DIAG ENABLED, DIAG undervoltage},
182
          {DIAG_CH_CELLVOLTAGE_UNDERVOLTAGE_MOL,
                                                           "CELLVOLT_UNDERVOLT_MOL",
          DIAG ERROR VOLTAGE SENSITIVITY MOL,
                                                        DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_undervoltage},
183
184
          {DIAG CH TEMP OVERTEMPERATURE CHARGE MSL,
                                                             "OVERTEMP CHARGE MSL",
                                                         DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_overtemperature_charge},
          DIAG_ERROR_TEMPERATURE_SENSITIVITY_MSL,
185
          {DIAG_CH_TEMP_OVERTEMPERATURE_CHARGE_RSL,
                                                             "OVERTEMP_CHARGE_RSL",
          DIAG ERROR TEMPERATURE SENSITIVITY RSL,
                                                         DIAG RECORDING ENABLED, DIAG ENABLED, DIAG overtemperature charge},
186
          {DIAG CH TEMP OVERTEMPERATURE CHARGE MOL,
                                                           "OVERTEMP CHARGE MOL",
          DIAG_ERROR_TEMPERATURE_SENSITIVITY_MOL,
                                                         DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_overtemperature_charge},
187
188
          {DIAG CH TEMP OVERTEMPERATURE DISCHARGE MSL,
                                                             "OVERTEMP DISCHARGE MSL",
          DIAG_ERROR_TEMPERATURE_SENSITIVITY_MSL,
                                                         DIAG RECORDING ENABLED, DIAG ENABLED,
          DIAG overtemperature discharge },
189
          {DIAG CH TEMP OVERTEMPERATURE DISCHARGE RSL,
                                                             "OVERTEMP DISCHARGE RSL",
          DIAG ERROR TEMPERATURE SENSITIVITY MSL,
                                                         DIAG RECORDING ENABLED, DIAG ENABLED,
          DIAG_overtemperature_discharge},
190
          {DIAG_CH_TEMP_OVERTEMPERATURE_DISCHARGE_MOL,
                                                           "OVERTEMP DISCHARGE MOL",
          DIAG ERROR TEMPERATURE SENSITIVITY MSL,
                                                         DIAG RECORDING ENABLED, DIAG ENABLED,
          DIAG_overtemperature_discharge},
191
192
          {DIAG CH TEMP UNDERTEMPERATURE CHARGE MSL,
                                                             "UNDERTEMP CHARGE MSL",
          DIAG ERROR TEMPERATURE SENSITIVITY MSL,
                                                         DIAG RECORDING ENABLED, DIAG ENABLED, DIAG undertemperature charge},
193
          {DIAG_CH_TEMP_UNDERTEMPERATURE_CHARGE_RSL,
                                                             "UNDERTEMP_CHARGE_RSL",
          DIAG ERROR TEMPERATURE SENSITIVITY MSL,
                                                         DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_undertemperature_charge},
194
          {DIAG CH TEMP UNDERTEMPERATURE CHARGE MOL,
                                                           "UNDERTEMP CHARGE MOL",
          DIAG ERROR TEMPERATURE SENSITIVITY MSL,
                                                         DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_undertemperature_charge},
195
196
          {DIAG CH TEMP UNDERTEMPERATURE DISCHARGE MSL,
                                                             "UNDERTEMP DISCHARGE MSL",
          DIAG ERROR TEMPERATURE SENSITIVITY MSL,
                                                         DIAG RECORDING ENABLED, DIAG ENABLED,
          DIAG_undertemperature_discharge},
197
          {DIAG_CH_TEMP_UNDERTEMPERATURE_DISCHARGE_RSL,
                                                             "UNDERTEMP_DISCHARGE_RSL",
          DIAG ERROR TEMPERATURE SENSITIVITY MSL,
                                                         DIAG_RECORDING_ENABLED, DIAG_ENABLED,
          DIAG undertemperature discharge),
198
          {DIAG_CH_TEMP_UNDERTEMPERATURE_DISCHARGE_MOL,
                                                           "UNDERTEMP DISCHARGE MOL",
          DIAG ERROR TEMPERATURE SENSITIVITY MSL,
                                                         DIAG_RECORDING_ENABLED, DIAG_ENABLED,
          DIAG undertemperature discharge),
199
200
          {DIAG CH OVERCURRENT PL NONE,
                                                     "OVERCUR NO POWERLINE",
                                                                                  DIAG_ERROR_CURRENT_SENSITIVITY_MSL,
          DIAG RECORDING ENABLED, DIAG ENABLED, DIAG overcurrent charge},
201
202
          {DIAG CH OVERCURRENT CHARGE CELL MSL,
                                                     "OVERCUR CHRG CELL MSL",
                                                                                   DIAG_ERROR_CURRENT_SENSITIVITY_MSL,
          DIAG RECORDING ENABLED, DIAG ENABLED, DIAG overcurrent charge},
203
          {DIAG CH OVERCURRENT CHARGE CELL RSL,
                                                     "OVERCUR CHRG CELL RSL",
                                                                                   DIAG ERROR CURRENT SENSITIVITY RSL,
          DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_overcurrent_charge},
204
          {DIAG_CH_OVERCURRENT_CHARGE_CELL_MOL,
                                                     "OVERCUR_CHRG_CELL_MOL",
                                                                                  DIAG_ERROR_CURRENT_SENSITIVITY_MOL,
          DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_overcurrent_charge},
```

205

```
206
          {DIAG_CH_OVERCURRENT_DISCHARGE CELL MSL.
                                                                                  DIAG ERROR CURRENT SENSITIVITY MSL,
                                                     "OVERCUR DCHRG CELL MSL",
          DIAG RECORDING ENABLED, DIAG ENABLED, DIAG overcurrent discharge},
207
          {DIAG CH OVERCURRENT DISCHARGE CELL RSL,
                                                    "OVERCUR DCHRG CELL RSL",
                                                                                  DIAG_ERROR_CURRENT_SENSITIVITY_RSL,
          DIAG RECORDING ENABLED, DIAG ENABLED, DIAG overcurrent discharge),
208
          {DIAG CH OVERCURRENT DISCHARGE CELL MOL, "OVERCUR DCHRG CELL MOL",
                                                                                  DIAG ERROR CURRENT SENSITIVITY MOL,
          DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_overcurrent_discharge},
209
210
          {DIAG CH OVERCURRENT CHARGE PLO MSL,
                                                      "OVERCUR CHRG PLO MSL",
                                                                                  DIAG ERROR CURRENT SENSITIVITY MSL,
          DIAG RECORDING ENABLED, DIAG ENABLED, DIAG overcurrent charge},
211
          {DIAG_CH_OVERCURRENT_CHARGE_PLO_RSL,
                                                      "OVERCUR CHRG PLO RSL",
                                                                                  DIAG_ERROR_CURRENT_SENSITIVITY_RSL,
          DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_overcurrent_charge},
212
          {DIAG CH OVERCURRENT CHARGE PLO MOL,
                                                      "OVERCUR CHRG PLO MOL",
                                                                                  DIAG ERROR CURRENT SENSITIVITY MOL,
          DIAG RECORDING ENABLED, DIAG ENABLED, DIAG overcurrent charge},
213
214
                                                                                  DIAG ERROR CURRENT SENSITIVITY MSL,
          {DIAG CH OVERCURRENT DISCHARGE PLO MSL,
                                                      "OVERCUR DCHRG PLO MSL",
          DIAG RECORDING ENABLED, DIAG ENABLED, DIAG overcurrent discharge},
                                                      "OVERCUR_DCHRG_PL0_RSL",
215
          {DIAG CH OVERCURRENT DISCHARGE PLO RSL,
                                                                                  DIAG_ERROR_CURRENT_SENSITIVITY_RSL,
          DIAG RECORDING ENABLED, DIAG ENABLED, DIAG overcurrent discharge),
216
          {DIAG CH OVERCURRENT DISCHARGE PLO MOL,
                                                      "OVERCUR DCHRG PLO MOL",
                                                                                  DIAG ERROR CURRENT SENSITIVITY MOL,
          DIAG RECORDING ENABLED, DIAG ENABLED, DIAG overcurrent discharge},
217
218
          {DIAG CH OVERCURRENT CHARGE PL1 MSL,
                                                      "OVERCUR CHRG PL1 MSL",
                                                                                  DIAG_ERROR_CURRENT_SENSITIVITY_MSL,
          DIAG RECORDING ENABLED, DIAG ENABLED, DIAG overcurrent charge},
219
          {DIAG_CH_OVERCURRENT_CHARGE_PL1_RSL,
                                                      "OVERCUR_CHRG_PL1_RSL",
                                                                                  DIAG_ERROR_CURRENT_SENSITIVITY_RSL,
          DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_overcurrent_charge},
220
          {DIAG CH OVERCURRENT CHARGE PL1 MOL,
                                                      "OVERCUR CHRG PL1 MOL",
                                                                                  DIAG ERROR CURRENT SENSITIVITY MOL,
          DIAG RECORDING ENABLED, DIAG ENABLED, DIAG overcurrent charge},
221
222
                                                      "OVERCUR_DCHRG_PL1_MSL",
          {DIAG CH OVERCURRENT DISCHARGE PL1 MSL,
                                                                                  DIAG_ERROR_CURRENT_SENSITIVITY_MSL,
          DIAG RECORDING ENABLED, DIAG ENABLED, DIAG overcurrent discharge},
223
          {DIAG CH OVERCURRENT DISCHARGE PL1 RSL,
                                                      "OVERCUR DCHRG PL1 RSL",
                                                                                  DIAG_ERROR_CURRENT_SENSITIVITY_RSL,
          DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_overcurrent discharge},
224
          {DIAG CH OVERCURRENT DISCHARGE PL1 MOL,
                                                      "OVERCUR DCHRG PL1 MOL",
                                                                                  DIAG ERROR CURRENT SENSITIVITY MOL,
          DIAG RECORDING ENABLED, DIAG ENABLED, DIAG overcurrent discharge},
225
226
          {DIAG_CH_LTC_SPI,
                                                               "LTC_SPI",
          DIAG_ERROR_LTC_SPI_SENSITIVITY,
                                                     DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_error_ltc},
227
          {DIAG CH LTC PEC,
                                                               "LTC PEC",
          DIAG_ERROR_LTC_PEC_SENSITIVITY,
                                                     DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_error_ltc},
228
          {DIAG CH LTC MUX,
                                                               "LTC MUX",
          DIAG ERROR LTC MUX SENSITIVITY,
                                                     DIAG RECORDING ENABLED, DIAG ENABLED, DIAG error ltc},
229
          {DIAG_CH_LTC_CONFIG,
                                                               "LTC_CONFIG",
          DIAG_ERROR_SENSITIVITY_HIGH,
                                                     DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_error_ltc},
230
231
          /* Communication events */
232
          {DIAG CH CAN TIMING,
                                                               "CAN TIMING",
                                                     DIAG_RECORDING_ENABLED, DIAG_CAN_TIMING, DIAG_error_cantiming},
          DIAG ERROR CAN TIMING SENSITIVITY,
233
          {DIAG CH CAN CC RESPONDING,
                                                               "CAN CC RESPONDING",
          DIAG_ERROR_CAN_TIMING_CC_SENSITIVITY,
                                                     DIAG_RECORDING_ENABLED, DIAG_CAN_SENSOR_PRESENT, DIAG_error_cantiming},
234
          {DIAG_CH_CURRENT_SENSOR_RESPONDING,
                                                               "CURRENT_SENSOR_RESPONDING",
          DIAG_ERROR_CAN_SENSOR_SENSITIVITY,
                                                     DIAG_RECORDING_ENABLED, DIAG_CAN_SENSOR_PRESENT,
          DIAG error cancurrentsensor },
```

```
235
      #if BUILD MODULE ENABLE CONTACTOR == 1
236
237
          /* Contactor Damage Error */
238
          {DIAG CH CONTACTOR DAMAGED,
                                                               "CONTACTOR DAMAGED",
          DIAG ERROR SENSITIVITY HIGH,
                                                     DIAG RECORDING ENABLED, DIAG ENABLED, dummyfu},
239
          {DIAG_CH_CONTACTOR_OPENING,
                                                               "CONTACTOR_OPENING",
          DIAG_ERROR_SENSITIVITY_HIGH,
                                                     DIAG_RECORDING_ENABLED, DIAG_ENABLED, dummyfu},
240
          {DIAG CH CONTACTOR CLOSING,
                                                               "CONTACTOR CLOSING",
          DIAG ERROR SENSITIVITY HIGH,
                                                    DIAG RECORDING ENABLED, DIAG ENABLED, dummyfu},
241
          /* Contactor Feedback Error */
242
243
          {DIAG CH CONTACTOR MAIN PLUS FEEDBACK,
                                                               "CONT MAIN PLUS FEED",
          DIAG ERROR MAIN PLUS SENSITIVITY,
                                                  DIAG RECORDING ENABLED, DIAG ENABLED, DIAG cont feedback },
244
          {DIAG_CH_CONTACTOR_MAIN_MINUS_FEEDBACK,
                                                               "CONT_MAIN_MINUS_FEED",
                                                  DIAG RECORDING ENABLED, DIAG ENABLED, DIAG cont feedback },
          DIAG ERROR MAIN MINUS SENSITIVITY,
245
          {DIAG CH CONTACTOR PRECHARGE FEEDBACK,
                                                               "CONT PRECHARGE FEED",
          DIAG_ERROR_PRECHARGE_SENSITIVITY,
                                                  DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_cont_feedback },
246
          {DIAG_CH_CONTACTOR_CHARGE_MAIN_PLUS_FEEDBACK,
                                                               "CONT CHRGE MAIN PLUS FEED",
          DIAG ERROR MAIN PLUS SENSITIVITY,
                                                  DIAG RECORDING ENABLED, DIAG ENABLED, DIAG cont feedback },
247
          {DIAG CH CONTACTOR CHARGE MAIN MINUS FEEDBACK,
                                                               "CONT CHRGE MAIN MINUS FEED",
          DIAG_ERROR_MAIN_MINUS_SENSITIVITY,
                                                  DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_cont_feedback },
248
          {DIAG_CH_CONTACTOR_CHARGE_PRECHARGE_FEEDBACK,
                                                               "CONT CHRGE PRECHARGE FEED",
          DIAG ERROR PRECHARGE SENSITIVITY,
                                                  DIAG RECORDING ENABLED, DIAG ENABLED, DIAG cont feedback },
249
250
          /* Fuse state */
251
          {DIAG CH FUSE STATE NORMAL,
                                                               "FUSE STATE NORMAL",
                                                  DIAG RECORDING ENABLED, DIAG ENABLED, DIAG error fuseState },
          DIAG ERROR SENSITIVITY LOW,
252
                                                               "FUSE_STATE_CHARGE",
          {DIAG_CH_FUSE_STATE_CHARGE,
          DIAG ERROR SENSITIVITY LOW,
                                                  DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_error_fuseState },
253
      #else
254
          /* Contactor Damage Error */
255
          {DIAG CH CONTACTOR DAMAGED,
                                                               "CONTACTOR DAMAGED",
          DIAG ERROR SENSITIVITY HIGH,
                                                     DIAG RECORDING DISABLED, DIAG DISABLED, dummyfu},
256
          {DIAG_CH_CONTACTOR_OPENING,
                                                               "CONTACTOR OPENING",
          DIAG_ERROR_SENSITIVITY_HIGH,
                                                    DIAG_RECORDING_DISABLED, DIAG_DISABLED, dummyfu},
257
          {DIAG_CH_CONTACTOR_CLOSING,
                                                               "CONTACTOR_CLOSING",
          DIAG_ERROR_SENSITIVITY_HIGH,
                                                    DIAG_RECORDING_DISABLED, DIAG_DISABLED, dummyfu},
258
259
          /* Contactor Feedback Error */
260
          {DIAG CH CONTACTOR MAIN PLUS FEEDBACK,
                                                               "CONT MAIN PLUS FEED",
          DIAG ERROR MAIN PLUS SENSITIVITY,
                                                  DIAG RECORDING DISABLED, DIAG DISABLED, DIAG cont feedback},
261
          {DIAG_CH_CONTACTOR_MAIN_MINUS_FEEDBACK,
                                                               "CONT_MAIN_MINUS_FEED",
                                                  DIAG RECORDING DISABLED, DIAG_DISABLED, DIAG_cont_feedback},
          DIAG ERROR MAIN MINUS SENSITIVITY,
262
          {DIAG CH CONTACTOR PRECHARGE FEEDBACK,
                                                               "CONT PRECHARGE FEED",
          DIAG ERROR PRECHARGE SENSITIVITY,
                                                  DIAG RECORDING DISABLED, DIAG DISABLED, DIAG cont feedback},
263
          {DIAG CH CONTACTOR CHARGE MAIN PLUS FEEDBACK,
                                                               "CONT CHRGE MAIN PLUS FEED",
          DIAG ERROR MAIN PLUS SENSITIVITY,
                                                  DIAG RECORDING DISABLED, DIAG DISABLED, DIAG cont feedback},
264
          {DIAG CH CONTACTOR CHARGE MAIN MINUS FEEDBACK,
                                                               "CONT CHRGE MAIN MINUS FEED",
          DIAG_ERROR_MAIN_MINUS_SENSITIVITY,
                                                  DIAG_RECORDING_DISABLED, DIAG_DISABLED, DIAG_cont_feedback},
265
          {DIAG_CH_CONTACTOR_CHARGE_PRECHARGE_FEEDBACK,
                                                               "CONT_CHRGE_PRECHARGE_FEED",
          DIAG ERROR PRECHARGE SENSITIVITY,
                                                  DIAG_RECORDING_DISABLED, DIAG_DISABLED, DIAG_cont_feedback},
266
```

```
267
          /* Fuse state */
268
          {DIAG CH FUSE STATE NORMAL,
                                                               "FUSE STATE NORMAL",
          DIAG_ERROR_SENSITIVITY_LOW,
                                                 DIAG_RECORDING_DISABLED, DIAG_DISABLED, DIAG_error_fuseState},
269
          {DIAG CH FUSE STATE CHARGE,
                                                               "FUSE STATE CHARGE",
          DIAG ERROR SENSITIVITY LOW,
                                                 DIAG RECORDING DISABLED, DIAG DISABLED, DIAG error fuseState},
270
271
     #endif
272
273
      #if BUILD MODULE ENABLE ILCK == 1
274
          /* Interlock Feedback Error */
275
          {DIAG_CH_INTERLOCK_FEEDBACK,
                                                               "INTERLOCK_FEEDBACK",
          DIAG ERROR INTERLOCK SENSITIVITY,
                                                  DIAG RECORDING ENABLED, DIAG ENABLED, DIAG error interlock},
276
      #else
                                                               "INTERLOCK FEEDBACK",
277
          {DIAG CH INTERLOCK FEEDBACK,
          DIAG ERROR INTERLOCK SENSITIVITY,
                                                  DIAG RECORDING DISABLED, DIAG DISABLED, DIAG error interlock},
278
      #endif
279
          /* Slave PCB temperature errors for under and over temperature */
280
281
          {DIAG CH SLAVE PCB UNDERTEMPERATURE MSL,
                                                             "SLAVE PCB UNDERTEMP MSL",
          DIAG ERROR SLAVE TEMP SENSITIVITY MSL,
                                                   DIAG RECORDING ENABLED, DIAG ENABLED, dummyfu},
282
          {DIAG_CH_SLAVE_PCB_UNDERTEMPERATURE_RSL,
                                                             "SLAVE_PCB_UNDERTEMP_RSL",
          DIAG_ERROR_SLAVE_TEMP_SENSITIVITY_RSL,
                                                   DIAG RECORDING ENABLED, DIAG ENABLED, dummyfu},
283
          {DIAG CH SLAVE PCB UNDERTEMPERATURE MOL,
                                                           "SLAVE PCB UNDERTEMP MOL",
          DIAG_ERROR_SLAVE_TEMP_SENSITIVITY_MOL, DIAG_RECORDING_ENABLED, DIAG_ENABLED, dummyfu},
284
285
          {DIAG CH SLAVE PCB OVERTEMPERATURE MSL,
                                                             "SLAVE PCB OVERTEMP MSL",
          DIAG ERROR SLAVE TEMP SENSITIVITY MSL,
                                                   DIAG RECORDING ENABLED, DIAG ENABLED, dummyfu},
286
          {DIAG_CH_SLAVE_PCB_OVERTEMPERATURE_RSL,
                                                             "SLAVE_PCB_OVERTEMP_RSL",
          DIAG ERROR SLAVE TEMP SENSITIVITY RSL,
                                                   DIAG_RECORDING_ENABLED, DIAG_ENABLED, dummyfu},
287
          {DIAG CH SLAVE PCB OVERTEMPERATURE MOL,
                                                           "SLAVE PCB OVERTEMP MOL",
          DIAG_ERROR_SLAVE_TEMP_SENSITIVITY_MOL, DIAG_RECORDING_ENABLED, DIAG_ENABLED, dummyfu},
288
289
          {DIAG CH ERROR MCU DIE TEMPERATURE,
                                                   "MCU DIE TEMPERATURE",
                                                                               DIAG ERROR SENSITIVITY LOW,
          DIAG RECORDING ENABLED, DIAG ENABLED, DIAG error MCUdieTemperature},
290
          {DIAG_CH_LOW_COIN_CELL_VOLTAGE,
                                                   "COIN_CELL_VOLT_LOW",
                                                                               DIAG_ERROR_SENSITIVITY_LOW,
          DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_error_coinCellVoltage},
291
          {DIAG_CH_CRIT_LOW_COIN_CELL_VOLTAGE,
                                                  "COIN_CELL_VOLT_CRITICAL",
                                                                               DIAG_ERROR_SENSITIVITY_LOW,
          DIAG RECORDING ENABLED, DIAG ENABLED, DIAG error coincellVoltage},
292
293
          {DIAG CH OPEN WIRE,
                                    "OPEN WIRE",
                                                          DIAG_ERROR_SENSITIVITY_HIGH, DIAG_RECORDING_DISABLED,
          DIAG DISABLED, DIAG error openWire},
294
          {DIAG_CH_DEEP_DISCHARGE_DETECTED,
                                               "DEEP-DISCHARGE detected", DIAG_ERROR_SENSITIVITY_HIGH,
          DIAG_RECORDING_ENABLED, DIAG_ENABLED, DIAG_error_deep_discharge_detected},
295
296
          /* Plausibility checks */
297
          {DIAG CH PLAUSIBILITY CELL VOLTAGE,
                                                  "PL CELL VOLT",
                                                                     DIAG_ERROR_SENSITIVITY_HIGH, DIAG_RECORDING_ENABLED,
          DIAG ENABLED, DIAG error plausibility check},
298
          {DIAG CH PLAUSIBILITY CELL TEMP,
                                                  "PL CELL TEMP",
                                                                     DIAG ERROR SENSITIVITY HIGH, DIAG RECORDING ENABLED,
          DIAG_ENABLED, DIAG_error_plausibility_check},
299
          {DIAG_CH_PLAUSIBILITY_PACK_VOLTAGE,
                                                  "PL_PACK_VOLT",
                                                                     DIAG_ERROR_PLAUSIBILITY_PACK_SENSITIVITY,
          DIAG RECORDING ENABLED, DIAG ENABLED, DIAG error plausibility check},
300
     };
```

```
typedef struct {
301
                                                                                                   DIAG_SYSMON_MODULE_ID_e id;
                       We cannot switch off the connectors
302
                                                                                                   DIAG_SYSMON_TYPE_e type;
                                                                                            339
                                                                                                   uint16_t threshold;
303
      DIAG_SYSMON_CH_CFG_s diag_sysmon_ch_cfg[] = {
                                                                                                   DIAG TYPE RECORDING e enablerecording;
304
          {DIAG SYSMON DATABASE ID,
                                            DIAG SYSMON CYCLICTASK, 10, DIAG RECORDING El341
                                                                                                   DIAG_SYSMON_HANDLING_TYPE_e handlingtype;
          DIAG SYSMON HANDLING SWITCHOFFCONTACTOR, DIAG_ENABLED, dummyfu2},
                                                                                                   DIAG_ENABLE_STATE_e state;
                                                                                                   void (*callbackfunc) (DIAG_SYSMON_MODULE_ID_e);
                                            DIAG_SYSMON_CYCLICTASK, 20, DIAG_RECORDING_El344 } DIAG_SYSMON_CH_CFG_s;
305
          {DIAG_SYSMON_SYS_ID,
          DIAG_SYSMON_HANDLING_SWITCHOFFCONTACTOR, DIAG_ENABLED, dummyfu2},
306
          {DIAG SYSMON BMS ID,
                                            DIAG SYSMON CYCLICTASK, 20, DIAG RECORDING ENABLED,
          DIAG SYSMON HANDLING SWITCHOFFCONTACTOR, DIAG ENABLED, dummyfu2},
                                                                                         266 typedef enum {
                                                                                                 DIAG_SYSMON_HANDLING_DONOTHING,
307
                                                                                                 DIAG_SYSMON_HANDLING_SWITCHOFFCONTACTOR,
308
      #if BUILD_MODULE_ENABLE_CONTACTOR == 1
                                                                                              } DIAG_SYSMON_HANDLING_TYPE_e;
                                            DIAG SYSMON CYCLICTASK, 20, DIAG RECORDING ENABLED,
309
          {DIAG SYSMON CONT ID,
          DIAG SYSMON HANDLING SWITCHOFFCONTACTOR, DIAG ENABLED, dummyfu2},
310
      #else
311
                                            DIAG SYSMON CYCLICTASK, 20, DIAG RECORDING DISABLED,
          {DIAG SYSMON CONT ID,
          DIAG SYSMON HANDLING SWITCHOFFCONTACTOR, DIAG DISABLED, dummyfu2},
312
      #endif
313
314
      #if BUILD MODULE ENABLE ILCK == 1
315
          {DIAG SYSMON ILCK ID,
                                            DIAG SYSMON CYCLICTASK, 20, DIAG RECORDING ENABLED,
          DIAG_SYSMON_HANDLING_SWITCHOFFCONTACTOR, DIAG_ENABLED, dummyfu2},
316
      #else
317
          {DIAG SYSMON ILCK ID,
                                            DIAG SYSMON CYCLICTASK, 20, DIAG RECORDING DISABLED,
          DIAG_SYSMON_HANDLING_SWITCHOFFCONTACTOR, DIAG_DISABLED, dummyfu2},
318
      #endif
319
          {DIAG SYSMON LTC ID,
                                            DIAG SYSMON CYCLICTASK, 5, DIAG RECORDING ENABLED,
          DIAG SYSMON HANDLING SWITCHOFFCONTACTOR, DIAG ENABLED, dummyfu2},
320
321
      #if BUILD MODULE ENABLE ISOGUARD == 1
322
          {DIAG SYSMON ISOGUARD ID,
                                            DIAG SYSMON CYCLICTASK, 400, DIAG RECORDING ENABLED,
          DIAG SYSMON HANDLING SWITCHOFFCONTACTOR, DIAG ENABLED, dummyfu2},
323
      #else
324
          {DIAG SYSMON ISOGUARD ID,
                                            DIAG SYSMON CYCLICTASK, 400, DIAG RECORDING DISABLED,
          DIAG SYSMON HANDLING SWITCHOFFCONTACTOR, DIAG DISABLED, dummyfu2},
325
      #endif
326
327
          {DIAG SYSMON CANS ID,
                                            DIAG SYSMON CYCLICTASK, 20, DIAG RECORDING ENABLED,
          DIAG SYSMON HANDLING SWITCHOFFCONTACTOR, DIAG ENABLED, dummyfu2},
328
          {DIAG_SYSMON_APPL_CYCLIC_1ms, DIAG_SYSMON_CYCLICTASK, 20, DIAG_RECORDING_ENABLED,
          DIAG SYSMON HANDLING SWITCHOFFCONTACTOR, DIAG ENABLED, dummyfu2},
329
          {DIAG SYSMON APPL CYCLIC 10ms, DIAG SYSMON CYCLICTASK, 20, DIAG RECORDING ENABLED,
          DIAG_SYSMON_HANDLING_SWITCHOFFCONTACTOR, DIAG_ENABLED, dummyfu2},
330
          {DIAG_SYSMON_APPL_CYCLIC_100ms, DIAG_SYSMON_CYCLICTASK, 200, DIAG_RECORDING_ENABLED,
          DIAG_SYSMON_HANDLING_SWITCHOFFCONTACTOR, DIAG_ENABLED, dummyfu2},
331
      };
332
333
334
      DIAG DEV s diag dev = {
          .nr of ch = sizeof(diag_ch_cfg)/sizeof(DIAG_CH_CFG_s),
335
336
          .ch_cfg
                      = &diag_ch_cfg[0],
337
      };
338
```

```
/*======== Static Function Implementations ==========*/
339
      /**
340
341
      * @brief dummy callback function of diagnosis events
342
      * /
343
      void dummyfu(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event) {
344
          /* Dummy function -> empty */
345
      }
346
     /**
347
348
      * @brief dummy callback function of system monitoring error events
349
350
      void dummyfu2 (DIAG_SYSMON_MODULE_ID_e ch_id) {
351
          /* Dummy function -> empty */
352
353
      /**
354
355
      * @brief diagnosis callback function for overvoltage events
356
      static void DIAG_overvoltage(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event) {
357
358
         if (ch id == DIAG CH CELLVOLTAGE OVERVOLTAGE MSL) {
359
              if (event == DIAG_EVENT_RESET) {
360
                  msl_flags.over_voltage = 0;
361
              } else if (...) {
362
              if (event == DIAG_EVENT_NOK) {
363
                  msl_flags.over_voltage = 1;
364
              }
365
         } else if (ch_id == DIAG_CH_CELLVOLTAGE_OVERVOLTAGE_RSL) {
366
              if (event == DIAG_EVENT_RESET) {
367
                  rsl_flags.over_voltage = 0;
368
              }
369
              if (event == DIAG_EVENT_NOK) {
370
                  rsl_flags.over_voltage = 1;
371
372
         } else if (ch id == DIAG CH CELLVOLTAGE OVERVOLTAGE MOL) {
373
              if (event == DIAG_EVENT_RESET) {
374
                  mol_flags.over_voltage = 0;
375
              }
376
              if (event == DIAG EVENT NOK) {
377
                  mol_flags.over_voltage = 1;
378
              }
379
         }
      }
381
      /**
382
383
      * @brief diagnosis callback function for undervoltage events
384
385
      static void DIAG undervoltage (DIAG CH ID e ch id, DIAG EVENT e event) {
386
         //return; // JHL to disable the undervoltage test.
387
         // Results: Cannot stop the under voltage error by by-passing this function.
388
          if (ch_id == DIAG_CH_CELLVOLTAGE_UNDERVOLTAGE_MSL) {
389
              if (event == DIAG_EVENT_RESET) {
390
                  msl_flags.under_voltage = 0;
```

```
391
              }
392
              if (event == DIAG_EVENT_NOK) {
393
                  msl_flags.under_voltage = 1;
394
395
          } else if (ch_id == DIAG_CH_CELLVOLTAGE_UNDERVOLTAGE_RSL) {
396
              if (event == DIAG_EVENT_RESET) {
397
                  rsl_flags.under_voltage = 0;
398
              }
399
              if (event == DIAG EVENT NOK) {
                  rsl_flags.under_voltage = 1;
400
401
402
          } else if (ch_id == DIAG_CH_CELLVOLTAGE_UNDERVOLTAGE_MOL) {
403
              if (event == DIAG EVENT RESET) {
404
                  mol_flags.under_voltage = 0;
405
              }
406
              if (event == DIAG EVENT NOK) {
407
                  mol_flags.under_voltage = 1;
408
              }
409
410
      }
411
412
      /**
413
       * @brief diagnosis callback function for overtemperature charge events
414
415
      static void DIAG_overtemperature_charge(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event) {
416
          if (ch id == DIAG CH TEMP OVERTEMPERATURE CHARGE MSL) {
417
              if (event == DIAG EVENT RESET) {
418
                  msl_flags.over_temperature_charge = 0;
419
              }
420
              if (event == DIAG EVENT NOK) {
421
                  msl_flags.over_temperature_charge = 1;
422
              }
423
          } else if (ch id == DIAG CH TEMP OVERTEMPERATURE CHARGE RSL) {
424
              if (event == DIAG EVENT RESET) {
425
                  rsl_flags.over_temperature_charge = 0;
426
              }
427
              if (event == DIAG EVENT NOK) {
428
                  rsl flags.over temperature charge = 1;
429
430
          } else if (ch id == DIAG CH TEMP OVERTEMPERATURE CHARGE MOL) {
431
              if (event == DIAG EVENT RESET) {
432
                  mol_flags.over_temperature_charge = 0;
433
              }
434
              if (event == DIAG EVENT NOK) {
435
                  mol flags.over temperature charge = 1;
436
              }
437
438
      }
439
440
      /**
441
       * @brief diagnosis callback function for overtemperature discharge events
442
       * /
```

```
443
      static void DIAG overtemperature discharge (DIAG CH ID e ch id, DIAG EVENT e event) {
          if (ch id == DIAG CH TEMP_OVERTEMPERATURE_DISCHARGE_MSL) {
444
445
              if (event == DIAG_EVENT_RESET) {
446
                  msl flags.over temperature discharge = 0;
447
              }
448
              if (event == DIAG_EVENT_NOK) {
449
                  msl_flags.over_temperature_discharge = 1;
450
451
          } else if (ch id == DIAG CH TEMP OVERTEMPERATURE DISCHARGE RSL) {
452
              if (event == DIAG_EVENT_RESET) {
453
                  rsl_flags.over_temperature_discharge = 0;
454
              }
455
              if (event == DIAG EVENT NOK) {
456
                  rsl_flags.over_temperature_discharge = 1;
457
              }
458
          } else if (ch id == DIAG CH TEMP OVERTEMPERATURE DISCHARGE MOL) {
459
              if (event == DIAG_EVENT_RESET) {
460
                  mol_flags.over_temperature_discharge = 0;
461
              }
462
              if (event == DIAG EVENT NOK) {
463
                  mol_flags.over_temperature_discharge = 1;
464
              }
465
          }
466
      }
467
      /**
468
469
       * @brief diagnosis callback function for undertemperature charge events
470
471
      static void DIAG_undertemperature_charge(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event) {
472
          if (ch id == DIAG CH TEMP UNDERTEMPERATURE CHARGE MSL) {
473
              if (event == DIAG_EVENT_RESET) {
474
                  msl_flags.under_temperature_charge = 0;
475
              }
476
              if (event == DIAG EVENT NOK) {
477
                  msl_flags.under_temperature_charge = 1;
478
479
          } else if (ch_id == DIAG_CH_TEMP_UNDERTEMPERATURE_CHARGE_RSL) {
480
              if (event == DIAG EVENT RESET) {
481
                  rsl_flags.under_temperature_charge = 0;
482
              }
483
              if (event == DIAG EVENT NOK) {
484
                  rsl_flags.under_temperature_charge = 1;
485
486
          } else if (ch id == DIAG CH TEMP UNDERTEMPERATURE CHARGE MOL) {
              if (event == DIAG EVENT RESET) {
487
488
                  mol_flags.under_temperature_charge = 0;
489
              }
              if (event == DIAG EVENT NOK) {
490
491
                  mol_flags.under_temperature_charge = 1;
492
              }
493
          }
494
      }
```

```
495
      /**
496
497
      * @brief diagnosis callback function for undertemperature discharge events
498
      * /
499
      static void DIAG undertemperature discharge (DIAG CH ID e ch id, DIAG EVENT e event) {
500
          if (ch_id == DIAG_CH_TEMP_UNDERTEMPERATURE_DISCHARGE_MSL) {
501
              if (event == DIAG_EVENT_RESET) {
502
                  msl flags.under temperature discharge = 0;
503
              }
504
              if (event == DIAG_EVENT_NOK) {
505
                  msl_flags.under_temperature_discharge = 1;
506
              1
507
          } else if (ch id == DIAG CH TEMP UNDERTEMPERATURE DISCHARGE RSL) {
508
              if (event == DIAG EVENT RESET) {
509
                  rsl flags.under temperature discharge = 0;
510
              1
511
              if (event == DIAG EVENT NOK) {
512
                  rsl_flags.under_temperature_discharge = 1;
513
              }
514
          } else if (ch id == DIAG CH TEMP UNDERTEMPERATURE DISCHARGE MOL) {
515
              if (event == DIAG_EVENT_RESET) {
516
                  mol_flags.under_temperature_discharge = 0;
517
              }
518
              if (event == DIAG_EVENT_NOK) {
519
                  mol_flags.under_temperature_discharge = 1;
520
              }
521
          }
522
     }
523
524
      /**
525
      * @brief diagnosis callback function for overcurrent charge events
526
      * /
527
     static void DIAG overcurrent charge (DIAG CH ID e ch id, DIAG EVENT e event) {
528
          switch (ch id) {
529
          case DIAG_CH_OVERCURRENT_CHARGE_CELL_MSL:
530
              if (event == DIAG_EVENT_RESET) {
531
                  msl_flags.over_current_charge_cell = 0;
532
              } else if (event == DIAG EVENT NOK) {
                  msl_flags.over_current_charge_cell = 1;
533
534
              } else {
535
                  /* no relevant event, do nothing */
536
              }
537
              break;
538
          case DIAG CH OVERCURRENT CHARGE CELL RSL:
539
              if (event == DIAG EVENT RESET) {
540
                  rsl flags.over current charge cell = 0;
541
              } else if (event == DIAG EVENT NOK) {
542
                  rsl flags.over current charge cell = 1;
543
              } else {
544
                  /* no relevant event, do nothing */
545
546
              break;
```

```
547
          case DIAG CH OVERCURRENT CHARGE CELL MOL:
548
              if (event == DIAG EVENT RESET) {
549
                  mol_flags.over_current_charge_cell = 0;
550
              } else if (event == DIAG EVENT NOK) {
551
                  mol flags.over current charge cell = 1;
552
              } else {
553
                  /* no relevant event, do nothing */
554
              }
555
              break;
556
          case DIAG_CH_OVERCURRENT_CHARGE_PLO_MSL:
557
              if (event == DIAG_EVENT_RESET) {
558
                  msl flags.over current charge pl0 = 0;
559
              } else if (event == DIAG EVENT NOK) {
560
                  msl_flags.over_current_charge_pl0 = 1;
561
              } else {
562
                  /* no relevant event, do nothing */
563
              }
564
              break;
565
          case DIAG_CH_OVERCURRENT_CHARGE_PLO_RSL:
566
              if (event == DIAG_EVENT_RESET) {
567
                  rsl_flags.over_current_charge_pl0 = 0;
568
              } else if (event == DIAG_EVENT_NOK) {
569
                  rsl flags.over current charge pl0 = 1;
570
              } else {
571
                  /* no relevant event, do nothing */
572
              }
573
              break:
574
          case DIAG_CH_OVERCURRENT_CHARGE_PL0_MOL:
575
              if (event == DIAG EVENT RESET) {
576
                  mol flags.over current charge pl0 = 0;
577
              } else if (event == DIAG EVENT NOK) {
578
                  mol flags.over current charge pl0 = 1;
579
              } else {
580
                  /* no relevant event, do nothing */
581
              }
582
              break;
          case DIAG_CH_OVERCURRENT_CHARGE_PL1_MSL:
583
              if (event == DIAG EVENT RESET) {
584
585
                  msl_flags.over_current_charge_pl1 = 0;
586
              } else if (event == DIAG EVENT NOK) {
587
                  msl flags.over current charge pl1 = 1;
588
              } else {
589
                  /* no relevant event, do nothing */
590
              }
591
              break;
592
          case DIAG CH OVERCURRENT CHARGE PL1 RSL:
593
              if (event == DIAG EVENT RESET) {
594
                  rsl flags.over current charge pl1 = 0;
595
              } else if (event == DIAG_EVENT_NOK) {
596
                  rsl_flags.over_current_charge_pl1 = 1;
597
              } else {
598
                  /* no relevant event, do nothing */
```

```
599
              }
600
              break:
601
          case DIAG_CH_OVERCURRENT_CHARGE_PL1_MOL:
602
              if (event == DIAG EVENT RESET) {
603
                  mol flags.over current charge pl1 = 0;
604
              } else if (event == DIAG_EVENT_NOK) {
605
                  mol_flags.over_current_charge_pl1 = 1;
606
              } else {
607
                  /* no relevant event, do nothing */
608
609
              break;
610
          case DIAG CH OVERCURRENT PL NONE:
611
              if (event == DIAG EVENT RESET) {
                  error_flags.currentOnOpenPowerline = 0;
612
613
              } else if (event == DIAG EVENT NOK) {
                  error flags.currentOnOpenPowerline = 1;
614
615
              } else {
616
                  /* no relevant event, do nothing */
617
618
              break;
619
          default:
620
              /* no relevant channel, do nothing */
621
              break;
622
623
     }
624
      /**
625
626
      * @brief diagnosis callback function for overcurrent discharge events
627
      * /
628
     static void DIAG overcurrent discharge (DIAG CH ID e ch id, DIAG EVENT e event) {
629
          switch (ch id) {
630
          case DIAG CH OVERCURRENT DISCHARGE CELL MSL:
631
              if (event == DIAG EVENT RESET) {
632
                  msl flags.over current discharge cell = 0;
633
              } else if (event == DIAG_EVENT_NOK) {
634
                  msl_flags.over_current_discharge_cell = 1;
635
              } else {
636
                  /* no relevant event, do nothing */
637
              }
638
              break;
639
          case DIAG CH OVERCURRENT_DISCHARGE_CELL_RSL:
640
              if (event == DIAG_EVENT_RESET) {
641
                  rsl_flags.over_current_discharge_cell = 0;
642
              } else if (event == DIAG EVENT NOK) {
                  rsl flags.over current discharge cell = 1;
643
644
              } else {
645
                  /* no relevant event, do nothing */
646
              }
647
              break;
648
          case DIAG_CH_OVERCURRENT_DISCHARGE_CELL_MOL:
649
              if (event == DIAG_EVENT_RESET) {
650
                  mol flags.over current discharge cell = 0;
```

```
651
              } else if (event == DIAG EVENT NOK) {
                  mol_flags.over_current_discharge_cell = 1;
652
653
              } else {
654
                  /* no relevant event, do nothing */
655
              }
656
              break;
657
          case DIAG_CH_OVERCURRENT_DISCHARGE_PLO_MSL:
658
              if (event == DIAG EVENT RESET) {
659
                  msl flags.over current discharge pl0 = 0;
660
              } else if (event == DIAG_EVENT_NOK) {
661
                  msl_flags.over_current_discharge_pl0 = 1;
662
              } else {
663
                  /* no relevant event, do nothing */
664
              }
665
              break:
          case DIAG CH OVERCURRENT DISCHARGE PLO RSL:
666
667
              if (event == DIAG_EVENT_RESET) {
668
                  rsl flags.over_current_discharge_pl0 = 0;
669
              } else if (event == DIAG EVENT NOK) {
                  rsl flags.over current discharge pl0 = 1;
670
671
              } else {
672
                  /* no relevant event, do nothing */
673
              }
674
              break;
675
          case DIAG_CH_OVERCURRENT_DISCHARGE_PLO_MOL:
676
              if (event == DIAG EVENT RESET) {
677
                  mol flags.over current discharge pl0 = 0;
678
              } else if (event == DIAG_EVENT_NOK) {
679
                  mol flags.over current discharge pl0 = 1;
680
              } else {
681
                  /* no relevant event, do nothing */
682
              }
683
              break;
684
          case DIAG_CH_OVERCURRENT_DISCHARGE_PL1_MSL:
685
              if (event == DIAG_EVENT_RESET) {
686
                  msl_flags.over_current_discharge_pl1 = 0;
              } else if (event == DIAG_EVENT_NOK) {
687
688
                  msl flags.over current discharge pl1 = 1;
689
              } else {
690
                  /* no relevant event, do nothing */
691
              }
692
              break;
693
          case DIAG CH OVERCURRENT DISCHARGE PL1 RSL:
694
              if (event == DIAG EVENT RESET) {
695
                  rsl flags.over current discharge pl1 = 0;
696
              } else if (event == DIAG EVENT NOK) {
697
                  rsl flags.over current discharge pl1 = 1;
698
              } else {
699
                  /* no relevant event, do nothing */
701
              break;
702
          case DIAG CH OVERCURRENT DISCHARGE PL1 MOL:
```

```
703
              if (event == DIAG EVENT RESET) {
704
                  mol flags.over current discharge pl1 = 0;
705
              } else if (event == DIAG_EVENT_NOK) {
706
                  mol_flags.over_current_discharge_pl1 = 1;
707
              } else {
708
                  /* no relevant event, do nothing */
709
710
              break;
711
          default:
712
              /* no relevant channel, do nothing */
713
              break;
714
          }
715
      }
716
      /**
717
718
      * @brief diagnosis callback function for can related events
719
720
      void DIAG_error_cantiming(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event) {
721
          if (ch_id == DIAG_CH_CAN_TIMING) {
722
              if (event == DIAG EVENT RESET) {
723
                  error_flags.can_timing = 0;
724
              1
725
              if (event == DIAG EVENT NOK) {
726
                  error_flags.can_timing = 1;
727
728
          } else if (ch id == DIAG CH CAN CC RESPONDING) {
729
              if (event == DIAG EVENT RESET) {
730
                  error_flags.can_timing_cc = 0;
731
              }
732
              if (event == DIAG EVENT NOK) {
733
                  error_flags.can_timing_cc = 1;
734
              }
735
          }
736
     }
737
738
      /**
739
      * @brief diagnosis callback function for current sensor related events
      * /
740
741
      void DIAG_error_cancurrentsensor(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event) {
742
          if (ch id == DIAG CH CURRENT SENSOR RESPONDING) {
743
              if (event == DIAG EVENT RESET) {
744
                  error_flags.currentsensorresponding = 0;
745
              }
              if (event == DIAG_EVENT_NOK) {
746
747
                  error flags.currentsensorresponding = 1;
748
749
          }
750
      }
751
752
      /**
753
      * @brief diagnosis callback function for LTC module related events
754
       * /
```

```
755
      static void DIAG error ltc (DIAG CH ID e ch id, DIAG EVENT e event) {
756
          if (ch id == DIAG CH LTC SPI) {
757
              if (event == DIAG_EVENT_RESET) {
758
                  error flags.spi error = 0;
759
760
              if (event == DIAG_EVENT_NOK) {
761
                  error_flags.spi_error = 1;
762
              }
          } else if (ch_id == DIAG_CH_LTC_PEC) {
763
764
              if (event == DIAG_EVENT_RESET) {
765
                  error_flags.crc_error = 0;
766
              }
767
              if (event == DIAG_EVENT_NOK) {
768
                  error_flags.crc_error = 1;
769
              }
770
          } else if (ch id == DIAG CH LTC MUX) {
771
              if (event == DIAG_EVENT_RESET) {
772
                  error_flags.mux_error = 0;
773
              }
774
              if (event == DIAG EVENT NOK) {
775
                  error_flags.mux_error = 1;
776
              1
777
          } else if (ch id == DIAG CH LTC CONFIG) {
778
              if (event == DIAG_EVENT_RESET) {
779
                  error_flags.ltc_config_error = 0;
780
              }
781
              if (event == DIAG EVENT NOK) {
782
                  error_flags.ltc_config_error = 1;
783
              }
784
          }
785
      }
786
787
      /**
788
      * @brief diagnosis callback function for contactor feedback events
789
       * /
790
      void DIAG_cont_feedback(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event) {
          if (ch_id == DIAG_CH_CONTACTOR_MAIN_PLUS_FEEDBACK) {
791
792
              if (event == DIAG EVENT RESET) {
793
                  error_flags.main_plus = 0;
794
              }
795
              if (event == DIAG EVENT NOK) {
796
                  error_flags.main_plus = 1;
797
798
          } else if (ch id == DIAG CH CONTACTOR MAIN MINUS FEEDBACK) {
799
              if (event == DIAG EVENT RESET) {
800
                  error_flags.main_minus = 0;
801
              }
802
              if (event == DIAG EVENT NOK) {
803
                  error_flags.main_minus = 1;
804
805
          } else if (ch_id == DIAG_CH_CONTACTOR_PRECHARGE_FEEDBACK) {
806
              if (event == DIAG EVENT RESET) {
```

```
807
                  error flags.precharge = 0;
808
              1
809
              if (event == DIAG_EVENT_NOK) {
810
                  error_flags.precharge = 1;
811
              }
812
          } else if (ch_id == DIAG_CH_CONTACTOR_CHARGE_MAIN_PLUS_FEEDBACK) {
813
              if (event == DIAG EVENT RESET) {
814
                  error flags.charge main plus = 0;
815
              }
              if (event == DIAG_EVENT_NOK) {
816
817
                  error_flags.charge_main_plus = 1;
818
              1
819
          } else if (ch_id == DIAG_CH_CONTACTOR_CHARGE_MAIN_MINUS_FEEDBACK) {
820
              if (event == DIAG_EVENT_RESET) {
821
                  error_flags.charge_main_minus = 0;
822
              }
823
              if (event == DIAG_EVENT_NOK) {
824
                  error_flags.charge_main_minus = 1;
825
              }
826
          } else if (ch id == DIAG CH CONTACTOR CHARGE PRECHARGE FEEDBACK) {
827
              if (event == DIAG_EVENT_RESET) {
828
                  error_flags.charge_precharge = 0;
829
              }
830
              if (event == DIAG_EVENT_NOK) {
831
                  error_flags.charge_precharge = 1;
832
              }
833
          }
834
      }
835
      /**
836
837
      * @brief diagnosis callback function for fuse related events
838
      * /
839
      void DIAG error fuseState(DIAG CH ID e ch id, DIAG EVENT e event) {
840
          if (ch id == DIAG CH FUSE STATE NORMAL) {
841
              if (event == DIAG_EVENT_RESET) {
842
                  error_flags.fuse_state_normal = 0;
843
              }
844
              if (event == DIAG EVENT NOK) {
845
                  error_flags.fuse_state_normal = 1;
846
              }
847
          } else if (ch id == DIAG CH FUSE STATE CHARGE) {
848
              if (event == DIAG_EVENT_RESET) {
849
                  error_flags.fuse_state_charge = 0;
850
              }
851
              if (event == DIAG EVENT NOK) {
852
                  error_flags.fuse_state_charge = 1;
853
              }
854
855
      }
856
857
858
       * @brief diagnosis callback function for interlock events
```

```
859
       * /
860
     void DIAG_error_interlock(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event) {
861
          if (ch_id == DIAG_CH_INTERLOCK_FEEDBACK) {
862
              if (event == DIAG_EVENT_RESET) {
863
                  error_flags.interlock = 0;
864
865
              if (event == DIAG EVENT NOK) {
866
                  error flags.interlock = 1;
867
868
          }
869
      }
870
871
872
      * @brief diagnosis callback function for insulation events
873
      * /
     void DIAG_error_insulation(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event) {
874
875
          if (ch_id == DIAG_CH_INSULATION_ERROR) {
876
              if (event == DIAG_EVENT_RESET) {
877
                  error flags.insulation error = 0;
878
              }
879
              if (event == DIAG_EVENT_NOK) {
                  error_flags.insulation_error = 1;
880
881
              }
882
883
      }
884
      /**
885
886
      * @brief diagnosis callback function for MCU die temperature events
887
      * /
888
     void DIAG_error_MCUdieTemperature(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event) {
889
          if (ch_id == DIAG_CH_ERROR_MCU_DIE_TEMPERATURE) {
890
              if (event == DIAG_EVENT_RESET) {
891
                  error flags.mcuDieTemperature = 0;
892
893
              if (event == DIAG_EVENT_NOK) {
894
                  error_flags.mcuDieTemperature = 1;
895
              }
896
897
      }
898
899
      /**
900
      * @brief diagnosis callback function for coin cell voltage events
901
902
      void DIAG_error_coinCellVoltage(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event) {
903
          if (ch id == DIAG CH LOW COIN CELL VOLTAGE) {
904
              if (event == DIAG_EVENT_RESET) {
905
                  error flags.coinCellVoltage &= 0xFE;
906
907
              if (event == DIAG_EVENT_NOK) {
908
                  error_flags.coinCellVoltage |= 0x01;
909
910
          } else if (ch id == DIAG CH CRIT LOW COIN CELL VOLTAGE) {
```

```
911
              if (event == DIAG EVENT RESET) {
912
                  error flags.coinCellVoltage &= 0xFD;
913
914
              if (event == DIAG_EVENT_NOK) {
915
                  error flags.coinCellVoltage = 0x02;
916
917
          }
918
     }
919
920
      /**
921
      * @brief diagnosis callback function for plausibility events
922
923
     void DIAG_error_plausibility_check(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event) {
924
          if (ch_id == DIAG_CH_PLAUSIBILITY_CELL_VOLTAGE) {
              if (event == DIAG_EVENT_RESET) {
925
926
                  error_flags.plausibilityCheck &= 0xFE;
927
928
              if (event == DIAG_EVENT_NOK) {
929
                  error flags.plausibilityCheck = 0x01;
930
              }
931
          } else if (ch_id == DIAG_CH_PLAUSIBILITY_CELL_TEMP) {
932
              if (event == DIAG_EVENT_RESET) {
933
                  error flags.plausibilityCheck &= 0xFD;
934
935
              if (event == DIAG_EVENT_NOK) {
936
                  error flags.plausibilityCheck = 0x02;
937
938
          } else if (ch_id == DIAG_CH_PLAUSIBILITY_PACK_VOLTAGE) {
939
              if (event == DIAG_EVENT_RESET) {
940
                  error_flags.plausibilityCheck &= 0xFB;
941
942
              if (event == DIAG_EVENT_NOK) {
943
                  error flags.plausibilityCheck = 0x04;
944
945
          }
946
      }
947
948
      /**
949
      * @brief diagnosis callback function for open-wire events
950
951
      void DIAG_error_openWire(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event) {
952
          if (ch_id == DIAG_CH_OPEN_WIRE) {
953
              if (event == DIAG_EVENT_RESET) {
954
                  error_flags.open_wire = 0;
955
956
              if (event == DIAG EVENT NOK) {
957
                  error flags.open wire = 1;
958
              }
959
          }
960
      }
961
     /**
962
```

```
963
       * @brief diagnosis callback function for deep-discharge related events
964
965
     void DIAG_error_deep_discharge_detected(DIAG_CH_ID_e ch_id, DIAG_EVENT_e event) {
966
         if (ch_id == DIAG_CH_DEEP_DISCHARGE_DETECTED) {
967
             if (event == DIAG EVENT RESET) {
968
                 error_flags.deepDischargeDetected = 0;
969
                 RTC_DEEP_DISCHARGE_DETECTED = 0;
970
             }
971
             if (event == DIAG EVENT NOK) {
972
                 error_flags.deepDischargeDetected = 1;
973
                 RTC_DEEP_DISCHARGE_DETECTED = 1;
974
             }
975
         }
976
     }
977
978
     /*===== Extern Function Implementations ======*/
979
     void DIAG_updateFlags(void) {
980
         DB_WriteBlock(&error_flags, DATA_BLOCK_ID_ERRORSTATE);
981
         DB WriteBlock (&msl flags, DATA BLOCK ID MSL);
982
         DB_WriteBlock(&rsl_flags, DATA_BLOCK_ID_RSL);
983
         DB_WriteBlock(&mol_flags, DATA_BLOCK_ID_MOL);
984
985
```