

useradd AkshatChaudhary

This command is used to create the user

passwd Akshat

This is used to add password to the user which has been created, in this case for user RachanaM

su – AkshatChaudhary

It is used to switch to the specified user

pwd

It is used to retrieve the present directory path

- home/RachanaM

cat > fileedit.txt

this is an editable file to all

chmod o+w fileedit.txt

This command grants write permission to others, meaning users who are neither the owner nor in the group can now modify the file.

chmod o+r fileedit.txt

This command gives read permission to others, allowing users outside the owner and group to read the file's contents.

chmod o+rw fileedit.txt

This command provides read, write, and execute permissions to others, so any user can now read, modify, and run the file.

chmod o-w fileedit.txt

This command removes write permission from others, preventing users outside the owner and group from modifying the file, though they can still read or execute it if allowed.

chmod u+rw fileedit.txt

This command gives the owner full control of the file by granting read, write, and execute permissions.

chmod g+rx fileedit.txt

This command grants the group full access to the file, allowing users in the file's group to read, write, and execute it.

HTTP Server using Firewall

mount iso file

cd /etc/yum.repos.d

Navigates to the directory containing YUM repository configuration files on a Linux system.

mv */*/opt/

This command moves all files with a .repo extension to the /opt/ directory
or

rm -f *.repo

This command forcefully deletes all files with a .repo extension in the current directory.

vi local.repo

Opens the file named local.repo in the vi text editor. If the file doesn't exist, it will create a new one.

Once in vi, you can:

Press **i** to enter insert mode and edit the file. After editing, press **Esc** to exit insert mode.
Type **:wq** to save and quit, or **:q!** to quit without saving

Add the below contents:

[dvd1]

name=AppStream

baseurl=/run/media/root/CentOS-Stream-9-BaseOS-x86_64/AppStream

gpgcheck=0

[dvd2]

name=BaseOS

baseurl=/run/media/root/CentOS-Stream-9-BaseOS-x86_64/BaseOSgpgcheck=0
:wq

yum clean all

Used to clean up all cached data in YUM. This includes:

- Package metadata
- Downloaded packages
- Old headers

yum repolist all

Lists all configured YUM repositories, showing which are enabled and which are disabled.

yum update -y

The command updates all installed packages to their latest available versions without prompting for confirmation. The -y flag automatically answers "yes" to any prompts during the update process.

yum install httpd* -y

The command installs all packages that start with httpd, which typically includes the Apache HTTP Server and related modules. The -y flag automatically confirms the installation without prompting for user input.

systemctl enable httpd

The command enables the Apache HTTP Server (httpd) to start automatically at boot. This means that the service will be launched whenever the system is restarted.

systemctl start httpd

The command starts the Apache HTTP Server (httpd) immediately. This allows the web server to begin serving web pages without needing to reboot the system.

firewall-cmd --permanent --add-service=http

The command adds the HTTP service to the firewall's permanent rules,

allowing incoming traffic on port 80 (the default port for HTTP).

firewall-cmd --permanent --add-service=https

The command adds the HTTPS service to the firewall's permanent rules, allowing incoming traffic on port 443 (the default port for HTTPS).

firewall-cmd --reload

The command reloads the firewall configuration, applying any changes made (such as adding or removing services) without restarting the system. This

