

FitHelper - Developer Guide

1. Setting up	1
2. Design	1
2.1. Architecture	2
2.2. UI component	4
2.3. Logic component	5
2.4. Model component	6
2.5. Storage component	7
2.6. Common classes	8
3. Implementation	8
3.1. Today Feature	8
3.2. Diary Feature	10
3.3. Calendar	12
3.4. Logging	12
3.5. Add Weight Records	13
3.6. Check calorie intake/consumption of some common food/sports	15
4. Testing	17
5. Dev Ops	17
Appendix A: Product Scope	17
Appendix B: User Stories	17
Appendix C: Use Cases	19
Appendix D: Non Functional Requirements	21
Appendix E: Glossary	21
Appendix F: Product Survey	22
Appendix G: Instructions for Manual Testing	22
G.1. Launch and Shutdown	23
G.2. Adding A New Weight Record	23
G.3. Saving data	24

By: **AY1920S2-CS2103-T09-4** Since: **Feb 2020** Licence: **MIT**

1. Setting up

Refer to the guide [here](#).

2. Design

2.1. Architecture




Figure 1. Architecture Diagram

The **Architecture Diagram** given above explains the high-level design of the App. Given below is a quick overview of each component.

TIP

The `.puml` files used to create diagrams in this document can be found in the [diagrams](#) folder. Refer to the [Using PlantUML guide](#) to learn how to create and edit diagrams.

Main has two classes called **Main** and **MainApp**. It is responsible for,

- At app launch: Initializes the components in the correct sequence, and connects them up with each other.
- At shut down: Shuts down the components and invokes cleanup method where necessary.

Commons represents a collection of classes used by multiple other components. The following class plays an important role at the architecture level:

- **LogsCenter** : Used by many classes to write log messages to the App's log file.

The rest of the App consists of four components.

- **UI:** The UI of the App.
- **Logic:** The command executor.
- **Model:** Holds the data of the App in-memory.
- **Storage:** Reads data from, and writes data to, the hard disk.

Each of the four components

- Defines its *API* in an **interface** with the same name as the Component.
- Exposes its functionality using a **{Component Name}Manager** class.

For example, the **Logic** component (see the class diagram given below) defines its API in the **Logic.java** interface and exposes its functionality using the **LogicManager.java** class.




Figure 2. Class Diagram of the Logic Component

How the architecture components interact with each other

The *Sequence Diagram* below shows how the components interact with each other for the scenario where the user issues the command **delete 1**.




Figure 3. Component interactions for `delete 1` command

The sections below give more details of each component.

2.2. UI component




Figure 4. Structure of the UI Component

API : `Ui.java`

The UI consists of a **MainWindow** that is made up of parts e.g. **CommandBox**, **ResultDisplay**, **PersonListPanel**, **StatusBarFooter** etc. All these, including the **MainWindow**, inherit from the abstract **UiPart** class.

The UI component uses JavaFx UI framework. The layout of these UI parts are defined in matching **.fxml** files that are in the **src/main/resources/view** folder. For example, the layout of the **MainWindow** is specified in **MainWindow.fxml**

The UI component,

- Executes user commands using the **Logic** component.
- Listens for changes to **Model** data so that the UI can be updated with the modified data.

2.3. Logic component




Figure 5. Structure of the Logic Component

API: **Logic.java**

1. **Logic** uses the **FitHelperParser** class to parse the user command.
2. This results in a **Command** object which is executed by the **LogicManager**.
3. The command execution can affect the **Model** (e.g. adding a person).
4. The result of the command execution is encapsulated as a **CommandResult** object which is passed back to the **Ui**.
5. In addition, the **CommandResult** object can also instruct the **Ui** to perform certain actions, such as

displaying help to the user.

Given below is the Sequence Diagram for interactions within the **Logic** component for the `execute("delete 1")` API call.




Figure 6. Interactions Inside the Logic Component for the `delete 1` Command

NOTE

The lifeline for `DeleteCommandParser` should end at the destroy marker (X) but due to a limitation of PlantUML, the lifeline reaches the end of diagram.

2.4. Model component




Figure 7. Structure of the Model Component


API : `Model.java`

The `Model`,

- stores a `UserPref` object that represents the user's preferences.
- stores the Address Book data.
- exposes an unmodifiable `ObservableList<Person>` that can be 'observed' e.g. the UI can be bound to this list so that the UI automatically updates when the data in the list change.
- does not depend on any of the other three components.

As a more OOP model, we can store a `Tag` list in `Address Book`, which `Person` can reference. This would allow `Address Book` to only require one `Tag` object per unique `Tag`, instead of each `Person` needing their own `Tag` object. An example of how such a model may look like is given below.

NOTE



2.5. Storage component




Figure 8. Structure of the Storage Component

API : `Storage.java`

The `Storage` component,

- can save `UserPref` objects in json format and read it back.
- can save the Address Book data in json format and read it back.

2.6. Common classes

Classes used by multiple components are in the `fitHelper.common` package.

3. Implementation

This section describes some noteworthy details on how certain features are implemented.

3.1. Today Feature

3.1.1. Implementation

FitHelper's entries have a `Time` attribute including a `Date` and a specific `Time` in the format of `yyyy-mm-dd HH:mm`. This feature allows the user to view entries with the `Date` of today, i.e. shows only entries in today. It fetches the `filteredFoodEntryList` and `FilteredSportsEntryList` stored in FitHelper storage.

The today mechanism is facilitated by `FilteredList` which wraps a `ObservableList` and filters using the provided Predicate. A `FilteredList<Entry> filteredEntries` is stored in the `ModelManager`. In `FitHelper`, there is an `ObservableList<Entry> entries` which contains all entries, regardless of its `Type` and `Date`. `filteredEntries` in the `ModelManager` is initialized with this `ObservableList`.

Since a `FilteredList` needs a Predicate, which matches the elements in the source list that should be visible, the filter mechanism implements the following operation to support filtering:

- `Model#updateFilteredEntryList(Predicate<Entry> predicate)` — Sets the value of the property Predicate in the `filteredEntries`.
 - Predicates are declared statically in the `Model` interface, namely `PREDICATE_SHOW_ALL_ENTRIES`, `PREDICATE_SHOW_UNDONE_ENTRIES`, and `PREDICATE_SHOW_TODAY_ENTRIES`. In particular `PREDICATE_SHOW_TODAY_ENTRIES` is as follows

```
Predicate<Entry> PREDICATE_SHOW_TODAY_ENTRIES = entry ->
    entry.getTime().getDateStr().equals(new Today().getTodayDateStr());
```

- The `TodayCommand` will call this method to change the visibility of entries with different status by passing in the corresponding predicate.

An example usage scenario and how the today mechanism behaves at each step is shown below.

Step 1. The user launches the application for the first time. `UniqueEntryList` will be initialized with a list of default entries in `FitHelper`. This list contains a few entries with various dates.

Step 2. The user inputs `today` to list all today entries. `UI` passes the input to `Logic`. `Logic` then uses a few `Parser` classes to extract layers of information out as seen from steps 3 to 5.

Step 3. `Logic` passes the user input to `FitHelperParser`. `FitHelperParser` identifies that this is a `TodayCommand` through the word "today". It then creates a `TodayCommandParser` to parse the it into a `TodayCommand` and return.

Step 4. `Logic` finally gets the `TodayCommand` and execute it. The execution firstly calls `Model#updateFilteredEntryList(Predicate<Entry> predicate)` to update the Predicate in `filteredEntries` in `Model`. This execution then returns a `CommandResult` to `UI`, containing the response to the user.

Step 5. `UI` displays the response in the `CommandResult`. In addition, `UI` will change to display today entries after model updates `filteredEntries`, since `UI` is constantly listening for the change in `Model`.

The Sequence Diagram below shows how the components interact with each other for the above mentioned scenario.




Figure 9. Sequence Diagram for Today Feature

3.2. Diary Feature

3.2.1. Implementation

FitHelper also allows the user to keep a diary with a **Date** in the format of **yyyy-mm-dd** and the **content** with no more than 200 characters. The diaries are represented as model **Diary** with the attributes of **DiaryId**, **DiaryDate**, and **Content**. This feature allows the user to view their diaries. It fetches the **filteredDiaryList** stored in FitHelper storage.

The diary feature is facilitated by **FilteredList** which wraps a **ObservableList** and filters using the provided Predicate. A **FilteredList<Diary> filteredDiaries** is stored in the **ModelManager**. In **FitHelper**, there is an **ObservableList<Diary> diaries** which contains all diaries, regardless of its **DiaryDate**. **filteredDiaries** in the **ModelManager** is initialized with this **ObservableList**.

Since a **FilteredList** needs a **Predicate**, which matches the elements in the source list that should be visible, the filter mechanism implements the following operation to support filtering:

- **Model#updateFilteredDiaryList(Predicate<Diary> predicate)** — Sets the value of the property Predicate in the **filteredDiaries**.
 - The predicate is declared statically in the **Model** interface, namely **PREDICATE_SHOW_ALL_DIARIES**. In particular **PREDICATE_SHOW_ALL_DIARIES** is as follows

```
Predicate<Diary> PREDICATE_SHOW_ALL_DIARIES = unused -> true;
```

- The **DiaryCommand** will call this method to change the visibility of diaries with different status by passing in the corresponding predicate.

An example usage scenario and how the diary mechanism behaves at each step is shown below.

Step 1. The user launches the application for the first time. **UniqueDiaryList** contains no default diaries before the user adds any.

Step 2. The user inputs **diary** to list all diaries. **UI** passes the input to **Logic**. Logic then uses a few **Parser** classes to extract layers of information out as seen from steps 3 to 5.

Step 3. Logic passes the user input to **FitHelperParser**. **FitHelperParser** identifies that this is a **DiaryCommand** through the word "diary". It then creates a **DiaryCommandParser** to parse the it into a **DiaryCommand** and return.

Step 4. **Logic** finally gets the **DiaryCommand** and execute it. The execution firstly calls **Model#updateFilteredDiaryList(Predicate<Diary> predicate)** to update the Predicate in **filteredDiaries** in **Model**. This execution then returns a **CommandResult** to **UI**, containing the response to the user.

Step 5. **UI** displays the response in the **CommandResult**. In addition, UI will change to display diaries after model updates **filteredDiaries**, since **UI** is constantly listening for the change in **Model**.

The Sequence Diagram below shows how the components interact with each other for the above mentioned scenario.





Figure 10. Sequence Diagram for Diary Feature

3.3. Calendar

1. The user enters a view command in the `calendar d/tmr`.
2. `LogicManager` parses the user input, constructs and executes the `CalendarCommand`.
3. The `CalendarCommand` reaches `setCalendarDate` in the `Model` and returns the `CommandResult` to the `LogicManager`.
4. The `LogicManager` returns the `CommandResult` to the `Ui`.
5. The `Ui` gets the `date` from `LogicManager` and updates the `Ui` to display the module. The following sequence diagram shows how the update operation works to change calendar page in model:



3.4. Logging

We are using `java.util.logging` package for logging. The `LogsCenter` class is used to manage the logging levels and logging destinations.

- The logging level can be controlled using the `logLevel` setting in the configuration file (See [Section 3.5, “Add Weight Records”](#))
- The `Logger` for a class can be obtained using `LogsCenter.getLogger(Class)` which will log messages according to the specified logging level
- Currently log messages are output through: `Console` and to a `.log` file.

Logging Levels

- **SEVERE** : Critical problem detected which may possibly cause the termination of the application
- **WARNING** : Can continue, but with caution
- **INFO** : Information showing the noteworthy actions by the App
- **FINE** : Details that is not usually noteworthy but may be useful in debugging e.g. print the actual list instead of just its size

3.5. Add Weight Records

FitHelper allows the user to track with their weight change easily by allowing user to add their current weight and previous weight.

3.5.1. Sample

An example usage scenario and how the **addWeight** command behaves at each step is shown below.

Step 1.

- The user launches the application for the first time.
- **UniqueWeightList** in Model contains no default weights before the user adds any.
- **weightrecords.json** in local Storage contains no weight records as well.

Step 2.

- The user inputs **addWeight** command word, followed by **v/WEIGHT_VALUE** and an optional **d/DATE**.
- **UI** passes the input to **Logic**.
- **Logic** then uses a few **Parser** classes to extract layers of information out as seen from steps 3 to 5.

Step 3.

- **Logic** passes the user input to **FitHelperParser**.
- **FitHelperParser** identifies that this is a **AddWeightCommand** through the command word "addWeight".
- It then creates a **AddWeightCommandParser** to parse the input into a **AddWeightCommand** and return back.

Step 4.

- **Logic** gets the **AddWeightCommand** and execute it.
- The execution firstly check is the new weight date is after today's date and if there is already a existing weight in the **UniqueList**.
- Both of these two cases will throw corresponding **CommandException**.
- Then the execution add the new **Weight** into model.
- Finally, it returns a **CommandResult** to **UI**, containing the response to the user and the displayPage,

which equals to `WEIGHT` page.

Step 5.

- UI displays the response in the `CommandResult`.
- In addition, UI will change to display Weight Page after updating Profile Page and Weight Page.

3.5.2. Implementation

Storage

A weight is stored with three attributes in the `weightrecords.json` database:

- `date` : the date of the weight record in format of `yyyy-MM-dd`, if no date is provided by the user, the **default value** is the date of today
- `weightValue` : a double value with two decimal places.
- `bmi` : the BMI value is also a double value with two decimal places. It is auto-computed and stored, using the formula : $BMI = \text{Weight Value(kg)} / \text{Height(m)}^2$. The Height value gets from user profile in `userprofile.json` database.

Model

- A single weight is represented as model `Weight` with the attributes of `Date`, `WeightValue`, and `Bmi`.
- In `ModelManager`, all weights are represented by `WeightRecords weightRecords`.
 - The `WeightRecords` class implements `ReadOnlyWeightRecords` interface, and therefore can return an **unmodifiable** version of a **unique** list of weights.
 - The `WeightRecords` wraps a `UniqueWeightList` which allows adding and iterating. **Unique** here refers to the constraint that no two weight with the same date can exist in the list/database.
- In `ModelManager`, a `FilteredList<Weight> filteredWeight` object is used to store and update a filtered version of all weights.
 - The `FilteredList` wraps a `ObservableList` and filters using a provided `Predicate`.

UI

When user input `addWeight` command to UI, the input is passed to `Logic` part as a `String`.

After `addWeight` command is executed, a `CommandResult` with `DisplayPage` equals `WEIGHT` will be passed back to `MainWindow` in UI part. Then:


- Firstly, it will call `updateProfilePage()`, since if the newly added weight has the latest date, Current Weight and Current BMI in user profile will need to be updated.
- Secondly, it will call `updateWeightPage()`, since if a new weight is added successfully, new points should be added on to Weight Line Chart and BMI Line Chart. The text content of top notification will also be updated if the gap between Current Weight and Target Weight is changed.
- Lastly, it will call `showWeightPage()`. This allows the Main Window auto-switch to Weight Page

after each `addWeight` command by user.

Logic

The Sequence Diagram below shows how the components interact with each other for the mentioned scenario in sample.

Sequence Diagram for Add Weight Feature



3.6. Check calorie intake/consumption of some common food/sports


3.6.1. Implementation

The check function is achieved by calling the `FitHelper` inside the `ModelManager` to search through either `FoodCalorieTable` or `SportsCalorieTable` for `CalorieEntry` that contain the keywords specified by the user.

Given below are example usage scenario:

Initialization: when the application is launched, `ModelManager` will initialize a `FitHelper`, which will in turn initialize both `FoodCalorieTable` and `SportsCalorieTable` to contain pre-set data which is a list of one type of `CalorieEntry` (either `FoodCalorieEntry` or `SportsCalorieEntry`).


Sequence Diagram of CalorieTables Initialization



Case 1: when the user enter the command `check x/sports k/swim`, the `LogicManager` will create a `CheckCommand`, which asks `ModelManager` to let `FitHelper` to search through `SportsCalorieTable` to add first 3 `CalorieEntry` whose name contains the keyword `swim` into a List, and return the list to `CheckCommand`. Since the list contains at least one `CalorieEntry` (meaning there is some matching entries), the `CheckCommand` returns a `CommandResult` whose `feedbackToUser` contains a success message followed by the string representation of each matching entries.

Case 2: when the user enter the command `check x/f k/swim`, the `LogicManager` will create a `CheckCommand`, which asks `ModelManager` to let `FitHelper` to search through `FoodCalorieTable` to add first 3 `CalorieEntry`'s whose name contains the keyword `swim` into a List, and return the list to `CheckCommand`. Since the list contains no `CalorieEntry` (meaning there is no matching entries), the `CheckCommand` returns a `CommandResult` whose `feedbackToUser` contains a failure message followed by the string representation of the keyword.

Sequence Diagram of Check Command



3.6.2. Design Considerations

Aspect: Data structure to store entries

- **Alternative 1 (current choice):** Use an `ArrayList` as an attribute in `CalorieTable` to store the entries.
 - pros: easy to implement partial-key search (compare the keyword with the name of each entry in the list).

- cons: $O(n)$ complexity for finding matching entries, where n is the number of entries in the list.
- **Alternative 2:** Use a **HashMap** as an attribute in CalorieTable to store the entries. The key is the name of the entry and the value is the entry.
 - pros: (theoretically) $O(1)$ time complexity for finding an entry given a complete keyword, regardless of how many entries are in the HashMap.
 - cons: hard to implement partial-key search (i.e. the keyword is only part of the name of the entry). == Documentation

Refer to the guide [here](#).

4. Testing

Refer to the guide [here](#).

5. Dev Ops

Refer to the guide [here](#).

Appendix A: Product Scope

Target user profile:

- has a need to control weight, therefore need to record daily food intake and sports
- prefer desktop apps over other types
- can type fast
- prefers typing over mouse input
- is reasonably comfortable using CLI apps

Value proposition: achieve fitness control faster than a typical mouse/GUI driven app

Appendix B: User Stories

Priorities: High (must have) - * * *, Medium (nice to have) - * *, Low (unlikely to have) - *

Priority	As a ...	I want to ...	So that I can...
* * *	new user	record my basic information such as name and gender	have a more complete profile
* * *	user who is concerned about body shape	record and update my current height and weight	have a clear view of my current body condition
* * *	user who wants to lose weight	set my target weight	have a clear target to work towards

Priority	As a ...	I want to ...	So that I can...
* * *	user who wants to set diet plans	add a food entry	can plan my diet
* * *	user who wants to control calorie intake	view the calorie in each food entry	can keep track of my calorie intake
* * *	user who wants to set sports plans	add a sport entry	can plan for my sport exercises
* * *	user who wants to increase calorie consumption	view the calorie consumption for each sport entry	can keep track of my calorie consumption
* * *	user who wants to adjust my diet/sports plans	edit a food/sports entry	can have my plans and records updated
* * *	user who wants to remove my diet/sports plans	delete a food/sports entry	
* * *	user who wants to search for an entry	search by keywords in the entry name	can find related entries without having to scan through all the entries
* * *	user who wants see today's plans	switch to Today Page and view the daily food/sports plans	can have a general idea of the daily diet/sports arrangements
* * *	user who needs some suggestions for my daily plan	switch to Today Page and view FitHelper feedback	I know whether my daily food/sports plan is suitable
* * *	user who wants to know my daily performance	switch to Today Page and view my performance report	I know my food calorie intake distribution and my task completion
* * *	user who types wrongly sometimes	undo my previous command	I do not need to delete explicitly using a long command
* * *	user who types wrongly sometimes	redo my previous undo command	I can re-executed a undone command
* * *	user who wants to keep a diary	add a diary log for a specific day	note down my schedules, feelings, goals and so on as a self-encouragement
* * *	user who wants to append more content to a previous diary	append new content to existing diaries	enrich my previous diaries' content
* * *	user who wants to replace the content of a previous diary with new content	edit existing diaries	modify the content to an updated version

Priority	As a ...	I want to ...	So that I can...
* * *	user who wants to remove some diary logs	delete existing diaries	keep abandon some diary logs that I do not want to keep
* * *	user who wants to clear my diary	clear all existing diaries	I can re-start my diary from a white paper
* *	user who wants keep fit	acknowledge my weight change trend according to time	keep track of my weight change easily
* *	user who wants to lose weight	compare between my current weight and target weight	know the gap clearly
* *	user	update my basic information such as address and name if necessary	have an updated profile at any time
* *	user	view pending tasks and status of daily calories goals in a calendar	have cleaner display of data
* *	user who wants to have a clean user interface	clear entries regularly	do not need to see irrelevant information
* *	user	leave the application when I need	It does not occupy additional space in my computer
* *	user	list all entries by certain criteria	I can filter the tasks by what I am looking for
* *	user	get reminders for tasks not done	I can focused on these tasks and complete them
* *	user who do not know very well about dieting and exercising	check calorie intake/consumption of common food and sports	I can input calorie intake/consumption without having to search about these information online.
* *	first-time user	view help page	I can know the functions of the application quickly

{More to be added}

Appendix C: Use Cases

(For all use cases below, the **System** is the **FitHelper** and the **Actor** is the **user**, unless specified otherwise)

Use case: UC01 - Add an Entry

MSS

1. User adds an entry specifying a meal or a sport with name, time, location, and calorie.
2. FitHelper stores the entry to the specific date file.
3. FitHelper display successful record and the entry status.

Use case ends.

Extensions

- 1a. User input incomplete values.

1a1. FitHelper shows an error message.

Use case ends.

- 1b. The input time has clashes with previous entries.

1b1. FitHelper shows an error message.

Use case ends.

Use case: UC02 - Edits an Entry

MSS

1. User edits an entry specifying a meal or a sport with name, time, location, and calorie.
2. FitHelper modifies the entry to the specific date file.
3. FitHelper display successful record and the entry status.

Use case ends.

Extensions

- 1a. User input repeated values that are already stored in the entry.

1a1. FitHelper ignores the edit command.

Use case ends.

Use case: UC03 - Deletes an Entry

MSS

1. User deletes an entry by using the `delete` command.
2. FitHelper deletes the corresponding entry in the list and in the file.
3. FitHelper display the entry status and the successfully-delete message.

Use case ends.

Extensions

1a. The **INDEX** specified by the user does not exist.

1a1. FitHelper shows an error message.

Use case ends.

{More to be added}

Appendix D: Non Functional Requirements

1. Should work on any **mainstream OS** as long as it has Java **11** or above installed.
2. Should be able to hold up to 1000 entries without a noticeable sluggishness in performance for typical usage
3. Should be able to function normally without internet access.
4. A user with above average typing speed for regular English text (i.e. not code, not system admin commands) should be able to accomplish most of the tasks faster using commands than using the mouse.
5. A user can get response from the system within 5 seconds after command input.
6. A user can be familiar with the system commands and interface within half an hour usage.

{More to be added}

Appendix E: Glossary

Mainstream OS

Windows, Linux, Unix, OS-X

Table 1. Command Prefix

Prefix	Meaning	Used in the following Command(s)
x/	Type of entry	add, check, delete, edit, find
i/	Index of entry	edit, delete, edit
n/	Name	add, edit
t/	Time in format of "date hour minute"	add, edit
l/	Location	add, edit
c/	Calorie	add, edit
s/	Status	add, edit

Prefix	Meaning	Used in the following Command(s)
r/	Remark	edit
d/	Date in format of yyyy-MM-dd	calendar, addWeight
dr/	Duration in format of yyyy-MM-dd yyyy-MM-dd	add, edit
dc/	Dairy contents	dairy
k/	Keyword	check, find
attr/	Attribute in user profile	update
v/	Attribute Value in user profile	update, addWeight

Table 2. Possible Command Flags

Command	Flag	Meaning
Sort	-a	Sort in ascending order
Sort	-d	Sort in descending order
Sort	-t	Sort according to time
Sort	-c	Sort according to calorie intake
Update	-f	Force update even with existing value

Appendix F: Product Survey

Product Name : FitHelper

Author: ...

Pros:

- ...
- ...

Cons:

- ...
- ...

Appendix G: Instructions for Manual Testing

Given below are instructions to test the app manually.

NOTE

These instructions only provide a starting point for testers to work on; testers are expected to do more *exploratory* testing.

G.1. Launch and Shutdown

1. Initial launch

a. Download the jar file and copy into an empty folder

b. Double-click the jar file

Expected: Shows the welcome page of FitHelper. On the left hand side, the user can see a list of page name. Users are able to click on the button or using corresponding command to direct to that page.

c. The window size is fixed.

2. Shutdown

a. Users are able to shutdown the application using CLI with following commands:

- `exit`
- `quit`
- `bye`

b. Users can also choose to shutdown the application by clicking on X button on the right top side if the window.

c. User data will be auto-saved if user choose to shutdown the application. Three local data file in json format can be find:

- `fithelper.json` : containg data related to entries and diaries.
- `userprofile.json` : containing data related to user profile.
- `weightrecords.json` : containing data related to all weight records.

G.2. Adding A New Weight Record

1. Add **first weight record** while there is no previous weight record in the database.

a. Prerequisites: None. Users are able to use `addWeight` command at any page.

b. Test case: `addWeight v/50.0`

Expected:

- A new `Weight` is added into `weightrecords` database, with `WeightValue` equals 50.0, `Date` with default value(today's date) and `BMI` calculated by `Height`.
- The window is automatically directed to weight page. A new point is shown on both Weight Line Graph and BMI Line Graph. The top notification is also updated.
- In profile page, Current Weight and Current BMI change from "Not Available Now" to the newest value.

c. Test case: `addWeight v/49.0 d/2050-01-01`

Expected: No new weight record is added since the date is after current date. An error

message is shown in the command result box.

2. Add new weight record when there is already **some previous weight records existing** in the database.
 - a. Prerequisites: None. Users are able to use `addWeight` command at any page.
 - b. Test case: `addWeight v/48.0`
Expected: No new weight record is added since there is existing weight record with the same date (by default is today's date) in the data base. An error message is shown in the command result box.
 - c. Test case : `addWeight v/47.0 d/2020-03-01`
Expected:
 - A new `Weight` is added into `weightrecords` database, with `WeightValue` equals 47.0, `Date` with 2020-03-01 and `BMI` calculated by `Height`.
 - The window is automatically directed to weight page. A new point is shown on both Weight Line Graph and BMI Line Graph, and form a new trend line with previous data points. The top notification is also updated.
 - In profile page, Current Weight and Current BMI remain the same, since the newly added weight record is not the most recent record in the database.

G.3. Saving data

1. Dealing with missing/corrupted data files
 - a. If the application is launched and shut down at least once, there will be three local database in json format.
 - b. Delete `fithelper.json`, and launch FitHelper again. All user manipulation on entries and diaries will be cleared. `Dashboard`, `Today`, `Calendar` and `Diary` Page will restart with sample data.
 - c. Delete `userprofile.json`, and launch FitHelper again. All user manipulation on user profile will be clear. `Profile` page will restart with sample user data.
 - d. Delete `weightrecords.json`, and launch FitHelper again. All user manipulation on weight records will be clear. `Profile` page will show Current Weight and Current BMI as "Not Available Now", and `Weight` Page will have no data point on the trend line graph.