
KEYBOARDWARRIOR

Developer Guide

Architecture, behavior and implementation.
Design decisions, data formats and verification.



ONLINE DEVELOPER GUIDE

https://ay2627s1-cs2113-w12-4.github.io/tp/DeveloperGuide.html

PRODUCT v2.0

27 October 2026

Contents

Acknowledgements . . . 3

Design and implementation . . . 3

Runtime and terminal input . . . 3

Game difficulty selection . . . 3

Seeds and reproducible choices . . . 4

Records and all-time leaderboard . . . 4

Active run saves . . . 7

Typing evaluation and damage . . . 9

Scenario progression and two-phase final boss . . . 12

Defensive programming and diagnostics . . . 16

Product scope and requirements . . . 16

Testing . . . 18

Automated checks . . . 18

Manual gameplay acceptance tests . . . 19

Manual evaluator checks . . . 21

Maintaining the documentation . . . 22

Acknowledgements

The project uses the CS2113 tP starter template, JLine for interactive terminal input and JUnit Jupiter for tests. Typing evaluation uses the Java standard library.

Design and implementation

Runtime and terminal input

`KeyboardWarrior.java` selects an input mode and starts the main menu. When no native console is available, it selects plain input before initializing JLine. Capable interactive terminals use JLine and `CountdownReader` to keep the live countdown above the passage while preserving edited input. A JLine terminal without redraw capabilities also falls back to plain input instead of returning before the menu. Both input modes accept `exit` and handle end-of-input as a clean shutdown.

The live input loop queues complete lines on a background reader; the main thread processes input and updates the state machine every 100 milliseconds. Plain mode uses a synchronous buffered line reader, prints the initial time allowance and passage, and handles each line on Enter without an automatic-expiry update tick. A line-buffered console may withhold typed characters until Enter, so plain mode waits for that line rather than scoring an empty input before it arrives. The clock still measures actual elapsed time, and a late line uses the ordinary evaluator and damage formula.

`MainMenuState` accepts `start`, asks for a seed and enters `GamePlayState` after the seed input. An empty seed line chooses a random seed. The gameplay state owns the run's player, current encounter, clock and challenge factory. The same player and prompt selection history survive scenario and boss phase transitions. `exit` stops the application from the menu, seed prompt, skill selection or an active typing challenge.

`run-game.bat` and `run-game.sh` first invoke Gradle's `prepareTerminalRun` task. That task depends on `classes`, writes the runtime classpath and the build JVM's Java home, and does not create a JAR. The launcher starts Java in the foreground with `-ea` and native access enabled. Direct terminal input avoids Gradle `run` and IDE Run console stream redirection, which can prevent JLine from seeing unsubmitted keystrokes. On Windows, the entry point selects the native Windows terminal type even when the launcher supplies `TERM=dumb`.

These scripts are conveniences for a source checkout. The release is one executable fat JAR for Windows, macOS and Linux and must start with Java 25 using `java -jar KeyboardWarrior.jar` without Gradle or repository scripts. Its manifest includes `Enable-Native-Access: ALL-UNNAMED` for JLine's bundled native support; this removes Java 25's native-access warning but does not create a terminal.

Game difficulty selection

`GameDifficulty` is separate from `TypingChallenge.Difficulty`: it describes run modifiers rather than passage content. Easy, Normal, Hard and Coder use multipliers 4, 2, 1 and 0.8 for player damage, starting health and countdowns. Hard is the default to preserve the original balance.

`MainMenuState` accepts numbers 1-6 or the names Start, Records, Exit, Choose Difficulty, Continue and Leaderboard. `DifficultySelectionState` accepts a mode number or name, then returns to a new menu with the same `SaveStore` and selected mode. Invalid input leaves the selection menu active. Gameplay passes that

mode back to the menu after victory or defeat, preserving it for the session. The menu selection is not saved separately, but the active run save includes its mode. Continue restores that mode.

`GamePlayState` creates the player with 400, 200, 100 or 80 HP and supplies the mode to the shared `TypingChallengeFactory` and every `CombatEncounter`, including both boss phases. The factory applies the countdown multiplier after calculating the normal base deadline and rounds up. Encryption uses a base of 60 seconds, becoming 240, 120, 60 or 48 seconds. `SkillResolver` multiplies typing damage before rounding down once. Automated enemy attacks keep their original base damage.

Seeds and reproducible choices

After Start, `MainMenuState` treats the next line as a seed rather than a menu choice. `SeedGenerator.parseSeed(...)` trims a nonblank line, parses it as a signed Java `long`, or uses the trimmed string's `hashCode()` if numeric parsing fails. Blank input generates a fresh random `long`. Text seeds are case-sensitive, and an out-of-range integer is handled as text. The resolved numeric seed is displayed. At this prompt `exit` quits; `3` is a seed, not the menu's Exit shortcut.

The menu constructs one `RunRandom` for the run. `GamePlayState` shares it between `EnemyFactory` and `PromptBank`, including Encryption generation. `RunRandom` extends `Random` and implements the same 48-bit linear congruential sequence, including Java's seed scrambling. Its `snapshot()` records the current internal position; `restore(...)` validates that position and resumes without replaying earlier draws. Gameplay uses `nextInt(...)` for its random choices.

`PromptBank` also tracks the last selected passage index for each `TypingChallenge.Difficulty`, excluding that passage from the next selection at that level. Switching skills does not clear the other levels' history. The bank and generator are shared across all scenarios and boss phases. Repeating a seed reproduces random choices for the same sequence of challenge requests and encounter transitions in the same product version. A different number of attempts or different skills can consume different draws; seeds do not fix typing speed, accuracy or combat outcomes.

Records and all-time leaderboard

Responsibilities and stored data

Records shows the latest ten typing attempts, oldest first. Leaderboard shows one all-time best attempt, even after that attempt leaves the ten-entry history. Both contain WPM and character accuracy rather than combat damage, player names or whole-run scores. Evaluated partial and empty attempts are eligible too; the first zero-score attempt creates a high score if none exists.

Class	Responsibility
`state.MainMenuState`	Handle Records and Leaderboard commands, report loading errors and redisplay the main menu
`state.GamePlayState`	Save each evaluated attempt before resolving its combat effects
`storage.SaveStore`	Retain the latest ten records and coordinate high-score initialization and updates
`storage.SaveStore.SavedRecord`	Hold one immutable pair of WPM and accuracy values
`storage.LeaderboardStore`	Load the all-time best and replace it only when a candidate ranks higher
`storage.FileStore`	Share absolute file locations and safe replacement through a temporary file
`ui.StateUi`	Format records, the best attempt or an empty message using the shared terminal output

`SaveStore` and `LeaderboardStore` extend `FileStore`. `SaveStore` owns a `LeaderboardStore` whose path is derived from the history filename, so an injected history location also isolates its high score. The default files are relative to the directory from which the game is launched:

File	Contents	Retention
`data/keyboardwarrior.txt`	UTF-8 lines in `wpm,accuracyPercent` format	Latest ten attempts, oldest first
`data/keyboardwarrior.txt.high-score`	Exactly one UTF-8 line in the same format	Best attempt until a better one is saved

For example, a custom history path `test-data/history.txt` uses `test-data/history.txt.high-score`. Neither file contains resumable game state; that belongs to `GameSaveStore`.

Saving attempts and preserving the best score

After evaluating an attempt, `GamePlayState` displays its typing summary and calls `SaveStore.save(result)` before `CombatEncounter.submitTypingResult(result)`. Saving follows this order:

1. Call `loadHighScore()` to preserve the best existing history entry if no high-score file exists.
2. Pass the new `SavedRecord` to `LeaderboardStore.saveIfHigher(...)`.
3. Read the existing history, append the new attempt and write only the latest ten entries.

`LeaderboardStore.SCORE_ORDER` compares full-precision WPM first, then accuracy. Higher WPM wins regardless of accuracy; higher accuracy wins when WPM is equal. Lower scores and exact ties leave the high-score file untouched. For example, after `60,95`, an attempt of `50,100` cannot replace it, `60,98` can, and `70,80` then becomes the best. The UI rounds values to two decimal places only for display.

`loadHighScore()` returns `Optional<SavedRecord>`. If the high-score file is missing, it finds the maximum among the available history records and persists it before returning. This supports existing installations and happens both when viewing the leaderboard and before saving another attempt. Initializing before history rotation prevents the oldest record from being discarded before it can become the initial high score. Attempts discarded before this feature existed cannot be recovered. Once a valid high-score file exists, loading it does not depend on the history file.

Both stores use `FileStore.writeSafely(...)`: write a complete temporary file in the destination directory, then replace the destination with an atomic move where supported, or a regular replacement move otherwise. Temporary files are cleaned up in `finally`. These are separate file writes, not a transaction across both files. If updating the high score fails, history is not appended; if history writing fails after the high score succeeds, the new best can remain saved without its history entry. The gameplay state reports the `IOException` as a typing-history saving error and still resolves combat.

Menu display and error handling

`MainMenuState` trims commands and accepts option names case-insensitively:

Command	Load and display flow
`2` or `records`	`SaveStore.load()` returns an immutable list, passed to `StateUi.showRecords(...)`
`6` or `leaderboard`	`SaveStore.loadHighScore()` selects `StateUi.showLeaderboard(SavedRecord)` or `StateUi.showEmptyLeaderboard()` through `ifPresentOrElse(...)`

After either result, empty message or loading error, the state calls `StateUi.showMainMenu(difficulty)`. The full menu appears below the output and accepts the next command immediately. No separate Records or Leaderboard state is created: the existing `MainMenuState`, selected difficulty and `SaveStore` remain active. The UI accepts a concrete `SavedRecord`; handling the optional result belongs to the state.

The same `SaveStore` is passed into gameplay and back to the menu after victory or defeat, preserving the file location across runs. `StateUi.printLine(...)` routes output through the attached terminal or standard output, so these views work with both live and plain input modes.

A missing history file produces an empty list. A missing high-score file triggers initialization; if there is also no history, the leaderboard shows its empty message. Loaded WPM must be finite and nonnegative, and accuracy must be finite and within 0-100. Each record needs exactly two fields, and the high-score file must contain exactly one line. Malformed loaded data and unreadable files produce `IOException`; an invalid high-score file is not silently overwritten or replaced from history. Records reports `Could not load typing history: ...`; Leaderboard reports `Could not load leaderboard: ...`.

Design choices and alternatives

Choice	Rationale	Alternative considered
Separate persistent high score	Keeps the best attempt after history rotation and application restarts	Computing a maximum from the latest ten loses older best attempts; an in-memory maximum is lost on restart
Two numeric fields per record	Reuses existing typing metrics and a simple local file format	Keeping every attempt would allow broader statistics but requires unbounded history or a retention policy
Redisplay the existing menu	Preserves difficulty and storage without extra navigation state	A dedicated state would be useful if these views later gained interactive filtering or pagination

Active run saves

`GameSave` is an immutable record of a stable player turn: format version, game difficulty, current player HP, zero-based scenario index, boss phase, enemy type identifier, current enemy HP, next enemy skill index and an optional `RandomSnapshot`. Its constructor validates version, progression combinations, health bounds and attack rotation against `EnemyFactory`. Regular encounters use scenario indices 0-4 with boss phase 0; the boss uses index 5 and phase 1 or 2. Dead participants cannot be saved.

`RandomSnapshot` holds the generator's internal position and an immutable copy of per-difficulty previous passage indices. It validates the position through `RunRandom.restore(...)` and the indices against a `PromptBank`. The original seed alone would restart the sequence rather than resume it.

`CombatEncounter.snapshot()` rejects calls before combat starts, during a pending typing attack, or after completion. `begin(savedAttackIndex)` restores rotation without taking a turn. `EnemyFactory.getTypeId(...)` supplies stable identifiers; loading recreates the exact enemy type with its standard skills instead of rerolling it. `GameSave.restoreEnemy()` applies the saved HP.

`GameSaveStore` uses UTF-8 Java properties at `data/game-save.properties`, independently of typing history and the leaderboard. For alternate history locations, run storage shares `SaveStore.getDirectory()`, allowing tests to use `@TempDir` throughout. `GameSaveStore` extends `FileStore` and uses its temporary-file replacement method, with an atomic move where supported and a regular replacement move otherwise. Invalid/missing fields and unsupported versions become `IOException`; an absent file means no run. Runtime saves and temporary files are excluded from Git.

Properties	Stored values
`version`, `difficulty`, `playerHealth`	Format version 1, game difficulty enum name and remaining player HP
`scenarioIndex`, `bossPhase`	Regular scenario 0-4 with phase 0, or scenario 5 with boss phase 1-2
`enemyType`, `enemyHealth`, `nextEnemySkillIndex`	Stable opponent identifier, remaining HP and next attack rotation index
`randomState`	Unsigned 48-bit generator position for the next random draw
`previousPrompt.<DIFFICULTY>`	Last selected passage index for each passage difficulty already used

The random fields are optional for compatibility with earlier version-1 saves. If neither `randomState` nor any `previousPrompt.*` key exists, loading returns a legacy save without a `RandomSnapshot`. A history key without `randomState`, an invalid difficulty/index or an invalid generator position is rejected. A valid generator position with no history keys is allowed, such as a save taken before the first passage is selected.

`GamePlayState.enter()` separates fresh-run initialization from restoration. The latter creates fresh runtime objects, directly restores player HP and progression, then begins the restored encounter at its saved rotation. It does not reapply the health multiplier or take an enemy turn. For current saves, construction restores `RunRandom` and `PromptBank` history before selecting any new passage or enemy. Legacy saves restore combat state but start with fresh randomness and empty passage history, so their original future choices cannot be recovered.

Clock state, terminal objects and unfinished typed text are not serialized. Resuming an interrupted challenge returns to its previous skill-selection point and restores that point's random state; choosing the same skill again reproduces the interrupted passage for a current save. Its timer starts again when that passage is shown.

Autosaves occur after encounter setup (including scenario/boss transitions) and after a surviving enemy's response. No manual save command is exposed. Continue loads before transitioning states, so invalid saves leave the menu usable. Start replaces the previous slot once the initial encounter is ready. Victory and defeat remove it; Exit retains it. IO errors are reported while gameplay remains usable.

Regression tests cover reopening stores, all modes and boss phases, corrupt values, temporary-file cleanup, exact random choices and enemy rotation after resume, interrupted attempts, new-run replacement, progression, deletion after completion and combat continuing when storage fails.

Assertions check the internal save/restore boundaries: autosaves require a living player, an active encounter, valid progression and no pending typing challenge. Combat snapshots check living participants and attack rotation. Restoration asserts that health, opponent and next attack match the saved data. File validation still uses exceptions because malformed saves must be rejected even without `-ea`.


Typing evaluation and damage

Responsibilities and data flow

The typing package evaluates a completed input snapshot. It does not read the terminal, measure time, apply damage or select an enemy. `GamePlayState` supplies expected text, current input, elapsed seconds and required seconds to `TypingEvaluator.evaluateTyping(...)`. The returned `TypingResult` is immutable. The state prints a summary and sends the same result to `CombatEncounter.submitTypingResult(...)`. The encounter delegates damage to `SkillResolver`, preserving the boundary between measurement and combat.

Class	Responsibility
`TypingEvaluator`	Validate and normalize the four inputs; coordinate metrics and retained word diagnostics
`AccuracyCalculator`	Compute character accuracy using Levenshtein edit distance
`WpmCalculator`	Compute gross WPM from normalized submitted character count and elapsed seconds
`WordErrorFinder`	Retain positional wrong, missing and extra word diagnostics for later features
`TypingResult`	Store full-precision metrics, supplied times and a defensive copy of word errors
`TypingResultFormatter`	Produce the short gameplay summary or optional detailed word report
`SkillResolver`	Convert WPM and character accuracy into player damage and apply health changes
`TypingChallengeFactory`	Select a skill's prompt and base deadline, then scale by the run difficulty

The sequence below focuses on evaluation. The calls to `TypingEvaluator` and `AccuracyCalculator` are static operations; formatting and combat happen after the result returns.



Sequence diagram for evaluating one typing attempt

Editable PlantUML source.

Normalization and character accuracy

Both strings are normalized with `trim()` and `replaceAll("\\s+", " ")`. This removes leading and trailing whitespace and collapses repeated internal whitespace. Capitalization and punctuation are preserved. Let `expected` and `typed` denote those normalized strings.

```
accuracyPercent = 100 * (1 - editDistance(expected, typed) / max(expectedLength, typedLength))
```

Edit distance is the minimum number of insertions, deletions and substitutions that transforms one string into the other. `AccuracyCalculator` compares Unicode code points, so a supplementary character counts as one character for accuracy. A deleted character is one edit rather than a shift that makes every later character incorrect. Empty typed text is valid and produces zero accuracy; expected text must remain nonempty after normalization, guaranteeing a positive denominator.

The implementation uses the usual dynamic programming recurrence. Each cell takes the minimum of insertion, deletion and substitution cost. Only the previous and current row are retained, and the shorter string occupies the columns. Runtime is `O(m * n)` and working memory is `O(min(m, n))` for code point counts `m` and `n`. English challenge passages keep these inputs small. Evaluation compares final text snapshots, so it cannot count mistakes that the player corrected before submission.

Word diagnostics remain separate from accuracy. `WordErrorFinder` still compares words at corresponding positions and produces `WRONG`, `MISSING` and `EXTRA` entries. These entries are preserved for future feedback; their count does not determine character accuracy. Gameplay uses `formatTypingSummary`, which prints WPM,

accuracy and the two times without the word list. `formatTypingResult` remains available for detailed component inspection.

Speed, damage and time allowance

Gross WPM remains `(normalizedTyped.length() / 5.0) / (elapsedSeconds / 60.0)`. The existing WPM contract uses Java `String.length()` (UTF-16 code units), whereas character accuracy uses code points. This produces the same length for the intended ASCII English passages. Incorrect submitted characters and normalized spaces count toward gross speed; Enter and discarded surrounding whitespace do not.

Player damage is now independent of the chosen skill's base damage:

```
accuracyFraction = accuracyPercent / 100
playerDamage = floor(wpm * accuracyFraction^4 * gameDifficultyMultiplier)
```

`SkillResolver` calculates with full precision and rounds down once. On Hard, at 50 WPM and 95% accuracy this is `floor(50 * 0.95^4) = 40`; at 50 WPM and 80% accuracy it is 20. The fourth power rewards accurate input and limits the benefit of entering fast, unrelated text. A skill still chooses passage difficulty. Its base damage continues to apply when the resolver receives no typing result for an automated enemy attack. This preserves existing enemy skill rotations.

The countdown limits how long an attempt can remain open. For skills other than Encryption, `TypingChallengeFactory` computes:

```
minimumSeconds = 15 / 30 / 30 / 45 for Easy / Medium / Hard / Ultimate
baselineSeconds = normalizedPrompt.length() * 60 / (5 * 50)
requiredSeconds = max(minimumSeconds, ceil(baselineSeconds * 1.2))
finalSeconds = ceil(requiredSeconds * gameDifficultyMultiplier)
```

This gives a 50 WPM player a 20% time buffer while retaining the previous minimum allowances. The buffer increases available typing time; it is not a damage multiplier. Required time therefore varies by passage. `ChallengeClock` starts after prompt display. Skill selection and previous turn feedback are outside the measured duration.

`CombatEncounter` calls `TypingChallengeFactory.generateForSkill(...)` so skills sharing a difficulty can use different passages. Encryption remains Ultimate, with a base deadline of exactly 60 seconds before applying the game difficulty multiplier. `PromptBank.getEncryptionPrompt()` uses a randomly selected Ultimate passage's character count as its target length, then generates random special characters in space-separated groups of one to six. The resulting passage is between the target length and six characters longer. Other skills continue to use the difficulty-based generator above.

Both Enter and live-terminal automatic expiry use the same evaluator. At expiry, `GamePlayState.update()` obtains `StateUi.takeCurrentInput()` before clearing the editable line and resolving the attempt. The actual elapsed duration is supplied, so captured partial text retains its measured WPM and accuracy. `isTimeLimitExceeded()` reports the strict comparison `elapsedSeconds > requiredSeconds`. It is metadata: overdue attempts receive no additional damage reduction. The retained compatibility getter `getTimeDamageMultiplier()` returns `1.0`; player damage does not depend on it. Plain mode does not call the automatic-expiry update tick; `handleInput(...)` evaluates the line when Enter arrives, retaining actual elapsed time even after the displayed deadline.

Validation and defensive checks

Null text or dependency references cause `NullPointerException`. Blank normalized expected text, nonpositive or nonfinite times and out-of-range result metrics cause `IllegalArgumentException`. Empty player text is a valid zero-score attempt. Result fields are immutable; word error lists are copied and exposed as unmodifiable lists. `WordError` positions begin at `1` and use an empty string for an absent word.

Assertions check computed accuracy bounds, finite nonnegative WPM, edit distance bounds and health updates. Public argument checks remain active without `-ea`. The state clears its active challenge before completing a turn, and the encounter requires exactly one pending skill before accepting a result. A duplicate result or invalid turn sequence causes `IllegalStateException`, preventing accidental double attacks. Existing `FINE` logging records combat events without cluttering gameplay.

Design choices and alternatives

Choice	Rationale	Alternative considered
Character edit distance	Local insertions and deletions produce local accuracy costs	Positional word matching can mark the rest of a passage wrong after one omitted word
Two-row dynamic programming	Retains the exact score with bounded working memory	A full matrix stores every cell and is only useful if a later feature needs an edit trace
Fourth-power accuracy factor	Makes careful typing matter while keeping one formula across skills	Linear accuracy penalizes fast inaccurate text less; skill base multipliers make equal typing performance deal different damage
Length-based deadline with a minimum	Makes longer passages achievable at the balance target	One fixed deadline per skill can demand very different WPM from randomly selected passages
Deadline as metadata	Capture still ends the turn, without a second score reduction	An extra late multiplier obscures the direct relationship between text, speed and damage


Scenario progression and two-phase final boss

Run structure and ownership

A run starts with one `Player` at the selected mode's starting HP (100 on Hard), passes through five regular scenarios and ends with two phases of the Kernel Overlord. Defeating scenario 5 starts the boss rather than winning the run. Only victory against boss phase 2 triggers the run victory message and return to the main menu. Player defeat at any point ends the run immediately. A new `start` creates a new player and resets scenario, phase and challenge state.

`GamePlayState` coordinates progression; `CombatEncounter` continues to resolve only one enemy at a time. This keeps the existing combat boundary intact. `scenarioIndex` tracks regular scenario progress, while `bossPhase` is `0` during regular scenarios and `1` or `2` during the boss. The private helpers `startScenario()`, `startBossPhase()` and `advanceAfterVictory()` separate encounter creation from transition decisions. `StateUi.showBossPhase(phase, total)` announces the phase without putting combat rules into the UI.

The focused class diagram shows the run's references and factory dependencies. Multiplicities apply to active gameplay; old encounters are replaced during progression. The diagram omits unrelated UI, skill and clock classes.



Class diagram for scenario and boss progression

Editable PlantUML source.

`EnemyFactory.createRandomEnemy(random, scenarioNumber)` accepts a one-based number from 1 to 5. It chooses an existing enemy type and skill rotation, then sets health from the scenario table. Random names therefore retain variety without changing how many successful attacks the balance target needs. The overloads that create named or unrestricted random enemies remain usable by sample code and component tests.


`EnemyFactory.createBossPhase(phase)` accepts only phase 1 or 2 and returns a fresh enemy named for that phase. Phase 1 has 50 HP and a fixed 10-damage attack; phase 2 has 70 HP and a fixed 20-damage attack. Each phase uses a new `CombatEncounter` with the existing player and shared prompt factory. The first phase's dead enemy object is not revived or repurposed.

Transition ordering and phase boundaries

`CombatEncounter.submitTypingResult(...)` resolves the player's attack first. If enemy HP reaches zero, it completes victory and returns before executing an enemy turn. Otherwise the enemy attacks; player defeat is checked before the next turn is offered. `GamePlayState` inspects the completed encounter and advances only on victory. It does not infer success merely because a challenge ended.

The following sequence covers the boundary after a lethal attack against boss phase 1. The next encounter is created only after the first one has completed. Activation boxes show execution; dashed arrows show returns. The omitted health check is explained in the note. For readability, the diagram omits the selected

`difficulty` argument passed to the new `CombatEncounter`; the implementation passes it after the shared challenge factory.



Sequence diagram for moving from boss phase 1 to phase 2

Editable PlantUML source.

The same player reference carries remaining HP into the next encounter. Neither a regular scenario transition nor a boss phase transition heals the player or triggers an extra enemy attack. Damage is clamped at zero HP on the current target; any excess is discarded. For example, dealing 60 damage to a phase with 10 HP remaining defeats that phase, then phase 2 begins with its full 70 HP. A very strong attack cannot skip phase 2 or immediately win.

A timeout uses this same sequence. Nonempty captured input can deal damage, including a lethal attack. An empty or inaccurate input can deal zero damage and still consume a turn. If the enemy survives and its response brings player HP to zero, the state returns to the menu without starting a later scenario or phase.

Balance target and verification

The Hard-mode balance target is 50 WPM and at least 95% character accuracy, yielding at least 40 damage per attempt. The table counts attacks and possible retaliation at exactly 40 damage. Regular enemies retain their usual skill rotation; the highest first attack among those rotations is 20 damage. Enemies requiring one attack do not retaliate, and those requiring two only use their first attack.

Encounter	HP	Player attacks	Maximum retaliation damage
Scenario 1	30	1	0
Scenario 2	35	1	0
Scenario 3	50	2	20
Scenario 4	60	2	20
Scenario 5	70	2	20
Boss phase 1	50	2	10
Boss phase 2	70	2	20
Total		**12**	**90**

Thus a target-performance player finishes even the strongest possible regular enemy selection with at least 10 of the original 100 HP. Random enemy selection cannot invalidate this bound. It is a balance guarantee for the stated performance, not for arbitrary typing: an additional low-damage turn can expose a later, stronger enemy skill and lead to defeat. The HP progression introduces extra turns gradually, and the boss tests the same typing mechanics with a clear phase transition.

Validation, invariants and alternatives

The factory rejects invalid scenario numbers and boss phases with `IllegalArgumentException` and null random sources with `NullPointerException`. Generated enemies must have positive HP and usable skill loadouts. Combat entities reject invalid health, and the resolver clamps damage at zero HP. The encounter guards start/prepare/submit sequencing with exceptions and checks living-participant assumptions through assertions. State and combat diagnostics remain hidden at normal logging levels.

Progression must preserve these invariants: one live player per run; at most one active challenge; only a completed victorious encounter advances; regular indices stay in the five-scenario range; boss phase remains 0, 1 or 2; and no run victory occurs before phase 2 is defeated. Resetting all progression state on entry prevents a new run from inheriting the previous boss phase.

Choice	Rationale	Alternative considered
Keep progression in `GamePlayState`	The state already owns the run and its transitions	A separate campaign manager adds another coordinator for a short fixed sequence
Reuse `CombatEncounter` per phase	Existing turn ordering and death checks apply unchanged	A special boss encounter subclass duplicates combat logic and increases testing scope
Create a fresh enemy for each phase	Fresh HP and loadout have explicit phase boundaries	Mutating a dead enemy risks retaining death flags, pending skills or rotation indices
Discard overkill and prohibit transition attacks	Every phase has a predictable initial state	Carrying overflow or adding a transition attack makes timing and difficulty less transparent
Set HP by scenario and preserve random identities	Progression is reproducible while encounters remain varied	Unrestricted random HP makes some runs substantially harder at equal typing performance

Defensive programming and diagnostics

Assertions expose internal programming errors during development; public validation uses exceptions and remains active when assertions are disabled. Gradle enables assertions for `run` and `test`, and the gameplay launchers pass `-ea`. Direct IntelliJ Application configurations should add `-ea` in **VM options**. See the README setup steps.

Diagnostics use `java.util.logging`. Combat events and state transitions use `FINE`, hidden at the default level. Terminal initialization and input failures use warning or severe levels. This gives maintainers failure context without filling the typing area with routine debug messages.

Product scope and requirements

The target users are players who want English typing practice through short combat encounters. Keyboard Warrior makes speed and accuracy visible through damage and provides a complete run with regular progression and a final boss.

Feature	As a player, I want to ...	So that ...
Typing feedback	receive character accuracy and WPM feedback	one local typo has a proportional accuracy cost
Typing damage	deal damage from speed and accuracy across all skills	I can understand how my typing affects combat
Timed input	retain my current input when time expires	unfinished typing still contributes to my attempt

Feature	As a player, I want to ...	So that ...
Scenario progression	face progressively tougher regular scenarios	the run builds up difficulty predictably
Final boss	fight a final boss with two phases	the run has a clear final challenge before victory
Difficulty	choose Easy, Normal, Hard or Coder	health, damage and typing allowances suit my ability
Seeds	enter a seed when starting a run	I can repeat random choices with the same gameplay sequence
Continue	resume the last stable turn after restarting	remaining health, progression and future random choices are retained
Records	review my latest ten attempts in chronological order	I can compare recent typing performance
Leaderboard	retain my best attempt across runs and restarts	I have a lasting score to improve on

Non-functional requirements:

- Build, run and test with Java 25.
- Return deterministic metrics and damage for the same texts and supplied times.
- Keep evaluation independent of terminal input, timing and scenario progression.
- Retain immutable results and reject invalid integration data before changing combat state.
- Keep gameplay usable in a supported terminal while countdown updates preserve input.
- Start from one standalone JAR on Windows, macOS and Linux, with plain input/output when no live terminal is available.

Glossary:

- **Gross WPM**: Five normalized submitted UTF-16 code units count as one word, including incorrect input.
- **Character accuracy**: One minus normalized character edit distance, expressed as a percentage.
- **Edit distance**: Minimum count of character insertions, deletions and substitutions.
- **Overkill**: Damage beyond the current target's remaining HP; discarded at encounter boundaries.
- **Phase**: One boss enemy configuration with its own HP and attack, resolved as one combat encounter.

Testing

Automated checks

Run `./gradlew check` on macOS/Linux or `.\gradlew.bat check` in Windows PowerShell with Java 25. This builds the executable JAR, runs JUnit (including packaged-JAR smoke tests) and runs Checkstyle. Tests live under `src/test/java/seedu/keyboardwarrior`.

Packaged-JAR smoke tests start Java 25 subprocesses in temporary working folders with redirected input/output. They verify that the actual release artifact displays the menu, processes commands and closes cleanly on `exit` or EOF without the unsupported-console shutdown or native-access warning. This covers application startup, which direct UI-component tests do not exercise.

The relevant regression checks cover character substitution/insertion/deletion, normalization, capitalization and punctuation, empty input, invalid values and immutable diagnostic lists. Formatter tests check four summary metrics and retained detailed word reports without a timing penalty line. Damage tests check the fourth-power formula, rounding, skill independence, empty input and unchanged enemy base attacks. Factory and gameplay tests cover scenario HP, both boss loadouts, HP carryover, phase boundaries, defeat and restart. Clock and terminal tests cover countdown output and captured unfinished input. Simulated terminal tests select JLine's `exec` provider for consistent stream-based input/output on Windows, macOS and Linux.

Storage tests verify both file contents and loaded records, retention after reopening, and invalid metric rejection. State integration tests check that starting and finishing a run retain the same history store. Enemy lookup is also tested under a Turkish default locale so case normalization cannot depend on the operating system's language.

Records and leaderboard regressions use stores under `@TempDir`, so they do not alter the player's files:

Test class	Coverage
`storage.SaveStoreTest`	Latest-ten chronological retention, reopening, invalid metrics and unusable storage paths; all-time best survives rotation and is replaced by a faster attempt; legacy history migrates before its best record is discarded
`storage.LeaderboardStoreTest`	Missing file, first zero score, higher WPM and accuracy tie-breaks; lower scores and exact ties preserve file contents and modification time; malformed scores are reported and left unchanged
`state.MainMenuStateTest`	Records and leaderboard results, empty data and loading errors; leaderboard text and numeric commands; one best entry after history changes; full menu redisplayed after results or errors and subsequent commands remain usable
`state.GamePlayStateTest`	The returned menu reads the same history store after a run, and combat continues when saving fails

In particular, `highScore_rotatedHistory_retainsBestUntilHigherAttempt` saves a best attempt, then twelve slower attempts through reopened stores, and verifies that a faster attempt finally replaces it.

`highScore_existingHistory_preservesBestBeforeFirstRotation` checks migration from a full legacy history and verifies that the persisted best remains readable even when the history file is subsequently absent.

Seed and save regressions cover the continuation contract:

- `seed.RunRandomTest` compares draws with Java `Random`, including rejection sampling, and checks restoration without replaying earlier draws.
- `storage.GameSaveStoreTest` checks random-state and passage-history round trips, legacy saves and malformed fields, as well as combat fields and safe replacement.
- `save_resumeAtEveryScenarioAndBossPhase_matchesUninterruptedSeededRun` compares resumed and uninterrupted choices at every encounter boundary, including Encryption passages.
- `save_resume_restoresHealthDamageAndNextEnemyAttackWithoutReplayingATurn` checks a quit during typing retains the stable turn and that resuming preserves HP and the next enemy attack.
- `handleInput_sameSeed_repeatsRunAndRetainsHistory` checks replay through the menu without clearing typing history.

The progression regressions in `GamePlayStateTest` include:

- `normalPerformance_eachRepeatedEnemyType_survivesFiveScenariosAndBothBossPhases` checks the balance target across each regular enemy type.
- `bossPhaseTransition_preservesPlayerHealthAndDiscardsOverkillWithoutRetaliation` checks the phase boundary.
- `bossPhaseOne_playerDefeat_returnsToMenuWithoutStartingPhaseTwo` and `bossPhaseTwo_playerDefeat_returnsToMenuWithoutVictory` check defeat in either phase.
- `update_liveCountdown_scoresUnsubmittedAnswerAndPreservesTimerOrder` checks unfinished input and countdown placement.

Manual gameplay acceptance tests

For the live-countdown checks, use a supported terminal with Java 25 and the release JAR. The optional `sh ./run-game.sh` or `.\run-game.bat` launchers are alternatives for a source checkout.

Test	Steps	Expected result
Standalone JAR launch	Run `java -jar KeyboardWarrior.jar` with only the JAR and Java 25 available	Menu appears without requiring Gradle or a source launcher
Redirected launch	Launch the JAR with piped `exit` input, then with empty input	Plain-text menu appears and both runs exit cleanly without terminal setup warnings
Plain-mode late input	In an IDE Run console, start a challenge, wait past its displayed allowance and submit a partial passage with Enter	Passage remains visible while waiting; submitted text is scored using actual elapsed time; no empty turn is submitted before Enter

Test	Steps	Expected result
Countdown and skill allowance	Start a run; choose each skill across several passages	Timer stays above the passage and updates while typing; ordinary skills use length-based allowances with minimums, while Encryption uses a fixed 60-second base, all scaled by game difficulty
Early submission	Submit a partly correct passage before expiry	Four metrics and damage appear; no wrong-word list; surviving enemy retaliates once
Timeout capture	Type part of a passage, correct a character, then let time expire without Enter	Final current input is scored; nonempty text has nonzero WPM; no separate late penalty; next input is clear
Empty timeout	Enter no text before expiry	Zero WPM, accuracy and damage; a surviving enemy takes its turn
Regular progression	Defeat enemies through scenarios 1 to 5	Enemy HP follows 30, 35, 50, 60, 70; same player HP carries; scenario 5 starts boss phase 1
Boss boundary and overkill	Defeat phase 1 with damage exceeding its remaining HP	Phase 2 starts at 70 HP; player HP is unchanged by transition; no extra boss attack; no run victory yet
Final victory	Defeat boss phase 2	Run victory appears and returns to menu
Phase-boundary defeat	Reach phase 2 with low HP, then make a nonlethal or empty attempt	Boss response can defeat player; no later phase or victory is announced
Restart and exit	Start after victory/defeat; try `exit` during a prompt	New run begins at scenario 1 with the selected mode's starting HP; exit ends the game cleanly
Game difficulty	Choose each mode by number or name, then Start	HP is 400/200/100/80; Encryption countdown is 240/120/60/48 seconds; selection persists after a run
Seed replay	Start with a chosen numeric or text seed; record enemies and passages, then restart with the same seed, difficulty and sequence of skills and turns	The same random choices recur; a blank seed instead generates and displays a fresh seed
Continue a current save	Complete a turn, note both HP values, exit, restart from the same folder and enter `5` or `continue`	Saved difficulty, encounter, HP, attack rotation and future random sequence are restored without an extra enemy turn

Test	Steps	Expected result
Interrupted passage	Select a skill, type without submitting, exit, then Continue and choose the same skill	Previous stable turn is restored with the same passage and a fresh timer; unfinished input is not restored
Run completion and save slot	Win or lose, then choose Continue	No active run remains; Records and Leaderboard remain available
History and restart	Complete an attempt, return to the menu, enter `2` or `records`, then restart from the same folder	Saved WPM and accuracy remain visible; at most the latest ten attempts appear, oldest first; the full menu follows the records
Persistent leaderboard	Record a best attempt, then at least eleven lower-WPM attempts; restart from the same folder and enter `6` or `leaderboard`	Exactly one best attempt is shown even though it has left Records; the full menu follows the result
Improved best	Beat the stored best WPM, return to the menu and view Leaderboard; restart and view it again	The higher score replaces the old best and persists; exact ties and lower scores do not replace it
Menu after empty results	Launch in a fresh temporary working folder, choose a nondefault difficulty, then view Records and Leaderboard	Each empty message is followed by all six menu options and the selected difficulty; Start remains available
Menu after loading errors	In an isolated test folder, use malformed history for Records and malformed high-score data for Leaderboard	The appropriate loading error appears, followed by the full menu; malformed files remain unchanged

For a balance check, select **Hard** and sustain at least 50 WPM and 95% character accuracy on each attempt. Confirm at least 40 damage per attack, at most two attacks per regular enemy or boss phase, and at least 10 HP remaining at victory. Use deterministic automated tests for the strongest regular enemy rotations; random manual runs demonstrate the flow but cannot establish the worst-case bound by themselves.

Manual evaluator checks

Compile with the Gradle `classes` task, then start Java 25's JShell from the repository folder:

```
jshell --class-path build/classes/java/main
```

Enter the following commands in JShell. These are interactive statements, not a standalone Java source file:

```
import seedu.keyboardwarrior.typing.TypingEvaluator;
import seedu.keyboardwarrior.typing.TypingResultFormatter;
var result = TypingEvaluator.evaluateTyping("Strike the goblin", "Strike teh goblin", 6.0, 10.0);
System.out.print(TypingResultFormatter.formatTypingResult(result));
```

Expected: 34.00 WPM, 88.24% accuracy, elapsed 6.00 and required 10.00 seconds. The detailed formatter still identifies word 2 as expected `the`, typed `teh`. Its positional word diagnostic does not set the character

score. The player damage formula yields 20 for this result on Hard (multiplier 1). The damage column below also assumes Hard; metrics themselves are independent of game difficulty.

Typed text (same expected text, six seconds)	WPM	Character accuracy	Player damage
`Strike the goblin`	34.00	100.00%	34
`Strike teh goblin`	34.00	88.24%	20
`Strike the`	20.00	58.82%	2
`Strike the goblin now`	42.00	80.95%	18
Empty string	0.00	0.00%	0

Changing only required seconds to `5.0` makes `isTimeLimitExceeded()` true and leaves the metrics and damage unchanged. Setting required seconds to `6.0` is on time because the comparison is strict. Zero, negative, NaN and infinite time values should throw `IllegalArgumentException`; null text should throw `NullPointerException`. Exit JShell with `/exit`.

Maintaining the documentation

The diagrams are ordinary SVG images so GitHub and GitHub Pages display them without Mermaid support or a server-side renderer. Each image has a neighboring `.puml` source for editing with PlantUML. The checked-in SVGs were laid out from those sources; keep each source and rendered image aligned when changing the design. Diagram maintenance notes describe their scope.

When gameplay or storage behavior changes, update the corresponding guide sections, examples and testing instructions. Regenerate the PDF copies after updating the Markdown guides so the online and printable versions describe the same product.