

Standards

Standards MX

Message Reference Guide

BankToCustomerDebitCreditNotificationV08 (camt.054.001.08)

This publication includes information exported from the MyStandards web platform.

For the official documentation of the messages included in this publication, see the relevant Standards MX Message Reference Guides available on swift.com > Support > Documentation

Table of Contents

1	MX camt.054.001.08 BankToCustomerDebitCreditNotificationV08	3
1.1	MessageDefinition Functionality	3
1.2	Structure	4
1.3	Constraints	5
1.4	Message Building Blocks	10
2	Message Items Types	34
2.1	MessageComponents	34
2.2	Message Datatypes	240
	Legal Notices	313

1 **MX camt.054.001.08**

BankToCustomerDebitCreditNotificationV08

1.1 **MessageDefinition Functionality**

Scope

The BankToCustomerDebitCreditNotification message is sent by the account servicer to an account owner or to a party authorised by the account owner to receive the message. It can be used to inform the account owner, or authorised party, of single or multiple debit and/or credit entries reported to the account.

Usage

The BankToCustomerDebitCreditNotification message can contain reports for more than one account. It provides information for cash management and/or reconciliation.

The BankToCustomerDebitCreditNotification message can be used to:

- report pending and booked items;
- notify one or more debit entries;
- notify one or more credit entries;
- notify a combination of debit and credit entries.

It can include underlying details of transactions that have been included in the entry.

It is possible that the receiver of the message is not the account owner, but a party entitled by the account owner to receive the account information (also known as recipient).

It does not contain balance information.

Outline

The BankToCustomerDebitCreditNotificationV08 MessageDefinition is composed of 3 MessageBuildingBlocks:

A. GroupHeader

Common information for the message.

B. Notification

Notifies debit and credit entries for the account.

C. SupplementaryData

Additional information that cannot be captured in the structured elements and/or any other specific block.

1.2 Structure

Index	Or	MessageElement/BuildingBlock<XML Tag>	Mult.	Type	Constr. No.	Page
		<i>Message root</i> <Document> <BkToCstmrDbtCdtNtfctn>	[1..1]		✓C15, C19	
		GroupHeader <GrpHdr>	[1..1]	±		10
		Notification <Ntfctn>	[1..*]			10
		Identification <Id>	[1..1]	Text		12
		NotificationPagination <NtfctnPgntn>	[0..1]	±		12
		ElectronicSequenceNumber <ElctrncSeqNb>	[0..1]	Quantity		13
		ReportingSequence <RptgSeq>	[0..1]	±		13
		LegalSequenceNumber <LglSeqNb>	[0..1]	Quantity		13
		CreationDateTime <CreDtTm>	[0..1]	DateTime		13
		FromDate <FrToDt>	[0..1]	±		14
		CopyDuplicateIndicator <CpyDplctInd>	[0..1]	CodeSet		14
		ReportingSource <RptgSrc>	[0..1]	±		14
		Account <Acct>	[1..1]	±		14
		RelatedAccount <RltdAcct>	[0..1]	±		15
		Interest <Intrst>	[0..*]			15
		Type <Tp>	[0..1]			16
	{Or	Code <Cd>	[1..1]	CodeSet		16
	Or}	Proprietary <Prtry>	[1..1]	Text		16
		Rate <Rate>	[0..*]			17
		Type <Tp>	[1..1]	±		17
		ValidityRange <VldtyRg>	[0..1]	±		17
		FromDate <FrToDt>	[0..1]	±		17
		Reason <Rsn>	[0..1]	Text		18
		Tax <Tax>	[0..1]			18
		Identification <Id>	[0..1]	Text		18
		Rate <Rate>	[0..1]	Rate		18
		Amount <Amt>	[0..1]	Amount	✓C2, ✓C6	18
		TransactionsSummary <TxSummry>	[0..1]	±		19
		Entry <Ntry>	[0..*]		C17	20

Index	Or	MessageElement/BuildingBlock<XML Tag>	Mult.	Type	Constr. No.	Page
		EntryReference <NtryRef>	[0..1]	Text		21
		Amount <Amt>	[1..1]	Amount	✓C2, ✓C6	22
		CreditDebitIndicator <CdtDbtInd>	[1..1]	CodeSet		22
		ReversalIndicator <RvslInd>	[0..1]	Indicator		22
		Status <Sts>	[1..1]	±		23
		BookingDate <BookgDt>	[0..1]	±		23
		ValueDate <ValDt>	[0..1]	±		23
		AccountServicerReference <AcctSvcrRef>	[0..1]	Text		24
		Availability <Avlbtty>	[0..*]	±		24
		BankTransactionCode <BkTxCd>	[1..1]	±	✓C10, C11	24
		CommissionWaiverIndicator <ComssnWvrlInd>	[0..1]	Indicator		25
		AdditionalInformationIndicator <AddtlInfInd>	[0..1]			25
		MessageNameIdentification <MsgNmId>	[0..1]	Text		26
		MessageIdentification <MsgId>	[0..1]	Text		26
		AmountDetails <AmtDtls>	[0..1]	±		26
		Charges <Chrgs>	[0..1]	±		28
		TechnicalInputChannel <TechInptChanI>	[0..1]			28
	{Or	Code <Cd>	[1..1]	CodeSet		29
	Or}	Proprietary <Prtry>	[1..1]	Text		29
		Interest <Intrst>	[0..1]	±		29
		CardTransaction <CardTx>	[0..1]	±		30
		EntryDetails <NtryDtls>	[0..*]	±		32
		AdditionalEntryInformation <AddtlNtryInf>	[0..1]	Text		32
		AdditionalNotificationInformation <AddtlNtfctnInf>	[0..1]	Text		33
		SupplementaryData <SplmtryData>	[0..*]	±	C20	33

1.3 Constraints

C1 ActiveCurrency ✓

(Rule)

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered

with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00005
- *Error Text:* Invalid currency code

C2 ActiveOrHistoricCurrency ✓

(Rule)

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

C3 AnyBIC ✓

(Rule)

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consists of eight (8) or eleven (11) contiguous characters. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

C4 BICFI ✓

(Rule)

Valid BICs for financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consist of eight (8) or eleven (11) contiguous characters. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid FI BIC.

C5 Country ✓

(Rule)

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code). (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

C6 CurrencyAmount ✓

(Rule)

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

C7 CurrencyAmount ✓

(Rule)

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

C8 DescriptionPresenceRule ✓

(Rule)

If Description is not present then either ISIN or at least one occurrence of OtherIdentification must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00192
- *Error Text:* At least one identification must be present.

C9 DescriptionUsageRule

(Rule)

Description must be used alone as the last resort.

C10 DomainOrProprietaryRule ✓

(Rule)

Either Proprietary or Domain or both must be present. (CrossElementSimpleRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00104
- *Error Text:* Invalid message content for bank transaction code.

C11 FamilyAndSubFamilyRule

(Rule)

If a specific (non-generic) Family code is not present, then a specific (non-generic) SubFamily code is not allowed.

C12 IBAN ✓

(Rule)

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00003
- *Error Text:* Invalid IBAN format or invalid check digits.

C13 ISINGuideline

(Rule)

When an ISIN code exists, it is strongly recommended that the ISIN be used.

C14 ISINPresenceRule ✓

(Rule)

If ISIN is not present then either Description or at least one occurrence of OtherIdentification must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00194
- *Error Text:* At least one identification must be present.

C15 MessageOrNotificationPaginationRule ✓

(Rule)

MessagePagination may be present or NotificationPagination may be present, but not both. (CrossElementSimpleRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00263
- *Error Text:* Pagination may only be present at message or notification level.

This constraint is defined at the MessageDefinition level.

C16 OtherIdentificationPresenceRule ✓

(Rule)

If OtherIdentification is not present then either ISIN or Description must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00193
- *Error Text:* At least one identification must be present.

C17 ReferenceGuideline

(Guideline)

At least one reference should be present to identify the underlying transaction(s).

C18 ReturnReasonRule ✓

(Rule)

If Reason/Code is equal to NARR, then AdditionalInformation must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00077
- *Error Text:* Invalid message content for additional return reason.

C19 SupplementaryDataRule

(Rule)

The SupplementaryData building block at message level must not be used to provide additional information about a transaction. The SupplementaryData element at transaction level should be used for that purpose.

This constraint is defined at the MessageDefinition level.

C20 SupplementaryDataRule

(Rule)

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

1.4 Message Building Blocks

This chapter describes the MessageBuildingBlocks of this MessageDefinition.

1.4.1 GroupHeader <GrpHdr>

Presence: [1..1]

Definition: Common information for the message.

GroupHeader <GrpHdr> contains the following elements (see [GroupHeader81](#) on page 178 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		MessageIdentification <MsgId>	[1..1]	Text		178
		CreationDateTime <CreDtTm>	[1..1]	DateTime		178
		MessageRecipient <MsgRcpt>	[0..1]	±		178
		MessagePagination <MsgPgntn>	[0..1]	±		179
		OriginalBusinessQuery <OrgnlBizQry>	[0..1]	±		179
		AdditionalInformation <AddtlInf>	[0..1]	Text		179

1.4.2 Notification <Ntfctn>

Presence: [1..*]

Definition: Notifies debit and credit entries for the account.

Notification <Ntfctn> contains the following **AccountNotification17** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		12
		NotificationPagination <NtfctnPgntr>	[0..1]	±		12
		ElectronicSequenceNumber <ElctrncSeqNb>	[0..1]	Quantity		13
		ReportingSequence <RptgSeq>	[0..1]	±		13
		LegalSequenceNumber <LglSeqNb>	[0..1]	Quantity		13
		CreationDateTime <CreDtTm>	[0..1]	DateTime		13
		FromToDate <FrToDt>	[0..1]	±		14
		CopyDuplicateIndicator <CpyDplctInd>	[0..1]	CodeSet		14
		ReportingSource <RptgSrc>	[0..1]	±		14
		Account <Acct>	[1..1]	±		14
		RelatedAccount <RltdAcct>	[0..1]	±		15
		Interest <Intrst>	[0..*]			15
		Type <Tp>	[0..1]			16
	{Or	Code <Cd>	[1..1]	CodeSet		16
	Or}	Proprietary <Prtry>	[1..1]	Text		16
		Rate <Rate>	[0..*]			17
		Type <Tp>	[1..1]	±		17
		ValidityRange <VldtyRg>	[0..1]	±		17
		FromToDate <FrToDt>	[0..1]	±		17
		Reason <Rsn>	[0..1]	Text		18
		Tax <Tax>	[0..1]			18
		Identification <Id>	[0..1]	Text		18
		Rate <Rate>	[0..1]	Rate		18
		Amount <Amt>	[0..1]	Amount	✓C2, ✓C6	18
		TransactionsSummary <Txsumry>	[0..1]	±		19
		Entry <Ntry>	[0..*]		C17	20
		EntryReference <NtryRef>	[0..1]	Text		21
		Amount <Amt>	[1..1]	Amount	✓C2, ✓C6	22
		CreditDebitIndicator <CdtDbtInd>	[1..1]	CodeSet		22
		ReversalIndicator <RvslInd>	[0..1]	Indicator		22

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Status <Sts>	[1..1]	±		23
		BookingDate <BookgDt>	[0..1]	±		23
		ValueDate <ValDt>	[0..1]	±		23
		AccountServicerReference <AcctSvcrRef>	[0..1]	Text		24
		Availability <Avlbt>	[0..*]	±		24
		BankTransactionCode <BkTxCd>	[1..1]	±	✓C10, C11	24
		CommissionWaiverIndicator <ComssnWvrInd>	[0..1]	Indicator		25
		AdditionalInformationIndicator <AddtlInfInd>	[0..1]			25
		MessageNameIdentification <MsgNmId>	[0..1]	Text		26
		MessageIdentification <MsgId>	[0..1]	Text		26
		AmountDetails <AmtDtls>	[0..1]	±		26
		Charges <Chrgs>	[0..1]	±		28
		TechnicalInputChannel <TechInptChanI>	[0..1]			28
	{Or	Code <Cd>	[1..1]	CodeSet		29
	Or}	Proprietary <Prtry>	[1..1]	Text		29
		Interest <Intrst>	[0..1]	±		29
		CardTransaction <CardTx>	[0..1]	±		30
		EntryDetails <NtryDtls>	[0..*]	±		32
		AdditionalEntryInformation <AddtlNtryInf>	[0..1]	Text		32
		AdditionalNotificationInformation <AddtlNtfctnInf>	[0..1]	Text		33

1.4.2.1 Identification <Id>

Presence: [1..1]

Definition: Unique identification, as assigned by the account servicer, to unambiguously identify the account notification.

Datatype: Max35Text on page 310

1.4.2.2 NotificationPagination <NtfctnPgntn>

Presence: [0..1]

Definition: Provides details on the page number of the notification.

Usage: The pagination of the notification is only allowed when agreed between the parties.

NotificationPagination <NtfctnPgntn> contains the following elements (see [Pagination1](#) on page 167 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PageNumber <PgNb>	[1..1]	Text		167
		LastPageIndicator <LastPgInd>	[1..1]	Indicator		167

1.4.2.3 ElectronicSequenceNumber <ElctrncSeqNb>

Presence: [0..1]

Definition: Sequential number of the notification, as assigned by the account servicer.

Usage: The sequential number is increased incrementally for each notification sent electronically.

Datatype: [Number on page 307](#)

1.4.2.4 ReportingSequence <RptgSeq>

Presence: [0..1]

Definition: Specifies the range of identification sequence numbers, as provided in the request.

ReportingSequence <RptgSeq> contains one of the following elements (see [SequenceRange1Choice](#) on page 165 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	FromSequence <FrSeq>	[1..1]	Text		166
	Or	ToSequence <ToSeq>	[1..1]	Text		166
	Or	FromToSequence <FrToSeq>	[1..*]			166
		FromSequence <FrSeq>	[1..1]	Text		166
		ToSequence <ToSeq>	[1..1]	Text		166
	Or	EqualSequence <EQSeq>	[1..*]	Text		167
	Or}	NotEqualSequence <NEQSeq>	[1..*]	Text		167

1.4.2.5 LegalSequenceNumber <LglSeqNb>

Presence: [0..1]

Definition: Legal sequential number of the notification, as assigned by the account servicer. It is increased incrementally for each notification sent.

Datatype: [Number on page 307](#)

1.4.2.6 CreationDateTime <CreDtTm>

Presence: [0..1]

Definition: Date and time at which the notification was created.

Datatype: [ISODatetime on page 303](#)

1.4.2.7 FromToDate <FrToDt>

Presence: [0..1]

Definition: Range of time between a start date and an end date for which the account notification is issued.

FromToDate <FrToDt> contains the following elements (see [DateTimePeriod1](#) on page 146 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FromDateTime <FrDtTm>	[1..1]	DateTime		146
		ToDateTime <ToDtTm>	[1..1]	DateTime		146

1.4.2.8 CopyDuplicateIndicator <CpyDplctInd>

Presence: [0..1]

Definition: Indicates whether the document is a copy, a duplicate, or a duplicate of a copy.

Datatype: [CopyDuplicate1Code](#) on page 258

CodeName	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

1.4.2.9 ReportingSource <RptgSrc>

Presence: [0..1]

Definition: Specifies the application used to generate the reporting.

ReportingSource <RptgSrc> contains one of the following elements (see [ReportingSource1Choice](#) on page 167 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		167
	Or}	Proprietary <Prtry>	[1..1]	Text		168

1.4.2.10 Account <Acct>

Presence: [1..1]

Definition: Unambiguous identification of the account to which credit and debit entries are made.

Account <Acct> contains the following elements (see [CashAccount39](#) on page 35 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		36
		Type <Tp>	[0..1]	±		36
		Currency <Ccy>	[0..1]	CodeSet		36
		Name <Nm>	[0..1]	Text		36
		Proxy <Prxy>	[0..1]	±		36
		Owner <Ownr>	[0..1]	±		37
		Servicer <Svcr>	[0..1]	±		37

1.4.2.11 RelatedAccount <RltdAcct>

Presence: [0..1]

Definition: Identifies the parent account of the account for which the notification has been issued.

RelatedAccount <RltdAcct> contains the following elements (see [CashAccount38](#) on page 34 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		34
		Type <Tp>	[0..1]	±		34
		Currency <Ccy>	[0..1]	CodeSet		34
		Name <Nm>	[0..1]	Text		35
		Proxy <Prxy>	[0..1]	±		35

1.4.2.12 Interest <Intrst>

Presence: [0..*]

Definition: Provides general interest information that applies to the account at a particular moment in time.

Interest <Intrst> contains the following **AccountInterest4** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			16
	{Or	Code <Cd>	[1..1]	CodeSet		16
	Or}	Proprietary <Prtry>	[1..1]	Text		16
		Rate <Rate>	[0..*]			17
		Type <Tp>	[1..1]	±		17
		ValidityRange <VldtyRg>	[0..1]	±		17
		FromDate <FrToDt>	[0..1]	±		17
		Reason <Rsn>	[0..1]	Text		18
		Tax <Tax>	[0..1]			18
		Identification <Id>	[0..1]	Text		18
		Rate <Rate>	[0..1]	Rate		18
		Amount <Amt>	[0..1]	Amount	✓C2, ✓C6	18

1.4.2.12.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of interest.

Type <Tp> contains one of the following **InterestType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		16
	Or}	Proprietary <Prtry>	[1..1]	Text		16

1.4.2.12.1.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the type of interest.

Datatype: InterestType1Code on page 280

CodeName	Name	Definition
INDY	IntraDay	During or within a business day.
OVN	OverNight	Period of time between the end of a business day and the start of the next business day (usually the day after).

1.4.2.12.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies the type of interest in uncoded form.

Datatype: [Max35Text](#) on page 310

1.4.2.12.2 Rate <Rate>

Presence: [0..*]

Definition: Set of elements used to qualify the interest rate.

Rate <Rate> contains the following **Rate4** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[1..1]	±		17
		ValidityRange <VldtyRg>	[0..1]	±		17

1.4.2.12.2.1 Type <Tp>

Presence: [1..1]

Definition: Specifies the type of interest rate.

Type <Tp> contains one of the following elements (see [RateType4Choice](#) on page 198 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Percentage <Pctg>	[1..1]	Rate		199
	Or}	Other <Othr>	[1..1]	Text		199

1.4.2.12.2.2 ValidityRange <VldtyRg>

Presence: [0..1]

Definition: An amount range where the interest rate is applicable.

ValidityRange <VldtyRg> contains the following elements (see [ActiveOrHistoricCurrencyAndAmountRange2](#) on page 55 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	±		55
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		56
		Currency <Ccy>	[1..1]	CodeSet		56

1.4.2.12.3 FromToDate <FrToDt>

Presence: [0..1]

Definition: Range of time between a start date and an end date for the calculation of the interest.

FromDate <FrToDt> contains the following elements (see [DateTimePeriod1](#) on page 146 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FromDateTime <FrDtTm>	[1..1]	DateTime		146
		ToDateTime <ToDtTm>	[1..1]	DateTime		146

1.4.2.12.4 Reason <Rsn>

Presence: [0..1]

Definition: Specifies the reason for the interest.

Datatype: [Max35Text](#) on page 310

1.4.2.12.5 Tax <Tax>

Presence: [0..1]

Definition: Provides details on the tax applied to charges.

Tax <Tax> contains the following **TaxCharges2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[0..1]	Text		18
		Rate <Rate>	[0..1]	Rate		18
		Amount <Amt>	[0..1]	Amount	✓C2, ✓C6	18

1.4.2.12.5.1 Identification <Id>

Presence: [0..1]

Definition: Unique reference to unambiguously identify the nature of the tax levied, such as Value Added Tax (VAT).

Datatype: [Max35Text](#) on page 310

1.4.2.12.5.2 Rate <Rate>

Presence: [0..1]

Definition: Rate used to calculate the tax.

Datatype: [PercentageRate](#) on page 307

1.4.2.12.5.3 Amount <Amt>

Presence: [0..1]

Definition: Amount of money resulting from the calculation of the tax.

Impacted by: ✓C2 [ActiveOrHistoricCurrency](#) ✓, ✓C6 [CurrencyAmount](#) ✓

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 242

Constraints

- **ActiveOrHistoricCurrency**

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

- **CurrencyAmount**

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

1.4.2.13 TransactionsSummary <TxSummary>

Presence: [0..1]

Definition: Provides summary information on entries.

TransactionsSummary <TxSummary> contains the following elements (see [TotalTransactions6](#) on page 168 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TotalEntries <TtlNtries>	[0..1]			168
		NumberOfEntries <NbOfNtries>	[0..1]	Text		169
		Sum <Sum>	[0..1]	Quantity		169
		TotalNetEntry <TtlNetNtry>	[0..1]	±		169
		TotalCreditEntries <TtlCdtNtries>	[0..1]	±		169
		TotalDebitEntries <TtlDbtNtries>	[0..1]	±		169
		TotalEntriesPerBankTransactionCode <TtlNtriesPerBkTxCd>	[0..*]			170
		NumberOfEntries <NbOfNtries>	[0..1]	Text		170
		Sum <Sum>	[0..1]	Quantity		170
		TotalNetEntry <TtlNetNtry>	[0..1]	±		170
		CreditEntries <CdtNtries>	[0..1]	±		171
		DebitEntries <DbtNtries>	[0..1]	±		171
		ForecastIndicator <FcstInd>	[0..1]	Indicator		171
		BankTransactionCode <BkTxCd>	[1..1]	±		171
		Availability <Avlbtty>	[0..*]	±		172
		Date <Dt>	[0..1]	±		172

1.4.2.14 Entry <Ntry>

Presence: [0..*]

Definition: Specifies an entry in the debit credit notification.

Usage: At least one reference must be provided to identify the entry and its underlying transaction(s).

Usage Rule: In case of a Payments R-transaction the creditor / debtor referenced of the original payment initiation messages is also used for reporting of the R-transaction. The original debtor/creditor in the reporting of R-Transactions is not inverted.

Following elements all defined in the TransactionDetails in RelatedParties or RelatedAgents are impacted by this usage rule:

Creditor, UltimateCreditor, CreditorAccount, CreditorAgent, Debtor, UltimateDebtor, DebtorAccount and DebtorAgent.

Impacted by: [C17 ReferenceGuideline](#)

Entry <Ntry> contains the following **ReportEntry10** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		EntryReference <NtryRef>	[0..1]	Text		21
		Amount <Amt>	[1..1]	Amount	✓C2, ✓C6	22
		CreditDebitIndicator <CdtDbtInd>	[1..1]	CodeSet		22
		ReversalIndicator <RvslInd>	[0..1]	Indicator		22
		Status <Sts>	[1..1]	±		23
		BookingDate <BookgDt>	[0..1]	±		23
		ValueDate <ValDt>	[0..1]	±		23
		AccountServicerReference <AcctSvcrRef>	[0..1]	Text		24
		Availability <Avlbtty>	[0..*]	±		24
		BankTransactionCode <BkTxCd>	[1..1]	±	✓C10, C11	24
		CommissionWaiverIndicator <ComssnWvrlInd>	[0..1]	Indicator		25
		AdditionalInformationIndicator <AddtlInfInd>	[0..1]			25
		MessageNameIdentification <MsgNmId>	[0..1]	Text		26
		MessageIdentification <MsgId>	[0..1]	Text		26
		AmountDetails <AmtDtls>	[0..1]	±		26
		Charges <Chrgs>	[0..1]	±		28
		TechnicalInputChannel <TechInptChanI>	[0..1]			28
	{Or	Code <Cd>	[1..1]	CodeSet		29
	Or}	Proprietary <Prtry>	[1..1]	Text		29
		Interest <Intrst>	[0..1]	±		29
		CardTransaction <CardTx>	[0..1]	±		30
		EntryDetails <NtryDtls>	[0..*]	±		32
		AdditionalEntryInformation <AddtlNtryInf>	[0..1]	Text		32

Constraints

- **ReferenceGuideline**

At least one reference should be present to identify the underlying transaction(s).

1.4.2.14.1 EntryReference <NtryRef>

Presence: [0..1]

Definition: Unique reference for the entry.

Datatype: [Max35Text on page 310](#)

1.4.2.14.2 Amount <Amt>*Presence:* [1..1]*Definition:* Amount of money in the cash entry.*Impacted by:* ✓ C2 ActiveOrHistoricCurrency ✓, ✓ C6 CurrencyAmount ✓*Datatype:* ActiveOrHistoricCurrencyAndAmount on page 242**Constraints**

- **ActiveOrHistoricCurrency**

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

- **CurrencyAmount**

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

1.4.2.14.3 CreditDebitIndicator <CdtDbtInd>*Presence:* [1..1]*Definition:* Indicates whether the entry is a credit or a debit entry.*Datatype:* CreditDebitCode on page 260

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

1.4.2.14.4 ReversalIndicator <RvsInd>*Presence:* [0..1]*Definition:* Indicates whether or not the entry is the result of a reversal.

Usage: This element should only be present if the entry is the result of a reversal.

If the CreditDebitIndicator is CRDT and ReversalIndicator is Yes, the original operation was a debit entry.

If the CreditDebitIndicator is DBIT and ReversalIndicator is Yes, the original operation was a credit entry.

Datatype: One of the following values must be used (see [TrueFalseIndicator](#) on page 306):

- *Meaning When True:* True
- *Meaning When False:* False

1.4.2.14.5 Status <Sts>

Presence: [1..1]

Definition: Status of an entry on the books of the account servicer.

Status <Sts> contains one of the following elements (see [EntryStatus1Choice](#) on page 226 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		227
	Or}	Proprietary <Prtry>	[1..1]	Text		227

1.4.2.14.6 BookingDate <BookgDt>

Presence: [0..1]

Definition: Date and time when an entry is posted to an account on the account servicer's books.

Usage: Booking date is the expected booking date, unless the status is booked, in which case it is the actual booking date.

BookingDate <BookgDt> contains one of the following elements (see [DateAndDateTime2Choice](#) on page 145 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Date <Dt>	[1..1]	Date		145
	Or}	DateTime <DtTm>	[1..1]	DateTime		145

1.4.2.14.7 ValueDate <ValDt>

Presence: [0..1]

Definition: Date and time at which assets become available to the account owner in case of a credit entry, or cease to be available to the account owner in case of a debit entry.

Usage: If entry status is pending and value date is present, then the value date refers to an expected/ requested value date.

For entries subject to availability/float and for which availability information is provided, the value date must not be used. In this case the availability component identifies the number of availability days.

ValueDate <ValDt> contains one of the following elements (see [DateAndDateTime2Choice](#) on page 145 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Date <Dt>	[1..1]	Date		145
	Or}	DateTime <DtTm>	[1..1]	DateTime		145

1.4.2.14.8 AccountServicerReference <AcctSvcrRef>

Presence: [0..1]

Definition: Unique reference as assigned by the account servicing institution to unambiguously identify the entry.

Datatype: [Max35Text](#) on page 310

1.4.2.14.9 Availability <Avlbt>

Presence: [0..*]

Definition: Indicates when the booked amount of money will become available, that is can be accessed and starts generating interest.

Usage: This type of information is used in the US and is linked to particular instruments such as cheques.

Example: When a cheque is deposited, it will be booked on the deposit day, but the amount of money will only be accessible as of the indicated availability day (according to national banking regulations).

Availability <Avlbt> contains the following elements (see [CashAvailability1](#) on page 139 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Date <Dt>	[1..1]			139
	{Or	NumberOfDays <NbOfDays>	[1..1]	Text		139
	Or}	ActualDate <ActlDt>	[1..1]	Date		139
		Amount <Amt>	[1..1]	Amount		139
		CreditDebitIndicator <CdtDbtInd>	[1..1]	CodeSet		140

1.4.2.14.10 BankTransactionCode <BkTxCd>

Presence: [1..1]

Definition: Set of elements used to fully identify the type of underlying transaction resulting in an entry.

Impacted by: ✓ [C10 DomainOrProprietaryRule](#) ✓, [C11 FamilyAndSubFamilyRule](#)

BankTransactionCode <BkTxCd> contains the following elements (see [BankTransactionCodeStructure4](#) on page 57 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Domain <Domn>	[0..1]	±		57
		Proprietary <Prtry>	[0..1]			58
		Code <Cd>	[1..1]	Text		58
		Issuer <Issr>	[0..1]	Text		58

Constraints

- **DomainOrProprietaryRule**

Either Proprietary or Domain or both must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00104
- *Error Text:* Invalid message content for bank transaction code.

- **FamilyAndSubFamilyRule**

If a specific (non-generic) Family code is not present, then a specific (non-generic) SubFamily code is not allowed.

1.4.2.14.11 CommissionWaiverIndicator <ComssnWvrInd>

Presence: [0..1]

Definition: Indicates whether the transaction is exempt from commission.

Datatype: One of the following values must be used (see [YesNoIndicator](#) on page 306):

- *Meaning When True:* Yes
- *Meaning When False:* No

1.4.2.14.12 AdditionalInformationIndicator <AddtlInfInd>

Presence: [0..1]

Definition: Indicates whether the underlying transaction details are provided through a separate message, as in the case of aggregate bookings.

AdditionalInformationIndicator <AddtlInfInd> contains the following **MessageIdentification2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		MessageNameIdentification <MsgNmId>	[0..1]	Text		26
		MessageIdentification <MsgId>	[0..1]	Text		26

1.4.2.14.12.1 MessageNameIdentification <MsgNmId>

Presence: [0..1]

Definition: Specifies the message name identifier of the message that will be used to provide additional details.

Datatype: Max35Text on page 310

1.4.2.14.12.2 MessageIdentification <MsgId>

Presence: [0..1]

Definition: Specifies the identification of the message that will be used to provide additional details.

Datatype: Max35Text on page 310

1.4.2.14.13 AmountDetails <AmtDtls>

Presence: [0..1]

Definition: Provides information on the original amount.

Usage: This component (on entry level) should be used when a total original batch or aggregate amount has to be provided. If required, the individual original amounts can be included in the same component on transaction details level.

AmountDetails <AmtDtls> contains the following elements (see [AmountAndCurrencyExchange3](#) on page 41 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		InstructedAmount <InstdAmt>	[0..1]			43
		Amount <Amt>	[1..1]	Amount		44
		CurrencyExchange <CcyXchg>	[0..1]			44
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		44
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		44
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		44
		ExchangeRate <XchgRate>	[1..1]	Rate		44
		ContractIdentification <CtrctId>	[0..1]	Text		45
		QuotationDate <QtnDt>	[0..1]	DateTime		45
		TransactionAmount <TxAmt>	[0..1]			45
		Amount <Amt>	[1..1]	Amount		45
		CurrencyExchange <CcyXchg>	[0..1]			45
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		46
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		46
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		46
		ExchangeRate <XchgRate>	[1..1]	Rate		46
		ContractIdentification <CtrctId>	[0..1]	Text		46
		QuotationDate <QtnDt>	[0..1]	DateTime		46
		CounterValueAmount <CntrValAmt>	[0..1]			47
		Amount <Amt>	[1..1]	Amount		47
		CurrencyExchange <CcyXchg>	[0..1]			47
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		48
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		48
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		48
		ExchangeRate <XchgRate>	[1..1]	Rate		48
		ContractIdentification <CtrctId>	[0..1]	Text		48
		QuotationDate <QtnDt>	[0..1]	DateTime		48
		AnnouncedPostingAmount <AnncdPstngAmt>	[0..1]			49
		Amount <Amt>	[1..1]	Amount		49
		CurrencyExchange <CcyXchg>	[0..1]			49

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		50
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		50
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		50
		ExchangeRate <XchgRate>	[1..1]	Rate		50
		ContractIdentification <CtrctId>	[0..1]	Text		50
		QuotationDate <QtnDt>	[0..1]	DateTime		50
		ProprietaryAmount <PrtryAmt>	[0..*]			51
		Type <Tp>	[1..1]	Text		51
		Amount <Amt>	[1..1]	Amount		51
		CurrencyExchange <CcyXchg>	[0..1]			51
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		52
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		52
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		52
		ExchangeRate <XchgRate>	[1..1]	Rate		52
		ContractIdentification <CtrctId>	[0..1]	Text		52
		QuotationDate <QtnDt>	[0..1]	DateTime		52

1.4.2.14.14 Charges <Chrgs>

Presence: [0..1]

Definition: Provides information on the charges, pre-advised or included in the entry amount.

Usage: This component is used on entry level in case of batch or aggregate bookings.

Charges <Chrgs> contains the following elements (see [Charges6 on page 143](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TotalChargesAndTaxAmount <TtlChrgsAndTaxAmt>	[0..1]	Amount		143
		Record <Rcrd>	[0..*]	±		143

1.4.2.14.15 TechnicalInputChannel <TechInptChanl>

Presence: [0..1]

Definition: Channel used to technically input the instruction related to the entry.

TechnicalInputChannel <TechInptChanI> contains one of the following **TechnicalInputChannel1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		29
	Or}	Proprietary <Prtry>	[1..1]	Text		29

1.4.2.14.15.1 Code <Cd>

Presence: [1..1]

Definition: Technical input channel, as published in an external technical input channel code list.

Datatype: [ExternalTechnicalInputChannel1Code on page 279](#)

1.4.2.14.15.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Technical channel used to input the instruction, in a proprietary form.

Datatype: [Max35Text on page 310](#)

1.4.2.14.16 Interest <Intrst>

Presence: [0..1]

Definition: Provides details of the interest amount included in the entry amount.

Usage: This component is used on entry level in the case of batch or aggregate bookings.

Interest <Intrst> contains the following elements (see [TransactionInterest4](#) on page 174 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TotalInterestAndTaxAmount <TtlIntrstAndTaxAmt>	[0..1]	Amount		174
		Record <Rcrd>	[0..*]			174
		Amount <Amt>	[1..1]	Amount		175
		CreditDebitIndicator <CdtDbtInd>	[1..1]	CodeSet		175
		Type <Tp>	[0..1]			175
	{Or	Code <Cd>	[1..1]	CodeSet		176
	Or}	Proprietary <Prtry>	[1..1]	Text		176
		Rate <Rate>	[0..1]			176
		Type <Tp>	[1..1]	±		176
		ValidityRange <VldtyRg>	[0..1]	±		177
		FromDate <FrToDt>	[0..1]	±		177
		Reason <Rsn>	[0..1]	Text		177
		Tax <Tax>	[0..1]			177
		Identification <Id>	[0..1]	Text		177
		Rate <Rate>	[0..1]	Rate		178
		Amount <Amt>	[0..1]	Amount		178

1.4.2.14.17 CardTransaction <CardTx>

Presence: [0..1]

Definition: Provides details of the card transaction included in the entry amount, when globalised by the account servicer.

CardTransaction <CardTx> contains the following elements (see [CardEntry4](#) on page 87 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Card <Card>	[0..1]			89
		PlainCardData <PlainCardData>	[0..1]			90
		PAN <PAN>	[1..1]	Text		91
		CardSequenceNumber <CardSeqNb>	[0..1]	Text		91
		EffectiveDate <FctvDt>	[0..1]	YearMonth		91
		ExpiryDate <XpryDt>	[1..1]	YearMonth		91
		ServiceCode <SvcCd>	[0..1]	Text		91
		TrackData <TrckData>	[0..*]			92
		TrackNumber <TrckNb>	[0..1]	Text		92
		TrackValue <TrckVal>	[1..1]	Text		92
		CardSecurityCode <CardSctyCd>	[0..1]			92
		CSCManagement <CSCMgmt>	[1..1]	CodeSet		92
		CSCValue <CSCVal>	[0..1]	Text		93
		CardCountryCode <CardCtryCd>	[0..1]	Text		93
		CardBrand <CardBrnd>	[0..1]	±		93
		AdditionalCardData <AddtlCardData>	[0..1]	Text		93
		POI <POI>	[0..1]			93
		Identification <Id>	[1..1]	±		94
		SystemName <SysNm>	[0..1]	Text		95
		GroupIdentification <Grpld>	[0..1]	Text		95
		Capabilities <Cpblties>	[0..1]			95
		CardReadingCapabilities <CardRdngCpblties>	[0..*]	CodeSet		95
		CardholderVerificationCapabilities <CrdhldrVrfctnCpblties>	[0..*]	CodeSet		96
		OnLineCapabilities <OnLineCpblties>	[0..1]	CodeSet		96
		DisplayCapabilities <DispCpblties>	[0..*]			97
		DisplayType <DispTp>	[1..1]	CodeSet		97
		NumberOfLines <NbOfLines>	[1..1]	Text		97
		LineWidth <LineWidth>	[1..1]	Text		97
		PrintLineWidth <PrtLineWidth>	[0..1]	Text		97

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Component <Cmpnt>	[0..*]			97
		POIComponentType <POICmpntTp>	[1..1]	CodeSet		98
		ManufacturerIdentification <ManfctrId>	[0..1]	Text		98
		Model <Mdl>	[0..1]	Text		98
		VersionNumber <VrsnNb>	[0..1]	Text		98
		SerialNumber <SrlNb>	[0..1]	Text		99
		ApprovalNumber <ApprvlNb>	[0..*]	Text		99
		AggregatedEntry <AggtdNtry>	[0..1]			99
		AdditionalService <AddtlSvc>	[0..1]	CodeSet		99
		TransactionCategory <TxCtgy>	[0..1]	CodeSet		100
		SaleReconciliationIdentification <SaleRcncltnId>	[0..1]	Text		100
		SequenceNumberRange <SeqNbRg>	[0..1]			100
		FirstTransaction <FrstTx>	[0..1]	Text		100
		LastTransaction <LastTx>	[0..1]	Text		100
		TransactionDateRange <TxDtRg>	[0..1]	±		101
		PrePaidAccount <PrePdAcct>	[0..1]	±		101

1.4.2.14.18 EntryDetails <NtryDtls>

Presence: [0..*]

Definition: Provides details on the entry.

EntryDetails <NtryDtls> contains the following elements (see [EntryDetails9](#) on page 102 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Batch <Btch>	[0..1]			102
		MessageIdentification <MsgId>	[0..1]	Text		103
		PaymentInformationIdentification <PmtInfId>	[0..1]	Text		103
		NumberOfTransactions <NbOfTx>	[0..1]	Text		103
		TotalAmount <TtlAmt>	[0..1]	Amount		103
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		103
		TransactionDetails <TxDtls>	[0..*]	±		103

1.4.2.14.19 AdditionalEntryInformation <AddtlNtryInf>

Presence: [0..1]

Definition: Further details of the entry.

Datatype: [Max500Text on page 310](#)

1.4.2.15 AdditionalNotificationInformation <AddtlNtfctnInf>

Presence: [0..1]

Definition: Further details of the account notification.

Datatype: [Max500Text on page 310](#)

1.4.3 SupplementaryData <SplmtryData>

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

Impacted by: [C20 SupplementaryDataRule](#)

SupplementaryData <SplmtryData> contains the following elements (see [SupplementaryData1 on page 172](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PlaceAndName <PlcAndNm>	[0..1]	Text		173
		Envelope <Envlp>	[1..1]	(External Schema)		173

Constraints

- **SupplementaryDataRule**

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

2 Message Items Types

2.1 MessageComponents

2.1.1 Account

2.1.1.1 CashAccount38

Definition: Provides the details to identify an account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		34
		Type <Tp>	[0..1]	±		34
		Currency <Ccy>	[0..1]	CodeSet		34
		Name <Nm>	[0..1]	Text		35
		Proxy <Prxy>	[0..1]	±		35

2.1.1.1.1 Identification <Id>

Presence: [1..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

Identification <Id> contains one of the following elements (see [AccountIdentification4Choice](#) on page 40 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	IBAN <IBAN>	[1..1]	IdentifierSet		41
	Or}	Other <Othr>	[1..1]	±		41

2.1.1.1.2 Type <Tp>

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

Type <Tp> contains one of the following elements (see [CashAccountType2Choice](#) on page 38 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		38
	Or}	Proprietary <Prtry>	[1..1]	Text		39

2.1.1.1.3 Currency <Ccy>

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: [ActiveOrHistoricCurrencyCode](#) on page 243

2.1.1.1.4 Name <Nm>

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: [Max70Text](#) on page 311

2.1.1.1.5 Proxy <Prxy>

Presence: [0..1]

Definition: Specifies an alternate assumed name for the identification of the account.

Proxy <Prxy> contains the following elements (see [ProxyAccountIdentification1](#) on page 37 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			38
	{Or	Code <Cd>	[1..1]	CodeSet		38
	Or}	Proprietary <Prtry>	[1..1]	Text		38
		Identification <Id>	[1..1]	Text		38

2.1.1.2 CashAccount39

Definition: Provides the details to identify an account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		36
		Type <Tp>	[0..1]	±		36
		Currency <Ccy>	[0..1]	CodeSet		36
		Name <Nm>	[0..1]	Text		36
		Proxy <Prxy>	[0..1]	±		36
		Owner <Ownr>	[0..1]	±		37
		Servicer <Svcr>	[0..1]	±		37

2.1.1.2.1 Identification <Id>

Presence: [1..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

Identification <Id> contains one of the following elements (see [AccountIdentification4Choice](#) on page 40 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	IBAN <IBAN>	[1..1]	IdentifierSet		41
	Or}	Other <Othr>	[1..1]	±		41

2.1.1.2.2 Type <Tp>

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

Type <Tp> contains one of the following elements (see [CashAccountType2Choice](#) on page 38 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		38
	Or}	Proprietary <Prtry>	[1..1]	Text		39

2.1.1.2.3 Currency <Ccy>

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Datatype: [ActiveOrHistoricCurrencyCode](#) on page 243

2.1.1.2.4 Name <Nm>

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: [Max70Text](#) on page 311

2.1.1.2.5 Proxy <Prxy>

Presence: [0..1]

Definition: Specifies an alternate assumed name for the identification of the account.

Proxy <Prxy> contains the following elements (see [ProxyAccountIdentification1](#) on page 37 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			38
	{Or	Code <Cd>	[1..1]	CodeSet		38
	Or}	Proprietary <Prtry>	[1..1]	Text		38
		Identification <Id>	[1..1]	Text		38

2.1.1.2.6 Owner <Ownr>

Presence: [0..1]

Definition: Party that legally owns the account.

Owner <Ownr> contains the following elements (see [PartyIdentification135](#) on page 184 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		185
		PostalAddress <PstlAdr>	[0..1]	±		185
		Identification <Id>	[0..1]	±		186
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		186
		ContactDetails <CtctDtls>	[0..1]	±		187

2.1.1.2.7 Servicer <Svcr>

Presence: [0..1]

Definition: Party that manages the account on behalf of the account owner, that is manages the registration and booking of entries on the account, calculates balances on the account and provides information about the account.

Servicer <Svcr> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 153 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		153
		BranchIdentification <BrnchId>	[0..1]	±		154

2.1.1.3 ProxyAccountIdentification1

Definition: Information related to a proxy identification of the account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			38
	{Or	Code <Cd>	[1..1]	CodeSet		38
	Or}	Proprietary <Prtry>	[1..1]	Text		38
		Identification <Id>	[1..1]	Text		38

2.1.1.3.1 Type <Tp>

Presence: [0..1]

Definition: Type of the proxy identification.

Type <Tp> contains one of the following **ProxyAccountType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		38
	Or}	Proprietary <Prtry>	[1..1]	Text		38

2.1.1.3.1.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: [ExternalProxyAccountType1Code on page 275](#)

2.1.1.3.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: [Max35Text on page 310](#)

2.1.1.3.2 Identification <Id>

Presence: [1..1]

Definition: Identification used to indicate the account identification under another specified name.

Datatype: [Max2048Text on page 309](#)

2.1.1.4 CashAccountType2Choice

Definition: Nature or use of the account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		38
	Or}	Proprietary <Prtry>	[1..1]	Text		39

2.1.1.4.1 Code <Cd>

Presence: [1..1]

Definition: Account type, in a coded form.

Datatype: [ExternalCashAccountType1Code](#) on page 267

2.1.1.4.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Nature or use of the account in a proprietary form.

Datatype: [Max35Text](#) on page 310

2.1.1.5 GenericAccountIdentification1

Definition: Information related to a generic account identification.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		39
		SchemeName <SchmeNm>	[0..1]			39
	{Or	Code <Cd>	[1..1]	CodeSet		39
	Or}	Proprietary <Prtry>	[1..1]	Text		39
		Issuer <Issr>	[0..1]	Text		40

2.1.1.5.1 Identification <Id>

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: [Max34Text](#) on page 309

2.1.1.5.2 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Name of the identification scheme.

SchemeName <SchmeNm> contains one of the following **AccountSchemeName1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		39
	Or}	Proprietary <Prtry>	[1..1]	Text		39

2.1.1.5.2.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: [ExternalAccountIdentification1Code](#) on page 263

2.1.1.5.2.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: [Max35Text on page 310](#)

2.1.1.5.3 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: [Max35Text on page 310](#)

2.1.2 Account Identification

2.1.2.1 SecuritiesAccount19

Definition: Account to or from which a securities entry is made.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		40
		Type <Tp>	[0..1]	±		40
		Name <Nm>	[0..1]	Text		40

2.1.2.1.1 Identification <Id>

Presence: [1..1]

Definition: Unambiguous identification for the account between the account owner and the account servicer.

Datatype: [Max35Text on page 310](#)

2.1.2.1.2 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of securities account.

Type <Tp> contains the following elements (see [GenericIdentification30 on page 158](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		158
		Issuer <Issr>	[1..1]	Text		158
		SchemeName <SchmeNm>	[0..1]	Text		158

2.1.2.1.3 Name <Nm>

Presence: [0..1]

Definition: Description of the account.

Datatype: [Max70Text on page 311](#)

2.1.2.2 AccountIdentification4Choice

Definition: Specifies the unique identification of an account as assigned by the account servicer.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	IBAN <IBAN>	[1..1]	IdentifierSet		41
	Or}	Other <Othr>	[1..1]	±		41

2.1.2.2.1 IBAN <IBAN>

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: [IBAN2007Identifier](#) on page 304

2.1.2.2.2 Other <Othr>

Presence: [1..1]

Definition: Unique identification of an account, as assigned by the account servicer, using an identification scheme.

Other <Othr> contains the following elements (see [GenericAccountIdentification1](#) on page 39 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		39
		SchemeName <SchmeNm>	[0..1]			39
	{Or	Code <Cd>	[1..1]	CodeSet		39
	Or}	Proprietary <Prtry>	[1..1]	Text		39
		Issuer <Issr>	[0..1]	Text		40

2.1.3 Amount

2.1.3.1 AmountAndCurrencyExchange3

Definition: Set of elements used to provide information on the original amount.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		InstructedAmount <InstdAmt>	[0..1]			43
		Amount <Amt>	[1..1]	Amount		44
		CurrencyExchange <CcyXchg>	[0..1]			44
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		44
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		44
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		44
		ExchangeRate <XchgRate>	[1..1]	Rate		44
		ContractIdentification <CtrctId>	[0..1]	Text		45
		QuotationDate <QtnDt>	[0..1]	DateTime		45
		TransactionAmount <TxAmt>	[0..1]			45
		Amount <Amt>	[1..1]	Amount		45
		CurrencyExchange <CcyXchg>	[0..1]			45
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		46
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		46
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		46
		ExchangeRate <XchgRate>	[1..1]	Rate		46
		ContractIdentification <CtrctId>	[0..1]	Text		46
		QuotationDate <QtnDt>	[0..1]	DateTime		46
		CounterValueAmount <CntrValAmt>	[0..1]			47
		Amount <Amt>	[1..1]	Amount		47
		CurrencyExchange <CcyXchg>	[0..1]			47
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		48
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		48
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		48
		ExchangeRate <XchgRate>	[1..1]	Rate		48
		ContractIdentification <CtrctId>	[0..1]	Text		48
		QuotationDate <QtnDt>	[0..1]	DateTime		48
		AnnouncedPostingAmount <AnncdPstngAmt>	[0..1]			49
		Amount <Amt>	[1..1]	Amount		49
		CurrencyExchange <CcyXchg>	[0..1]			49
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		50

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		50
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		50
		ExchangeRate <XchgRate>	[1..1]	Rate		50
		ContractIdentification <CtrctId>	[0..1]	Text		50
		QuotationDate <QtnDt>	[0..1]	DateTime		50
		ProprietaryAmount <PrtryAmt>	[0..*]			51
		Type <Tp>	[1..1]	Text		51
		Amount <Amt>	[1..1]	Amount		51
		CurrencyExchange <CcyXchg>	[0..1]			51
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		52
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		52
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		52
		ExchangeRate <XchgRate>	[1..1]	Rate		52
		ContractIdentification <CtrctId>	[0..1]	Text		52
		QuotationDate <QtnDt>	[0..1]	DateTime		52

2.1.3.1.1 InstructedAmount <InstdAmt>

Presence: [0..1]

Definition: Identifies the amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party and provides currency exchange information in case the instructed amount and/or currency is/are different from the entry amount and/or currency.

InstructedAmount <InstdAmt> contains the following **AmountAndCurrencyExchangeDetails3** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Amount		44
		CurrencyExchange <CcyXchg>	[0..1]			44
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		44
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		44
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		44
		ExchangeRate <XchgRate>	[1..1]	Rate		44
		ContractIdentification <CtrctId>	[0..1]	Text		45
		QuotationDate <QtnDt>	[0..1]	DateTime		45

2.1.3.1.1.1 Amount <Amt>*Presence:* [1..1]*Definition:* Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.*Datatype:* [ActiveOrHistoricCurrencyAndAmount on page 242](#)**2.1.3.1.1.2 CurrencyExchange <CcyXchg>***Presence:* [0..1]*Definition:* Set of elements used to provide details on the currency exchange.**CurrencyExchange <CcyXchg>** contains the following **CurrencyExchange5** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		44
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		44
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		44
		ExchangeRate <XchgRate>	[1..1]	Rate		44
		ContractIdentification <CtrctId>	[0..1]	Text		45
		QuotationDate <QtnDt>	[0..1]	DateTime		45

2.1.3.1.1.2.1 SourceCurrency <SrcCcy>*Presence:* [1..1]*Definition:* Currency from which an amount is to be converted in a currency conversion.*Datatype:* [ActiveOrHistoricCurrencyCode on page 243](#)**2.1.3.1.1.2.2 TargetCurrency <TrgtCcy>***Presence:* [0..1]*Definition:* Currency into which an amount is to be converted in a currency conversion.*Datatype:* [ActiveOrHistoricCurrencyCode on page 243](#)**2.1.3.1.1.2.3 UnitCurrency <UnitCcy>***Presence:* [0..1]*Definition:* Currency in which the rate of exchange is expressed in a currency exchange. In the example 1GBP = xxxCUR, the unit currency is GBP.*Datatype:* [ActiveOrHistoricCurrencyCode on page 243](#)**2.1.3.1.1.2.4 ExchangeRate <XchgRate>***Presence:* [1..1]*Definition:* Factor used to convert an amount from one currency into another. This reflects the price at which one currency was bought with another currency.*Usage:* ExchangeRate expresses the ratio between UnitCurrency and QuotedCurrency (ExchangeRate = UnitCurrency/QuotedCurrency).

Datatype: [BaseOneRate on page 307](#)

2.1.3.1.1.2.5 ContractIdentification <CtrctId>

Presence: [0..1]

Definition: Unique identification to unambiguously identify the foreign exchange contract.

Datatype: [Max35Text on page 310](#)

2.1.3.1.1.2.6 QuotationDate <QtnDt>

Presence: [0..1]

Definition: Date and time at which an exchange rate is quoted.

Datatype: [ISODatetime on page 303](#)

2.1.3.1.2 TransactionAmount <TxAmt>

Presence: [0..1]

Definition: Amount of the underlying transaction.

TransactionAmount <TxAmt> contains the following **AmountAndCurrencyExchangeDetails3** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Amount		45
		CurrencyExchange <CcyXchg>	[0..1]			45
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		46
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		46
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		46
		ExchangeRate <XchgRate>	[1..1]	Rate		46
		ContractIdentification <CtrctId>	[0..1]	Text		46
		QuotationDate <QtnDt>	[0..1]	DateTime		46

2.1.3.1.2.1 Amount <Amt>

Presence: [1..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 242](#)

2.1.3.1.2.2 CurrencyExchange <CcyXchg>

Presence: [0..1]

Definition: Set of elements used to provide details on the currency exchange.

CurrencyExchange <CcyXchg> contains the following **CurrencyExchange5** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		46
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		46
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		46
		ExchangeRate <XchgRate>	[1..1]	Rate		46
		ContractIdentification <CtrctId>	[0..1]	Text		46
		QuotationDate <QtnDt>	[0..1]	DateTime		46

2.1.3.1.2.2.1 SourceCurrency <SrcCcy>

Presence: [1..1]

Definition: Currency from which an amount is to be converted in a currency conversion.

Datatype: [ActiveOrHistoricCurrencyCode on page 243](#)

2.1.3.1.2.2.2 TargetCurrency <TrgtCcy>

Presence: [0..1]

Definition: Currency into which an amount is to be converted in a currency conversion.

Datatype: [ActiveOrHistoricCurrencyCode on page 243](#)

2.1.3.1.2.2.3 UnitCurrency <UnitCcy>

Presence: [0..1]

Definition: Currency in which the rate of exchange is expressed in a currency exchange. In the example 1GBP = xxxCUR, the unit currency is GBP.

Datatype: [ActiveOrHistoricCurrencyCode on page 243](#)

2.1.3.1.2.2.4 ExchangeRate <XchgRate>

Presence: [1..1]

Definition: Factor used to convert an amount from one currency into another. This reflects the price at which one currency was bought with another currency.

Usage: ExchangeRate expresses the ratio between UnitCurrency and QuotedCurrency (ExchangeRate = UnitCurrency/QuotedCurrency).

Datatype: [BaseOneRate on page 307](#)

2.1.3.1.2.2.5 ContractIdentification <CtrctId>

Presence: [0..1]

Definition: Unique identification to unambiguously identify the foreign exchange contract.

Datatype: [Max35Text on page 310](#)

2.1.3.1.2.2.6 QuotationDate <QtnDt>

Presence: [0..1]

Definition: Date and time at which an exchange rate is quoted.

Datatype: [ISODatetime](#) on page 303

2.1.3.1.3 CounterValueAmount <CntrValAmt>

Presence: [0..1]

Definition: Set of elements used to provide the countervalue amount and currency exchange information.

Usage: This can be either the counter amount quoted in an FX deal, or the result of the currency information applied to an instructed amount, before deduction of charges.

CounterValueAmount <CntrValAmt> contains the following **AmountAndCurrencyExchangeDetails3** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Amount		47
		CurrencyExchange <CcyXchg>	[0..1]			47
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		48
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		48
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		48
		ExchangeRate <XchgRate>	[1..1]	Rate		48
		ContractIdentification <CtrctId>	[0..1]	Text		48
		QuotationDate <QtnDt>	[0..1]	DateTime		48

2.1.3.1.3.1 Amount <Amt>

Presence: [1..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 242

2.1.3.1.3.2 CurrencyExchange <CcyXchg>

Presence: [0..1]

Definition: Set of elements used to provide details on the currency exchange.

CurrencyExchange <CcyXchg> contains the following **CurrencyExchange5** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		48
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		48
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		48
		ExchangeRate <XchgRate>	[1..1]	Rate		48
		ContractIdentification <CtrctId>	[0..1]	Text		48
		QuotationDate <QtnDt>	[0..1]	DateTime		48

2.1.3.1.3.2.1 SourceCurrency <SrcCcy>

Presence: [1..1]

Definition: Currency from which an amount is to be converted in a currency conversion.

Datatype: [ActiveOrHistoricCurrencyCode on page 243](#)

2.1.3.1.3.2.2 TargetCurrency <TrgtCcy>

Presence: [0..1]

Definition: Currency into which an amount is to be converted in a currency conversion.

Datatype: [ActiveOrHistoricCurrencyCode on page 243](#)

2.1.3.1.3.2.3 UnitCurrency <UnitCcy>

Presence: [0..1]

Definition: Currency in which the rate of exchange is expressed in a currency exchange. In the example 1GBP = xxxCUR, the unit currency is GBP.

Datatype: [ActiveOrHistoricCurrencyCode on page 243](#)

2.1.3.1.3.2.4 ExchangeRate <XchgRate>

Presence: [1..1]

Definition: Factor used to convert an amount from one currency into another. This reflects the price at which one currency was bought with another currency.

Usage: ExchangeRate expresses the ratio between UnitCurrency and QuotedCurrency (ExchangeRate = UnitCurrency/QuotedCurrency).

Datatype: [BaseOneRate on page 307](#)

2.1.3.1.3.2.5 ContractIdentification <CtrctId>

Presence: [0..1]

Definition: Unique identification to unambiguously identify the foreign exchange contract.

Datatype: [Max35Text on page 310](#)

2.1.3.1.3.2.6 QuotationDate <QtnDt>

Presence: [0..1]

Definition: Date and time at which an exchange rate is quoted.

Datatype: [ISODatetime](#) on page 303

2.1.3.1.4 AnnouncedPostingAmount <AnncdPstngAmt>

Presence: [0..1]

Definition: Amount of money, based on terms of corporate action event and balance of underlying securities, entitled to/from the account owner.

In some situations, this amount may alternatively be called entitled amount.

AnnouncedPostingAmount <AnncdPstngAmt> contains the following **AmountAndCurrencyExchangeDetails3** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Amount		49
		CurrencyExchange <CcyXchg>	[0..1]			49
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		50
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		50
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		50
		ExchangeRate <XchgRate>	[1..1]	Rate		50
		ContractIdentification <CtrctId>	[0..1]	Text		50
		QuotationDate <QtnDt>	[0..1]	DateTime		50

2.1.3.1.4.1 Amount <Amt>

Presence: [1..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 242

2.1.3.1.4.2 CurrencyExchange <CcyXchg>

Presence: [0..1]

Definition: Set of elements used to provide details on the currency exchange.

CurrencyExchange <CcyXchg> contains the following **CurrencyExchange5** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		50
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		50
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		50
		ExchangeRate <XchgRate>	[1..1]	Rate		50
		ContractIdentification <CtrctId>	[0..1]	Text		50
		QuotationDate <QtnDt>	[0..1]	DateTime		50

2.1.3.1.4.2.1 SourceCurrency <SrcCcy>

Presence: [1..1]

Definition: Currency from which an amount is to be converted in a currency conversion.

Datatype: [ActiveOrHistoricCurrencyCode on page 243](#)

2.1.3.1.4.2.2 TargetCurrency <TrgtCcy>

Presence: [0..1]

Definition: Currency into which an amount is to be converted in a currency conversion.

Datatype: [ActiveOrHistoricCurrencyCode on page 243](#)

2.1.3.1.4.2.3 UnitCurrency <UnitCcy>

Presence: [0..1]

Definition: Currency in which the rate of exchange is expressed in a currency exchange. In the example 1GBP = xxxCUR, the unit currency is GBP.

Datatype: [ActiveOrHistoricCurrencyCode on page 243](#)

2.1.3.1.4.2.4 ExchangeRate <XchgRate>

Presence: [1..1]

Definition: Factor used to convert an amount from one currency into another. This reflects the price at which one currency was bought with another currency.

Usage: ExchangeRate expresses the ratio between UnitCurrency and QuotedCurrency (ExchangeRate = UnitCurrency/QuotedCurrency).

Datatype: [BaseOneRate on page 307](#)

2.1.3.1.4.2.5 ContractIdentification <CtrctId>

Presence: [0..1]

Definition: Unique identification to unambiguously identify the foreign exchange contract.

Datatype: [Max35Text on page 310](#)

2.1.3.1.4.2.6 QuotationDate <QtnDt>

Presence: [0..1]

Definition: Date and time at which an exchange rate is quoted.

Datatype: [ISODateTime](#) on page 303

2.1.3.1.5 ProprietaryAmount <PrtryAmt>

Presence: [0..*]

Definition: Set of elements used to provide information on the original amount and currency exchange.

ProprietaryAmount <PrtryAmt> contains the following **AmountAndCurrencyExchangeDetails4** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[1..1]	Text		51
		Amount <Amt>	[1..1]	Amount		51
		CurrencyExchange <CcyXchg>	[0..1]			51
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		52
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		52
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		52
		ExchangeRate <XchgRate>	[1..1]	Rate		52
		ContractIdentification <CtrctId>	[0..1]	Text		52
		QuotationDate <QtnDt>	[0..1]	DateTime		52

2.1.3.1.5.1 Type <Tp>

Presence: [1..1]

Definition: Specifies the type of amount.

Datatype: [Max35Text](#) on page 310

2.1.3.1.5.2 Amount <Amt>

Presence: [1..1]

Definition: Amount of money to be exchanged against another amount of money in the counter currency.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 242

2.1.3.1.5.3 CurrencyExchange <CcyXchg>

Presence: [0..1]

Definition: Set of elements used to provide details on the currency exchange.

CurrencyExchange <CcyXchg> contains the following **CurrencyExchange5** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		52
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		52
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		52
		ExchangeRate <XchgRate>	[1..1]	Rate		52
		ContractIdentification <CtrctId>	[0..1]	Text		52
		QuotationDate <QtnDt>	[0..1]	DateTime		52

2.1.3.1.5.3.1 SourceCurrency <SrcCcy>

Presence: [1..1]

Definition: Currency from which an amount is to be converted in a currency conversion.

Datatype: [ActiveOrHistoricCurrencyCode on page 243](#)

2.1.3.1.5.3.2 TargetCurrency <TrgtCcy>

Presence: [0..1]

Definition: Currency into which an amount is to be converted in a currency conversion.

Datatype: [ActiveOrHistoricCurrencyCode on page 243](#)

2.1.3.1.5.3.3 UnitCurrency <UnitCcy>

Presence: [0..1]

Definition: Currency in which the rate of exchange is expressed in a currency exchange. In the example 1GBP = xxxCUR, the unit currency is GBP.

Datatype: [ActiveOrHistoricCurrencyCode on page 243](#)

2.1.3.1.5.3.4 ExchangeRate <XchgRate>

Presence: [1..1]

Definition: Factor used to convert an amount from one currency into another. This reflects the price at which one currency was bought with another currency.

Usage: ExchangeRate expresses the ratio between UnitCurrency and QuotedCurrency (ExchangeRate = UnitCurrency/QuotedCurrency).

Datatype: [BaseOneRate on page 307](#)

2.1.3.1.5.3.5 ContractIdentification <CtrctId>

Presence: [0..1]

Definition: Unique identification to unambiguously identify the foreign exchange contract.

Datatype: [Max35Text on page 310](#)

2.1.3.1.5.3.6 QuotationDate <QtnDt>

Presence: [0..1]

Definition: Date and time at which an exchange rate is quoted.

Datatype: [ISODateTime](#) on page 303

2.1.3.2 AmountAndDirection35

Definition: Resulting debit or credit amount of the netted amounts for all debit and credit entries.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Quantity		53
		CreditDebitIndicator <CdtDbtInd>	[1..1]	CodeSet		53

2.1.3.2.1 Amount <Amt>

Presence: [1..1]

Definition: Resulting amount of the netted amounts for all debit and credit entries.

Datatype: [NonNegativeDecimalNumber](#) on page 306

2.1.3.2.2 CreditDebitIndicator <CdtDbtInd>

Presence: [1..1]

Definition: Indicates whether the amount is a credit or a debit amount.

Datatype: [CreditDebitCode](#) on page 260

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

2.1.4 Amount Range

2.1.4.1 ImpliedCurrencyAmountRange1Choice

Definition: Choice between ranges of values in which an amount is considered valid or a specified amount value which has to be matched or unmatched to be valid.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	FromAmount <FrAmt>	[1..1]	±		54
	Or	ToAmount <ToAmt>	[1..1]	±		54
	Or	FromToAmount <FrToAmt>	[1..1]			54
		FromAmount <FrAmt>	[1..1]	±		54
		ToAmount <ToAmt>	[1..1]	±		55
	Or	EqualAmount <EQAmt>	[1..1]	Amount		55
	Or}	NotEqualAmount <NEQAmt>	[1..1]	Amount		55

2.1.4.1.1 FromAmount <FrAmt>*Presence:* [1..1]*Definition:* Lower boundary of a range of amount values.**FromAmount <FrAmt>** contains the following elements (see [AmountRangeBoundary1](#) on page 56 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		BoundaryAmount <BdryAmt>	[1..1]	Amount		56
		Included <Incl>	[1..1]	Indicator		56

2.1.4.1.2 ToAmount <ToAmt>*Presence:* [1..1]*Definition:* Upper boundary of a range of amount values.**ToAmount <ToAmt>** contains the following elements (see [AmountRangeBoundary1](#) on page 56 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		BoundaryAmount <BdryAmt>	[1..1]	Amount		56
		Included <Incl>	[1..1]	Indicator		56

2.1.4.1.3 FromToAmount <FrToAmt>*Presence:* [1..1]*Definition:* Range of valid amount values.**FromToAmount <FrToAmt>** contains the following **FromToAmountRange1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FromAmount <FrAmt>	[1..1]	±		54
		ToAmount <ToAmt>	[1..1]	±		55

2.1.4.1.3.1 FromAmount <FrAmt>*Presence:* [1..1]*Definition:* Lower boundary of a range of amount values.**FromAmount <FrAmt>** contains the following elements (see [AmountRangeBoundary1](#) on page 56 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		BoundaryAmount <BdryAmt>	[1..1]	Amount		56
		Included <Incl>	[1..1]	Indicator		56

2.1.4.1.3.2 ToAmount <ToAmt>

Presence: [1..1]

Definition: Upper boundary of a range of amount values.

ToAmount <ToAmt> contains the following elements (see [AmountRangeBoundary1](#) on page 56 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		BoundaryAmount <BdryAmt>	[1..1]	Amount		56
		Included <Incl>	[1..1]	Indicator		56

2.1.4.1.4 EqualAmount <EQAmt>

Presence: [1..1]

Definition: Exact value an amount must match to be considered valid.

Datatype: [ImpliedCurrencyAndAmount](#) on page 243

2.1.4.1.5 NotEqualAmount <NEQAmt>

Presence: [1..1]

Definition: Value that an amount must not match to be considered valid.

Datatype: [ImpliedCurrencyAndAmount](#) on page 243

2.1.4.2 ActiveOrHistoricCurrencyAndAmountRange2

Definition: Range of amount values.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	±		55
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		56
		Currency <Ccy>	[1..1]	CodeSet		56

2.1.4.2.1 Amount <Amt>

Presence: [1..1]

Definition: Specified amount or amount range.

Amount <Amt> contains one of the following elements (see [ImpliedCurrencyAmountRange1Choice](#) on page 53 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	FromAmount <FrAmt>	[1..1]	±		54
	Or	ToAmount <ToAmt>	[1..1]	±		54
	Or	FromToAmount <FrToAmt>	[1..1]			54
		FromAmount <FrAmt>	[1..1]	±		54
		ToAmount <ToAmt>	[1..1]	±		55
	Or	EqualAmount <EQAmt>	[1..1]	Amount		55
	Or}	NotEqualAmount <NEQAmt>	[1..1]	Amount		55

2.1.4.2.2 CreditDebitIndicator <CdtDbtInd>

Presence: [0..1]

Definition: Indicates whether the amount is a credited or debited amount.

Datatype: [CreditDebitCode](#) on page 260

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

2.1.4.2.3 Currency <Ccy>

Presence: [1..1]

Definition: Medium of exchange of value, used to qualify an amount.

Datatype: [ActiveOrHistoricCurrencyCode](#) on page 243

2.1.4.3 AmountRangeBoundary1

Definition: Limit for an amount range.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		BoundaryAmount <BdryAmt>	[1..1]	Amount		56
		Included <Incl>	[1..1]	Indicator		56

2.1.4.3.1 BoundaryAmount <BdryAmt>

Presence: [1..1]

Definition: Amount value of the range limit.

Datatype: [ImpliedCurrencyAndAmount](#) on page 243

2.1.4.3.2 Included <Incl>

Presence: [1..1]

Definition: Indicates whether the boundary amount is included in the range of amount values.

Datatype: One of the following values must be used (see [YesNoIndicator](#) on page 306):

- *Meaning When True:* Yes
- *Meaning When False:* No

2.1.5 Bank Transaction Code

2.1.5.1 BankTransactionCodeStructure4

Definition: Set of elements used to identify the type or operations code of a transaction entry.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Domain <Domn>	[0..1]	±		57
		Proprietary <Prtry>	[0..1]			58
		Code <Cd>	[1..1]	Text		58
		Issuer <Issr>	[0..1]	Text		58

Constraints

- **DomainOrProprietaryRule**

Either Proprietary or Domain or both must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00104
- *Error Text:* Invalid message content for bank transaction code.

- **FamilyAndSubFamilyRule**

If a specific (non-generic) Family code is not present, then a specific (non-generic) SubFamily code is not allowed.

2.1.5.1.1 Domain <Domn>

Presence: [0..1]

Definition: Set of elements used to provide the domain, the family and the sub-family of the bank transaction code, in a structured and hierarchical format.

Usage: If a specific family or sub-family code cannot be provided, the generic family code defined for the domain or the generic sub-family code defined for the family should be provided.

Domain <Domn> contains the following elements (see [BankTransactionCodeStructure5](#) on page 59 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Code <Cd>	[1..1]	CodeSet		59
		Family <Fmly>	[1..1]	±		59

2.1.5.1.2 Proprietary <Prtry>

Presence: [0..1]

Definition: Bank transaction code in a proprietary form, as defined by the issuer.

Proprietary <Prtry> contains the following **ProprietaryBankTransactionCodeStructure1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Code <Cd>	[1..1]	Text		58
		Issuer <Issr>	[0..1]	Text		58

2.1.5.1.2.1 Code <Cd>

Presence: [1..1]

Definition: Proprietary bank transaction code to identify the underlying transaction.

Datatype: [Max35Text](#) on page 310

2.1.5.1.2.2 Issuer <Issr>

Presence: [0..1]

Definition: Identification of the issuer of the proprietary bank transaction code.

Datatype: [Max35Text](#) on page 310

2.1.5.2 BankTransactionCodeStructure6

Definition: Set of elements used to identify the type or operations code of a transaction entry.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Code <Cd>	[1..1]	CodeSet		58
		SubFamilyCode <SubFmlyCd>	[1..1]	CodeSet		58

2.1.5.2.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the family within a domain.

Datatype: [ExternalBankTransactionFamily1Code](#) on page 265

2.1.5.2.2 SubFamilyCode <SubFmlyCd>

Presence: [1..1]

Definition: Specifies the sub-product family within a specific family.

Datatype: [ExternalBankTransactionSubFamily1Code](#) on page 266

2.1.5.3 BankTransactionCodeStructure5

Definition: Set of elements used to identify the type or operations code of a transaction entry.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Code <Cd>	[1..1]	CodeSet		59
		Family <Fmly>	[1..1]	±		59

2.1.5.3.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the business area of the underlying transaction.

Datatype: [ExternalBankTransactionDomain1Code](#) on page 264

2.1.5.3.2 Family <Fmly>

Presence: [1..1]

Definition: Specifies the family and the sub-family of the bank transaction code, within a specific domain, in a structured and hierarchical format.

Family <Fmly> contains the following elements (see [BankTransactionCodeStructure6](#) on page 58 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Code <Cd>	[1..1]	CodeSet		58
		SubFamilyCode <SubFmlyCd>	[1..1]	CodeSet		58

2.1.6 Card Transaction

2.1.6.1 CardTransaction17

Definition: Card transaction details.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Card <Card>	[0..1]			62
		PlainCardData <PlainCardData>	[0..1]			63
		PAN <PAN>	[1..1]	Text		64
		CardSequenceNumber <CardSeqNb>	[0..1]	Text		64
		EffectiveDate <FctvDt>	[0..1]	YearMonth		64
		ExpiryDate <XpryDt>	[1..1]	YearMonth		64
		ServiceCode <SvcCd>	[0..1]	Text		64
		TrackData <TrckData>	[0..*]			65
		TrackNumber <TrckNb>	[0..1]	Text		65
		TrackValue <TrckVal>	[1..1]	Text		65
		CardSecurityCode <CardSctyCd>	[0..1]			65
		CSCManagement <CSCMgmt>	[1..1]	CodeSet		65
		CSCValue <CSCVal>	[0..1]	Text		66
		CardCountryCode <CardCtryCd>	[0..1]	Text		66
		CardBrand <CardBrnd>	[0..1]	±		66
		AdditionalCardData <AddtlCardData>	[0..1]	Text		66
		POI <POI/>	[0..1]			66
		Identification <Id>	[1..1]	±		67
		SystemName <SysNm>	[0..1]	Text		68
		GroupIdentification <Grpld>	[0..1]	Text		68
		Capabilities <Cpblties>	[0..1]			68
		CardReadingCapabilities <CardRdngCpblties>	[0..*]	CodeSet		68
		CardholderVerificationCapabilities <CrdhldrVrfctnCpblties>	[0..*]	CodeSet		69
		OnLineCapabilities <OnLineCpblties>	[0..1]	CodeSet		69
		DisplayCapabilities <DispCpblties>	[0..*]			70
		DisplayType <DispTp>	[1..1]	CodeSet		70
		NumberOfLines <NbOfLines>	[1..1]	Text		70
		LineWidth <LineWidth>	[1..1]	Text		70
		PrintLineWidth <PrtLineWidth>	[0..1]	Text		70
		Component <Cmpnt>	[0..*]			70
		POIComponentType <POICmpntTp>	[1..1]	CodeSet		71

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ManufacturerIdentification <ManfctrId>	[0..1]	Text		71
		Model <Mdl>	[0..1]	Text		71
		VersionNumber <VrsnNb>	[0..1]	Text		71
		SerialNumber <SrINb>	[0..1]	Text		72
		ApprovalNumber <ApprvINb>	[0..*]	Text		72
		Transaction <Tx>	[0..1]			72
	{Or	Aggregated <Aggtd>	[1..1]			74
		AdditionalService <AddtlSvc>	[0..1]	CodeSet		74
		TransactionCategory <TxCtgy>	[0..1]	CodeSet		75
		SaleReconciliationIdentification <SaleRcncltnId>	[0..1]	Text		75
		SequenceNumberRange <SeqNbRg>	[0..1]			75
		FirstTransaction <FrstTx>	[0..1]	Text		75
		LastTransaction <LastTx>	[0..1]	Text		75
		TransactionDateRange <TxDtRg>	[0..1]	±		76
	Or}	Individual <Indv>	[1..1]			76
		ICCRRelatedData <ICCRltdData>	[0..1]	Text		78
		PaymentContext <PmtCntxt>	[0..1]			78
		CardPresent <CardPres>	[0..1]	Indicator		78
		CardholderPresent <CrhdldrPres>	[0..1]	Indicator		79
		OnLineContext <OnLineCntxt>	[0..1]	Indicator		79
		AttendanceContext <AttdncCntxt>	[0..1]	CodeSet		79
		TransactionEnvironment <TxEnv>	[0..1]	CodeSet		79
		TransactionChannel <TxChanl>	[0..1]	CodeSet		79
		AttendantMessageCapable <AttdntMsgCpbl>	[0..1]	Indicator		80
		AttendantLanguage <AttdntLang>	[0..1]	CodeSet		80
		CardDataEntryMode <CardDataNtryMd>	[1..1]	CodeSet		80
		FallbackIndicator <FlbkInd>	[0..1]	Indicator		81
		AuthenticationMethod <AuthntcnMtd>	[0..1]			81
		AuthenticationMethod <AuthntcnMtd>	[1..1]	CodeSet		81
		AuthenticationEntity <AuthntcnNtty>	[1..1]	CodeSet		82
		AdditionalService <AddtlSvc>	[0..1]	CodeSet		82

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TransactionCategory <TxCtgy>	[0..1]	CodeSet		82
		SaleReconciliationIdentification <SaleRcncltnId>	[0..1]	Text		82
		SaleReferenceNumber <SaleRefNb>	[0..1]	Text		83
		RePresentmentReason <RePresntmntRsn>	[0..1]	CodeSet		83
		SequenceNumber <SeqNb>	[0..1]	Text		83
		TransactionIdentification <TxId>	[0..1]	±		83
		Product <Pdct>	[0..1]			83
		ProductCode <PdctCd>	[1..1]	Text		84
		UnitOfMeasure <UnitOfMeasr>	[0..1]	CodeSet		84
		ProductQuantity <PdctQty>	[0..1]	Quantity		86
		UnitPrice <UnitPric>	[0..1]	Amount		86
		ProductAmount <PdctAmt>	[0..1]	Amount		86
		TaxType <TaxTp>	[0..1]	Text		86
		AdditionalProductInformation <AddtlPdctInf>	[0..1]	Text		86
		ValidationDate <VldtnDt>	[0..1]	Date		86
		ValidationSequenceNumber <VldtnSeqNb>	[0..1]	Text		86
		PrePaidAccount <PrePdAcct>	[0..1]	±		86

2.1.6.1.1 Card <Card>

Presence: [0..1]

Definition: Electronic money product that provides the cardholder with a portable and specialised computer device, which typically contains a microprocessor.

Card <Card> contains the following **PaymentCard4** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PlainCardData <PlainCardData>	[0..1]			63
		PAN <PAN>	[1..1]	Text		64
		CardSequenceNumber <CardSeqNb>	[0..1]	Text		64
		EffectiveDate <FctvDt>	[0..1]	YearMonth		64
		ExpiryDate <XpryDt>	[1..1]	YearMonth		64
		ServiceCode <SvcCd>	[0..1]	Text		64
		TrackData <TrckData>	[0..*]			65
		TrackNumber <TrckNb>	[0..1]	Text		65
		TrackValue <TrckVal>	[1..1]	Text		65
		CardSecurityCode <CardSctyCd>	[0..1]			65
		CSCManagement <CSCMgmt>	[1..1]	CodeSet		65
		CSCValue <CSCVal>	[0..1]	Text		66
		CardCountryCode <CardCtryCd>	[0..1]	Text		66
		CardBrand <CardBrnd>	[0..1]	±		66
		AdditionalCardData <AddtlCardData>	[0..1]	Text		66

2.1.6.1.1.1 PlainCardData <PlainCardData>

Presence: [0..1]

Definition: Sensitive data associated with the card performing the transaction.

PlainCardData <PlainCardData> contains the following **PlainCardData1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PAN <PAN>	[1..1]	Text		64
		CardSequenceNumber <CardSeqNb>	[0..1]	Text		64
		EffectiveDate <FctvDt>	[0..1]	YearMonth		64
		ExpiryDate <XpryDt>	[1..1]	YearMonth		64
		ServiceCode <SvcCd>	[0..1]	Text		64
		TrackData <TrckData>	[0..*]			65
		TrackNumber <TrckNb>	[0..1]	Text		65
		TrackValue <TrckVal>	[1..1]	Text		65
		CardSecurityCode <CardSctyCd>	[0..1]			65
		CSCManagement <CSCMgmt>	[1..1]	CodeSet		65
		CSCValue <CSCVal>	[0..1]	Text		66

2.1.6.1.1.1.1 PAN <PAN>

Presence: [1..1]

Definition: Primary Account Number (PAN) of the card, or card number.

Datatype: Min8Max28NumericText on page 311

2.1.6.1.1.1.2 CardSequenceNumber <CardSeqNb>

Presence: [0..1]

Definition: Identify a card inside a set of cards with the same card number (PAN).

Datatype: Min2Max3NumericText on page 311

2.1.6.1.1.1.3 EffectiveDate <FctvDt>

Presence: [0..1]

Definition: Date as from which the card can be used.

Datatype: ISOYearMonth on page 312

2.1.6.1.1.1.4 ExpiryDate <XpryDt>

Presence: [1..1]

Definition: Expiry date of the card.

Datatype: ISOYearMonth on page 312

2.1.6.1.1.1.5 ServiceCode <SvcCd>

Presence: [0..1]

Definition: Services attached to the card, as defined in ISO 7813.

Datatype: Exact3NumericText on page 307

2.1.6.1.1.1.6 TrackData <TrckData>*Presence:* [0..*]*Definition:* Magnetic track or equivalent payment card data.**TrackData <TrckData>** contains the following **TrackData1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TrackNumber <TrckNb>	[0..1]	Text		65
		TrackValue <TrckVal>	[1..1]	Text		65

2.1.6.1.1.1.6.1 TrackNumber <TrckNb>*Presence:* [0..1]*Definition:* Track number of the card.*Datatype:* Exact1NumericText on page 307**2.1.6.1.1.1.6.2 TrackValue <TrckVal>***Presence:* [1..1]*Definition:* Card track content or equivalent.*Datatype:* Max140Text on page 308**2.1.6.1.1.1.7 CardSecurityCode <CardSctyCd>***Presence:* [0..1]*Definition:* Card security code (CSC) associated with the card performing the transaction.**CardSecurityCode <CardSctyCd>** contains the following **CardSecurityInformation1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CSCManagement <CSCMgmt>	[1..1]	CodeSet		65
		CSCValue <CSCVal>	[0..1]	Text		66

2.1.6.1.1.1.7.1 CSCManagement <CSCMgmt>*Presence:* [1..1]*Definition:* Card security code (CSC) management associated with the transaction.*Datatype:* CSCManagement1Code on page 260

CodeName	Name	Definition
PRST	CSCPresent	Card security code present.
BYPS	CSCByPass	Card security code by-passed or not provided by the merchant.
UNRD	CSCUnread	Card security code unreadable.
NCSC	NoCSC	No card security code imprint.

2.1.6.1.1.1.7.2 CSCValue <CSCVal>*Presence:* [0..1]*Definition:* Card security code (CSC).*Datatype:* [Min3Max4NumericText on page 311](#)**2.1.6.1.1.2 CardCountryCode <CardCtryCd>***Presence:* [0..1]*Definition:* Country code assigned to the card by the card issuer.*Datatype:* [Exact3NumericText on page 307](#)**2.1.6.1.1.3 CardBrand <CardBrnd>***Presence:* [0..1]*Definition:* Brand name of the card.**CardBrand <CardBrnd>** contains the following elements (see [GenericIdentification1 on page 160](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		161
		SchemeName <SchmeNm>	[0..1]	Text		161
		Issuer </ssr>	[0..1]	Text		161

2.1.6.1.1.4 AdditionalCardData <AddtlCardData>*Presence:* [0..1]*Definition:* Additional card issuer specific data.*Datatype:* [Max70Text on page 311](#)**2.1.6.1.2 POI <POI>***Presence:* [0..1]*Definition:* Physical or logical card payment terminal containing software and hardware components.

POI <POI> contains the following **PointOfInteraction1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		67
		SystemName <SysNm>	[0..1]	Text		68
		GroupIdentification <GrpId>	[0..1]	Text		68
		Capabilities <Cpblties>	[0..1]			68
		CardReadingCapabilities <CardRdngCpblties>	[0..*]	CodeSet		68
		CardholderVerificationCapabilities <CrdhldrVrfctnCpblties>	[0..*]	CodeSet		69
		OnLineCapabilities <OnLineCpblties>	[0..1]	CodeSet		69
		DisplayCapabilities <DispCpblties>	[0..*]			70
		DisplayType <DispTp>	[1..1]	CodeSet		70
		NumberOfLines <NbOfLines>	[1..1]	Text		70
		LineWidth <LineWidth>	[1..1]	Text		70
		PrintLineWidth <PrtLineWidth>	[0..1]	Text		70
		Component <Cmpnt>	[0..*]			70
		POIComponentType <POICmpntTp>	[1..1]	CodeSet		71
		ManufacturerIdentification <ManfctrId>	[0..1]	Text		71
		Model <Mdl>	[0..1]	Text		71
		VersionNumber <VrsnNb>	[0..1]	Text		71
		SerialNumber <SrINb>	[0..1]	Text		72
		ApprovalNumber <ApprvINb>	[0..*]	Text		72

2.1.6.1.2.1 Identification <Id>

Presence: [1..1]

Definition: Identification of the POI (Point Of Interaction) for the acquirer or its agent.

Identification <Id> contains the following elements (see [GenericIdentification32](#) on page 159 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		159
		Type <Tp>	[0..1]	CodeSet		160
		Issuer <Issr>	[0..1]	CodeSet		160
		ShortName <ShrtNm>	[0..1]	Text		160

2.1.6.1.2.2 SystemName <SysNm>*Presence:* [0..1]*Definition:* Common name assigned by the acquirer to the POI system.*Datatype:* [Max70Text on page 311](#)**2.1.6.1.2.3 GroupIdentification <GrpId>***Presence:* [0..1]*Definition:* Identifier assigned by the merchant identifying a set of POI terminals performing some categories of transactions.*Datatype:* [Max35Text on page 310](#)**2.1.6.1.2.4 Capabilities <Cpblties>***Presence:* [0..1]*Definition:* Capabilities of the POI performing the transaction.**Capabilities <Cpblties>** contains the following **PointOfInteractionCapabilities1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CardReadingCapabilities <CardRdngCpblties>	[0..*]	CodeSet		68
		CardholderVerificationCapabilities <CrdhldrVrfctnCpblties>	[0..*]	CodeSet		69
		OnLineCapabilities <OnLineCpblties>	[0..1]	CodeSet		69
		DisplayCapabilities <DispCpblties>	[0..*]			70
		DisplayType <DispTp>	[1..1]	CodeSet		70
		NumberOfLines <NbOfLines>	[1..1]	Text		70
		LineWidth <LineWidth>	[1..1]	Text		70
		PrintLineWidth <PrtLineWidth>	[0..1]	Text		70

2.1.6.1.2.4.1 CardReadingCapabilities <CardRdngCpblties>*Presence:* [0..*]*Definition:* Card reading capabilities of the POI performing the transaction.*Datatype:* [CardDataReading1Code on page 250](#)

CodeName	Name	Definition
TAGC	Tag	Tag reading capabilities (RFID, etc.).
PHYS	Physical	Keyboard entry or OCR reading of embossing or printed data, either at time of transaction or after the event.
BRCD	BarCode	Bar code.
MGST	MagneticStripe	Magnetic stripe.
CICC	ICC	ICC (Integrated Circuit Card) with contact containing software applications conform to ISO 7816.

CodeName	Name	Definition
DFLE	AccountData	Account data on file.
CTLS	ProximityReader	Contactless proximity reader.
ECTL	EMVProximityReader	Contactless proximity reader, with application conform to the standard EMV (standard initiated by Europay, Mastercard and Visa).

2.1.6.1.2.4.2 CardholderVerificationCapabilities <CrdhldrVrfctnCpblties>

Presence: [0..*]

Definition: Cardholder verification capabilities of the POI performing the transaction.

Datatype: [CardholderVerificationCapability1Code on page 252](#)

CodeName	Name	Definition
MNSG	ManualSignature	Manual signature verification.
NPIN	OnLinePIN	Online PIN (Personal Identification Number).
FCPN	OfflinePINCLEAR	Offline PIN in clear (Personal Identification Number).
FEPN	OfflinePINEncrypted	Offline PIN encrypted (Personal Identification Number).
FDSG	OfflineDigitalSignature	Offline digital signature analysis.
FBIO	OfflineBiometrics	Offline biometrics.
MNVR	ManualVerification	Other manual verification, for example passport or drivers license.
FBIG	OfflineBiographics	Offline biographics.
APKI	AccountDigitalSignature	Account based digital signature.
PKIS	PKISignature	PKI (Public Key Infrastructure) based digital signature.
CHDT	CardholderData	Cardholder authentication data.
SCEC	SecureElectronicCommerce	Three domain secure (three domain secure authentication of the cardholder).

2.1.6.1.2.4.3 OnLineCapabilities <OnLineCpblties>

Presence: [0..1]

Definition: On-line and off-line capabilities of the POI.

Datatype: [OnLineCapability1Code on page 281](#)

CodeName	Name	Definition
OFLN	OffLine	Off-line only capable.
ONLN	OnLine	On-line only capable.
SMON	SemiOffLine	Off-line capable with possible on-line requests to the acquirer.

2.1.6.1.2.4.4 DisplayCapabilities <DispCpblties>

Presence: [0..*]

Definition: Capabilities of the display components performing the transaction.

DisplayCapabilities <DispCpblties> contains the following **DisplayCapabilities1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DisplayType <DispTp>	[1..1]	CodeSet		70
		NumberOfLines <NbOfLines>	[1..1]	Text		70
		LineWidth <LineWidth>	[1..1]	Text		70

2.1.6.1.2.4.4.1 DisplayType <DispTp>

Presence: [1..1]

Definition: Type of display (for example merchant or cardholder).

Datatype: [UserInterface2Code on page 301](#)

CodeName	Name	Definition
MDSP	MerchantDisplay	Merchant display or interface.
CDSP	CardholderDisplay	Cardholder display or interface.

2.1.6.1.2.4.4.2 NumberOfLines <NbOfLines>

Presence: [1..1]

Definition: Number of lines of the display component.

Datatype: [Max3NumericText on page 310](#)

2.1.6.1.2.4.4.3 LineWidth <LineWidth>

Presence: [1..1]

Definition: Number of columns of the display component.

Datatype: [Max3NumericText on page 310](#)

2.1.6.1.2.4.5 PrintLineWidth <PrtLineWidth>

Presence: [0..1]

Definition: Number of columns of the printer component.

Datatype: [Max3NumericText on page 310](#)

2.1.6.1.2.5 Component <Cmpnt>

Presence: [0..*]

Definition: Data related to a component of the POI performing the transaction.

Component <Cmpnt> contains the following **PointOfInteractionComponent1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		POIComponentType <POICmpntTp>	[1..1]	CodeSet		71
		ManufacturerIdentification <ManfctrId>	[0..1]	Text		71
		Model <Mdl>	[0..1]	Text		71
		VersionNumber <VrsnNb>	[0..1]	Text		71
		SerialNumber <SrlNb>	[0..1]	Text		72
		ApprovalNumber <ApprvlNb>	[0..*]	Text		72

2.1.6.1.2.5.1 POIComponentType <POICmpntTp>

Presence: [1..1]

Definition: Type of component belonging to a POI Terminal.

Datatype: POIComponentType1Code on page 286

CodeName	Name	Definition
SOFT	Soft	Payment or other software application.
EMVK	EMVKernel	EMV application kernel (EMV is the chip card specifications initially defined by Eurocard, Mastercard and Visa).
EMVO	EMVLevel1	EMV physical interface (EMV is the chip card specifications initially defined by Eurocard, Mastercard and Visa).
MRIT	MerchantInterface	Merchant interface.
CHIT	CardholderInterface	Cardholder Interface.
SECM	SecureModule	Security module.
PEDV	PINEntryDevice	Personal identification number (or PIN) entry device (PED).

2.1.6.1.2.5.2 ManufacturerIdentification <ManfctrId>

Presence: [0..1]

Definition: Identification of the software, hardware or system provider of the POI component.

Datatype: Max35Text on page 310

2.1.6.1.2.5.3 Model <Mdl>

Presence: [0..1]

Definition: Identification of a model of POI component for a given manufacturer.

Datatype: Max35Text on page 310

2.1.6.1.2.5.4 VersionNumber <VrsnNb>

Presence: [0..1]

Definition: Version of component belonging to a given model.

Datatype: Max16Text on page 309

2.1.6.1.2.5.5 SerialNumber <SrlNb>

Presence: [0..1]

Definition: Serial number of a component.

Datatype: Max35Text on page 310

2.1.6.1.2.5.6 ApprovalNumber <ApprvINb>

Presence: [0..*]

Definition: Unique approval number for a component, delivered by a certification body.

Usage: More than one approval number could be present, when assigned by different bodies. The certification body identification must be provided within the approval number (for example at the beginning of the value).

Datatype: Max70Text on page 311

2.1.6.1.3 Transaction <Tx>

Presence: [0..1]

Definition: Card transaction details, which can be either globalised by the acquirer or individual transaction.

Transaction <Tx> contains one of the following **CardTransaction3Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Aggregated <Aggtd>	[1..1]			74
		AdditionalService <AddtlSvc>	[0..1]	CodeSet		74
		TransactionCategory <TxCtgy>	[0..1]	CodeSet		75
		SaleReconciliationIdentification <SaleRcnccltnId>	[0..1]	Text		75
		SequenceNumberRange <SeqNbRg>	[0..1]			75
		FirstTransaction <FrstTx>	[0..1]	Text		75
		LastTransaction <LastTx>	[0..1]	Text		75
		TransactionDateRange <TxDtRg>	[0..1]	±		76
	Or}	Individual <Indv>	[1..1]			76
		ICCRelatedData <ICCRltdData>	[0..1]	Text		78
		PaymentContext <PmtCntxt>	[0..1]			78
		CardPresent <CardPres>	[0..1]	Indicator		78
		CardholderPresent <CrdhldrPres>	[0..1]	Indicator		79
		OnLineContext <OnLineCntxt>	[0..1]	Indicator		79
		AttendanceContext <AttdncCntxt>	[0..1]	CodeSet		79
		TransactionEnvironment <TxEnvnt>	[0..1]	CodeSet		79
		TransactionChannel <TxChanl>	[0..1]	CodeSet		79
		AttendantMessageCapable <AttdntMsgCpbl>	[0..1]	Indicator		80
		AttendantLanguage <AttdntLang>	[0..1]	CodeSet		80
		CardDataEntryMode <CardDataNtryMd>	[1..1]	CodeSet		80
		FallbackIndicator <FlbckInd>	[0..1]	Indicator		81
		AuthenticationMethod <AuthntcnMtd>	[0..1]			81
		AuthenticationMethod <AuthntcnMtd>	[1..1]	CodeSet		81
		AuthenticationEntity <AuthntcnNtty>	[1..1]	CodeSet		82
		AdditionalService <AddtlSvc>	[0..1]	CodeSet		82
		TransactionCategory <TxCtgy>	[0..1]	CodeSet		82
		SaleReconciliationIdentification <SaleRcnccltnId>	[0..1]	Text		82
		SaleReferenceNumber <SaleRefNb>	[0..1]	Text		83
		RePresentmentReason <RePresntmntRsn>	[0..1]	CodeSet		83
		SequenceNumber <SeqNb>	[0..1]	Text		83

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TransactionIdentification <TxId>	[0..1]	±		83
		Product <Pdct>	[0..1]			83
		ProductCode <PdctCd>	[1..1]	Text		84
		UnitOfMeasure <UnitOfMeasr>	[0..1]	CodeSet		84
		ProductQuantity <PdctQty>	[0..1]	Quantity		86
		UnitPrice <UnitPric>	[0..1]	Amount		86
		ProductAmount <PdctAmt>	[0..1]	Amount		86
		TaxType <TaxTp>	[0..1]	Text		86
		AdditionalProductInformation <AddtlPdctInf>	[0..1]	Text		86
		ValidationDate <VldtnDt>	[0..1]	Date		86
		ValidationSequenceNumber <VldtnSeqNb>	[0..1]	Text		86

2.1.6.1.3.1 Aggregated <Aggtd>

Presence: [1..1]

Definition: Card transaction details, based on card transaction aggregated data performed by the card acquirer.

Aggregated <Aggtd> contains the following **CardAggregated2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AdditionalService <AddtlSvc>	[0..1]	CodeSet		74
		TransactionCategory <TxCtgy>	[0..1]	CodeSet		75
		SaleReconciliationIdentification <SaleRcncltnId>	[0..1]	Text		75
		SequenceNumberRange <SeqNbRg>	[0..1]			75
		FirstTransaction <FrstTx>	[0..1]	Text		75
		LastTransaction <LastTx>	[0..1]	Text		75
		TransactionDateRange <TxDtRg>	[0..1]	±		76

2.1.6.1.3.1.1 AdditionalService <AddtlSvc>

Presence: [0..1]

Definition: Service in addition to the main service.

Datatype: CardPaymentServiceType2Code on page 254

CodeName	Name	Definition
AGGR	Aggregation	Aggregation of low payments.
DCCV	DCC	Dynamic currency conversion (DCC).

CodeName	Name	Definition
GRTT	Gratuity	Card payment with gratuity.
INSP	Instalment	Instalment payment.
LOYT	Loyalty	Loyalty services.
NRES	NoShow	No show after reservation.
PUCO	PurchaseCorporate	Purchase and corporate data.
RECP	RecurringPayment	Recurring payment.
SOAF	SolicitedAvailableFunds	Solicited available funds.
UNAF	UnsolicitedAvailableFunds	Unsolicited available funds.
VCAU	VoiceAuthorisation	Voice authorisation.

2.1.6.1.3.1.2 TransactionCategory <TxCtgy>

Presence: [0..1]

Definition: Category code conform to ISO 18245, related to the type of services or goods the merchant provides for the transaction.

Datatype: [ExternalCardTransactionCategory1Code](#) on page 266

2.1.6.1.3.1.3 SaleReconciliationIdentification <SaleRcncltnId>

Presence: [0..1]

Definition: Unique identification of the sales reconciliation period between the acceptor and the acquirer. This identification might be linked to the identification of the settlement for further verification by the merchant.

Datatype: [Max35Text](#) on page 310

2.1.6.1.3.1.4 SequenceNumberRange <SeqNbRg>

Presence: [0..1]

Definition: Range of sequence numbers on which the globalisation applies.

SequenceNumberRange <SeqNbRg> contains the following **CardSequenceNumberRange1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FirstTransaction <FrstTx>	[0..1]	Text		75
		LastTransaction <LastTx>	[0..1]	Text		75

2.1.6.1.3.1.4.1 FirstTransaction <FrstTx>

Presence: [0..1]

Definition: CardSequenceNumberRange1: FirstTransactionSequenceNumberMessage element to be finalised once feedback from Card SEG has been received.

Datatype: [Max35Text](#) on page 310

2.1.6.1.3.1.4.2 LastTransaction <LastTx>

Presence: [0..1]

Definition: CardSequenceNumberRange1: LastTransactionSequenceNumberMessage element to be finalised once feedback from Card SEG has been received.

Datatype: [Max35Text on page 310](#)

2.1.6.1.3.1.5 TransactionDateRange <TxDtRg>

Presence: [0..1]

Definition: Date range on which the globalisation applies.

TransactionDateRange <TxDtRg> contains one of the following elements (see [DateOrDateTimePeriod1Choice on page 145](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Date <Dt>	[1..1]	±		145
	Or}	DateTime <DtTm>	[1..1]	±		145

2.1.6.1.3.2 Individual <Indv>

Presence: [1..1]

Definition: Card transaction details for the individual transaction, as recorded at the POI (point of interaction).

Individual <Indv> contains the following **CardIndividualTransaction2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ICCRRelatedData <ICCRltdData>	[0..1]	Text		78
		PaymentContext <PmtCntxt>	[0..1]			78
		CardPresent <CardPres>	[0..1]	Indicator		78
		CardholderPresent <CrhdldrPres>	[0..1]	Indicator		79
		OnLineContext <OnLineCntxt>	[0..1]	Indicator		79
		AttendanceContext <AttdncCntxt>	[0..1]	CodeSet		79
		TransactionEnvironment <TxEnvnt>	[0..1]	CodeSet		79
		TransactionChannel <TxChanl>	[0..1]	CodeSet		79
		AttendantMessageCapable <AttdntMsgCpbl>	[0..1]	Indicator		80
		AttendantLanguage <AttdntLang>	[0..1]	CodeSet		80
		CardDataEntryMode <CardDataNtryMd>	[1..1]	CodeSet		80
		FallbackIndicator <FlbckInd>	[0..1]	Indicator		81
		AuthenticationMethod <AuthntcnMtd>	[0..1]			81
		AuthenticationMethod <AuthntcnMtd>	[1..1]	CodeSet		81
		AuthenticationEntity <AuthntcnNtty>	[1..1]	CodeSet		82
		AdditionalService <AddtlSvc>	[0..1]	CodeSet		82
		TransactionCategory <TxCtgy>	[0..1]	CodeSet		82
		SaleReconciliationIdentification <SaleRcncitnId>	[0..1]	Text		82
		SaleReferenceNumber <SaleRefNb>	[0..1]	Text		83
		RePresentmentReason <RePresntmntRsn>	[0..1]	CodeSet		83
		SequenceNumber <SeqNb>	[0..1]	Text		83
		TransactionIdentification <TxId>	[0..1]	±		83
		Product <Pdct>	[0..1]			83
		ProductCode <PdctCd>	[1..1]	Text		84
		UnitOfMeasure <UnitOfMeasr>	[0..1]	CodeSet		84
		ProductQuantity <PdctQty>	[0..1]	Quantity		86
		UnitPrice <UnitPric>	[0..1]	Amount		86
		ProductAmount <PdctAmt>	[0..1]	Amount		86
		TaxType <TaxTp>	[0..1]	Text		86
		AdditionalProductInformation <AddtlPdctInf>	[0..1]	Text		86

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ValidationDate <VldtnDt>	[0..1]	Date		86
		ValidationSequenceNumber <VldtnSeqNb>	[0..1]	Text		86

2.1.6.1.3.2.1 ICCRelatedData <ICCRltdData>

Presence: [0..1]

Definition: Data related to an integrated circuit card application.

Datatype: [Max1025Text](#) on page 308

2.1.6.1.3.2.2 PaymentContext <PmtCntxt>

Presence: [0..1]

Definition: Context of the card payment transaction.

PaymentContext <PmtCntxt> contains the following **PaymentContext3** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CardPresent <CardPres>	[0..1]	Indicator		78
		CardholderPresent <CrdhldrPres>	[0..1]	Indicator		79
		OnLineContext <OnLineCntxt>	[0..1]	Indicator		79
		AttendanceContext <AttdncCntxt>	[0..1]	CodeSet		79
		TransactionEnvironment <TxEnvt>	[0..1]	CodeSet		79
		TransactionChannel <TxChan/ >	[0..1]	CodeSet		79
		AttendantMessageCapable <AttdntMsgCpbl>	[0..1]	Indicator		80
		AttendantLanguage <AttdntLang>	[0..1]	CodeSet		80
		CardDataEntryMode <CardDataNtryMd>	[1..1]	CodeSet		80
		FallbackIndicator <FlbckInd>	[0..1]	Indicator		81
		AuthenticationMethod <AuthntcnMtd>	[0..1]			81
		AuthenticationMethod <AuthntcnMtd>	[1..1]	CodeSet		81
		AuthenticationEntity <AuthntcnNtty>	[1..1]	CodeSet		82

2.1.6.1.3.2.2.1 CardPresent <CardPres>

Presence: [0..1]

Definition: Indicates whether the transaction has been initiated by a card physically present or not.

Datatype: One of the following values must be used (see [TrueFalseIndicator](#) on page 306):

- *Meaning When True:* True
- *Meaning When False:* False

2.1.6.1.3.2.2.2 CardholderPresent <CrhdldrPres>*Presence:* [0..1]*Definition:* Indicates whether the transaction has been initiated in presence of the cardholder or not.*Datatype:* One of the following values must be used (see [TrueFalseIndicator on page 306](#)):

- *Meaning When True:* True
- *Meaning When False:* False

2.1.6.1.3.2.2.3 OnLineContext <OnLineCntxt>*Presence:* [0..1]*Definition:* On-line or off-line context of the transaction.*Datatype:* One of the following values must be used (see [TrueFalseIndicator on page 306](#)):

- *Meaning When True:* True
- *Meaning When False:* False

2.1.6.1.3.2.2.4 AttendanceContext <AttdncCntxt>*Presence:* [0..1]*Definition:* Human attendance at the POI location during the transaction.*Datatype:* [AttendanceContext1Code on page 245](#)

CodeName	Name	Definition
ATTD	Attended	Attended payment, with an attendant.
SATT	SemiAttended	Semi-attended, including self checkout. An attendant supervises several payment, and could be called to help the cardholder.
UATT	Unattended	Unattended payment, no attendant present.

2.1.6.1.3.2.2.5 TransactionEnvironment <TxEnvnt>*Presence:* [0..1]*Definition:* Indicates the environment of the transaction.*Datatype:* [TransactionEnvironment1Code on page 294](#)

CodeName	Name	Definition
MERC	Merchant	Merchant environment.
PRIV	Private	Private environment.
PUBL	Public	Public environment.

2.1.6.1.3.2.2.6 TransactionChannel <TxChanl>*Presence:* [0..1]*Definition:* Identifies the type of the communication channels used by the cardholder to the acceptor system.

Datatype: [TransactionChannel1Code on page 293](#)

CodeName	Name	Definition
MAIL	MailOrder	Mail order.
TLPH	TelephoneOrder	Telephone order.
ECOM	ElectronicCommerce	Electronic commerce.
TVPY	TelevisionPayment	Payment on television.

2.1.6.1.3.2.2.7 AttendantMessageCapable <AtndntMsgCpbl>

Presence: [0..1]

Definition: Indicates whether a message can be sent or not on an attendant display (attendant display present or not).

Datatype: One of the following values must be used (see [TrueFalseIndicator on page 306](#)):

- *Meaning When True:* True
- *Meaning When False:* False

2.1.6.1.3.2.2.8 AttendantLanguage <AtndntLang>

Presence: [0..1]

Definition: Language used to display messages to the attendant.

Datatype: [ISO2ALanguageCode on page 280](#)

2.1.6.1.3.2.2.9 CardDataEntryMode <CardDataNtryMd>

Presence: [1..1]

Definition: Entry mode of the card data.

Datatype: [CardDataReading1Code on page 250](#)

CodeName	Name	Definition
TAGC	Tag	Tag reading capabilities (RFID, etc.).
PHYS	Physical	Keyboard entry or OCR reading of embossing or printed data, either at time of transaction or after the event.
BRCD	BarCode	Bar code.
MGST	MagneticStripe	Magnetic stripe.
CICC	ICC	ICC (Integrated Circuit Card) with contact containing software applications conform to ISO 7816.
DFLE	AccountData	Account data on file.
CTLS	ProximityReader	Contactless proximity reader.
ECTL	EMVProximityReader	Contactless proximity reader, with application conform to the standard EMV (standard initiated by Europay, Mastercard and Visa).

2.1.6.1.3.2.2.10 FallbackIndicator <FllbckInd>

Presence: [0..1]

Definition: Indicator of a card entry mode fallback.

Datatype: One of the following values must be used (see [TrueFalseIndicator](#) on page 306):

- *Meaning When True:* True
- *Meaning When False:* False

2.1.6.1.3.2.2.11 AuthenticationMethod <AuthntcnMtd>

Presence: [0..1]

Definition: Method used to authenticate a cardholder.

AuthenticationMethod <AuthntcnMtd> contains the following **CardholderAuthentication2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AuthenticationMethod <AuthntcnMtd>	[1..1]	CodeSet		81
		AuthenticationEntity <AuthntcnNtty>	[1..1]	CodeSet		82

2.1.6.1.3.2.2.11.1 AuthenticationMethod <AuthntcnMtd>

Presence: [1..1]

Definition: Method used to authenticate the cardholder.

Datatype: [AuthenticationMethod1Code](#) on page 247

CodeName	Name	Definition
UKNW	UnknownMethod	Authentication method is performed unknown.
BYPS	Bypass	Authentication bypassed by the merchant.
NPIN	OnLinePIN	On-line PIN authentication (Personal Identification Number).
FPIN	OfflinePIN	Off-line PIN authentication (Personal Identification Number).
CPSG	SignatureCapture	Electronic signature capture (handwritten signature).
PPSG	PaperSignature	Handwritten paper signature.
MANU	ManualVerification	Manual verification, for example passport or drivers license.
MERC	MerchantAuthentication	Merchant-related authentication.
SCRT	SecureCertificate	Electronic commerce transaction secured with the X.509 certificate of a customer.
SNCT	SecureNoCertificate	Secure electronic transaction without cardholder certificate.
SCNL	SecuredChannel	Channel-encrypted transaction.

2.1.6.1.3.2.2.11.2 AuthenticationEntity <AuthntcnNtty>*Presence:* [1..1]*Definition:* Entity or object in charge of verifying the cardholder authenticity.*Datatype:* [AuthenticationEntity1Code on page 246](#)

CodeName	Name	Definition
ICCD	ICC	Application in the chip card (Integrated Circuit Card), for instance an offline PIN verification.
AGNT	AuthorisedAgent	Authorisation agent of the issuer.
MERC	Merchant	Merchant (for example signature verification by the attendant).

2.1.6.1.3.2.3 AdditionalService <AddtlSvc>*Presence:* [0..1]*Definition:* Service in addition to the main service.*Datatype:* [CardPaymentServiceType2Code on page 254](#)

CodeName	Name	Definition
AGGR	Aggregation	Aggregation of low payments.
DCCV	DCC	Dynamic currency conversion (DCC).
GRTT	Gratuity	Card payment with gratuity.
INSP	Instalment	Instalment payment.
LOYT	Loyalty	Loyalty services.
NRES	NoShow	No show after reservation.
PUCO	PurchaseCorporate	Purchase and corporate data.
RECP	RecurringPayment	Recurring payment.
SOAF	SolicitedAvailableFunds	Solicited available funds.
UNAF	UnsolicitedAvailableFunds	Unsolicited available funds.
VCAU	VoiceAuthorisation	Voice authorisation.

2.1.6.1.3.2.4 TransactionCategory <TxCtgy>*Presence:* [0..1]*Definition:* Category code conform to ISO 18245, related to the type of services or goods the merchant provides for the transaction.

This element is also known as the MerchantCategoryCode.

Datatype: [ExternalCardTransactionCategory1Code on page 266](#)**2.1.6.1.3.2.5 SaleReconciliationIdentification <SaleRcncldId>***Presence:* [0..1]

Definition: Unique identification of the sales reconciliation period between the acceptor and the acquirer. This identification might be linked to the identification of the settlement for further verification by the merchant.

Datatype: [Max35Text on page 310](#)

2.1.6.1.3.2.6 SaleReferenceNumber <SaleRefNb>

Presence: [0..1]

Definition: Unique reference of the sales as provided by the merchant.

Datatype: [Max35Text on page 310](#)

2.1.6.1.3.2.7 RePresentmentReason <RePresntmntRsn>

Presence: [0..1]

Definition: Reason for representment of a card transaction.

Datatype: [ExternalRePresentmentReason1Code on page 277](#)

2.1.6.1.3.2.8 SequenceNumber <SeqNb>

Presence: [0..1]

Definition: Sequential number of the card transaction, as assigned by the POI (Point of Interaction).

Usage: The sequential number is increased incrementally for each transaction.

Datatype: [Max35Text on page 310](#)

2.1.6.1.3.2.9 TransactionIdentification <TxId>

Presence: [0..1]

Definition: Identification of the transaction assigned by the POI (Point Of Interaction).

TransactionIdentification <TxId> contains the following elements (see [TransactionIdentifier1 on page 181](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TransactionDateTime <TxDtTm>	[1..1]	DateTime		181
		TransactionReference <TxRef>	[1..1]	Text		181

2.1.6.1.3.2.10 Product <Pdct>

Presence: [0..1]

Definition: Product purchased with the transaction.

Product <Pdct> contains the following **Product2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ProductCode <PdctCd>	[1..1]	Text		84
		UnitOfMeasure <UnitOfMeasr>	[0..1]	CodeSet		84
		ProductQuantity <PdctQty>	[0..1]	Quantity		86
		UnitPrice <UnitPric>	[0..1]	Amount		86
		ProductAmount <PdctAmt>	[0..1]	Amount		86
		TaxType <TaxTp>	[0..1]	Text		86
		AdditionalProductInformation <AddtlPdctInf>	[0..1]	Text		86

2.1.6.1.3.2.10.1 ProductCode <PdctCd>

Presence: [1..1]

Definition: Product code of the item purchased.

Datatype: Max70Text on page 311

2.1.6.1.3.2.10.2 UnitOfMeasure <UnitOfMeasr>

Presence: [0..1]

Definition: Unit of measure of the item purchased.

Datatype: UnitOfMeasure1Code on page 295

CodeName	Name	Definition
PIEC	Piece	Standard length of cloth, wallpaper, as an item for sale or amount of a substance.
TONS	Ton	Measure of weight, in Britain 2240lb (long ton)and in the US 2000lb (short ton).
FOOT	Foot	Unit of length equal to 1/3 yard.
GBGA	GBGallon	Unit of volume that is equal to 8 pints.
USGA	USGallon	Unit of volume that is equal to 8 pints.
GRAM	Gram	Unit of measure that is equal to a 1, 000th of a kilo.
INCH	Inch	Measure of length equal to 2.54 cm.
KILO	Kilogram	Basic unit of mass in the SI system, 1000 grams.
PUND	Pound	Unit of weight equal to 0.454 kilograms.
METR	Metre	Unit of length in the metric system, equal to 39.37 inches.
CMET	Centimetre	Unit of measure that is equal to one hundredth of a metre.

CodeName	Name	Definition
MMET	Millimetre	Unit of measure that is a thousandth of one metre.
LITR	Litre	Unit of volume that is equal to a thousand cubic centimetres.
CELI	Centilitre	Unit of volume that is equal to one hundredth of a litre.
MILI	MilliLitre	Unit of volume that is equal to one thousandth of a litre.
GBOU	GBOunce	Unit of weight equal to a sixteenth of a pound.
USOU	USOunce	Unit of weight equal to a sixteenth of a pound.
GBQA	GBQuart	Unit of volume that is equal to 2 pints.
USQA	USQuart	Unit of volume that is equal to 2 pints.
GBPI	GBPint	Unit of volume that is equal to 568 cubic centimetres.
USPI	USPint	Unit of volume that is equal to 473 cubic centimetres.
MILE	Mile	Unit of length equal to 1, 760 yards.
KMET	Kilometre	Unit of measure that is equal to 1, 000 meters.
YARD	Yard	Unit of length equal to 3 feet or 0.9144 metre.
SQKI	SquareKilometre	Measure of a surface, one kilometre by one kilometre.
HECT	Hectare	Unit of measure that is equal to 10, 000 square meters.
ARES	Are	Unit of measure equal to a 100 square meters.
SMET	SquareMetre	Measure of a surface, one metre by one metre.
SCMT	SquareCentimetre	Measure of a surface, one centimetre by one centimetre.
SMIL	SquareMillimetre	Measure of a surface, one millimetre by one millimetre.
SQMI	SquareMile	Measure of a surface, one mile by one mile.
SQYA	SquareYard	Measure of a surface, one yard by one yard.
SQFO	SquareFoot	Measure of a surface, one foot by one foot.
SQIN	SquareInch	Measure of a surface, one inch by one inch.
ACRE	Acre	Unit of measure equal to 4, 840 square yards.

2.1.6.1.3.2.10.3 ProductQuantity <PdctQty>

Presence: [0..1]

Definition: Product quantity.

Datatype: DecimalNumber on page 306

2.1.6.1.3.2.10.4 UnitPrice <UnitPric>

Presence: [0..1]

Definition: Price per unit of product.

Datatype: ImpliedCurrencyAndAmount on page 243

2.1.6.1.3.2.10.5 ProductAmount <PdctAmt>

Presence: [0..1]

Definition: Monetary value of purchased product.

Datatype: ImpliedCurrencyAndAmount on page 243

2.1.6.1.3.2.10.6 TaxType <TaxTp>

Presence: [0..1]

Definition: Information on tax paid on the product.

Datatype: Max35Text on page 310

2.1.6.1.3.2.10.7 AdditionalProductInformation <AddtlPdctInf>

Presence: [0..1]

Definition: Additional information related to the product.

Datatype: Max35Text on page 310

2.1.6.1.3.2.11 ValidationDate <VldtnDt>

Presence: [0..1]

Definition: Date when the deposit was validated by the financial institution that collected the cash.

Datatype: ISODate on page 303

2.1.6.1.3.2.12 ValidationSequenceNumber <VldtnSeqNb>

Presence: [0..1]

Definition: Sequential number of the validation of the cash deposit.

Usage: The sequential number is increased incrementally for each transaction.

Datatype: Max35Text on page 310

2.1.6.1.4 PrePaidAccount <PrePdAcct>

Presence: [0..1]

Definition: Prepaid account for the transfer or loading of an amount of money.

PrePaidAccount <PrePdAcct> contains the following elements (see [CashAccount38](#) on page 34 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		34
		Type <Tp>	[0..1]	±		34
		Currency <Ccy>	[0..1]	CodeSet		34
		Name <Nm>	[0..1]	Text		35
		Proxy <Prxy>	[0..1]	±		35

2.1.6.2 CardEntry4

Definition: Card transaction entry.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Card <Card>	[0..1]			89
		PlainCardData <PlainCardData>	[0..1]			90
		PAN <PAN>	[1..1]	Text		91
		CardSequenceNumber <CardSeqNb>	[0..1]	Text		91
		EffectiveDate <FctvDt>	[0..1]	YearMonth		91
		ExpiryDate <XpryDt>	[1..1]	YearMonth		91
		ServiceCode <SvcCd>	[0..1]	Text		91
		TrackData <TrckData>	[0..*]			92
		TrackNumber <TrckNb>	[0..1]	Text		92
		TrackValue <TrckVal>	[1..1]	Text		92
		CardSecurityCode <CardSctyCd>	[0..1]			92
		CSCManagement <CSCMgmt>	[1..1]	CodeSet		92
		CSCValue <CSCVal>	[0..1]	Text		93
		CardCountryCode <CardCtryCd>	[0..1]	Text		93
		CardBrand <CardBrnd>	[0..1]	±		93
		AdditionalCardData <AddtlCardData>	[0..1]	Text		93
		POI <POI>	[0..1]			93
		Identification <Id>	[1..1]	±		94
		SystemName <SysNm>	[0..1]	Text		95
		GroupIdentification <Grpld>	[0..1]	Text		95
		Capabilities <Cpblties>	[0..1]			95
		CardReadingCapabilities <CardRdngCpblties>	[0..*]	CodeSet		95
		CardholderVerificationCapabilities <CrdhldrVrfctnCpblties>	[0..*]	CodeSet		96
		OnLineCapabilities <OnLineCpblties>	[0..1]	CodeSet		96
		DisplayCapabilities <DispCpblties>	[0..*]			97
		DisplayType <DispTp>	[1..1]	CodeSet		97
		NumberOfLines <NbOfLines>	[1..1]	Text		97
		LineWidth <LineWidth>	[1..1]	Text		97
		PrintLineWidth <PrtLineWidth>	[0..1]	Text		97
		Component <Cmpnt>	[0..*]			97
		POIComponentType <POICmpntTp>	[1..1]	CodeSet		98

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ManufacturerIdentification <ManfctrId>	[0..1]	Text		98
		Model <Mdl>	[0..1]	Text		98
		VersionNumber <VrsnNb>	[0..1]	Text		98
		SerialNumber <SrlNb>	[0..1]	Text		99
		ApprovalNumber <ApprvlNb>	[0..*]	Text		99
		AggregatedEntry <AggtdNtry>	[0..1]			99
		AdditionalService <AddtlSvc>	[0..1]	CodeSet		99
		TransactionCategory <TxCtgy>	[0..1]	CodeSet		100
		SaleReconciliationIdentification <SaleRcnclnId>	[0..1]	Text		100
		SequenceNumberRange <SeqNbRg>	[0..1]			100
		FirstTransaction <FrstTx>	[0..1]	Text		100
		LastTransaction <LastTx>	[0..1]	Text		100
		TransactionDateRange <TxDtRg>	[0..1]	±		101
		PrePaidAccount <PrePdAcct>	[0..1]	±		101

2.1.6.2.1 Card <Card>

Presence: [0..1]

Definition: Electronic money product that provides the cardholder with a portable and specialised computer device, which typically contains a microprocessor.

Card <Card> contains the following **PaymentCard4** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PlainCardData <PlainCardData>	[0..1]			90
		PAN <PAN>	[1..1]	Text		91
		CardSequenceNumber <CardSeqNb>	[0..1]	Text		91
		EffectiveDate <FctvDt>	[0..1]	YearMonth		91
		ExpiryDate <XpryDt>	[1..1]	YearMonth		91
		ServiceCode <SvcCd>	[0..1]	Text		91
		TrackData <TrckData>	[0..*]			92
		TrackNumber <TrckNb>	[0..1]	Text		92
		TrackValue <TrckVal>	[1..1]	Text		92
		CardSecurityCode <CardSctyCd>	[0..1]			92
		CSCManagement <CSCMgmt>	[1..1]	CodeSet		92
		CSCValue <CSCVal>	[0..1]	Text		93
		CardCountryCode <CardCtryCd>	[0..1]	Text		93
		CardBrand <CardBrnd>	[0..1]	±		93
		AdditionalCardData <AddtlCardData>	[0..1]	Text		93

2.1.6.2.1.1 PlainCardData <PlainCardData>

Presence: [0..1]

Definition: Sensitive data associated with the card performing the transaction.

PlainCardData <PlainCardData> contains the following **PlainCardData1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PAN <PAN>	[1..1]	Text		91
		CardSequenceNumber <CardSeqNb>	[0..1]	Text		91
		EffectiveDate <FctvDt>	[0..1]	YearMonth		91
		ExpiryDate <XpryDt>	[1..1]	YearMonth		91
		ServiceCode <SvcCd>	[0..1]	Text		91
		TrackData <TrckData>	[0..*]			92
		TrackNumber <TrckNb>	[0..1]	Text		92
		TrackValue <TrckVal>	[1..1]	Text		92
		CardSecurityCode <CardSctyCd>	[0..1]			92
		CSCManagement <CSCMgmt>	[1..1]	CodeSet		92
		CSCValue <CSCVal>	[0..1]	Text		93

2.1.6.2.1.1.1 PAN <PAN>

Presence: [1..1]

Definition: Primary Account Number (PAN) of the card, or card number.

Datatype: Min8Max28NumericText on page 311

2.1.6.2.1.1.2 CardSequenceNumber <CardSeqNb>

Presence: [0..1]

Definition: Identify a card inside a set of cards with the same card number (PAN).

Datatype: Min2Max3NumericText on page 311

2.1.6.2.1.1.3 EffectiveDate <FctvDt>

Presence: [0..1]

Definition: Date as from which the card can be used.

Datatype: ISOYearMonth on page 312

2.1.6.2.1.1.4 ExpiryDate <XpryDt>

Presence: [1..1]

Definition: Expiry date of the card.

Datatype: ISOYearMonth on page 312

2.1.6.2.1.1.5 ServiceCode <SvcCd>

Presence: [0..1]

Definition: Services attached to the card, as defined in ISO 7813.

Datatype: Exact3NumericText on page 307

2.1.6.2.1.1.6 TrackData <TrckData>*Presence:* [0..*]*Definition:* Magnetic track or equivalent payment card data.**TrackData <TrckData>** contains the following **TrackData1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TrackNumber <TrckNb>	[0..1]	Text		92
		TrackValue <TrckVal>	[1..1]	Text		92

2.1.6.2.1.1.6.1 TrackNumber <TrckNb>*Presence:* [0..1]*Definition:* Track number of the card.*Datatype:* Exact1NumericText on page 307**2.1.6.2.1.1.6.2 TrackValue <TrckVal>***Presence:* [1..1]*Definition:* Card track content or equivalent.*Datatype:* Max140Text on page 308**2.1.6.2.1.1.7 CardSecurityCode <CardSctyCd>***Presence:* [0..1]*Definition:* Card security code (CSC) associated with the card performing the transaction.**CardSecurityCode <CardSctyCd>** contains the following **CardSecurityInformation1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CSCManagement <CSCMgmt>	[1..1]	CodeSet		92
		CSCValue <CSCVal>	[0..1]	Text		93

2.1.6.2.1.1.7.1 CSCManagement <CSCMgmt>*Presence:* [1..1]*Definition:* Card security code (CSC) management associated with the transaction.*Datatype:* CSCManagement1Code on page 260

CodeName	Name	Definition
PRST	CSCPresent	Card security code present.
BYPS	CSCByPass	Card security code by-passed or not provided by the merchant.
UNRD	CSCUnread	Card security code unreadable.
NCSC	NoCSC	No card security code imprint.

2.1.6.2.1.1.7.2 CSCValue <CSCVal>

Presence: [0..1]

Definition: Card security code (CSC).

Datatype: [Min3Max4NumericText on page 311](#)

2.1.6.2.1.2 CardCountryCode <CardCtryCd>

Presence: [0..1]

Definition: Country code assigned to the card by the card issuer.

Datatype: [Exact3NumericText on page 307](#)

2.1.6.2.1.3 CardBrand <CardBrnd>

Presence: [0..1]

Definition: Brand name of the card.

CardBrand <CardBrnd> contains the following elements (see [GenericIdentification1 on page 160](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		161
		SchemeName <SchmeNm>	[0..1]	Text		161
		Issuer <Issr>	[0..1]	Text		161

2.1.6.2.1.4 AdditionalCardData <AddtlCardData>

Presence: [0..1]

Definition: Additional card issuer specific data.

Datatype: [Max70Text on page 311](#)

2.1.6.2.2 POI <POI>

Presence: [0..1]

Definition: Physical or logical card payment terminal containing software and hardware components.

POI <POI> contains the following **PointOfInteraction1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		94
		SystemName <SysNm>	[0..1]	Text		95
		GroupIdentification <GrpId>	[0..1]	Text		95
		Capabilities <Cpblties>	[0..1]			95
		CardReadingCapabilities <CardRdngCpblties>	[0..*]	CodeSet		95
		CardholderVerificationCapabilities <CrdhldrVrfctnCpblties>	[0..*]	CodeSet		96
		OnLineCapabilities <OnLineCpblties>	[0..1]	CodeSet		96
		DisplayCapabilities <DispCpblties>	[0..*]			97
		DisplayType <DispTp>	[1..1]	CodeSet		97
		NumberOfLines <NbOfLines>	[1..1]	Text		97
		LineWidth <LineWidth>	[1..1]	Text		97
		PrintLineWidth <PrtLineWidth>	[0..1]	Text		97
		Component <Cmpnt>	[0..*]			97
		POIComponentType <POICmpntTp>	[1..1]	CodeSet		98
		ManufacturerIdentification <ManfctrId>	[0..1]	Text		98
		Model <Mdl>	[0..1]	Text		98
		VersionNumber <VrsnNb>	[0..1]	Text		98
		SerialNumber <SrInb>	[0..1]	Text		99
		ApprovalNumber <ApprvInb>	[0..*]	Text		99

2.1.6.2.2.1 Identification <Id>

Presence: [1..1]

Definition: Identification of the POI (Point Of Interaction) for the acquirer or its agent.

Identification <Id> contains the following elements (see [GenericIdentification32](#) on page 159 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		159
		Type <Tp>	[0..1]	CodeSet		160
		Issuer <Issr>	[0..1]	CodeSet		160
		ShortName <ShrtNm>	[0..1]	Text		160

2.1.6.2.2.2 SystemName <SysNm>*Presence:* [0..1]*Definition:* Common name assigned by the acquirer to the POI system.*Datatype:* [Max70Text on page 311](#)**2.1.6.2.2.3 GroupIdentification <GrpId>***Presence:* [0..1]*Definition:* Identifier assigned by the merchant identifying a set of POI terminals performing some categories of transactions.*Datatype:* [Max35Text on page 310](#)**2.1.6.2.2.4 Capabilities <Cpblties>***Presence:* [0..1]*Definition:* Capabilities of the POI performing the transaction.**Capabilities <Cpblties>** contains the following **PointOfInteractionCapabilities1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CardReadingCapabilities <CardRdngCpblties>	[0..*]	CodeSet		95
		CardholderVerificationCapabilities <CrdhldrVrfctnCpblties>	[0..*]	CodeSet		96
		OnLineCapabilities <OnLineCpblties>	[0..1]	CodeSet		96
		DisplayCapabilities <DispCpblties>	[0..*]			97
		DisplayType <DispTp>	[1..1]	CodeSet		97
		NumberOfLines <NbOfLines>	[1..1]	Text		97
		LineWidth <LineWidth>	[1..1]	Text		97
		PrintLineWidth <PrtLineWidth>	[0..1]	Text		97

2.1.6.2.2.4.1 CardReadingCapabilities <CardRdngCpblties>*Presence:* [0..*]*Definition:* Card reading capabilities of the POI performing the transaction.*Datatype:* [CardDataReading1Code on page 250](#)

CodeName	Name	Definition
TAGC	Tag	Tag reading capabilities (RFID, etc.).
PHYS	Physical	Keyboard entry or OCR reading of embossing or printed data, either at time of transaction or after the event.
BRCD	BarCode	Bar code.
MGST	MagneticStripe	Magnetic stripe.
CICC	ICC	ICC (Integrated Circuit Card) with contact containing software applications conform to ISO 7816.

CodeName	Name	Definition
DFLE	AccountData	Account data on file.
CTLS	ProximityReader	Contactless proximity reader.
ECTL	EMVProximityReader	Contactless proximity reader, with application conform to the standard EMV (standard initiated by Europay, Mastercard and Visa).

2.1.6.2.2.4.2 CardholderVerificationCapabilities <CrdhldrVrfctnCpblties>

Presence: [0..*]

Definition: Cardholder verification capabilities of the POI performing the transaction.

Datatype: [CardholderVerificationCapability1Code on page 252](#)

CodeName	Name	Definition
MNSG	ManualSignature	Manual signature verification.
NPIN	OnLinePIN	Online PIN (Personal Identification Number).
FCPN	OfflinePINCLEAR	Offline PIN in clear (Personal Identification Number).
FEPN	OfflinePINEncrypted	Offline PIN encrypted (Personal Identification Number).
FDSG	OfflineDigitalSignature	Offline digital signature analysis.
FBIO	OfflineBiometrics	Offline biometrics.
MNVR	ManualVerification	Other manual verification, for example passport or drivers license.
FBIG	OfflineBiographics	Offline biographics.
APKI	AccountDigitalSignature	Account based digital signature.
PKIS	PKISignature	PKI (Public Key Infrastructure) based digital signature.
CHDT	CardholderData	Cardholder authentication data.
SCEC	SecureElectronicCommerce	Three domain secure (three domain secure authentication of the cardholder).

2.1.6.2.2.4.3 OnLineCapabilities <OnLineCpblties>

Presence: [0..1]

Definition: On-line and off-line capabilities of the POI.

Datatype: [OnLineCapability1Code on page 281](#)

CodeName	Name	Definition
OFLN	OffLine	Off-line only capable.
ONLN	OnLine	On-line only capable.
SMON	SemiOffLine	Off-line capable with possible on-line requests to the acquirer.

2.1.6.2.2.4.4 DisplayCapabilities <DispCpblties>

Presence: [0..*]

Definition: Capabilities of the display components performing the transaction.

DisplayCapabilities <DispCpblties> contains the following **DisplayCapabilities1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DisplayType <DispTp>	[1..1]	CodeSet		97
		NumberOfLines <NbOfLines>	[1..1]	Text		97
		LineWidth <LineWidth>	[1..1]	Text		97

2.1.6.2.2.4.4.1 DisplayType <DispTp>

Presence: [1..1]

Definition: Type of display (for example merchant or cardholder).

Datatype: [UserInterface2Code on page 301](#)

CodeName	Name	Definition
MDSP	MerchantDisplay	Merchant display or interface.
CDSP	CardholderDisplay	Cardholder display or interface.

2.1.6.2.2.4.4.2 NumberOfLines <NbOfLines>

Presence: [1..1]

Definition: Number of lines of the display component.

Datatype: [Max3NumericText on page 310](#)

2.1.6.2.2.4.4.3 LineWidth <LineWidth>

Presence: [1..1]

Definition: Number of columns of the display component.

Datatype: [Max3NumericText on page 310](#)

2.1.6.2.2.4.5 PrintLineWidth <PrtLineWidth>

Presence: [0..1]

Definition: Number of columns of the printer component.

Datatype: [Max3NumericText on page 310](#)

2.1.6.2.2.5 Component <Cmpnt>

Presence: [0..*]

Definition: Data related to a component of the POI performing the transaction.

Component <Cmpnt> contains the following **PointOfInteractionComponent1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		POIComponentType <POICmpntTp>	[1..1]	CodeSet		98
		ManufacturerIdentification <ManfctrId>	[0..1]	Text		98
		Model <Mdl>	[0..1]	Text		98
		VersionNumber <VrsnNb>	[0..1]	Text		98
		SerialNumber <SrlNb>	[0..1]	Text		99
		ApprovalNumber <ApprvlNb>	[0..*]	Text		99

2.1.6.2.2.5.1 POIComponentType <POICmpntTp>

Presence: [1..1]

Definition: Type of component belonging to a POI Terminal.

Datatype: [POIComponentType1Code](#) on page 286

CodeName	Name	Definition
SOFT	Soft	Payment or other software application.
EMVK	EMVKernel	EMV application kernel (EMV is the chip card specifications initially defined by Eurocard, Mastercard and Visa).
EMVO	EMVLevel1	EMV physical interface (EMV is the chip card specifications initially defined by Eurocard, Mastercard and Visa).
MRIT	MerchantInterface	Merchant interface.
CHIT	CardholderInterface	Cardholder Interface.
SECM	SecureModule	Security module.
PEDV	PINEntryDevice	Personal identification number (or PIN) entry device (PED).

2.1.6.2.2.5.2 ManufacturerIdentification <ManfctrId>

Presence: [0..1]

Definition: Identification of the software, hardware or system provider of the POI component.

Datatype: [Max35Text](#) on page 310

2.1.6.2.2.5.3 Model <Mdl>

Presence: [0..1]

Definition: Identification of a model of POI component for a given manufacturer.

Datatype: [Max35Text](#) on page 310

2.1.6.2.2.5.4 VersionNumber <VrsnNb>

Presence: [0..1]

Definition: Version of component belonging to a given model.

Datatype: [Max16Text on page 309](#)

2.1.6.2.2.5.5 SerialNumber <SrlNb>

Presence: [0..1]

Definition: Serial number of a component.

Datatype: [Max35Text on page 310](#)

2.1.6.2.2.5.6 ApprovalNumber <ApprvINb>

Presence: [0..*]

Definition: Unique approval number for a component, delivered by a certification body.

Usage: More than one approval number could be present, when assigned by different bodies. The certification body identification must be provided within the approval number (for example at the beginning of the value).

Datatype: [Max70Text on page 311](#)

2.1.6.2.3 AggregatedEntry <AggtdNtry>

Presence: [0..1]

Definition: Card entry details, based on card transaction aggregated data performed by the account servicer.

AggregatedEntry <AggtdNtry> contains the following **CardAggregated2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AdditionalService <AddtlSvc>	[0..1]	CodeSet		99
		TransactionCategory <TxCtgy>	[0..1]	CodeSet		100
		SaleReconciliationIdentification <SaleRcncltnId>	[0..1]	Text		100
		SequenceNumberRange <SeqNbRg>	[0..1]			100
		FirstTransaction <FrstTx>	[0..1]	Text		100
		LastTransaction <LastTx>	[0..1]	Text		100
		TransactionDateRange <TxDtRg>	[0..1]	±		101

2.1.6.2.3.1 AdditionalService <AddtlSvc>

Presence: [0..1]

Definition: Service in addition to the main service.

Datatype: [CardPaymentServiceType2Code on page 254](#)

CodeName	Name	Definition
AGGR	Aggregation	Aggregation of low payments.
DCCV	DCC	Dynamic currency conversion (DCC).
GRTT	Gratuity	Card payment with gratuity.
INSP	Instalment	Instalment payment.

CodeName	Name	Definition
LOYT	Loyalty	Loyalty services.
NRES	NoShow	No show after reservation.
PUCO	PurchaseCorporate	Purchase and corporate data.
RECP	RecurringPayment	Recurring payment.
SOAF	SolicitedAvailableFunds	Solicited available funds.
UNAF	UnsolicitedAvailableFunds	Unsolicited available funds.
VCAU	VoiceAuthorisation	Voice authorisation.

2.1.6.2.3.2 TransactionCategory <TxCtgy>

Presence: [0..1]

Definition: Category code conform to ISO 18245, related to the type of services or goods the merchant provides for the transaction.

Datatype: [ExternalCardTransactionCategory1Code](#) on page 266

2.1.6.2.3.3 SaleReconciliationIdentification <SaleRcncltnId>

Presence: [0..1]

Definition: Unique identification of the sales reconciliation period between the acceptor and the acquirer. This identification might be linked to the identification of the settlement for further verification by the merchant.

Datatype: [Max35Text](#) on page 310

2.1.6.2.3.4 SequenceNumberRange <SeqNbRg>

Presence: [0..1]

Definition: Range of sequence numbers on which the globalisation applies.

SequenceNumberRange <SeqNbRg> contains the following **CardSequenceNumberRange1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FirstTransaction <FrstTx>	[0..1]	Text		100
		LastTransaction <LastTx>	[0..1]	Text		100

2.1.6.2.3.4.1 FirstTransaction <FrstTx>

Presence: [0..1]

Definition: CardSequenceNumberRange1: FirstTransactionSequenceNumberMessage element to be finalised once feedback from Card SEG has been received.

Datatype: [Max35Text](#) on page 310

2.1.6.2.3.4.2 LastTransaction <LastTx>

Presence: [0..1]

Definition: CardSequenceNumberRange1: LastTransactionSequenceNumberMessage element to be finalised once feedback from Card SEG has been received.

Datatype: [Max35Text on page 310](#)

2.1.6.2.3.5 TransactionDateRange <TxDtRg>

Presence: [0..1]

Definition: Date range on which the globalisation applies.

TransactionDateRange <TxDtRg> contains one of the following elements (see [DateOrDateTimePeriod1Choice on page 145](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Date <Dt>	[1..1]	±		145
	Or}	DateTime <DtTm>	[1..1]	±		145

2.1.6.2.4 PrePaidAccount <PrePdAcct>

Presence: [0..1]

Definition: Prepaid account for the transfer or loading of an amount of money.

PrePaidAccount <PrePdAcct> contains the following elements (see [CashAccount38 on page 34](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		34
		Type <Tp>	[0..1]	±		34
		Currency <Ccy>	[0..1]	CodeSet		34
		Name <Nm>	[0..1]	Text		35
		Proxy <Prxy>	[0..1]	±		35

2.1.7 Cash

2.1.7.1 CashDeposit1

Definition: Deposit of an amount of money defined in cash notes and/or coins.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		NoteDenomination <NoteDnmtn>	[1..1]	Amount		101
		NumberOfNotes <NbOfNotes>	[1..1]	Text		102
		Amount <Amt>	[1..1]	Amount		102

2.1.7.1.1 NoteDenomination <NoteDnmtn>

Presence: [1..1]

Definition: Specifies the note or coin denomination, including the currency, such as a 50 euro note.

Datatype: [ActiveCurrencyAndAmount on page 240](#)

2.1.7.1.2 NumberOfNotes <NbOfNotes>

Presence: [1..1]

Definition: Specifies the number of notes of the same denomination in the deposit.

Datatype: [Max15NumericText](#) on page 309

2.1.7.1.3 Amount <Amt>

Presence: [1..1]

Definition: Specifies the total amount of money in the cash deposit, that is the note denomination times the number of notes.

Datatype: [ActiveCurrencyAndAmount](#) on page 240

2.1.8 Cash Entry

2.1.8.1 EntryDetails9

Definition: Identifies the underlying transaction(s) and/or batched entries.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Batch <Btch>	[0..1]			102
		MessageIdentification <MsgId>	[0..1]	Text		103
		PaymentInformationIdentification <PmtInfId>	[0..1]	Text		103
		NumberOfTransactions <NbOfTx>	[0..1]	Text		103
		TotalAmount <TtlAmt>	[0..1]	Amount		103
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		103
		TransactionDetails <TxDtls>	[0..*]	±		103

2.1.8.1.1 Batch <Btch>

Presence: [0..1]

Definition: Provides details on batched transactions.

Batch <Btch> contains the following **BatchInformation2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		MessageIdentification <MsgId>	[0..1]	Text		103
		PaymentInformationIdentification <PmtInfId>	[0..1]	Text		103
		NumberOfTransactions <NbOfTx>	[0..1]	Text		103
		TotalAmount <TtlAmt>	[0..1]	Amount		103
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		103

2.1.8.1.1.1 MessageIdentification <MsgId>*Presence:* [0..1]*Definition:* Point to point reference, as assigned by the sending party, to unambiguously identify the batch of transactions.*Datatype:* [Max35Text on page 310](#)**2.1.8.1.1.2 PaymentInformationIdentification <PmtInfId>***Presence:* [0..1]*Definition:* Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message.*Datatype:* [Max35Text on page 310](#)**2.1.8.1.1.3 NumberOfTransactions <NbOfTx>***Presence:* [0..1]*Definition:* Number of individual transactions included in the batch.*Datatype:* [Max15NumericText on page 309](#)**2.1.8.1.1.4 TotalAmount <TtlAmt>***Presence:* [0..1]*Definition:* Total amount of money reported in the batch entry.*Datatype:* [ActiveOrHistoricCurrencyAndAmount on page 242](#)**2.1.8.1.1.5 CreditDebitIndicator <CdtDbtInd>***Presence:* [0..1]*Definition:* Indicates whether the batch entry is a credit or a debit entry.*Datatype:* [CreditDebitCode on page 260](#)

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

2.1.8.1.2 TransactionDetails <TxDtIs>*Presence:* [0..*]*Definition:* Provides information on the underlying transaction(s).

TransactionDetails <TxDtIs> contains the following elements (see [EntryTransaction10](#) on page 107 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		References <Refs>	[0..1]			111
		MessageIdentification <MsgId>	[0..1]	Text		111
		AccountServicerReference <AcctSvcrRef>	[0..1]	Text		111
		PaymentInformationIdentification <PmtInfId>	[0..1]	Text		112
		InstructionIdentification <InstrId>	[0..1]	Text		112
		EndToEndIdentification <EndToEndId>	[0..1]	Text		112
		UETR <UETR>	[0..1]	IdentifierSet		112
		TransactionIdentification <TxId>	[0..1]	Text		112
		MandateIdentification <MndtId>	[0..1]	Text		112
		ChequeNumber <ChqNb>	[0..1]	Text		113
		ClearingSystemReference <ClrSysRef>	[0..1]	Text		113
		AccountOwnerTransactionIdentification <AcctOwnrTxId>	[0..1]	Text		113
		AccountServicerTransactionIdentification <AcctSvcrTxId>	[0..1]	Text		113
		MarketInfrastructureTransactionIdentification <MktInfstrctrTxId>	[0..1]	Text		113
		ProcessingIdentification <PrctlId>	[0..1]	Text		113
		Proprietary <Prtry>	[0..*]			113
		Type <Tp>	[1..1]	Text		114
		Reference <Ref>	[1..1]	Text		114
		Amount <Amt>	[0..1]	Amount		114
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		114
		AmountDetails <AmtDtIs>	[0..1]	±		114
		Availability <Avlbtty>	[0..*]	±		116
		BankTransactionCode <BkTxCd>	[0..1]	±		117
		Charges <Chrgs>	[0..1]	±		117
		Interest <Intrst>	[0..1]	±		117
		RelatedParties <RltdPties>	[0..1]			118
		InitiatingParty <InitgPty>	[0..1]	±		119
		Debtor <Dbtr>	[0..1]	±		119
		DebtorAccount <DbtrAcct>	[0..1]	±		119

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		UltimateDebtor <UltmtDbtr>	[0..1]	±		120
		Creditor <Cdtr>	[0..1]	±		120
		CreditorAccount <CdtrAcct>	[0..1]	±		120
		UltimateCreditor <UltmtCdtr>	[0..1]	±		121
		TradingParty <TradgPty>	[0..1]	±		121
		Proprietary <Prtry>	[0..*]			121
		Type <Tp>	[1..1]	Text		122
		Party <Pty>	[1..1]	±		122
		RelatedAgents <RltdAgts>	[0..1]			122
		InstructingAgent <InstgAgt>	[0..1]	±		123
		InstructedAgent <InstdAgt>	[0..1]	±		123
		DebtorAgent <DbtrAgt>	[0..1]	±		124
		CreditorAgent <CdtrAgt>	[0..1]	±		124
		IntermediaryAgent1 <IntrmyAgt1>	[0..1]	±		124
		IntermediaryAgent2 <IntrmyAgt2>	[0..1]	±		124
		IntermediaryAgent3 <IntrmyAgt3>	[0..1]	±		125
		ReceivingAgent <RcvgAgt>	[0..1]	±		125
		DeliveringAgent <DlvrAgt>	[0..1]	±		125
		IssuingAgent <IssgAgt>	[0..1]	±		126
		SettlementPlace <SttlmPlc>	[0..1]	±		126
		Proprietary <Prtry>	[0..*]			126
		Type <Tp>	[1..1]	Text		126
		Agent <Agt>	[1..1]	±		127
		LocalInstrument <LclInstrm>	[0..1]			127
	{Or	Code <Cd>	[1..1]	CodeSet		127
	Or}	Proprietary <Prtry>	[1..1]	Text		127
		Purpose <Purp>	[0..1]	±		127
		RelatedRemittanceInformation <RltdRmtInf>	[0..10]	±		128
		RemittanceInformation <RmtInf>	[0..1]	±		128
		RelatedDates <RltdDts>	[0..1]			128
		AcceptanceDateTime <AcceptncDtTm>	[0..1]	DateTime		129

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TradeActivityContractualSettlementDate <TradActvtyCtrctlSttlmDt>	[0..1]	Date		129
		TradeDate <TradDt>	[0..1]	Date		129
		InterbankSettlementDate <IntrBkSttlmDt>	[0..1]	Date		129
		StartDate <StartDt>	[0..1]	Date		129
		EndDate <EndDt>	[0..1]	Date		130
		TransactionDateTime <TxDtTm>	[0..1]	DateTime		130
		Proprietary <Prtry>	[0..*]			130
		Type <Tp>	[1..1]	Text		130
		Date <Dt>	[1..1]	±		130
		RelatedPrice <RltdPric>	[0..1]			130
	{Or	DealPrice <DealPric>	[1..1]	±		131
	Or}	Proprietary <Prtry>	[1..*]			131
		Type <Tp>	[1..1]	Text		131
		Price <Pric>	[1..1]	Amount		131
		RelatedQuantities <RltdQties>	[0..*]			132
	{Or	Quantity <Qty>	[1..1]	±		132
	Or	OriginalAndCurrentFaceAmount <OrgnlAndCurFaceAmt>	[1..1]	±		132
	Or}	Proprietary <Prtry>	[1..1]			132
		Type <Tp>	[1..1]	Text		133
		Quantity <Qty>	[1..1]	Text		133
		FinancialInstrumentIdentification <FinInstrmId>	[0..1]	±		133
		Tax <Tax>	[0..1]	±		133
		ReturnInformation <RtrInf>	[0..1]	±		134
		CorporateAction <CorpActn>	[0..1]			134
		EventType <EvtTp>	[1..1]	Text		135
		EventIdentification <EvtId>	[1..1]	Text		135
		SafekeepingAccount <SfkpgAcct>	[0..1]	±		135
		CashDeposit <CshDpst>	[0..*]	±		135
		CardTransaction <CardTx>	[0..1]	±		135
		AdditionalTransactionInformation <AddtlTxInf>	[0..1]	Text		138
		SupplementaryData <SplmtryData>	[0..*]	±		138

2.1.8.2 EntryTransaction10

Definition: Identifies the underlying transaction.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		References <Refs>	[0..1]			111
		MessageIdentification <MsgId>	[0..1]	Text		111
		AccountServicerReference <AcctSvcrRef>	[0..1]	Text		111
		PaymentInformationIdentification <PmtInfId>	[0..1]	Text		112
		InstructionIdentification <InstrId>	[0..1]	Text		112
		EndToEndIdentification <EndToEndId>	[0..1]	Text		112
		UETR <UETR>	[0..1]	IdentifierSet		112
		TransactionIdentification <TxId>	[0..1]	Text		112
		MandateIdentification <MndtId>	[0..1]	Text		112
		ChequeNumber <ChqNb>	[0..1]	Text		113
		ClearingSystemReference <ClrSysRef>	[0..1]	Text		113
		AccountOwnerTransactionIdentification <AcctOwnrTxId>	[0..1]	Text		113
		AccountServicerTransactionIdentification <AcctSvcrTxId>	[0..1]	Text		113
		MarketInfrastructureTransactionIdentification <MktInfstrctrTxId>	[0..1]	Text		113
		ProcessingIdentification <PrctlId>	[0..1]	Text		113
		Proprietary <Prtry>	[0..*]			113
		Type <Tp>	[1..1]	Text		114
		Reference <Ref>	[1..1]	Text		114
		Amount <Amt>	[0..1]	Amount		114
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		114
		AmountDetails <AmtDtls>	[0..1]	±		114
		Availability <Avlbt>	[0..*]	±		116
		BankTransactionCode <BkTxCd>	[0..1]	±		117
		Charges <Chrgs>	[0..1]	±		117
		Interest <Intrst>	[0..1]	±		117
		RelatedParties <RltdPties>	[0..1]			118
		InitiatingParty <InitgPty>	[0..1]	±		119
		Debtor <Dbtr>	[0..1]	±		119
		DebtorAccount <DbtrAcct>	[0..1]	±		119
		UltimateDebtor <UltmtDbtr>	[0..1]	±		120

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Creditor <Cdtr>	[0..1]	±		120
		CreditorAccount <CdtrAcct>	[0..1]	±		120
		UltimateCreditor <UltmtCdtr>	[0..1]	±		121
		TradingParty <TradgPty>	[0..1]	±		121
		Proprietary <Prtry>	[0..*]			121
		Type <Tp>	[1..1]	Text		122
		Party <Pty>	[1..1]	±		122
		RelatedAgents <RltdAgts>	[0..1]			122
		InstructingAgent <InstgAgt>	[0..1]	±		123
		InstructedAgent <InstdAgt>	[0..1]	±		123
		DebtorAgent <DbtrAgt>	[0..1]	±		124
		CreditorAgent <CdtrAgt>	[0..1]	±		124
		IntermediaryAgent1 <IntrmyAgt1>	[0..1]	±		124
		IntermediaryAgent2 <IntrmyAgt2>	[0..1]	±		124
		IntermediaryAgent3 <IntrmyAgt3>	[0..1]	±		125
		ReceivingAgent <RcvgAgt>	[0..1]	±		125
		DeliveringAgent <DlvrAgt>	[0..1]	±		125
		IssuingAgent <IssgAgt>	[0..1]	±		126
		SettlementPlace <SttlmPlc>	[0..1]	±		126
		Proprietary <Prtry>	[0..*]			126
		Type <Tp>	[1..1]	Text		126
		Agent <Agt>	[1..1]	±		127
		LocalInstrument <LclInstrm>	[0..1]			127
	{Or	Code <Cd>	[1..1]	CodeSet		127
	Or}	Proprietary <Prtry>	[1..1]	Text		127
		Purpose <Purp>	[0..1]	±		127
		RelatedRemittanceInformation <RltdRmtInf>	[0..10]	±		128
		RemittanceInformation <RmtInf>	[0..1]	±		128
		RelatedDates <RltdDts>	[0..1]			128
		AcceptanceDateTime <AcceptncDtTm>	[0..1]	DateTime		129
		TradeActivityContractualSettlementDate <TradActvtyCtrctlSttlmDt>	[0..1]	Date		129

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TradeDate <TradDt>	[0..1]	Date		129
		InterbankSettlementDate <IntrBkSttlmDt>	[0..1]	Date		129
		StartDate <StartDt>	[0..1]	Date		129
		EndDate <EndDt>	[0..1]	Date		130
		TransactionDateTime <TxDtTm>	[0..1]	DateTime		130
		Proprietary <Prtry>	[0..*]			130
		Type <Tp>	[1..1]	Text		130
		Date <Dt>	[1..1]	±		130
		RelatedPrice <RltdPric>	[0..1]			130
	{Or	DealPrice <DealPric>	[1..1]	±		131
	Or}	Proprietary <Prtry>	[1..*]			131
		Type <Tp>	[1..1]	Text		131
		Price <Pric>	[1..1]	Amount		131
		RelatedQuantities <RltdQties>	[0..*]			132
	{Or	Quantity <Qty>	[1..1]	±		132
	Or	OriginalAndCurrentFaceAmount <OrgnlAndCurFaceAmt>	[1..1]	±		132
	Or}	Proprietary <Prtry>	[1..1]			132
		Type <Tp>	[1..1]	Text		133
		Quantity <Qty>	[1..1]	Text		133
		FinancialInstrumentIdentification <FinInstrmId>	[0..1]	±		133
		Tax <Tax>	[0..1]	±		133
		ReturnInformation <RtrInf>	[0..1]	±		134
		CorporateAction <CorpActn>	[0..1]			134
		EventType <EvtTp>	[1..1]	Text		135
		EventIdentification <EvtId>	[1..1]	Text		135
		SafekeepingAccount <SfkpgAcct>	[0..1]	±		135
		CashDeposit <CshDpst>	[0..*]	±		135
		CardTransaction <CardTx>	[0..1]	±		135
		AdditionalTransactionInformation <AddtlTxInf>	[0..1]	Text		138
		SupplementaryData <SplmtryData>	[0..*]	±		138

2.1.8.2.1 References <Refs>

Presence: [0..1]

Definition: Provides the identification of the underlying transaction.

References <Refs> contains the following **TransactionReferences6** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		MessageIdentification <MsgId>	[0..1]	Text		111
		AccountServicerReference <AcctSvcrRef>	[0..1]	Text		111
		PaymentInformationIdentification <PmtInfId>	[0..1]	Text		112
		InstructionIdentification <InstrId>	[0..1]	Text		112
		EndToEndIdentification <EndToEndId>	[0..1]	Text		112
		UETR <UETR>	[0..1]	IdentifierSet		112
		TransactionIdentification <TxId>	[0..1]	Text		112
		MandateIdentification <MndtId>	[0..1]	Text		112
		ChequeNumber <ChqNb>	[0..1]	Text		113
		ClearingSystemReference <ClrSysRef>	[0..1]	Text		113
		AccountOwnerTransactionIdentification <AcctOwnrTxId>	[0..1]	Text		113
		AccountServicerTransactionIdentification <AcctSvcrTxId>	[0..1]	Text		113
		MarketInfrastructureTransactionIdentification <MktInfstrctrTxId>	[0..1]	Text		113
		ProcessingIdentification <PrcgId>	[0..1]	Text		113
		Proprietary <Prtry>	[0..*]			113
		Type <Tp>	[1..1]	Text		114
		Reference <Ref>	[1..1]	Text		114

2.1.8.2.1.1 MessageIdentification <MsgId>

Presence: [0..1]

Definition: Point to point reference, as assigned by the instructing party of the underlying message.

Datatype: [Max35Text on page 310](#)

2.1.8.2.1.2 AccountServicerReference <AcctSvcrRef>

Presence: [0..1]

Definition: Unique reference, as assigned by the account servicing institution, to unambiguously identify the instruction.

Datatype: [Max35Text on page 310](#)

2.1.8.2.1.3 PaymentInformationIdentification <PmtInflId>

Presence: [0..1]

Definition: Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message.

Datatype: Max35Text on page 310

2.1.8.2.1.4 InstructionIdentification <InstrId>

Presence: [0..1]

Definition: Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the instruction.

Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction.

Datatype: Max35Text on page 310

2.1.8.2.1.5 EndToEndIdentification <EndToEndId>

Presence: [0..1]

Definition: Unique identification, as assigned by the initiating party, to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.

Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction.

Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain.

Datatype: Max35Text on page 310

2.1.8.2.1.6 UETR <UETR>

Presence: [0..1]

Definition: Universally unique identifier to provide an end-to-end reference of a payment transaction.

Datatype: UUIDv4Identifier on page 305

2.1.8.2.1.7 TransactionIdentification <TxId>

Presence: [0..1]

Definition: Unique identification, as assigned by the first instructing agent, to unambiguously identify the transaction that is passed on, unchanged, throughout the entire interbank chain.

Usage: The transaction identification can be used for reconciliation, tracking or to link tasks relating to the transaction on the interbank level.

Usage: The instructing agent has to make sure that the transaction identification is unique for a pre-agreed period.

Datatype: Max35Text on page 310

2.1.8.2.1.8 MandateIdentification <MndtId>

Presence: [0..1]

Definition: Unique identification, as assigned by the creditor, to unambiguously identify the mandate.

Datatype: [Max35Text on page 310](#)

2.1.8.2.1.9 ChequeNumber <ChqNb>

Presence: [0..1]

Definition: Unique and unambiguous identifier for a cheque as assigned by the agent.

Datatype: [Max35Text on page 310](#)

2.1.8.2.1.10 ClearingSystemReference <ClrSysRef>

Presence: [0..1]

Definition: Unique reference, as assigned by a clearing system, to unambiguously identify the instruction.

Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain.

Datatype: [Max35Text on page 310](#)

2.1.8.2.1.11 AccountOwnerTransactionIdentification <AcctOwnrTxId>

Presence: [0..1]

Definition: Unambiguous identification of the securities transaction as known by the securities account owner (or the instructing party managing the account).

Datatype: [Max35Text on page 310](#)

2.1.8.2.1.12 AccountServicerTransactionIdentification <AcctSvcrTxId>

Presence: [0..1]

Definition: Unambiguous identification of the securities transaction as known by the securities account servicer.

Datatype: [Max35Text on page 310](#)

2.1.8.2.1.13 MarketInfrastructureTransactionIdentification <MktInfrstrctrTxId>

Presence: [0..1]

Definition: Identification of a securities transaction assigned by a market infrastructure other than a central securities depository, for example, Target2-Securities.

Datatype: [Max35Text on page 310](#)

2.1.8.2.1.14 ProcessingIdentification <PrcgId>

Presence: [0..1]

Definition: Identification of the securities transaction assigned by the processor of the instruction other than the securities account owner, the securities account servicer and the market infrastructure.

Datatype: [Max35Text on page 310](#)

2.1.8.2.1.15 Proprietary <Prtry>

Presence: [0..*]

Definition: Proprietary reference related to the underlying transaction.

Proprietary <Prtry> contains the following **ProprietaryReference1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[1..1]	Text		114
		Reference <Ref>	[1..1]	Text		114

2.1.8.2.1.15.1 Type <Tp>

Presence: [1..1]

Definition: Identifies the type of reference reported.

Datatype: [Max35Text on page 310](#)

2.1.8.2.1.15.2 Reference <Ref>

Presence: [1..1]

Definition: Proprietary reference specification related to the underlying transaction.

Datatype: [Max35Text on page 310](#)

2.1.8.2.2 Amount <Amt>

Presence: [0..1]

Definition: Amount of money in the cash transaction.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 242](#)

2.1.8.2.3 CreditDebitIndicator <CdtDbtInd>

Presence: [0..1]

Definition: Indicates whether the transaction is a credit or a debit transaction.

Datatype: [CreditDebitCode on page 260](#)

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

2.1.8.2.4 AmountDetails <AmtDtls>

Presence: [0..1]

Definition: Provides detailed information on the original amount.

Usage: This component (on transaction level) should be used in case booking is for a single transaction and the original amount is different from the entry amount. It can also be used in case individual original amounts are provided in case of a batch or aggregate booking.

AmountDetails <AmtDtls> contains the following elements (see [AmountAndCurrencyExchange3](#) on page 41 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		InstructedAmount <InstdAmt>	[0..1]			43
		Amount <Amt>	[1..1]	Amount		44
		CurrencyExchange <CcyXchg>	[0..1]			44
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		44
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		44
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		44
		ExchangeRate <XchgRate>	[1..1]	Rate		44
		ContractIdentification <CtrctId>	[0..1]	Text		45
		QuotationDate <QtnDt>	[0..1]	DateTime		45
		TransactionAmount <TxAmt>	[0..1]			45
		Amount <Amt>	[1..1]	Amount		45
		CurrencyExchange <CcyXchg>	[0..1]			45
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		46
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		46
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		46
		ExchangeRate <XchgRate>	[1..1]	Rate		46
		ContractIdentification <CtrctId>	[0..1]	Text		46
		QuotationDate <QtnDt>	[0..1]	DateTime		46
		CounterValueAmount <CntrValAmt>	[0..1]			47
		Amount <Amt>	[1..1]	Amount		47
		CurrencyExchange <CcyXchg>	[0..1]			47
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		48
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		48
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		48
		ExchangeRate <XchgRate>	[1..1]	Rate		48
		ContractIdentification <CtrctId>	[0..1]	Text		48
		QuotationDate <QtnDt>	[0..1]	DateTime		48
		AnnouncedPostingAmount <AnncdPstngAmt>	[0..1]			49
		Amount <Amt>	[1..1]	Amount		49
		CurrencyExchange <CcyXchg>	[0..1]			49

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		50
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		50
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		50
		ExchangeRate <XchgRate>	[1..1]	Rate		50
		ContractIdentification <CtrctId>	[0..1]	Text		50
		QuotationDate <QtnDt>	[0..1]	DateTime		50
		ProprietaryAmount <PrtryAmt>	[0..*]			51
		Type <Tp>	[1..1]	Text		51
		Amount <Amt>	[1..1]	Amount		51
		CurrencyExchange <CcyXchg>	[0..1]			51
		SourceCurrency <SrcCcy>	[1..1]	CodeSet		52
		TargetCurrency <TrgtCcy>	[0..1]	CodeSet		52
		UnitCurrency <UnitCcy>	[0..1]	CodeSet		52
		ExchangeRate <XchgRate>	[1..1]	Rate		52
		ContractIdentification <CtrctId>	[0..1]	Text		52
		QuotationDate <QtnDt>	[0..1]	DateTime		52

2.1.8.2.5 Availability <Avlbt>

Presence: [0..*]

Definition: Indicates when the booked amount of money will become available, that is can be accessed and starts generating interest.

Usage: This type of information is used in the US and is linked to particular instruments such as cheques.

Example: When a cheque is deposited, it will be booked on the deposit day, but the amount of money will only be accessible as of the indicated availability day (according to national banking regulations).

Availability <Avlbt> contains the following elements (see [CashAvailability1](#) on page 139 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Date <Dt>	[1..1]			139
	{Or	NumberOfDays <NbOfDays>	[1..1]	Text		139
	Or}	ActualDate <ActlDt>	[1..1]	Date		139
		Amount <Amt>	[1..1]	Amount		139
		CreditDebitIndicator <CdtDbtInd>	[1..1]	CodeSet		140

2.1.8.2.6 BankTransactionCode <BkTxCd>

Presence: [0..1]

Definition: Set of elements used to fully identify the type of underlying transaction resulting in an entry.

BankTransactionCode <BkTxCd> contains the following elements (see [BankTransactionCodeStructure4](#) on page 57 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Domain <Domn>	[0..1]	±		57
		Proprietary <Prtry>	[0..1]			58
		Code <Cd>	[1..1]	Text		58
		Issuer <Issr>	[0..1]	Text		58

2.1.8.2.7 Charges <Chrgs>

Presence: [0..1]

Definition: Provides information on the charges, pre-advised or included in the entry amount.

Usage: This component (on transaction level) can be used in case the booking is for a single transaction, and charges are included in the entry amount. It can also be used in case individual charge amounts are applied to individual transactions in case of a batch or aggregate amount booking.

Charges <Chrgs> contains the following elements (see [Charges6](#) on page 143 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TotalChargesAndTaxAmount <TtlChrgsAndTaxAmt>	[0..1]	Amount		143
		Record <Rcrd>	[0..*]	±		143

2.1.8.2.8 Interest <Intrst>

Presence: [0..1]

Definition: Provides details of the interest amount included in the entry amount.

Usage: This component (on transaction level) can be used if the booking is for a single transaction, and interest amount is included in the entry amount. It can also be used if individual interest amounts are applied to individual transactions in the case of a batch or aggregate amount booking.

Interest <Intrst> contains the following elements (see [TransactionInterest4](#) on page 174 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TotalInterestAndTaxAmount <TtlIntrstAndTaxAmt>	[0..1]	Amount		174
		Record <Rcrd>	[0..*]			174
		Amount <Amt>	[1..1]	Amount		175
		CreditDebitIndicator <CdtDbtInd>	[1..1]	CodeSet		175
		Type <Tp>	[0..1]			175
	{Or	Code <Cd>	[1..1]	CodeSet		176
	Or}	Proprietary <Prtry>	[1..1]	Text		176
		Rate <Rate>	[0..1]			176
		Type <Tp>	[1..1]	±		176
		ValidityRange <VldtyRg>	[0..1]	±		177
		FromDate <FrToDt>	[0..1]	±		177
		Reason <Rsn>	[0..1]	Text		177
		Tax <Tax>	[0..1]			177
		Identification <Id>	[0..1]	Text		177
		Rate <Rate>	[0..1]	Rate		178
		Amount <Amt>	[0..1]	Amount		178

2.1.8.2.9 RelatedParties <RltdPties>

Presence: [0..1]

Definition: Set of elements used to identify the parties related to the underlying transaction.

RelatedParties <RltdPties> contains the following **TransactionParties6** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		InitiatingParty <InitgPty>	[0..1]	±		119
		Debtor <Dbtr>	[0..1]	±		119
		DebtorAccount <DbtrAcct>	[0..1]	±		119
		UltimateDebtor <UltmtDbtr>	[0..1]	±		120
		Creditor <Cdtr>	[0..1]	±		120
		CreditorAccount <CdtrAcct>	[0..1]	±		120
		UltimateCreditor <UltmtCdtr>	[0..1]	±		121
		TradingParty <TradgPty>	[0..1]	±		121
		Proprietary <Prtry>	[0..*]			121
		Type <Tp>	[1..1]	Text		122
		Party <Pty>	[1..1]	±		122

2.1.8.2.9.1 InitiatingParty <InitgPty>

Presence: [0..1]

Definition: Party that initiated the payment that is reported in the entry.

InitiatingParty <InitgPty> contains one of the following elements (see [Party40Choice](#) on page 184 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Party <Pty>	[1..1]	±		184
	Or}	Agent <Agt>	[1..1]	±		184

2.1.8.2.9.2 Debtor <Dbtr>

Presence: [0..1]

Definition: Party that owes an amount of money to the (ultimate) creditor.

Debtor <Dbtr> contains one of the following elements (see [Party40Choice](#) on page 184 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Party <Pty>	[1..1]	±		184
	Or}	Agent <Agt>	[1..1]	±		184

2.1.8.2.9.3 DebtorAccount <DbtrAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the debtor.

DebtorAccount <DbtrAcct> contains the following elements (see [CashAccount38](#) on page 34 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		34
		Type <Tp>	[0..1]	±		34
		Currency <Ccy>	[0..1]	CodeSet		34
		Name <Nm>	[0..1]	Text		35
		Proxy <Prxy>	[0..1]	±		35

2.1.8.2.9.4 UltimateDebtor <UltmtDbtr>

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor.

UltimateDebtor <UltmtDbtr> contains one of the following elements (see [Party40Choice](#) on page 184 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Party <Pty>	[1..1]	±		184
	Or}	Agent <Agt>	[1..1]	±		184

2.1.8.2.9.5 Creditor <Cdtr>

Presence: [0..1]

Definition: Party to which an amount of money is due.

Creditor <Cdtr> contains one of the following elements (see [Party40Choice](#) on page 184 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Party <Pty>	[1..1]	±		184
	Or}	Agent <Agt>	[1..1]	±		184

2.1.8.2.9.6 CreditorAccount <CdtrAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor to which a credit entry has been posted as a result of the payment transaction.

CreditorAccount <CdtrAcct> contains the following elements (see [CashAccount38](#) on page 34 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		34
		Type <Tp>	[0..1]	±		34
		Currency <Ccy>	[0..1]	CodeSet		34
		Name <Nm>	[0..1]	Text		35
		Proxy <Prxy>	[0..1]	±		35

2.1.8.2.9.7 UltimateCreditor <UltmtCdtr>

Presence: [0..1]

Definition: Ultimate party to which an amount of money is due.

UltimateCreditor <UltmtCdtr> contains one of the following elements (see [Party40Choice](#) on page 184 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Party <Pty>	[1..1]	±		184
	Or}	Agent <Agt>	[1..1]	±		184

2.1.8.2.9.8 TradingParty <TradgPty>

Presence: [0..1]

Definition: Party that plays an active role in planning and executing the transactions that create or liquidate investments of the investors assets, or that move the investor's assets from one investment to another. A trading party is a trade instructor, an investment decision-maker, a post trade administrator, or a trader. In the context of treasury, it is the party that negotiates and executes the treasury transaction.

TradingParty <TradgPty> contains one of the following elements (see [Party40Choice](#) on page 184 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Party <Pty>	[1..1]	±		184
	Or}	Agent <Agt>	[1..1]	±		184

2.1.8.2.9.9 Proprietary <Prtry>

Presence: [0..*]

Definition: Proprietary party related to the underlying transaction.

Proprietary <Prtry> contains the following **ProprietaryParty5** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[1..1]	Text		122
		Party <Pty>	[1..1]	±		122

2.1.8.2.9.9.1 Type <Tp>

Presence: [1..1]

Definition: Specifies the type of proprietary party.

Datatype: [Max35Text](#) on page 310

2.1.8.2.9.9.2 Party <Pty>

Presence: [1..1]

Definition: Proprietary party.

Party <Pty> contains one of the following elements (see [Party40Choice](#) on page 184 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Party <Pty>	[1..1]	±		184
	Or}	Agent <Agt>	[1..1]	±		184

2.1.8.2.10 RelatedAgents <RltdAgts>

Presence: [0..1]

Definition: Set of elements used to identify the agents related to the underlying transaction.

RelatedAgents <RltdAgts> contains the following **TransactionAgents5** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		InstructingAgent <InstgAgt>	[0..1]	±		123
		InstructedAgent <InstdAgt>	[0..1]	±		123
		DebtorAgent <DbtrAgt>	[0..1]	±		124
		CreditorAgent <CdtrAgt>	[0..1]	±		124
		IntermediaryAgent1 <IntrmyAgt1>	[0..1]	±		124
		IntermediaryAgent2 <IntrmyAgt2>	[0..1]	±		124
		IntermediaryAgent3 <IntrmyAgt3>	[0..1]	±		125
		ReceivingAgent <RcvgAgt>	[0..1]	±		125
		DeliveringAgent <DlvrgAgt>	[0..1]	±		125
		IssuingAgent <IssgAgt>	[0..1]	±		126
		SettlementPlace <SttlmPlc>	[0..1]	±		126
		Proprietary <Prtry>	[0..*]			126
		Type <Tp>	[1..1]	Text		126
		Agent <Agt>	[1..1]	±		127

2.1.8.2.10.1 InstructingAgent <InstgAgt>

Presence: [0..1]

Definition: Agent that instructs the next party in the chain to carry out the (set of) instruction(s).

InstructingAgent <InstgAgt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 153 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		153
		BranchIdentification <BrnchId>	[0..1]	±		154

2.1.8.2.10.2 InstructedAgent <InstdAgt>

Presence: [0..1]

Definition: Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s).

InstructedAgent <InstdAgt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 153 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		153
		BranchIdentification <BrnchId>	[0..1]	±		154

2.1.8.2.10.3 DebtorAgent <DbtrAgt>*Presence:* [0..1]*Definition:* Financial institution servicing an account for the debtor.**DebtorAgent <DbtrAgt>** contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 153 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		153
		BranchIdentification <BrnchId>	[0..1]	±		154

2.1.8.2.10.4 CreditorAgent <CdtrAgt>*Presence:* [0..1]*Definition:* Financial institution servicing an account for the creditor.**CreditorAgent <CdtrAgt>** contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 153 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		153
		BranchIdentification <BrnchId>	[0..1]	±		154

2.1.8.2.10.5 IntermediaryAgent1 <IntrmyAgt1>*Presence:* [0..1]*Definition:* Agent between the debtor's agent and the creditor's agent.*Usage:* If more than one intermediary agent is present, then IntermediaryAgent1 identifies the agent between the DebtorAgent and the IntermediaryAgent2.**IntermediaryAgent1 <IntrmyAgt1>** contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 153 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		153
		BranchIdentification <BrnchId>	[0..1]	±		154

2.1.8.2.10.6 IntermediaryAgent2 <IntrmyAgt2>*Presence:* [0..1]*Definition:* Agent between the debtor's agent and the creditor's agent.*Usage:* If more than two intermediary agents are present, then IntermediaryAgent2 identifies the agent between the IntermediaryAgent1 and the IntermediaryAgent3.

IntermediaryAgent2 <IntrmyAgt2> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 153 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		153
		BranchIdentification <BrnchId>	[0..1]	±		154

2.1.8.2.10.7 IntermediaryAgent3 <IntrmyAgt3>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If IntermediaryAgent3 is present, then it identifies the agent between the IntermediaryAgent 2 and the CreditorAgent.

IntermediaryAgent3 <IntrmyAgt3> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 153 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		153
		BranchIdentification <BrnchId>	[0..1]	±		154

2.1.8.2.10.8 ReceivingAgent <RcvgAgt>

Presence: [0..1]

Definition: Party that receives securities from the delivering agent at the place of settlement, such as central securities depository.

Can also be used in the context of treasury operations.

ReceivingAgent <RcvgAgt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 153 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		153
		BranchIdentification <BrnchId>	[0..1]	±		154

2.1.8.2.10.9 DeliveringAgent <DlvrgAgt>

Presence: [0..1]

Definition: Party that delivers securities to the receiving agent at the place of settlement, such as a central securities depository.

Can also be used in the context of treasury operations.

DeliveringAgent <DlvrgAgt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 153 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		153
		BranchIdentification <BrnchId>	[0..1]	±		154

2.1.8.2.10.10 IssuingAgent <IssgAgt>

Presence: [0..1]

Definition: Legal entity that has the right to issue securities.

IssuingAgent <IssgAgt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 153 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		153
		BranchIdentification <BrnchId>	[0..1]	±		154

2.1.8.2.10.11 SettlementPlace <SttlmPlc>

Presence: [0..1]

Definition: Place where settlement of the securities takes place.

Usage: This is typed by a financial institution identification as this is the standard way to identify a securities settlement agent/central system.

SettlementPlace <SttlmPlc> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 153 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		153
		BranchIdentification <BrnchId>	[0..1]	±		154

2.1.8.2.10.12 Proprietary <Prtry>

Presence: [0..*]

Definition: Proprietary agent related to the underlying transaction.

Proprietary <Prtry> contains the following **ProprietaryAgent4** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[1..1]	Text		126
		Agent <Agt>	[1..1]	±		127

2.1.8.2.10.12.1 Type <Tp>

Presence: [1..1]

Definition: Specifies the type of proprietary agent.

Datatype: [Max35Text on page 310](#)

2.1.8.2.10.12.2 Agent <Agt>

Presence: [1..1]

Definition: Organisation established primarily to provide financial services.

Agent <Agt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6 on page 153](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		153
		BranchIdentification <BrnchId>	[0..1]	±		154

2.1.8.2.11 LocalInstrument <LclInstrm>

Presence: [0..1]

Definition: User community specific instrument.

Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.

LocalInstrument <LclInstrm> contains one of the following **LocalInstrument2Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		127
	Or}	Proprietary <Prtry>	[1..1]	Text		127

2.1.8.2.11.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the local instrument, as published in an external local instrument code list.

Datatype: [ExternalLocalInstrument1Code on page 273](#)

2.1.8.2.11.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies the local instrument, as a proprietary code.

Datatype: [Max35Text on page 310](#)

2.1.8.2.12 Purpose <Purp>

Presence: [0..1]

Definition: Underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

Purpose <Purp> contains one of the following elements (see [Purpose2Choice](#) on page 173 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		173
	Or}	Proprietary <Prtry>	[1..1]	Text		174

2.1.8.2.13 RelatedRemittanceInformation <RltdRmtInf>

Presence: [0..10]

Definition: Provides information related to the handling of the remittance information by any of the agents in the transaction processing chain.

RelatedRemittanceInformation <RltdRmtInf> contains the following elements (see [RemittanceLocation7](#) on page 221 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		RemittanceIdentification <RmtId>	[0..1]	Text		221
		RemittanceLocationDetails <RmtLctnDtls>	[0..*]	±		221

2.1.8.2.14 RemittanceInformation <RmtInf>

Presence: [0..1]

Definition: Structured information that enables the matching, that is reconciliation, of a payment with the items that the payment is intended to settle, such as commercial invoices in an account receivable system.

RemittanceInformation <RmtInf> contains the following elements (see [RemittanceInformation16](#) on page 202 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Unstructured <Ustrd>	[0..*]	Text		202
		Structured <Strd>	[0..*]	±		202

2.1.8.2.15 RelatedDates <RltdDts>

Presence: [0..1]

Definition: Set of elements used to identify the dates related to the underlying transactions.

RelatedDates <RltdDts> contains the following **TransactionDates3** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AcceptanceDateTime <AccptncDtTm>	[0..1]	DateTime		129
		TradeActivityContractualSettlementDate <TradActvtyCtrctlSttlmDt>	[0..1]	Date		129
		TradeDate <TradDt>	[0..1]	Date		129
		InterbankSettlementDate <IntrBkSttlmDt>	[0..1]	Date		129
		StartDate <StartDt>	[0..1]	Date		129
		EndDate <EndDt>	[0..1]	Date		130
		TransactionDateTime <TxDtTm>	[0..1]	DateTime		130
		Proprietary <Prtry>	[0..*]			130
		Type <Tp>	[1..1]	Text		130
		Date <Dt>	[1..1]	±		130

2.1.8.2.15.1 AcceptanceDateTime <AccptncDtTm>

Presence: [0..1]

Definition: Point in time when the payment order from the initiating party meets the processing conditions of the account servicing agent. This means that the account servicing agent has received the payment order and has applied checks such as authorisation, availability of funds.

Datatype: ISODatetime on page 303

2.1.8.2.15.2 TradeActivityContractualSettlementDate <TradActvtyCtrctlSttlmDt>

Presence: [0..1]

Definition: Identifies when an amount of money should have contractually been credited or debited the account versus when the amount of money was actually settled (debited/credited) on the cash account.

Datatype: ISODate on page 303

2.1.8.2.15.3 TradeDate <TradDt>

Presence: [0..1]

Definition: Date on which the trade was executed.

Datatype: ISODate on page 303

2.1.8.2.15.4 InterbankSettlementDate <IntrBkSttlmDt>

Presence: [0..1]

Definition: Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.

Datatype: ISODate on page 303

2.1.8.2.15.5 StartDate <StartDt>

Presence: [0..1]

Definition: Start date of the underlying transaction, such as a treasury transaction, an investment plan.

Datatype: [ISODate on page 303](#)

2.1.8.2.15.6 EndDate <EndDt>

Presence: [0..1]

Definition: End date of the underlying transaction, such as a treasury transaction, an investment plan.

Datatype: [ISODate on page 303](#)

2.1.8.2.15.7 TransactionDateTime <TxDtTm>

Presence: [0..1]

Definition: Date and time of the underlying transaction.

Datatype: [ISODatetime on page 303](#)

2.1.8.2.15.8 Proprietary <Prtry>

Presence: [0..*]

Definition: Proprietary date related to the underlying transaction.

Proprietary <Prtry> contains the following **ProprietaryDate3** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[1..1]	Text		130
		Date <Dt>	[1..1]	±		130

2.1.8.2.15.8.1 Type <Tp>

Presence: [1..1]

Definition: Specifies the type of date.

Datatype: [Max35Text on page 310](#)

2.1.8.2.15.8.2 Date <Dt>

Presence: [1..1]

Definition: Date in ISO format.

Date <Dt> contains one of the following elements (see [DateAndDateTime2Choice on page 145](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Date <Dt>	[1..1]	Date		145
	Or}	DateTime <DtTm>	[1..1]	DateTime		145

2.1.8.2.16 RelatedPrice <RltdPric>

Presence: [0..1]

Definition: Set of elements used to identify the price information related to the underlying transaction.

RelatedPrice <RltdPric> contains one of the following **TransactionPrice4Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	DealPrice <DealPric>	[1..1]	±		131
	Or}	Proprietary <Prtry>	[1..*]			131
		Type <Tp>	[1..1]	Text		131
		Price <Pric>	[1..1]	Amount		131

2.1.8.2.16.1 DealPrice <DealPric>

Presence: [1..1]

Definition: Specifies the price of the traded financial instrument.

This is the deal price of the individual trade transaction.

If there is only one trade transaction for the execution of the trade, then the deal price could equal the executed trade price (unless, for example, the price includes commissions or rounding, or some other factor has been applied to the deal price or the executed trade price, or both).

DealPrice <DealPric> contains the following elements (see [Price7 on page 197](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[1..1]	±		197
		Value <Val>	[1..1]	±		198

2.1.8.2.16.2 Proprietary <Prtry>

Presence: [1..*]

Definition: Proprietary price specification related to the underlying transaction.

Proprietary <Prtry> contains the following **ProprietaryPrice2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[1..1]	Text		131
		Price <Pric>	[1..1]	Amount		131

2.1.8.2.16.2.1 Type <Tp>

Presence: [1..1]

Definition: Specifies the type of price.

Datatype: [Max35Text on page 310](#)

2.1.8.2.16.2.2 Price <Pric>

Presence: [1..1]

Definition: Proprietary price specification related to the underlying transaction.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 242](#)

2.1.8.2.17 RelatedQuantities <RltdQties>

Presence: [0..*]

Definition: Set of elements used to identify the related quantities, such as securities, in the underlying transaction.

RelatedQuantities <RltdQties> contains one of the following **TransactionQuantities3Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Quantity <Qty>	[1..1]	±		132
	Or	OriginalAndCurrentFaceAmount <OrgnlAndCurFaceAmt>	[1..1]	±		132
	Or}	Proprietary <Prtry>	[1..1]			132
		Type <Tp>	[1..1]	Text		133
		Quantity <Qty>	[1..1]	Text		133

2.1.8.2.17.1 Quantity <Qty>

Presence: [1..1]

Definition: Specifies the quantity (such as securities) in the underlying transaction.

Quantity <Qty> contains one of the following elements (see [FinancialInstrumentQuantity1Choice](#) on page 157 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Unit <Unit>	[1..1]	Quantity		157
	Or	FaceAmount <FaceAmt>	[1..1]	Amount		157
	Or}	AmortisedValue <AmtsdVal>	[1..1]	Amount		157

2.1.8.2.17.2 OriginalAndCurrentFaceAmount <OrgnlAndCurFaceAmt>

Presence: [1..1]

Definition: Face amount and amortised value of security.

OriginalAndCurrentFaceAmount <OrgnlAndCurFaceAmt> contains the following elements (see [OriginalAndCurrentQuantities1](#) on page 224 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FaceAmount <FaceAmt>	[1..1]	Amount		224
		AmortisedValue <AmtsdVal>	[1..1]	Amount		225

2.1.8.2.17.3 Proprietary <Prtry>

Presence: [1..1]

Definition: Proprietary quantities specification defined in the underlying transaction.

Proprietary <Prtry> contains the following **ProprietaryQuantity1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[1..1]	Text		133
		Quantity <Qty>	[1..1]	Text		133

2.1.8.2.17.3.1 Type <Tp>

Presence: [1..1]

Definition: Identifies the type of proprietary quantity reported.

Datatype: [Max35Text on page 310](#)

2.1.8.2.17.3.2 Quantity <Qty>

Presence: [1..1]

Definition: Provides the proprietary quantity in free format.

Datatype: [Max35Text on page 310](#)

2.1.8.2.18 FinancialInstrumentIdentification <FinInstrmId>

Presence: [0..1]

Definition: Identification of a security, as assigned under a formal or proprietary identification scheme.

FinancialInstrumentIdentification <FinInstrmId> contains the following elements (see [SecurityIdentification19 on page 155](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ISIN <ISIN>	[0..1]	IdentifierSet		156
		OtherIdentification <OthrId>	[0..*]			156
		Identification <Id>	[1..1]	Text		156
		Suffix <Sfx>	[0..1]	Text		156
		Type <Tp>	[1..1]	±		157
		Description <Desc>	[0..1]	Text		157

2.1.8.2.19 Tax <Tax>

Presence: [0..1]

Definition: Provides details on the tax.

Tax <Tax> contains the following elements (see [TaxInformation8](#) on page 233 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Creditor <Cdtr>	[0..1]	±		234
		Debtor <Dbtr>	[0..1]	±		234
		AdministrationZone <AdmstnZone>	[0..1]	Text		235
		ReferenceNumber <RefNb>	[0..1]	Text		235
		Method <Mtd>	[0..1]	Text		235
		TotalTaxableBaseAmount <TtlTaxblBaseAmt>	[0..1]	Amount		235
		TotalTaxAmount <TtlTaxAmt>	[0..1]	Amount		235
		Date <Dt>	[0..1]	Date		235
		SequenceNumber <SeqNb>	[0..1]	Quantity		235
		Record <Rcrd>	[0..*]	±		235

2.1.8.2.20 ReturnInformation <RtrInf>

Presence: [0..1]

Definition: Provides the return information.

ReturnInformation <RtrInf> contains the following elements (see [PaymentReturnReason5](#) on page 225 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		OriginalBankTransactionCode <OrgnlBkTxCd>	[0..1]	±		225
		Originator <Orgtr>	[0..1]	±		226
		Reason <Rsn>	[0..1]			226
	{Or	Code <Cd>	[1..1]	CodeSet		226
	Or}	Proprietary <Prtry>	[1..1]	Text		226
		AdditionalInformation <AddtlInf>	[0..*]	Text		226

2.1.8.2.21 CorporateAction <CorpActn>

Presence: [0..1]

Definition: Set of elements used to identify the underlying corporate action.

CorporateAction <CorpActn> contains the following **CorporateAction9** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		EventType <EvtTp>	[1..1]	Text		135
		EventIdentification <EvtId>	[1..1]	Text		135

2.1.8.2.21.1 EventType <EvtTp>*Presence:* [1..1]*Definition:* Type of corporate action event, in a free-text format.*Datatype:* [Max35Text on page 310](#)**2.1.8.2.21.2 EventIdentification <EvtId>***Presence:* [1..1]*Definition:* Identification of a corporate action assigned by an official central body/entity within a given market.*Datatype:* [Max35Text on page 310](#)**2.1.8.2.22 SafekeepingAccount <SfkpgAcct>***Presence:* [0..1]*Definition:* Safekeeping or investment account. A safekeeping account is an account on which a securities entry is made. An investment account is an account between an investor(s) and a fund manager or a fund. The account can contain holdings in any investment fund or investment fund class managed (or distributed) by the fund manager, within the same fund family.**SafekeepingAccount <SfkpgAcct>** contains the following elements (see [SecuritiesAccount19 on page 40](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		40
		Type <Tp>	[0..1]	±		40
		Name <Nm>	[0..1]	Text		40

2.1.8.2.23 CashDeposit <CshDpst>*Presence:* [0..*]*Definition:* Provides the details of a cash deposit for an amount of money in cash notes and/or coins.**CashDeposit <CshDpst>** contains the following elements (see [CashDeposit1 on page 101](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		NoteDenomination <NoteDnmtn>	[1..1]	Amount		101
		NumberOfNotes <NbOfNotes>	[1..1]	Text		102
		Amount <Amt>	[1..1]	Amount		102

2.1.8.2.24 CardTransaction <CardTx>*Presence:* [0..1]*Definition:* Provides the data related to the card (number, scheme), terminal (number, identification) and transactional data used to uniquely identify a card transaction.

CardTransaction <CardTx> contains the following elements (see [CardTransaction17](#) on page 59 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Card <Card>	[0..1]			62
		PlainCardData <PlainCardData>	[0..1]			63
		PAN <PAN>	[1..1]	Text		64
		CardSequenceNumber <CardSeqNb>	[0..1]	Text		64
		EffectiveDate <FctvDt>	[0..1]	YearMonth		64
		ExpiryDate <XpryDt>	[1..1]	YearMonth		64
		ServiceCode <SvcCd>	[0..1]	Text		64
		TrackData <TrckData>	[0..*]			65
		TrackNumber <TrckNb>	[0..1]	Text		65
		TrackValue <TrckVal>	[1..1]	Text		65
		CardSecurityCode <CardSctyCd>	[0..1]			65
		CSCManagement <CSCMgmt>	[1..1]	CodeSet		65
		CSCValue <CSCVal>	[0..1]	Text		66
		CardCountryCode <CardCtryCd>	[0..1]	Text		66
		CardBrand <CardBrnd>	[0..1]	±		66
		AdditionalCardData <AddtlCardData>	[0..1]	Text		66
		POI <POI>	[0..1]			66
		Identification <Id>	[1..1]	±		67
		SystemName <SysNm>	[0..1]	Text		68
		GroupIdentification <Grpld>	[0..1]	Text		68
		Capabilities <Cpblties>	[0..1]			68
		CardReadingCapabilities <CardRdngCpblties>	[0..*]	CodeSet		68
		CardholderVerificationCapabilities <CrdhldrVrfctnCpblties>	[0..*]	CodeSet		69
		OnLineCapabilities <OnLineCpblties>	[0..1]	CodeSet		69
		DisplayCapabilities <DispCpblties>	[0..*]			70
		DisplayType <DispTp>	[1..1]	CodeSet		70
		NumberOfLines <NbOfLines>	[1..1]	Text		70
		LineWidth <LineWidth>	[1..1]	Text		70
		PrintLineWidth <PrtLineWidth>	[0..1]	Text		70

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Component <Cmpnt>	[0..*]			70
		POIComponentType <POICmpntTp>	[1..1]	CodeSet		71
		ManufacturerIdentification <ManfctrId>	[0..1]	Text		71
		Model <Mdl>	[0..1]	Text		71
		VersionNumber <VrsnNb>	[0..1]	Text		71
		SerialNumber <SrlNb>	[0..1]	Text		72
		ApprovalNumber <ApprvlNb>	[0..*]	Text		72
		Transaction <Tx>	[0..1]			72
	{Or	Aggregated <Aggtd>	[1..1]			74
		AdditionalService <AddtlSvc>	[0..1]	CodeSet		74
		TransactionCategory <TxCtgy>	[0..1]	CodeSet		75
		SaleReconciliationIdentification <SaleRcncltnId>	[0..1]	Text		75
		SequenceNumberRange <SeqNbRg>	[0..1]			75
		FirstTransaction <FrstTx>	[0..1]	Text		75
		LastTransaction <LastTx>	[0..1]	Text		75
		TransactionDateRange <TxDtRg>	[0..1]	±		76
	Or}	Individual <Indv>	[1..1]			76
		ICCRelatedData <ICCRltdData>	[0..1]	Text		78
		PaymentContext <PmtCntxt>	[0..1]			78
		CardPresent <CardPres>	[0..1]	Indicator		78
		CardholderPresent <CrhdldrPres>	[0..1]	Indicator		79
		OnLineContext <OnLineCntxt>	[0..1]	Indicator		79
		AttendanceContext <AttndncCntxt>	[0..1]	CodeSet		79
		TransactionEnvironment <TxEnvnt>	[0..1]	CodeSet		79
		TransactionChannel <TxChanl>	[0..1]	CodeSet		79
		AttendantMessageCapable <AttndntMsgCpbl>	[0..1]	Indicator		80
		AttendantLanguage <AttndntLang>	[0..1]	CodeSet		80
		CardDataEntryMode <CardDataNtryMd>	[1..1]	CodeSet		80
		FallbackIndicator <FlbckInd>	[0..1]	Indicator		81
		AuthenticationMethod <AuthntcnMtd>	[0..1]			81
		AuthenticationMethod <AuthntcnMtd>	[1..1]	CodeSet		81

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AuthenticationEntity <AuthntcnNtty>	[1..1]	CodeSet		82
		AdditionalService <AddtlSvc>	[0..1]	CodeSet		82
		TransactionCategory <TxCtgy>	[0..1]	CodeSet		82
		SaleReconciliationIdentification <SaleRcncltnId>	[0..1]	Text		82
		SaleReferenceNumber <SaleRefNb>	[0..1]	Text		83
		RePresentmentReason <RePresntmntRsn>	[0..1]	CodeSet		83
		SequenceNumber <SeqNb>	[0..1]	Text		83
		TransactionIdentification <TxId>	[0..1]	±		83
		Product <Pdct>	[0..1]			83
		ProductCode <PdctCd>	[1..1]	Text		84
		UnitOfMeasure <UnitOfMeasr>	[0..1]	CodeSet		84
		ProductQuantity <PdctQty>	[0..1]	Quantity		86
		UnitPrice <UnitPric>	[0..1]	Amount		86
		ProductAmount <PdctAmt>	[0..1]	Amount		86
		TaxType <TaxTp>	[0..1]	Text		86
		AdditionalProductInformation <AddtlPdctInf>	[0..1]	Text		86
		ValidationDate <VldtnDt>	[0..1]	Date		86
		ValidationSequenceNumber <VldtnSeqNb>	[0..1]	Text		86
		PrePaidAccount <PrePdAcct>	[0..1]	±		86

2.1.8.2.25 AdditionalTransactionInformation <AddtlTxInf>

Presence: [0..1]

Definition: Further details of the transaction.

Datatype: [Max500Text on page 310](#)

2.1.8.2.26 SupplementaryData <SplmtryData>

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

SupplementaryData <SplmtryData> contains the following elements (see [SupplementaryData1](#) on page 172 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PlaceAndName <PlcAndNm>	[0..1]	Text		173
		Envelope <Envlp>	[1..1]	(External Schema)		173

2.1.8.3 CashAvailability1

Definition: Indicates when the amount of money will become available, that is can be accessed and start generating interest.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Date <Dt>	[1..1]			139
	{Or	NumberOfDays <NbOfDays>	[1..1]	Text		139
	Or}	ActualDate <ActlDt>	[1..1]	Date		139
		Amount <Amt>	[1..1]	Amount		139
		CreditDebitIndicator <CdtDbtInd>	[1..1]	CodeSet		140

2.1.8.3.1 Date <Dt>

Presence: [1..1]

Definition: Indicates when the amount of money will become available.

Date <Dt> contains one of the following **CashAvailabilityDate1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	NumberOfDays <NbOfDays>	[1..1]	Text		139
	Or}	ActualDate <ActlDt>	[1..1]	Date		139

2.1.8.3.1.1 NumberOfDays <NbOfDays>

Presence: [1..1]

Definition: Indicates the number of float days attached to the balance.

Datatype: [Max15PlusSignedNumericText](#) on page 309

2.1.8.3.1.2 ActualDate <ActlDt>

Presence: [1..1]

Definition: Identifies the actual availability date.

Datatype: [ISODate](#) on page 303

2.1.8.3.2 Amount <Amt>

Presence: [1..1]

Definition: Identifies the available amount.

Datatype: ActiveOrHistoricCurrencyAndAmount on page 242

2.1.8.3.3 CreditDebitIndicator <CdtDbtInd>

Presence: [1..1]

Definition: Indicates whether the availability balance is a credit or a debit balance.

Usage: A zero balance is considered to be a credit balance.

Datatype: CreditDebitCode on page 260

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

2.1.9 Charge

2.1.9.1 ChargesRecord3

Definition: Provides further individual record details on the charges related to the payment transaction.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Amount		140
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		141
		ChargeIncludedIndicator <ChrgInclInd>	[0..1]	Indicator		141
		Type <Tp>	[0..1]			141
	{Or	Code <Cd>	[1..1]	CodeSet		141
	Or}	Proprietary <Prtry>	[1..1]	±		141
		Rate <Rate>	[0..1]	Rate		142
		Bearer 	[0..1]	CodeSet		142
		Agent <Agt>	[0..1]	±		142
		Tax <Tax>	[0..1]			143
		Identification <Id>	[0..1]	Text		143
		Rate <Rate>	[0..1]	Rate		143
		Amount <Amt>	[0..1]	Amount		143

2.1.9.1.1 Amount <Amt>

Presence: [1..1]

Definition: Transaction charges to be paid by the charge bearer.

Datatype: ActiveOrHistoricCurrencyAndAmount on page 242

2.1.9.1.2 CreditDebitIndicator <CdtDbtInd>

Presence: [0..1]

Definition: Indicates whether the charges amount is a credit or a debit amount.

Usage: A zero amount is considered to be a credit.

Datatype: [CreditDebitCode](#) on page 260

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

2.1.9.1.3 ChargeIncludedIndicator <ChrgInclInd>

Presence: [0..1]

Definition: Indicates whether the charge should be included in the amount or is added as pre-advice.

Datatype: One of the following values must be used (see [ChargeIncludedIndicator](#) on page 306):

- *Meaning When True:* Included
- *Meaning When False:* Pre-advised

2.1.9.1.4 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of charge.

Type <Tp> contains one of the following **ChargeType3Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		141
	Or}	Proprietary <Prtry>	[1..1]	±		141

2.1.9.1.4.1 Code <Cd>

Presence: [1..1]

Definition: Charge type, in a coded form.

Datatype: [ExternalChargeType1Code](#) on page 268

2.1.9.1.4.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Type of charge in a proprietary form, as defined by the issuer.

Proprietary <Prtry> contains the following elements (see [GenericIdentification3](#) on page 158 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		158
		Issuer <Issr>	[0..1]	Text		159

2.1.9.1.5 Rate <Rate>

Presence: [0..1]

Definition: Rate used to calculate the amount of the charge or fee.

Datatype: [PercentageRate](#) on page 307

2.1.9.1.6 Bearer

Presence: [0..1]

Definition: Specifies which party/parties will bear the charges associated with the processing of the payment transaction.

Datatype: [ChargeBearerType1Code](#) on page 257

CodeName	Name	Definition
DEBT	BorneByDebtor	All transaction charges are to be borne by the debtor.
CRED	BorneByCreditor	All transaction charges are to be borne by the creditor.
SHAR	Shared	In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor.
SLEV	FollowingServiceLevel	Charges are to be applied following the rules agreed in the service level and/or scheme.

2.1.9.1.7 Agent <Agt>

Presence: [0..1]

Definition: Agent that takes the transaction charges or to which the transaction charges are due.

Agent <Agt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 153 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		153
		BranchIdentification <BrnchId>	[0..1]	±		154

2.1.9.1.8 Tax <Tax>

Presence: [0..1]

Definition: Provides details on the tax applied to charges.

Tax <Tax> contains the following **TaxCharges2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[0..1]	Text		143
		Rate <Rate>	[0..1]	Rate		143
		Amount <Amt>	[0..1]	Amount		143

2.1.9.1.8.1 Identification <Id>

Presence: [0..1]

Definition: Unique reference to unambiguously identify the nature of the tax levied, such as Value Added Tax (VAT).

Datatype: [Max35Text](#) on page 310

2.1.9.1.8.2 Rate <Rate>

Presence: [0..1]

Definition: Rate used to calculate the tax.

Datatype: [PercentageRate](#) on page 307

2.1.9.1.8.3 Amount <Amt>

Presence: [0..1]

Definition: Amount of money resulting from the calculation of the tax.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 242

2.1.9.2 Charges6

Definition: Provides further details on the charges related to the payment transaction.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TotalChargesAndTaxAmount <TtlChrgsAndTaxAmt>	[0..1]	Amount		143
		Record <Rcrd>	[0..*]	±		143

2.1.9.2.1 TotalChargesAndTaxAmount <TtlChrgsAndTaxAmt>

Presence: [0..1]

Definition: Total of all charges and taxes applied to the entry.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 242

2.1.9.2.2 Record <Rcrd>

Presence: [0..*]

Definition: Provides details of the individual charges record.

Record <Rcrd> contains the following elements (see [ChargesRecord3](#) on page 140 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Amount		140
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		141
		ChargeIncludedIndicator <ChrgInclInd>	[0..1]	Indicator		141
		Type <Tp>	[0..1]			141
	{Or	Code <Cd>	[1..1]	CodeSet		141
	Or}	Proprietary <Prtry>	[1..1]	±		141
		Rate <Rate>	[0..1]	Rate		142
		Bearer 	[0..1]	CodeSet		142
		Agent <Agt>	[0..1]	±		142
		Tax <Tax>	[0..1]			143
		Identification <Id>	[0..1]	Text		143
		Rate <Rate>	[0..1]	Rate		143
		Amount <Amt>	[0..1]	Amount		143

2.1.10 Date Period

2.1.10.1 DatePeriod2

Definition: Range of time defined by a start date and an end date.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FromDate <FrDt>	[1..1]	Date		144
		ToDate <ToDt>	[1..1]	Date		144

2.1.10.1.1 FromDate <FrDt>

Presence: [1..1]

Definition: Start date of the range.

Datatype: [ISODate](#) on page 303

2.1.10.1.2 ToDate <ToDt>

Presence: [1..1]

Definition: End date of the range.

Datatype: [ISODate](#) on page 303

2.1.11 Date Time

2.1.11.1 DateAndDateTime2Choice

Definition: Choice between a date or a date and time format.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Date <Dt>	[1..1]	Date		145
	Or}	DateTime <DtTm>	[1..1]	DateTime		145

2.1.11.1.1 Date <Dt>

Presence: [1..1]

Definition: Specified date.

Datatype: [ISODate on page 303](#)

2.1.11.1.2 DateTime <DtTm>

Presence: [1..1]

Definition: Specified date and time.

Datatype: [ISODateTime on page 303](#)

2.1.12 Date Time Period

2.1.12.1 DateOrDateTimePeriod1Choice

Definition: Choice between a date or a date and time format for a period.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Date <Dt>	[1..1]	±		145
	Or}	DateTime <DtTm>	[1..1]	±		145

2.1.12.1.1 Date <Dt>

Presence: [1..1]

Definition: Period expressed with dates.

Date <Dt> contains the following elements (see [DatePeriod2 on page 144](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FromDate <FrDt>	[1..1]	Date		144
		ToDate <ToDt>	[1..1]	Date		144

2.1.12.1.2 DateTime <DtTm>

Presence: [1..1]

Definition: Period expressed a dates and times.

DateTime <DtTm> contains the following elements (see [DateTimePeriod1](#) on page 146 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FromDateTime <FrDtTm>	[1..1]	DateTime		146
		ToDateTime <ToDtTm>	[1..1]	DateTime		146

2.1.12.2 DateTimePeriod1

Definition: Time span defined by a start date and time, and an end date and time.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FromDateTime <FrDtTm>	[1..1]	DateTime		146
		ToDateTime <ToDtTm>	[1..1]	DateTime		146

2.1.12.2.1 FromDateTime <FrDtTm>

Presence: [1..1]

Definition: Date and time at which the period starts.

Datatype: [ISODatetime](#) on page 303

2.1.12.2.2 ToDateTime <ToDtTm>

Presence: [1..1]

Definition: Date and time at which the period ends.

Datatype: [ISODatetime](#) on page 303

2.1.13 Document

2.1.13.1 CreditorReferenceInformation2

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			147
		CodeOrProprietary <CdOrPrtry>	[1..1]			147
	{Or	Code <Cd>	[1..1]	CodeSet		147
	Or}	Proprietary <Prtry>	[1..1]	Text		148
		Issuer <Issr>	[0..1]	Text		148
		Reference <Ref>	[0..1]	Text		148

2.1.13.1.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of creditor reference.

Type <Tp> contains the following **CreditorReferenceType2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CodeOrProprietary <CdOrPrtry>	[1..1]			147
	{Or	Code <Cd>	[1..1]	CodeSet		147
	Or}	Proprietary <Prtry>	[1..1]	Text		148
		Issuer <Issr>	[0..1]	Text		148

2.1.13.1.1.1 CodeOrProprietary <CdOrPrtry>

Presence: [1..1]

Definition: Coded or proprietary format creditor reference type.

CodeOrProprietary <CdOrPrtry> contains one of the following **CreditorReferenceType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		147
	Or}	Proprietary <Prtry>	[1..1]	Text		148

2.1.13.1.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Type of creditor reference, in a coded form.

Datatype: [DocumentType3Code](#) on page 261

CodeName	Name	Definition
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, for example, in a cover scenario.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
DISP	DispatchAdvice	Document is a dispatch advice.
PUOR	PurchaseOrder	Document is a purchase order.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.

2.1.13.1.1.1.2 Proprietary <Prtry>*Presence:* [1..1]*Definition:* Creditor reference type, in a proprietary form.*Datatype:* [Max35Text on page 310](#)**2.1.13.1.1.2 Issuer <Issr>***Presence:* [0..1]*Definition:* Entity that assigns the credit reference type.*Datatype:* [Max35Text on page 310](#)**2.1.13.1.2 Reference <Ref>***Presence:* [0..1]*Definition:* Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction.*Usage:* If available, the initiating party should provide this reference in the structured remittance information, to enable reconciliation by the creditor upon receipt of the amount of money.*If the business context requires the use of a creditor reference or a payment remit identification, and only one identifier can be passed through the end-to-end chain, the creditor's reference or payment remittance identification should be quoted in the end-to-end transaction identification.**Datatype:* [Max35Text on page 310](#)**2.1.14 Financial Institution Identification****2.1.14.1 FinancialInstitutionIdentification18***Definition:* Specifies the details to identify a financial institution.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		BICFI <BICFI>	[0..1]	IdentifierSet		148
		ClearingSystemMemberIdentification <ClrSysMmbld>	[0..1]	±		149
		LEI <LEI>	[0..1]	IdentifierSet		149
		Name <Nm>	[0..1]	Text		149
		PostalAddress <PstlAdr>	[0..1]	±		149
		Other <Othr>	[0..1]	±		150

2.1.14.1.1 BICFI <BICFI>*Presence:* [0..1]*Definition:* Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".*Datatype:* [BICFIDec2014Identifier on page 304](#)

2.1.14.1.2 ClearingSystemMemberIdentification <ClrSysMmbld>

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

ClearingSystemMemberIdentification <ClrSysMmbld> contains the following elements (see [ClearingSystemMemberIdentification2](#) on page 154 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ClearingSystemIdentification <ClrSysId>	[0..1]	±		154
		MemberIdentification <Mmbld>	[1..1]	Text		155

2.1.14.1.3 LEI <LEI>

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: [LEIIdentifier](#) on page 305

2.1.14.1.4 Name <Nm>

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: [Max140Text](#) on page 308

2.1.14.1.5 PostalAddress <PstlAdr>

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

PostalAddress <PstAdr> contains the following elements (see [PostalAddress24](#) on page 194 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AddressType <AdrTp>	[0..1]			194
	{Or	Code <Cd>	[1..1]	CodeSet		195
	Or}	Proprietary <Prtry>	[1..1]	±		195
		Department <Dept>	[0..1]	Text		195
		SubDepartment <SubDept>	[0..1]	Text		195
		StreetName <StrtNm>	[0..1]	Text		196
		BuildingNumber <BldgNb>	[0..1]	Text		196
		BuildingName <BldgNm>	[0..1]	Text		196
		Floor <Flr>	[0..1]	Text		196
		PostBox <PstBx>	[0..1]	Text		196
		Room <Room>	[0..1]	Text		196
		PostCode <PstCd>	[0..1]	Text		196
		TownName <TwnNm>	[0..1]	Text		196
		TownLocationName <TwnLctnNm>	[0..1]	Text		197
		DistrictName <DstrctNm>	[0..1]	Text		197
		CountrySubDivision <CtrySubDvsn>	[0..1]	Text		197
		Country <Ctry>	[0..1]	CodeSet		197
		AddressLine <AdrLine>	[0..7]	Text		197

2.1.14.1.6 Other <Othr>

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

Other <Othr> contains the following elements (see [GenericFinancialIdentification1](#) on page 152 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		152
		SchemeName <SchmeNm>	[0..1]			153
	{Or	Code <Cd>	[1..1]	CodeSet		153
	Or}	Proprietary <Prtry>	[1..1]	Text		153
		Issuer <Issr>	[0..1]	Text		153

2.1.14.2 BranchData3

Definition: Information that locates and identifies a specific branch of a financial institution.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[0..1]	Text		151
		LEI <LEI>	[0..1]	IdentifierSet		151
		Name <Nm>	[0..1]	Text		151
		PostalAddress <PstlAdr>	[0..1]	±		151

2.1.14.2.1 Identification <Id>

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: [Max35Text on page 310](#)

2.1.14.2.2 LEI <LEI>

Presence: [0..1]

Definition: Legal entity identification for the branch of the financial institution.

Datatype: [LEIIdentifier on page 305](#)

2.1.14.2.3 Name <Nm>

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: [Max140Text on page 308](#)

2.1.14.2.4 PostalAddress <PstlAdr>

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

PostalAddress <PstlAdr> contains the following elements (see [PostalAddress24](#) on page 194 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AddressType <AdrTp>	[0..1]			194
	{Or	Code <Cd>	[1..1]	CodeSet		195
	Or}	Proprietary <Prtry>	[1..1]	±		195
		Department <Dept>	[0..1]	Text		195
		SubDepartment <SubDept>	[0..1]	Text		195
		StreetName <StrtNm>	[0..1]	Text		196
		BuildingNumber <BldgNb>	[0..1]	Text		196
		BuildingName <BldgNm>	[0..1]	Text		196
		Floor <Flr>	[0..1]	Text		196
		PostBox <PstBx>	[0..1]	Text		196
		Room <Room>	[0..1]	Text		196
		PostCode <PstCd>	[0..1]	Text		196
		TownName <TwnNm>	[0..1]	Text		196
		TownLocationName <TwnLctnNm>	[0..1]	Text		197
		DistrictName <DstrctNm>	[0..1]	Text		197
		CountrySubDivision <CtrySubDvsn>	[0..1]	Text		197
		Country <Ctry>	[0..1]	CodeSet		197
		AddressLine <AdrLine>	[0..7]	Text		197

2.1.14.3 GenericFinancialIdentification1

Definition: Information related to an identification of a financial institution.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		152
		SchemeName <SchmeNm>	[0..1]			153
	{Or	Code <Cd>	[1..1]	CodeSet		153
	Or}	Proprietary <Prtry>	[1..1]	Text		153
		Issuer <Issr>	[0..1]	Text		153

2.1.14.3.1 Identification <Id>

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: [Max35Text on page 310](#)

2.1.14.3.2 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Name of the identification scheme.

SchemeName <SchmeNm> contains one of the following **FinancialIdentificationSchemeName1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		153
	Or}	Proprietary <Prtry>	[1..1]	Text		153

2.1.14.3.2.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: [ExternalFinancialInstitutionIdentification1Code on page 271](#)

2.1.14.3.2.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: [Max35Text on page 310](#)

2.1.14.3.3 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: [Max35Text on page 310](#)

2.1.14.4 BranchAndFinancialInstitutionIdentification6

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		153
		BranchIdentification <BrnchId>	[0..1]	±		154

2.1.14.4.1 FinancialInstitutionIdentification <FinInstnId>

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

FinancialInstitutionIdentification <FinInstnId> contains the following elements (see [FinancialInstitutionIdentification18](#) on page 148 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		BICFI <BICFI>	[0..1]	IdentifierSet		148
		ClearingSystemMemberIdentification <ClrSysMmbld>	[0..1]	±		149
		LEI <LEI>	[0..1]	IdentifierSet		149
		Name <Nm>	[0..1]	Text		149
		PostalAddress <PstlAdr>	[0..1]	±		149
		Other <Othr>	[0..1]	±		150

2.1.14.4.2 BranchIdentification <BrnchId>

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

BranchIdentification <BrnchId> contains the following elements (see [BranchData3](#) on page 151 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[0..1]	Text		151
		LEI <LEI>	[0..1]	IdentifierSet		151
		Name <Nm>	[0..1]	Text		151
		PostalAddress <PstlAdr>	[0..1]	±		151

2.1.14.5 ClearingSystemMemberIdentification2

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ClearingSystemIdentification <ClrSysId>	[0..1]	±		154
		MemberIdentification <Mmbld>	[1..1]	Text		155

2.1.14.5.1 ClearingSystemIdentification <ClrSysId>

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

ClearingSystemIdentification <ClrSysId> contains one of the following elements (see [ClearingSystemIdentification2Choice](#) on page 227 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		227
	Or}	Proprietary <Prtry>	[1..1]	Text		227

2.1.14.5.2 MemberIdentification <Mmbld>

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: [Max35Text](#) on page 310

2.1.15 Financial Instrument

2.1.15.1 SecurityIdentification19

Definition: Identification of a security.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ISIN <ISIN>	[0..1]	IdentifierSet		156
		OtherIdentification <OthrId>	[0..*]			156
		Identification <Id>	[1..1]	Text		156
		Suffix <Sfx>	[0..1]	Text		156
		Type <Tp>	[1..1]	±		157
		Description <Desc>	[0..1]	Text		157

Constraints

- **DescriptionPresenceRule**

If Description is not present then either ISIN or at least one occurrence of OtherIdentification must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00192
- *Error Text:* At least one identification must be present.

- **DescriptionUsageRule**

Description must be used alone as the last resort.

- **ISINGuideline**

When an ISIN code exists, it is strongly recommended that the ISIN be used.

- **ISINPresenceRule**

If ISIN is not present then either Description or at least one occurrence of OtherIdentification must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00194
- *Error Text:* At least one identification must be present.

- **OtherIdentificationPresenceRule**

If OtherIdentification is not present then either ISIN or Description must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00193
- *Error Text:* At least one identification must be present.

2.1.15.1.1 ISIN <ISIN>

Presence: [0..1]

Definition: International Securities Identification Number (ISIN). A numbering system designed by the United Nation's International Organisation for Standardisation (ISO). The ISIN is composed of a 2-character prefix representing the country of issue, followed by the national security number (if one exists), and a check digit. Each country has a national numbering agency that assigns ISIN numbers for securities in that country.

Datatype: [ISINOct2015Identifier on page 305](#)

2.1.15.1.2 OtherIdentification <OthrId>

Presence: [0..*]

Definition: Identification of a security by proprietary or domestic identification scheme.

OtherIdentification <OthrId> contains the following **OtherIdentification1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		156
		Suffix <Sfx>	[0..1]	Text		156
		Type <Tp>	[1..1]	±		157

2.1.15.1.2.1 Identification <Id>

Presence: [1..1]

Definition: Identification of a security.

Datatype: [Max35Text on page 310](#)

2.1.15.1.2.2 Suffix <Sfx>

Presence: [0..1]

Definition: Identifies the suffix of the security identification.

Datatype: [Max16Text on page 309](#)

2.1.15.1.2.3 Type <Tp>

Presence: [1..1]

Definition: Type of the identification.

Type <Tp> contains one of the following elements (see [IdentificationSource3Choice on page 159](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		159
	Or}	Proprietary <Prtry>	[1..1]	Text		159

2.1.15.1.3 Description <Desc>

Presence: [0..1]

Definition: Textual description of a security instrument.

Datatype: [Max140Text on page 308](#)

2.1.16 Financial Instrument Quantity

2.1.16.1 FinancialInstrumentQuantity1Choice

Definition: Choice between formats for the quantity of security.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Unit <Unit>	[1..1]	Quantity		157
	Or	FaceAmount <FaceAmt>	[1..1]	Amount		157
	Or}	AmortisedValue <AmtsdVal>	[1..1]	Amount		157

2.1.16.1.1 Unit <Unit>

Presence: [1..1]

Definition: Quantity expressed as a number, for example, a number of shares.

Datatype: [DecimalNumber on page 306](#)

2.1.16.1.2 FaceAmount <FaceAmt>

Presence: [1..1]

Definition: Quantity expressed as an amount representing the face amount, that is, the principal, of a debt instrument.

Datatype: [ImpliedCurrencyAndAmount on page 243](#)

2.1.16.1.3 AmortisedValue <AmtsdVal>

Presence: [1..1]

Definition: Quantity expressed as an amount representing the current amortised face amount of a bond, for example, a periodic reduction/increase of a bond's principal amount.

Datatype: [ImpliedCurrencyAndAmount](#) on page 243

2.1.17 Identification Information

2.1.17.1 GenericIdentification30

Definition: Information related to an identification, for example, party identification or account identification.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		158
		Issuer <Issr>	[1..1]	Text		158
		SchemeName <SchmeNm>	[0..1]	Text		158

2.1.17.1.1 Identification <Id>

Presence: [1..1]

Definition: Proprietary information, often a code, issued by the data source scheme issuer.

Datatype: [Exact4AlphaNumericText](#) on page 308

2.1.17.1.2 Issuer <Issr>

Presence: [1..1]

Definition: Entity that assigns the identification.

Datatype: [Max35Text](#) on page 310

2.1.17.1.3 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Short textual description of the scheme.

Datatype: [Max35Text](#) on page 310

2.1.17.2 GenericIdentification3

Definition: Information related to an identification, for example, party identification or account identification.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		158
		Issuer <Issr>	[0..1]	Text		159

2.1.17.2.1 Identification <Id>

Presence: [1..1]

Definition: Name or number assigned by an entity to enable recognition of that entity, for example, account identifier.

Datatype: [Max35Text on page 310](#)

2.1.17.2.2 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: [Max35Text on page 310](#)

2.1.17.3 IdentificationSource3Choice

Definition: Choice between source of identification of a financial instrument.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		159
	Or}	Proprietary <Prtry>	[1..1]	Text		159

2.1.17.3.1 Code <Cd>

Presence: [1..1]

Definition: Unique and unambiguous identification source, as assigned via a pre-determined code list.

Datatype: [ExternalFinancialInstrumentIdentificationType1Code on page 272](#)

2.1.17.3.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Unique and unambiguous identification source using a proprietary identification scheme.

Datatype: [Max35Text on page 310](#)

2.1.17.4 GenericIdentification32

Definition: Identification of an entity.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		159
		Type <Tp>	[0..1]	CodeSet		160
		Issuer <Issr>	[0..1]	CodeSet		160
		ShortName <ShrtNm>	[0..1]	Text		160

2.1.17.4.1 Identification <Id>

Presence: [1..1]

Definition: Identification of the entity.

Datatype: [Max35Text on page 310](#)

2.1.17.4.2 Type <Tp>*Presence:* [0..1]*Definition:* Type of identified entity.*Datatype:* [PartyType3Code on page 282](#)

CodeName	Name	Definition
OPOI	OriginatingPOI	Point Of Interaction initiating the card payment transaction.
MERC	Merchant	Merchant providing goods and service in the card payment transaction.
ACCP	Acceptor	Card acceptor, party accepting the card and presenting transaction data to the acquirer.
ITAG	IntermediaryAgent	Party acting on behalf of other parties to process or forward data to other parties.
ACQR	Acquirer	Entity acquiring card transactions.
CISS	CardIssuer	Party that issues cards.
DLIS	DelegateIssuer	Party to whom the card issuer delegates to authorise card payment transactions.

2.1.17.4.3 Issuer <Issr>*Presence:* [0..1]*Definition:* Entity assigning the identification (for example merchant, acceptor, acquirer, or tax authority).*Datatype:* [PartyType4Code on page 282](#)

CodeName	Name	Definition
MERC	Merchant	Merchant providing goods and service in the card payment transaction.
ACCP	Acceptor	Card acceptor, party accepting the card and presenting transaction data to the acquirer.
ITAG	IntermediaryAgent	Party acting on behalf of other parties to process or forward data to other parties.
ACQR	Acquirer	Entity acquiring card transactions.
CISS	CardIssuer	Party that issues cards.
TAXH	TaxAuthority	Tax authority.

2.1.17.4.4 ShortName <ShrtNm>*Presence:* [0..1]*Definition:* Name of the entity.*Datatype:* [Max35Text on page 310](#)**2.1.17.5 GenericIdentification1***Definition:* Information related to an identification, for example party identification or account identification.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		161
		SchemeName <SchmeNm>	[0..1]	Text		161
		Issuer <Issr>	[0..1]	Text		161

2.1.17.5.1 Identification <Id>

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: [Max35Text on page 310](#)

2.1.17.5.2 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Name of the identification scheme.

Datatype: [Max35Text on page 310](#)

2.1.17.5.3 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: [Max35Text on page 310](#)

2.1.18 Miscellaneous

2.1.18.1 RemittanceAmount2

Definition: Nature of the amount and currency on a document referred to in the remittance section, typically either the original amount due/payable or the amount actually remitted for the referenced document.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DuePayableAmount <DuePyblAmt>	[0..1]	Amount		162
		DiscountAppliedAmount <DscntApldAmt>	[0..*]			162
		Type <Tp>	[0..1]			163
	{Or	Code <Cd>	[1..1]	CodeSet		163
	Or}	Proprietary <Prtry>	[1..1]	Text		163
		Amount <Amt>	[1..1]	Amount		163
		CreditNoteAmount <CdtNoteAmt>	[0..1]	Amount		163
		TaxAmount <TaxAmt>	[0..*]			163
		Type <Tp>	[0..1]			164
	{Or	Code <Cd>	[1..1]	CodeSet		164
	Or}	Proprietary <Prtry>	[1..1]	Text		164
		Amount <Amt>	[1..1]	Amount		164
		AdjustmentAmountAndReason <AdjstmntAmtAndRsn>	[0..*]			164
		Amount <Amt>	[1..1]	Amount		165
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		165
		Reason <Rsn>	[0..1]	Text		165
		AdditionalInformation <AddtlInf>	[0..1]	Text		165
		RemittedAmount <RmtdAmt>	[0..1]	Amount		165

2.1.18.1.1 DuePayableAmount <DuePyblAmt>

Presence: [0..1]

Definition: Amount specified is the exact amount due and payable to the creditor.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 242

2.1.18.1.2 DiscountAppliedAmount <DscntApldAmt>

Presence: [0..*]

Definition: Amount specified for the referred document is the amount of discount to be applied to the amount due and payable to the creditor.

DiscountAppliedAmount <DscntApldAmt> contains the following **DiscountAmountAndType1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			163
	{Or	Code <Cd>	[1..1]	CodeSet		163
	Or}	Proprietary <Prtry>	[1..1]	Text		163
		Amount <Amt>	[1..1]	Amount		163

2.1.18.1.2.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of the amount.

Type <Tp> contains one of the following **DiscountAmountType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		163
	Or}	Proprietary <Prtry>	[1..1]	Text		163

2.1.18.1.2.1.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: [ExternalDiscountAmountType1Code](#) on page 269

2.1.18.1.2.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: [Max35Text](#) on page 310

2.1.18.1.2.2 Amount <Amt>

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 242

2.1.18.1.3 CreditNoteAmount <CdtNoteAmt>

Presence: [0..1]

Definition: Amount specified for the referred document is the amount of a credit note.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 242

2.1.18.1.4 TaxAmount <TaxAmt>

Presence: [0..*]

Definition: Quantity of cash resulting from the calculation of the tax.

TaxAmount <TaxAmt> contains the following **TaxAmountAndType1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			164
	{Or	Code <Cd>	[1..1]	CodeSet		164
	Or}	Proprietary <Prtry>	[1..1]	Text		164
		Amount <Amt>	[1..1]	Amount		164

2.1.18.1.4.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of the amount.

Type <Tp> contains one of the following **TaxAmountType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		164
	Or}	Proprietary <Prtry>	[1..1]	Text		164

2.1.18.1.4.1.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: [ExternalTaxAmountType1Code](#) on page 278

2.1.18.1.4.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: [Max35Text](#) on page 310

2.1.18.1.4.2 Amount <Amt>

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 242

2.1.18.1.5 AdjustmentAmountAndReason <AdjstmntAmtAndRsn>

Presence: [0..*]

Definition: Specifies detailed information on the amount and reason of the document adjustment.

AdjustmentAmountAndReason <AdjstmntAmtAndRsn> contains the following **DocumentAdjustment1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Amount		165
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		165
		Reason <Rsn>	[0..1]	Text		165
		AdditionalInformation <AddtlInf>	[0..1]	Text		165

2.1.18.1.5.1 Amount <Amt>

Presence: [1..1]

Definition: Amount of money of the document adjustment.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 242

2.1.18.1.5.2 CreditDebitIndicator <CdtDbtInd>

Presence: [0..1]

Definition: Specifies whether the adjustment must be subtracted or added to the total amount.

Datatype: [CreditDebitCode](#) on page 260

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

2.1.18.1.5.3 Reason <Rsn>

Presence: [0..1]

Definition: Specifies the reason for the adjustment.

Datatype: [Max4Text](#) on page 310

2.1.18.1.5.4 AdditionalInformation <AddtlInf>

Presence: [0..1]

Definition: Provides further details on the document adjustment.

Datatype: [Max140Text](#) on page 308

2.1.18.1.6 RemittedAmount <RmtdAmt>

Presence: [0..1]

Definition: Amount of money remitted for the referred document.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 242

2.1.18.2 SequenceRange1Choice

Definition: Specifies a choice of sequences.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	FromSequence <FrSeq>	[1..1]	Text		166
	Or	ToSequence <ToSeq>	[1..1]	Text		166
	Or	FromToSequence <FrToSeq>	[1..*]			166
		FromSequence <FrSeq>	[1..1]	Text		166
		ToSequence <ToSeq>	[1..1]	Text		166
	Or	EqualSequence <EQSeq>	[1..*]	Text		167
	Or}	NotEqualSequence <NEQSeq>	[1..*]	Text		167

2.1.18.2.1 FromSequence <FrSeq>

Presence: [1..1]

Definition: Start sequence of the range.

Datatype: [Max35Text](#) on page 310

2.1.18.2.2 ToSequence <ToSeq>

Presence: [1..1]

Definition: End sequence of the range.

Datatype: [Max35Text](#) on page 310

2.1.18.2.3 FromToSequence <FrToSeq>

Presence: [1..*]

Definition: Particular sequence range specified between a start sequence and an end sequence.

FromToSequence <FrToSeq> contains the following **SequenceRange1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FromSequence <FrSeq>	[1..1]	Text		166
		ToSequence <ToSeq>	[1..1]	Text		166

2.1.18.2.3.1 FromSequence <FrSeq>

Presence: [1..1]

Definition: Start sequence of the range.

Datatype: [Max35Text](#) on page 310

2.1.18.2.3.2 ToSequence <ToSeq>

Presence: [1..1]

Definition: End sequence of the range.

Datatype: [Max35Text](#) on page 310

2.1.18.2.4 EqualSequence <EQSeq>

Presence: [1..*]

Definition: Specified sequence to match.

Datatype: [Max35Text on page 310](#)

2.1.18.2.5 NotEqualSequence <NEQSeq>

Presence: [1..*]

Definition: Specified sequence to be excluded.

Datatype: [Max35Text on page 310](#)

2.1.18.3 Pagination1

Definition: Number used to sequence pages when it is not possible for data to be conveyed in a single message and the data has to be split across several pages (messages).

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PageNumber <PgNb>	[1..1]	Text		167
		LastPageIndicator <LastPgInd>	[1..1]	Indicator		167

2.1.18.3.1 PageNumber <PgNb>

Presence: [1..1]

Definition: Page number.

Datatype: [Max5NumericText on page 311](#)

2.1.18.3.2 LastPageIndicator <LastPgInd>

Presence: [1..1]

Definition: Indicates the last page.

Datatype: One of the following values must be used (see [YesNoIndicator on page 306](#)):

- *Meaning When True:* Yes
- *Meaning When False:* No

2.1.18.4 ReportingSource1Choice

Definition: Specifies the source used to generate the reporting.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		167
	Or}	Proprietary <Prtry>	[1..1]	Text		168

2.1.18.4.1 Code <Cd>

Presence: [1..1]

Definition: Reporting source, as published in an external reporting source code list.

Datatype: [ExternalReportingSource1Code](#) on page 276

2.1.18.4.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Reporting source, in a proprietary form.

Datatype: [Max35Text](#) on page 310

2.1.18.5 TotalTransactions6

Definition: Set of elements used to provide summary information on entries.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TotalEntries <TtlNtries>	[0..1]			168
		NumberOfEntries <NbOfNtries>	[0..1]	Text		169
		Sum <Sum>	[0..1]	Quantity		169
		TotalNetEntry <TtlNetNtry>	[0..1]	±		169
		TotalCreditEntries <TtlCdtNtries>	[0..1]	±		169
		TotalDebitEntries <TtlDbtNtries>	[0..1]	±		169
		TotalEntriesPerBankTransactionCode <TtlNtriesPerBkTxCd>	[0..*]			170
		NumberOfEntries <NbOfNtries>	[0..1]	Text		170
		Sum <Sum>	[0..1]	Quantity		170
		TotalNetEntry <TtlNetNtry>	[0..1]	±		170
		CreditEntries <CdtNtries>	[0..1]	±		171
		DebitEntries <DbtNtries>	[0..1]	±		171
		ForecastIndicator <FcstInd>	[0..1]	Indicator		171
		BankTransactionCode <BkTxCd>	[1..1]	±		171
		Availability <Avlbt>	[0..*]	±		172
		Date <Dt>	[0..1]	±		172

2.1.18.5.1 TotalEntries <TtlNtries>

Presence: [0..1]

Definition: Specifies the total number and sum of debit and credit entries.

TotalEntries <TtlNtries> contains the following **NumberAndSumOfTransactions4** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		NumberOfEntries <NbOfNtries>	[0..1]	Text		169
		Sum <Sum>	[0..1]	Quantity		169
		TotalNetEntry <TtlNetNtry>	[0..1]	±		169

2.1.18.5.1.1 NumberOfEntries <NbOfNtries>

Presence: [0..1]

Definition: Number of individual entries included in the report.

Datatype: Max15NumericText on page 309

2.1.18.5.1.2 Sum <Sum>

Presence: [0..1]

Definition: Total of all individual entries included in the report.

Datatype: DecimalNumber on page 306

2.1.18.5.1.3 TotalNetEntry <TtlNetNtry>

Presence: [0..1]

Definition: Resulting debit or credit amount of the netted amounts for all debit and credit entries.

TotalNetEntry <TtlNetNtry> contains the following elements (see AmountAndDirection35 on page 53 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Quantity		53
		CreditDebitIndicator <CdtDbtInd>	[1..1]	CodeSet		53

2.1.18.5.2 TotalCreditEntries <TtlCdtNtries>

Presence: [0..1]

Definition: Specifies the total number and sum of credit entries.

TotalCreditEntries <TtlCdtNtries> contains the following elements (see NumberAndSumOfTransactions1 on page 180 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		NumberOfEntries <NbOfNtries>	[0..1]	Text		180
		Sum <Sum>	[0..1]	Quantity		181

2.1.18.5.3 TotalDebitEntries <TtlDbtNtries>

Presence: [0..1]

Definition: Specifies the total number and sum of debit entries.

TotalDebitEntries <TtlDbtNtries> contains the following elements (see [NumberAndSumOfTransactions1](#) on page 180 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		NumberOfEntries <NbOfNtries>	[0..1]	Text		180
		Sum <Sum>	[0..1]	Quantity		181

2.1.18.5.4 TotalEntriesPerBankTransactionCode <TtlNtriesPerBkTxCd>

Presence: [0..*]

Definition: Specifies the total number and sum of entries per bank transaction code.

TotalEntriesPerBankTransactionCode <TtlNtriesPerBkTxCd> contains the following **TotalsPerBankTransactionCode5** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		NumberOfEntries <NbOfNtries>	[0..1]	Text		170
		Sum <Sum>	[0..1]	Quantity		170
		TotalNetEntry <TtlNetNtry>	[0..1]	±		170
		CreditEntries <CdtNtries>	[0..1]	±		171
		DebitEntries <DbtNtries>	[0..1]	±		171
		ForecastIndicator <FcstInd>	[0..1]	Indicator		171
		BankTransactionCode <BkTxCd>	[1..1]	±		171
		Availability <Avlbtty>	[0..*]	±		172
		Date <Dt>	[0..1]	±		172

2.1.18.5.4.1 NumberOfEntries <NbOfNtries>

Presence: [0..1]

Definition: Number of individual entries for the bank transaction code.

Datatype: [Max15NumericText](#) on page 309

2.1.18.5.4.2 Sum <Sum>

Presence: [0..1]

Definition: Total of all individual entries included in the report.

Datatype: [DecimalNumber](#) on page 306

2.1.18.5.4.3 TotalNetEntry <TtlNetNtry>

Presence: [0..1]

Definition: Total debit or credit amount that is the result of the netted amounts for all debit and credit entries per bank transaction code.

TotalNetEntry <TtlNetNtry> contains the following elements (see [AmountAndDirection35](#) on page 53 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Quantity		53
		CreditDebitIndicator <CdtDbtInd>	[1..1]	CodeSet		53

2.1.18.5.4.4 CreditEntries <CdtNtries>

Presence: [0..1]

Definition: Number of individual credit entries for the bank transaction code.

CreditEntries <CdtNtries> contains the following elements (see [NumberAndSumOfTransactions1](#) on page 180 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		NumberOfEntries <NbOfNtries>	[0..1]	Text		180
		Sum <Sum>	[0..1]	Quantity		181

2.1.18.5.4.5 DebitEntries <DbtNtries>

Presence: [0..1]

Definition: Number of individual debit entries for the bank transaction code.

DebitEntries <DbtNtries> contains the following elements (see [NumberAndSumOfTransactions1](#) on page 180 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		NumberOfEntries <NbOfNtries>	[0..1]	Text		180
		Sum <Sum>	[0..1]	Quantity		181

2.1.18.5.4.6 ForecastIndicator <FcstInd>

Presence: [0..1]

Definition: Indicates whether the bank transaction code is related to booked or forecast items.

Datatype: One of the following values must be used (see [TrueFalseIndicator](#) on page 306):

- *Meaning When True:* True
- *Meaning When False:* False

2.1.18.5.4.7 BankTransactionCode <BkTxCd>

Presence: [1..1]

Definition: Set of elements used to fully identify the type of underlying transaction resulting in an entry.

BankTransactionCode <BkTxCd> contains the following elements (see [BankTransactionCodeStructure4](#) on page 57 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Domain <Domn>	[0..1]	±		57
		Proprietary <Prtry>	[0..1]			58
		Code <Cd>	[1..1]	Text		58
		Issuer <Issr>	[0..1]	Text		58

2.1.18.5.4.8 Availability <Avlbty>

Presence: [0..*]

Definition: Set of elements used to indicate when the booked amount of money will become available, that is can be accessed and starts generating interest.

Availability <Avlbty> contains the following elements (see [CashAvailability1](#) on page 139 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Date <Dt>	[1..1]			139
	{Or	NumberOfDays <NbOfDays>	[1..1]	Text		139
	Or}	ActualDate <ActlDt>	[1..1]	Date		139
		Amount <Amt>	[1..1]	Amount		139
		CreditDebitIndicator <CdtDbtInd>	[1..1]	CodeSet		140

2.1.18.5.4.9 Date <Dt>

Presence: [0..1]

Definition: Indicates the date (and time) of the transaction summary.

Date <Dt> contains one of the following elements (see [DateAndDateTime2Choice](#) on page 145 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Date <Dt>	[1..1]	Date		145
	Or}	DateTime <DtTm>	[1..1]	DateTime		145

2.1.18.6 SupplementaryData1

Definition: Additional information that can not be captured in the structured fields and/or any other specific block.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PlaceAndName <PlcAndNm>	[0..1]	Text		173
		Envelope <Envlp>	[1..1]	(External Schema)		173

Constraints

- **SupplementaryDataRule**

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

2.1.18.6.1 PlaceAndName <PlcAndNm>

Presence: [0..1]

Definition: Unambiguous reference to the location where the supplementary data must be inserted in the message instance.

In the case of XML, this is expressed by a valid XPath.

Datatype: Max350Text on page 310

2.1.18.6.2 Envelope <Envlp>

Presence: [1..1]

Definition: Technical element wrapping the supplementary data.

Type: (External Schema)

Technical component that contains the validated supplementary data information. This technical envelope allows to segregate the supplementary data information from any other information.

2.1.18.7 Purpose2Choice

Definition: Specifies the underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		173
	Or}	Proprietary <Prtry>	[1..1]	Text		174

2.1.18.7.1 Code <Cd>

Presence: [1..1]

Definition: Underlying reason for the payment transaction, as published in an external purpose code list.

Datatype: ExternalPurpose1Code on page 276

2.1.18.7.2 Proprietary <Prtry>*Presence:* [1..1]*Definition:* Purpose, in a proprietary form.*Datatype:* Max35Text on page 310**2.1.18.8 TransactionInterest4***Definition:* Provide further details on transaction specific interest information that applies to the underlying transaction.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TotalInterestAndTaxAmount <TtlIntrstAndTaxAmt>	[0..1]	Amount		174
		Record <Rcrd>	[0..*]			174
		Amount <Amt>	[1..1]	Amount		175
		CreditDebitIndicator <CdtDbtInd>	[1..1]	CodeSet		175
		Type <Tp>	[0..1]			175
	{Or	Code <Cd>	[1..1]	CodeSet		176
	Or}	Proprietary <Prtry>	[1..1]	Text		176
		Rate <Rate>	[0..1]			176
		Type <Tp>	[1..1]	±		176
		ValidityRange <VldtyRg>	[0..1]	±		177
		FromDate <FrToDt>	[0..1]	±		177
		Reason <Rsn>	[0..1]	Text		177
		Tax <Tax>	[0..1]			177
		Identification <Id>	[0..1]	Text		177
		Rate <Rate>	[0..1]	Rate		178
		Amount <Amt>	[0..1]	Amount		178

2.1.18.8.1 TotalInterestAndTaxAmount <TtlIntrstAndTaxAmt>*Presence:* [0..1]*Definition:* Total amount of interests and taxes included in the entry amount.*Datatype:* ActiveOrHistoricCurrencyAndAmount on page 242**2.1.18.8.2 Record <Rcrd>***Presence:* [0..*]*Definition:* Individual interest record.

Record <Rcrd> contains the following **InterestRecord2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Amount		175
		CreditDebitIndicator <CdtDbtInd>	[1..1]	CodeSet		175
		Type <Tp>	[0..1]			175
	{Or	Code <Cd>	[1..1]	CodeSet		176
	Or}	Proprietary <Prtry>	[1..1]	Text		176
		Rate <Rate>	[0..1]			176
		Type <Tp>	[1..1]	±		176
		ValidityRange <VldtyRg>	[0..1]	±		177
		FromDate <FrToDt>	[0..1]	±		177
		Reason <Rsn>	[0..1]	Text		177
		Tax <Tax>	[0..1]			177
		Identification <Id>	[0..1]	Text		177
		Rate <Rate>	[0..1]	Rate		178
		Amount <Amt>	[0..1]	Amount		178

2.1.18.8.2.1 Amount <Amt>

Presence: [1..1]

Definition: Amount of interest included in the entry amount.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 242](#)

2.1.18.8.2.2 CreditDebitIndicator <CdtDbtInd>

Presence: [1..1]

Definition: Indicates whether the interest amount included in the entry is credit or debit amount.

Usage: A zero amount is considered to be a credit.

Datatype: [CreditDebitCode on page 260](#)

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

2.1.18.8.2.3 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of interest.

Type <Tp> contains one of the following **InterestType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		176
	Or}	Proprietary <Prtry>	[1..1]	Text		176

2.1.18.8.2.3.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the type of interest.

Datatype: [InterestType1Code](#) on page 280

CodeName	Name	Definition
INDY	IntraDay	During or within a business day.
OVN	OverNight	Period of time between the end of a business day and the start of the next business day (usually the day after).

2.1.18.8.2.3.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies the type of interest in uncoded form.

Datatype: [Max35Text](#) on page 310

2.1.18.8.2.4 Rate <Rate>

Presence: [0..1]

Definition: Set of elements used to qualify the interest rate.

Rate <Rate> contains the following **Rate4** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[1..1]	±		176
		ValidityRange <VldtyRg>	[0..1]	±		177

2.1.18.8.2.4.1 Type <Tp>

Presence: [1..1]

Definition: Specifies the type of interest rate.

Type <Tp> contains one of the following elements (see [RateType4Choice](#) on page 198 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Percentage <Pctg>	[1..1]	Rate		199
	Or}	Other <Othr>	[1..1]	Text		199

2.1.18.8.2.4.2 ValidityRange <VldtyRg>

Presence: [0..1]

Definition: An amount range where the interest rate is applicable.

ValidityRange <VldtyRg> contains the following elements (see [ActiveOrHistoricCurrencyAndAmountRange2](#) on page 55 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	±		55
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		56
		Currency <Ccy>	[1..1]	CodeSet		56

2.1.18.8.2.5 FromToDate <FrToDt>

Presence: [0..1]

Definition: Range of time between a start date and an end date for the calculation of the interest.

FromToDate <FrToDt> contains the following elements (see [DateTimePeriod1](#) on page 146 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FromDateTime <FrDtTm>	[1..1]	DateTime		146
		ToDateTime <ToDtTm>	[1..1]	DateTime		146

2.1.18.8.2.6 Reason <Rsn>

Presence: [0..1]

Definition: Specifies the reason for the interest.

Datatype: [Max35Text](#) on page 310

2.1.18.8.2.7 Tax <Tax>

Presence: [0..1]

Definition: Provides details on the tax applied to charges.

Tax <Tax> contains the following **TaxCharges2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[0..1]	Text		177
		Rate <Rate>	[0..1]	Rate		178
		Amount <Amt>	[0..1]	Amount		178

2.1.18.8.2.7.1 Identification <Id>

Presence: [0..1]

Definition: Unique reference to unambiguously identify the nature of the tax levied, such as Value Added Tax (VAT).

Datatype: [Max35Text on page 310](#)

2.1.18.8.2.7.2 Rate <Rate>

Presence: [0..1]

Definition: Rate used to calculate the tax.

Datatype: [PercentageRate on page 307](#)

2.1.18.8.2.7.3 Amount <Amt>

Presence: [0..1]

Definition: Amount of money resulting from the calculation of the tax.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 242](#)

2.1.18.9 GroupHeader81

Definition: Provides further details on the message.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		MessageIdentification <MsgId>	[1..1]	Text		178
		CreationDateTime <CreDtTm>	[1..1]	DateTime		178
		MessageRecipient <MsgRcpt>	[0..1]	±		178
		MessagePagination <MsgPgntn>	[0..1]	±		179
		OriginalBusinessQuery <OrgnlBizQry>	[0..1]	±		179
		AdditionalInformation <AddtlInf>	[0..1]	Text		179

2.1.18.9.1 MessageIdentification <MsgId>

Presence: [1..1]

Definition: Point to point reference, as assigned by the account servicing institution, and sent to the account owner or the party authorised to receive the message, to unambiguously identify the message.

Usage: The account servicing institution has to make sure that MessageIdentification is unique per account owner for a pre-agreed period.

Datatype: [Max35Text on page 310](#)

2.1.18.9.2 CreationDateTime <CreDtTm>

Presence: [1..1]

Definition: Date and time at which the message was created.

Datatype: [ISODatetime on page 303](#)

2.1.18.9.3 MessageRecipient <MsgRcpt>

Presence: [0..1]

Definition: Party authorised by the account owner to receive information about movements on the account.

Usage: MessageRecipient should only be identified when different from the account owner.

MessageRecipient <MsgRcpt> contains the following elements (see [PartyIdentification135](#) on page 184 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		185
		PostalAddress <PstlAdr>	[0..1]	±		185
		Identification <Id>	[0..1]	±		186
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		186
		ContactDetails <CtctDtls>	[0..1]	±		187

2.1.18.9.4 MessagePagination <MsgPgtn>

Presence: [0..1]

Definition: Provides details on the page number of the message.

Usage: The pagination of the message is only allowed when agreed between the parties.

MessagePagination <MsgPgtn> contains the following elements (see [Pagination1](#) on page 167 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PageNumber <PgNb>	[1..1]	Text		167
		LastPageIndicator <LastPgInd>	[1..1]	Indicator		167

2.1.18.9.5 OriginalBusinessQuery <OrgnlBizQry>

Presence: [0..1]

Definition: Unique identification, as assigned by the original requestor, to unambiguously identify the business query message.

OriginalBusinessQuery <OrgnlBizQry> contains the following elements (see [OriginalBusinessQuery1](#) on page 181 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		MessageIdentification <MsgId>	[1..1]	Text		181
		MessageNameIdentification <MsgNmId>	[0..1]	Text		181
		CreationDateTime <CreDtTm>	[0..1]	DateTime		182

2.1.18.9.6 AdditionalInformation <AddtlInf>

Presence: [0..1]

Definition: Further details of the message.

Datatype: [Max500Text](#) on page 310

2.1.18.10 YieldedOrValueType1Choice

Definition: Choice of value type.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Yielded <Yldd>	[1..1]	Indicator		180
	Or}	ValueType <ValTp>	[1..1]	CodeSet		180

2.1.18.10.1 Yielded <Yldd>

Presence: [1..1]

Definition: Indicates whether the price is expressed as a yield.

Datatype: One of the following values must be used (see [YesNoIndicator](#) on page 306):

- *Meaning When True:* Yes
- *Meaning When False:* No

2.1.18.10.2 ValueType <ValTp>

Presence: [1..1]

Definition: Type of value in which the price is expressed.

Datatype: [PriceValueType1Code](#) on page 289

CodeName	Name	Definition
DISC	Discount	Price expressed as a number of percentage points below par, for example, a discount price of 2.0% equals a price of 98 when par is 100.
PREM	Premium	Price expressed as a number of percentage points above par, for example, a premium price of 2.0% equals a price of 102 when par is 100.
PARV	Par	Price is the face amount.

2.1.18.11 NumberAndSumOfTransactions1

Definition: Set of elements providing the total sum of entries.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		NumberOfEntries <NbOfNtries>	[0..1]	Text		180
		Sum <Sum>	[0..1]	Quantity		181

2.1.18.11.1 NumberOfEntries <NbOfNtries>

Presence: [0..1]

Definition: Number of individual entries included in the report.

Datatype: [Max15NumericText](#) on page 309

2.1.18.11.2 Sum <Sum>

Presence: [0..1]

Definition: Total of all individual entries included in the report.

Datatype: [DecimalNumber on page 306](#)

2.1.18.12 TransactionIdentifier1

Definition: Identification of the transaction in an unambiguous way.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TransactionDateTime <TxDtTm>	[1..1]	DateTime		181
		TransactionReference <TxRef>	[1..1]	Text		181

2.1.18.12.1 TransactionDateTime <TxDtTm>

Presence: [1..1]

Definition: Local date and time of the transaction assigned by the POI (Point Of Interaction).

Datatype: [ISODatetime on page 303](#)

2.1.18.12.2 TransactionReference <TxRef>

Presence: [1..1]

Definition: Identification of the transaction that has to be unique for a time period.

Datatype: [Max35Text on page 310](#)

2.1.18.13 OriginalBusinessQuery1

Definition: Unique identification, as assigned by the original requestor, to unambiguously identify the business query message.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		MessageIdentification <MsgId>	[1..1]	Text		181
		MessageNameIdentification <MsgNmId>	[0..1]	Text		181
		CreationDateTime <CreDtTm>	[0..1]	DateTime		182

2.1.18.13.1 MessageIdentification <MsgId>

Presence: [1..1]

Definition: Point to point reference, as assigned by the original initiating party, to unambiguously identify the original query message.

Datatype: [Max35Text on page 310](#)

2.1.18.13.2 MessageNameIdentification <MsgNmId>

Presence: [0..1]

Definition: Specifies the query message name identifier to which the message refers.

Datatype: [Max35Text on page 310](#)

2.1.18.13.3 CreationDateTime <CreDtTm>

Presence: [0..1]

Definition: Date and time at which the message was created.

Datatype: [ISODatetime on page 303](#)

2.1.19 Organisation Identification

2.1.19.1 OrganisationIdentification29

Definition: Unique and unambiguous way to identify an organisation.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AnyBIC <AnyBIC>	[0..1]	IdentifierSet		182
		LEI <LEI>	[0..1]	IdentifierSet		182
		Other <Othr>	[0..*]			182
		Identification <Id>	[1..1]	Text		183
		SchemeName <SchmeNm>	[0..1]			183
	{Or	Code <Cd>	[1..1]	CodeSet		183
	Or}	Proprietary <Prtry>	[1..1]	Text		183
		Issuer <Issr>	[0..1]	Text		183

2.1.19.1.1 AnyBIC <AnyBIC>

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: [AnyBICDec2014Identifier on page 303](#)

2.1.19.1.2 LEI <LEI>

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: [LEIIdentifier on page 305](#)

2.1.19.1.3 Other <Othr>

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

Other <Othr> contains the following **GenericOrganisationIdentification1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		183
		SchemeName <SchmeNm>	[0..1]			183
	{Or	Code <Cd>	[1..1]	CodeSet		183
	Or}	Proprietary <Prtry>	[1..1]	Text		183
		Issuer <Issr>	[0..1]	Text		183

2.1.19.1.3.1 Identification <Id>

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: [Max35Text on page 310](#)

2.1.19.1.3.2 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Name of the identification scheme.

SchemeName <SchmeNm> contains one of the following **OrganisationIdentificationSchemeName1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		183
	Or}	Proprietary <Prtry>	[1..1]	Text		183

2.1.19.1.3.2.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: [ExternalOrganisationIdentification1Code on page 274](#)

2.1.19.1.3.2.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: [Max35Text on page 310](#)

2.1.19.1.3.3 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: [Max35Text on page 310](#)

2.1.20 Party Identification

2.1.20.1 Party40Choice

Definition: Identification of a person, an organisation or a financial institution.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Party <Pty>	[1..1]	±		184
	Or}	Agent <Agt>	[1..1]	±		184

2.1.20.1.1 Party <Pty>

Presence: [1..1]

Definition: Identification of a person or an organisation.

Party <Pty> contains the following elements (see [PartyIdentification135](#) on page 184 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		185
		PostalAddress <PstlAdr>	[0..1]	±		185
		Identification <Id>	[0..1]	±		186
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		186
		ContactDetails <CtctDtls>	[0..1]	±		187

2.1.20.1.2 Agent <Agt>

Presence: [1..1]

Definition: Identification of a financial institution.

Agent <Agt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 153 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		153
		BranchIdentification <BrnchId>	[0..1]	±		154

2.1.20.2 PartyIdentification135

Definition: Specifies the identification of a person or an organisation.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		185
		PostalAddress <PstlAdr>	[0..1]	±		185
		Identification <Id>	[0..1]	±		186
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		186
		ContactDetails <CtctDtls>	[0..1]	±		187

2.1.20.2.1 Name <Nm>

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: [Max140Text on page 308](#)

2.1.20.2.2 PostalAddress <PstlAdr>

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

PostalAddress <PstlAdr> contains the following elements (see [PostalAddress24](#) on page 194 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AddressType <AdrTp>	[0..1]			194
	{Or	Code <Cd>	[1..1]	CodeSet		195
	Or}	Proprietary <Prtry>	[1..1]	±		195
		Department <Dept>	[0..1]	Text		195
		SubDepartment <SubDept>	[0..1]	Text		195
		StreetName <StrtNm>	[0..1]	Text		196
		BuildingNumber <BldgNb>	[0..1]	Text		196
		BuildingName <BldgNm>	[0..1]	Text		196
		Floor <Flr>	[0..1]	Text		196
		PostBox <PstBx>	[0..1]	Text		196
		Room <Room>	[0..1]	Text		196
		PostCode <PstCd>	[0..1]	Text		196
		TownName <TwnNm>	[0..1]	Text		196
		TownLocationName <TwnLctnNm>	[0..1]	Text		197
		DistrictName <DstrctNm>	[0..1]	Text		197
		CountrySubDivision <CtrySubDvsn>	[0..1]	Text		197
		Country <Ctry>	[0..1]	CodeSet		197
		AddressLine <AdrLine>	[0..7]	Text		197

2.1.20.2.3 Identification <Id>

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

Identification <Id> contains one of the following elements (see [Party38Choice](#) on page 187 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	OrganisationIdentification <OrgId>	[1..1]	±		187
	Or}	PrivateIdentification <PrvtId>	[1..1]	±		188

2.1.20.2.4 CountryOfResidence <CtryOfRes>

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: [CountryCode](#) on page 259

2.1.20.2.5 ContactDetails <CtctDtls>

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

ContactDetails <CtctDtls> contains the following elements (see [Contact4](#) on page 191 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		NamePrefix <NmPrfx>	[0..1]	CodeSet		191
		Name <Nm>	[0..1]	Text		192
		PhoneNumber <PhneNb>	[0..1]	Text		192
		MobileNumber <MobNb>	[0..1]	Text		192
		FaxNumber <FaxNb>	[0..1]	Text		192
		EmailAddress <EmailAdr>	[0..1]	Text		192
		EmailPurpose <EmailPurp>	[0..1]	Text		192
		JobTitle <JobTitl>	[0..1]	Text		192
		Responsibility <Rspnsblty>	[0..1]	Text		193
		Department <Dept>	[0..1]	Text		193
		Other <Othr>	[0..*]			193
		ChannelType <ChanlTp>	[1..1]	Text		193
		Identification <Id>	[0..1]	Text		193
		PreferredMethod <PrefrdMtd>	[0..1]	CodeSet		193

2.1.20.3 Party38Choice

Definition: Nature or use of the account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	OrganisationIdentification <Orgld>	[1..1]	±		187
	Or}	PrivateIdentification <Prvtld>	[1..1]	±		188

2.1.20.3.1 OrganisationIdentification <Orgld>

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

OrganisationIdentification <OrgId> contains the following elements (see [OrganisationIdentification29](#) on page 182 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AnyBIC <AnyBIC>	[0..1]	IdentifierSet		182
		LEI <LEI>	[0..1]	IdentifierSet		182
		Other <Othr>	[0..*]			182
		Identification <Id>	[1..1]	Text		183
		SchemeName <SchmeNm>	[0..1]			183
	{Or	Code <Cd>	[1..1]	CodeSet		183
	Or}	Proprietary <Prtry>	[1..1]	Text		183
		Issuer <Issr>	[0..1]	Text		183

2.1.20.3.2 PrivateIdentification <PrvtId>

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

PrivateIdentification <PrvtId> contains the following elements (see [PersonIdentification13](#) on page 188 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DateAndPlaceOfBirth <DtAndPlcOfBirth>	[0..1]			189
		BirthDate <BirthDt>	[1..1]	Date		189
		ProvinceOfBirth <PrvcOfBirth>	[0..1]	Text		189
		CityOfBirth <CityOfBirth>	[1..1]	Text		189
		CountryOfBirth <CtryOfBirth>	[1..1]	CodeSet		190
		Other <Othr>	[0..*]			190
		Identification <Id>	[1..1]	Text		190
		SchemeName <SchmeNm>	[0..1]			190
	{Or	Code <Cd>	[1..1]	CodeSet		190
	Or}	Proprietary <Prtry>	[1..1]	Text		191
		Issuer <Issr>	[0..1]	Text		191

2.1.21 Person Identification

2.1.21.1 PersonIdentification13

Definition: Unique and unambiguous way to identify a person.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DateAndPlaceOfBirth <DtAndPlcOfBirth>	[0..1]			189
		BirthDate <BirthDt>	[1..1]	Date		189
		ProvinceOfBirth <PrvcOfBirth>	[0..1]	Text		189
		CityOfBirth <CityOfBirth>	[1..1]	Text		189
		CountryOfBirth <CtryOfBirth>	[1..1]	CodeSet		190
		Other <Othr>	[0..*]			190
		Identification <Id>	[1..1]	Text		190
		SchemeName <SchmeNm>	[0..1]			190
	{Or	Code <Cd>	[1..1]	CodeSet		190
	Or}	Proprietary <Prtry>	[1..1]	Text		191
		Issuer <Issr>	[0..1]	Text		191

2.1.21.1.1 DateAndPlaceOfBirth <DtAndPlcOfBirth>

Presence: [0..1]

Definition: Date and place of birth of a person.

DateAndPlaceOfBirth <DtAndPlcOfBirth> contains the following **DateAndPlaceOfBirth1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		BirthDate <BirthDt>	[1..1]	Date		189
		ProvinceOfBirth <PrvcOfBirth>	[0..1]	Text		189
		CityOfBirth <CityOfBirth>	[1..1]	Text		189
		CountryOfBirth <CtryOfBirth>	[1..1]	CodeSet		190

2.1.21.1.1.1 BirthDate <BirthDt>

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: [ISODate](#) on page 303

2.1.21.1.1.2 ProvinceOfBirth <PrvcOfBirth>

Presence: [0..1]

Definition: Province where a person was born.

Datatype: [Max35Text](#) on page 310

2.1.21.1.1.3 CityOfBirth <CityOfBirth>

Presence: [1..1]

Definition: City where a person was born.

Datatype: [Max35Text on page 310](#)

2.1.21.1.1.4 CountryOfBirth <CtryOfBirth>

Presence: [1..1]

Definition: Country where a person was born.

Datatype: [CountryCode on page 259](#)

2.1.21.1.2 Other <Othr>

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

Other <Othr> contains the following **GenericPersonIdentification1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		190
		SchemeName <SchmeNm>	[0..1]			190
	{Or	Code <Cd>	[1..1]	CodeSet		190
	Or}	Proprietary <Prtry>	[1..1]	Text		191
		Issuer <Issr>	[0..1]	Text		191

2.1.21.1.2.1 Identification <Id>

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: [Max35Text on page 310](#)

2.1.21.1.2.2 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Name of the identification scheme.

SchemeName <SchmeNm> contains one of the following **PersonIdentificationSchemeName1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		190
	Or}	Proprietary <Prtry>	[1..1]	Text		191

2.1.21.1.2.2.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: [ExternalPersonIdentification1Code on page 274](#)

2.1.21.1.2.2.2 Proprietary <Prtry>*Presence:* [1..1]*Definition:* Name of the identification scheme, in a free text form.*Datatype:* [Max35Text on page 310](#)**2.1.21.1.2.3 Issuer <Issr>***Presence:* [0..1]*Definition:* Entity that assigns the identification.*Datatype:* [Max35Text on page 310](#)**2.1.21.2 Contact4***Definition:* Specifies the details of the contact person.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		NamePrefix <NmPrfx>	[0..1]	CodeSet		191
		Name <Nm>	[0..1]	Text		192
		PhoneNumber <PhneNb>	[0..1]	Text		192
		MobileNumber <MobNb>	[0..1]	Text		192
		FaxNumber <FaxNb>	[0..1]	Text		192
		EmailAddress <EmailAdr>	[0..1]	Text		192
		EmailPurpose <EmailPurp>	[0..1]	Text		192
		JobTitle <JobTitl>	[0..1]	Text		192
		Responsibility <Rspnsblty>	[0..1]	Text		193
		Department <Dept>	[0..1]	Text		193
		Other <Othr>	[0..*]			193
		ChannelType <ChanITp>	[1..1]	Text		193
		Identification <Id>	[0..1]	Text		193
		PreferredMethod <PrefrdMtd>	[0..1]	CodeSet		193

2.1.21.2.1 NamePrefix <NmPrfx>*Presence:* [0..1]*Definition:* Specifies the terms used to formally address a person.*Datatype:* [NamePrefix2Code on page 280](#)

CodeName	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MISS	Miss	Title of the person is Miss.

CodeName	Name	Definition
MIST	Mister	Title of the person is Mister or Mr.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).

2.1.21.2.2 Name <Nm>

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: [Max140Text on page 308](#)

2.1.21.2.3 PhoneNumber <PhneNb>

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: [PhoneNumber on page 311](#)

2.1.21.2.4 MobileNumber <MobNb>

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: [PhoneNumber on page 311](#)

2.1.21.2.5 FaxNumber <FaxNb>

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: [PhoneNumber on page 311](#)

2.1.21.2.6 EmailAddress <EmailAdr>

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: [Max2048Text on page 309](#)

2.1.21.2.7 EmailPurpose <EmailPurp>

Presence: [0..1]

Definition: Purpose for which an email address may be used.

Datatype: [Max35Text on page 310](#)

2.1.21.2.8 JobTitle <JobTitl>

Presence: [0..1]

Definition: Title of the function.

Datatype: [Max35Text on page 310](#)

2.1.21.2.9 Responsibility <Rspnsblty>

Presence: [0..1]

Definition: Role of a person in an organisation.

Datatype: [Max35Text on page 310](#)

2.1.21.2.10 Department <Dept>

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: [Max70Text on page 311](#)

2.1.21.2.11 Other <Othr>

Presence: [0..*]

Definition: Contact details in another form.

Other <Othr> contains the following **OtherContact1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ChannelType <ChanITp>	[1..1]	Text		193
		Identification <Id>	[0..1]	Text		193

2.1.21.2.11.1 ChannelType <ChanITp>

Presence: [1..1]

Definition: Method used to contact the financial institution's contact for the specific tax region.

Datatype: [Max4Text on page 310](#)

2.1.21.2.11.2 Identification <Id>

Presence: [0..1]

Definition: Communication value such as phone number or email address.

Datatype: [Max128Text on page 308](#)

2.1.21.2.12 PreferredMethod <PrefrdMtd>

Presence: [0..1]

Definition: Preferred method used to reach the contact.

Datatype: [PreferredContactMethod1Code on page 288](#)

CodeName	Name	Definition
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.

CodeName	Name	Definition
FAXX	Fax	Preferred method used to reach the contact is per fax.
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.

2.1.22 Postal Address

2.1.22.1 PostalAddress24

Definition: Information that locates and identifies a specific address, as defined by postal services.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AddressType <AdrTp>	[0..1]			194
	{Or	Code <Cd>	[1..1]	CodeSet		195
	Or}	Proprietary <Prtry>	[1..1]	±		195
		Department <Dept>	[0..1]	Text		195
		SubDepartment <SubDept>	[0..1]	Text		195
		StreetName <StrtNm>	[0..1]	Text		196
		BuildingNumber <BldgNb>	[0..1]	Text		196
		BuildingName <BldgNm>	[0..1]	Text		196
		Floor <Flr>	[0..1]	Text		196
		PostBox <PstBx>	[0..1]	Text		196
		Room <Room>	[0..1]	Text		196
		PostCode <PstCd>	[0..1]	Text		196
		TownName <TwnNm>	[0..1]	Text		196
		TownLocationName <TwnLctnNm>	[0..1]	Text		197
		DistrictName <DstrctNm>	[0..1]	Text		197
		CountrySubDivision <CtrySubDvsn>	[0..1]	Text		197
		Country <Ctry>	[0..1]	CodeSet		197
		AddressLine <AdrLine>	[0..7]	Text		197

2.1.22.1.1 AddressType <AdrTp>

Presence: [0..1]

Definition: Identifies the nature of the postal address.

AddressType <AdrTp> contains one of the following **AddressType3Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		195
	Or}	Proprietary <Prtry>	[1..1]	±		195

2.1.22.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Type of address expressed as a code.

Datatype: [AddressType2Code](#) on page 244

CodeName	Name	Definition
ADDR	Postal	Address is the complete postal address.
PBOX	POBox	Address is a postal office (PO) box.
HOME	Residential	Address is the home address.
BIZZ	Business	Address is the business address.
MLTO	MailTo	Address is the address to which mail is sent.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.

2.1.22.1.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Type of address expressed as a proprietary code.

Proprietary <Prtry> contains the following elements (see [GenericIdentification30](#) on page 158 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		158
		Issuer <Issr>	[1..1]	Text		158
		SchemeName <SchmeNm>	[0..1]	Text		158

2.1.22.1.2 Department <Dept>

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: [Max70Text](#) on page 311

2.1.22.1.3 SubDepartment <SubDept>

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: [Max70Text](#) on page 311

2.1.22.1.4 StreetName <StrtNm>

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: [Max70Text on page 311](#)

2.1.22.1.5 BuildingNumber <BldgNb>

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: [Max16Text on page 309](#)

2.1.22.1.6 BuildingName <BldgNm>

Presence: [0..1]

Definition: Name of the building or house.

Datatype: [Max35Text on page 310](#)

2.1.22.1.7 Floor <Flr>

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: [Max70Text on page 311](#)

2.1.22.1.8 PostBox <PstBx>

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: [Max16Text on page 309](#)

2.1.22.1.9 Room <Room>

Presence: [0..1]

Definition: Building room number.

Datatype: [Max70Text on page 311](#)

2.1.22.1.10 PostCode <PstCd>

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: [Max16Text on page 309](#)

2.1.22.1.11 TownName <TwnNm>

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: [Max35Text on page 310](#)

2.1.22.1.12 TownLocationName <TwnLctnNm>

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: [Max35Text on page 310](#)

2.1.22.1.13 DistrictName <DstrctNm>

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: [Max35Text on page 310](#)

2.1.22.1.14 CountrySubDivision <CtrySubDvsn>

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: [Max35Text on page 310](#)

2.1.22.1.15 Country <Ctry>

Presence: [0..1]

Definition: Nation with its own government.

Datatype: [CountryCode on page 259](#)

2.1.22.1.16 AddressLine <AdrLine>

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: [Max70Text on page 311](#)

2.1.23 Price

2.1.23.1 Price7

Definition: Type and information about a price.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[1..1]	±		197
		Value <Val>	[1..1]	±		198

2.1.23.1.1 Type <Tp>

Presence: [1..1]

Definition: Specification of the price type.

Type <Tp> contains one of the following elements (see [YieldedOrValueType1Choice](#) on page 180 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Yielded <Yldd>	[1..1]	Indicator		180
	Or}	ValueType <ValTp>	[1..1]	CodeSet		180

2.1.23.1.2 Value <Val>

Presence: [1..1]

Definition: Value of the price, for example, as a currency and value.

Value <Val> contains one of the following elements (see [PriceRateOrAmount3Choice](#) on page 198 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Rate <Rate>	[1..1]	Rate		198
	Or}	Amount <Amt>	[1..1]	Amount		198

2.1.23.2 PriceRateOrAmount3Choice

Definition: Choice of formats for the price.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Rate <Rate>	[1..1]	Rate		198
	Or}	Amount <Amt>	[1..1]	Amount		198

2.1.23.2.1 Rate <Rate>

Presence: [1..1]

Definition: Price expressed as a rate, that is percentage.

Datatype: [PercentageRate](#) on page 307

2.1.23.2.2 Amount <Amt>

Presence: [1..1]

Definition: Price expressed as a currency and value.

Datatype: [ActiveOrHistoricCurrencyAnd13DecimalAmount](#) on page 241

2.1.24 Rate

2.1.24.1 RateType4Choice

Definition: Specifies the rate as a percentage or a text.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Percentage <Pctg>	[1..1]	Rate		199
	Or}	Other <Othr>	[1..1]	Text		199

2.1.24.1.1 Percentage <Pctg>

Presence: [1..1]

Definition: Ratio of the amount of interest paid during a certain period of time compared to the principal amount of the interest bearing financial instrument.

Datatype: [PercentageRate](#) on page 307

2.1.24.1.2 Other <Othr>

Presence: [1..1]

Definition: Rate type expressed, in an other form.

Datatype: [Max35Text](#) on page 310

2.1.25 Remittance

2.1.25.1 Garnishment3

Definition: Provides remittance information about a payment for garnishment-related purposes.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[1..1]			199
		CodeOrProprietary <CdOrPrtry>	[1..1]			200
	{Or	Code <Cd>	[1..1]	CodeSet		200
	Or}	Proprietary <Prtry>	[1..1]	Text		200
		Issuer <Issr>	[0..1]	Text		200
		Garnishee <Grnshee>	[0..1]	±		200
		GarnishmentAdministrator <GrnshmtAdmstr>	[0..1]	±		201
		ReferenceNumber <RefNb>	[0..1]	Text		201
		Date <Dt>	[0..1]	Date		201
		RemittedAmount <RmtdAmt>	[0..1]	Amount		201
		FamilyMedicalInsuranceIndicator <FmlyMdclInsrncInd>	[0..1]	Indicator		202
		EmployeeTerminationIndicator <MplyeeTermtnInd>	[0..1]	Indicator		202

2.1.25.1.1 Type <Tp>

Presence: [1..1]

Definition: Specifies the type of garnishment.

Type <Tp> contains the following **GarnishmentType1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CodeOrProprietary <CdOrPrtry>	[1..1]			200
	{Or	Code <Cd>	[1..1]	CodeSet		200
	Or}	Proprietary <Prtry>	[1..1]	Text		200
		Issuer <Issr>	[0..1]	Text		200

2.1.25.1.1.1 CodeOrProprietary <CdOrPrtry>

Presence: [1..1]

Definition: Provides the type details of the garnishment.

CodeOrProprietary <CdOrPrtry> contains one of the following **GarnishmentType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		200
	Or}	Proprietary <Prtry>	[1..1]	Text		200

2.1.25.1.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Garnishment type in a coded form.

Would suggest this to be an External Code List to contain:

GNCS Garnishment from a third party payer for Child Support

GNDP Garnishment from a Direct Payer for Child Support

GTPP Garnishment from a third party payer to taxing agency.

Datatype: [ExternalGarnishmentType1Code on page 272](#)

2.1.25.1.1.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Proprietary identification of the type of garnishment.

Datatype: [Max35Text on page 310](#)

2.1.25.1.1.2 Issuer <Issr>

Presence: [0..1]

Definition: Identification of the issuer of the garnishment type.

Datatype: [Max35Text on page 310](#)

2.1.25.1.2 Garnishee <Grnshee>

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor, in this case, to the garnisher.

Garnishee <Grnshee> contains the following elements (see [PartyIdentification135](#) on page 184 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		185
		PostalAddress <PstlAdr>	[0..1]	±		185
		Identification <Id>	[0..1]	±		186
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		186
		ContactDetails <CtctDtls>	[0..1]	±		187

2.1.25.1.3 GarnishmentAdministrator <GrnshmtAdmstr>

Presence: [0..1]

Definition: Party on the credit side of the transaction who administers the garnishment on behalf of the ultimate beneficiary.

GarnishmentAdministrator <GrnshmtAdmstr> contains the following elements (see [PartyIdentification135](#) on page 184 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		185
		PostalAddress <PstlAdr>	[0..1]	±		185
		Identification <Id>	[0..1]	±		186
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		186
		ContactDetails <CtctDtls>	[0..1]	±		187

2.1.25.1.4 ReferenceNumber <RefNb>

Presence: [0..1]

Definition: Reference information that is specific to the agency receiving the garnishment.

Datatype: [Max140Text](#) on page 308

2.1.25.1.5 Date <Dt>

Presence: [0..1]

Definition: Date of payment which garnishment was taken from.

Datatype: [ISODate](#) on page 303

2.1.25.1.6 RemittedAmount <RmtdAmt>

Presence: [0..1]

Definition: Amount of money remitted for the referred document.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 242

2.1.25.1.7 FamilyMedicalInsuranceIndicator <FmlyMdclInsrncInd>

Presence: [0..1]

Definition: Indicates if the person to whom the garnishment applies (that is, the ultimate debtor) has family medical insurance coverage available.

Datatype: One of the following values must be used (see [TrueFalseIndicator](#) on page 306):

- *Meaning When True:* True
- *Meaning When False:* False

2.1.25.1.8 EmployeeTerminationIndicator <MplyeeTermtnInd>

Presence: [0..1]

Definition: Indicates if the employment of the person to whom the garnishment applies (that is, the ultimate debtor) has been terminated.

Datatype: One of the following values must be used (see [TrueFalseIndicator](#) on page 306):

- *Meaning When True:* True
- *Meaning When False:* False

2.1.25.2 RemittanceInformation16

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Unstructured <Ustrd>	[0..*]	Text		202
		Structured <Strd>	[0..*]	±		202

2.1.25.2.1 Unstructured <Ustrd>

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form.

Datatype: [Max140Text](#) on page 308

2.1.25.2.2 Structured <Strd>

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

Structured <Strd> contains the following elements (see [StructuredRemittanceInformation16](#) on page 204 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ReferredDocumentInformation <RfrdDocInf>	[0..*]			206
		Type <Tp>	[0..1]			208
		CodeOrProprietary <CdOrPrtry>	[1..1]			208
	{Or	Code <Cd>	[1..1]	CodeSet		208
	Or}	Proprietary <Prtry>	[1..1]	Text		209
		Issuer <Issr>	[0..1]	Text		209
		Number <Nb>	[0..1]	Text		209
		RelatedDate <RltdDt>	[0..1]	Date		210
		LineDetails <LineDtls>	[0..*]			210
		Identification <Id>	[1..*]			211
		Type <Tp>	[0..1]			212
		CodeOrProprietary <CdOrPrtry>	[1..1]			212
	{Or	Code <Cd>	[1..1]	CodeSet		212
	Or}	Proprietary <Prtry>	[1..1]	Text		213
		Issuer <Issr>	[0..1]	Text		213
		Number <Nb>	[0..1]	Text		213
		RelatedDate <RltdDt>	[0..1]	Date		213
		Description <Desc>	[0..1]	Text		213
		Amount <Amt>	[0..1]			213
		DuePayableAmount <DuePyblAmt>	[0..1]	Amount		214
		DiscountAppliedAmount <DscntApldAmt>	[0..*]			214
		Type <Tp>	[0..1]			215
	{Or	Code <Cd>	[1..1]	CodeSet		215
	Or}	Proprietary <Prtry>	[1..1]	Text		215
		Amount <Amt>	[1..1]	Amount		215
		CreditNoteAmount <CdtNoteAmt>	[0..1]	Amount		215
		TaxAmount <TaxAmt>	[0..*]			215
		Type <Tp>	[0..1]			216
	{Or	Code <Cd>	[1..1]	CodeSet		216
	Or}	Proprietary <Prtry>	[1..1]	Text		216

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Amount		216
		AdjustmentAmountAndReason <AdjstmntAmtAndRsn>	[0..*]			216
		Amount <Amt>	[1..1]	Amount		217
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		217
		Reason <Rsn>	[0..1]	Text		217
		AdditionalInformation <AddtlInf>	[0..1]	Text		217
		RemittedAmount <RmtdAmt>	[0..1]	Amount		217
		ReferredDocumentAmount <RfrdDocAmt>	[0..1]	±		217
		CreditorReferenceInformation <CdtrRefInf>	[0..1]	±		218
		Invoicer <Invcr>	[0..1]	±		219
		Invoicee <Invcee>	[0..1]	±		219
		TaxRemittance <TaxRmt>	[0..1]	±		220
		GarnishmentRemittance <GrnshmtRmt>	[0..1]	±		220
		AdditionalRemittanceInformation <AddtlRmtInf>	[0..3]	Text		221

2.1.25.3 StructuredRemittanceInformation16

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ReferredDocumentInformation <RfrdDocInf>	[0..*]			206
		Type <Tp>	[0..1]			208
		CodeOrProprietary <CdOrPrtry>	[1..1]			208
	{Or	Code <Cd>	[1..1]	CodeSet		208
	Or}	Proprietary <Prtry>	[1..1]	Text		209
		Issuer <Issr>	[0..1]	Text		209
		Number <Nb>	[0..1]	Text		209
		RelatedDate <RltdDt>	[0..1]	Date		210
		LineDetails <LineDtls>	[0..*]			210
		Identification <Id>	[1..*]			211
		Type <Tp>	[0..1]			212
		CodeOrProprietary <CdOrPrtry>	[1..1]			212
	{Or	Code <Cd>	[1..1]	CodeSet		212
	Or}	Proprietary <Prtry>	[1..1]	Text		213
		Issuer <Issr>	[0..1]	Text		213
		Number <Nb>	[0..1]	Text		213
		RelatedDate <RltdDt>	[0..1]	Date		213
		Description <Desc>	[0..1]	Text		213
		Amount <Amt>	[0..1]			213
		DuePayableAmount <DuePyblAmt>	[0..1]	Amount		214
		DiscountAppliedAmount <DscntApldAmt>	[0..*]			214
		Type <Tp>	[0..1]			215
	{Or	Code <Cd>	[1..1]	CodeSet		215
	Or}	Proprietary <Prtry>	[1..1]	Text		215
		Amount <Amt>	[1..1]	Amount		215
		CreditNoteAmount <CdtNoteAmt>	[0..1]	Amount		215
		TaxAmount <TaxAmt>	[0..*]			215
		Type <Tp>	[0..1]			216
	{Or	Code <Cd>	[1..1]	CodeSet		216
	Or}	Proprietary <Prtry>	[1..1]	Text		216
		Amount <Amt>	[1..1]	Amount		216

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AdjustmentAmountAndReason <AdjstmntAmtAndRsn>	[0..*]			216
		Amount <Amt>	[1..1]	Amount		217
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		217
		Reason <Rsn>	[0..1]	Text		217
		AdditionalInformation <AddtlInf>	[0..1]	Text		217
		RemittedAmount <RmtdAmt>	[0..1]	Amount		217
		ReferredDocumentAmount <RfrdDocAmt>	[0..1]	±		217
		CreditorReferenceInformation <CdtrRefInf>	[0..1]	±		218
		Invoice <Invcr>	[0..1]	±		219
		Invoicee <Invcee>	[0..1]	±		219
		TaxRemittance <TaxRmt>	[0..1]	±		220
		GarnishmentRemittance <GrnshmtRmt>	[0..1]	±		220
		AdditionalRemittanceInformation <AddtlRmtInf>	[0..3]	Text		221

2.1.25.3.1 ReferredDocumentInformation <RfrdDocInf>

Presence: [0..*]

Definition: Provides the identification and the content of the referred document.

ReferredDocumentInformation <RfrdDocInf> contains the following **ReferredDocumentInformation7** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			208
		CodeOrProprietary <CdOrPrtry>	[1..1]			208
	{Or	Code <Cd>	[1..1]	CodeSet		208
	Or}	Proprietary <Prtry>	[1..1]	Text		209
		Issuer <Issr>	[0..1]	Text		209
		Number <Nb>	[0..1]	Text		209
		RelatedDate <RltdDt>	[0..1]	Date		210
		LineDetails <LineDtls>	[0..*]			210
		Identification <Id>	[1..*]			211
		Type <Tp>	[0..1]			212
		CodeOrProprietary <CdOrPrtry>	[1..1]			212
	{Or	Code <Cd>	[1..1]	CodeSet		212
	Or}	Proprietary <Prtry>	[1..1]	Text		213
		Issuer <Issr>	[0..1]	Text		213
		Number <Nb>	[0..1]	Text		213
		RelatedDate <RltdDt>	[0..1]	Date		213
		Description <Desc>	[0..1]	Text		213
		Amount <Amt>	[0..1]			213
		DuePayableAmount <DuePyblAmt>	[0..1]	Amount		214
		DiscountAppliedAmount <DscntApldAmt>	[0..*]			214
		Type <Tp>	[0..1]			215
	{Or	Code <Cd>	[1..1]	CodeSet		215
	Or}	Proprietary <Prtry>	[1..1]	Text		215
		Amount <Amt>	[1..1]	Amount		215
		CreditNoteAmount <CdtNoteAmt>	[0..1]	Amount		215
		TaxAmount <TaxAmt>	[0..*]			215
		Type <Tp>	[0..1]			216
	{Or	Code <Cd>	[1..1]	CodeSet		216
	Or}	Proprietary <Prtry>	[1..1]	Text		216
		Amount <Amt>	[1..1]	Amount		216

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AdjustmentAmountAndReason <AdjstmntAmtAndRsn>	[0..*]			216
		Amount <Amt>	[1..1]	Amount		217
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		217
		Reason <Rsn>	[0..1]	Text		217
		AdditionalInformation <AddtlInf>	[0..1]	Text		217
		RemittedAmount <RmtdAmt>	[0..1]	Amount		217

2.1.25.3.1.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of referred document.

Type <Tp> contains the following **ReferredDocumentType4** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CodeOrProprietary <CdOrPrtry>	[1..1]			208
	{Or	Code <Cd>	[1..1]	CodeSet		208
	Or}	Proprietary <Prtry>	[1..1]	Text		209
		Issuer <Issr>	[0..1]	Text		209

2.1.25.3.1.1.1 CodeOrProprietary <CdOrPrtry>

Presence: [1..1]

Definition: Provides the type details of the referred document.

CodeOrProprietary <CdOrPrtry> contains one of the following **ReferredDocumentType3Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		208
	Or}	Proprietary <Prtry>	[1..1]	Text		209

2.1.25.3.1.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Document type in a coded form.

Datatype: DocumentType6Code on page 261

CodeName	Name	Definition
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.

CodeName	Name	Definition
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
CINV	CommercialInvoice	Document is an invoice.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
DISP	DispatchAdvice	Document is a dispatch advice.
BOLD	BillOfLading	Document is a shipping notice.
VCHR	Voucher	Document is an electronic payment document.
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
PUOR	PurchaseOrder	Document is a purchase order.

2.1.25.3.1.1.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Proprietary identification of the type of the remittance document.

Datatype: [Max35Text on page 310](#)

2.1.25.3.1.1.1.2 Issuer <Issr>

Presence: [0..1]

Definition: Identification of the issuer of the reference document type.

Datatype: [Max35Text on page 310](#)

2.1.25.3.1.1.2 Number <Nb>

Presence: [0..1]

Definition: Unique and unambiguous identification of the referred document.

Datatype: Max35Text on page 310

2.1.25.3.1.3 RelatedDate <RltdDt>

Presence: [0..1]

Definition: Date associated with the referred document.

Datatype: ISODate on page 303

2.1.25.3.1.4 LineDetails <LineDtls>

Presence: [0..*]

Definition: Set of elements used to provide the content of the referred document line.

LineDetails <LineDtls> contains the following **DocumentLineInformation1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..*]			211
		Type <Tp>	[0..1]			212
		CodeOrProprietary <CdOrPrtry>	[1..1]			212
	{Or	Code <Cd>	[1..1]	CodeSet		212
	Or}	Proprietary <Prtry>	[1..1]	Text		213
		Issuer <Issr>	[0..1]	Text		213
		Number <Nb>	[0..1]	Text		213
		RelatedDate <RltdDt>	[0..1]	Date		213
		Description <Desc>	[0..1]	Text		213
		Amount <Amt>	[0..1]			213
		DuePayableAmount <DuePyblAmt>	[0..1]	Amount		214
		DiscountAppliedAmount <DscntApldAmt>	[0..*]			214
		Type <Tp>	[0..1]			215
	{Or	Code <Cd>	[1..1]	CodeSet		215
	Or}	Proprietary <Prtry>	[1..1]	Text		215
		Amount <Amt>	[1..1]	Amount		215
		CreditNoteAmount <CdtNoteAmt>	[0..1]	Amount		215
		TaxAmount <TaxAmt>	[0..*]			215
		Type <Tp>	[0..1]			216
	{Or	Code <Cd>	[1..1]	CodeSet		216
	Or}	Proprietary <Prtry>	[1..1]	Text		216
		Amount <Amt>	[1..1]	Amount		216
		AdjustmentAmountAndReason <AdjstmntAmtAndRsn>	[0..*]			216
		Amount <Amt>	[1..1]	Amount		217
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		217
		Reason <Rsn>	[0..1]	Text		217
		AdditionalInformation <AddtlInf>	[0..1]	Text		217
		RemittedAmount <RmtdAmt>	[0..1]	Amount		217

2.1.25.3.1.4.1 Identification <Id>

Presence: [1..*]

Definition: Provides identification of the document line.

Identification <Id> contains the following **DocumentLineIdentification1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			212
		CodeOrProprietary <CdOrPrtry>	[1..1]			212
	{Or	Code <Cd>	[1..1]	CodeSet		212
	Or}	Proprietary <Prtry>	[1..1]	Text		213
		Issuer <Issr>	[0..1]	Text		213
		Number <Nb>	[0..1]	Text		213
		RelatedDate <RltdDt>	[0..1]	Date		213

2.1.25.3.1.4.1.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of referred document line identification.

Type <Tp> contains the following **DocumentLineType1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CodeOrProprietary <CdOrPrtry>	[1..1]			212
	{Or	Code <Cd>	[1..1]	CodeSet		212
	Or}	Proprietary <Prtry>	[1..1]	Text		213
		Issuer <Issr>	[0..1]	Text		213

2.1.25.3.1.4.1.1.1 CodeOrProprietary <CdOrPrtry>

Presence: [1..1]

Definition: Provides the type details of the referred document line identification.

CodeOrProprietary <CdOrPrtry> contains one of the following **DocumentLineType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		212
	Or}	Proprietary <Prtry>	[1..1]	Text		213

2.1.25.3.1.4.1.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Line identification type in a coded form.

Datatype: ExternalDocumentLineType1Code on page 270

2.1.25.3.1.4.1.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Proprietary identification of the type of the remittance document.

Datatype: Max35Text on page 310

2.1.25.3.1.4.1.1.2 Issuer <Issr>

Presence: [0..1]

Definition: Identification of the issuer of the reference document line identificationtype.

Datatype: Max35Text on page 310

2.1.25.3.1.4.1.2 Number <Nb>

Presence: [0..1]

Definition: Identification of the type specified for the referred document line.

Datatype: Max35Text on page 310

2.1.25.3.1.4.1.3 RelatedDate <RltdDt>

Presence: [0..1]

Definition: Date associated with the referred document line.

Datatype: ISODate on page 303

2.1.25.3.1.4.2 Description <Desc>

Presence: [0..1]

Definition: Description associated with the document line.

Datatype: Max2048Text on page 309

2.1.25.3.1.4.3 Amount <Amt>

Presence: [0..1]

Definition: Provides details on the amounts of the document line.

Amount <Amt> contains the following **RemittanceAmount3** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DuePayableAmount <DuePyblAmt>	[0..1]	Amount		214
		DiscountAppliedAmount <DscntApldAmt>	[0..*]			214
		Type <Tp>	[0..1]			215
	{Or	Code <Cd>	[1..1]	CodeSet		215
	Or}	Proprietary <Prtry>	[1..1]	Text		215
		Amount <Amt>	[1..1]	Amount		215
		CreditNoteAmount <CdtNoteAmt>	[0..1]	Amount		215
		TaxAmount <TaxAmt>	[0..*]			215
		Type <Tp>	[0..1]			216
	{Or	Code <Cd>	[1..1]	CodeSet		216
	Or}	Proprietary <Prtry>	[1..1]	Text		216
		Amount <Amt>	[1..1]	Amount		216
		AdjustmentAmountAndReason <AdjstmntAmtAndRsn>	[0..*]			216
		Amount <Amt>	[1..1]	Amount		217
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		217
		Reason <Rsn>	[0..1]	Text		217
		AdditionalInformation <AddtlInf>	[0..1]	Text		217
		RemittedAmount <RmtdAmt>	[0..1]	Amount		217

2.1.25.3.1.4.3.1 DuePayableAmount <DuePyblAmt>

Presence: [0..1]

Definition: Amount specified is the exact amount due and payable to the creditor.

Datatype: ActiveOrHistoricCurrencyAndAmount on page 242

2.1.25.3.1.4.3.2 DiscountAppliedAmount <DscntApldAmt>

Presence: [0..*]

Definition: Amount of discount to be applied to the amount due and payable to the creditor.

DiscountAppliedAmount <DscntApldAmt> contains the following **DiscountAmountAndType1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			215
	{Or	Code <Cd>	[1..1]	CodeSet		215
	Or}	Proprietary <Prtry>	[1..1]	Text		215
		Amount <Amt>	[1..1]	Amount		215

2.1.25.3.1.4.3.2.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of the amount.

Type <Tp> contains one of the following **DiscountAmountType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		215
	Or}	Proprietary <Prtry>	[1..1]	Text		215

2.1.25.3.1.4.3.2.1.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: [ExternalDiscountAmountType1Code](#) on page 269

2.1.25.3.1.4.3.2.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: [Max35Text](#) on page 310

2.1.25.3.1.4.3.2.2 Amount <Amt>

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 242

2.1.25.3.1.4.3.3 CreditNoteAmount <CdtNoteAmt>

Presence: [0..1]

Definition: Amount of a credit note.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 242

2.1.25.3.1.4.3.4 TaxAmount <TaxAmt>

Presence: [0..*]

Definition: Amount of the tax.

TaxAmount <TaxAmt> contains the following **TaxAmountAndType1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			216
	{Or	Code <Cd>	[1..1]	CodeSet		216
	Or}	Proprietary <Prtry>	[1..1]	Text		216
		Amount <Amt>	[1..1]	Amount		216

2.1.25.3.1.4.3.4.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of the amount.

Type <Tp> contains one of the following **TaxAmountType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		216
	Or}	Proprietary <Prtry>	[1..1]	Text		216

2.1.25.3.1.4.3.4.1.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: [ExternalTaxAmountType1Code](#) on page 278

2.1.25.3.1.4.3.4.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: [Max35Text](#) on page 310

2.1.25.3.1.4.3.4.2 Amount <Amt>

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 242

2.1.25.3.1.4.3.5 AdjustmentAmountAndReason <AdjstmntAmtAndRsn>

Presence: [0..*]

Definition: Specifies detailed information on the amount and reason of the adjustment.

AdjustmentAmountAndReason <AdjstmntAmtAndRsn> contains the following **DocumentAdjustment1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Amount		217
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		217
		Reason <Rsn>	[0..1]	Text		217
		AdditionalInformation <AddtlInf>	[0..1]	Text		217

2.1.25.3.1.4.3.5.1 Amount <Amt>

Presence: [1..1]

Definition: Amount of money of the document adjustment.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 242](#)

2.1.25.3.1.4.3.5.2 CreditDebitIndicator <CdtDbtInd>

Presence: [0..1]

Definition: Specifies whether the adjustment must be subtracted or added to the total amount.

Datatype: [CreditDebitCode on page 260](#)

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

2.1.25.3.1.4.3.5.3 Reason <Rsn>

Presence: [0..1]

Definition: Specifies the reason for the adjustment.

Datatype: [Max4Text on page 310](#)

2.1.25.3.1.4.3.5.4 AdditionalInformation <AddtlInf>

Presence: [0..1]

Definition: Provides further details on the document adjustment.

Datatype: [Max140Text on page 308](#)

2.1.25.3.1.4.3.6 RemittedAmount <RmtdAmt>

Presence: [0..1]

Definition: Amount of money remitted.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 242](#)

2.1.25.3.2 ReferredDocumentAmount <RfrdDocAmt>

Presence: [0..1]

Definition: Provides details on the amounts of the referred document.

ReferredDocumentAmount <RfrdDocAmt> contains the following elements (see [RemittanceAmount2](#) on page 161 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DuePayableAmount <DuePyblAmt>	[0..1]	Amount		162
		DiscountAppliedAmount <DscntApldAmt>	[0..*]			162
		Type <Tp>	[0..1]			163
	{Or	Code <Cd>	[1..1]	CodeSet		163
	Or}	Proprietary <Prtry>	[1..1]	Text		163
		Amount <Amt>	[1..1]	Amount		163
		CreditNoteAmount <CdtNoteAmt>	[0..1]	Amount		163
		TaxAmount <TaxAmt>	[0..*]			163
		Type <Tp>	[0..1]			164
	{Or	Code <Cd>	[1..1]	CodeSet		164
	Or}	Proprietary <Prtry>	[1..1]	Text		164
		Amount <Amt>	[1..1]	Amount		164
		AdjustmentAmountAndReason <AdjstmntAmtAndRsn>	[0..*]			164
		Amount <Amt>	[1..1]	Amount		165
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		165
		Reason <Rsn>	[0..1]	Text		165
		AdditionalInformation <AddtlInf>	[0..1]	Text		165
		RemittedAmount <RmtdAmt>	[0..1]	Amount		165

2.1.25.3.3 CreditorReferenceInformation <CdtrRefInf>

Presence: [0..1]

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

CreditorReferenceInformation <CdtrRefInf> contains the following elements (see [CreditorReferenceInformation2](#) on page 146 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			147
		CodeOrProprietary <CdOrPrtry>	[1..1]			147
	{Or	Code <Cd>	[1..1]	CodeSet		147
	Or}	Proprietary <Prtry>	[1..1]	Text		148
		Issuer <Issr>	[0..1]	Text		148
		Reference <Ref>	[0..1]	Text		148

2.1.25.3.4 Invoicer <Invcr>

Presence: [0..1]

Definition: Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor.

Invoicer <Invcr> contains the following elements (see [PartyIdentification135](#) on page 184 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		185
		PostalAddress <PstlAdr>	[0..1]	±		185
		Identification <Id>	[0..1]	±		186
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		186
		ContactDetails <CtctDtls>	[0..1]	±		187

2.1.25.3.5 Invoicee <Invcee>

Presence: [0..1]

Definition: Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor.

Invoicee <Invcee> contains the following elements (see [PartyIdentification135](#) on page 184 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		185
		PostalAddress <PstlAdr>	[0..1]	±		185
		Identification <Id>	[0..1]	±		186
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		186
		ContactDetails <CtctDtls>	[0..1]	±		187

2.1.25.3.6 TaxRemittance <TaxRmt>

Presence: [0..1]

Definition: Provides remittance information about a payment made for tax-related purposes.

TaxRemittance <TaxRmt> contains the following elements (see [TaxInformation7](#) on page 229 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Creditor <Cdtr>	[0..1]	±		229
		Debtor <Dbtr>	[0..1]	±		229
		UltimateDebtor <UltmtDbtr>	[0..1]	±		230
		AdministrationZone <AdmstnZone>	[0..1]	Text		230
		ReferenceNumber <RefNb>	[0..1]	Text		230
		Method <Mtd>	[0..1]	Text		230
		TotalTaxableBaseAmount <TtlTaxblBaseAmt>	[0..1]	Amount		231
		TotalTaxAmount <TtlTaxAmt>	[0..1]	Amount		231
		Date <Dt>	[0..1]	Date		231
		SequenceNumber <SeqNb>	[0..1]	Quantity		231
		Record <Rcrd>	[0..*]	±		231

2.1.25.3.7 GarnishmentRemittance <GrnshmtRmt>

Presence: [0..1]

Definition: Provides remittance information about a payment for garnishment-related purposes.

GarnishmentRemittance <GrnshmtRmt> contains the following elements (see [Garnishment3](#) on page 199 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[1..1]			199
		CodeOrProprietary <CdOrPrtry>	[1..1]			200
	{Or	Code <Cd>	[1..1]	CodeSet		200
	Or}	Proprietary <Prtry>	[1..1]	Text		200
		Issuer <Issr>	[0..1]	Text		200
		Garnishee <Grnshee>	[0..1]	±		200
		GarnishmentAdministrator <GrnshmtAdmstr>	[0..1]	±		201
		ReferenceNumber <RefNb>	[0..1]	Text		201
		Date <Dt>	[0..1]	Date		201
		RemittedAmount <RmtdAmt>	[0..1]	Amount		201
		FamilyMedicalInsuranceIndicator <FmlyMdclInsrncInd>	[0..1]	Indicator		202
		EmployeeTerminationIndicator <MplyeeTermtnInd>	[0..1]	Indicator		202

2.1.25.3.8 AdditionalRemittanceInformation <AddtlRmtInf>

Presence: [0..3]

Definition: Additional information, in free text form, to complement the structured remittance information.

Datatype: [Max140Text](#) on page 308

2.1.25.4 RemittanceLocation7

Definition: Provides information on the remittance advice.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		RemittanceIdentification <RmtId>	[0..1]	Text		221
		RemittanceLocationDetails <RmtLctnDtls>	[0..*]	±		221

2.1.25.4.1 RemittanceIdentification <RmtId>

Presence: [0..1]

Definition: Unique identification, as assigned by the initiating party, to unambiguously identify the remittance information sent separately from the payment instruction, such as a remittance advice.

Datatype: [Max35Text](#) on page 310

2.1.25.4.2 RemittanceLocationDetails <RmtLctnDtls>

Presence: [0..*]

Definition: Set of elements used to provide information on the location and/or delivery of the remittance information.

RemittanceLocationDetails <RmtLctnDtls> contains the following elements (see [RemittanceLocationData1](#) on page 222 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Method <Mtd>	[1..1]	CodeSet		222
		ElectronicAddress <ElctrncAdr>	[0..1]	Text		223
		PostalAddress <PstlAdr>	[0..1]			223
		Name <Nm>	[1..1]	Text		223
		Address <Adr>	[1..1]	±		223

2.1.25.5 RemittanceLocationData1

Definition: Provides additional details on the remittance advice.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Method <Mtd>	[1..1]	CodeSet		222
		ElectronicAddress <ElctrncAdr>	[0..1]	Text		223
		PostalAddress <PstlAdr>	[0..1]			223
		Name <Nm>	[1..1]	Text		223
		Address <Adr>	[1..1]	±		223

2.1.25.5.1 Method <Mtd>

Presence: [1..1]

Definition: Method used to deliver the remittance advice information.

Datatype: [RemittanceLocationMethod2Code](#) on page 290

CodeName	Name	Definition
FAXI	Fax	Remittance advice information must be faxed.
EDIC	ElectronicDataInterchange	Remittance advice information must be sent through Electronic Data Interchange (EDI).
URID	UniformResourceIdentifier	Remittance advice information needs to be sent to a Uniform Resource Identifier (URI). URI is a compact string of characters that uniquely identify an abstract or physical resource. URI's are the super-set of identifiers, such as URLs, email addresses, ftp sites, etc, and as such, provide the syntax for all of the identification schemes.
EMAL	EMail	Remittance advice information must be sent through e-mail.

CodeName	Name	Definition
POST	Post	Remittance advice information must be sent through postal services.
SMSM	SMS	Remittance advice information must be sent through by phone as a short message service (SMS).

2.1.25.5.2 ElectronicAddress <ElctrncAdr>

Presence: [0..1]

Definition: Electronic address to which an agent is to send the remittance information.

Datatype: [Max2048Text on page 309](#)

2.1.25.5.3 PostalAddress <PstlAdr>

Presence: [0..1]

Definition: Postal address to which an agent is to send the remittance information.

PostalAddress <PstlAdr> contains the following **NameAndAddress16** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[1..1]	Text		223
		Address <Adr>	[1..1]	±		223

2.1.25.5.3.1 Name <Nm>

Presence: [1..1]

Definition: Name by which a party is known and is usually used to identify that party.

Datatype: [Max140Text on page 308](#)

2.1.25.5.3.2 Address <Adr>

Presence: [1..1]

Definition: Postal address of a party.

Address <Adr> contains the following elements (see [PostalAddress24](#) on page 194 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AddressType <AdrTp>	[0..1]			194
	{Or	Code <Cd>	[1..1]	CodeSet		195
	Or}	Proprietary <Prtry>	[1..1]	±		195
		Department <Dept>	[0..1]	Text		195
		SubDepartment <SubDept>	[0..1]	Text		195
		StreetName <StrtNm>	[0..1]	Text		196
		BuildingNumber <BldgNb>	[0..1]	Text		196
		BuildingName <BldgNm>	[0..1]	Text		196
		Floor <Flr>	[0..1]	Text		196
		PostBox <PstBx>	[0..1]	Text		196
		Room <Room>	[0..1]	Text		196
		PostCode <PstCd>	[0..1]	Text		196
		TownName <TwnNm>	[0..1]	Text		196
		TownLocationName <TwnLctnNm>	[0..1]	Text		197
		DistrictName <DstrctNm>	[0..1]	Text		197
		CountrySubDivision <CtrySubDvsn>	[0..1]	Text		197
		Country <Ctry>	[0..1]	CodeSet		197
		AddressLine <AdrLine>	[0..7]	Text		197

2.1.26 Securities Quantity

2.1.26.1 OriginalAndCurrentQuantities1

Definition: Original and current value of an asset-back instrument.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FaceAmount <FaceAmt>	[1..1]	Amount		224
		AmortisedValue <AmtsdVal>	[1..1]	Amount		225

2.1.26.1.1 FaceAmount <FaceAmt>

Presence: [1..1]

Definition: Quantity expressed as an amount representing the face amount, that is, the principal of a debt instrument.

Datatype: [ImpliedCurrencyAndAmount](#) on page 243

2.1.26.1.2 AmortisedValue <AmtsdVal>

Presence: [1..1]

Definition: Quantity expressed as an amount representing the current amortised face amount of a bond, for example, a periodic reduction/increase of a bond's principal amount.

Datatype: ImpliedCurrencyAndAmount on page 243

2.1.27 Status

2.1.27.1 PaymentReturnReason5

Definition: Provides further details on the reason of the return of the transaction.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		OriginalBankTransactionCode <OrgnlBkTxCd>	[0..1]	±		225
		Originator <Orgtr>	[0..1]	±		226
		Reason <Rsn>	[0..1]			226
	{Or	Code <Cd>	[1..1]	CodeSet		226
	Or}	Proprietary <Prtry>	[1..1]	Text		226
		AdditionalInformation <AddtlInf>	[0..*]	Text		226

Constraints

- **ReturnReasonRule**

If Reason/Code is equal to NARR, then AdditionalInformation must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00077
- *Error Text:* Invalid message content for additional return reason.

2.1.27.1.1 OriginalBankTransactionCode <OrgnlBkTxCd>

Presence: [0..1]

Definition: Bank transaction code included in the original entry for the transaction.

OriginalBankTransactionCode <OrgnlBkTxCd> contains the following elements (see BankTransactionCodeStructure4 on page 57 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Domain <Domn>	[0..1]	±		57
		Proprietary <Prtry>	[0..1]			58
		Code <Cd>	[1..1]	Text		58
		Issuer <Issr>	[0..1]	Text		58

2.1.27.1.2 Originator <Orgtr>*Presence:* [0..1]*Definition:* Party that issues the return.**Originator <Orgtr>** contains the following elements (see [PartyIdentification135](#) on page 184 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		185
		PostalAddress <PstlAdr>	[0..1]	±		185
		Identification <Id>	[0..1]	±		186
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		186
		ContactDetails <CtctDtls>	[0..1]	±		187

2.1.27.1.3 Reason <Rsn>*Presence:* [0..1]*Definition:* Specifies the reason for the return.**Reason <Rsn>** contains one of the following **ReturnReason5Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		226
	Or}	Proprietary <Prtry>	[1..1]	Text		226

2.1.27.1.3.1 Code <Cd>*Presence:* [1..1]*Definition:* Reason for the return, as published in an external reason code list.*Datatype:* [ExternalReturnReason1Code](#) on page 277**2.1.27.1.3.2 Proprietary <Prtry>***Presence:* [1..1]*Definition:* Reason for the return, in a proprietary form.*Datatype:* [Max35Text](#) on page 310**2.1.27.1.4 AdditionalInformation <AddtlInf>***Presence:* [0..*]*Definition:* Further details on the return reason.*Datatype:* [Max105Text](#) on page 308**2.1.27.2 EntryStatus1Choice***Definition:* Specifies the status of an entry on the books of the account servicer.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		227
	Or}	Proprietary <Prtry>	[1..1]	Text		227

2.1.27.2.1 Code <Cd>

Presence: [1..1]

Definition: Entry status, in a coded form.

Datatype: [ExternalEntryStatus1Code on page 270](#)

2.1.27.2.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Entry status, in a proprietary form.

Datatype: [Max35Text on page 310](#)

2.1.28 System Identification

2.1.28.1 ClearingSystemIdentification2Choice

Definition: Choice of a clearing system identifier.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		227
	Or}	Proprietary <Prtry>	[1..1]	Text		227

2.1.28.1.1 Code <Cd>

Presence: [1..1]

Definition: Identification of a clearing system, in a coded form as published in an external list.

Datatype: [ExternalClearingSystemIdentification1Code on page 268](#)

2.1.28.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Identification code for a clearing system, that has not yet been identified in the list of clearing systems.

Datatype: [Max35Text on page 310](#)

2.1.29 Tax

2.1.29.1 TaxParty2

Definition: Details about the entity involved in the tax paid or to be paid.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TaxIdentification <TaxId>	[0..1]	Text		228
		RegistrationIdentification <RegnId>	[0..1]	Text		228
		TaxType <TaxTp>	[0..1]	Text		228
		Authorisation <Authstn>	[0..1]			228
		Title <Titl>	[0..1]	Text		228
		Name <Nm>	[0..1]	Text		228

2.1.29.1.1 TaxIdentification <TaxId>

Presence: [0..1]

Definition: Tax identification number of the debtor.

Datatype: [Max35Text on page 310](#)

2.1.29.1.2 RegistrationIdentification <RegnId>

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: [Max35Text on page 310](#)

2.1.29.1.3 TaxType <TaxTp>

Presence: [0..1]

Definition: Type of tax payer.

Datatype: [Max35Text on page 310](#)

2.1.29.1.4 Authorisation <Authstn>

Presence: [0..1]

Definition: Details of the authorised tax paying party.

Authorisation <Authstn> contains the following **TaxAuthorisation1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Title <Titl>	[0..1]	Text		228
		Name <Nm>	[0..1]	Text		228

2.1.29.1.4.1 Title <Titl>

Presence: [0..1]

Definition: Title or position of debtor or the debtor's authorised representative.

Datatype: [Max35Text on page 310](#)

2.1.29.1.4.2 Name <Nm>

Presence: [0..1]

Definition: Name of the debtor or the debtor's authorised representative.

Datatype: [Max140Text](#) on page 308

2.1.29.2 TaxInformation7

Definition: Details about tax paid, or to be paid, to the government in accordance with the law, including pre-defined parameters such as thresholds and type of account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Creditor <Cdtr>	[0..1]	±		229
		Debtor <Dbtr>	[0..1]	±		229
		UltimateDebtor <UltmtDbtr>	[0..1]	±		230
		AdministrationZone <AdmstnZone>	[0..1]	Text		230
		ReferenceNumber <RefNb>	[0..1]	Text		230
		Method <Mtd>	[0..1]	Text		230
		TotalTaxableBaseAmount <TtlTaxblBaseAmt>	[0..1]	Amount		231
		TotalTaxAmount <TtlTaxAmt>	[0..1]	Amount		231
		Date <Dt>	[0..1]	Date		231
		SequenceNumber <SeqNb>	[0..1]	Quantity		231
		Record <Rcrd>	[0..*]	±		231

2.1.29.2.1 Creditor <Cdtr>

Presence: [0..1]

Definition: Party on the credit side of the transaction to which the tax applies.

Creditor <Cdtr> contains the following elements (see [TaxParty1](#) on page 232 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TaxIdentification <TaxId>	[0..1]	Text		232
		RegistrationIdentification <RegnId>	[0..1]	Text		232
		TaxType <TaxTp>	[0..1]	Text		232

2.1.29.2.2 Debtor <Dbtr>

Presence: [0..1]

Definition: Identifies the party on the debit side of the transaction to which the tax applies.

Debtor <Dbtr> contains the following elements (see [TaxParty2](#) on page 227 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TaxIdentification <TaxId>	[0..1]	Text		228
		RegistrationIdentification <RegnId>	[0..1]	Text		228
		TaxType <TaxTp>	[0..1]	Text		228
		Authorisation <Authstn>	[0..1]			228
		Title <Titl>	[0..1]	Text		228
		Name <Nm>	[0..1]	Text		228

2.1.29.2.3 UltimateDebtor <UltmtDbtr>

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor, in this case, to the taxing authority.

UltimateDebtor <UltmtDbtr> contains the following elements (see [TaxParty2](#) on page 227 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TaxIdentification <TaxId>	[0..1]	Text		228
		RegistrationIdentification <RegnId>	[0..1]	Text		228
		TaxType <TaxTp>	[0..1]	Text		228
		Authorisation <Authstn>	[0..1]			228
		Title <Titl>	[0..1]	Text		228
		Name <Nm>	[0..1]	Text		228

2.1.29.2.4 AdministrationZone <AdmstnZone>

Presence: [0..1]

Definition: Territorial part of a country to which the tax payment is related.

Datatype: [Max35Text](#) on page 310

2.1.29.2.5 ReferenceNumber <RefNb>

Presence: [0..1]

Definition: Tax reference information that is specific to a taxing agency.

Datatype: [Max140Text](#) on page 308

2.1.29.2.6 Method <Mtd>

Presence: [0..1]

Definition: Method used to indicate the underlying business or how the tax is paid.

Datatype: [Max35Text](#) on page 310

2.1.29.2.7 TotalTaxableBaseAmount <TtlTaxblBaseAmt>

Presence: [0..1]

Definition: Total amount of money on which the tax is based.

Datatype: ActiveOrHistoricCurrencyAndAmount on page 242

2.1.29.2.8 TotalTaxAmount <TtlTaxAmt>

Presence: [0..1]

Definition: Total amount of money as result of the calculation of the tax.

Datatype: ActiveOrHistoricCurrencyAndAmount on page 242

2.1.29.2.9 Date <Dt>

Presence: [0..1]

Definition: Date by which tax is due.

Datatype: ISODate on page 303

2.1.29.2.10 SequenceNumber <SeqNb>

Presence: [0..1]

Definition: Sequential number of the tax report.

Datatype: Number on page 307

2.1.29.2.11 Record <Rcrd>

Presence: [0..*]

Definition: Record of tax details.

Record <Rcrd> contains the following elements (see [TaxRecord2](#) on page 236 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]	Text		237
		Category <Ctgy>	[0..1]	Text		237
		CategoryDetails <CtgyDtls>	[0..1]	Text		237
		DebtorStatus <DbtrSts>	[0..1]	Text		237
		CertificateIdentification <CertId>	[0..1]	Text		237
		FormsCode <FrmsCd>	[0..1]	Text		237
		Period <Prd>	[0..1]	±		237
		TaxAmount <TaxAmt>	[0..1]			238
		Rate <Rate>	[0..1]	Rate		238
		TaxableBaseAmount <TaxblBaseAmt>	[0..1]	Amount		238
		TotalAmount <TtlAmt>	[0..1]	Amount		238
		Details <Dtls>	[0..*]	±		238
		AdditionalInformation <AddtlInf>	[0..1]	Text		238

2.1.29.3 TaxParty1

Definition: Details about the entity involved in the tax paid or to be paid.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TaxIdentification <TaxId>	[0..1]	Text		232
		RegistrationIdentification <RegnId>	[0..1]	Text		232
		TaxType <TaxTp>	[0..1]	Text		232

2.1.29.3.1 TaxIdentification <TaxId>

Presence: [0..1]

Definition: Tax identification number of the creditor.

Datatype: [Max35Text](#) on page 310

2.1.29.3.2 RegistrationIdentification <RegnId>

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: [Max35Text](#) on page 310

2.1.29.3.3 TaxType <TaxTp>

Presence: [0..1]

Definition: Type of tax payer.

Datatype: [Max35Text on page 310](#)

2.1.29.4 TaxRecordDetails2

Definition: Provides information on the individual tax amount(s) per period of the tax record.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Period <Prd>	[0..1]	±		233
		Amount <Amt>	[1..1]	Amount		233

2.1.29.4.1 Period <Prd>

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

Period <Prd> contains the following elements (see [TaxPeriod2 on page 239](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Year <Yr>	[0..1]	Date		239
		Type <Tp>	[0..1]	CodeSet		239
		FromToDate <FrToDt>	[0..1]	±		240

2.1.29.4.2 Amount <Amt>

Presence: [1..1]

Definition: Underlying tax amount related to the specified period.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 242](#)

2.1.29.5 TaxInformation8

Definition: Details about tax paid, or to be paid, to the government in accordance with the law, including pre-defined parameters such as thresholds and type of account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Creditor <Cdtr>	[0..1]	±		234
		Debtor <Dbtr>	[0..1]	±		234
		AdministrationZone <AdmstnZone>	[0..1]	Text		235
		ReferenceNumber <RefNb>	[0..1]	Text		235
		Method <Mtd>	[0..1]	Text		235
		TotalTaxableBaseAmount <TtlTaxblBaseAmt>	[0..1]	Amount		235
		TotalTaxAmount <TtlTaxAmt>	[0..1]	Amount		235
		Date <Dt>	[0..1]	Date		235
		SequenceNumber <SeqNb>	[0..1]	Quantity		235
		Record <Rcrd>	[0..*]	±		235

2.1.29.5.1 Creditor <Cdtr>

Presence: [0..1]

Definition: Party on the credit side of the transaction to which the tax applies.

Creditor <Cdtr> contains the following elements (see [TaxParty1](#) on page 232 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TaxIdentification <TaxId>	[0..1]	Text		232
		RegistrationIdentification <RegnId>	[0..1]	Text		232
		TaxType <TaxTp>	[0..1]	Text		232

2.1.29.5.2 Debtor <Dbtr>

Presence: [0..1]

Definition: Party on the debit side of the transaction to which the tax applies.

Debtor <Dbtr> contains the following elements (see [TaxParty2](#) on page 227 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TaxIdentification <TaxId>	[0..1]	Text		228
		RegistrationIdentification <RegnId>	[0..1]	Text		228
		TaxType <TaxTp>	[0..1]	Text		228
		Authorisation <Authstn>	[0..1]			228
		Title <Titl>	[0..1]	Text		228
		Name <Nm>	[0..1]	Text		228

2.1.29.5.3 AdministrationZone <AdmstnZone>

Presence: [0..1]

Definition: Territorial part of a country to which the tax payment is related.

Datatype: Max35Text on page 310

2.1.29.5.4 ReferenceNumber <RefNb>

Presence: [0..1]

Definition: Tax reference information that is specific to a taxing agency.

Datatype: Max140Text on page 308

2.1.29.5.5 Method <Mtd>

Presence: [0..1]

Definition: Method used to indicate the underlying business or how the tax is paid.

Datatype: Max35Text on page 310

2.1.29.5.6 TotalTaxableBaseAmount <TtlTaxblBaseAmt>

Presence: [0..1]

Definition: Total amount of money on which the tax is based.

Datatype: ActiveOrHistoricCurrencyAndAmount on page 242

2.1.29.5.7 TotalTaxAmount <TtlTaxAmt>

Presence: [0..1]

Definition: Total amount of money as result of the calculation of the tax.

Datatype: ActiveOrHistoricCurrencyAndAmount on page 242

2.1.29.5.8 Date <Dt>

Presence: [0..1]

Definition: Date by which tax is due.

Datatype: ISODate on page 303

2.1.29.5.9 SequenceNumber <SeqNb>

Presence: [0..1]

Definition: Sequential number of the tax report.

Datatype: Number on page 307

2.1.29.5.10 Record <Rcrd>

Presence: [0..*]

Definition: Record of tax details.

Record <Rcrd> contains the following elements (see [TaxRecord2](#) on page 236 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]	Text		237
		Category <Ctgy>	[0..1]	Text		237
		CategoryDetails <CtgyDtls>	[0..1]	Text		237
		DebtorStatus <DbtrSts>	[0..1]	Text		237
		CertificateIdentification <CertId>	[0..1]	Text		237
		FormsCode <FrmsCd>	[0..1]	Text		237
		Period <Prd>	[0..1]	±		237
		TaxAmount <TaxAmt>	[0..1]			238
		Rate <Rate>	[0..1]	Rate		238
		TaxableBaseAmount <TaxblBaseAmt>	[0..1]	Amount		238
		TotalAmount <TtlAmt>	[0..1]	Amount		238
		Details <Dtls>	[0..*]	±		238
		AdditionalInformation <AddtlInf>	[0..1]	Text		238

2.1.29.6 TaxRecord2

Definition: Set of elements used to define the tax record.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]	Text		237
		Category <Ctgy>	[0..1]	Text		237
		CategoryDetails <CtgyDtls>	[0..1]	Text		237
		DebtorStatus <DbtrSts>	[0..1]	Text		237
		CertificateIdentification <CertId>	[0..1]	Text		237
		FormsCode <FrmsCd>	[0..1]	Text		237
		Period <Prd>	[0..1]	±		237
		TaxAmount <TaxAmt>	[0..1]			238
		Rate <Rate>	[0..1]	Rate		238
		TaxableBaseAmount <TaxblBaseAmt>	[0..1]	Amount		238
		TotalAmount <TtlAmt>	[0..1]	Amount		238
		Details <Dtls>	[0..*]	±		238
		AdditionalInformation <AddtlInf>	[0..1]	Text		238

2.1.29.6.1 Type <Tp>*Presence:* [0..1]*Definition:* High level code to identify the type of tax details.*Datatype:* [Max35Text on page 310](#)**2.1.29.6.2 Category <Ctgy>***Presence:* [0..1]*Definition:* Specifies the tax code as published by the tax authority.*Datatype:* [Max35Text on page 310](#)**2.1.29.6.3 CategoryDetails <CtgyDtls>***Presence:* [0..1]*Definition:* Provides further details of the category tax code.*Datatype:* [Max35Text on page 310](#)**2.1.29.6.4 DebtorStatus <DbtrSts>***Presence:* [0..1]*Definition:* Code provided by local authority to identify the status of the party that has drawn up the settlement document.*Datatype:* [Max35Text on page 310](#)**2.1.29.6.5 CertificateIdentification <CertId>***Presence:* [0..1]*Definition:* Identification number of the tax report as assigned by the taxing authority.*Datatype:* [Max35Text on page 310](#)**2.1.29.6.6 FormsCode <FrmsCd>***Presence:* [0..1]*Definition:* Identifies, in a coded form, on which template the tax report is to be provided.*Datatype:* [Max35Text on page 310](#)**2.1.29.6.7 Period <Prd>***Presence:* [0..1]*Definition:* Set of elements used to provide details on the period of time related to the tax payment.**Period <Prd>** contains the following elements (see [TaxPeriod2 on page 239](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Year <Yr>	[0..1]	Date		239
		Type <Tp>	[0..1]	CodeSet		239
		FromDate <FrToDt>	[0..1]	±		240

2.1.29.6.8 TaxAmount <TaxAmt>

Presence: [0..1]

Definition: Set of elements used to provide information on the amount of the tax record.

TaxAmount <TaxAmt> contains the following **TaxAmount2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Rate <Rate>	[0..1]	Rate		238
		TaxableBaseAmount <TaxblBaseAmt>	[0..1]	Amount		238
		TotalAmount <TtlAmt>	[0..1]	Amount		238
		Details <Dtls>	[0..*]	±		238

2.1.29.6.8.1 Rate <Rate>

Presence: [0..1]

Definition: Rate used to calculate the tax.

Datatype: [PercentageRate](#) on page 307

2.1.29.6.8.2 TaxableBaseAmount <TaxblBaseAmt>

Presence: [0..1]

Definition: Amount of money on which the tax is based.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 242

2.1.29.6.8.3 TotalAmount <TtlAmt>

Presence: [0..1]

Definition: Total amount that is the result of the calculation of the tax for the record.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 242

2.1.29.6.8.4 Details <Dtls>

Presence: [0..*]

Definition: Set of elements used to provide details on the tax period and amount.

Details <Dtls> contains the following elements (see [TaxRecordDetails2](#) on page 233 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Period <Prd>	[0..1]	±		233
		Amount <Amt>	[1..1]	Amount		233

2.1.29.6.9 AdditionalInformation <AddtlInf>

Presence: [0..1]

Definition: Further details of the tax record.

Datatype: [Max140Text](#) on page 308

2.1.29.7 TaxPeriod2

Definition: Period of time details related to the tax payment.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Year <Yr>	[0..1]	Date		239
		Type <Tp>	[0..1]	CodeSet		239
		FromDate <FrToDt>	[0..1]	±		240

2.1.29.7.1 Year <Yr>

Presence: [0..1]

Definition: Year related to the tax payment.

Datatype: [ISODate on page 303](#)

2.1.29.7.2 Type <Tp>

Presence: [0..1]

Definition: Identification of the period related to the tax payment.

Datatype: [TaxRecordPeriod1Code on page 291](#)

CodeName	Name	Definition
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.

CodeName	Name	Definition
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.

2.1.29.7.3 FromToDate <FrToDt>

Presence: [0..1]

Definition: Range of time between a start date and an end date for which the tax report is provided.

FromToDate <FrToDt> contains the following elements (see [DatePeriod2](#) on page 144 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FromDate <FrDt>	[1..1]	Date		144
		ToDate <ToDt>	[1..1]	Date		144

2.2 Message Datatypes

2.2.1 Amount

2.2.1.1 ActiveCurrencyAndAmount

Definition: A number of monetary units specified in an active currency where the unit of currency is explicit and compliant with ISO 4217.

Type: Amount

This data type contains the following XML attribute:

Name	Attribute XML Name	Datatype
Currency	Ccy	ActiveCurrencyCode on page 243

Format

minInclusive	0
totalDigits	18
fractionDigits	5

Constraints

- **ActiveCurrency**

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00005
- *Error Text:* Invalid currency code

- **CurrencyAmount**

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

2.2.1.2 ActiveOrHistoricCurrencyAnd13DecimalAmount

Definition: A number of monetary units specified in an active or a historic currency where the unit of currency is explicit and compliant with ISO 4217. The number of fractional digits (or minor unit of currency) is not checked as per ISO 4217: It must be lesser than or equal to 13.

Note: The decimal separator is a dot.

Type: Amount

This data type contains the following XML attribute:

Name	Attribute XML Name	Datatype
Currency	Ccy	ActiveOrHistoricCurrencyCode on page 243

Format

minInclusive	0
totalDigits	18
fractionDigits	13

Constraints

- **ActiveOrHistoricCurrency**

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3)

contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

2.2.1.3 ActiveOrHistoricCurrencyAndAmount

Definition: A number of monetary units specified in an active or a historic currency where the unit of currency is explicit and compliant with ISO 4217.

Type: Amount

This data type contains the following XML attribute:

Name	Attribute XML Name	Datatype
Currency	Ccy	ActiveOrHistoricCurrencyCode on page 243

Format

minInclusive	0
totalDigits	18
fractionDigits	5

Constraints

- **ActiveOrHistoricCurrency**

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

- **CurrencyAmount**

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

2.2.1.4 ImpliedCurrencyAndAmount

Definition: Number of monetary units specified in a currency where the unit of currency is implied by the context and compliant with ISO 4217. The decimal separator is a dot.

Note: a zero amount is considered a positive amount.

Type: Amount

Format

minInclusive	0
totalDigits	18
fractionDigits	5

2.2.2 CodeSet

2.2.2.1 ActiveCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern	[A-Z]{3,3}
---------	------------

Constraints

- **ActiveCurrency**

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00005
- *Error Text:* Invalid currency code

Restricts

ParentCurrencyCode on page 282

2.2.2.2 ActiveOrHistoricCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme, as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern [A-Z]{3,3}

Constraints

- **ActiveOrHistoricCurrency**

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

Restricts

ParentCurrencyCode on page 282

2.2.2.3 AddressType2Code

Definition: Specifies the type of address.

Type: CodeSet

CodeName	Name	Definition
ADDR	Postal	Address is the complete postal address.
PBOX	POBox	Address is a postal office (PO) box.
HOME	Residential	Address is the home address.
BIZZ	Business	Address is the business address.
MLTO	MailTo	Address is the address to which mail is sent.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.

Restricts

AddressTypeCode on page 244

2.2.2.4 AddressTypeCode

Definition: Specifies the type of address.

Type: CodeSet

CodeName	Name	Definition
HOME	Residential	Address is the home address.
BIZZ	Business	Address is the business address.
ADDR	Postal	Address is the complete postal address.

CodeName	Name	Definition
PBOX	POBox	Address is a postal office (PO) box.
MLTO	MailTo	Address is the address to which mail is sent.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.

Is restricted by

[AddressType2Code on page 244](#)

2.2.2.5 AmountDirectionCode

Definition: Specifies if an operation is an increase or a decrease or the result of a reversal operation.

Type: CodeSet

CodeName	Name	Definition
DBIT	Debit	Operation is a decrease.
CRDT	Credit	Operation is an increase.
RVDB	ReversalDebit	Credit entry used to reverse a previously booked debit entry.
RVCD	ReversalCredit	Debit entry used to reverse a previously booked credit entry.

Is restricted by

[CreditDebitCode on page 260](#)

2.2.2.6 AttendanceContext1Code

Definition: Human attendance at the POI location during the transaction.

Type: CodeSet

CodeName	Name	Definition
ATTD	Attended	Attended payment, with an attendant.
SATT	SemiAttended	Semi-attended, including self checkout. An attendant supervises several payment, and could be called to help the cardholder.
UATT	Unattended	Unattended payment, no attendant present.

Restricts

[AttendanceContextCode on page 245](#)

2.2.2.7 AttendanceContextCode

Definition: Human attendance at the POI location during the transaction.

Type: CodeSet

CodeName	Name	Definition
ATTD	Attended	Attended payment, with an attendant.
SATT	SemiAttended	Semi-attended, including self checkout. An attendant supervises several payment, and could be called to help the cardholder.
UATT	Unattended	Unattended payment, no attendant present.
ATTL	AttendantDelivery	Delivery by an attendant.
CUST	CustomerDelivery	Delivery by the customer.
CARR	CarrierDelivery	Delivery by a carrier.
FULL	FullServe	Full service for fuel distribution.
SELF	SelfServe	Self service for fuel distribution.

Is restricted by

AttendanceContext1Code on page 245

2.2.2.8 AuthenticationEntity1Code

Definition: Entity or object in charge of verifying the cardholder authenticity.

Type: CodeSet

CodeName	Name	Definition
ICCD	ICC	Application in the chip card (Integrated Circuit Card), for instance an offline PIN verification.
AGNT	AuthorisedAgent	Authorisation agent of the issuer.
MERC	Merchant	Merchant (for example signature verification by the attendant).

Restricts

AuthenticationEntityCode on page 246

2.2.2.9 AuthenticationEntityCode

Definition: Entity or object in charge of verifying the cardholder authenticity.

Type: CodeSet

CodeName	Name	Definition
ICCD	ICC	Application in the chip card (Integrated Circuit Card), for instance an offline PIN verification.
AGNT	AuthorisedAgent	Authorisation agent of the issuer.
MERC	Merchant	Merchant (for example signature verification by the attendant).
ACQR	Acquirer	Acquirer of the transaction.

CodeName	Name	Definition
ISSR	Issuer	Card issuer.
TRML	Terminal	Secure application in the terminal.

Is restricted by

[AuthenticationEntity1Code on page 246](#)

2.2.2.10 AuthenticationMethod1Code

Definition: Method used to authenticate a cardholder.

Type: CodeSet

CodeName	Name	Definition
UKNW	UnknownMethod	Authentication method is performed unknown.
BYPS	Bypass	Authentication bypassed by the merchant.
NPIN	OnLinePIN	On-line PIN authentication (Personal Identification Number).
FPIN	OfflinePIN	Off-line PIN authentication (Personal Identification Number).
CPSG	SignatureCapture	Electronic signature capture (handwritten signature).
PPSG	PaperSignature	Handwritten paper signature.
MANU	ManualVerification	Manual verification, for example passport or drivers license.
MERC	MerchantAuthentication	Merchant-related authentication.
SCRT	SecureCertificate	Electronic commerce transaction secured with the X.509 certificate of a customer.
SNCT	SecureNoCertificate	Secure electronic transaction without cardholder certificate.
SCNL	SecuredChannel	Channel-encrypted transaction.

Restricts

[AuthenticationMethodCode on page 247](#)

2.2.2.11 AuthenticationMethodCode

Definition: Method used to authenticate a cardholder.

Type: CodeSet

CodeName	Name	Definition
UKNW	UnknownMethod	Authentication method is performed unknown.
BYPS	Bypass	Authentication bypassed by the merchant.

CodeName	Name	Definition
NPIN	OnLinePIN	On-line PIN authentication (Personal Identification Number).
FPIN	OfflinePIN	Off-line PIN authentication (Personal Identification Number).
CPSG	SignatureCapture	Electronic signature capture (handwritten signature).
PPSG	PaperSignature	Handwritten paper signature.
MANU	ManualVerification	Manual verification, for example passport or drivers license.
MERC	MerchantAuthentication	Merchant-related authentication.
SCRT	SecureCertificate	Electronic commerce transaction secured with the X.509 certificate of a customer.
SNCT	SecureNoCertificate	Secure electronic transaction without cardholder certificate.
SCNL	SecuredChannel	Channel-encrypted transaction.
PSWD	Password	Authentication by a password.
ADDB	BillingAddressVerification	Cardholder billing address verification.
BIOM	Biometry	Biometric authentication of the cardholder.
CDHI	CardholderIdentificationData	Cardholder data provided for verification, for instance social security number, driver license number, passport number.
CRYP	CryptogramVerification	Verification of a cryptogram generated by a chip card or another device, for instance ARQC (Authorisation Request Cryptogram).
CSCV	CSCVerification	Verification of Card Security Code.
PSVE	PassiveAuthentication	Authentication based on statistical cardholder behaviour.
CSEC	SecureElectronicCommerce	Authentication performed during a secure electronic commerce transaction.
ADDS	ShippingAddressVerification	Cardholder shipping address verification.
TOKN	TokenAuthentication	Cryptogram generated by the token requestor or a customer device to validate the authorised use of a token.
TOKP	PaymentToken	Verification or authentication related to the use of a payment token, for instance the validation of the authorised use of a token.
TOKA	AuthenticationToken	A token is used to verify an already performed authentication.
MOBL	Mobile	Customer mobile device.
OTHR	Other	Other customer authentication.
ADVF	AddressDigits	Digits of the address.

CodeName	Name	Definition
ARNB	AlienRegistrationNumber	Number assigned by a government agency to identify foreign nationals.
ARQC	ARQCVerification	Verification of a cryptogram generated by a chip card, for instance an ARQC (Authorisation Request Cryptogram).
BTHD	BirthDate	Date of birth of a person.
CHDN	CardholderName	Name of cardholder
COFB	CityOfBirth	City of birth to authenticate a person.
CUID	CustomerIdentification	Customer number used as a mechanism of authentication.
DRVI	DriverIdentification	Identification of a driver in a fleet of vehicles.
DRLN	DriverLicenseNumber	Number assigned by a driving license authority to a person driving a car.
EMAL	Email	Electronic mail address
EMIN	EmployeeIdentificationNumber	Number assigned to an employee by an employer.
EMRN	EmployerIdentificationNumber	Number assigned to an employer by a registration authority.
IDCN	IdentityCardNumber	Number assigned by a national authority to an identity card.
OTPW	OneTimePassword	Verification of a one-time password provided by the issuer.
OCHI	OtherCardholderIdentification	Other cardholder data provided for identification.
OTHC	OtherCryptogram	Verification of a cryptogram generated by a non-card form factor.
PASN	PassportNumber	Number assigned by a passport authority to a passport.
PCDV	PostalCode	Verification based on digits of the postal code.
SHAF	ShippingAddressFrom	Shipping address from verification.
SHAT	ShippingAddressTo	Shipping address to verification
CHSA	CardholderAddress	Verification whether the address corresponds to the cardholder's one.
NVSC	NonVisibleCSC	Non visible Card Security Code.
OTHN	OtherNational	Other type of verification defined at national level.
OTHP	OtherPrivate	Other type of verification defined at private level
PLOB	PlaceOfBirth	Place of birth of a person.
SSNB	SocialSecurityNumber	Number assigned by a social security agency.

CodeName	Name	Definition
TXIN	TaxIdentificationNumber	Number assigned by a tax authority to an entity.
APKI	AccountDigitalSignature	Account-based digital signature authentication.
ARPC	ARPCVerification	Response Card Cryptogram (ARPC) verification.
ATCC	ATC	Application Transaction Counter
FBIG	OffLineBiographics	Biographics authentication in an offline mode.
FBIO	OffLineBiometrics	Biometrics authentication in an offline mode
OLDA	OffLineDataAuthentication	Authentication of data in an offline mode
OLDS	OffLineDigitisedSignatureAnalysis	Analysis of signature transmitted offline
OFPE	OffLinePINEncrypted	PIN generated offline and transmitted encrypted
FCPN	OffLinePINInClear	PIN generated offline and transmitted in clear
NBIG	OnLineBiographics	Biographics authentication in an online mode.
PHOM	PhoneHome	Customer home phone number.
PWOR	PhoneWork	Customer work phone number
PKIS	PKISignature	PKI (Public Key Infrastructure) based digital signature
QWAC	QualifiedCertificate	QualifiedCertificate
THDS	ThreeDS	Authentication performed during a secure electronic commerce transaction.
CHSN	CardholderCertificateSerialNumber	Serial number of the cardholder's certificate.
ACSN	AcceptorCertificateSerialNumber	Serial number of the acceptor's certificate.
NTID	NationalIdentifier	Nationally assigned identifier.

Is restricted by

AuthenticationMethod1Code on page 247

2.2.2.12 CardDataReading1Code

Definition: Type of reading of the card data.

Type: CodeSet

CodeName	Name	Definition
TAGC	Tag	Tag reading capabilities (RFID, etc.).

CodeName	Name	Definition
PHYS	Physical	Keyboard entry or OCR reading of embossing or printed data, either at time of transaction or after the event.
BRCD	BarCode	Bar code.
MGST	MagneticStripe	Magnetic stripe.
CICC	ICC	ICC (Integrated Circuit Card) with contact containing software applications conform to ISO 7816.
DFLE	AccountData	Account data on file.
CTLS	ProximityReader	Contactless proximity reader.
ECTL	EMVProximityReader	Contactless proximity reader, with application conform to the standard EMV (standard initiated by Europay, Mastercard and Visa).

Restricts

CardDataReadingCode on page 251

2.2.2.13 CardDataReadingCode

Definition: Type of reading of the card data.

Type: CodeSet

CodeName	Name	Definition
TAGC	Tag	Tag reading capabilities (RFID, etc.).
PHYS	Physical	Keyboard entry or OCR reading of embossing or printed data, either at time of transaction or after the event.
BRCD	BarCode	Bar code.
MGST	MagneticStripe	Magnetic stripe.
CICC	ICC	ICC (Integrated Circuit Card) with contact containing software applications conform to ISO 7816.
DFLE	AccountData	Account data on file.
CTLS	ProximityReader	Contactless proximity reader.
ECTL	EMVProximityReader	Contactless proximity reader, with application conform to the standard EMV (standard initiated by Europay, Mastercard and Visa).
CDFL	CardOnFile	Card information are stored on a file.
UNKW	Unknown	Unknown card reading capability.
SICC	SynchronousIntegratedCircuitCard	Synchronous ICC - (Integrated Circuit Card) with contact.
ICCY	ICCContact	ICC contact capability
ICPY	ICCPximity	ICC contactless proximity

CodeName	Name	Definition
MICR	MagneticInkCharacterRecognition	Recognition of magnetic ink characters
MLEY	ManualEntry	Manual, no terminal used.
MSIP	MSIPProximity	Magstripe image contactless proximity
OCRR	OpticalCharacterRecognition	OCR either at time of transaction or after the event.
OPTC	OpticalCode	Optical coded reading capabilities (e.g. barcode, QR code, etc.)
OTHN	OtherNational	Other national capability type assigned at national level.
OTHP	OtherPrivate	Other card reading capability assigned on a private basis.
RFID	RFIDTag	Radio Frequency Identification tag capabilities.
UNSP	Unspecified	Unspecified capability.
KEEN	KeyEntered	Key entered.
QRCD	QRCode	Quick response code.
CAMR	Camera	Card details captured via camera.
MBNK	MobileBankingApplication	Card details were obtained via a mobile banking application.
TOKN	Token	Card details were obtained via a token.
MGSP	MagneticStripePartial	Magnetic stripe is read, only partial data is available.
ICCP	ICCPContactPartial	Integrated circuit card read; only partial data is available.
NFCF	TypeF	NFC Type-F frequency.
CDFS	CredentialOnServer	Card information are stored on a server.
DCPY	ICCPProximityPrivate	Domestic ICC Contactless
ICFM	ICCFallbackManual	ICC contact with fallback to manual mode
ICMG	ICCFallbackMagstripe	ICC contact with fallback to magstripe mode
OTHR	Other	Other card data reading mode.

Is restricted by

CardDataReading1Code on page 250

2.2.2.14 CardholderVerificationCapability1Code

Definition: Cardholder verification capabilities of the POI (Personal Identification Number) performing the transaction.

Type: CodeSet

CodeName	Name	Definition
MNSG	ManualSignature	Manual signature verification.
NPIN	OnLinePIN	Online PIN (Personal Identification Number).
FCPN	OfflinePINClear	Offline PIN in clear (Personal Identification Number).
FEPN	OfflinePINEncrypted	Offline PIN encrypted (Personal Identification Number).
FDSG	OfflineDigitalSignature	Offline digital signature analysis.
FBIO	OfflineBiometrics	Offline biometrics.
MNVR	ManualVerification	Other manual verification, for example passport or drivers license.
FBIG	OfflineBiographics	Offline biographics.
APKI	AccountDigitalSignature	Account based digital signature.
PKIS	PKISignature	PKI (Public Key Infrastructure) based digital signature.
CHDT	CardholderData	Cardholder authentication data.
SCEC	SecureElectronicCommerce	Three domain secure (three domain secure authentication of the cardholder).

Restricts

CardholderVerificationCapabilityCode on page 253

2.2.2.15 CardholderVerificationCapabilityCode

Definition: Cardholder verification capabilities of the POI (Personal Identification Number) performing the transaction.

Type: CodeSet

CodeName	Name	Definition
MNSG	ManualSignature	Manual signature verification.
NPIN	OnLinePIN	Online PIN (Personal Identification Number).
FCPN	OfflinePINClear	Offline PIN in clear (Personal Identification Number).
FEPN	OfflinePINEncrypted	Offline PIN encrypted (Personal Identification Number).
FDSG	OfflineDigitalSignature	Offline digital signature analysis.
FBIO	OfflineBiometrics	Offline biometrics.
MNVR	ManualVerification	Other manual verification, for example passport or drivers license.
FBIG	OfflineBiographics	Offline biographics.
APKI	AccountDigitalSignature	Account based digital signature.

CodeName	Name	Definition
PKIS	PKISignature	PKI (Public Key Infrastructure) based digital signature.
CHDT	CardholderData	Cardholder authentication data.
SCEC	SecureElectronicCommerce	Three domain secure (three domain secure authentication of the cardholder).
UNKW	Unknown	Unknown cardholder verification capability.
PCOD	PersonalCode	Personal code of the customer for banking services.
NOVF	NoCapabilities	No cardholder verification capability.
NBIO	OnLineBiometrics	Online biometrics.
OTHR	Other	Other cardholder verification capabilities.
OTHN	OtherNational	Other type of cardholder verification defined at national level
OTHP	OtherPrivate	Other type of cardholder verification defined in a private manner.
SIGN	Signature	Handwritten signature verification
UNSP	Unspecified	Cardholder verification capability unspecified.
VORN	VoiceRecognition	Recognition by voice.
NOPN	NoPINEntry	Device has no pin entry capability.
NOOP	NoOnLinePINEntry	Device has no online pin entry capability.

Is restricted by

CardholderVerificationCapability1Code on page 252

2.2.2.16 CardPaymentServiceType2Code

Definition: Service provided by the card payment transaction, in addition to the main service.

Type: CodeSet

CodeName	Name	Definition
AGGR	Aggregation	Aggregation of low payments.
DCCV	DCC	Dynamic currency conversion (DCC).
GRTT	Gratuity	Card payment with gratuity.
INSP	Instalment	Instalment payment.
LOYT	Loyalty	Loyalty services.
NRES	NoShow	No show after reservation.
PUCO	PurchaseCorporate	Purchase and corporate data.
RECP	RecurringPayment	Recurring payment.
SOAF	SolicitedAvailableFunds	Solicited available funds.

CodeName	Name	Definition
UNAF	UnsolicitedAvailableFunds	Unsolicited available funds.
VCAU	VoiceAuthorisation	Voice authorisation.

Restricts

CardPaymentServiceTypeCode on page 255

2.2.2.17 CardPaymentServiceTypeCode

Definition: Service provided by a card payment transaction.

Type: CodeSet

CodeName	Name	Definition
CAFT	CardsFundTransfer	Transfer of funds to and/or from a card account.
ORCR	OriginalCredit	Original credit.
CRDP	CardPayment	Card payment.
CSHB	CashBack	Card payment with cash-back.
CSHW	CashAdvance	Cash advance or withdrawals on a POI (Point Of Interaction), or at a bank counter.
CSHD	CashDeposit	Cash deposit.
DEFR	DeferredPayment	Deferred payment.
RESA	Reservation	Reservation (pre-authorisation).
LOAD	Loading	Loading or reloading non-financial account.
RFND	Refund	Refund transaction.
QUCH	QuasiCash	Quasi-cash.
BALC	Balance	Balance enquiry.
CACT	CardActivation	Card activation.
CAVR	CardVerification	Card verification.
PINC	PINChange	PIN (Personal Identification Number) change.
VALC	ValidityCheck	Card validity check.
AGGR	Aggregation	Aggregation of low payments.
DCCV	DCC	Dynamic currency conversion (DCC).
GR TT	Gratuity	Card payment with gratuity.
INSP	Instalment	Instalment payment.
LOYT	Loyalty	Loyalty services.
NRES	NoShow	No show after reservation.
PUCO	PurchaseCorporate	Purchase and corporate data.

CodeName	Name	Definition
RECP	RecurringPayment	Recurring payment.
SOAF	SolicitedAvailableFunds	Solicited available funds.
UNAF	UnsolicitedAvailableFunds	Unsolicited available funds.
VCAU	VoiceAuthorisation	Voice authorisation.
IRES	InitialReservation	Initial reservation.
URES	UpdateReservation	Update reservation.
PRES	PaymentReservation	Payment after reservation.
ARES	AdditionalPayment	Additional payment after reservation.
FREC	FirstRecurring	Initial recurring payment.
RREC	FollowingRecurring	Repeat recurring payment.
TP2B	PersonToBusiness	Card payment transaction transfer from person to business.
TP2P	PersonToPerson	Card payment transaction transfer from person to person.
INSA	AcceptorInstalment	Instalment payment transaction performed by the acceptor or the acquirer.
INSI	IssuerInstalment	Instalment payment transaction performed by the card issuer.
UNLD	Unloading	Unloading non-financial account.
CAFH	CardsFundTransferPush	Transfer of funds to a card or an account.
CAFL	CardsFundTransferPull	Transfer of funds from a card or an account.
CHWD	CashWithdrawal	Withdrawal of cash on an ATM.
PINU	PINUnblock	Unblock the cardholder PIN.
CSWD	ChosenWithdrawal	Amount and notes values are chosen by the customer.
AUWS	PreAuthorisedWithdrawal	Withdrawal transaction was pre-authorised by another channel (amount could be absent).
PFWD	ProfileWithdrawal	Amount and Notes Values are pre-defined by the customer profile.
SDWD	StandardWithdrawal	Customer pressed a button associated with a withdrawal of unique amount and notes mix.
TFBL	TransferCardBillPayment	Transfer for payment of bills.
TFCS	TransferFromCash	Transfer from cash deposit.
TFCH	TransferFromCheque	Transfer from cheque deposit.
TFDB	TransferFundsDisbursementGeneral	Transfer for general disbursement.
TFGD	TransferGovernmentDisbursement	Transfer for government disbursement.

CodeName	Name	Definition
TFMD	TransferMerchantDisbursement	Transfer for merchant disbursement.
TFPD	TransferPayrollPensionDisbursement	Transfer for payroll pension disbursement.
NRFD	NonRefundable	Payment of goods or services which are not refundable, for instance low cost airline tickets.
INST	Instant	Instant transaction.
CADJ	CreditAdjustment	Credit adjustment to a previous transaction.
DADJ	DebitAdjustment	Debit adjustment to a previous transaction.
CRTC	CreateCertificate	Creation of an X.509 certificate with the public key and the information of the owner of the asymmetric key provided by the requestor.
CRTR	RenewCerificate	Renewal of an X.509 certificate, protected by the certificate to renew.
CRTK	RevokeCertificate	Revocation of an active X.509 certificate.
WLSA	AddWhiteList	Add a POI in the white list of the terminal manager.
WLSR	RemoveWhiteList	Remove a POI from the white list of the terminal manager.
CIDD	CardInitiatingDirectDebit	Direct Debit initiated by Card.
GOPT	GuaranteeOfPayment	Acceptor claims for guarantee of payment.
PPMS	POIPaymentMethodSelection	Used to inform the POI that it could select the payment instrument type to use.
DFCL	DeferredClearing	DeferredClearing identifies transactions, like ones related to health care system, that allows a delay in clearing which ensure the payer to be refunded by a system, for example an insurance, before its bank account is debited.

Is restricted by

[CardPaymentServiceType2Code on page 254](#)

2.2.2.18 ChargeBearerType1Code

Definition: Specifies which party(ies) will pay charges due for processing of the instruction.

Type: CodeSet

CodeName	Name	Definition
DEBT	BorneByDebtor	All transaction charges are to be borne by the debtor.
CRED	BorneByCreditor	All transaction charges are to be borne by the creditor.

CodeName	Name	Definition
SHAR	Shared	In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor.
SLEV	FollowingServiceLevel	Charges are to be applied following the rules agreed in the service level and/or scheme.

Restricts

ChargeBearerTypeCode on page 258

2.2.2.19 ChargeBearerTypeCode

Definition: Specifies which party(ies) will pay charges due for processing of the instruction.

Type: CodeSet

CodeName	Name	Definition
DEBT	BorneByDebtor	All transaction charges are to be borne by the debtor.
CRED	BorneByCreditor	All transaction charges are to be borne by the creditor.
SHAR	Shared	In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor.
SLEV	FollowingServiceLevel	Charges are to be applied following the rules agreed in the service level and/or scheme.

Is restricted by

ChargeBearerType1Code on page 257

2.2.2.20 CopyDuplicate1Code

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

CodeName	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message

CodeName	Name	Definition
		is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Restricts

CopyDuplicateCode on page 259

2.2.2.21 CopyDuplicateCode

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

CodeName	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Is restricted by

CopyDuplicate1Code on page 258

2.2.2.22 CountryCode

Definition: Code to identify a country, a dependency, or another area of particular geopolitical interest, on the basis of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Type: CodeSet

Format

pattern [A-Z]{2,2}

Constraints

- Country**

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

2.2.2.23 CreditDebitCode

Definition: Specifies if an operation is an increase or a decrease.

Type: CodeSet

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

Restricts

AmountDirectionCode on page 245

2.2.2.24 CSCManagement1Code

Definition: CSC (Card Security Code) management associated with the transaction.

Type: CodeSet

CodeName	Name	Definition
PRST	CSCPresent	Card security code present.
BYPS	CSCByPass	Card security code by-passed or not provided by the merchant.
UNRD	CSCUnread	Card security code unreadable.
NCSC	NoCSC	No card security code imprint.

Restricts

CSCManagementCode on page 260

2.2.2.25 CSCManagementCode

Definition: CSC (Card Security Code) management associated with the transaction.

Type: CodeSet

CodeName	Name	Definition
PRST	CSCPresent	Card security code present.
BYPS	CSCByPass	Card security code by-passed or not provided by the merchant.
UNRD	CSCUnread	Card security code unreadable.
NCSC	NoCSC	No card security code imprint.

Is restricted by

[CSCManagement1Code](#) on page 260

2.2.2.26 DocumentType3Code

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

CodeName	Name	Definition
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, for example, in a cover scenario.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
DISP	DispatchAdvice	Document is a dispatch advice.
PUOR	PurchaseOrder	Document is a purchase order.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.

Restricts

[DocumentTypeCode](#) on page 262

2.2.2.27 DocumentType6Code

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

CodeName	Name	Definition
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
CINV	CommercialInvoice	Document is an invoice.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.

CodeName	Name	Definition
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
DISP	DispatchAdvice	Document is a dispatch advice.
BOLD	BillOfLading	Document is a shipping notice.
VCHR	Voucher	Document is an electronic payment document.
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
PUOR	PurchaseOrder	Document is a purchase order.

Restricts

DocumentTypeCode on page 262

2.2.2.28 DocumentTypeCode

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

CodeName	Name	Definition
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
CINV	CommercialInvoice	Document is an invoice.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.

CodeName	Name	Definition
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, for example, in a cover scenario.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
DISP	DispatchAdvice	Document is a dispatch advice.
PUOR	PurchaseOrder	Document is a purchase order.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.
BOLD	BillOfLading	Document is a shipping notice.
VCHR	Voucher	Document is an electronic payment document.
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
HRCP	CashierReceipt	When the Sale system print the Cashier copy of the Payment receipt.
CRCP	CustomerReceipt	When the Sale System requires the POI system to print the Customer receipt.
JNRL	Journal	When the POI or the Sale System wants to store a message on the journal printer or electronic journal of the Sale Terminal (it is sometimes a Sale Logging/Journal Printer).
SRCP	SaleReceipt	When the Sale System requires the POI system to print the Sale receipt.

Is restricted by

[DocumentType3Code](#) on page 261, [DocumentType6Code](#) on page 261

2.2.2.29 ExternalAccountIdentification1Code

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalAccountIdentificationCode on page 264](#)

2.2.2.30 ExternalAccountIdentificationCode

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalAccountIdentification1Code on page 263](#)

2.2.2.31 ExternalBankTransactionDomain1Code

Definition: Specifies the bank transaction code domain, as published in an external bank transaction code domain code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalBankTransactionDomainCode on page 264](#)

2.2.2.32 ExternalBankTransactionDomainCode

Definition: Specifies the external domain code of the bank transaction code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalBankTransactionDomain1Code on page 264](#)

2.2.2.33 ExternalBankTransactionFamily1Code

Definition: Specifies the bank transaction code family, as published in an external bank transaction code family code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalBankTransactionFamilyCode on page 265](#)

2.2.2.34 ExternalBankTransactionFamilyCode

Definition: Specifies the external family code of the bank transaction code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately, and is a sub-list of the bank transaction domain list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalBankTransactionFamily1Code on page 265](#)

2.2.2.35 ExternalBankTransactionSubFamily1Code

Definition: Specifies the bank transaction code sub-family, as published in an external bank transaction code sub-family code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalBankTransactionSubFamilyCode on page 266](#)

2.2.2.36 ExternalBankTransactionSubFamilyCode

Definition: Specifies the external sub-family code of the bank transaction code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately, and is a sub-list of the bank transaction family code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalBankTransactionSubFamily1Code on page 266](#)

2.2.2.37 ExternalCardTransactionCategory1Code

Definition: Specifies the category of card transaction in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalCardTransactionCategoryCode on page 267](#)

2.2.2.38 ExternalCardTransactionCategoryCode

Definition: Specifies the category of card transaction in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalCardTransactionCategory1Code on page 266](#)

2.2.2.39 ExternalCashAccountType1Code

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalCashAccountTypeCode on page 267](#)

2.2.2.40 ExternalCashAccountTypeCode

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

ExternalCashAccountType1Code on page 267

2.2.2.41 ExternalChargeType1Code

Definition: Specifies the nature, or use, of the charges in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

ExternalChargeTypeCode on page 268

2.2.2.42 ExternalChargeTypeCode

Definition: Specifies the nature, or use, of the charges in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code set published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

ExternalChargeType1Code on page 268

2.2.2.43 ExternalClearingSystemIdentification1Code

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	5

Restricts

[ExternalClearingSystemIdentificationCode on page 269](#)

2.2.2.44 ExternalClearingSystemIdentificationCode

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	5

Is restricted by

[ExternalClearingSystemIdentification1Code on page 268](#)

2.2.2.45 ExternalDiscountAmountType1Code

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalDiscountAmountTypeCode on page 269](#)

2.2.2.46 ExternalDiscountAmountTypeCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalDiscountAmountType1Code on page 269](#)

2.2.2.47 ExternalDocumentLineType1Code

Definition: Specifies the document line type as published in an external document type code list.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalDocumentLineTypeCode on page 270](#)

2.2.2.48 ExternalDocumentLineTypeCode

Definition: Specifies the document line type as published in an external document type code list.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalDocumentLineType1Code on page 270](#)

2.2.2.49 ExternalEntryStatus1Code

Definition: Specifies the status of an entry on the books of the account servicer, as published in an external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalEntryStatusCode on page 271](#)

2.2.2.50 ExternalEntryStatusCode

Definition: Specifies the status of an entry on the books of the account servicer, as published in an external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalEntryStatus1Code on page 270](#)

2.2.2.51 ExternalFinancialInstitutionIdentification1Code

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalFinancialInstitutionIdentificationCode on page 271](#)

2.2.2.52 ExternalFinancialInstitutionIdentificationCode

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalFinancialInstitutionIdentification1Code on page 271](#)

2.2.2.53 ExternalFinancialInstrumentIdentificationType1Code

Definition: Specifies the external financial instrument identification type scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalFinancialInstrumentIdentificationTypeCode on page 272](#)

2.2.2.54 ExternalFinancialInstrumentIdentificationTypeCode

Definition: Specifies the external financial instrument identification type scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalFinancialInstrumentIdentificationType1Code on page 272](#)

2.2.2.55 ExternalGarnishmentType1Code

Definition: Specifies the garnishment type as published in an external document type code list.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalGarnishmentTypeCode on page 273](#)

2.2.2.56 ExternalGarnishmentTypeCode

Definition: Specifies the garnishment type as published in an external document type code list.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

ExternalGarnishmentType1Code on page 272

2.2.2.57 ExternalLocalInstrument1Code

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	35

Restricts

ExternalLocalInstrumentCode on page 273

2.2.2.58 ExternalLocalInstrumentCode

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	35

Is restricted by

ExternalLocalInstrument1Code on page 273

2.2.2.59 ExternalOrganisationIdentification1Code

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalOrganisationIdentificationCode on page 274](#)

2.2.2.60 ExternalOrganisationIdentificationCode

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalOrganisationIdentification1Code on page 274](#)

2.2.2.61 ExternalPersonIdentification1Code

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalPersonIdentificationCode](#) on page 275

2.2.2.62 ExternalPersonIdentificationCode

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalPersonIdentification1Code](#) on page 274

2.2.2.63 ExternalProxyAccountType1Code

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalProxyAccountTypeCode](#) on page 275

2.2.2.64 ExternalProxyAccountTypeCode

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalProxyAccountType1Code on page 275](#)

2.2.2.65 ExternalPurpose1Code

Definition: Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalPurposeCode on page 276](#)

2.2.2.66 ExternalPurposeCode

Definition: Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalPurpose1Code on page 276](#)

2.2.2.67 ExternalReportingSource1Code

Definition: Specifies the reporting source, as published in an external reporting source code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalReportingSourceCode](#) on page 277

2.2.2.68 ExternalReportingSourceCode

Definition: Specifies the reporting source, as published in an external reporting source code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalReportingSource1Code](#) on page 276

2.2.2.69 ExternalRePresentmentReason1Code

Definition: Specifies the external representment reason code in the format of character string with a maximum length of 4 characters. The list of valid codes is an external code list published separately.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalRePresentmentReasonCode](#) on page 277

2.2.2.70 ExternalRePresentmentReasonCode

Definition: Specifies the external representment reason code in the format of character string with a maximum length of 4 characters. The list of valid codes is an external code list published separately.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalRePresentmentReason1Code](#) on page 277

2.2.2.71 ExternalReturnReason1Code

Definition: Specifies the return reason, as published in an external return reason code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

ExternalReturnReasonCode on page 278

2.2.2.72 ExternalReturnReasonCode

Definition: Specifies the return reason, as published in an external return reason code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

ExternalReturnReason1Code on page 277

2.2.2.73 ExternalTaxAmountType1Code

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

ExternalTaxAmountTypeCode on page 278

2.2.2.74 ExternalTaxAmountTypeCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalTaxAmountType1Code on page 278](#)

2.2.2.75 ExternalTechnicalInputChannel1Code

Definition: Specifies the technical input channel, as published in an external technical input channel code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalTechnicalInputChannelCode on page 279](#)

2.2.2.76 ExternalTechnicalInputChannelCode

Definition: Specifies the technical input channel, as published in an external technical input channel code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalTechnicalInputChannel1Code on page 279](#)

2.2.2.77 InterestCode

Definition: Indicates which type of interest is applied to a balance left on an account.

Type: CodeSet

CodeName	Name	Definition
INDY	IntraDay	During or within a business day.
OVNR	OverNight	Period of time between the end of a business day and the start of the next business day (usually the day after).

Is restricted by

[InterestType1Code on page 280](#)

2.2.2.78 InterestType1Code

Definition: Indicates which type of interest is applied to a balance left on an account.

Type: CodeSet

CodeName	Name	Definition
INDY	IntraDay	During or within a business day.
OVNR	OverNight	Period of time between the end of a business day and the start of the next business day (usually the day after).

Restricts

[InterestCode on page 279](#)

2.2.2.79 ISO2ALanguageCode

Definition: Identification of the language name according to the ISO 639-1 codes. The type is validated by the list of values coded with two alphabetic characters, defined in the standard.

Type: CodeSet

Format

pattern [a-z]{2,2}

2.2.2.80 NamePrefix2Code

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

CodeName	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).

Restricts

[NamePrefixCode on page 281](#)

2.2.2.81 NamePrefixCode

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

CodeName	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MIST	Mister	Title of the person is Mister or Mr.
MISS	Miss	Title of the person is Miss.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).

Is restricted by

[NamePrefix2Code on page 280](#)

2.2.2.82 OnLineCapability1Code

Definition: On-line and off-line capabilities of the POI (Point Of Interaction).

Type: CodeSet

CodeName	Name	Definition
OFLN	OffLine	Off-line only capable.
ONLN	OnLine	On-line only capable.
SMON	SemiOffLine	Off-line capable with possible on-line requests to the acquirer.

Restricts

[OnLineCapabilityCode on page 281](#)

2.2.2.83 OnLineCapabilityCode

Definition: On-line and off-line capabilities of the POI (Point Of Interaction).

Type: CodeSet

CodeName	Name	Definition
OFLN	OffLine	Off-line only capable.
ONLN	OnLine	On-line only capable.
SMON	SemiOffLine	Off-line capable with possible on-line requests to the acquirer.
BOTH	BothOnLineAndOffLine	Both online and offline

Is restricted by

[OnLineCapability1Code on page 281](#)

2.2.2.84 ParentCurrencyCode

Definition: Code allocated to a currency, by a maintenance agency, under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds". Valid currency codes are registered with the ISO 4217 Maintenance Agency, and consist of three contiguous letters.

Type: CodeSet

Format

pattern [A-Z]{3,3}

Is restricted by

[ActiveCurrencyCode on page 243](#), [ActiveOrHistoricCurrencyCode on page 243](#)

2.2.2.85 PartyType3Code

Definition: Identification of the type of entity involved in a transaction.

Type: CodeSet

CodeName	Name	Definition
OPOI	OriginatingPOI	Point Of Interaction initiating the card payment transaction.
MERC	Merchant	Merchant providing goods and service in the card payment transaction.
ACCP	Acceptor	Card acceptor, party accepting the card and presenting transaction data to the acquirer.
ITAG	IntermediaryAgent	Party acting on behalf of other parties to process or forward data to other parties.
ACQR	Acquirer	Entity acquiring card transactions.
CISS	CardIssuer	Party that issues cards.
DLIS	DelegatIssuer	Party to whom the card issuer delegates to authorise card payment transactions.

Restricts

[PartyTypeCode on page 283](#)

2.2.2.86 PartyType4Code

Definition: Entity assigning an identification (for example merchant, acceptor, acquirer, tax authority, etc.).

Type: CodeSet

CodeName	Name	Definition
MERC	Merchant	Merchant providing goods and service in the card payment transaction.
ACCP	Acceptor	Card acceptor, party accepting the card and presenting transaction data to the acquirer.

CodeName	Name	Definition
ITAG	IntermediaryAgent	Party acting on behalf of other parties to process or forward data to other parties.
ACQR	Acquirer	Entity acquiring card transactions.
CISS	CardIssuer	Party that issues cards.
TAXH	TaxAuthority	Tax authority.

Restricts

PartyTypeCode on page 283

2.2.2.87 PartyTypeCode

Definition: Specifies the entitled party.

Type: CodeSet

CodeName	Name	Definition
SALE	SaleSystem	Party selling goods and services.
PCPT	POIComponent	Party component of a POI system or POI terminal (Point of Interaction).
ISUR	Issuer	Issuer is the entitled party.
HLDR	Holder	Holder is the entitled party.
INVE	Investor	Party, either an individual or organisation, whose assets are being invested.
EXEC	ExecutingFirm	Party that identifies an executing / give-up broker.
BROK	BrokerOfCredit	Party that receives the trade credit.
CORR	CorrespondentClearingFirm	Party that is going to carry the position on their books at another clearinghouse (exchanges).
COFI	ContraFirm	Party that is the counterparty in a trade.
COCL	ContraClearingFirm	Party that is the clearing firm of the counterparty in a trade.
UNDE	UnderlyingContraFirm	Party (broker or other firm), which is the contra side of the trade for the underlying security.
GIVE	GiveUpClearingFirm	Party to which the trade is given up (carries the position that results from a trade).
ORDE	OrderOriginationFirm	Party that originates an order.
SPON	SponsoringFirm	Party (member of an exchange) that is sponsoring an entering firm to send orders directly to the exchange.
CLEA	Clearingfirm	Party (broker) that settles security transactions from another broker for a fee = take up broker.

CodeName	Name	Definition
INTR	IntroducingFirm	Party that can relay an order directly to the trading floor, or give clients direct access to the floor. The introducing firm delegates the work of the floor operation, trade execution and accounting.
ENTE	EnteringFirm	Party that has recorded or reported an execution of a trade. When an entering firm that is not a party to a trade enters the trade into a trade recording system, any inquiries can be directed to the appropriate source.
CLIE	Client	A client is identified in third party-transactions or for investor in intermediary transactions.
STEP	StepInBroker	Broker to which the investment manager directs the execution of a portion of the trade.
AFFI	AffirmingParty	Party (buyer or seller) that positively affirms the details of a previously agreed security trade confirmation.
ETC1	ETCServiceProvider1	Party acting as the Electronic Trade Confirmation (ETC) service provider 1.
ETC2	ETCServiceProvider2	Party acting as the Electronic Trade Confirmation (ETC) service provider 2.
RQBR	RequestedBroker	In a directed order, broker with which the Receiver of the message is requested to execute the order.
TAXH	TaxAuthority	Tax authority.
DLIS	DelegatIssuer	Party to whom the card issuer delegates to authorise card payment transactions.
OPOI	OriginatingPOI	Point Of Interaction initiating the card payment transaction.
CISS	CardIssuer	Party that issues cards.
ACCP	Acceptor	Card acceptor, party accepting the card and presenting transaction data to the acquirer.
MERC	Merchant	Merchant providing goods and service in the card payment transaction.
ACQR	Acquirer	Entity acquiring card transactions.
ITAG	IntermediaryAgent	Party acting on behalf of other parties to process or forward data to other parties.
MTMG	MasterTerminalManager	Responsible for the maintenance of a card payment acceptance terminal.
TMGT	TerminalManager	Responsible for one or several maintenance functions of a card payment acceptance terminal.
ACQP	AcquirerProcessor	Entity providing acquiring card payment processing services on behalf on an acquirer.

CodeName	Name	Definition
CISP	CardIssuerProcessor	Entity providing issuing card payment processing services on behalf on an issuer.
CSCH	CardScheme	Entity defining rules and procedures for card payment transactions acting as an intermediary between an acquirer and an issuer.
SCHP	CardSchemeProcessor	Entity providing card payment processing services acting on behalf of a card scheme.
ATMG	ATMManager	Entity managing the ATM.
HSTG	HostingEntity	Entity hosting the ATM.
OATM	OriginatingATM	ATM initiating the transaction.
OTRM	OriginatingTerminal	Application on the terminal which has initiated the transaction.
ICCA	CardApplication	Application in the smart card.
PSYS	POISystem	Configuration to apply to the whole POI system.
PGRP	POIGroup	Configuration to apply to a subset of the whole POI system.
PSNG	SinglePOI	Configuration to apply to a single POI terminal.
BKAF	AccountFromBank	The bank of the source account.
BKAT	AccountToBank	The bank of the destination account.
AGNT	Agent	Entity providing card payment processing services acting as an intermediary between an acquirer and an issuer.
CRDH	Cardholder	Holder of a payment card.
CLRA	ClearingAgent	Agent in charge of clearing payment or related transactions.
GVIU	GovernmentInvestigationUnit	Government organisation investigation unit.
OTHN	OtherNational	Other card payment entity type defined at national level
OTHP	OtherPrivate	Other card payment entity type defined at private level
PISP	PaymentInitiationServiceProvider	Payment Initiation Service Provider (PISP)
PASP	PaymentServiceProvider	Entity providing payments services.
POOI	PointOfInteraction	Party in charge of controlling or supervising a card acceptance Point of Interaction
SETA	SettlementAgent	Agent in charge of the settlement of a payment or related transaction.

CodeName	Name	Definition
WLPR	WalletProvider	Provider of an electronic wallet
MKTP	Marketplace	Marketplace providing payment acceptance services on behalf of a merchant.
PFAC	PaymentFacilitator	Payment facilitator providing payment acceptance services on behalf of a merchant.

Is restricted by

[PartyType3Code](#) on page 282, [PartyType4Code](#) on page 282

2.2.2.88 POIComponentType1Code

Definition: Generic component type belonging to a POI (Point of Interaction) Terminal.

Type: CodeSet

CodeName	Name	Definition
SOFT	Soft	Payment or other software application.
EMVK	EMVKernel	EMV application kernel (EMV is the chip card specifications initially defined by Eurocard, Mastercard and Visa).
EMVO	EMVLevel1	EMV physical interface (EMV is the chip card specifications initially defined by Eurocard, Mastercard and Visa).
MRIT	MerchantInterface	Merchant interface.
CHIT	CardholderInterface	Cardholder Interface.
SECM	SecureModule	Security module.
PEDV	PINEntryDevice	Personal identification number (or PIN) entry device (PED).

Restricts

[POIComponentTypeCode](#) on page 286

2.2.2.89 POIComponentTypeCode

Definition: Generic component type belonging to a POI (Point of Interaction) Terminal.

Type: CodeSet

CodeName	Name	Definition
SOFT	Soft	Payment or other software application.
EMVK	EMVKernel	EMV application kernel (EMV is the chip card specifications initially defined by Eurocard, Mastercard and Visa).
EMVO	EMVLevel1	EMV physical interface (EMV is the chip card specifications initially defined by Eurocard, Mastercard and Visa).
MRIT	MerchantInterface	Merchant interface.

CodeName	Name	Definition
CHIT	CardholderInterface	Cardholder Interface.
SECM	SecureModule	Security module.
PEDV	PINEntryDevice	Personal identification number (or PIN) entry device (PED).
AQPR	AcquirerParameters	Acquirer specific configuration parameters for the point of interaction (POI) system.
MRPR	MerchantParameters	Merchant configuration parameters for the point of interaction (POI).
VDPR	VendorParameters	Point of interaction parameters defined by the manufacturer for instance the PIN verification capabilities.
AQPP	AcquirerProtocolParameters	Parameters for acquirer interface of the point of interaction, including acquirer host configuration parameters.
APPR	ApplicationParameters	Parameters of a payment application running on the point of interaction.
DVCE	Device	Device sub-component of a component of the point of interaction.
DRVR	Driver	Driver module of the point of interaction.
MDWR	Middleware	Software module of the point of interaction.
OPST	OperatingSystem	Software that manages hardware to provide common services to the applications.
APLI	PaymentApplication	Payment application software.
SCPR	SecurityParameters	Security parameters of the point of interaction.
SERV	Server	Payment server of a point of interaction system.
TERM	Terminal	Payment terminal point of interaction.
TLPR	TerminalParameters	Manufacturer configuration parameters of the point of interaction.
CRTF	CertificateParameters	Certificate provided by a terminal manager.
TMSP	TMSProtocolParameters	Configuration parameters for the TMS protocol.
SAPR	SaleToPOIProtocolParameters	Parameters related to the Sale to POI protocol.
SACP	SaleComponent	Component of the Sale system.
LOGF	LogFile	Any repository used for recording log traces.
MDFL	MediaFile	Media file managed by an application of the POI.
CONF	ConfigurationFile	Configuration file relevant for the POI.

CodeName	Name	Definition
RPFL	ReportFile	Report file generated by the POI.
PROB	Probe	Probe used to monitor a feature on the POI.

Is restricted by

[POIComponentType1Code on page 286](#)

2.2.2.90 PreferredContactMethod1Code

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

CodeName	Name	Definition
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.

Restricts

[PreferredContactMethodCode on page 288](#)

2.2.2.91 PreferredContactMethodCode

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

CodeName	Name	Definition
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
ONLI	Online	Preferred method used to reach the contact is online.

Is restricted by

[PreferredContactMethod1Code on page 288](#)

2.2.2.92 PriceValueType1Code

Definition: Specifies a type of value of the price.

Type: CodeSet

CodeName	Name	Definition
DISC	Discount	Price expressed as a number of percentage points below par, for example, a discount price of 2.0% equals a price of 98 when par is 100.
PREM	Premium	Price expressed as a number of percentage points above par, for example, a premium price of 2.0% equals a price of 102 when par is 100.
PARV	Par	Price is the face amount.

Restricts

[PriceValueTypeCode on page 289](#)

2.2.2.93 PriceValueTypeCode

Definition: Price will not be paid.

Type: CodeSet

CodeName	Name	Definition
DISC	Discount	Price expressed as a number of percentage points below par, for example, a discount price of 2.0% equals a price of 98 when par is 100.
PREM	Premium	Price expressed as a number of percentage points above par, for example, a premium price of 2.0% equals a price of 102 when par is 100.
PARV	Par	Price is the face amount.
YIEL	Yield	Price expressed as a yield.
SPRE	Spread	Difference between a market maker's bid and asked price.
PEUN	PerUnit	Price expressed per unit.
ABSO	Absolute	Price is expressed as absolute.
TEDP	TEDPrice	Price is expressed as Treasury Euro Dollar price.
TEDY	TEDYield	Price is expressed as Treasury Euro Dollar yield.
FICT	FixedCabinetTrade	Cabinet trades are used to indicate prices that trade at a price lower than that available on an exchange and they

CodeName	Name	Definition
		can be fixed or variable (primarily used for listed futures and options).
VACT	VariableCabinetTrade	Cabinet trades are used to indicate prices that trade at a price lower than that available on an exchange and they can be fixed or variable (primarily used for listed futures and options).
PRCT	Percentage	Price expressed as a percentage of par.
UKWN	Unknown	Price is unknown by the sender or has not been established.
OPEN	OpenDated	Price has not been established.
UNSP	Unspecified	Price is not required to be specified by account owner.
TBSP	ToBeSpecified	Price to be specified by account owner.
ACTU	ActualAmount	Price expressed as a currency and amount per unit or per share.
NILP	NilPayment	Price will not be paid.
NEGA	NegativeActualAmount	Price must be interpreted as a negative amount of currency per unit or per share.

Is restricted by

PriceValueType1Code on page 289

2.2.2.94 RemittanceLocationMethod2Code

Definition: Specifies the method used to deliver the remittance advice information.

Type: CodeSet

CodeName	Name	Definition
FAXI	Fax	Remittance advice information must be faxed.
EDIC	ElectronicDataInterchange	Remittance advice information must be sent through Electronic Data Interchange (EDI).
URID	UniformResourceIdentifier	Remittance advice information needs to be sent to a Uniform Resource Identifier (URI). URI is a compact string of characters that uniquely identify an abstract or physical resource. URI's are the super-set of identifiers, such as URLs, email addresses, ftp sites, etc, and as such, provide the syntax for all of the identification schemes.
EMAL	EMail	Remittance advice information must be sent through e-mail.
POST	Post	Remittance advice information must be sent through postal services.

CodeName	Name	Definition
SMSM	SMS	Remittance advice information must be sent through by phone as a short message service (SMS).

Restricts

[RemittanceLocationMethodCode on page 291](#)

2.2.2.95 RemittanceLocationMethodCode

Definition: Specifies the method used to deliver the remittance advice information.

Type: CodeSet

CodeName	Name	Definition
FAXI	Fax	Remittance advice information must be faxed.
EDIC	ElectronicDataInterchange	Remittance advice information must be sent through Electronic Data Interchange (EDI).
URID	UniformResourceIdentifier	Remittance advice information needs to be sent to a Uniform Resource Identifier (URI). URI is a compact string of characters that uniquely identify an abstract or physical resource. URI's are the super-set of identifiers, such as URLs, email addresses, ftp sites, etc, and as such, provide the syntax for all of the identification schemes.
EMAL	EMail	Remittance advice information must be sent through e-mail.
POST	Post	Remittance advice information must be sent through postal services.
SMSM	SMS	Remittance advice information must be sent through by phone as a short message service (SMS).

Is restricted by

[RemittanceLocationMethod2Code on page 290](#)

2.2.2.96 TaxRecordPeriod1Code

Definition: Specifies the period related to the tax payment.

Type: CodeSet

CodeName	Name	Definition
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.

CodeName	Name	Definition
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.

Restricts

TaxRecordPeriodCode on page 292

2.2.2.97 TaxRecordPeriodCode

Definition: Specifies the period related to the tax payment.

Type: CodeSet

CodeName	Name	Definition
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.

CodeName	Name	Definition
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.

Is restricted by

TaxRecordPeriod1Code on page 291

2.2.2.98 TransactionChannel1Code

Definition: Identifies the type of the communication channels used by the cardholder to the acceptor system.

Type: CodeSet

CodeName	Name	Definition
MAIL	MailOrder	Mail order.
TLPH	TelephoneOrder	Telephone order.
ECOM	ElectronicCommerce	Electronic commerce.
TVPY	TelevisionPayment	Payment on television.

Restricts

[TransactionChannelCode on page 294](#)

2.2.2.99 TransactionChannelCode

Definition: Specifies the type of communication channel.

Type: CodeSet

CodeName	Name	Definition
MAIL	MailOrder	Mail order.
TLPH	TelephoneOrder	Telephone order.
ECOM	ElectronicCommerce	Electronic commerce.
TVPY	TelevisionPayment	Payment on television.
BRAN	OfficeOrBranch	Office or branch.
HOBA	HomeBanking	Home banking.
FIAD	FinancialAdvisor	Financial advisor.
MOBL	MobilePayment	Payment performed through a cardholder mobile device.
SECM	SecuredElectronicCommerce	Electronic commerce with cardholder authentication.
MPOS	MobilePOS	Payment performed through a merchant mobile device.

Is restricted by

[TransactionChannel1Code on page 293](#)

2.2.2.100 TransactionEnvironment1Code

Definition: Indicates the environment of the transaction.

Type: CodeSet

CodeName	Name	Definition
MERC	Merchant	Merchant environment.
PRIV	Private	Private environment.
PUBL	Public	Public environment.

Restricts

[TransactionEnvironmentCode on page 294](#)

2.2.2.101 TransactionEnvironmentCode

Definition: Indicates the environment of the transaction.

Type: CodeSet

CodeName	Name	Definition
MERC	Merchant	Merchant environment.

CodeName	Name	Definition
PRIV	Private	Private environment.
PUBL	Public	Public environment.
BRCH	Branch	Bank environment.
OTHR	Other	Other environments, for instance a mall or an airport.

Is restricted by

[TransactionEnvironment1Code](#) on page 294

2.2.2.102 UnitOfMeasure1Code

Definition: Unit of measure of the item purchased.

Type: CodeSet

CodeName	Name	Definition
PIEC	Piece	Standard length of cloth, wallpaper, as an item for sale or amount of a substance.
TONS	Ton	Measure of weight, in Britain 2240lb (long ton)and in the US 2000lb (short ton).
FOOT	Foot	Unit of length equal to 1/3 yard.
GBGA	GBGallon	Unit of volume that is equal to 8 pints.
USGA	USGallon	Unit of volume that is equal to 8 pints.
GRAM	Gram	Unit of measure that is equal to a 1, 000th of a kilo.
INCH	Inch	Measure of length equal to 2.54 cm.
KILO	Kilogram	Basic unit of mass in the SI system, 1000 grams.
PUND	Pound	Unit of weight equal to 0.454 kilograms.
METR	Metre	Unit of length in the metric system, equal to 39.37 inches.
CMET	Centimetre	Unit of measure that is equal to one hundredth of a metre.
MMET	Millimetre	Unit of measure that is a thousandth of one metre.
LITR	Litre	Unit of volume that is equal to a thousand cubic centimetres.
CELI	Centilitre	Unit of volume that is equal to one hundredth of a litre.
MILI	MilliLitre	Unit of volume that is equal to one thousandth of a litre.
GBOU	GBOunce	Unit of weight equal to a sixteenth of a pound.

CodeName	Name	Definition
USOU	USOunce	Unit of weight equal to a sixteenth of a pound.
GBQA	GBQuart	Unit of volume that is equal to 2 pints.
USQA	USQuart	Unit of volume that is equal to 2 pints.
GBPI	GBPint	Unit of volume that is equal to 568 cubic centimetres.
USPI	USPint	Unit of volume that is equal to 473 cubic centimetres.
MILE	Mile	Unit of length equal to 1, 760 yards.
KMET	Kilometre	Unit of measure that is equal to 1, 000 meters.
YARD	Yard	Unit of length equal to 3 feet or 0.9144 metre.
SQKI	SquareKilometre	Measure of a surface, one kilometre by one kilometre.
HECT	Hectare	Unit of measure that is equal to 10, 000 square meters.
ARES	Are	Unit of measure equal to a 100 square meters.
SMET	SquareMetre	Measure of a surface, one metre by one metre.
SCMT	SquareCentimetre	Measure of a surface, one centimetre by one centimetre.
SMIL	SquareMillimetre	Measure of a surface, one millimetre by one millimetre.
SQMI	SquareMile	Measure of a surface, one mile by one mile.
SQYA	SquareYard	Measure of a surface, one yard by one yard.
SQFO	SquareFoot	Measure of a surface, one foot by one foot.
SQIN	SquareInch	Measure of a surface, one inch by one inch.
ACRE	Acre	Unit of measure equal to 4, 840 square yards.

Restricts

UnitOfMeasureCode on page 296

2.2.2.103 UnitOfMeasureCode

Definition: Identifies the unit of measure by means of a code.

Type: CodeSet

CodeName	Name	Definition
KILO	Kilogram	Basic unit of mass in the SI system, 1000 grams.
PIEC	Piece	Standard length of cloth, wallpaper, as an item for sale or amount of a substance.
TONS	Ton	Measure of weight, in Britain 2240lb (long ton)and in the US 2000lb (short ton).
METR	Metre	Unit of length in the metric system, equal to 39.37 inches.
INCH	Inch	Measure of length equal to 2.54 cm.
YARD	Yard	Unit of length equal to 3 feet or 0.9144 metre.
GBGA	GBGallon	Unit of volume that is equal to 8 pints.
GRAM	Gram	Unit of measure that is equal to a 1, 000th of a kilo.
CMET	Centimetre	Unit of measure that is equal to one hundredth of a metre.
SMET	SquareMetre	Measure of a surface, one metre by one metre.
FOOT	Foot	Unit of length equal to 1/3 yard.
MILE	Mile	Unit of length equal to 1, 760 yards.
SQIN	SquareInch	Measure of a surface, one inch by one inch.
SQFO	SquareFoot	Measure of a surface, one foot by one foot.
SQMI	SquareMile	Measure of a surface, one mile by one mile.
GBOU	GBOunce	Unit of weight equal to a sixteenth of a pound.
USOU	USOunce	Unit of weight equal to a sixteenth of a pound.
GBPI	GBPint	Unit of volume that is equal to 568 cubic centimetres.
USPI	USPint	Unit of volume that is equal to 473 cubic centimetres.
GBQA	GBQuart	Unit of volume that is equal to 2 pints.
USQA	USQuart	Unit of volume that is equal to 2 pints.
USGA	USGallon	Unit of volume that is equal to 8 pints.
MMET	Millimetre	Unit of measure that is a thousandth of one metre.
KMET	Kilometre	Unit of measure that is equal to 1, 000 meters.

CodeName	Name	Definition
SQYA	SquareYard	Measure of a surface, one yard by one yard.
ACRE	Acre	Unit of measure equal to 4, 840 square yards.
ARES	Are	Unit of measure equal to a 100 square meters.
SMIL	SquareMillimetre	Measure of a surface, one millimetre by one millimetre.
SCMT	SquareCentimetre	Measure of a surface, one centimetre by one centimetre.
HECT	Hectare	Unit of measure that is equal to 10, 000 square meters.
SQKI	SquareKilometre	Measure of a surface, one kilometre by one kilometre.
MILI	MilliLitre	Unit of volume that is equal to one thousandth of a litre.
CELI	Centilitre	Unit of volume that is equal to one hundredth of a litre.
LITR	Litre	Unit of volume that is equal to a thousand cubic centimetres.
PUND	Pound	Unit of weight equal to 0.454 kilograms.
ALOW	Allowances	Amount of money deducted from a price or an amount due.
ACCY	AmountOfCurrency	Number of monetary units specified in a currency, where the unit of currency is explicit and compliant with ISO 4217.
BARL	Barrels	Unit of volume that is equal to 42 US gallons.
BCUF	BillionCubicFeet	Unit of measure for large volumes of natural gas equivalent to 28316846 cubic meters.
BDFT	BoardFeet	Measure of length equal to 144 cubic inches.
BUSL	Bushels	Unit of weight that is equal to 8 gallons. Mostly used for agricultural products with a specification of weight defined for each commodity differently.
CEER	CertifiedEmissionsReduction	Unit of emissions type (or carbon credits) issued by the Clean Development Mechanism (CDM) Executive Board for emission reductions achieved by CDM projects and verified by a DOE (Designated Operational Entity) under the rules of the Kyoto Protocol.
CLRT	ClimateReserveTonnes	Unit of offset credits used by the Climate Action Reserve. One Climate Reserve Tonne is equal to one metric ton of Greenhouse Gas (GHG) reduced/ sequestered.

CodeName	Name	Definition
CBME	CubicMeters	Unit of volume that is equal to one meter in length, breadth and height or also equal to 1000 liters.
DAYS	Days	Unit of time that is equal to 24 hours.
DMET	DryMetricTons	Unit of weight that is equal to the same mass value as a metric ton excluding moisture.
ENVC	EnvironmentalCredit	Unit of measure for ownership of credit (or allowance) of carbon dioxide emission (in metric ton).
ENVO	EnvironmentalOffset	Unit of measure for reduction of carbon dioxide emission (in metric ton) that may result in Environmental Credit.
HUWG	Hundredweight	Unit of weight or mass of various values in the Imperial Unit System also known as quintal, cental or centum.
KWDC	KilowattDayCapacity	Unit of measure of the capacity of production of electric power equal to 1000 watt in one day.
KWHO	KilowattHours	Unit of measure that is equal to the power consumption of one kilowatt during one hour.
KWHC	KilowattHoursCapacity	Unit of measure of the capacity of production of electric power equal to 1000 watt in one hour.
KMOC	KilowattMinuteCapacity	Unit of measure of the capacity of production of electric power equal to 1000 watt in one minute.
KWMC	KilowattMonthCapacity	Unit of measure of the capacity of production of electric power equal to 1000 watt in one month.
KWYC	KilowattYearCapacity	Unit of measure of the capacity of production of electric power equal to 1000 watt in one year.
MWDC	MegawattDayCapacity	Unit of measure of the capacity of production of electric power equal to 1000000 watt in one day.
MWHO	MegawattHours	Unit of measure that is equal to the power consumption of one megawatt during one hour.
MWHC	MegawattHoursCapacity	Unit of measure of the capacity of production of electric power equal to 1000000 watt in one hour.
MWMC	MegawattMinuteCapacity	Unit of measure of the capacity of production of electric power equal to 1000000 watt in one minute.
MMOC	MegawattMonthCapacity	Unit of measure of the capacity of production of electric power equal to 1000000 watt in one month.

CodeName	Name	Definition
MWYC	MegawattYearCapacity	Unit of measure of the capacity of production of electric power equal to 1000000 watt in one year.
TONE	MetricTons	Unit of mass equal to 1000 kilograms; equivalent to approximately 2,204.6 pounds, 1.102 short tons (US) or 0.984 long tons (imperial).
MIBA	MillionBarrels	Unit of volume that is equal to 1 million barrels equivalent to 42.000.000 US gallons.
MBTU	OneMillionBTU	Unit of measure of heat equal to one million British thermal unit (BTU).
OZTR	TroyOunces	Unit of weight equal to 31.1034768 grams. Used in precious metals.
UCWT	USHundredweight	Unit of weight or mass of various values in the US Customary System also known as quintal, cental or centum. Equal to 100 lbs.
IPNT	IndexPoint	Decimal number used to calculate an amount or a price.
PWRD	PrincipalWithRelationToDebtInstrument	Amount of money borrowed, or part of that amount which remains unpaid (excluding interest).
DGEU	DieselGallonEquivalent	Amount of fuel alternative equal to one gallon of diesel.
GGEU	GasolineGallonEquivalent	Amount of fuel alternative equal to one gallon of gasoline.
TOCD	TonsOfCarbonDioxide	Tons of carbon dioxide.
SHAS	Shares	Financial instrument that gives the owner right to dividends paid by a company and the most junior claim on the companies assets in the event of a bankruptcy.
THMS	Therms	Unit of heat, often used a unit of measure for natural gas in the UK.
FUTU	Future	Exchange traded contract that defines an agreement to buy specific quantities of a commodity or financial instrument at an agreed time in the future.
GWHO	GigawattHours	Unit of measure that is equal to the power consumption of one Gigawatt during one hour.
BRTU	BritishThermalUnit	Unit of measure of heat required to raise the temperature of one pound of water by one degree Fahrenheit.
LOTS	Lot	Indication of the unit of measurement.
BAGG	Bag	Code for a bag.
BALE	Bale	Code for a bale.
BOTL	Bottle	Code for a bottle.

CodeName	Name	Definition
BOXX	Box	Code for a box.
CRTN	Carton	Code for a carton.
CNTR	Container	Code for a container.
CRAT	Crate	Code for a crate.
CBIN	CubicInch	Measure of a volume, one inch by one inch by one inch.
CBML	CubicMillimetre	Unit of volume that is equal to one thousandth of a litre.
GBFO	GBFuildOunce	Unit of volume equal to 2, 841 306 centilitre.
GBTN	GBTon	Measure of weight, in Britain 2240 lb (long ton).
USBA	USBarrel	Unit of volume equal to 158, 9873 litre.
USFO	USFluidOunce	Unit of volume equal to 2, 957353 centilitre.
USTN	USTon	Measure of weight, in the US 2000 lb (short ton).
CDDA	CoolingDegreeDay	Cooling degree day
HDDA	HeatingDegreeDay	Heating degree day
CPDA	CriticalPrecipitationDay	Critical precipitation day
CHMT	ChargingMinutes	EV Charging minutes.

Is restricted by

UnitOfMeasure1Code on page 295

2.2.2.104 UserInterface2Code

Definition: Type of interface to display a message.

Type: CodeSet

CodeName	Name	Definition
MDSP	MerchantDisplay	Merchant display or interface.
CDSP	CardholderDisplay	Cardholder display or interface.

Restricts

UserInterfaceCode on page 301

2.2.2.105 UserInterfaceCode

Definition: Type of user interface to display or print information.

Type: CodeSet

CodeName	Name	Definition
CDSP	CardholderDisplay	Cardholder display or interface.
CRCP	CardholderReceipt	Cardholder receipt.
MDSP	MerchantDisplay	Merchant display or interface.
MRCP	MerchantReceipt	Merchant receipt.
ACQU	Acquirer	Acquirer.
ISSR	Issuer	Issuer.
AGNT	Agent	Agent.
CRDO	OtherCardholderInterface	Other interface of the cardholder, for instance e-mail or smartphone message.
CHAP	CardholderApplication	Information dedicated to a software application related to a device belonging to the cardholder.
CLRA	ClearingAgentApplication	Data dedicated to an application maintained by a clearing agent.
CLRL	ClearingAgentLog	Data dedicated to a log maintained by the clearing agent.
DSPU	Dispute	Interface used in case of disputes or chargebacks.
FILE	File	File used to store the message.
LOGF	Log	Information dedicated to a log file.
MRAP	MerchantApplication	Information dedicated to a software application related to a device belonging to the merchant.
OTAI	OtherAcquirerInterface	Other type of acquirer interface.
OCAI	OtherClearingAgentInterface	Data dedicated to another interface maintained by the clearing agent.
OTII	OtherIssuerInterface	Other type of issuer interface.
MRIN	OtherMerchantInterface	Other interface of the merchant for instance e-mail or smartphone message.
OTHN	OtherNational	Other type of interface defined at national level.
OTHP	OtherPrivate	Other type of interface defined at private level.
OSAI	OtherSettlementAgentInterface	Other settlement agent interface.
STLI	SettlementAgent	Settlement agent interface.
TUCR	TopUpCredit	Credit information related to a top-up account.
CSTM	CustomerStatement	Cardholder bank statement.

Is restricted by

UserInterface2Code on page 301

2.2.3 Date

2.2.3.1 ISODate

Definition: A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Type: Date

2.2.4 DateTime

2.2.4.1 ISODateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: DateTime

2.2.5 IdentifierSet

2.2.5.1 AnyBICDec2014Identifier

Definition: Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Identification scheme: SWIFT; AnyBICIdentifier

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Constraints

- **AnyBIC**

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consists of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

2.2.5.2 BICFIDec2014Identifier

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Identification scheme: SWIFT; BICIdentifier

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Constraints

- **BICFI**

Valid BICs for financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consist of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid FI BIC.

2.2.5.3 IBAN2007Identifier

Definition: The International Bank Account Number is a code used internationally by financial institutions to uniquely identify the account of a customer at a financial institution as described in the 2007 edition of the ISO 13616 standard "Banking and related financial services - International Bank Account Number (IBAN)" and replaced by the more recent edition of the standard.

Type: IdentifierSet

Identification scheme: National Banking Association; International Bank Account Number (ISO 13616)

Format

pattern [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}

Constraints

- **IBAN**

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00003
- *Error Text:* Invalid IBAN format or invalid check digits.

2.2.5.4 ISINOct2015Identifier

Definition: The International Securities Identification Number is a code allocated to financial instruments as well as referential instruments, as described in the ISO 6166 standard, associated with the minimum descriptive data. The ISIN consists of a prefix using the alpha-2 country codes or reserved codes specified in ISO 3166 or other prefixes as may be determined by the Registration Authority for the ISO 6166 standard, a nine characters (alphanumeric) basic code and a check digit.

Note: this identifier also supports the new version of the standard, which was published in 2021 (ISO 6166:2021) as there is no update in the pattern.

Type: IdentifierSet

Identification scheme: ANNA; ISINIdentifier

Format

pattern [A-Z]{2,2}[A-Z0-9]{9,9}[0-9]{1,1}

2.2.5.5 LEIdentifier

Definition: Legal Entity Identifier is a code allocated to a party as described in ISO 17442 "Financial Services - Legal Entity Identifier (LEI)".

Type: IdentifierSet

Identification scheme: Global LEI System; LEIdentifier

Format

pattern [A-Z0-9]{18,18}[0-9]{2,2}

2.2.5.6 UUIDv4Identifier

Definition: Universally Unique Identifier (UUID) version 4, as described in IETF RFC 4122 "Universally Unique Identifier (UUID) URN Namespace".

Type: IdentifierSet

Identification scheme: RFC4122; UUIDv4

Format

pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}

2.2.6 Indicator

2.2.6.1 ChargeIncludedIndicator

Definition: Indicates whether charges have already been included.

Type: Indicator

Meaning When True: Included

Meaning When False: Pre-advised

2.2.6.2 TrueFalseIndicator

Definition: A flag indicating a True or False value.

Type: Indicator

Meaning When True: True

Meaning When False: False

2.2.6.3 YesNoIndicator

Definition: Indicates a "Yes" or "No" type of answer for an element.

Type: Indicator

Meaning When True: Yes

Meaning When False: No

2.2.7 Quantity

2.2.7.1 DecimalNumber

Definition: Number of objects represented as a decimal number, for example 0.75 or 45.6.

Type: Quantity

Format

totalDigits	18
fractionDigits	17

2.2.7.2 NonNegativeDecimalNumber

Definition: Number of objects represented as a non negative decimal number, for example, 0.75 or 45.6.

Type: Quantity

Format

minInclusive	0
totalDigits	18
fractionDigits	17

2.2.7.3 Number

Definition: Number of objects represented as an integer.

Type: Quantity

Format

totalDigits	18
fractionDigits	0

2.2.8 Rate

2.2.8.1 BaseOneRate

Definition: Rate expressed as a decimal, for example, 0.7 is 7/10 and 70%.

Type: Rate

Format

totalDigits	11
fractionDigits	10
baseValue	1.0

2.2.8.2 PercentageRate

Definition: Rate expressed as a percentage, that is, in hundredths, for example, 0.7 is 7/10 of a percent, and 7.0 is 7%.

Type: Rate

Format

totalDigits	11
fractionDigits	10
baseValue	100.0

2.2.9 Text

2.2.9.1 Exact1NumericText

Definition: Specifies a numeric string with an exact length of 1 digit.

Type: Text

Format

pattern	[0-9]
---------	-------

2.2.9.2 Exact3NumericText

Definition: Specifies a numeric string with an exact length of 3 digits.

Type: Text

Format

pattern	[0-9]{3}
---------	----------

2.2.9.3 Exact4AlphaNumericText

Definition: Specifies an alphanumeric string with a length of 4 characters.

Type: Text

Format

pattern	[a-zA-Z0-9]{4}
---------	----------------

2.2.9.4 Max1025Text

Definition: Specifies a character string with a maximum length of 1025 characters.

Type: Text

Format

minLength	1
maxLength	1025

2.2.9.5 Max105Text

Definition: Specifies a character string with a maximum length of 105 characters.

Type: Text

Format

minLength	1
maxLength	105

2.2.9.6 Max128Text

Definition: Specifies a character string with a maximum length of 128 characters.

Type: Text

Format

minLength	1
maxLength	128

2.2.9.7 Max140Text

Definition: Specifies a character string with a maximum length of 140 characters.

Type: Text

Format

minLength	1
maxLength	140

2.2.9.8 Max15NumericText

Definition: Specifies a numeric string with a maximum length of 15 digits.

Type: Text

Format

pattern	[0-9]{1,15}
---------	-------------

2.2.9.9 Max15PlusSignedNumericText

Definition: Specifies a numeric string with a maximum length of 15 digits and may be prefixed with a plus sign.

Type: Text

Format

pattern	[+]{0,1}[0-9]{1,15}
---------	---------------------

2.2.9.10 Max16Text

Definition: Specifies a character string with a maximum length of 16 characters.

Type: Text

Format

minLength	1
maxLength	16

2.2.9.11 Max2048Text

Definition: Specifies a character string with a maximum length of 2048 characters.

Type: Text

Format

minLength	1
maxLength	2048

2.2.9.12 Max34Text

Definition: Specifies a character string with a maximum length of 34 characters.

Type: Text

Format

minLength	1
-----------	---

maxLength	34
-----------	----

2.2.9.13 Max350Text

Definition: Specifies a character string with a maximum length of 350 characters.

Type: Text

Format

minLength	1
maxLength	350

2.2.9.14 Max35Text

Definition: Specifies a character string with a maximum length of 35 characters.

Type: Text

Format

minLength	1
maxLength	35

2.2.9.15 Max3NumericText

Definition: Specifies a numeric string with a maximum length of 3 digits.

Type: Text

Format

pattern	[0-9]{1,3}
---------	------------

2.2.9.16 Max4Text

Definition: Specifies a character string with a maximum length of 4 characters.

Type: Text

Format

minLength	1
maxLength	4

2.2.9.17 Max500Text

Definition: Specifies a character string with a maximum length of 500 characters.

Type: Text

Format

minLength	1
maxLength	500

2.2.9.18 Max5NumericText

Definition: Specifies a numeric string with a maximum length of 5 digits.

Type: Text

Format

pattern	[0-9]{1,5}
---------	------------

2.2.9.19 Max70Text

Definition: Specifies a character string with a maximum length of 70characters.

Type: Text

Format

minLength	1
maxLength	70

2.2.9.20 Min2Max3NumericText

Definition: Specifies a numeric string with a minimum length of 2 digits, and a maximum length of 3 digits.

Type: Text

Format

pattern	[0-9]{2,3}
---------	------------

2.2.9.21 Min3Max4NumericText

Definition: Specifies a numeric string with a minimum length of 3 digits, and a maximum length of 4 digits.

Type: Text

Format

pattern	[0-9]{3,4}
---------	------------

2.2.9.22 Min8Max28NumericText

Definition: Specifies a numeric string with a minimum length of 8 digits, and a maximum length of 28 digits.

Type: Text

Format

pattern	[0-9]{8,28}
---------	-------------

2.2.9.23 PhoneNumber

Definition: The collection of information which identifies a specific phone or FAX number as defined by telecom services.

It consists of a "+" followed by the country code (from 1 to 3 characters) then a "-" and finally, any combination of numbers, "(", ")", "+", and "-" (up to 30 characters).

Type: Text

Format

pattern	\+[0-9]{1,3}-[0-9()+\-]{1,30}
---------	-------------------------------

2.2.10 YearMonth

2.2.10.1 ISOYearMonth

Definition: Month within a particular calendar year represented by YYYY-MM (ISO 8601).

Type: YearMonth

Legal Notices

Copyright

S.W.I.F.T. SC © 2026. All rights reserved.

You may copy this publication within your organisation. Any such copy must include these legal notices.

Confidentiality

This publication may contain Swift or third-party confidential information. Do not disclose this publication outside your organisation without the prior written consent of Swift.

Disclaimer

The information in this publication may change from time to time. You must always refer to the latest available version.

Swift Standards Intellectual Property Rights (IPR) Policy - End-User License Agreement

Swift Standards are licensed subject to the terms and conditions of the *Swift Standards IPR Policy - End-User License Agreement* available at www.swift.com > About Swift > Legal > Swift Standards IPR Policy.

Translations

The English version of Swift documentation is the only official version.

Trademarks and Patents

Swift is the trade name of S.W.I.F.T. SC. The following are registered trademarks of Swift: 3SKey, Innotribe, MyStandards, Sibos, Swift, SwiftNet, the Standards Forum logo, the Swift logo, Swift GPI with logo, the Swift GPI logo, and UETR. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.