

Standards

Standards MX

Message Reference Guide

AccountReportingRequestV05 (camt.060.001.05)

This publication includes information exported from the MyStandards web platform.

For the official documentation of the messages included in this publication, see the relevant Standards MX Message Reference Guides available on swift.com > Support > Documentation

Table of Contents

1	MX camt.060.001.05 AccountReportingRequestV05	3
1.1	MessageDefinition Functionality	3
1.2	Structure	4
1.3	Constraints	4
1.4	Message Building Blocks	6
2	Message Items Types	14
2.1	MessageComponents	14
2.2	Message Datatypes	46
	Legal Notices	65

1 MX camt.060.001.05 AccountReportingRequestV05

1.1 MessageDefinition Functionality

Scope

The AccountReportingRequest message is sent by the account owner, either directly or through a forwarding agent, to one of its account servicing institutions. It is used to ask the account servicing institution to send a report on the account owner's account in a BankToCustomerAccountReport (camt.052), a BankToCustomerStatement (camt.053) or a BankToCustomerDebitCreditNotification (camt.054).

Outline

The AccountReportingRequestV05 MessageDefinition is composed of 3 MessageBuildingBlocks:

A. GroupHeader

Set of elements used to provide further details on the message.

B. ReportingRequest

Set of elements used to provide further details on the reporting request.

C. SupplementaryData

Additional information that cannot be captured in the structured elements and/or any other specific block.

1.2 Structure

Index	Or	MessageElement/BuildingBlock<XML Tag>	Mult.	Type	Constr. No.	Page
		Message root <Document> <AcctRptgReq>	[1..1]			
		GroupHeader <GrpHdr>	[1..1]	±		6
		ReportingRequest <RptgReq>	[1..*]			6
		Identification <Id>	[0..1]	Text		7
		RequestedMessageNameIdentification <ReqdMsgNmId>	[1..1]	Text		7
		Account <Acct>	[0..1]	±		7
		AccountOwner <AcctOwnr>	[1..1]	±		8
		AccountServicer <AcctSvcr>	[0..1]	±		8
		ReportingPeriod <RptgPrd>	[0..1]			8
		FromDate <FrToDt>	[1..1]	±		9
		FromTime <FrToTm>	[0..1]	±		9
		Type <Tp>	[1..1]	CodeSet		9
		ReportingSequence <RptgSeq>	[0..1]	±		10
		RequestedTransactionType <ReqdTxDp>	[0..1]			10
		Status <Sts>	[1..1]	±		10
		CreditDebitIndicator <CdtDbtInd>	[1..1]	CodeSet		11
		FloorLimit <FlrLmt>	[0..*]			11
		Amount <Amt>	[1..1]	Amount	✓C1, ✓C5	11
		CreditDebitIndicator <CdtDbtInd>	[1..1]	CodeSet		12
		RequestedBalanceType <ReqdBalTp>	[0..*]	±		12
		SupplementaryData <SplmtryData>	[0..*]	±	C7	12

1.3 Constraints

C1 ActiveOrHistoricCurrency ✓

(Rule)

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

C2 AnyBIC ✓*(Rule)*

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consists of eight (8) or eleven (11) contiguous characters. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

C3 BICFI ✓*(Rule)*

Valid BICs for financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consist of eight (8) or eleven (11) contiguous characters. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid FI BIC.

C4 Country ✓*(Rule)*

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code). (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

C5 CurrencyAmount ✓*(Rule)*

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

C6 IBAN ✓

(Rule)

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00003
- *Error Text:* Invalid IBAN format or invalid check digits.

C7 SupplementaryDataRule

(Rule)

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

1.4 Message Building Blocks

This chapter describes the MessageBuildingBlocks of this MessageDefinition.

1.4.1 GroupHeader <GrpHdr>

Presence: [1..1]

Definition: Set of elements used to provide further details on the message.

GroupHeader <GrpHdr> contains the following elements (see [GroupHeader77](#) on page 28 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		MessageIdentification <MsgId>	[1..1]	Text		28
		CreationDateTime <CreDtTm>	[1..1]	DateTime		28
		MessageSender <MsgSndr>	[0..1]	±		28

1.4.2 ReportingRequest <RptgReq>

Presence: [1..*]

Definition: Set of elements used to provide further details on the reporting request.

ReportingRequest <RptgReq> contains the following **ReportingRequest5** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[0..1]	Text		7
		RequestedMessageNameIdentification <ReqdMsgNmId>	[1..1]	Text		7
		Account <Acct>	[0..1]	±		7
		AccountOwner <AcctOwnr>	[1..1]	±		8
		AccountServicer <AcctSvcr>	[0..1]	±		8
		ReportingPeriod <RptgPrd>	[0..1]			8
		FromDate <FrToDt>	[1..1]	±		9
		FromTime <FrToTm>	[0..1]	±		9
		Type <Tp>	[1..1]	CodeSet		9
		ReportingSequence <RptgSeq>	[0..1]	±		10
		RequestedTransactionType <ReqdTxDp>	[0..1]			10
		Status <Sts>	[1..1]	±		10
		CreditDebitIndicator <CdtDbtInd>	[1..1]	CodeSet		11
		FloorLimit <FlrLmt>	[0..*]			11
		Amount <Amt>	[1..1]	Amount	✓C1, ✓C5	11
		CreditDebitIndicator <CdtDbtInd>	[1..1]	CodeSet		12
		RequestedBalanceType <ReqdBalTp>	[0..*]	±		12

1.4.2.1 Identification <Id>

Presence: [0..1]

Definition: Unique identification, as assigned by the account owner, to unambiguously identify the account reporting request.

Datatype: Max35Text on page 63

1.4.2.2 RequestedMessageNameIdentification <ReqdMsgNmId>

Presence: [1..1]

Definition: Specifies the type of the requested reporting message.

Datatype: Max35Text on page 63

1.4.2.3 Account <Acct>

Presence: [0..1]

Definition: Unambiguous identification of the account to which the reporting request refers.

Account <Acct> contains the following elements (see [CashAccount38](#) on page 14 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		14
		Type <Tp>	[0..1]	±		14
		Currency <Ccy>	[0..1]	CodeSet		14
		Name <Nm>	[0..1]	Text		15
		Proxy <Prxy>	[0..1]	±		15

1.4.2.4 AccountOwner <AcctOwnr>

Presence: [1..1]

Definition: Party that legally owns the account.

AccountOwner <AcctOwnr> contains one of the following elements (see [Party40Choice](#) on page 32 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Party <Pty>	[1..1]	±		32
	Or}	Agent <Agt>	[1..1]	±		33

1.4.2.5 AccountServicer <AcctSvcr>

Presence: [0..1]

Definition: Party that manages the account on behalf of the account owner, that is manages the registration and booking of entries on the account, calculates balances on the account and provides information about the account.

AccountServicer <AcctSvcr> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 25 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		25
		BranchIdentification <BrnchId>	[0..1]	±		26

1.4.2.6 ReportingPeriod <RptgPrd>

Presence: [0..1]

Definition: Specifies the requested reporting period.

ReportingPeriod <RptgPrd> contains the following **ReportingPeriod2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FromDate <FrToDt>	[1..1]	±		9
		FromTime <FrToTm>	[0..1]	±		9
		Type <Tp>	[1..1]	CodeSet		9

1.4.2.6.1 FromToDate <FrToDt>

Presence: [1..1]

Definition: Specifies a date range.

FromDate <FrToDt> contains the following elements (see [DatePeriodDetails1](#) on page 20 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FromDate <FrDt>	[1..1]	Date		20
		ToDate <ToDt>	[0..1]	Date		20

1.4.2.6.2 FromToTime <FrToTm>

Presence: [0..1]

Definition: Specifies a time range.

FromTime <FrToTm> contains the following elements (see [TimePeriodDetails1](#) on page 20 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FromTime <FrTm>	[1..1]	Time		20
		ToTime <ToTm>	[0..1]	Time		21

1.4.2.6.3 Type <Tp>

Presence: [1..1]

Definition: Specifies whether all matching items need to be reported or only those items that are new or have changed since the last similar request was made.

Datatype: [QueryType3Code](#) on page 59

CodeName	Name	Definition
ALLL	All	Specifies that the query requests that all matching items be returned.
CHNG	Changed	Specifies that the query requests that only new matching items since the last similar query be returned.
MODF	Modified	Specifies that the query requests that only items that have changed since the last query be returned.

1.4.2.7 ReportingSequence <RptgSeq>

Presence: [0..1]

Definition: Specifies the range of identification sequence numbers which are being requested.

ReportingSequence <RptgSeq> contains one of the following elements (see [SequenceRange1Choice](#) on page 28 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	FromSequence <FrSeq>	[1..1]	Text		29
	Or	ToSequence <ToSeq>	[1..1]	Text		29
	Or	FromToSequence <FrToSeq>	[1..*]			29
		FromSequence <FrSeq>	[1..1]	Text		29
		ToSequence <ToSeq>	[1..1]	Text		29
	Or	EqualSequence <EQSeq>	[1..*]	Text		30
	Or}	NotEqualSequence <NEQSeq>	[1..*]	Text		30

1.4.2.8 RequestedTransactionType <ReqdTxDp>

Presence: [0..1]

Definition: Identifies the transactions to be reported.

RequestedTransactionType <ReqdTxDp> contains the following **TransactionType2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Status <Sts>	[1..1]	±		10
		CreditDebitIndicator <CdtDbtInd>	[1..1]	CodeSet		11
		FloorLimit <FlrLmt>	[0..*]			11
		Amount <Amt>	[1..1]	Amount	✓C1, ✓C5	11
		CreditDebitIndicator <CdtDbtInd>	[1..1]	CodeSet		12

1.4.2.8.1 Status <Sts>

Presence: [1..1]

Definition: Specifies the status on the books of the account servicer of the transactions to be reported.

Status <Sts> contains one of the following elements (see [EntryStatus1Choice](#) on page 45 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		45
	Or}	Proprietary <Prtry>	[1..1]	Text		46

1.4.2.8.2 CreditDebitIndicator <CdtDbtInd>

Presence: [1..1]

Definition: Indicates whether the reporting request refers to credit or debit entries.

Datatype: CreditDebitCode on page 49

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

1.4.2.8.3 FloorLimit <FlrLmt>

Presence: [0..*]

Definition: Specifies the minimum value of entries to be reported in the requested message.

FloorLimit <FlrLmt> contains the following **Limit2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Amount	✓C1, ✓C5	11
		CreditDebitIndicator <CdtDbtInd>	[1..1]	CodeSet		12

1.4.2.8.3.1 Amount <Amt>

Presence: [1..1]

Definition: Minimum transaction amount to be reported in the requested message.

Impacted by: ✓C1 ActiveOrHistoricCurrency ✓, ✓C5 CurrencyAmount ✓

Datatype: ActiveOrHistoricCurrencyAndAmount on page 46

Constraints

- **ActiveOrHistoricCurrency**

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

- **CurrencyAmount**

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

1.4.2.8.3.2 CreditDebitIndicator <CdtDbtInd>*Presence:* [1..1]*Definition:* Indicates whether the floor limit applies to credit, to debit or to both credit and debit entries.*Datatype:* [FloorLimitType1Code](#) on page 56

CodeName	Name	Definition
CRED	Credit	Floor limit applies to credit entries.
DEBT	Debit	Floor limit applies to debit entries.
BOTH	Both	Floor limit applies to both credit and debit entries.

1.4.2.9 RequestedBalanceType <ReqdBalTp>*Presence:* [0..*]*Definition:* Provides details on the requested balance reporting.**RequestedBalanceType <ReqdBalTp>** contains the following elements (see [BalanceType13](#) on page 18 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CodeOrProprietary <CdOrPrtry>	[1..1]			19
	{Or	Code <Cd>	[1..1]	CodeSet		19
	Or}	Proprietary <Prtry>	[1..1]	Text		19
		SubType <SubTp>	[0..1]			19
	{Or	Code <Cd>	[1..1]	CodeSet		19
	Or}	Proprietary <Prtry>	[1..1]	Text		20

1.4.3 SupplementaryData <SplmtryData>*Presence:* [0..*]*Definition:* Additional information that cannot be captured in the structured elements and/or any other specific block.*Impacted by:* [C7 SupplementaryDataRule](#)

SupplementaryData <SplmtryData> contains the following elements (see [SupplementaryData1](#) on page 30 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PlaceAndName <PlcAndNm>	[0..1]	Text		30
		Envelope <Envlp>	[1..1]	(External Schema)		30

Constraints

- **SupplementaryDataRule**

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

2 Message Items Types

2.1 MessageComponents

2.1.1 Account

2.1.1.1 CashAccount38

Definition: Provides the details to identify an account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		14
		Type <Tp>	[0..1]	±		14
		Currency <Ccy>	[0..1]	CodeSet		14
		Name <Nm>	[0..1]	Text		15
		Proxy <Prxy>	[0..1]	±		15

2.1.1.1.1 Identification <Id>

Presence: [1..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

Identification <Id> contains one of the following elements (see [AccountIdentification4Choice](#) on page 18 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	IBAN <IBAN>	[1..1]	IdentifierSet		18
	Or}	Other <Othr>	[1..1]	±		18

2.1.1.1.2 Type <Tp>

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

Type <Tp> contains one of the following elements (see [CashAccountType2Choice](#) on page 16 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		16
	Or}	Proprietary <Prtry>	[1..1]	Text		16

2.1.1.1.3 Currency <Ccy>

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: [ActiveOrHistoricCurrencyCode](#) on page 47

2.1.1.1.4 Name <Nm>

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: [Max70Text](#) on page 64

2.1.1.1.5 Proxy <Prxy>

Presence: [0..1]

Definition: Specifies an alternate assumed name for the identification of the account.

Proxy <Prxy> contains the following elements (see [ProxyAccountIdentification1](#) on page 15 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			15
	{Or	Code <Cd>	[1..1]	CodeSet		16
	Or}	Proprietary <Prtry>	[1..1]	Text		16
		Identification <Id>	[1..1]	Text		16

2.1.1.2 ProxyAccountIdentification1

Definition: Information related to a proxy identification of the account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			15
	{Or	Code <Cd>	[1..1]	CodeSet		16
	Or}	Proprietary <Prtry>	[1..1]	Text		16
		Identification <Id>	[1..1]	Text		16

2.1.1.2.1 Type <Tp>

Presence: [0..1]

Definition: Type of the proxy identification.

Type <Tp> contains one of the following **ProxyAccountType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		16
	Or}	Proprietary <Prtry>	[1..1]	Text		16

2.1.1.2.1.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: [ExternalProxyAccountType1Code on page 56](#)

2.1.1.2.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: [Max35Text on page 63](#)

2.1.1.2.2 Identification <Id>

Presence: [1..1]

Definition: Identification used to indicate the account identification under another specified name.

Datatype: [Max2048Text on page 63](#)

2.1.1.3 CashAccountType2Choice

Definition: Nature or use of the account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		16
	Or}	Proprietary <Prtry>	[1..1]	Text		16

2.1.1.3.1 Code <Cd>

Presence: [1..1]

Definition: Account type, in a coded form.

Datatype: [ExternalCashAccountType1Code on page 51](#)

2.1.1.3.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Nature or use of the account in a proprietary form.

Datatype: [Max35Text on page 63](#)

2.1.1.4 GenericAccountIdentification1

Definition: Information related to a generic account identification.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		17
		SchemeName <SchmeNm>	[0..1]			17
	{Or	Code <Cd>	[1..1]	CodeSet		17
	Or}	Proprietary <Prtry>	[1..1]	Text		17
		Issuer <Issr>	[0..1]	Text		17

2.1.1.4.1 Identification <Id>

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: [Max34Text on page 63](#)

2.1.1.4.2 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Name of the identification scheme.

SchemeName <SchmeNm> contains one of the following **AccountSchemeName1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		17
	Or}	Proprietary <Prtry>	[1..1]	Text		17

2.1.1.4.2.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: [ExternalAccountIdentification1Code on page 50](#)

2.1.1.4.2.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: [Max35Text on page 63](#)

2.1.1.4.3 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: [Max35Text on page 63](#)

2.1.2 Account Identification

2.1.2.1 AccountIdentification4Choice

Definition: Specifies the unique identification of an account as assigned by the account servicer.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	IBAN <IBAN>	[1..1]	IdentifierSet		18
	Or}	Other <Othr>	[1..1]	±		18

2.1.2.1.1 IBAN <IBAN>

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: [IBAN2007Identifier on page 61](#)

2.1.2.1.2 Other <Othr>

Presence: [1..1]

Definition: Unique identification of an account, as assigned by the account servicer, using an identification scheme.

Other <Othr> contains the following elements (see [GenericAccountIdentification1 on page 16](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		17
		SchemeName <SchmeNm>	[0..1]			17
	{Or	Code <Cd>	[1..1]	CodeSet		17
	Or}	Proprietary <Prtry>	[1..1]	Text		17
		Issuer <Issr>	[0..1]	Text		17

2.1.3 Balance

2.1.3.1 BalanceType13

Definition: Set of elements used to define the balance type and sub-type.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CodeOrProprietary <CdOrPrtry>	[1..1]			19
	{Or	Code <Cd>	[1..1]	CodeSet		19
	Or}	Proprietary <Prtry>	[1..1]	Text		19
		SubType <SubTp>	[0..1]			19
	{Or	Code <Cd>	[1..1]	CodeSet		19
	Or}	Proprietary <Prtry>	[1..1]	Text		20

2.1.3.1.1 CodeOrProprietary <CdOrPrtry>

Presence: [1..1]

Definition: Coded or proprietary format balance type.

CodeOrProprietary <CdOrPrtry> contains one of the following **BalanceType10Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		19
	Or}	Proprietary <Prtry>	[1..1]	Text		19

2.1.3.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Balance type, in a coded format.

Datatype: [ExternalBalanceType1Code on page 51](#)

2.1.3.1.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Balance type, in a proprietary format.

Datatype: [Max35Text on page 63](#)

2.1.3.1.2 SubType <SubTp>

Presence: [0..1]

Definition: Specifies the balance sub-type.

SubType <SubTp> contains one of the following **BalanceSubType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		19
	Or}	Proprietary <Prtry>	[1..1]	Text		20

2.1.3.1.2.1 Code <Cd>

Presence: [1..1]

Definition: Balance sub-type, as published in an external balance sub-type code list.

Datatype: [ExternalBalanceSubType1Code on page 50](#)

2.1.3.1.2.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies a proprietary code for the balance type.

Datatype: [Max35Text on page 63](#)

2.1.4 Date Period

2.1.4.1 DatePeriodDetails1

Definition: Range of time defined by a start date and an end date.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FromDate <FrDt>	[1..1]	Date		20
		ToDate <ToDt>	[0..1]	Date		20

2.1.4.1.1 FromDate <FrDt>

Presence: [1..1]

Definition: Start date of the range.

Datatype: [ISODate on page 59](#)

2.1.4.1.2 ToDate <ToDt>

Presence: [0..1]

Definition: End date of the range.

Datatype: [ISODate on page 59](#)

2.1.5 Date Time Period

2.1.5.1 TimePeriodDetails1

Definition: Particular time span specified between a start time and an end time. The time period cannot exceed 24 hours.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FromTime <FrTm>	[1..1]	Time		20
		ToTime <ToTm>	[0..1]	Time		21

2.1.5.1.1 FromTime <FrTm>

Presence: [1..1]

Definition: Time at which the time span starts.

Datatype: [ISOTime on page 64](#)

2.1.5.1.2 ToTime <ToTm>

Presence: [0..1]

Definition: Time at which the time span ends.

Datatype: [ISOTime on page 64](#)

2.1.6 Financial Institution Identification

2.1.6.1 FinancialInstitutionIdentification18

Definition: Specifies the details to identify a financial institution.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		BICFI <BICFI>	[0..1]	IdentifierSet		21
		ClearingSystemMemberIdentification <ClrSysMmbld>	[0..1]	±		21
		LEI <LEI>	[0..1]	IdentifierSet		21
		Name <Nm>	[0..1]	Text		22
		PostalAddress <PstlAdr>	[0..1]	±		22
		Other <Othr>	[0..1]	±		22

2.1.6.1.1 BICFI <BICFI>

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: [BICFIDec2014Identifier on page 61](#)

2.1.6.1.2 ClearingSystemMemberIdentification <ClrSysMmbld>

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

ClearingSystemMemberIdentification <ClrSysMmbld> contains the following elements (see [ClearingSystemMemberIdentification2 on page 26](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ClearingSystemIdentification <ClrSysId>	[0..1]	±		26
		MemberIdentification <Mmbld>	[1..1]	Text		27

2.1.6.1.3 LEI <LEI>

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: [LEIIdentifier on page 62](#)

2.1.6.1.4 Name <Nm>*Presence:* [0..1]*Definition:* Name by which an agent is known and which is usually used to identify that agent.*Datatype:* [Max140Text](#) on page 62**2.1.6.1.5 PostalAddress <PstlAdr>***Presence:* [0..1]*Definition:* Information that locates and identifies a specific address, as defined by postal services.**PostalAddress <PstlAdr>** contains the following elements (see [PostalAddress24](#) on page 42 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AddressType <AdrTp>	[0..1]			42
	{Or	Code <Cd>	[1..1]	CodeSet		43
	Or}	Proprietary <Prtry>	[1..1]	±		43
		Department <Dept>	[0..1]	Text		43
		SubDepartment <SubDept>	[0..1]	Text		43
		StreetName <StrtNm>	[0..1]	Text		44
		BuildingNumber <BldgNb>	[0..1]	Text		44
		BuildingName <BldgNm>	[0..1]	Text		44
		Floor <Flr>	[0..1]	Text		44
		PostBox <PstBx>	[0..1]	Text		44
		Room <Room>	[0..1]	Text		44
		PostCode <PstCd>	[0..1]	Text		44
		TownName <TwnNm>	[0..1]	Text		44
		TownLocationName <TwnLctnNm>	[0..1]	Text		45
		DistrictName <DstrctNm>	[0..1]	Text		45
		CountrySubDivision <CtrySubDvsn>	[0..1]	Text		45
		Country <Ctry>	[0..1]	CodeSet		45
		AddressLine <AdrLine>	[0..7]	Text		45

2.1.6.1.6 Other <Othr>*Presence:* [0..1]*Definition:* Unique identification of an agent, as assigned by an institution, using an identification scheme.

Other <Othr> contains the following elements (see [GenericFinancialIdentification1](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		24
		SchemeName <SchmeNm>	[0..1]			25
	{Or	Code <Cd>	[1..1]	CodeSet		25
	Or}	Proprietary <Prtry>	[1..1]	Text		25
		Issuer <Issr>	[0..1]	Text		25

2.1.6.2 BranchData3

Definition: Information that locates and identifies a specific branch of a financial institution.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[0..1]	Text		23
		LEI <LEI>	[0..1]	IdentifierSet		23
		Name <Nm>	[0..1]	Text		23
		PostalAddress <PstlAdr>	[0..1]	±		23

2.1.6.2.1 Identification <Id>

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: [Max35Text](#) on page 63

2.1.6.2.2 LEI <LEI>

Presence: [0..1]

Definition: Legal entity identification for the branch of the financial institution.

Datatype: [LEIIdentifier](#) on page 62

2.1.6.2.3 Name <Nm>

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: [Max140Text](#) on page 62

2.1.6.2.4 PostalAddress <PstlAdr>

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

PostalAddress <PstlAdr> contains the following elements (see [PostalAddress24](#) on page 42 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AddressType <AdrTp>	[0..1]			42
	{Or	Code <Cd>	[1..1]	CodeSet		43
	Or}	Proprietary <Prtry>	[1..1]	±		43
		Department <Dept>	[0..1]	Text		43
		SubDepartment <SubDept>	[0..1]	Text		43
		StreetName <StrtNm>	[0..1]	Text		44
		BuildingNumber <BldgNb>	[0..1]	Text		44
		BuildingName <BldgNm>	[0..1]	Text		44
		Floor <Flr>	[0..1]	Text		44
		PostBox <PstBx>	[0..1]	Text		44
		Room <Room>	[0..1]	Text		44
		PostCode <PstCd>	[0..1]	Text		44
		TownName <TwnNm>	[0..1]	Text		44
		TownLocationName <TwnLctnNm>	[0..1]	Text		45
		DistrictName <DstrctNm>	[0..1]	Text		45
		CountrySubDivision <CtrySubDvsn>	[0..1]	Text		45
		Country <Ctry>	[0..1]	CodeSet		45
		AddressLine <AdrLine>	[0..7]	Text		45

2.1.6.3 GenericFinancialIdentification1

Definition: Information related to an identification of a financial institution.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		24
		SchemeName <SchmeNm>	[0..1]			25
	{Or	Code <Cd>	[1..1]	CodeSet		25
	Or}	Proprietary <Prtry>	[1..1]	Text		25
		Issuer <Issr>	[0..1]	Text		25

2.1.6.3.1 Identification <Id>

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: [Max35Text on page 63](#)

2.1.6.3.2 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Name of the identification scheme.

SchemeName <SchmeNm> contains one of the following **FinancialIdentificationSchemeName1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		25
	Or}	Proprietary <Prtry>	[1..1]	Text		25

2.1.6.3.2.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: [ExternalFinancialInstitutionIdentification1Code on page 53](#)

2.1.6.3.2.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: [Max35Text on page 63](#)

2.1.6.3.3 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: [Max35Text on page 63](#)

2.1.6.4 BranchAndFinancialInstitutionIdentification6

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		25
		BranchIdentification <BrnchId>	[0..1]	±		26

2.1.6.4.1 FinancialInstitutionIdentification <FinInstnId>

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

FinancialInstitutionIdentification <FinInstnId> contains the following elements (see [FinancialInstitutionIdentification18](#) on page 21 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		BICFI <BICFI>	[0..1]	IdentifierSet		21
		ClearingSystemMemberIdentification <ClrSysMmbld>	[0..1]	±		21
		LEI <LEI>	[0..1]	IdentifierSet		21
		Name <Nm>	[0..1]	Text		22
		PostalAddress <PstlAdr>	[0..1]	±		22
		Other <Othr>	[0..1]	±		22

2.1.6.4.2 BranchIdentification <BrnchId>

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

BranchIdentification <BrnchId> contains the following elements (see [BranchData3](#) on page 23 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[0..1]	Text		23
		LEI <LEI>	[0..1]	IdentifierSet		23
		Name <Nm>	[0..1]	Text		23
		PostalAddress <PstlAdr>	[0..1]	±		23

2.1.6.5 ClearingSystemMemberIdentification2

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ClearingSystemIdentification <ClrSysId>	[0..1]	±		26
		MemberIdentification <Mmbld>	[1..1]	Text		27

2.1.6.5.1 ClearingSystemIdentification <ClrSysId>

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

ClearingSystemIdentification <ClrSysId> contains one of the following elements (see [ClearingSystemIdentification2Choice](#) on page 46 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		46
	Or}	Proprietary <Prtry>	[1..1]	Text		46

2.1.6.5.2 MemberIdentification <Mmbld>

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: [Max35Text](#) on page 63

2.1.7 Identification Information

2.1.7.1 GenericIdentification30

Definition: Information related to an identification, for example, party identification or account identification.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		27
		Issuer <Issr>	[1..1]	Text		27
		SchemeName <SchmeNm>	[0..1]	Text		27

2.1.7.1.1 Identification <Id>

Presence: [1..1]

Definition: Proprietary information, often a code, issued by the data source scheme issuer.

Datatype: [Exact4AlphaNumericText](#) on page 62

2.1.7.1.2 Issuer <Issr>

Presence: [1..1]

Definition: Entity that assigns the identification.

Datatype: [Max35Text](#) on page 63

2.1.7.1.3 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Short textual description of the scheme.

Datatype: [Max35Text](#) on page 63

2.1.8 Miscellaneous

2.1.8.1 GroupHeader77

Definition: Provides further details on the message.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		MessageIdentification <MsgId>	[1..1]	Text		28
		CreationDateTime <CreDtTm>	[1..1]	DateTime		28
		MessageSender <MsgSndr>	[0..1]	±		28

2.1.8.1.1 MessageIdentification <MsgId>

Presence: [1..1]

Definition: Point to point reference, as assigned by the account owner or the party authorised to send the message, and sent to the account servicing institution, to unambiguously identify the message.

Usage: The sender has to make sure that 'MessageIdentification' is unique per account servicing institution for a pre-agreed period.

Datatype: [Max35Text on page 63](#)

2.1.8.1.2 CreationDateTime <CreDtTm>

Presence: [1..1]

Definition: Date and time at which the message was created.

Datatype: [ISODatetime on page 60](#)

2.1.8.1.3 MessageSender <MsgSndr>

Presence: [0..1]

Definition: Identification of the party that is sending the message, when different from the account owner.

MessageSender <MsgSndr> contains one of the following elements (see [Party40Choice on page 32](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Party <Pty>	[1..1]	±		32
	Or}	Agent <Agt>	[1..1]	±		33

2.1.8.2 SequenceRange1Choice

Definition: Specifies a choice of sequences.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	FromSequence <FrSeq>	[1..1]	Text		29
	Or	ToSequence <ToSeq>	[1..1]	Text		29
	Or	FromToSequence <FrToSeq>	[1..*]			29
		FromSequence <FrSeq>	[1..1]	Text		29
		ToSequence <ToSeq>	[1..1]	Text		29
	Or	EqualSequence <EQSeq>	[1..*]	Text		30
	Or}	NotEqualSequence <NEQSeq>	[1..*]	Text		30

2.1.8.2.1 FromSequence <FrSeq>

Presence: [1..1]

Definition: Start sequence of the range.

Datatype: [Max35Text](#) on page 63

2.1.8.2.2 ToSequence <ToSeq>

Presence: [1..1]

Definition: End sequence of the range.

Datatype: [Max35Text](#) on page 63

2.1.8.2.3 FromToSequence <FrToSeq>

Presence: [1..*]

Definition: Particular sequence range specified between a start sequence and an end sequence.

FromToSequence <FrToSeq> contains the following **SequenceRange1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FromSequence <FrSeq>	[1..1]	Text		29
		ToSequence <ToSeq>	[1..1]	Text		29

2.1.8.2.3.1 FromSequence <FrSeq>

Presence: [1..1]

Definition: Start sequence of the range.

Datatype: [Max35Text](#) on page 63

2.1.8.2.3.2 ToSequence <ToSeq>

Presence: [1..1]

Definition: End sequence of the range.

Datatype: [Max35Text](#) on page 63

2.1.8.2.4 EqualSequence <EQSeq>

Presence: [1..*]

Definition: Specified sequence to match.

Datatype: Max35Text on page 63

2.1.8.2.5 NotEqualSequence <NEQSeq>

Presence: [1..*]

Definition: Specified sequence to be excluded.

Datatype: Max35Text on page 63

2.1.8.3 SupplementaryData1

Definition: Additional information that can not be captured in the structured fields and/or any other specific block.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PlaceAndName <PlcAndNm>	[0..1]	Text		30
		Envelope <Envlp>	[1..1]	(External Schema)		30

Constraints

- **SupplementaryDataRule**

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

2.1.8.3.1 PlaceAndName <PlcAndNm>

Presence: [0..1]

Definition: Unambiguous reference to the location where the supplementary data must be inserted in the message instance.

In the case of XML, this is expressed by a valid XPath.

Datatype: Max350Text on page 63

2.1.8.3.2 Envelope <Envlp>

Presence: [1..1]

Definition: Technical element wrapping the supplementary data.

Type: (External Schema)

Technical component that contains the validated supplementary data information. This technical envelope allows to segregate the supplementary data information from any other information.

2.1.9 Organisation Identification

2.1.9.1 OrganisationIdentification29

Definition: Unique and unambiguous way to identify an organisation.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AnyBIC <AnyBIC>	[0..1]	IdentifierSet		31
		LEI <LEI>	[0..1]	IdentifierSet		31
		Other <Othr>	[0..*]			31
		Identification <Id>	[1..1]	Text		31
		SchemeName <SchmeNm>	[0..1]			32
	{Or	Code <Cd>	[1..1]	CodeSet		32
	Or}	Proprietary <Prtry>	[1..1]	Text		32
		Issuer <Issr>	[0..1]	Text		32

2.1.9.1.1 AnyBIC <AnyBIC>

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: AnyBICDec2014Identifier on page 60

2.1.9.1.2 LEI <LEI>

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: LEIIdentifier on page 62

2.1.9.1.3 Other <Othr>

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

Other <Othr> contains the following **GenericOrganisationIdentification1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		31
		SchemeName <SchmeNm>	[0..1]			32
	{Or	Code <Cd>	[1..1]	CodeSet		32
	Or}	Proprietary <Prtry>	[1..1]	Text		32
		Issuer <Issr>	[0..1]	Text		32

2.1.9.1.3.1 Identification <Id>

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: Max35Text on page 63

2.1.9.1.3.2 SchemeName <SchmeNm>*Presence:* [0..1]*Definition:* Name of the identification scheme.

SchemeName <SchmeNm> contains one of the following **OrganisationIdentificationSchemeName1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		32
	Or}	Proprietary <Prtry>	[1..1]	Text		32

2.1.9.1.3.2.1 Code <Cd>*Presence:* [1..1]*Definition:* Name of the identification scheme, in a coded form as published in an external list.*Datatype:* [ExternalOrganisationIdentification1Code on page 54](#)**2.1.9.1.3.2.2 Proprietary <Prtry>***Presence:* [1..1]*Definition:* Name of the identification scheme, in a free text form.*Datatype:* [Max35Text on page 63](#)**2.1.9.1.3.3 Issuer <Issr>***Presence:* [0..1]*Definition:* Entity that assigns the identification.*Datatype:* [Max35Text on page 63](#)**2.1.10 Party Identification****2.1.10.1 Party40Choice***Definition:* Identification of a person, an organisation or a financial institution.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Party <Pty>	[1..1]	±		32
	Or}	Agent <Agt>	[1..1]	±		33

2.1.10.1.1 Party <Pty>*Presence:* [1..1]*Definition:* Identification of a person or an organisation.

Party <Pty> contains the following elements (see [PartyIdentification135](#) on page 33 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		33
		PostalAddress <PstlAdr>	[0..1]	±		33
		Identification <Id>	[0..1]	±		34
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		34
		ContactDetails <CtctDtls>	[0..1]	±		35

2.1.10.1.2 Agent <Agt>

Presence: [1..1]

Definition: Identification of a financial institution.

Agent <Agt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 25 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		25
		BranchIdentification <BrnchId>	[0..1]	±		26

2.1.10.2 PartyIdentification135

Definition: Specifies the identification of a person or an organisation.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		33
		PostalAddress <PstlAdr>	[0..1]	±		33
		Identification <Id>	[0..1]	±		34
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		34
		ContactDetails <CtctDtls>	[0..1]	±		35

2.1.10.2.1 Name <Nm>

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: [Max140Text](#) on page 62

2.1.10.2.2 PostalAddress <PstlAdr>

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

PostalAddress <PstlAdr> contains the following elements (see [PostalAddress24](#) on page 42 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AddressType <AdrTp>	[0..1]			42
	{Or	Code <Cd>	[1..1]	CodeSet		43
	Or}	Proprietary <Prtry>	[1..1]	±		43
		Department <Dept>	[0..1]	Text		43
		SubDepartment <SubDept>	[0..1]	Text		43
		StreetName <StrtNm>	[0..1]	Text		44
		BuildingNumber <BldgNb>	[0..1]	Text		44
		BuildingName <BldgNm>	[0..1]	Text		44
		Floor <Flr>	[0..1]	Text		44
		PostBox <PstBx>	[0..1]	Text		44
		Room <Room>	[0..1]	Text		44
		PostCode <PstCd>	[0..1]	Text		44
		TownName <TwnNm>	[0..1]	Text		44
		TownLocationName <TwnLctnNm>	[0..1]	Text		45
		DistrictName <DstrctNm>	[0..1]	Text		45
		CountrySubDivision <CtrySubDvsn>	[0..1]	Text		45
		Country <Ctry>	[0..1]	CodeSet		45
		AddressLine <AdrLine>	[0..7]	Text		45

2.1.10.2.3 Identification <Id>

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

Identification <Id> contains one of the following elements (see [Party38Choice](#) on page 35 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	OrganisationIdentification <OrgId>	[1..1]	±		35
	Or}	PrivateIdentification <PrvtId>	[1..1]	±		36

2.1.10.2.4 CountryOfResidence <CtryOfRes>

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: [CountryCode](#) on page 49

2.1.10.2.5 ContactDetails <CtctDtls>

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

ContactDetails <CtctDtls> contains the following elements (see [Contact4](#) on page 39 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		NamePrefix <NmPrfx>	[0..1]	CodeSet		39
		Name <Nm>	[0..1]	Text		40
		PhoneNumber <PhneNb>	[0..1]	Text		40
		MobileNumber <MobNb>	[0..1]	Text		40
		FaxNumber <FaxNb>	[0..1]	Text		40
		EmailAddress <EmailAdr>	[0..1]	Text		40
		EmailPurpose <EmailPurp>	[0..1]	Text		40
		JobTitle <JobTitl>	[0..1]	Text		40
		Responsibility <Rspnsblty>	[0..1]	Text		41
		Department <Dept>	[0..1]	Text		41
		Other <Othr>	[0..*]			41
		ChannelType <ChanlTp>	[1..1]	Text		41
		Identification <Id>	[0..1]	Text		41
		PreferredMethod <PrefrdMtd>	[0..1]	CodeSet		41

2.1.10.3 Party38Choice

Definition: Nature or use of the account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	OrganisationIdentification <Orgld>	[1..1]	±		35
	Or}	PrivateIdentification <Prvtld>	[1..1]	±		36

2.1.10.3.1 OrganisationIdentification <Orgld>

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

OrganisationIdentification <OrgId> contains the following elements (see [OrganisationIdentification29](#) on page 30 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AnyBIC <AnyBIC>	[0..1]	IdentifierSet		31
		LEI <LEI>	[0..1]	IdentifierSet		31
		Other <Othr>	[0..*]			31
		Identification <Id>	[1..1]	Text		31
		SchemeName <SchmeNm>	[0..1]			32
	{Or	Code <Cd>	[1..1]	CodeSet		32
	Or}	Proprietary <Prtry>	[1..1]	Text		32
		Issuer <Issr>	[0..1]	Text		32

2.1.10.3.2 PrivateIdentification <PrvtId>

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

PrivateIdentification <PrvtId> contains the following elements (see [PersonIdentification13](#) on page 36 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DateAndPlaceOfBirth <DtAndPlcOfBirth>	[0..1]			37
		BirthDate <BirthDt>	[1..1]	Date		37
		ProvinceOfBirth <PrvcOfBirth>	[0..1]	Text		37
		CityOfBirth <CityOfBirth>	[1..1]	Text		37
		CountryOfBirth <CtryOfBirth>	[1..1]	CodeSet		38
		Other <Othr>	[0..*]			38
		Identification <Id>	[1..1]	Text		38
		SchemeName <SchmeNm>	[0..1]			38
	{Or	Code <Cd>	[1..1]	CodeSet		38
	Or}	Proprietary <Prtry>	[1..1]	Text		39
		Issuer <Issr>	[0..1]	Text		39

2.1.11 Person Identification

2.1.11.1 PersonIdentification13

Definition: Unique and unambiguous way to identify a person.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DateAndPlaceOfBirth <DtAndPlcOfBirth>	[0..1]			37
		BirthDate <BirthDt>	[1..1]	Date		37
		ProvinceOfBirth <PrvcOfBirth>	[0..1]	Text		37
		CityOfBirth <CityOfBirth>	[1..1]	Text		37
		CountryOfBirth <CtryOfBirth>	[1..1]	CodeSet		38
		Other <Othr>	[0..*]			38
		Identification <Id>	[1..1]	Text		38
		SchemeName <SchmeNm>	[0..1]			38
	{Or	Code <Cd>	[1..1]	CodeSet		38
	Or}	Proprietary <Prtry>	[1..1]	Text		39
		Issuer <Issr>	[0..1]	Text		39

2.1.11.1.1 DateAndPlaceOfBirth <DtAndPlcOfBirth>

Presence: [0..1]

Definition: Date and place of birth of a person.

DateAndPlaceOfBirth <DtAndPlcOfBirth> contains the following **DateAndPlaceOfBirth1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		BirthDate <BirthDt>	[1..1]	Date		37
		ProvinceOfBirth <PrvcOfBirth>	[0..1]	Text		37
		CityOfBirth <CityOfBirth>	[1..1]	Text		37
		CountryOfBirth <CtryOfBirth>	[1..1]	CodeSet		38

2.1.11.1.1.1 BirthDate <BirthDt>

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: [ISODate](#) on page 59

2.1.11.1.1.2 ProvinceOfBirth <PrvcOfBirth>

Presence: [0..1]

Definition: Province where a person was born.

Datatype: [Max35Text](#) on page 63

2.1.11.1.1.3 CityOfBirth <CityOfBirth>

Presence: [1..1]

Definition: City where a person was born.

Datatype: [Max35Text on page 63](#)

2.1.11.1.1.4 CountryOfBirth <CtryOfBirth>

Presence: [1..1]

Definition: Country where a person was born.

Datatype: [CountryCode on page 49](#)

2.1.11.1.2 Other <Othr>

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

Other <Othr> contains the following **GenericPersonIdentification1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		38
		SchemeName <SchmeNm>	[0..1]			38
	{Or	Code <Cd>	[1..1]	CodeSet		38
	Or}	Proprietary <Prtry>	[1..1]	Text		39
		Issuer <Issr>	[0..1]	Text		39

2.1.11.1.2.1 Identification <Id>

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: [Max35Text on page 63](#)

2.1.11.1.2.2 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Name of the identification scheme.

SchemeName <SchmeNm> contains one of the following **PersonIdentificationSchemeName1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		38
	Or}	Proprietary <Prtry>	[1..1]	Text		39

2.1.11.1.2.2.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: [ExternalPersonIdentification1Code on page 55](#)

2.1.11.1.2.2.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: [Max35Text on page 63](#)

2.1.11.1.2.3 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: [Max35Text on page 63](#)

2.1.11.2 Contact4

Definition: Specifies the details of the contact person.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		NamePrefix <NmPrfx>	[0..1]	CodeSet		39
		Name <Nm>	[0..1]	Text		40
		PhoneNumber <PhneNb>	[0..1]	Text		40
		MobileNumber <MobNb>	[0..1]	Text		40
		FaxNumber <FaxNb>	[0..1]	Text		40
		EmailAddress <EmailAdr>	[0..1]	Text		40
		EmailPurpose <EmailPurp>	[0..1]	Text		40
		JobTitle <JobTitl>	[0..1]	Text		40
		Responsibility <Rspnsblty>	[0..1]	Text		41
		Department <Dept>	[0..1]	Text		41
		Other <Othr>	[0..*]			41
		ChannelType <ChanlTp>	[1..1]	Text		41
		Identification <Id>	[0..1]	Text		41
		PreferredMethod <PrefrdMtd>	[0..1]	CodeSet		41

2.1.11.2.1 NamePrefix <NmPrfx>

Presence: [0..1]

Definition: Specifies the terms used to formally address a person.

Datatype: [NamePrefix2Code on page 57](#)

CodeName	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MISS	Miss	Title of the person is Miss.

CodeName	Name	Definition
MIST	Mister	Title of the person is Mister or Mr.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).

2.1.11.2.2 Name <Nm>

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: [Max140Text on page 62](#)

2.1.11.2.3 PhoneNumber <PhneNb>

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: [PhoneNumber on page 64](#)

2.1.11.2.4 MobileNumber <MobNb>

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: [PhoneNumber on page 64](#)

2.1.11.2.5 FaxNumber <FaxNb>

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: [PhoneNumber on page 64](#)

2.1.11.2.6 EmailAddress <EmailAdr>

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: [Max2048Text on page 63](#)

2.1.11.2.7 EmailPurpose <EmailPurp>

Presence: [0..1]

Definition: Purpose for which an email address may be used.

Datatype: [Max35Text on page 63](#)

2.1.11.2.8 JobTitle <JobTitl>

Presence: [0..1]

Definition: Title of the function.

Datatype: [Max35Text on page 63](#)

2.1.11.2.9 Responsibility <Rspnsblty>

Presence: [0..1]

Definition: Role of a person in an organisation.

Datatype: [Max35Text on page 63](#)

2.1.11.2.10 Department <Dept>

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: [Max70Text on page 64](#)

2.1.11.2.11 Other <Othr>

Presence: [0..*]

Definition: Contact details in another form.

Other <Othr> contains the following **OtherContact1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ChannelType <ChanITp>	[1..1]	Text		41
		Identification <Id>	[0..1]	Text		41

2.1.11.2.11.1 ChannelType <ChanITp>

Presence: [1..1]

Definition: Method used to contact the financial institution's contact for the specific tax region.

Datatype: [Max4Text on page 63](#)

2.1.11.2.11.2 Identification <Id>

Presence: [0..1]

Definition: Communication value such as phone number or email address.

Datatype: [Max128Text on page 62](#)

2.1.11.2.12 PreferredMethod <PrefrdMtd>

Presence: [0..1]

Definition: Preferred method used to reach the contact.

Datatype: [PreferredContactMethod1Code on page 58](#)

CodeName	Name	Definition
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.

CodeName	Name	Definition
FAXX	Fax	Preferred method used to reach the contact is per fax.
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.

2.1.12 Postal Address

2.1.12.1 PostalAddress24

Definition: Information that locates and identifies a specific address, as defined by postal services.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AddressType <AdrTp>	[0..1]			42
	{Or	Code <Cd>	[1..1]	CodeSet		43
	Or}	Proprietary <Prtry>	[1..1]	±		43
		Department <Dept>	[0..1]	Text		43
		SubDepartment <SubDept>	[0..1]	Text		43
		StreetName <StrtNm>	[0..1]	Text		44
		BuildingNumber <BldgNb>	[0..1]	Text		44
		BuildingName <BldgNm>	[0..1]	Text		44
		Floor <Flr>	[0..1]	Text		44
		PostBox <PstBx>	[0..1]	Text		44
		Room <Room>	[0..1]	Text		44
		PostCode <PstCd>	[0..1]	Text		44
		TownName <TwnNm>	[0..1]	Text		44
		TownLocationName <TwnLctnNm>	[0..1]	Text		45
		DistrictName <DstrctNm>	[0..1]	Text		45
		CountrySubDivision <CtrySubDvsn>	[0..1]	Text		45
		Country <Ctry>	[0..1]	CodeSet		45
		AddressLine <AdrLine>	[0..7]	Text		45

2.1.12.1.1 AddressType <AdrTp>

Presence: [0..1]

Definition: Identifies the nature of the postal address.

AddressType <AdrTp> contains one of the following **AddressType3Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		43
	Or}	Proprietary <Prtry>	[1..1]	±		43

2.1.12.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Type of address expressed as a code.

Datatype: [AddressType2Code](#) on page 48

CodeName	Name	Definition
ADDR	Postal	Address is the complete postal address.
PBOX	POBox	Address is a postal office (PO) box.
HOME	Residential	Address is the home address.
BIZZ	Business	Address is the business address.
MLTO	MailTo	Address is the address to which mail is sent.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.

2.1.12.1.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Type of address expressed as a proprietary code.

Proprietary <Prtry> contains the following elements (see [GenericIdentification30](#) on page 27 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		27
		Issuer <Issr>	[1..1]	Text		27
		SchemeName <SchmeNm>	[0..1]	Text		27

2.1.12.1.2 Department <Dept>

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: [Max70Text](#) on page 64

2.1.12.1.3 SubDepartment <SubDept>

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: [Max70Text](#) on page 64

2.1.12.1.4 StreetName <StrtNm>

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: [Max70Text on page 64](#)

2.1.12.1.5 BuildingNumber <BldgNb>

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: [Max16Text on page 62](#)

2.1.12.1.6 BuildingName <BldgNm>

Presence: [0..1]

Definition: Name of the building or house.

Datatype: [Max35Text on page 63](#)

2.1.12.1.7 Floor <Flr>

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: [Max70Text on page 64](#)

2.1.12.1.8 PostBox <PstBx>

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: [Max16Text on page 62](#)

2.1.12.1.9 Room <Room>

Presence: [0..1]

Definition: Building room number.

Datatype: [Max70Text on page 64](#)

2.1.12.1.10 PostCode <PstCd>

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: [Max16Text on page 62](#)

2.1.12.1.11 TownName <TwnNm>

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: [Max35Text on page 63](#)

2.1.12.1.12 TownLocationName <TwnLctnNm>

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: [Max35Text on page 63](#)

2.1.12.1.13 DistrictName <DstrctNm>

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: [Max35Text on page 63](#)

2.1.12.1.14 CountrySubDivision <CtrySubDvsn>

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: [Max35Text on page 63](#)

2.1.12.1.15 Country <Ctry>

Presence: [0..1]

Definition: Nation with its own government.

Datatype: [CountryCode on page 49](#)

2.1.12.1.16 AddressLine <AdrLine>

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: [Max70Text on page 64](#)

2.1.13 Status

2.1.13.1 EntryStatus1Choice

Definition: Specifies the status of an entry on the books of the account servicer.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		45
	Or}	Proprietary <Prtry>	[1..1]	Text		46

2.1.13.1.1 Code <Cd>

Presence: [1..1]

Definition: Entry status, in a coded form.

Datatype: [ExternalEntryStatus1Code on page 53](#)

2.1.13.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Entry status, in a proprietary form.

Datatype: [Max35Text on page 63](#)

2.1.14 System Identification

2.1.14.1 ClearingSystemIdentification2Choice

Definition: Choice of a clearing system identifier.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		46
	Or}	Proprietary <Prtry>	[1..1]	Text		46

2.1.14.1.1 Code <Cd>

Presence: [1..1]

Definition: Identification of a clearing system, in a coded form as published in an external list.

Datatype: [ExternalClearingSystemIdentification1Code on page 52](#)

2.1.14.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Identification code for a clearing system, that has not yet been identified in the list of clearing systems.

Datatype: [Max35Text on page 63](#)

2.2 Message Datatypes

2.2.1 Amount

2.2.1.1 ActiveOrHistoricCurrencyAndAmount

Definition: A number of monetary units specified in an active or a historic currency where the unit of currency is explicit and compliant with ISO 4217.

Type: Amount

This data type contains the following XML attribute:

Name	Attribute XML Name	Datatype
Currency	Ccy	ActiveOrHistoricCurrencyCode on page 47

Format

minInclusive 0

totalDigits	18
fractionDigits	5

Constraints

- **ActiveOrHistoricCurrency**

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

- **CurrencyAmount**

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

2.2.2 CodeSet

2.2.2.1 ActiveOrHistoricCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme, as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern	[A-Z]{3,3}
---------	------------

Constraints

- **ActiveOrHistoricCurrency**

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

Restricts

ParentCurrencyCode on page 57

2.2.2.2 AddressType2Code

Definition: Specifies the type of address.

Type: CodeSet

CodeName	Name	Definition
ADDR	Postal	Address is the complete postal address.
PBOX	POBox	Address is a postal office (PO) box.
HOME	Residential	Address is the home address.
BIZZ	Business	Address is the business address.
MLTO	MailTo	Address is the address to which mail is sent.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.

Restricts

AddressTypeCode on page 48

2.2.2.3 AddressTypeCode

Definition: Specifies the type of address.

Type: CodeSet

CodeName	Name	Definition
HOME	Residential	Address is the home address.
BIZZ	Business	Address is the business address.
ADDR	Postal	Address is the complete postal address.
PBOX	POBox	Address is a postal office (PO) box.
MLTO	MailTo	Address is the address to which mail is sent.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.

Is restricted by

AddressType2Code on page 48

2.2.2.4 AmountDirectionCode

Definition: Specifies if an operation is an increase or a decrease or the result of a reversal operation.

Type: CodeSet

CodeName	Name	Definition
DBIT	Debit	Operation is a decrease.
CRDT	Credit	Operation is an increase.
RVDB	ReversalDebit	Credit entry used to reverse a previously booked debit entry.
RVCD	ReversalCredit	Debit entry used to reverse a previously booked credit entry.

Is restricted by

CreditDebitCode on page 49

2.2.2.5 CountryCode

Definition: Code to identify a country, a dependency, or another area of particular geopolitical interest, on the basis of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Type: CodeSet

Format

pattern [A-Z]{2,2}

Constraints

- **Country**

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

2.2.2.6 CreditDebitCode

Definition: Specifies if an operation is an increase or a decrease.

Type: CodeSet

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

Restricts

AmountDirectionCode on page 49

2.2.2.7 ExternalAccountIdentification1Code

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalAccountIdentificationCode on page 50](#)

2.2.2.8 ExternalAccountIdentificationCode

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalAccountIdentification1Code on page 50](#)

2.2.2.9 ExternalBalanceSubType1Code

Definition: Specifies the balance sub-type, as published in an external balance sub-type code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalBalanceSubTypeCode on page 51](#)

2.2.2.10 ExternalBalanceSubTypeCode

Definition: Specifies the balance sub-type, as published in an external balance sub-type code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalBalanceSubType1Code on page 50](#)

2.2.2.11 ExternalBalanceType1Code

Definition: Specifies the balance type, as published in an external balance type code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalBalanceTypeCode on page 51](#)

2.2.2.12 ExternalBalanceTypeCode

Definition: Specifies the balance type, as published in an external balance type code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalBalanceType1Code on page 51](#)

2.2.2.13 ExternalCashAccountType1Code

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalCashAccountTypeCode](#) on page 52

2.2.2.14 ExternalCashAccountTypeCode

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalCashAccountType1Code](#) on page 51

2.2.2.15 ExternalClearingSystemIdentification1Code

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	5

Restricts

[ExternalClearingSystemIdentificationCode](#) on page 52

2.2.2.16 ExternalClearingSystemIdentificationCode

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	5

Is restricted by

ExternalClearingSystemIdentification1Code on page 52

2.2.2.17 ExternalEntryStatus1Code

Definition: Specifies the status of an entry on the books of the account servicer, as published in an external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

ExternalEntryStatusCode on page 53

2.2.2.18 ExternalEntryStatusCode

Definition: Specifies the status of an entry on the books of the account servicer, as published in an external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

ExternalEntryStatus1Code on page 53

2.2.2.19 ExternalFinancialInstitutionIdentification1Code

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

ExternalFinancialInstitutionIdentificationCode on page 54

2.2.2.20 ExternalFinancialInstitutionIdentificationCode

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

ExternalFinancialInstitutionIdentification1Code on page 53

2.2.2.21 ExternalOrganisationIdentification1Code

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

ExternalOrganisationIdentificationCode on page 54

2.2.2.22 ExternalOrganisationIdentificationCode

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalOrganisationIdentification1Code](#) on page 54

2.2.2.23 ExternalPersonIdentification1Code

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalPersonIdentificationCode](#) on page 55

2.2.2.24 ExternalPersonIdentificationCode

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalPersonIdentification1Code](#) on page 55

2.2.2.25 ExternalProxyAccountType1Code

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalProxyAccountTypeCode on page 56](#)

2.2.2.26 ExternalProxyAccountTypeCode

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalProxyAccountType1Code on page 56](#)

2.2.2.27 FloorLimitType1Code

Definition: Indicates whether the floor limit applies to credit, to debit or to both credit and debit entries.

Type: CodeSet

CodeName	Name	Definition
CRED	Credit	Floor limit applies to credit entries.
DEBT	Debit	Floor limit applies to debit entries.
BOTH	Both	Floor limit applies to both credit and debit entries.

Restricts

[FloorLimitTypeCode on page 56](#)

2.2.2.28 FloorLimitTypeCode

Definition: Indicates whether the floor limit applies to credit, to debit or to both credit and debit entries.

Type: CodeSet

CodeName	Name	Definition
CRED	Credit	Floor limit applies to credit entries.
DEBT	Debit	Floor limit applies to debit entries.
BOTH	Both	Floor limit applies to both credit and debit entries.

Is restricted by

FloorLimitType1Code on page 56

2.2.2.29 NamePrefix2Code

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

CodeName	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).

Restricts

NamePrefixCode on page 57

2.2.2.30 NamePrefixCode

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

CodeName	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MIST	Mister	Title of the person is Mister or Mr.
MISS	Miss	Title of the person is Miss.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).

Is restricted by

NamePrefix2Code on page 57

2.2.2.31 ParentCurrencyCode

Definition: Code allocated to a currency, by a maintenance agency, under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the

representation of currencies and funds". Valid currency codes are registered with the ISO 4217 Maintenance Agency, and consist of three contiguous letters.

Type: CodeSet

Format

pattern [A-Z]{3,3}

Is restricted by

ActiveOrHistoricCurrencyCode on page 47

2.2.2.32 PreferredContactMethod1Code

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

CodeName	Name	Definition
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.

Restricts

PreferredContactMethodCode on page 58

2.2.2.33 PreferredContactMethodCode

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

CodeName	Name	Definition
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
ONLI	Online	Preferred method used to reach the contact is online.

Is restricted by

[PreferredContactMethod1Code on page 58](#)

2.2.2.34 QueryType3Code

Definition: Specifies the nature of the request, that is whether all information be returned or only information that has changed since the last similar request was returned.

Type: CodeSet

CodeName	Name	Definition
ALLL	All	Specifies that the query requests that all matching items be returned.
CHNG	Changed	Specifies that the query requests that only new matching items since the last similar query be returned.
MODF	Modified	Specifies that the query requests that only items that have changed since the last query be returned.

Restricts

[QueryTypeCode on page 59](#)

2.2.2.35 QueryTypeCode

Definition: Specifies the nature of the query, i.e. whether the query requests that all matching items be returned or only new matching items since the last similar query be returned.

Type: CodeSet

CodeName	Name	Definition
ALLL	All	Specifies that the query requests that all matching items be returned.
CHNG	Changed	Specifies that the query requests that only new matching items since the last similar query be returned.
MODF	Modified	Specifies that the query requests that only items that have changed since the last query be returned.
DELD	Deleted	Specifies that the query requests that items that have been deleted since the last query be returned.

Is restricted by

[QueryType3Code on page 59](#)

2.2.3 Date

2.2.3.1 ISODate

Definition: A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Type: Date

2.2.4 DateTime

2.2.4.1 ISODateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: DateTime

2.2.5 IdentifierSet

2.2.5.1 AnyBICDec2014Identifier

Definition: Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Identification scheme: SWIFT; AnyBICIdentifier

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Constraints

- AnyBIC

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consists of eight (8) or eleven (11) contiguous characters.

Error handling:

– Error severity: Fatal

– Error Code: D00008

- *Error Text:* Invalid BIC.

2.2.5.2 BICFIDec2014Identifier

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Identification scheme: SWIFT; BICIdentifier

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Constraints

- **BICFI**

Valid BICs for financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consist of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid FI BIC.

2.2.5.3 IBAN2007Identifier

Definition: The International Bank Account Number is a code used internationally by financial institutions to uniquely identify the account of a customer at a financial institution as described in the 2007 edition of the ISO 13616 standard "Banking and related financial services - International Bank Account Number (IBAN)" and replaced by the more recent edition of the standard.

Type: IdentifierSet

Identification scheme: National Banking Association; International Bank Account Number (ISO 13616)

Format

pattern [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}

Constraints

- **IBAN**

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00003

– *Error Text:* Invalid IBAN format or invalid check digits.

2.2.5.4 LEIdentifier

Definition: Legal Entity Identifier is a code allocated to a party as described in ISO 17442 "Financial Services - Legal Entity Identifier (LEI)".

Type: IdentifierSet

Identification scheme: Global LEI System; LEIdentifier

Format

pattern	[A-Z0-9]{18,18}[0-9]{2,2}
---------	---------------------------

2.2.6 Text

2.2.6.1 Exact4AlphaNumericText

Definition: Specifies an alphanumeric string with a length of 4 characters.

Type: Text

Format

pattern	[a-zA-Z0-9]{4}
---------	----------------

2.2.6.2 Max128Text

Definition: Specifies a character string with a maximum length of 128 characters.

Type: Text

Format

minLength	1
maxLength	128

2.2.6.3 Max140Text

Definition: Specifies a character string with a maximum length of 140 characters.

Type: Text

Format

minLength	1
maxLength	140

2.2.6.4 Max16Text

Definition: Specifies a character string with a maximum length of 16 characters.

Type: Text

Format

minLength	1
maxLength	16

2.2.6.5 Max2048Text

Definition: Specifies a character string with a maximum length of 2048 characters.

Type: Text

Format

minLength	1
maxLength	2048

2.2.6.6 Max34Text

Definition: Specifies a character string with a maximum length of 34 characters.

Type: Text

Format

minLength	1
maxLength	34

2.2.6.7 Max350Text

Definition: Specifies a character string with a maximum length of 350 characters.

Type: Text

Format

minLength	1
maxLength	350

2.2.6.8 Max35Text

Definition: Specifies a character string with a maximum length of 35 characters.

Type: Text

Format

minLength	1
maxLength	35

2.2.6.9 Max4Text

Definition: Specifies a character string with a maximum length of 4 characters.

Type: Text

Format

minLength	1
maxLength	4

2.2.6.10 Max70Text

Definition: Specifies a character string with a maximum length of 70characters.

Type: Text

Format

minLength	1
maxLength	70

2.2.6.11 PhoneNumber

Definition: The collection of information which identifies a specific phone or FAX number as defined by telecom services.

It consists of a "+" followed by the country code (from 1 to 3 characters) then a "-" and finally, any combination of numbers, "(", ")", "+" and "-" (up to 30 characters).

Type: Text

Format

pattern	\+[0-9]{1,3}-[0-9()+\-]{1,30}
---------	-------------------------------

2.2.7 Time**2.2.7.1 ISOTime**

Definition: A particular point in the progression of time in a calendar day expressed in either UTC time format (hh:mm:ss.sssZ), local time with UTC offset format (hh:mm:ss.sss+/-hh:mm), or local time format (hh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: Time

Legal Notices

Copyright

S.W.I.F.T. SC © 2026. All rights reserved.

You may copy this publication within your organisation. Any such copy must include these legal notices.

Confidentiality

This publication may contain Swift or third-party confidential information. Do not disclose this publication outside your organisation without the prior written consent of Swift.

Disclaimer

The information in this publication may change from time to time. You must always refer to the latest available version.

Swift Standards Intellectual Property Rights (IPR) Policy - End-User License Agreement

Swift Standards are licensed subject to the terms and conditions of the *Swift Standards IPR Policy - End-User License Agreement* available at www.swift.com > About Swift > Legal > Swift Standards IPR Policy.

Translations

The English version of Swift documentation is the only official version.

Trademarks and Patents

Swift is the trade name of S.W.I.F.T. SC. The following are registered trademarks of Swift: 3SKey, Innotribe, MyStandards, Sibos, Swift, SwiftNet, the Standards Forum logo, the Swift logo, Swift GPI with logo, the Swift GPI logo, and UETR. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.