

Standards

Standards MX

Message Reference Guide

FIToFICustomerCreditTransferV08 (pacs.008.001.08)

This publication includes information exported from the MyStandards web platform.

For the official documentation of the messages included in this publication, see the relevant Standards MX Message Reference Guides available on swift.com > Support > Documentation

Table of Contents

1	MX pacs.008.001.08 FIToFICustomerCreditTransferV08	3
1.1	MessageDefinition Functionality	3
1.2	Structure	4
1.3	Constraints	4
1.4	Message Building Blocks	15
2	Message Items Types	24
2.1	MessageComponents	24
2.2	Message Datatypes	136
	Legal Notices	173

1 **MX pacs.008.001.08**

FIToFICustomerCreditTransferV08

1.1 MessageDefinition Functionality

Scope

The FinancialInstitutionToFinancialInstitutionCustomerCreditTransfer message is sent by the debtor agent to the creditor agent, directly or through other agents and/or a payment clearing and settlement system. It is used to move funds from a debtor account to a creditor.

Usage

The FIToFICustomerCreditTransfer message is exchanged between agents and can contain one or more customer credit transfer instructions.

The FIToFICustomerCreditTransfer message does not allow for grouping: a CreditTransferTransactionInformation block must be present for each credit transfer transaction.

The FIToFICustomerCreditTransfer message can be used in different ways:

- If the instructing agent and the instructed agent wish to use their direct account relationship in the currency of the transfer then the message contains both the funds for the customer transfer(s) as well as the payment details;
- If the instructing agent and the instructed agent have no direct account relationship in the currency of the transfer, or do not wish to use their account relationship, then other (reimbursement) agents will be involved to cover for the customer transfer(s). The FIToFICustomerCreditTransfer contains only the payment details and the instructing agent must cover the customer transfer by sending a FinancialInstitutionCreditTransfer to a reimbursement agent. This payment method is called the Cover method;
- If more than two financial institutions are involved in the payment chain and if the FIToFICustomerCreditTransfer is sent from one financial institution to the next financial institution in the payment chain, then the payment method is called the Serial method.

The FIToFICustomerCreditTransfer message can be used in domestic and cross-border scenarios.

Outline

The FIToFICustomerCreditTransferV08 MessageDefinition is composed of 3 MessageBuildingBlocks:

A. GroupHeader

Set of characteristics shared by all individual transactions included in the message.

B. CreditTransferTransactionInformation

Set of elements providing information specific to the individual credit transfer(s).

C. SupplementaryData

Additional information that cannot be captured in the structured elements and/or any other specific block.

1.2 Structure

Index	Or	MessageElement/BuildingBlock<XML Tag>	Mult.	Type	Constr. No.	Page
		<i>Message root</i> <Document> <FIToFICstmrCdtTrf>	[1..1]		✓C12, ✓C14, ✓C19, C27, ✓C28, C39, C44, ✓C45, ✓C47	
		GroupHeader <GrpHdr>	[1..1]	±	✓C43	15
		CreditTransferTransactionInformation <CdtTrfTxInf>	[1..*]	±	✓C5, ✓C7, ✓C15, ✓C16, ✓C17, ✓C21, ✓C22, ✓C23, ✓C24, ✓C25, ✓C26, ✓C29, ✓C31, ✓C32, ✓C33, ✓C34, C6, C8, C30, C48, C49	16
		SupplementaryData <SplmtryData>	[0..*]	±	C40	23

1.3 Constraints

C1 ActiveCurrency ✓

(Rule)

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00005
- *Error Text:* Invalid currency code

C2 ActiveOrHistoricCurrency ✓

(Rule)

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

C3 AnyBIC ✓

(Rule)

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consists of eight (8) or eleven (11) contiguous characters. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

C4 BICFI ✓

(Rule)

Valid BICs for financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consist of eight (8) or eleven (11) contiguous characters. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid FI BIC.

C5 ChargeBearerAndChargesInformationRule ✓

(Rule)

If ChargeBearer contains DEBT, then ChargesInformation may be present to communicate charges that have been added for (the) InstructedAgent(s).

If ChargeBearer contains CRED, then at least one occurrence of ChargesInformation must be present to communicate charges that have been deducted from the InstructedAmount by (the) InstructingAgent(s).

If ChargeBearer contains SHAR or SLEV, then ChargesInformation is optional. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00046
- *Error Text:* Invalid message content for charge bearer and charges information.

C6 ChargesAmountGuideline*(Guideline)*

If ChargesInformation is present, then the currency of ChargesInformation/ChargesAmount is recommended to be the same as the currency of InterbankSettlementAmount.

C7 ChargesInformationAndInstructedAmountRule ✓*(Rule)*

If ChargesInformation is present, then InstructedAmount must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00048
- *Error Text:* Invalid message content for instructed amount when charges information is present.

C8 ChargesInformationGuideline*(Guideline)*

The repetitive ChargesInformation should contain all information on charges amount and which party has taken the charges, separately for each agent along the payment chain.

C9 Country ✓*(Rule)*

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code). (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

C10 CurrencyAmount ✓*(Rule)*

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007

- *Error Text*: Invalid currency code or too many decimal digits.

C11 CurrencyAmount ✓

(Rule)

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot. (Algorithm)

Error handling:

- *Error severity*: Fatal
- *Error Code*: D00007
- *Error Text*: Invalid currency code or too many decimal digits.

C12 GroupHeaderInterbankSettlementDateRule ✓

(Rule)

If GroupHeader/InterbankSettlementDate is present, then CreditTransferTransactionInformation/InterbankSettlementDate is not allowed. (CrossElementComplexRule)

Error handling:

- *Error severity*: Fatal
- *Error Code*: X00045
- *Error Text*: Invalid message content for interbank settlement date.

This constraint is defined at the MessageDefinition level.

C13 IBAN ✓

(Rule)

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN. (Algorithm)

Error handling:

- *Error severity*: Fatal
- *Error Code*: D00003
- *Error Text*: Invalid IBAN format or invalid check digits.

C14 InstructedAgentRule ✓

(Rule)

If GroupHeader/InstructedAgent is present, then CreditTransferTransactionInformation/InstructedAgent is not allowed. (CrossElementComplexRule)

Error handling:

- *Error severity*: Fatal
- *Error Code*: X00008
- *Error Text*: Invalid message content for instructed agent.

This constraint is defined at the MessageDefinition level.

C15 InstructedAmountAndExchangeRate1Rule ✓

(Rule)

If InstructedAmount is present and the currency is different from the currency in InterbankSettlementAmount, then ExchangeRate must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00049
- *Error Text:* Invalid message content for exchange rate when instructed amount is present.

C16 InstructedAmountAndExchangeRate2Rule ✓

(Rule)

If InstructedAmount is present and the currency is the same as the currency in InterbankSettlementAmount, then ExchangeRate is not allowed. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00050
- *Error Text:* Invalid message content for exchange rate when instructed amount is not present.

C17 InstructedAmountAndExchangeRate3Rule ✓

(Rule)

If InstructedAmount is not present, then ExchangeRate is not allowed. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00061
- *Error Text:* Invalid message content for exchange rate and instructed amount.

C18 InstructedReimbursementAgentAccountRule ✓

(Rule)

If InstructedReimbursementAgentAccount is present, then InstructedReimbursementAgent must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00037
- *Error Text:* Invalid message content for instructed reimbursement agent account.

C19 InstructingAgentRule ✓

(Rule)

If GroupHeader/InstructingAgent is present, then CreditTransferTransactionInformation/InstructingAgent is not allowed. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00007
- *Error Text:* Invalid message content for instructing agent.

This constraint is defined at the MessageDefinition level.

C20 InstructingReimbursementAgentAccountRule ✓

(Rule)

If InstructingReimbursementAgentAccount is present, then InstructingReimbursementAgent must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00038
- *Error Text:* Invalid message content for instructing reimbursement agent account.

C21 InstructionForCreditorAgentRule ✓

(Rule)

If InstructionForCreditorAgent/Code contains CHQB (PayCreditorByCheque), then CreditorAccount is not allowed. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00051
- *Error Text:* Invalid message content for PayCreditorByCheque instruction for creditor agent.

C22 IntermediaryAgent1AccountRule ✓

(Rule)

If IntermediaryAgent1Account is present, then IntermediaryAgent1 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00052
- *Error Text:* Invalid message content for intermediary agent 1 account.

C23 IntermediaryAgent2AccountRule ✓

(Rule)

If IntermediaryAgent2Account is present, then IntermediaryAgent2 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00053
- *Error Text:* Invalid message content for intermediary agent 2 account.

C24 IntermediaryAgent2Rule ✓

(Rule)

If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00056
- *Error Text:* Invalid message content for intermediary agent 2.

C25 IntermediaryAgent3AccountRule ✓

(Rule)

If IntermediaryAgent3Account is present, then IntermediaryAgent3 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00054
- *Error Text:* Invalid message content for intermediary agent 3 account.

C26 IntermediaryAgent3Rule ✓

(Rule)

If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00057
- *Error Text:* Invalid message content for intermediary agent 3.

C27 NumberOfTransactionsAndCreditTransfersRule

(Rule)

GroupHeader/NumberOfTransactions must equal the number of occurrences of CreditTransferTransactionInformation. (CrossElementSimpleRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00062
- *Error Text:* Invalid message content for number of transactions.

This constraint is defined at the MessageDefinition level.

C28 PaymentTypeInformationRule ✓

(Rule)

If GroupHeader/PaymentTypeInformation is present, then CreditTransferTransactionInformation/PaymentTypeInformation is not allowed. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00009
- *Error Text:* Invalid message content for payment type information.

This constraint is defined at the MessageDefinition level.

C29 PreviousInstructingAgent1AccountRule ✓

(Rule)

If PreviousInstructingAgent1Account is present, then PreviousInstructingAgent1 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00411
- *Error Text:* Invalid message content for previous instructing agent account.

C30 PreviousInstructingAgent1Guideline

(Guideline)

It is recommended that, when present, PreviousInstructingAgent1 is the closest to the DebtorAgent in the payment chain.

C31 PreviousInstructingAgent2AccountRule ✓

(Rule)

If PreviousInstructingAgent2Account is present, then PreviousInstructingAgent2 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00412
- *Error Text:* Invalid message content for previous instructing agent account.

C32 PreviousInstructingAgent3AccountRule ✓

(Rule)

If PreviousInstructingAgent3Account is present, then PreviousInstructingAgent3 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00413
- *Error Text:* Invalid message content for previous instructing agent account.

C33 PreviousInstructionAgent2Rule ✓

(Rule)

If PreviousInstructingAgent2 is present, then PreviousInstructingAgent1 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00415
- *Error Text:* Invalid message content for intermediary agent 1.

C34 PreviousInstructionAgent3Rule ✓

(Rule)

If PreviousInstructingAgent3 is present, then PreviousInstructingAgent2 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00416
- *Error Text:* Invalid message content for intermediary agent 1.

C35 SettlementMethodAgentRule ✓

(Rule)

If SettlementMethod is equal to INDA or INGA, then ReimbursementAgent(s) and ClearingSystem are not allowed. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00018
- *Error Text:* Invalid message content for settlement method INGA or INDA.

C36 SettlementMethodClearingRule ✓

(Rule)

If SettlementMethod is equal to CLRG, then SettlementAccount and ReimbursementAgent(s) are not allowed. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00019
- *Error Text:* Invalid message content for settlement method CLRG.

C37 SettlementMethodCoverAgentRule ✓

(Rule)

If SettlementMethod is equal to COVE, then InstructedReimbursementAgent or InstructingReimbursementAgent must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00076
- *Error Text:* Invalid message content for cover settlement method and reimbursement agents.

C38 SettlementMethodCoverRule ✓

(Rule)

If SettlementMethod is equal to COVE, then SettlementAccount and ClearingSystem are not allowed. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00075
- *Error Text:* Invalid message content for cover settlement method with settlement account and clearing system.

C39 SupplementaryDataRule

(Rule)

The SupplementaryData building block at message level must not be used to provide additional information about a transaction. The SupplementaryData element at transaction level should be used for that purpose.

This constraint is defined at the MessageDefinition level.

C40 SupplementaryDataRule

(Rule)

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

C41 ThirdReimbursementAgentAccountRule ✓

(Rule)

If ThirdReimbursementAgentAccount is present, then ThirdReimbursementAgent must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00039
- *Error Text:* Invalid message content for third reimbursement agent account.

C42 ThirdReimbursementAgentRule ✓*(Rule)*

If ThirdReimbursementAgent is present, then InstructingReimbursementAgent and InstructedReimbursementAgent must both be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00040
- *Error Text:* Invalid message content for third reimbursement agent.

C43 TotalInterbankSettlementAmountAndDateRule ✓*(Rule)*

If TotalInterbankSettlementAmount is present, then InterbankSettlementDate must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00044
- *Error Text:* Invalid message content for group header interbank settlement date.

C44 TotalInterbankSettlementAmountAndSumRule*(Rule)*

If GroupHeader/TotalInterbankSettlementAmount is present, then it must equal the sum of all occurrences of CreditTransferTransactionInformation/InterbankSettlementAmount. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00043
- *Error Text:* Invalid message content for the total interbank settlement amount and sum of individual interbank settlement amounts.

This constraint is defined at the MessageDefinition level.

C45 TotalInterbankSettlementAmountRule ✓*(Rule)*

If GroupHeader/TotalInterbankSettlementAmount is present, then all occurrences of CreditTransferTransactionInformation/InterbankSettlementAmount must have the same currency as the currency of GroupHeader/TotalInterbankSettlementAmount. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00042
- *Error Text:* Invalid message content for the total interbank settlement amount and individual interbank settlement amount currencies.

This constraint is defined at the MessageDefinition level.

C46 TransactionIdentificationPresenceRule

(Rule)

TransactionIdentification or UETR must be present. Both may be present (CrossElementSimpleRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00420
- *Error Text:* No transaction identification is present

C47 TransactionInterbankSettlementDateRule ✓

(Rule)

If GroupHeader/InterbankSettlementDate is not present, then CreditTransferTransactionInformation/InterbankSettlementDate must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00290
- *Error Text:* Invalid message content for interbank settlement date.

This constraint is defined at the MessageDefinition level.

C48 UltimateCreditorGuideline

(Guideline)

UltimateCreditor may only be present if different from Creditor.

C49 UltimateDebtorGuideline

(Guideline)

UltimateDebtor may only be present if different from Debtor.

1.4 Message Building Blocks

This chapter describes the MessageBuildingBlocks of this MessageDefinition.

1.4.1 GroupHeader <GrpHdr>

Presence: [1..1]

Definition: Set of characteristics shared by all individual transactions included in the message.

Impacted by: ✓C43 TotalInterbankSettlementAmountAndDateRule ✓

GroupHeader <GrpHdr> contains the following elements (see [GroupHeader93](#) on page 44 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		MessageIdentification <MsgId>	[1..1]	Text		45
		CreationDateTime <CreDtTm>	[1..1]	DateTime		45
		BatchBooking <BtchBookg>	[0..1]	Indicator		45
		NumberOfTransactions <NbOfTx>	[1..1]	Text		46
		ControlSum <CtrlSum>	[0..1]	Quantity		46
		TotalInterbankSettlementAmount <TtlIntrBkSttlmAmt>	[0..1]	Amount		46
		InterbankSettlementDate <IntrBkSttlmDt>	[0..1]	Date		46
		SettlementInformation <SttlmInf>	[1..1]	±		46
		PaymentTypeInformation <PmtTpInf>	[0..1]	±		47
		InstructingAgent <InstgAgt>	[0..1]	±		48
		InstructedAgent <InstdAgt>	[0..1]	±		48

Constraints

- **TotalInterbankSettlementAmountAndDateRule**

If TotalInterbankSettlementAmount is present, then InterbankSettlementDate must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00044
- *Error Text:* Invalid message content for group header interbank settlement date.

1.4.2 CreditTransferTransactionInformation <CdtTrfTxInf>

Presence: [1..*]

Definition: Set of elements providing information specific to the individual credit transfer(s).

Impacted by: ✓C5 ChargeBearerAndChargesInformationRule ✓, ✓C7 ChargesInformationAndInstructedAmountRule ✓, ✓C15 InstructedAmountAndExchangeRate1Rule ✓, ✓C16 InstructedAmountAndExchangeRate2Rule ✓, ✓C17 InstructedAmountAndExchangeRate3Rule ✓, ✓C21 InstructionForCreditorAgentRule ✓, ✓C22 IntermediaryAgent1AccountRule ✓, ✓C23 IntermediaryAgent2AccountRule ✓, ✓C24 IntermediaryAgent2Rule ✓, ✓C25 IntermediaryAgent3AccountRule ✓, ✓C26 IntermediaryAgent3Rule ✓, ✓C29 PreviousInstructingAgent1AccountRule ✓, ✓C31 PreviousInstructingAgent2AccountRule ✓, ✓C32 PreviousInstructingAgent3AccountRule ✓, ✓C33 PreviousInstructionAgent2Rule ✓, ✓C34 PreviousInstructionAgent3Rule ✓, C6

ChargesAmountGuideline, C8 ChargesInformationGuideline, C30 PreviousInstructingAgent1Guideline,
C48 UltimateCreditorGuideline, C49 UltimateDebtorGuideline

CreditTransferTransactionInformation <CdtTrfTxInf> contains the following elements (see [CreditTransferTransaction39](#) on page 57 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PaymentIdentification <PmtId>	[1..1]	±		63
		PaymentTypeInfo <PmtTpInf>	[0..1]	±		63
		InterbankSettlementAmount <IntrBkSttlmAmt>	[1..1]	Amount		64
		InterbankSettlementDate <IntrBkSttlmDt>	[0..1]	Date		64
		SettlementPriority <SttlmPrty>	[0..1]	CodeSet		64
		SettlementTimeIndication <SttlmTmIndctn>	[0..1]			64
		DebitDateTime <DbtDtTm>	[0..1]	DateTime		64
		CreditDateTime <CdtDtTm>	[0..1]	DateTime		64
		SettlementTimeRequest <SttlmTmReq>	[0..1]	±		65
		AcceptanceDateTime <AcceptncDtTm>	[0..1]	DateTime		65
		PoolingAdjustmentDate <PoolgAdjstmntDt>	[0..1]	Date		65
		InstructedAmount <InstdAmt>	[0..1]	Amount		65
		ExchangeRate <XchgRate>	[0..1]	Rate		65
		ChargeBearer <ChrgBr>	[1..1]	CodeSet		66
		ChargesInformation <ChrgsInf>	[0..*]	±		66
		PreviousInstructingAgent1 <PrvsInstgAgt1>	[0..1]	±		66
		PreviousInstructingAgent1Account <PrvsInstgAgt1Acct>	[0..1]	±		67
		PreviousInstructingAgent2 <PrvsInstgAgt2>	[0..1]	±		67
		PreviousInstructingAgent2Account <PrvsInstgAgt2Acct>	[0..1]	±		67
		PreviousInstructingAgent3 <PrvsInstgAgt3>	[0..1]	±		68
		PreviousInstructingAgent3Account <PrvsInstgAgt3Acct>	[0..1]	±		68
		InstructingAgent <InstgAgt>	[0..1]	±		68
		InstructedAgent <InstdAgt>	[0..1]	±		68
		IntermediaryAgent1 <IntrmyAgt1>	[0..1]	±		69
		IntermediaryAgent1Account <IntrmyAgt1Acct>	[0..1]	±		69
		IntermediaryAgent2 <IntrmyAgt2>	[0..1]	±		69
		IntermediaryAgent2Account <IntrmyAgt2Acct>	[0..1]	±		70
		IntermediaryAgent3 <IntrmyAgt3>	[0..1]	±		70
		IntermediaryAgent3Account <IntrmyAgt3Acct>	[0..1]	±		70

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		UltimateDebtor <UltmtDbtr>	[0..1]	±		71
		InitiatingParty <InitgPty>	[0..1]	±		71
		Debtor <Dbtr>	[1..1]	±		72
		DebtorAccount <DbtrAcct>	[0..1]	±		72
		DebtorAgent <DbtrAgt>	[1..1]	±		72
		DebtorAgentAccount <DbtrAgtAcct>	[0..1]	±		72
		CreditorAgent <CdtrAgt>	[1..1]	±		73
		CreditorAgentAccount <CdtrAgtAcct>	[0..1]	±		73
		Creditor <Cdtr>	[1..1]	±		73
		CreditorAccount <CdtrAcct>	[0..1]	±		74
		UltimateCreditor <UltmtCdtr>	[0..1]	±		74
		InstructionForCreditorAgent <InstrForCdtrAgt>	[0..*]	±		74
		InstructionForNextAgent <InstrForNxtAgt>	[0..*]			75
		Code <Cd>	[0..1]	CodeSet		75
		InstructionInformation <InstrInf>	[0..1]	Text		75
		Purpose <Purp>	[0..1]	±		76
		RegulatoryReporting <RgltryRptg>	[0..10]	±		76
		Tax <Tax>	[0..1]	±		76
		RelatedRemittanceInformation <RltdRmtInf>	[0..10]	±		77
		RemittanceInformation <RmtInf>	[0..1]	±		77
		SupplementaryData <SplmtryData>	[0..*]	±		77

Constraints

• ChargeBearerAndChargesInformationRule

If ChargeBearer contains DEBT, then ChargesInformation may be present to communicate charges that have been added for (the) InstructedAgent(s).

If ChargeBearer contains CRED, then at least one occurrence of ChargesInformation must be present to communicate charges that have been deducted from the InstructedAmount by (the) InstructingAgent(s).

If ChargeBearer contains SHAR or SLEV, then ChargesInformation is optional.

Error handling:

- Error severity: Fatal
- Error Code: X00046

- *Error Text:* Invalid message content for charge bearer and charges information.

- **ChargesAmountGuideline**

If ChargesInformation is present, then the currency of ChargesInformation/ChargesAmount is recommended to be the same as the currency of InterbankSettlementAmount.

- **ChargesInformationAndInstructedAmountRule**

If ChargesInformation is present, then InstructedAmount must be present.

Error handling:

- *Error severity:* Fatal

- *Error Code:* X00048

- *Error Text:* Invalid message content for instructed amount when charges information is present.

- **ChargesInformationGuideline**

The repetitive ChargesInformation should contain all information on charges amount and which party has taken the charges, separately for each agent along the payment chain.

- **InstructedAmountAndExchangeRate1Rule**

If InstructedAmount is present and the currency is different from the currency in InterbankSettlementAmount, then ExchangeRate must be present.

Error handling:

- *Error severity:* Fatal

- *Error Code:* X00049

- *Error Text:* Invalid message content for exchange rate when instructed amount is present.

- **InstructedAmountAndExchangeRate2Rule**

If InstructedAmount is present and the currency is the same as the currency in InterbankSettlementAmount, then ExchangeRate is not allowed.

Error handling:

- *Error severity:* Fatal

- *Error Code:* X00050

- *Error Text:* Invalid message content for exchange rate when instructed amount is not present.

- **InstructedAmountAndExchangeRate3Rule**

If InstructedAmount is not present, then ExchangeRate is not allowed.

Error handling:

- *Error severity:* Fatal

- *Error Code:* X00061

- *Error Text:* Invalid message content for exchange rate and instructed amount.

- **InstructionForCreditorAgentRule**

If InstructionForCreditorAgent/Code contains CHQB (PayCreditorByCheque), then CreditorAccount is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00051
- *Error Text:* Invalid message content for PayCreditorByCheque instruction for creditor agent.

- **IntermediaryAgent1AccountRule**

If IntermediaryAgent1Account is present, then IntermediaryAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00052
- *Error Text:* Invalid message content for intermediary agent 1 account.

- **IntermediaryAgent2AccountRule**

If IntermediaryAgent2Account is present, then IntermediaryAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00053
- *Error Text:* Invalid message content for intermediary agent 2 account.

- **IntermediaryAgent2Rule**

If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00056
- *Error Text:* Invalid message content for intermediary agent 2.

- **IntermediaryAgent3AccountRule**

If IntermediaryAgent3Account is present, then IntermediaryAgent3 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00054
- *Error Text:* Invalid message content for intermediary agent 3 account.

- **IntermediaryAgent3Rule**

If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00057
- *Error Text:* Invalid message content for intermediary agent 3.

- **PreviousInstructingAgent1AccountRule**

If PreviousInstructingAgent1Account is present, then PreviousInstructingAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00411
- *Error Text:* Invalid message content for previous instructing agent account.

- **PreviousInstructingAgent1Guideline**

It is recommended that, when present, PreviousInstructingAgent1 is the closest to the DebtorAgent in the payment chain.

- **PreviousInstructingAgent2AccountRule**

If PreviousInstructingAgent2Account is present, then PreviousInstructingAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00412
- *Error Text:* Invalid message content for previous instructing agent account.

- **PreviousInstructingAgent3AccountRule**

If PreviousInstructingAgent3Account is present, then PreviousInstructingAgent3 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00413
- *Error Text:* Invalid message content for previous instructing agent account.

- **PreviousInstructionAgent2Rule**

If PreviousInstructingAgent2 is present, then PreviousInstructingAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00415
- *Error Text:* Invalid message content for intermediary agent 1.

- **PreviousInstructionAgent3Rule**

If PreviousInstructingAgent3 is present, then PreviousInstructingAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00416
- *Error Text:* Invalid message content for intermediary agent 1.

- **UltimateCreditorGuideline**

UltimateCreditor may only be present if different from Creditor.

- **UltimateDebtorGuideline**

UltimateDebtor may only be present if different from Debtor.

1.4.3 **SupplementaryData <SplmtryData>**

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

Impacted by: [C40 SupplementaryDataRule](#)

SupplementaryData <SplmtryData> contains the following elements (see [SupplementaryData1 on page 48](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PlaceAndName <PlcAndNm>	[0..1]	Text		48
		Envelope <Envlp>	[1..1]	(External Schema)		49

Constraints

- **SupplementaryDataRule**

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

2 Message Items Types

2.1 MessageComponents

2.1.1 Account

2.1.1.1 CashAccount38

Definition: Provides the details to identify an account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.1.1.1 Identification <Id>

Presence: [1..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

Identification <Id> contains one of the following elements (see [AccountIdentification4Choice](#) on page 28 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	IBAN <IBAN>	[1..1]	IdentifierSet		28
	Or}	Other <Othr>	[1..1]	±		28

2.1.1.1.2 Type <Tp>

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

Type <Tp> contains one of the following elements (see [CashAccountType2Choice](#) on page 26 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		26
	Or}	Proprietary <Prtry>	[1..1]	Text		26

2.1.1.1.3 Currency <Ccy>

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: [ActiveOrHistoricCurrencyCode](#) on page 139

2.1.1.1.4 Name <Nm>

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: [Max70Text](#) on page 171

2.1.1.1.5 Proxy <Prxy>

Presence: [0..1]

Definition: Specifies an alternate assumed name for the identification of the account.

Proxy <Prxy> contains the following elements (see [ProxyAccountIdentification1](#) on page 25 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			25
	{Or	Code <Cd>	[1..1]	CodeSet		26
	Or}	Proprietary <Prtry>	[1..1]	Text		26
		Identification <Id>	[1..1]	Text		26

2.1.1.2 ProxyAccountIdentification1

Definition: Information related to a proxy identification of the account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			25
	{Or	Code <Cd>	[1..1]	CodeSet		26
	Or}	Proprietary <Prtry>	[1..1]	Text		26
		Identification <Id>	[1..1]	Text		26

2.1.1.2.1 Type <Tp>

Presence: [0..1]

Definition: Type of the proxy identification.

Type <Tp> contains one of the following **ProxyAccountType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		26
	Or}	Proprietary <Prtry>	[1..1]	Text		26

2.1.1.2.1.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: [ExternalProxyAccountType1Code on page 153](#)

2.1.1.2.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: [Max35Text on page 171](#)

2.1.1.2.2 Identification <Id>

Presence: [1..1]

Definition: Identification used to indicate the account identification under another specified name.

Datatype: [Max2048Text on page 170](#)

2.1.1.3 CashAccountType2Choice

Definition: Nature or use of the account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		26
	Or}	Proprietary <Prtry>	[1..1]	Text		26

2.1.1.3.1 Code <Cd>

Presence: [1..1]

Definition: Account type, in a coded form.

Datatype: [ExternalCashAccountType1Code on page 146](#)

2.1.1.3.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Nature or use of the account in a proprietary form.

Datatype: [Max35Text on page 171](#)

2.1.1.4 GenericAccountIdentification1

Definition: Information related to a generic account identification.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		27
		SchemeName <SchmeNm>	[0..1]			27
	{Or	Code <Cd>	[1..1]	CodeSet		27
	Or}	Proprietary <Prtry>	[1..1]	Text		27
		Issuer <Issr>	[0..1]	Text		27

2.1.1.4.1 Identification <Id>

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: [Max34Text on page 170](#)

2.1.1.4.2 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Name of the identification scheme.

SchemeName <SchmeNm> contains one of the following **AccountSchemeName1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		27
	Or}	Proprietary <Prtry>	[1..1]	Text		27

2.1.1.4.2.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: [ExternalAccountIdentification1Code on page 145](#)

2.1.1.4.2.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: [Max35Text on page 171](#)

2.1.1.4.3 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: [Max35Text on page 171](#)

2.1.2 Account Identification

2.1.2.1 AccountIdentification4Choice

Definition: Specifies the unique identification of an account as assigned by the account servicer.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	IBAN <IBAN>	[1..1]	IdentifierSet		28
	Or}	Other <Othr>	[1..1]	±		28

2.1.2.1.1 IBAN <IBAN>

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: [IBAN2007Identifier on page 167](#)

2.1.2.1.2 Other <Othr>

Presence: [1..1]

Definition: Unique identification of an account, as assigned by the account servicer, using an identification scheme.

Other <Othr> contains the following elements (see [GenericAccountIdentification1 on page 26](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		27
		SchemeName <SchmeNm>	[0..1]			27
	{Or	Code <Cd>	[1..1]	CodeSet		27
	Or}	Proprietary <Prtry>	[1..1]	Text		27
		Issuer <Issr>	[0..1]	Text		27

2.1.3 Charge

2.1.3.1 Charges7

Definition: Provides information on the charges related to the payment transaction.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Amount		29
		Agent <Agt>	[1..1]	±		29

2.1.3.1.1 Amount <Amt>

Presence: [1..1]

Definition: Transaction charges to be paid by the charge bearer.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 137

2.1.3.1.2 Agent <Agt>

Presence: [1..1]

Definition: Agent that takes the transaction charges or to which the transaction charges are due.

Agent <Agt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 36 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		36
		BranchIdentification <BrnchId>	[0..1]	±		37

2.1.4 Date Period

2.1.4.1 DatePeriod2

Definition: Range of time defined by a start date and an end date.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FromDate <FrDt>	[1..1]	Date		29
		ToDate <ToDt>	[1..1]	Date		29

2.1.4.1.1 FromDate <FrDt>

Presence: [1..1]

Definition: Start date of the range.

Datatype: [ISODate](#) on page 165

2.1.4.1.2 ToDate <ToDt>

Presence: [1..1]

Definition: End date of the range.

Datatype: [ISODate](#) on page 165

2.1.5 Document

2.1.5.1 CreditorReferenceInformation2

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			30
		CodeOrProprietary <CdOrPrtry>	[1..1]			30
	{Or	Code <Cd>	[1..1]	CodeSet		30
	Or}	Proprietary <Prtry>	[1..1]	Text		31
		Issuer <Issr>	[0..1]	Text		31
		Reference <Ref>	[0..1]	Text		31

2.1.5.1.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of creditor reference.

Type <Tp> contains the following **CreditorReferenceType2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CodeOrProprietary <CdOrPrtry>	[1..1]			30
	{Or	Code <Cd>	[1..1]	CodeSet		30
	Or}	Proprietary <Prtry>	[1..1]	Text		31
		Issuer <Issr>	[0..1]	Text		31

2.1.5.1.1.1 CodeOrProprietary <CdOrPrtry>

Presence: [1..1]

Definition: Coded or proprietary format creditor reference type.

CodeOrProprietary <CdOrPrtry> contains one of the following **CreditorReferenceType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		30
	Or}	Proprietary <Prtry>	[1..1]	Text		31

2.1.5.1.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Type of creditor reference, in a coded form.

Datatype: [DocumentType3Code](#) on page 143

CodeName	Name	Definition
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment

CodeName	Name	Definition
		instruction is related, for example, in a cover scenario.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
DISP	DispatchAdvice	Document is a dispatch advice.
PUOR	PurchaseOrder	Document is a purchase order.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.

2.1.5.1.1.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Creditor reference type, in a proprietary form.

Datatype: [Max35Text on page 171](#)

2.1.5.1.1.2 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the credit reference type.

Datatype: [Max35Text on page 171](#)

2.1.5.1.2 Reference <Ref>

Presence: [0..1]

Definition: Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction.

Usage: If available, the initiating party should provide this reference in the structured remittance information, to enable reconciliation by the creditor upon receipt of the amount of money.

If the business context requires the use of a creditor reference or a payment remit identification, and only one identifier can be passed through the end-to-end chain, the creditor's reference or payment remittance identification should be quoted in the end-to-end transaction identification.

Datatype: [Max35Text on page 171](#)

2.1.6 Financial Institution Identification

2.1.6.1 FinancialInstitutionIdentification18

Definition: Specifies the details to identify a financial institution.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		BICFI <BICFI>	[0..1]	IdentifierSet		32
		ClearingSystemMemberIdentification <ClrSysMmbld>	[0..1]	±		32
		LEI <LEI>	[0..1]	IdentifierSet		32
		Name <Nm>	[0..1]	Text		32
		PostalAddress <PstlAdr>	[0..1]	±		32
		Other <Othr>	[0..1]	±		33

2.1.6.1.1 BICFI <BICFI>

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: [BICFIDec2014Identifier on page 166](#)

2.1.6.1.2 ClearingSystemMemberIdentification <ClrSysMmbld>

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

ClearingSystemMemberIdentification <ClrSysMmbld> contains the following elements (see [ClearingSystemMemberIdentification2 on page 37](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ClearingSystemIdentification <ClrSysId>	[0..1]	±		37
		MemberIdentification <Mmbld>	[1..1]	Text		38

2.1.6.1.3 LEI <LEI>

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: [LEIIdentifier on page 167](#)

2.1.6.1.4 Name <Nm>

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: [Max140Text on page 170](#)

2.1.6.1.5 PostalAddress <PstlAdr>

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

PostalAddress <PstlAdr> contains the following elements (see [PostalAddress24](#) on page 86 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AddressType <AdrTp>	[0..1]			86
	{Or	Code <Cd>	[1..1]	CodeSet		87
	Or}	Proprietary <Prtry>	[1..1]	±		87
		Department <Dept>	[0..1]	Text		87
		SubDepartment <SubDept>	[0..1]	Text		87
		StreetName <StrtNm>	[0..1]	Text		88
		BuildingNumber <BldgNb>	[0..1]	Text		88
		BuildingName <BldgNm>	[0..1]	Text		88
		Floor <Flr>	[0..1]	Text		88
		PostBox <PstBx>	[0..1]	Text		88
		Room <Room>	[0..1]	Text		88
		PostCode <PstCd>	[0..1]	Text		88
		TownName <TwnNm>	[0..1]	Text		88
		TownLocationName <TwnLctnNm>	[0..1]	Text		89
		DistrictName <DstrctNm>	[0..1]	Text		89
		CountrySubDivision <CtrySubDvsn>	[0..1]	Text		89
		Country <Ctry>	[0..1]	CodeSet		89
		AddressLine <AdrLine>	[0..7]	Text		89

2.1.6.1.6 Other <Othr>

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

Other <Othr> contains the following elements (see [GenericFinancialIdentification1](#) on page 35 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		35
		SchemeName <SchmeNm>	[0..1]			36
	{Or	Code <Cd>	[1..1]	CodeSet		36
	Or}	Proprietary <Prtry>	[1..1]	Text		36
		Issuer <Issr>	[0..1]	Text		36

2.1.6.2 BranchData3

Definition: Information that locates and identifies a specific branch of a financial institution.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[0..1]	Text		34
		LEI <LEI>	[0..1]	IdentifierSet		34
		Name <Nm>	[0..1]	Text		34
		PostalAddress <PstlAdr>	[0..1]	±		34

2.1.6.2.1 Identification <Id>

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: [Max35Text on page 171](#)

2.1.6.2.2 LEI <LEI>

Presence: [0..1]

Definition: Legal entity identification for the branch of the financial institution.

Datatype: [LEIIdentifier on page 167](#)

2.1.6.2.3 Name <Nm>

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: [Max140Text on page 170](#)

2.1.6.2.4 PostalAddress <PstlAdr>

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

PostalAddress <PstlAdr> contains the following elements (see [PostalAddress24](#) on page 86 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AddressType <AdrTp>	[0..1]			86
	{Or	Code <Cd>	[1..1]	CodeSet		87
	Or}	Proprietary <Prtry>	[1..1]	±		87
		Department <Dept>	[0..1]	Text		87
		SubDepartment <SubDept>	[0..1]	Text		87
		StreetName <StrtNm>	[0..1]	Text		88
		BuildingNumber <BldgNb>	[0..1]	Text		88
		BuildingName <BldgNm>	[0..1]	Text		88
		Floor <Flr>	[0..1]	Text		88
		PostBox <PstBx>	[0..1]	Text		88
		Room <Room>	[0..1]	Text		88
		PostCode <PstCd>	[0..1]	Text		88
		TownName <TwnNm>	[0..1]	Text		88
		TownLocationName <TwnLctnNm>	[0..1]	Text		89
		DistrictName <DstrctNm>	[0..1]	Text		89
		CountrySubDivision <CtrySubDvsn>	[0..1]	Text		89
		Country <Ctry>	[0..1]	CodeSet		89
		AddressLine <AdrLine>	[0..7]	Text		89

2.1.6.3 GenericFinancialIdentification1

Definition: Information related to an identification of a financial institution.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		35
		SchemeName <SchmeNm>	[0..1]			36
	{Or	Code <Cd>	[1..1]	CodeSet		36
	Or}	Proprietary <Prtry>	[1..1]	Text		36
		Issuer <Issr>	[0..1]	Text		36

2.1.6.3.1 Identification <Id>

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: [Max35Text on page 171](#)

2.1.6.3.2 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Name of the identification scheme.

SchemeName <SchmeNm> contains one of the following **FinancialIdentificationSchemeName1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		36
	Or}	Proprietary <Prtry>	[1..1]	Text		36

2.1.6.3.2.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: [ExternalFinancialInstitutionIdentification1Code on page 150](#)

2.1.6.3.2.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: [Max35Text on page 171](#)

2.1.6.3.3 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: [Max35Text on page 171](#)

2.1.6.4 BranchAndFinancialInstitutionIdentification6

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		36
		BranchIdentification <BrnchId>	[0..1]	±		37

2.1.6.4.1 FinancialInstitutionIdentification <FinInstnId>

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

FinancialInstitutionIdentification <FinInstnId> contains the following elements (see [FinancialInstitutionIdentification18](#) on page 31 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		BICFI <BICFI>	[0..1]	IdentifierSet		32
		ClearingSystemMemberIdentification <ClrSysMmbld>	[0..1]	±		32
		LEI <LEI>	[0..1]	IdentifierSet		32
		Name <Nm>	[0..1]	Text		32
		PostalAddress <PstlAdr>	[0..1]	±		32
		Other <Othr>	[0..1]	±		33

2.1.6.4.2 BranchIdentification <BrnchId>

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

BranchIdentification <BrnchId> contains the following elements (see [BranchData3](#) on page 34 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[0..1]	Text		34
		LEI <LEI>	[0..1]	IdentifierSet		34
		Name <Nm>	[0..1]	Text		34
		PostalAddress <PstlAdr>	[0..1]	±		34

2.1.6.5 ClearingSystemMemberIdentification2

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ClearingSystemIdentification <ClrSysId>	[0..1]	±		37
		MemberIdentification <Mmbld>	[1..1]	Text		38

2.1.6.5.1 ClearingSystemIdentification <ClrSysId>

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

ClearingSystemIdentification <ClrSysId> contains one of the following elements (see [ClearingSystemIdentification2Choice on page 123](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		123
	Or}	Proprietary <Prtry>	[1..1]	Text		124

2.1.6.5.2 MemberIdentification <Mmbld>

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: [Max35Text on page 171](#)

2.1.7 Identification Information

2.1.7.1 GenericIdentification30

Definition: Information related to an identification, for example, party identification or account identification.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		38
		Issuer <Issr>	[1..1]	Text		38
		SchemeName <SchmeNm>	[0..1]	Text		38

2.1.7.1.1 Identification <Id>

Presence: [1..1]

Definition: Proprietary information, often a code, issued by the data source scheme issuer.

Datatype: [Exact4AlphaNumericText on page 169](#)

2.1.7.1.2 Issuer <Issr>

Presence: [1..1]

Definition: Entity that assigns the identification.

Datatype: [Max35Text on page 171](#)

2.1.7.1.3 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Short textual description of the scheme.

Datatype: [Max35Text on page 171](#)

2.1.7.2 PaymentIdentification7

Definition: Provides further means of referencing a payment transaction.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		InstructionIdentification <InstrId>	[0..1]	Text		39
		EndToEndIdentification <EndToEndId>	[1..1]	Text		39
		TransactionIdentification <TxId>	[0..1]	Text		39
		UETR <UETR>	[0..1]	IdentifierSet		40
		ClearingSystemReference <ClrSysRef>	[0..1]	Text		40

Constraints

- **TransactionIdentificationPresenceRule**

TransactionIdentification or UETR must be present. Both may be present

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00420
- *Error Text:* No transaction identification is present

2.1.7.2.1 InstructionIdentification <InstrId>

Presence: [0..1]

Definition: Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the instruction.

Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction.

Datatype: Max35Text on page 171

2.1.7.2.2 EndToEndIdentification <EndToEndId>

Presence: [1..1]

Definition: Unique identification, as assigned by the initiating party, to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.

Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction.

Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain.

Datatype: Max35Text on page 171

2.1.7.2.3 TransactionIdentification <TxId>

Presence: [0..1]

Definition: Unique identification, as assigned by the first instructing agent, to unambiguously identify the transaction that is passed on, unchanged, throughout the entire interbank chain.

Usage: The transaction identification can be used for reconciliation, tracking or to link tasks relating to the transaction on the interbank level.

Usage: The instructing agent has to make sure that the transaction identification is unique for a pre-agreed period.

Datatype: Max35Text on page 171

2.1.7.2.4 UETR <UETR>

Presence: [0..1]

Definition: Universally unique identifier to provide an end-to-end reference of a payment transaction.

Datatype: UIDv4Identifier on page 167

2.1.7.2.5 ClearingSystemReference <ClrSysRef>

Presence: [0..1]

Definition: Unique reference, as assigned by a clearing system, to unambiguously identify the instruction.

Datatype: Max35Text on page 171

2.1.8 Miscellaneous

2.1.8.1 RemittanceAmount2

Definition: Nature of the amount and currency on a document referred to in the remittance section, typically either the original amount due/payable or the amount actually remitted for the referenced document.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DuePayableAmount <DuePyblAmt>	[0..1]	Amount		41
		DiscountAppliedAmount <DscntApldAmt>	[0..*]			41
		Type <Tp>	[0..1]			42
	{Or	Code <Cd>	[1..1]	CodeSet		42
	Or}	Proprietary <Prtry>	[1..1]	Text		42
		Amount <Amt>	[1..1]	Amount		42
		CreditNoteAmount <CdtNoteAmt>	[0..1]	Amount		42
		TaxAmount <TaxAmt>	[0..*]			42
		Type <Tp>	[0..1]			43
	{Or	Code <Cd>	[1..1]	CodeSet		43
	Or}	Proprietary <Prtry>	[1..1]	Text		43
		Amount <Amt>	[1..1]	Amount		43
		AdjustmentAmountAndReason <AdjstmntAmtAndRsn>	[0..*]			43
		Amount <Amt>	[1..1]	Amount		44
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		44
		Reason <Rsn>	[0..1]	Text		44
		AdditionalInformation <AddtlInf>	[0..1]	Text		44
		RemittedAmount <RmtdAmt>	[0..1]	Amount		44

2.1.8.1.1 DuePayableAmount <DuePyblAmt>

Presence: [0..1]

Definition: Amount specified is the exact amount due and payable to the creditor.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 137

2.1.8.1.2 DiscountAppliedAmount <DscntApldAmt>

Presence: [0..*]

Definition: Amount specified for the referred document is the amount of discount to be applied to the amount due and payable to the creditor.

DiscountAppliedAmount <DscntApldAmt> contains the following **DiscountAmountAndType1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			42
	{Or	Code <Cd>	[1..1]	CodeSet		42
	Or}	Proprietary <Prtry>	[1..1]	Text		42
		Amount <Amt>	[1..1]	Amount		42

2.1.8.1.2.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of the amount.

Type <Tp> contains one of the following **DiscountAmountType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		42
	Or}	Proprietary <Prtry>	[1..1]	Text		42

2.1.8.1.2.1.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: [ExternalDiscountAmountType1Code on page 149](#)

2.1.8.1.2.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: [Max35Text on page 171](#)

2.1.8.1.2.2 Amount <Amt>

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 137](#)

2.1.8.1.3 CreditNoteAmount <CdtNoteAmt>

Presence: [0..1]

Definition: Amount specified for the referred document is the amount of a credit note.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 137](#)

2.1.8.1.4 TaxAmount <TaxAmt>

Presence: [0..*]

Definition: Quantity of cash resulting from the calculation of the tax.

TaxAmount <TaxAmt> contains the following **TaxAmountAndType1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			43
	{Or	Code <Cd>	[1..1]	CodeSet		43
	Or}	Proprietary <Prtry>	[1..1]	Text		43
		Amount <Amt>	[1..1]	Amount		43

2.1.8.1.4.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of the amount.

Type <Tp> contains one of the following **TaxAmountType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		43
	Or}	Proprietary <Prtry>	[1..1]	Text		43

2.1.8.1.4.1.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: [ExternalTaxAmountType1Code](#) on page 155

2.1.8.1.4.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: [Max35Text](#) on page 171

2.1.8.1.4.2 Amount <Amt>

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 137

2.1.8.1.5 AdjustmentAmountAndReason <AdjstmntAmtAndRsn>

Presence: [0..*]

Definition: Specifies detailed information on the amount and reason of the document adjustment.

AdjustmentAmountAndReason <AdjstmntAmtAndRsn> contains the following **DocumentAdjustment1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Amount		44
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		44
		Reason <Rsn>	[0..1]	Text		44
		AdditionalInformation <AddtlInf>	[0..1]	Text		44

2.1.8.1.5.1 Amount <Amt>

Presence: [1..1]

Definition: Amount of money of the document adjustment.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 137](#)

2.1.8.1.5.2 CreditDebitIndicator <CdtDbtInd>

Presence: [0..1]

Definition: Specifies whether the adjustment must be subtracted or added to the total amount.

Datatype: [CreditDebitCode on page 142](#)

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

2.1.8.1.5.3 Reason <Rsn>

Presence: [0..1]

Definition: Specifies the reason for the adjustment.

Datatype: [Max4Text on page 171](#)

2.1.8.1.5.4 AdditionalInformation <AddtlInf>

Presence: [0..1]

Definition: Provides further details on the document adjustment.

Datatype: [Max140Text on page 170](#)

2.1.8.1.6 RemittedAmount <RmtdAmt>

Presence: [0..1]

Definition: Amount of money remitted for the referred document.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 137](#)

2.1.8.2 GroupHeader93

Definition: Set of characteristics shared by all individual transactions included in the message.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		MessageIdentification <MsgId>	[1..1]	Text		45
		CreationDateTime <CreDtTm>	[1..1]	DateTime		45
		BatchBooking <BtchBookg>	[0..1]	Indicator		45
		NumberOfTransactions <NbOfTxs>	[1..1]	Text		46
		ControlSum <CtrlSum>	[0..1]	Quantity		46
		TotalInterbankSettlementAmount <TtlIntrBkSttlmAmt>	[0..1]	Amount		46
		InterbankSettlementDate <IntrBkSttlmDt>	[0..1]	Date		46
		SettlementInformation <SttlmInf>	[1..1]	±		46
		PaymentTypeInformation <PmtTpInf>	[0..1]	±		47
		InstructingAgent <InstgAgt>	[0..1]	±		48
		InstructedAgent <InstdAgt>	[0..1]	±		48

Constraints

- **TotalInterbankSettlementAmountAndDateRule**

If TotalInterbankSettlementAmount is present, then InterbankSettlementDate must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00044
- *Error Text:* Invalid message content for group header interbank settlement date.

2.1.8.2.1 MessageIdentification <MsgId>

Presence: [1..1]

Definition: Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message.

Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period.

Datatype: [Max35Text on page 171](#)

2.1.8.2.2 CreationDateTime <CreDtTm>

Presence: [1..1]

Definition: Date and time at which the message was created.

Datatype: [ISODatetime on page 165](#)

2.1.8.2.3 BatchBooking <BtchBookg>

Presence: [0..1]

Definition: Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested.

Usage: Batch booking is used to request and not order a possible batch booking.

Datatype: One of the following values must be used (see [BatchBookingIndicator](#) on page 168):

- *Meaning When True:* Identifies that a batch entry for the sum of the amounts of all transactions in the batch or message is requested.
- *Meaning When False:* Identifies that a single entry for each of the transactions in the batch or message is requested.

2.1.8.2.4 NumberOfTransactions <NbOfTx>

Presence: [1..1]

Definition: Number of individual transactions contained in the message.

Datatype: [Max15NumericText](#) on page 170

2.1.8.2.5 ControlSum <CtrlSum>

Presence: [0..1]

Definition: Total of all individual amounts included in the message, irrespective of currencies.

Datatype: [DecimalNumber](#) on page 168

2.1.8.2.6 TotalInterbankSettlementAmount <TtlIntrBkSttlmAmt>

Presence: [0..1]

Definition: Total amount of money moved between the instructing agent and the instructed agent.

Datatype: [ActiveCurrencyAndAmount](#) on page 136

2.1.8.2.7 InterbankSettlementDate <IntrBkSttlmDt>

Presence: [0..1]

Definition: Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.

Datatype: [ISODate](#) on page 165

2.1.8.2.8 SettlementInformation <SttlmInf>

Presence: [1..1]

Definition: Specifies the details on how the settlement of the transaction(s) between the instructing agent and the instructed agent is completed.

SettlementInformation <SttlmInf> contains the following elements (see [SettlementInstruction7](#) on page 117 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		SettlementMethod <SttlmMtd>	[1..1]	CodeSet		120
		SettlementAccount <SttlmAcct>	[0..1]	±		120
		ClearingSystem <ClrSys>	[0..1]			120
	{Or	Code <Cd>	[1..1]	CodeSet		121
	Or}	Proprietary <Prtry>	[1..1]	Text		121
		InstructingReimbursementAgent <InstgRmbrsmntAgt>	[0..1]	±		121
		InstructingReimbursementAgentAccount <InstgRmbrsmntAgtAcct>	[0..1]	±		121
		InstructedReimbursementAgent <InstdRmbrsmntAgt>	[0..1]	±		122
		InstructedReimbursementAgentAccount <InstdRmbrsmntAgtAcct>	[0..1]	±		122
		ThirdReimbursementAgent <ThrdRmbrsmntAgt>	[0..1]	±		123
		ThirdReimbursementAgentAccount <ThrdRmbrsmntAgtAcct>	[0..1]	±		123

2.1.8.2.9 PaymentTypeInformation <PmtTpInf>

Presence: [0..1]

Definition: Set of elements used to further specify the type of transaction.

PaymentTypeInformation <PmtTpInf> contains the following elements (see [PaymentTypeInformation28](#) on page 78 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		InstructionPriority <InstrPrty>	[0..1]	CodeSet		78
		ClearingChannel <ClrChanl>	[0..1]	CodeSet		78
		ServiceLevel <SvcLv>	[0..*]			79
	{Or	Code <Cd>	[1..1]	CodeSet		79
	Or}	Proprietary <Prtry>	[1..1]	Text		79
		LocalInstrument <LclInstrm>	[0..1]			79
	{Or	Code <Cd>	[1..1]	CodeSet		80
	Or}	Proprietary <Prtry>	[1..1]	Text		80
		CategoryPurpose <CtgyPurp>	[0..1]			80
	{Or	Code <Cd>	[1..1]	CodeSet		80
	Or}	Proprietary <Prtry>	[1..1]	Text		80

2.1.8.2.10 InstructingAgent <InstgAgt>

Presence: [0..1]

Definition: Agent that instructs the next party in the chain to carry out the (set of) instruction(s).

InstructingAgent <InstgAgt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 36 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		36
		BranchIdentification <BrnchId>	[0..1]	±		37

2.1.8.2.11 InstructedAgent <InstdAgt>

Presence: [0..1]

Definition: Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s).

InstructedAgent <InstdAgt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 36 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		36
		BranchIdentification <BrnchId>	[0..1]	±		37

2.1.8.3 SupplementaryData1

Definition: Additional information that can not be captured in the structured fields and/or any other specific block.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PlaceAndName <PlcAndNm>	[0..1]	Text		48
		Envelope <Envlp>	[1..1]	(External Schema)		49

Constraints

- **SupplementaryDataRule**

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

2.1.8.3.1 PlaceAndName <PlcAndNm>

Presence: [0..1]

Definition: Unambiguous reference to the location where the supplementary data must be inserted in the message instance.

In the case of XML, this is expressed by a valid XPath.

Datatype: [Max350Text](#) on page 171

2.1.8.3.2 Envelope <Envlp>

Presence: [1..1]

Definition: Technical element wrapping the supplementary data.

Type: (External Schema)

Technical component that contains the validated supplementary data information. This technical envelope allows to segregate the supplementary data information from any other information.

2.1.8.4 Purpose2Choice

Definition: Specifies the underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		49
	Or}	Proprietary <Prtry>	[1..1]	Text		49

2.1.8.4.1 Code <Cd>

Presence: [1..1]

Definition: Underlying reason for the payment transaction, as published in an external purpose code list.

Datatype: [ExternalPurpose1Code on page 154](#)

2.1.8.4.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Purpose, in a proprietary form.

Datatype: [Max35Text on page 171](#)

2.1.9 Organisation Identification

2.1.9.1 OrganisationIdentification29

Definition: Unique and unambiguous way to identify an organisation.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AnyBIC <AnyBIC>	[0..1]	IdentifierSet		50
		LEI <LEI>	[0..1]	IdentifierSet		50
		Other <Othr>	[0..*]			50
		Identification <Id>	[1..1]	Text		50
		SchemeName <SchmeNm>	[0..1]			51
	{Or	Code <Cd>	[1..1]	CodeSet		51
	Or}	Proprietary <Prtry>	[1..1]	Text		51
		Issuer <Issr>	[0..1]	Text		51

2.1.9.1.1 AnyBIC <AnyBIC>

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: AnyBICDec2014Identifier on page 166

2.1.9.1.2 LEI <LEI>

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: LEIIdentifier on page 167

2.1.9.1.3 Other <Othr>

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

Other <Othr> contains the following **GenericOrganisationIdentification1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		50
		SchemeName <SchmeNm>	[0..1]			51
	{Or	Code <Cd>	[1..1]	CodeSet		51
	Or}	Proprietary <Prtry>	[1..1]	Text		51
		Issuer <Issr>	[0..1]	Text		51

2.1.9.1.3.1 Identification <Id>

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: Max35Text on page 171

2.1.9.1.3.2 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Name of the identification scheme.

SchemeName <SchmeNm> contains one of the following **OrganisationIdentificationSchemeName1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		51
	Or}	Proprietary <Prtry>	[1..1]	Text		51

2.1.9.1.3.2.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: [ExternalOrganisationIdentification1Code on page 152](#)

2.1.9.1.3.2.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: [Max35Text on page 171](#)

2.1.9.1.3.3 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: [Max35Text on page 171](#)

2.1.10 Party Identification

2.1.10.1 Party38Choice

Definition: Nature or use of the account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	OrganisationIdentification <OrgId>	[1..1]	±		51
	Or}	PrivateIdentification <PrvtId>	[1..1]	±		52

2.1.10.1.1 OrganisationIdentification <OrgId>

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

OrganisationIdentification <OrgId> contains the following elements (see [OrganisationIdentification29](#) on page 49 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AnyBIC <AnyBIC>	[0..1]	IdentifierSet		50
		LEI <LEI>	[0..1]	IdentifierSet		50
		Other <Othr>	[0..*]			50
		Identification <Id>	[1..1]	Text		50
		SchemeName <SchmeNm>	[0..1]			51
	{Or	Code <Cd>	[1..1]	CodeSet		51
	Or}	Proprietary <Prtry>	[1..1]	Text		51
		Issuer <Issr>	[0..1]	Text		51

2.1.10.1.2 PrivateIdentification <PrvtId>

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

PrivateIdentification <PrvtId> contains the following elements (see [PersonIdentification13](#) on page 80 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DateAndPlaceOfBirth <DtAndPlcOfBirth>	[0..1]			81
		BirthDate <BirthDt>	[1..1]	Date		81
		ProvinceOfBirth <PrvcOfBirth>	[0..1]	Text		81
		CityOfBirth <CityOfBirth>	[1..1]	Text		81
		CountryOfBirth <CtryOfBirth>	[1..1]	CodeSet		82
		Other <Othr>	[0..*]			82
		Identification <Id>	[1..1]	Text		82
		SchemeName <SchmeNm>	[0..1]			82
	{Or	Code <Cd>	[1..1]	CodeSet		82
	Or}	Proprietary <Prtry>	[1..1]	Text		83
		Issuer <Issr>	[0..1]	Text		83

2.1.10.2 PartyIdentification135

Definition: Specifies the identification of a person or an organisation.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		53
		PostalAddress <PstlAdr>	[0..1]	±		53
		Identification <Id>	[0..1]	±		54
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		54
		ContactDetails <CtctDtls>	[0..1]	±		55

2.1.10.2.1 Name <Nm>

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: Max140Text on page 170

2.1.10.2.2 PostalAddress <PstlAdr>

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

PostalAddress <PstlAdr> contains the following elements (see [PostalAddress24](#) on page 86 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AddressType <AdrTp>	[0..1]			86
	{Or	Code <Cd>	[1..1]	CodeSet		87
	Or}	Proprietary <Prtry>	[1..1]	±		87
		Department <Dept>	[0..1]	Text		87
		SubDepartment <SubDept>	[0..1]	Text		87
		StreetName <StrtNm>	[0..1]	Text		88
		BuildingNumber <BldgNb>	[0..1]	Text		88
		BuildingName <BldgNm>	[0..1]	Text		88
		Floor <Flr>	[0..1]	Text		88
		PostBox <PstBx>	[0..1]	Text		88
		Room <Room>	[0..1]	Text		88
		PostCode <PstCd>	[0..1]	Text		88
		TownName <TwnNm>	[0..1]	Text		88
		TownLocationName <TwnLctnNm>	[0..1]	Text		89
		DistrictName <DstrctNm>	[0..1]	Text		89
		CountrySubDivision <CtrySubDvsn>	[0..1]	Text		89
		Country <Ctry>	[0..1]	CodeSet		89
		AddressLine <AdrLine>	[0..7]	Text		89

2.1.10.2.3 Identification <Id>

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

Identification <Id> contains one of the following elements (see [Party38Choice](#) on page 51 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	OrganisationIdentification <OrgId>	[1..1]	±		51
	Or}	PrivateIdentification <PrvtId>	[1..1]	±		52

2.1.10.2.4 CountryOfResidence <CtryOfRes>

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: [CountryCode](#) on page 142

2.1.10.2.5 ContactDetails <CtctDtls>

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

ContactDetails <CtctDtls> contains the following elements (see [Contact4](#) on page 83 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		NamePrefix <NmPrfx>	[0..1]	CodeSet		83
		Name <Nm>	[0..1]	Text		84
		PhoneNumber <PhneNb>	[0..1]	Text		84
		MobileNumber <MobNb>	[0..1]	Text		84
		FaxNumber <FaxNb>	[0..1]	Text		84
		EmailAddress <EmailAdr>	[0..1]	Text		84
		EmailPurpose <EmailPurp>	[0..1]	Text		84
		JobTitle <JobTitl>	[0..1]	Text		84
		Responsibility <Rspnsblty>	[0..1]	Text		85
		Department <Dept>	[0..1]	Text		85
		Other <Othr>	[0..*]			85
		ChannelType <ChanlTp>	[1..1]	Text		85
		Identification <Id>	[0..1]	Text		85
		PreferredMethod <PrefrdMtd>	[0..1]	CodeSet		85

2.1.11 Payment

2.1.11.1 SettlementTimeRequest2

Definition: Provides information on the requested settlement time(s) of the payment instruction.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CLSTime <CLSTm>	[0..1]	Time		55
		TillTime <TillTm>	[0..1]	Time		56
		FromTime <FrTm>	[0..1]	Time		56
		RejectTime <RjctTm>	[0..1]	Time		56

2.1.11.1.1 CLSTime <CLSTm>

Presence: [0..1]

Definition: Time by which the amount of money must be credited, with confirmation, to the CLS Bank's account at the central bank.

Usage: Time must be expressed in Central European Time (CET).

Datatype: [ISOTime on page 172](#)

2.1.11.1.2 TillTime <TillTm>

Presence: [0..1]

Definition: Time until when the payment may be settled.

Datatype: [ISOTime on page 172](#)

2.1.11.1.3 FromTime <FrTm>

Presence: [0..1]

Definition: Time as from when the payment may be settled.

Datatype: [ISOTime on page 172](#)

2.1.11.1.4 RejectTime <RjctTm>

Presence: [0..1]

Definition: Time by when the payment must be settled to avoid rejection.

Datatype: [ISOTime on page 172](#)

2.1.11.2 InstructionForCreditorAgent1

Definition: Further information related to the processing of the payment instruction that may need to be acted upon by the creditor's agent. The instruction may relate to a level of service, or may be an instruction that has to be executed by the creditor's agent, or may be information required by the creditor's agent.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Code <Cd>	[0..1]	CodeSet		56
		InstructionInformation <InstrInf>	[0..1]	Text		57

2.1.11.2.1 Code <Cd>

Presence: [0..1]

Definition: Coded information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor's agent.

Datatype: [Instruction3Code on page 156](#)

CodeName	Name	Definition
CHQB	PayCreditorByCheque	(Ultimate) creditor must be paid by cheque.
HOLD	HoldCashForCreditor	Amount of money must be held for the (ultimate) creditor, who will call. Pay on identification.

CodeName	Name	Definition
PHOB	PhoneBeneficiary	Please advise/contact (ultimate) creditor/claimant by phone.
TELB	Telecom	Please advise/contact (ultimate) creditor/claimant by the most efficient means of telecommunication.

2.1.11.2.2 InstructionInformation <InstrInf>

Presence: [0..1]

Definition: Further information complementing the coded instruction or instruction to the creditor's agent that is bilaterally agreed or specific to a user community.

Datatype: [Max140Text on page 170](#)

2.1.11.3 CreditTransferTransaction39

Definition: Provides further details specific to the individual transaction(s) included in the message.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PaymentIdentification <PmtId>	[1..1]	±		63
		PaymentTypeInfoInformation <PmtTplnf>	[0..1]	±		63
		InterbankSettlementAmount <IntrBkSttlmAmt>	[1..1]	Amount		64
		InterbankSettlementDate <IntrBkSttlmDt>	[0..1]	Date		64
		SettlementPriority <SttlmPrty>	[0..1]	CodeSet		64
		SettlementTimeIndication <SttlmTmIndctn>	[0..1]			64
		DebitDateTime <DbtDtTm>	[0..1]	DateTime		64
		CreditDateTime <CdtDtTm>	[0..1]	DateTime		64
		SettlementTimeRequest <SttlmTmReq>	[0..1]	±		65
		AcceptanceDateTime <AcceptncDtTm>	[0..1]	DateTime		65
		PoolingAdjustmentDate <PoolgAdjstmntDt>	[0..1]	Date		65
		InstructedAmount <InstdAmt>	[0..1]	Amount		65
		ExchangeRate <XchgRate>	[0..1]	Rate		65
		ChargeBearer <ChrgBr>	[1..1]	CodeSet		66
		ChargesInformation <ChrgsInf>	[0..*]	±		66
		PreviousInstructingAgent1 <PrvsInstgAgt1>	[0..1]	±		66
		PreviousInstructingAgent1Account <PrvsInstgAgt1Acct>	[0..1]	±		67
		PreviousInstructingAgent2 <PrvsInstgAgt2>	[0..1]	±		67
		PreviousInstructingAgent2Account <PrvsInstgAgt2Acct>	[0..1]	±		67
		PreviousInstructingAgent3 <PrvsInstgAgt3>	[0..1]	±		68
		PreviousInstructingAgent3Account <PrvsInstgAgt3Acct>	[0..1]	±		68
		InstructingAgent <InstgAgt>	[0..1]	±		68
		InstructedAgent <InstdAgt>	[0..1]	±		68
		IntermediaryAgent1 <IntrmyAgt1>	[0..1]	±		69
		IntermediaryAgent1Account <IntrmyAgt1Acct>	[0..1]	±		69
		IntermediaryAgent2 <IntrmyAgt2>	[0..1]	±		69
		IntermediaryAgent2Account <IntrmyAgt2Acct>	[0..1]	±		70
		IntermediaryAgent3 <IntrmyAgt3>	[0..1]	±		70
		IntermediaryAgent3Account <IntrmyAgt3Acct>	[0..1]	±		70
		UltimateDebtor <UltmtDbtr>	[0..1]	±		71

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		InitiatingParty <InitgPty>	[0..1]	±		71
		Debtor <Dbtr>	[1..1]	±		72
		DebtorAccount <DbtrAcct>	[0..1]	±		72
		DebtorAgent <DbtrAgt>	[1..1]	±		72
		DebtorAgentAccount <DbtrAgtAcct>	[0..1]	±		72
		CreditorAgent <CdtrAgt>	[1..1]	±		73
		CreditorAgentAccount <CdtrAgtAcct>	[0..1]	±		73
		Creditor <Cdtr>	[1..1]	±		73
		CreditorAccount <CdtrAcct>	[0..1]	±		74
		UltimateCreditor <UltmtCdtr>	[0..1]	±		74
		InstructionForCreditorAgent <InstrForCdtrAgt>	[0..*]	±		74
		InstructionForNextAgent <InstrForNxtAgt>	[0..*]			75
		Code <Cd>	[0..1]	CodeSet		75
		InstructionInformation <InstrInf>	[0..1]	Text		75
		Purpose <Purp>	[0..1]	±		76
		RegulatoryReporting <RgltryRptg>	[0..10]	±		76
		Tax <Tax>	[0..1]	±		76
		RelatedRemittanceInformation <RltdRmtInf>	[0..10]	±		77
		RemittanceInformation <RmtInf>	[0..1]	±		77
		SupplementaryData <SplmtryData>	[0..*]	±		77

Constraints

• ChargeBearerAndChargesInformationRule

If ChargeBearer contains DEBT, then ChargesInformation may be present to communicate charges that have been added for (the) InstructedAgent(s).

If ChargeBearer contains CRED, then at least one occurrence of ChargesInformation must be present to communicate charges that have been deducted from the InstructedAmount by (the) InstructingAgent(s).

If ChargeBearer contains SHAR or SLEV, then ChargesInformation is optional.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00046
- *Error Text:* Invalid message content for charge bearer and charges information.

- **ChargesAmountGuideline**

If ChargesInformation is present, then the currency of ChargesInformation/ChargesAmount is recommended to be the same as the currency of InterbankSettlementAmount.

- **ChargesInformationAndInstructedAmountRule**

If ChargesInformation is present, then InstructedAmount must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00048
- *Error Text:* Invalid message content for instructed amount when charges information is present.

- **ChargesInformationGuideline**

The repetitive ChargesInformation should contain all information on charges amount and which party has taken the charges, separately for each agent along the payment chain.

- **InstructedAmountAndExchangeRate1Rule**

If InstructedAmount is present and the currency is different from the currency in InterbankSettlementAmount, then ExchangeRate must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00049
- *Error Text:* Invalid message content for exchange rate when instructed amount is present.

- **InstructedAmountAndExchangeRate2Rule**

If InstructedAmount is present and the currency is the same as the currency in InterbankSettlementAmount, then ExchangeRate is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00050
- *Error Text:* Invalid message content for exchange rate when instructed amount is not present.

- **InstructedAmountAndExchangeRate3Rule**

If InstructedAmount is not present, then ExchangeRate is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00061
- *Error Text:* Invalid message content for exchange rate and instructed amount.

- **InstructionForCreditorAgentRule**

If InstructionForCreditorAgent/Code contains CHQB (PayCreditorByCheque), then CreditorAccount is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00051
- *Error Text:* Invalid message content for PayCreditorByCheque instruction for creditor agent.

- **IntermediaryAgent1AccountRule**

If IntermediaryAgent1Account is present, then IntermediaryAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00052
- *Error Text:* Invalid message content for intermediary agent 1 account.

- **IntermediaryAgent2AccountRule**

If IntermediaryAgent2Account is present, then IntermediaryAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00053
- *Error Text:* Invalid message content for intermediary agent 2 account.

- **IntermediaryAgent2Rule**

If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00056
- *Error Text:* Invalid message content for intermediary agent 2.

- **IntermediaryAgent3AccountRule**

If IntermediaryAgent3Account is present, then IntermediaryAgent3 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00054
- *Error Text:* Invalid message content for intermediary agent 3 account.

- **IntermediaryAgent3Rule**

If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00057

– *Error Text:* Invalid message content for intermediary agent 3.

- **PreviousInstructingAgent1AccountRule**

If PreviousInstructingAgent1Account is present, then PreviousInstructingAgent1 must be present.

Error handling:

– *Error severity:* Fatal

– *Error Code:* X00411

– *Error Text:* Invalid message content for previous instructing agent account.

- **PreviousInstructingAgent1Guideline**

It is recommended that, when present, PreviousInstructingAgent1 is the closest to the DebtorAgent in the payment chain.

- **PreviousInstructingAgent2AccountRule**

If PreviousInstructingAgent2Account is present, then PreviousInstructingAgent2 must be present.

Error handling:

– *Error severity:* Fatal

– *Error Code:* X00412

– *Error Text:* Invalid message content for previous instructing agent account.

- **PreviousInstructingAgent3AccountRule**

If PreviousInstructingAgent3Account is present, then PreviousInstructingAgent3 must be present.

Error handling:

– *Error severity:* Fatal

– *Error Code:* X00413

– *Error Text:* Invalid message content for previous instructing agent account.

- **PreviousInstructionAgent2Rule**

If PreviousInstructingAgent2 is present, then PreviousInstructingAgent1 must be present.

Error handling:

– *Error severity:* Fatal

– *Error Code:* X00415

– *Error Text:* Invalid message content for intermediary agent 1.

- **PreviousInstructionAgent3Rule**

If PreviousInstructingAgent3 is present, then PreviousInstructingAgent2 must be present.

Error handling:

– *Error severity:* Fatal

– *Error Code:* X00416

– *Error Text:* Invalid message content for intermediary agent 1.

- **UltimateCreditorGuideline**

UltimateCreditor may only be present if different from Creditor.

- **UltimateDebtorGuideline**

UltimateDebtor may only be present if different from Debtor.

2.1.11.3.1 PaymentIdentification <PmtId>

Presence: [1..1]

Definition: Set of elements used to reference a payment instruction.

PaymentIdentification <PmtId> contains the following elements (see [PaymentIdentification7](#) on page 38 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		InstructionIdentification <InstrId>	[0..1]	Text		39
		EndToEndIdentification <EndToEndId>	[1..1]	Text		39
		TransactionIdentification <TxId>	[0..1]	Text		39
		UETR <UETR>	[0..1]	IdentifierSet		40
		ClearingSystemReference <ClrSysRef>	[0..1]	Text		40

2.1.11.3.2 PaymentTypeInformation <PmtTpInf>

Presence: [0..1]

Definition: Set of elements used to further specify the type of transaction.

PaymentTypeInformation <PmtTpInf> contains the following elements (see [PaymentTypeInformation28](#) on page 78 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		InstructionPriority <InstrPrty>	[0..1]	CodeSet		78
		ClearingChannel <ClrChanl>	[0..1]	CodeSet		78
		ServiceLevel <SvcLvl>	[0..*]			79
	{Or	Code <Cd>	[1..1]	CodeSet		79
	Or}	Proprietary <Prtry>	[1..1]	Text		79
		LocalInstrument <LclInstrm>	[0..1]			79
	{Or	Code <Cd>	[1..1]	CodeSet		80
	Or}	Proprietary <Prtry>	[1..1]	Text		80
		CategoryPurpose <CtgyPurp>	[0..1]			80
	{Or	Code <Cd>	[1..1]	CodeSet		80
	Or}	Proprietary <Prtry>	[1..1]	Text		80

2.1.11.3.3 InterbankSettlementAmount <IntrBkSttlmAmt>*Presence:* [1..1]*Definition:* Amount of money moved between the instructing agent and the instructed agent.*Datatype:* ActiveCurrencyAndAmount on page 136**2.1.11.3.4 InterbankSettlementDate <IntrBkSttlmDt>***Presence:* [0..1]*Definition:* Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.*Datatype:* ISODate on page 165**2.1.11.3.5 SettlementPriority <SttlmPrty>***Presence:* [0..1]*Definition:* Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the settlement instruction.*Datatype:* Priority3Code on page 160

CodeName	Name	Definition
URGT	Urgent	Priority level is urgent (highest priority possible).
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

2.1.11.3.6 SettlementTimeIndication <SttlmTmIndctn>*Presence:* [0..1]*Definition:* Provides information on the occurred settlement time(s) of the payment transaction.**SettlementTimeIndication <SttlmTmIndctn>** contains the following **SettlementDateTimeIndication1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DebitDateTime <DbtDtTm>	[0..1]	DateTime		64
		CreditDateTime <CdtDtTm>	[0..1]	DateTime		64

2.1.11.3.6.1 DebitDateTime <DbtDtTm>*Presence:* [0..1]*Definition:* Date and time at which a payment has been debited at the transaction administrator. In the case of TARGET, the date and time at which the payment has been debited at the central bank, expressed in Central European Time (CET).*Datatype:* ISODatetime on page 165**2.1.11.3.6.2 CreditDateTime <CdtDtTm>***Presence:* [0..1]

Definition: Date and time at which a payment has been credited at the transaction administrator. In the case of TARGET, the date and time at which the payment has been credited at the receiving central bank, expressed in Central European Time (CET).

Datatype: [ISODatetime](#) on page 165

2.1.11.3.7 SettlementTimeRequest <SttlmTmReq>

Presence: [0..1]

Definition: Provides information on the requested settlement time(s) of the payment instruction.

SettlementTimeRequest <SttlmTmReq> contains the following elements (see [SettlementTimeRequest2](#) on page 55 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CLSTime <CLSTm>	[0..1]	Time		55
		TillTime <TillTm>	[0..1]	Time		56
		FromTime <FrTm>	[0..1]	Time		56
		RejectTime <RjctTm>	[0..1]	Time		56

2.1.11.3.8 AcceptanceDateTime <AcceptncDtTm>

Presence: [0..1]

Definition: Point in time when the payment order from the initiating party meets the processing conditions of the account servicing agent. This means that the account servicing agent has received the payment order and has applied checks such as authorisation, availability of funds.

Datatype: [ISODatetime](#) on page 165

2.1.11.3.9 PoolingAdjustmentDate <PoolgAdjstmntDt>

Presence: [0..1]

Definition: Date used for the correction of the value date of a cash pool movement that has been posted with a different value date.

Datatype: [ISODate](#) on page 165

2.1.11.3.10 InstructedAmount <InstdAmt>

Presence: [0..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

Usage: This amount has to be transported unchanged through the transaction chain.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 137

2.1.11.3.11 ExchangeRate <XchgRate>

Presence: [0..1]

Definition: Factor used to convert an amount from one currency into another. This reflects the price at which one currency was bought with another currency.

Datatype: [BaseOneRate](#) on page 169

2.1.11.3.12 ChargeBearer <ChrgBr>

Presence: [1..1]

Definition: Specifies which party/parties will bear the charges associated with the processing of the payment transaction.

Datatype: [ChargeBearerType1Code](#) on page 140

CodeName	Name	Definition
DEBT	BorneByDebtor	All transaction charges are to be borne by the debtor.
CRED	BorneByCreditor	All transaction charges are to be borne by the creditor.
SHAR	Shared	In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor.
SLEV	FollowingServiceLevel	Charges are to be applied following the rules agreed in the service level and/or scheme.

2.1.11.3.13 ChargesInformation <ChrgsInf>

Presence: [0..*]

Definition: Provides information on the charges to be paid by the charge bearer(s) related to the payment transaction.

ChargesInformation <ChrgsInf> contains the following elements (see [Charges7](#) on page 28 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Amount		29
		Agent <Agt>	[1..1]	±		29

2.1.11.3.14 PreviousInstructingAgent1 <PrvsInstgAgt1>

Presence: [0..1]

Definition: Agent immediately prior to the instructing agent.

PreviousInstructingAgent1 <PrvsInstgAgt1> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 36 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		36
		BranchIdentification <BrnchId>	[0..1]	±		37

2.1.11.3.15 PreviousInstructingAgent1Account <PrvsInstgAgt1Acct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain.

PreviousInstructingAgent1Account <PrvsInstgAgt1Acct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.11.3.16 PreviousInstructingAgent2 <PrvsInstgAgt2>

Presence: [0..1]

Definition: Agent immediately prior to the instructing agent.

PreviousInstructingAgent2 <PrvsInstgAgt2> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 36 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		36
		BranchIdentification <BrnchId>	[0..1]	±		37

2.1.11.3.17 PreviousInstructingAgent2Account <PrvsInstgAgt2Acct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain.

PreviousInstructingAgent2Account <PrvsInstgAgt2Acct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.11.3.18 PreviousInstructingAgent3 <PrvsInstgAgt3>*Presence:* [0..1]*Definition:* Agent immediately prior to the instructing agent.**PreviousInstructingAgent3 <PrvsInstgAgt3>** contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 36 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		36
		BranchIdentification <BrnchId>	[0..1]	±		37

2.1.11.3.19 PreviousInstructingAgent3Account <PrvsInstgAgt3Acct>*Presence:* [0..1]*Definition:* Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain.**PreviousInstructingAgent3Account <PrvsInstgAgt3Acct>** contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.11.3.20 InstructingAgent <InstgAgt>*Presence:* [0..1]*Definition:* Agent that instructs the next party in the chain to carry out the (set of) instruction(s).**InstructingAgent <InstgAgt>** contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 36 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		36
		BranchIdentification <BrnchId>	[0..1]	±		37

2.1.11.3.21 InstructedAgent <InstdAgt>*Presence:* [0..1]*Definition:* Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s).

InstructedAgent <InstdAgt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 36 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		36
		BranchIdentification <BrnchId>	[0..1]	±		37

2.1.11.3.22 IntermediaryAgent1 <IntrmyAgt1>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than one intermediary agent is present, then IntermediaryAgent1 identifies the agent between the DebtorAgent and the IntermediaryAgent2.

IntermediaryAgent1 <IntrmyAgt1> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 36 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		36
		BranchIdentification <BrnchId>	[0..1]	±		37

2.1.11.3.23 IntermediaryAgent1Account <IntrmyAgt1Acct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 1 at its servicing agent in the payment chain.

IntermediaryAgent1Account <IntrmyAgt1Acct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.11.3.24 IntermediaryAgent2 <IntrmyAgt2>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than two intermediary agents are present, then IntermediaryAgent2 identifies the agent between the IntermediaryAgent1 and the IntermediaryAgent3.

IntermediaryAgent2 <IntrmyAgt2> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 36 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		36
		BranchIdentification <BrnchId>	[0..1]	±		37

2.1.11.3.25 IntermediaryAgent2Account <IntrmyAgt2Acct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 2 at its servicing agent in the payment chain.

IntermediaryAgent2Account <IntrmyAgt2Acct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.11.3.26 IntermediaryAgent3 <IntrmyAgt3>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If IntermediaryAgent3 is present, then it identifies the agent between the IntermediaryAgent 2 and the CreditorAgent.

IntermediaryAgent3 <IntrmyAgt3> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 36 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		36
		BranchIdentification <BrnchId>	[0..1]	±		37

2.1.11.3.27 IntermediaryAgent3Account <IntrmyAgt3Acct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 3 at its servicing agent in the payment chain.

IntermediaryAgent3Account <IntrmyAgt3Acct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.11.3.28 UltimateDebtor <UltmtDbtr>

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor.

UltimateDebtor <UltmtDbtr> contains the following elements (see [PartyIdentification135](#) on page 52 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		53
		PostalAddress <PstlAdr>	[0..1]	±		53
		Identification <Id>	[0..1]	±		54
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		54
		ContactDetails <CtctDtls>	[0..1]	±		55

2.1.11.3.29 InitiatingParty <InitgPty>

Presence: [0..1]

Definition: Party that initiates the payment.

Usage: This can be either the debtor or a party that initiates the credit transfer on behalf of the debtor.

InitiatingParty <InitgPty> contains the following elements (see [PartyIdentification135](#) on page 52 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		53
		PostalAddress <PstlAdr>	[0..1]	±		53
		Identification <Id>	[0..1]	±		54
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		54
		ContactDetails <CtctDtls>	[0..1]	±		55

2.1.11.3.30 Debtor <Dbtr>*Presence:* [1..1]*Definition:* Party that owes an amount of money to the (ultimate) creditor.**Debtor <Dbtr>** contains the following elements (see [PartyIdentification135](#) on page 52 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		53
		PostalAddress <PstlAdr>	[0..1]	±		53
		Identification <Id>	[0..1]	±		54
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		54
		ContactDetails <CtctDtls>	[0..1]	±		55

2.1.11.3.31 DebtorAccount <DbtrAcct>*Presence:* [0..1]*Definition:* Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.**DebtorAccount <DbtrAcct>** contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.11.3.32 DebtorAgent <DbtrAgt>*Presence:* [1..1]*Definition:* Financial institution servicing an account for the debtor.**DebtorAgent <DbtrAgt>** contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 36 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		36
		BranchIdentification <BrnchId>	[0..1]	±		37

2.1.11.3.33 DebtorAgentAccount <DbtrAgtAcct>*Presence:* [0..1]

Definition: Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain.

DebtorAgentAccount <DbtrAgtAcct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.11.3.34 CreditorAgent <CdtrAgt>

Presence: [1..1]

Definition: Financial institution servicing an account for the creditor.

CreditorAgent <CdtrAgt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 36 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		36
		BranchIdentification <BrnchId>	[0..1]	±		37

2.1.11.3.35 CreditorAgentAccount <CdtrAgtAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction.

CreditorAgentAccount <CdtrAgtAcct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.11.3.36 Creditor <Cdtr>

Presence: [1..1]

Definition: Party to which an amount of money is due.

Creditor <Cdtr> contains the following elements (see [PartyIdentification135](#) on page 52 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		53
		PostalAddress <PstlAdr>	[0..1]	±		53
		Identification <Id>	[0..1]	±		54
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		54
		ContactDetails <CtctDtls>	[0..1]	±		55

2.1.11.3.37 CreditorAccount <CdtrAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.

CreditorAccount <CdtrAcct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.11.3.38 UltimateCreditor <UltmtCdtr>

Presence: [0..1]

Definition: Ultimate party to which an amount of money is due.

UltimateCreditor <UltmtCdtr> contains the following elements (see [PartyIdentification135](#) on page 52 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		53
		PostalAddress <PstlAdr>	[0..1]	±		53
		Identification <Id>	[0..1]	±		54
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		54
		ContactDetails <CtctDtls>	[0..1]	±		55

2.1.11.3.39 InstructionForCreditorAgent <InstrForCdtrAgt>

Presence: [0..*]

Definition: Further information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor agent.

InstructionForCreditorAgent <InstrForCdtrAgt> contains the following elements (see [InstructionForCreditorAgent1](#) on page 56 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Code <Cd>	[0..1]	CodeSet		56
		InstructionInformation <InstrInf>	[0..1]	Text		57

2.1.11.3.40 InstructionForNextAgent <InstrForNxtAgt>

Presence: [0..*]

Definition: Further information related to the processing of the payment instruction that may need to be acted upon by the next agent.

Usage: The next agent may not be the creditor agent.

The instruction can relate to a level of service, can be an instruction that has to be executed by the agent, or can be information required by the next agent.

InstructionForNextAgent <InstrForNxtAgt> contains the following **InstructionForNextAgent1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Code <Cd>	[0..1]	CodeSet		75
		InstructionInformation <InstrInf>	[0..1]	Text		75

2.1.11.3.40.1 Code <Cd>

Presence: [0..1]

Definition: Coded information related to the processing of the payment instruction, provided by the initiating party, and intended for the next agent in the payment chain.

Datatype: [Instruction4Code](#) on page 157

CodeName	Name	Definition
PHOA	PhoneNextAgent	Please advise/contact next agent by phone.
TELA	TelecomNextAgent	Please advise/contact next agent by the most efficient means of telecommunication.

2.1.11.3.40.2 InstructionInformation <InstrInf>

Presence: [0..1]

Definition: Further information complementing the coded instruction or instruction to the next agent that is bilaterally agreed or specific to a user community.

Datatype: [Max140Text](#) on page 170

2.1.11.3.41 Purpose <Purp>

Presence: [0..1]

Definition: Underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

Purpose <Purp> contains one of the following elements (see [Purpose2Choice](#) on page 49 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		49
	Or}	Proprietary <Prtry>	[1..1]	Text		49

2.1.11.3.42 RegulatoryReporting <RgltryRptg>

Presence: [0..10]

Definition: Information needed due to regulatory and statutory requirements.

RegulatoryReporting <RgltryRptg> contains the following elements (see [RegulatoryReporting3](#) on page 89 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DebitCreditReportingIndicator <DbtCdtRptgInd>	[0..1]	CodeSet		90
		Authority <Authrty>	[0..1]			90
		Name <Nm>	[0..1]	Text		90
		Country <Ctry>	[0..1]	CodeSet		91
		Details <Dtls>	[0..*]			91
		Type <Tp>	[0..1]	Text		91
		Date <Dt>	[0..1]	Date		91
		Country <Ctry>	[0..1]	CodeSet		91
		Code <Cd>	[0..1]	Text		91
		Amount <Amt>	[0..1]	Amount		92
		Information <Inf>	[0..*]	Text		92

2.1.11.3.43 Tax <Tax>

Presence: [0..1]

Definition: Provides details on the tax.

Tax <Tax> contains the following elements (see [TaxInformation8](#) on page 129 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Creditor <Cdtr>	[0..1]	±		130
		Debtor <Dbtr>	[0..1]	±		130
		AdministrationZone <AdmstnZone>	[0..1]	Text		131
		ReferenceNumber <RefNb>	[0..1]	Text		131
		Method <Mtd>	[0..1]	Text		131
		TotalTaxableBaseAmount <TtlTaxblBaseAmt>	[0..1]	Amount		131
		TotalTaxAmount <TtlTaxAmt>	[0..1]	Amount		131
		Date <Dt>	[0..1]	Date		131
		SequenceNumber <SeqNb>	[0..1]	Quantity		131
		Record <Rcrd>	[0..*]	±		131

2.1.11.3.44 RelatedRemittanceInformation <RltdRmtInf>

Presence: [0..10]

Definition: Provides information related to the handling of the remittance information by any of the agents in the transaction processing chain.

RelatedRemittanceInformation <RltdRmtInf> contains the following elements (see [RemittanceLocation7](#) on page 114 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		RemittanceIdentification <RmtId>	[0..1]	Text		114
		RemittanceLocationDetails <RmtLctnDtls>	[0..*]	±		114

2.1.11.3.45 RemittanceInformation <RmtInf>

Presence: [0..1]

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.

RemittanceInformation <RmtInf> contains the following elements (see [RemittanceInformation16](#) on page 95 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Unstructured <Ustrd>	[0..*]	Text		95
		Structured <Strd>	[0..*]	±		95

2.1.11.3.46 SupplementaryData <SplmtryData>

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

SupplementaryData <SplmtryData> contains the following elements (see [SupplementaryData1](#) on page 48 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PlaceAndName <PlcAndNm>	[0..1]	Text		48
		Envelope <Envlp>	[1..1]	(External Schema)		49

2.1.12 Payment Type

2.1.12.1 PaymentTypeInfoInformation28

Definition: Provides further details of the type of payment.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		InstructionPriority <InstrPrty>	[0..1]	CodeSet		78
		ClearingChannel <ClrChanl>	[0..1]	CodeSet		78
		ServiceLevel <SvcLv>	[0..*]			79
	{Or	Code <Cd>	[1..1]	CodeSet		79
	Or}	Proprietary <Prtry>	[1..1]	Text		79
		LocalInstrument <LclInstrm>	[0..1]			79
	{Or	Code <Cd>	[1..1]	CodeSet		80
	Or}	Proprietary <Prtry>	[1..1]	Text		80
		CategoryPurpose <CtgyPurp>	[0..1]			80
	{Or	Code <Cd>	[1..1]	CodeSet		80
	Or}	Proprietary <Prtry>	[1..1]	Text		80

2.1.12.1.1 InstructionPriority <InstrPrty>

Presence: [0..1]

Definition: Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction.

Datatype: [Priority2Code](#) on page 159

CodeName	Name	Definition
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

2.1.12.1.2 ClearingChannel <ClrChanl>

Presence: [0..1]

Definition: Specifies the clearing channel to be used to process the payment instruction.

Datatype: [ClearingChannel2Code](#) on page 141

CodeName	Name	Definition
RTGS	RealTimeGrossSettlementSystem	Clearing channel is a real-time gross settlement system.
RTNS	RealTimeNetSettlementSystem	Clearing channel is a real-time net settlement system.
MPNS	MassPaymentNetSystem	Clearing channel is a mass payment net settlement system.
BOOK	BookTransfer	Payment through internal book transfer.

2.1.12.1.3 ServiceLevel <SvcLvl>

Presence: [0..*]

Definition: Agreement under which or rules under which the transaction should be processed.

ServiceLevel <SvcLvl> contains one of the following **ServiceLevel8Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		79
	Or}	Proprietary <Prtry>	[1..1]	Text		79

2.1.12.1.3.1 Code <Cd>

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list.

Datatype: [ExternalServiceLevel1Code](#) on page 155

2.1.12.1.3.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as a proprietary code.

Datatype: [Max35Text](#) on page 171

2.1.12.1.4 LocalInstrument <LclInstrm>

Presence: [0..1]

Definition: User community specific instrument.

Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.

LocalInstrument <LclInstrm> contains one of the following **LocalInstrument2Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		80
	Or}	Proprietary <Prtry>	[1..1]	Text		80

2.1.12.1.4.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the local instrument, as published in an external local instrument code list.

Datatype: [ExternalLocalInstrument1Code on page 151](#)

2.1.12.1.4.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies the local instrument, as a proprietary code.

Datatype: [Max35Text on page 171](#)

2.1.12.1.5 CategoryPurpose <CtgyPurp>

Presence: [0..1]

Definition: Specifies the high level purpose of the instruction based on a set of pre-defined categories.

Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.

CategoryPurpose <CtgyPurp> contains one of the following **CategoryPurpose1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		80
	Or}	Proprietary <Prtry>	[1..1]	Text		80

2.1.12.1.5.1 Code <Cd>

Presence: [1..1]

Definition: Category purpose, as published in an external category purpose code list.

Datatype: [ExternalCategoryPurpose1Code on page 148](#)

2.1.12.1.5.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Category purpose, in a proprietary form.

Datatype: [Max35Text on page 171](#)

2.1.13 Person Identification

2.1.13.1 PersonIdentification13

Definition: Unique and unambiguous way to identify a person.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DateAndPlaceOfBirth <DtAndPlcOfBirth>	[0..1]			81
		BirthDate <BirthDt>	[1..1]	Date		81
		ProvinceOfBirth <PrvcOfBirth>	[0..1]	Text		81
		CityOfBirth <CityOfBirth>	[1..1]	Text		81
		CountryOfBirth <CtryOfBirth>	[1..1]	CodeSet		82
		Other <Othr>	[0..*]			82
		Identification <Id>	[1..1]	Text		82
		SchemeName <SchmeNm>	[0..1]			82
	{Or	Code <Cd>	[1..1]	CodeSet		82
	Or}	Proprietary <Prtry>	[1..1]	Text		83
		Issuer <Issr>	[0..1]	Text		83

2.1.13.1.1 DateAndPlaceOfBirth <DtAndPlcOfBirth>

Presence: [0..1]

Definition: Date and place of birth of a person.

DateAndPlaceOfBirth <DtAndPlcOfBirth> contains the following **DateAndPlaceOfBirth1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		BirthDate <BirthDt>	[1..1]	Date		81
		ProvinceOfBirth <PrvcOfBirth>	[0..1]	Text		81
		CityOfBirth <CityOfBirth>	[1..1]	Text		81
		CountryOfBirth <CtryOfBirth>	[1..1]	CodeSet		82

2.1.13.1.1.1 BirthDate <BirthDt>

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: [ISODate](#) on page 165

2.1.13.1.1.2 ProvinceOfBirth <PrvcOfBirth>

Presence: [0..1]

Definition: Province where a person was born.

Datatype: [Max35Text](#) on page 171

2.1.13.1.1.3 CityOfBirth <CityOfBirth>

Presence: [1..1]

Definition: City where a person was born.

Datatype: [Max35Text on page 171](#)

2.1.13.1.1.4 CountryOfBirth <CtryOfBirth>

Presence: [1..1]

Definition: Country where a person was born.

Datatype: [CountryCode on page 142](#)

2.1.13.1.2 Other <Othr>

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

Other <Othr> contains the following **GenericPersonIdentification1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		82
		SchemeName <SchmeNm>	[0..1]			82
	{Or	Code <Cd>	[1..1]	CodeSet		82
	Or}	Proprietary <Prtry>	[1..1]	Text		83
		Issuer <Issr>	[0..1]	Text		83

2.1.13.1.2.1 Identification <Id>

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: [Max35Text on page 171](#)

2.1.13.1.2.2 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Name of the identification scheme.

SchemeName <SchmeNm> contains one of the following **PersonIdentificationSchemeName1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		82
	Or}	Proprietary <Prtry>	[1..1]	Text		83

2.1.13.1.2.2.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: [ExternalPersonIdentification1Code on page 153](#)

2.1.13.1.2.2.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: [Max35Text on page 171](#)

2.1.13.1.2.3 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: [Max35Text on page 171](#)

2.1.13.2 Contact4

Definition: Specifies the details of the contact person.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		NamePrefix <NmPrfx>	[0..1]	CodeSet		83
		Name <Nm>	[0..1]	Text		84
		PhoneNumber <PhneNb>	[0..1]	Text		84
		MobileNumber <MobNb>	[0..1]	Text		84
		FaxNumber <FaxNb>	[0..1]	Text		84
		EmailAddress <EmailAdr>	[0..1]	Text		84
		EmailPurpose <EmailPurp>	[0..1]	Text		84
		JobTitle <JobTitl>	[0..1]	Text		84
		Responsibility <Rspnsblty>	[0..1]	Text		85
		Department <Dept>	[0..1]	Text		85
		Other <Othr>	[0..*]			85
		ChannelType <ChanITp>	[1..1]	Text		85
		Identification <Id>	[0..1]	Text		85
		PreferredMethod <PrefrdMtd>	[0..1]	CodeSet		85

2.1.13.2.1 NamePrefix <NmPrfx>

Presence: [0..1]

Definition: Specifies the terms used to formally address a person.

Datatype: [NamePrefix2Code on page 158](#)

CodeName	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MISS	Miss	Title of the person is Miss.

CodeName	Name	Definition
MIST	Mister	Title of the person is Mister or Mr.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).

2.1.13.2.2 Name <Nm>

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: [Max140Text on page 170](#)

2.1.13.2.3 PhoneNumber <PhneNb>

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: [PhoneNumber on page 171](#)

2.1.13.2.4 MobileNumber <MobNb>

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: [PhoneNumber on page 171](#)

2.1.13.2.5 FaxNumber <FaxNb>

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: [PhoneNumber on page 171](#)

2.1.13.2.6 EmailAddress <EmailAdr>

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: [Max2048Text on page 170](#)

2.1.13.2.7 EmailPurpose <EmailPurp>

Presence: [0..1]

Definition: Purpose for which an email address may be used.

Datatype: [Max35Text on page 171](#)

2.1.13.2.8 JobTitle <JobTitl>

Presence: [0..1]

Definition: Title of the function.

Datatype: [Max35Text on page 171](#)

2.1.13.2.9 Responsibility <Rspnsblty>

Presence: [0..1]

Definition: Role of a person in an organisation.

Datatype: [Max35Text on page 171](#)

2.1.13.2.10 Department <Dept>

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: [Max70Text on page 171](#)

2.1.13.2.11 Other <Othr>

Presence: [0..*]

Definition: Contact details in another form.

Other <Othr> contains the following **OtherContact1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ChannelType <ChanITp>	[1..1]	Text		85
		Identification <Id>	[0..1]	Text		85

2.1.13.2.11.1 ChannelType <ChanITp>

Presence: [1..1]

Definition: Method used to contact the financial institution's contact for the specific tax region.

Datatype: [Max4Text on page 171](#)

2.1.13.2.11.2 Identification <Id>

Presence: [0..1]

Definition: Communication value such as phone number or email address.

Datatype: [Max128Text on page 169](#)

2.1.13.2.12 PreferredMethod <PrefrdMtd>

Presence: [0..1]

Definition: Preferred method used to reach the contact.

Datatype: [PreferredContactMethod1Code on page 159](#)

CodeName	Name	Definition
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.

CodeName	Name	Definition
FAXX	Fax	Preferred method used to reach the contact is per fax.
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.

2.1.14 Postal Address

2.1.14.1 PostalAddress24

Definition: Information that locates and identifies a specific address, as defined by postal services.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AddressType <AdrTp>	[0..1]			86
	{Or	Code <Cd>	[1..1]	CodeSet		87
	Or}	Proprietary <Prtry>	[1..1]	±		87
		Department <Dept>	[0..1]	Text		87
		SubDepartment <SubDept>	[0..1]	Text		87
		StreetName <StrtNm>	[0..1]	Text		88
		BuildingNumber <BldgNb>	[0..1]	Text		88
		BuildingName <BldgNm>	[0..1]	Text		88
		Floor <Flr>	[0..1]	Text		88
		PostBox <PstBx>	[0..1]	Text		88
		Room <Room>	[0..1]	Text		88
		PostCode <PstCd>	[0..1]	Text		88
		TownName <TwnNm>	[0..1]	Text		88
		TownLocationName <TwnLctnNm>	[0..1]	Text		89
		DistrictName <DstrctNm>	[0..1]	Text		89
		CountrySubDivision <CtrySubDvsn>	[0..1]	Text		89
		Country <Ctry>	[0..1]	CodeSet		89
		AddressLine <AdrLine>	[0..7]	Text		89

2.1.14.1.1 AddressType <AdrTp>

Presence: [0..1]

Definition: Identifies the nature of the postal address.

AddressType <AdrTp> contains one of the following **AddressType3Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		87
	Or}	Proprietary <Prtry>	[1..1]	±		87

2.1.14.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Type of address expressed as a code.

Datatype: [AddressType2Code](#) on page 139

CodeName	Name	Definition
ADDR	Postal	Address is the complete postal address.
PBOX	POBox	Address is a postal office (PO) box.
HOME	Residential	Address is the home address.
BIZZ	Business	Address is the business address.
MLTO	MailTo	Address is the address to which mail is sent.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.

2.1.14.1.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Type of address expressed as a proprietary code.

Proprietary <Prtry> contains the following elements (see [GenericIdentification30](#) on page 38 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		38
		Issuer <Issr>	[1..1]	Text		38
		SchemeName <SchmeNm>	[0..1]	Text		38

2.1.14.1.2 Department <Dept>

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: [Max70Text](#) on page 171

2.1.14.1.3 SubDepartment <SubDept>

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: [Max70Text](#) on page 171

2.1.14.1.4 StreetName <StrtNm>

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: [Max70Text on page 171](#)

2.1.14.1.5 BuildingNumber <BldgNb>

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: [Max16Text on page 170](#)

2.1.14.1.6 BuildingName <BldgNm>

Presence: [0..1]

Definition: Name of the building or house.

Datatype: [Max35Text on page 171](#)

2.1.14.1.7 Floor <Flr>

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: [Max70Text on page 171](#)

2.1.14.1.8 PostBox <PstBx>

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: [Max16Text on page 170](#)

2.1.14.1.9 Room <Room>

Presence: [0..1]

Definition: Building room number.

Datatype: [Max70Text on page 171](#)

2.1.14.1.10 PostCode <PstCd>

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: [Max16Text on page 170](#)

2.1.14.1.11 TownName <TwnNm>

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: [Max35Text on page 171](#)

2.1.14.1.12 TownLocationName <TwnLctnNm>

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: Max35Text on page 171

2.1.14.1.13 DistrictName <DstrctNm>

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: Max35Text on page 171

2.1.14.1.14 CountrySubDivision <CtrySubDvsn>

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: Max35Text on page 171

2.1.14.1.15 Country <Ctry>

Presence: [0..1]

Definition: Nation with its own government.

Datatype: CountryCode on page 142

2.1.14.1.16 AddressLine <AdrLine>

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: Max70Text on page 171

2.1.15 Regulatory Reporting

2.1.15.1 RegulatoryReporting3

Definition: Information needed due to regulatory and/or statutory requirements.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DebitCreditReportingIndicator <DbtCdtRptgInd>	[0..1]	CodeSet		90
		Authority <Authrty>	[0..1]			90
		Name <Nm>	[0..1]	Text		90
		Country <Ctry>	[0..1]	CodeSet		91
		Details <Dtls>	[0..*]			91
		Type <Tp>	[0..1]	Text		91
		Date <Dt>	[0..1]	Date		91
		Country <Ctry>	[0..1]	CodeSet		91
		Code <Cd>	[0..1]	Text		91
		Amount <Amt>	[0..1]	Amount		92
		Information <Inf>	[0..*]	Text		92

2.1.15.1.1 DebitCreditReportingIndicator <DbtCdtRptgInd>

Presence: [0..1]

Definition: Identifies whether the regulatory reporting information applies to the debit side, to the credit side or to both debit and credit sides of the transaction.

Datatype: RegulatoryReportingType1Code on page 160

CodeName	Name	Definition
CRED	Credit	Regulatory information applies to the credit side.
DEBT	Debit	Regulatory information applies to the debit side.
BOTH	Both	Regulatory information applies to both credit and debit sides.

2.1.15.1.2 Authority <Authrty>

Presence: [0..1]

Definition: Entity requiring the regulatory reporting information.

Authority <Authrty> contains the following **RegulatoryAuthority2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		90
		Country <Ctry>	[0..1]	CodeSet		91

2.1.15.1.2.1 Name <Nm>

Presence: [0..1]

Definition: Name of the entity requiring the regulatory reporting information.

Datatype: [Max140Text on page 170](#)

2.1.15.1.2.2 Country <Ctry>

Presence: [0..1]

Definition: Country of the entity that requires the regulatory reporting information.

Datatype: [CountryCode on page 142](#)

2.1.15.1.3 Details <Dtls>

Presence: [0..*]

Definition: Set of elements used to provide details on the regulatory reporting information.

Details <Dtls> contains the following **StructuredRegulatoryReporting3** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]	Text		91
		Date <Dt>	[0..1]	Date		91
		Country <Ctry>	[0..1]	CodeSet		91
		Code <Cd>	[0..1]	Text		91
		Amount <Amt>	[0..1]	Amount		92
		Information <Inf>	[0..*]	Text		92

2.1.15.1.3.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of the information supplied in the regulatory reporting details.

Datatype: [Max35Text on page 171](#)

2.1.15.1.3.2 Date <Dt>

Presence: [0..1]

Definition: Date related to the specified type of regulatory reporting details.

Datatype: [ISODate on page 165](#)

2.1.15.1.3.3 Country <Ctry>

Presence: [0..1]

Definition: Country related to the specified type of regulatory reporting details.

Datatype: [CountryCode on page 142](#)

2.1.15.1.3.4 Code <Cd>

Presence: [0..1]

Definition: Specifies the nature, purpose, and reason for the transaction to be reported for regulatory and statutory requirements in a coded form.

Datatype: [Max10Text on page 169](#)

2.1.15.1.3.5 Amount <Amt>*Presence:* [0..1]*Definition:* Amount of money to be reported for regulatory and statutory requirements.*Datatype:* ActiveOrHistoricCurrencyAndAmount on page 137**2.1.15.1.3.6 Information <Inf>***Presence:* [0..*]*Definition:* Additional details that cater for specific domestic regulatory requirements.*Datatype:* Max35Text on page 171**2.1.16 Remittance****2.1.16.1 Garnishment3***Definition:* Provides remittance information about a payment for garnishment-related purposes.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[1..1]			92
		CodeOrProprietary <CdOrPrtry>	[1..1]			93
	{Or	Code <Cd>	[1..1]	CodeSet		93
	Or}	Proprietary <Prtry>	[1..1]	Text		93
		Issuer <Issr>	[0..1]	Text		93
		Garnishee <Grnshee>	[0..1]	±		93
		GarnishmentAdministrator <GrnshmtAdmstr>	[0..1]	±		94
		ReferenceNumber <RefNb>	[0..1]	Text		94
		Date <Dt>	[0..1]	Date		94
		RemittedAmount <RmtdAmt>	[0..1]	Amount		94
		FamilyMedicalInsuranceIndicator <FmlyMdclInsrncInd>	[0..1]	Indicator		95
		EmployeeTerminationIndicator <MplyeeTermntnInd>	[0..1]	Indicator		95

2.1.16.1.1 Type <Tp>*Presence:* [1..1]*Definition:* Specifies the type of garnishment.

Type <Tp> contains the following **GarnishmentType1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CodeOrProprietary <CdOrPrtry>	[1..1]			93
	{Or	Code <Cd>	[1..1]	CodeSet		93
	Or}	Proprietary <Prtry>	[1..1]	Text		93
		Issuer <Issr>	[0..1]	Text		93

2.1.16.1.1.1 CodeOrProprietary <CdOrPrtry>

Presence: [1..1]

Definition: Provides the type details of the garnishment.

CodeOrProprietary <CdOrPrtry> contains one of the following **GarnishmentType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		93
	Or}	Proprietary <Prtry>	[1..1]	Text		93

2.1.16.1.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Garnishment type in a coded form.

Would suggest this to be an External Code List to contain:

GNCS Garnishment from a third party payer for Child Support

GNDP Garnishment from a Direct Payer for Child Support

GTPP Garnishment from a third party payer to taxing agency.

Datatype: [ExternalGarnishmentType1Code on page 151](#)

2.1.16.1.1.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Proprietary identification of the type of garnishment.

Datatype: [Max35Text on page 171](#)

2.1.16.1.1.2 Issuer <Issr>

Presence: [0..1]

Definition: Identification of the issuer of the garnishment type.

Datatype: [Max35Text on page 171](#)

2.1.16.1.2 Garnishee <Grnshee>

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor, in this case, to the garnisher.

Garnishee <Grnshee> contains the following elements (see [PartyIdentification135](#) on page 52 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		53
		PostalAddress <PstlAdr>	[0..1]	±		53
		Identification <Id>	[0..1]	±		54
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		54
		ContactDetails <CtctDtls>	[0..1]	±		55

2.1.16.1.3 GarnishmentAdministrator <GrnshmtAdmstr>

Presence: [0..1]

Definition: Party on the credit side of the transaction who administers the garnishment on behalf of the ultimate beneficiary.

GarnishmentAdministrator <GrnshmtAdmstr> contains the following elements (see [PartyIdentification135](#) on page 52 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		53
		PostalAddress <PstlAdr>	[0..1]	±		53
		Identification <Id>	[0..1]	±		54
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		54
		ContactDetails <CtctDtls>	[0..1]	±		55

2.1.16.1.4 ReferenceNumber <RefNb>

Presence: [0..1]

Definition: Reference information that is specific to the agency receiving the garnishment.

Datatype: [Max140Text](#) on page 170

2.1.16.1.5 Date <Dt>

Presence: [0..1]

Definition: Date of payment which garnishment was taken from.

Datatype: [ISODate](#) on page 165

2.1.16.1.6 RemittedAmount <RmtdAmt>

Presence: [0..1]

Definition: Amount of money remitted for the referred document.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 137

2.1.16.1.7 FamilyMedicalInsuranceIndicator <FmlyMdclInsrncInd>

Presence: [0..1]

Definition: Indicates if the person to whom the garnishment applies (that is, the ultimate debtor) has family medical insurance coverage available.

Datatype: One of the following values must be used (see [TrueFalseIndicator](#) on page 168):

- *Meaning When True:* True
- *Meaning When False:* False

2.1.16.1.8 EmployeeTerminationIndicator <MplyeeTermntnInd>

Presence: [0..1]

Definition: Indicates if the employment of the person to whom the garnishment applies (that is, the ultimate debtor) has been terminated.

Datatype: One of the following values must be used (see [TrueFalseIndicator](#) on page 168):

- *Meaning When True:* True
- *Meaning When False:* False

2.1.16.2 RemittanceInformation16

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Unstructured <Ustrd>	[0..*]	Text		95
		Structured <Strd>	[0..*]	±		95

2.1.16.2.1 Unstructured <Ustrd>

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form.

Datatype: [Max140Text](#) on page 170

2.1.16.2.2 Structured <Strd>

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

Structured <Strd> contains the following elements (see [StructuredRemittanceInformation16](#) on page 97 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ReferredDocumentInformation <RfrdDocInf>	[0..*]			99
		Type <Tp>	[0..1]			101
		CodeOrProprietary <CdOrPrtry>	[1..1]			101
	{Or	Code <Cd>	[1..1]	CodeSet		101
	Or}	Proprietary <Prtry>	[1..1]	Text		102
		Issuer <Issr>	[0..1]	Text		102
		Number <Nb>	[0..1]	Text		102
		RelatedDate <RltdDt>	[0..1]	Date		103
		LineDetails <LineDtls>	[0..*]			103
		Identification <Id>	[1..*]			104
		Type <Tp>	[0..1]			105
		CodeOrProprietary <CdOrPrtry>	[1..1]			105
	{Or	Code <Cd>	[1..1]	CodeSet		105
	Or}	Proprietary <Prtry>	[1..1]	Text		106
		Issuer <Issr>	[0..1]	Text		106
		Number <Nb>	[0..1]	Text		106
		RelatedDate <RltdDt>	[0..1]	Date		106
		Description <Desc>	[0..1]	Text		106
		Amount <Amt>	[0..1]			106
		DuePayableAmount <DuePyblAmt>	[0..1]	Amount		107
		DiscountAppliedAmount <DscntApldAmt>	[0..*]			107
		Type <Tp>	[0..1]			108
	{Or	Code <Cd>	[1..1]	CodeSet		108
	Or}	Proprietary <Prtry>	[1..1]	Text		108
		Amount <Amt>	[1..1]	Amount		108
		CreditNoteAmount <CdtNoteAmt>	[0..1]	Amount		108
		TaxAmount <TaxAmt>	[0..*]			108
		Type <Tp>	[0..1]			109
	{Or	Code <Cd>	[1..1]	CodeSet		109
	Or}	Proprietary <Prtry>	[1..1]	Text		109

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Amount		109
		AdjustmentAmountAndReason <AdjstmntAmtAndRsn>	[0..*]			109
		Amount <Amt>	[1..1]	Amount		110
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		110
		Reason <Rsn>	[0..1]	Text		110
		AdditionalInformation <AddtlInf>	[0..1]	Text		110
		RemittedAmount <RmtdAmt>	[0..1]	Amount		110
		ReferredDocumentAmount <RfrdDocAmt>	[0..1]	±		110
		CreditorReferenceInformation <CdtrRefInf>	[0..1]	±		111
		Invoicer <Invcr>	[0..1]	±		112
		Invoicee <Invcee>	[0..1]	±		112
		TaxRemittance <TaxRmt>	[0..1]	±		113
		GarnishmentRemittance <GrnshmtRmt>	[0..1]	±		113
		AdditionalRemittanceInformation <AddtlRmtInf>	[0..3]	Text		114

2.1.16.3 StructuredRemittanceInformation16

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ReferredDocumentInformation <RfrdDocInf>	[0..*]			99
		Type <Tp>	[0..1]			101
		CodeOrProprietary <CdOrPrtry>	[1..1]			101
	{Or	Code <Cd>	[1..1]	CodeSet		101
	Or}	Proprietary <Prtry>	[1..1]	Text		102
		Issuer <Issr>	[0..1]	Text		102
		Number <Nb>	[0..1]	Text		102
		RelatedDate <RltdDt>	[0..1]	Date		103
		LineDetails <LineDtls>	[0..*]			103
		Identification <Id>	[1..*]			104
		Type <Tp>	[0..1]			105
		CodeOrProprietary <CdOrPrtry>	[1..1]			105
	{Or	Code <Cd>	[1..1]	CodeSet		105
	Or}	Proprietary <Prtry>	[1..1]	Text		106
		Issuer <Issr>	[0..1]	Text		106
		Number <Nb>	[0..1]	Text		106
		RelatedDate <RltdDt>	[0..1]	Date		106
		Description <Desc>	[0..1]	Text		106
		Amount <Amt>	[0..1]			106
		DuePayableAmount <DuePyblAmt>	[0..1]	Amount		107
		DiscountAppliedAmount <DscntApldAmt>	[0..*]			107
		Type <Tp>	[0..1]			108
	{Or	Code <Cd>	[1..1]	CodeSet		108
	Or}	Proprietary <Prtry>	[1..1]	Text		108
		Amount <Amt>	[1..1]	Amount		108
		CreditNoteAmount <CdtNoteAmt>	[0..1]	Amount		108
		TaxAmount <TaxAmt>	[0..*]			108
		Type <Tp>	[0..1]			109
	{Or	Code <Cd>	[1..1]	CodeSet		109
	Or}	Proprietary <Prtry>	[1..1]	Text		109
		Amount <Amt>	[1..1]	Amount		109

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AdjustmentAmountAndReason <AdjstmntAmtAndRsn>	[0..*]			109
		Amount <Amt>	[1..1]	Amount		110
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		110
		Reason <Rsn>	[0..1]	Text		110
		AdditionalInformation <AddtlInf>	[0..1]	Text		110
		RemittedAmount <RmtdAmt>	[0..1]	Amount		110
		ReferredDocumentAmount <RfrdDocAmt>	[0..1]	±		110
		CreditorReferenceInformation <CdtrRefInf>	[0..1]	±		111
		Invoicer <Invcr>	[0..1]	±		112
		Invoicee <Invcee>	[0..1]	±		112
		TaxRemittance <TaxRmt>	[0..1]	±		113
		GarnishmentRemittance <GrnshmtRmt>	[0..1]	±		113
		AdditionalRemittanceInformation <AddtlRmtInf>	[0..3]	Text		114

2.1.16.3.1 ReferredDocumentInformation <RfrdDocInf>

Presence: [0..*]

Definition: Provides the identification and the content of the referred document.

ReferredDocumentInformation <RfrdDocInf> contains the following **ReferredDocumentInformation7** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			101
		CodeOrProprietary <CdOrPrtry>	[1..1]			101
	{Or	Code <Cd>	[1..1]	CodeSet		101
	Or}	Proprietary <Prtry>	[1..1]	Text		102
		Issuer <Issr>	[0..1]	Text		102
		Number <Nb>	[0..1]	Text		102
		RelatedDate <RltdDt>	[0..1]	Date		103
		LineDetails <LineDtls>	[0..*]			103
		Identification <Id>	[1..*]			104
		Type <Tp>	[0..1]			105
		CodeOrProprietary <CdOrPrtry>	[1..1]			105
	{Or	Code <Cd>	[1..1]	CodeSet		105
	Or}	Proprietary <Prtry>	[1..1]	Text		106
		Issuer <Issr>	[0..1]	Text		106
		Number <Nb>	[0..1]	Text		106
		RelatedDate <RltdDt>	[0..1]	Date		106
		Description <Desc>	[0..1]	Text		106
		Amount <Amt>	[0..1]			106
		DuePayableAmount <DuePyblAmt>	[0..1]	Amount		107
		DiscountAppliedAmount <DscntApldAmt>	[0..*]			107
		Type <Tp>	[0..1]			108
	{Or	Code <Cd>	[1..1]	CodeSet		108
	Or}	Proprietary <Prtry>	[1..1]	Text		108
		Amount <Amt>	[1..1]	Amount		108
		CreditNoteAmount <CdtNoteAmt>	[0..1]	Amount		108
		TaxAmount <TaxAmt>	[0..*]			108
		Type <Tp>	[0..1]			109
	{Or	Code <Cd>	[1..1]	CodeSet		109
	Or}	Proprietary <Prtry>	[1..1]	Text		109
		Amount <Amt>	[1..1]	Amount		109

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AdjustmentAmountAndReason <AdjstmntAmtAndRsn>	[0..*]			109
		Amount <Amt>	[1..1]	Amount		110
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		110
		Reason <Rsn>	[0..1]	Text		110
		AdditionalInformation <AddtlInf>	[0..1]	Text		110
		RemittedAmount <RmtdAmt>	[0..1]	Amount		110

2.1.16.3.1.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of referred document.

Type <Tp> contains the following **ReferredDocumentType4** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CodeOrProprietary <CdOrPrtry>	[1..1]			101
	{Or	Code <Cd>	[1..1]	CodeSet		101
	Or}	Proprietary <Prtry>	[1..1]	Text		102
		Issuer <Issr>	[0..1]	Text		102

2.1.16.3.1.1.1 CodeOrProprietary <CdOrPrtry>

Presence: [1..1]

Definition: Provides the type details of the referred document.

CodeOrProprietary <CdOrPrtry> contains one of the following **ReferredDocumentType3Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		101
	Or}	Proprietary <Prtry>	[1..1]	Text		102

2.1.16.3.1.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Document type in a coded form.

Datatype: DocumentType6Code on page 143

CodeName	Name	Definition
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.

CodeName	Name	Definition
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
CINV	CommercialInvoice	Document is an invoice.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
DISP	DispatchAdvice	Document is a dispatch advice.
BOLD	BillOfLading	Document is a shipping notice.
VCHR	Voucher	Document is an electronic payment document.
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
PUOR	PurchaseOrder	Document is a purchase order.

2.1.16.3.1.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Proprietary identification of the type of the remittance document.

Datatype: Max35Text on page 171

2.1.16.3.1.1.2 Issuer <Issr>

Presence: [0..1]

Definition: Identification of the issuer of the reference document type.

Datatype: Max35Text on page 171

2.1.16.3.1.2 Number <Nb>

Presence: [0..1]

Definition: Unique and unambiguous identification of the referred document.

Datatype: Max35Text on page 171

2.1.16.3.1.3 RelatedDate <RltdDt>

Presence: [0..1]

Definition: Date associated with the referred document.

Datatype: ISODate on page 165

2.1.16.3.1.4 LineDetails <LineDtls>

Presence: [0..*]

Definition: Set of elements used to provide the content of the referred document line.

LineDetails <LineDtls> contains the following **DocumentLineInformation1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..*]			104
		Type <Tp>	[0..1]			105
		CodeOrProprietary <CdOrPrtry>	[1..1]			105
	{Or	Code <Cd>	[1..1]	CodeSet		105
	Or}	Proprietary <Prtry>	[1..1]	Text		106
		Issuer <Issr>	[0..1]	Text		106
		Number <Nb>	[0..1]	Text		106
		RelatedDate <RltdDt>	[0..1]	Date		106
		Description <Desc>	[0..1]	Text		106
		Amount <Amt>	[0..1]			106
		DuePayableAmount <DuePyblAmt>	[0..1]	Amount		107
		DiscountAppliedAmount <DscntApldAmt>	[0..*]			107
		Type <Tp>	[0..1]			108
	{Or	Code <Cd>	[1..1]	CodeSet		108
	Or}	Proprietary <Prtry>	[1..1]	Text		108
		Amount <Amt>	[1..1]	Amount		108
		CreditNoteAmount <CdtNoteAmt>	[0..1]	Amount		108
		TaxAmount <TaxAmt>	[0..*]			108
		Type <Tp>	[0..1]			109
	{Or	Code <Cd>	[1..1]	CodeSet		109
	Or}	Proprietary <Prtry>	[1..1]	Text		109
		Amount <Amt>	[1..1]	Amount		109
		AdjustmentAmountAndReason <AdjstmntAmtAndRsn>	[0..*]			109
		Amount <Amt>	[1..1]	Amount		110
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		110
		Reason <Rsn>	[0..1]	Text		110
		AdditionalInformation <AddtlInf>	[0..1]	Text		110
		RemittedAmount <RmtdAmt>	[0..1]	Amount		110

2.1.16.3.1.4.1 Identification <Id>

Presence: [1..*]

Definition: Provides identification of the document line.

Identification <Id> contains the following **DocumentLineIdentification1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			105
		CodeOrProprietary <CdOrPrtry>	[1..1]			105
	{Or	Code <Cd>	[1..1]	CodeSet		105
	Or}	Proprietary <Prtry>	[1..1]	Text		106
		Issuer <Issr>	[0..1]	Text		106
		Number <Nb>	[0..1]	Text		106
		RelatedDate <RltdDt>	[0..1]	Date		106

2.1.16.3.1.4.1.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of referred document line identification.

Type <Tp> contains the following **DocumentLineType1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CodeOrProprietary <CdOrPrtry>	[1..1]			105
	{Or	Code <Cd>	[1..1]	CodeSet		105
	Or}	Proprietary <Prtry>	[1..1]	Text		106
		Issuer <Issr>	[0..1]	Text		106

2.1.16.3.1.4.1.1.1 CodeOrProprietary <CdOrPrtry>

Presence: [1..1]

Definition: Provides the type details of the referred document line identification.

CodeOrProprietary <CdOrPrtry> contains one of the following **DocumentLineType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		105
	Or}	Proprietary <Prtry>	[1..1]	Text		106

2.1.16.3.1.4.1.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Line identification type in a coded form.

Datatype: ExternalDocumentLineType1Code on page 149

2.1.16.3.1.4.1.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Proprietary identification of the type of the remittance document.

Datatype: Max35Text on page 171

2.1.16.3.1.4.1.1.2 Issuer <Issr>

Presence: [0..1]

Definition: Identification of the issuer of the reference document line identificationtype.

Datatype: Max35Text on page 171

2.1.16.3.1.4.1.2 Number <Nb>

Presence: [0..1]

Definition: Identification of the type specified for the referred document line.

Datatype: Max35Text on page 171

2.1.16.3.1.4.1.3 RelatedDate <RltdDt>

Presence: [0..1]

Definition: Date associated with the referred document line.

Datatype: ISODate on page 165

2.1.16.3.1.4.2 Description <Desc>

Presence: [0..1]

Definition: Description associated with the document line.

Datatype: Max2048Text on page 170

2.1.16.3.1.4.3 Amount <Amt>

Presence: [0..1]

Definition: Provides details on the amounts of the document line.

Amount <Amt> contains the following **RemittanceAmount3** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DuePayableAmount <DuePyblAmt>	[0..1]	Amount		107
		DiscountAppliedAmount <DscntApldAmt>	[0..*]			107
		Type <Tp>	[0..1]			108
	{Or	Code <Cd>	[1..1]	CodeSet		108
	Or}	Proprietary <Prtry>	[1..1]	Text		108
		Amount <Amt>	[1..1]	Amount		108
		CreditNoteAmount <CdtNoteAmt>	[0..1]	Amount		108
		TaxAmount <TaxAmt>	[0..*]			108
		Type <Tp>	[0..1]			109
	{Or	Code <Cd>	[1..1]	CodeSet		109
	Or}	Proprietary <Prtry>	[1..1]	Text		109
		Amount <Amt>	[1..1]	Amount		109
		AdjustmentAmountAndReason <AdjstmntAmtAndRsn>	[0..*]			109
		Amount <Amt>	[1..1]	Amount		110
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		110
		Reason <Rsn>	[0..1]	Text		110
		AdditionalInformation <AddtlInf>	[0..1]	Text		110
		RemittedAmount <RmtdAmt>	[0..1]	Amount		110

2.1.16.3.1.4.3.1 DuePayableAmount <DuePyblAmt>

Presence: [0..1]

Definition: Amount specified is the exact amount due and payable to the creditor.

Datatype: ActiveOrHistoricCurrencyAndAmount on page 137

2.1.16.3.1.4.3.2 DiscountAppliedAmount <DscntApldAmt>

Presence: [0..*]

Definition: Amount of discount to be applied to the amount due and payable to the creditor.

DiscountAppliedAmount <DscntApldAmt> contains the following **DiscountAmountAndType1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			108
	{Or	Code <Cd>	[1..1]	CodeSet		108
	Or}	Proprietary <Prtry>	[1..1]	Text		108
		Amount <Amt>	[1..1]	Amount		108

2.1.16.3.1.4.3.2.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of the amount.

Type <Tp> contains one of the following **DiscountAmountType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		108
	Or}	Proprietary <Prtry>	[1..1]	Text		108

2.1.16.3.1.4.3.2.1.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: [ExternalDiscountAmountType1Code on page 149](#)

2.1.16.3.1.4.3.2.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: [Max35Text on page 171](#)

2.1.16.3.1.4.3.2.2 Amount <Amt>

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 137](#)

2.1.16.3.1.4.3.3 CreditNoteAmount <CdtNoteAmt>

Presence: [0..1]

Definition: Amount of a credit note.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 137](#)

2.1.16.3.1.4.3.4 TaxAmount <TaxAmt>

Presence: [0..*]

Definition: Amount of the tax.

TaxAmount <TaxAmt> contains the following **TaxAmountAndType1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			109
	{Or	Code <Cd>	[1..1]	CodeSet		109
	Or}	Proprietary <Prtry>	[1..1]	Text		109
		Amount <Amt>	[1..1]	Amount		109

2.1.16.3.1.4.3.4.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of the amount.

Type <Tp> contains one of the following **TaxAmountType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		109
	Or}	Proprietary <Prtry>	[1..1]	Text		109

2.1.16.3.1.4.3.4.1.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: [ExternalTaxAmountType1Code](#) on page 155

2.1.16.3.1.4.3.4.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: [Max35Text](#) on page 171

2.1.16.3.1.4.3.4.2 Amount <Amt>

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 137

2.1.16.3.1.4.3.5 AdjustmentAmountAndReason <AdjstmntAmtAndRsn>

Presence: [0..*]

Definition: Specifies detailed information on the amount and reason of the adjustment.

AdjustmentAmountAndReason <AdjstmntAmtAndRsn> contains the following **DocumentAdjustment1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Amount		110
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		110
		Reason <Rsn>	[0..1]	Text		110
		AdditionalInformation <AddtlInf>	[0..1]	Text		110

2.1.16.3.1.4.3.5.1 Amount <Amt>

Presence: [1..1]

Definition: Amount of money of the document adjustment.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 137](#)

2.1.16.3.1.4.3.5.2 CreditDebitIndicator <CdtDbtInd>

Presence: [0..1]

Definition: Specifies whether the adjustment must be subtracted or added to the total amount.

Datatype: [CreditDebitCode on page 142](#)

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

2.1.16.3.1.4.3.5.3 Reason <Rsn>

Presence: [0..1]

Definition: Specifies the reason for the adjustment.

Datatype: [Max4Text on page 171](#)

2.1.16.3.1.4.3.5.4 AdditionalInformation <AddtlInf>

Presence: [0..1]

Definition: Provides further details on the document adjustment.

Datatype: [Max140Text on page 170](#)

2.1.16.3.1.4.3.6 RemittedAmount <RmtdAmt>

Presence: [0..1]

Definition: Amount of money remitted.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 137](#)

2.1.16.3.2 ReferredDocumentAmount <RfrdDocAmt>

Presence: [0..1]

Definition: Provides details on the amounts of the referred document.

ReferredDocumentAmount <RfrdDocAmt> contains the following elements (see [RemittanceAmount2](#) on page 40 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DuePayableAmount <DuePyblAmt>	[0..1]	Amount		41
		DiscountAppliedAmount <DscntApldAmt>	[0..*]			41
		Type <Tp>	[0..1]			42
	{Or	Code <Cd>	[1..1]	CodeSet		42
	Or}	Proprietary <Prtry>	[1..1]	Text		42
		Amount <Amt>	[1..1]	Amount		42
		CreditNoteAmount <CdtNoteAmt>	[0..1]	Amount		42
		TaxAmount <TaxAmt>	[0..*]			42
		Type <Tp>	[0..1]			43
	{Or	Code <Cd>	[1..1]	CodeSet		43
	Or}	Proprietary <Prtry>	[1..1]	Text		43
		Amount <Amt>	[1..1]	Amount		43
		AdjustmentAmountAndReason <AdjstmntAmtAndRsn>	[0..*]			43
		Amount <Amt>	[1..1]	Amount		44
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		44
		Reason <Rsn>	[0..1]	Text		44
		AdditionalInformation <AddtlInf>	[0..1]	Text		44
		RemittedAmount <RmtdAmt>	[0..1]	Amount		44

2.1.16.3.3 CreditorReferenceInformation <CdtrRefInf>

Presence: [0..1]

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

CreditorReferenceInformation <CdtrRefInf> contains the following elements (see [CreditorReferenceInformation2](#) on page 29 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			30
		CodeOrProprietary <CdOrPrtry>	[1..1]			30
	{Or	Code <Cd>	[1..1]	CodeSet		30
	Or}	Proprietary <Prtry>	[1..1]	Text		31
		Issuer <Issr>	[0..1]	Text		31
		Reference <Ref>	[0..1]	Text		31

2.1.16.3.4 Invoicer <Invcr>

Presence: [0..1]

Definition: Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor.

Invoicer <Invcr> contains the following elements (see [PartyIdentification135](#) on page 52 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		53
		PostalAddress <PstlAdr>	[0..1]	±		53
		Identification <Id>	[0..1]	±		54
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		54
		ContactDetails <CtctDtls>	[0..1]	±		55

2.1.16.3.5 Invoicee <Invcee>

Presence: [0..1]

Definition: Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor.

Invoicee <Invcee> contains the following elements (see [PartyIdentification135](#) on page 52 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		53
		PostalAddress <PstlAdr>	[0..1]	±		53
		Identification <Id>	[0..1]	±		54
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		54
		ContactDetails <CtctDtls>	[0..1]	±		55

2.1.16.3.6 TaxRemittance <TaxRmt>

Presence: [0..1]

Definition: Provides remittance information about a payment made for tax-related purposes.

TaxRemittance <TaxRmt> contains the following elements (see [TaxInformation7](#) on page 125 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Creditor <Cdtr>	[0..1]	±		125
		Debtor <Dbtr>	[0..1]	±		126
		UltimateDebtor <UltmtDbtr>	[0..1]	±		126
		AdministrationZone <AdmstnZone>	[0..1]	Text		126
		ReferenceNumber <RefNb>	[0..1]	Text		127
		Method <Mtd>	[0..1]	Text		127
		TotalTaxableBaseAmount <TtlTaxblBaseAmt>	[0..1]	Amount		127
		TotalTaxAmount <TtlTaxAmt>	[0..1]	Amount		127
		Date <Dt>	[0..1]	Date		127
		SequenceNumber <SeqNb>	[0..1]	Quantity		127
		Record <Rcrd>	[0..*]	±		127

2.1.16.3.7 GarnishmentRemittance <GrnshmtRmt>

Presence: [0..1]

Definition: Provides remittance information about a payment for garnishment-related purposes.

GarnishmentRemittance <GrnshmtRmt> contains the following elements (see [Garnishment3](#) on page 92 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[1..1]			92
		CodeOrProprietary <CdOrPrtry>	[1..1]			93
	{Or	Code <Cd>	[1..1]	CodeSet		93
	Or}	Proprietary <Prtry>	[1..1]	Text		93
		Issuer <Issr>	[0..1]	Text		93
		Garnishee <Grnshee>	[0..1]	±		93
		GarnishmentAdministrator <GrnshmtAdmstr>	[0..1]	±		94
		ReferenceNumber <RefNb>	[0..1]	Text		94
		Date <Dt>	[0..1]	Date		94
		RemittedAmount <RmtdAmt>	[0..1]	Amount		94
		FamilyMedicalInsuranceIndicator <FmlyMdclInsrncInd>	[0..1]	Indicator		95
		EmployeeTerminationIndicator <MplyeeTermtnInd>	[0..1]	Indicator		95

2.1.16.3.8 AdditionalRemittanceInformation <AddtlRmtInf>

Presence: [0..3]

Definition: Additional information, in free text form, to complement the structured remittance information.

Datatype: [Max140Text](#) on page 170

2.1.16.4 RemittanceLocation7

Definition: Provides information on the remittance advice.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		RemittanceIdentification <RmtId>	[0..1]	Text		114
		RemittanceLocationDetails <RmtLctnDtls>	[0..*]	±		114

2.1.16.4.1 RemittanceIdentification <RmtId>

Presence: [0..1]

Definition: Unique identification, as assigned by the initiating party, to unambiguously identify the remittance information sent separately from the payment instruction, such as a remittance advice.

Datatype: [Max35Text](#) on page 171

2.1.16.4.2 RemittanceLocationDetails <RmtLctnDtls>

Presence: [0..*]

Definition: Set of elements used to provide information on the location and/or delivery of the remittance information.

RemittanceLocationDetails <RmtLctnDtls> contains the following elements (see [RemittanceLocationData1](#) on page 115 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Method <Mtd>	[1..1]	CodeSet		115
		ElectronicAddress <ElctrncAdr>	[0..1]	Text		116
		PostalAddress <PstlAdr>	[0..1]			116
		Name <Nm>	[1..1]	Text		116
		Address <Adr>	[1..1]	±		116

2.1.16.5 RemittanceLocationData1

Definition: Provides additional details on the remittance advice.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Method <Mtd>	[1..1]	CodeSet		115
		ElectronicAddress <ElctrncAdr>	[0..1]	Text		116
		PostalAddress <PstlAdr>	[0..1]			116
		Name <Nm>	[1..1]	Text		116
		Address <Adr>	[1..1]	±		116

2.1.16.5.1 Method <Mtd>

Presence: [1..1]

Definition: Method used to deliver the remittance advice information.

Datatype: [RemittanceLocationMethod2Code](#) on page 161

CodeName	Name	Definition
FAXI	Fax	Remittance advice information must be faxed.
EDIC	ElectronicDataInterchange	Remittance advice information must be sent through Electronic Data Interchange (EDI).
URID	UniformResourceIdentifier	Remittance advice information needs to be sent to a Uniform Resource Identifier (URI). URI is a compact string of characters that uniquely identify an abstract or physical resource. URI's are the super-set of identifiers, such as URLs, email addresses, ftp sites, etc, and as such, provide the syntax for all of the identification schemes.
EMAL	EMail	Remittance advice information must be sent through e-mail.

CodeName	Name	Definition
POST	Post	Remittance advice information must be sent through postal services.
SMSM	SMS	Remittance advice information must be sent through by phone as a short message service (SMS).

2.1.16.5.2 ElectronicAddress <ElctrncAdr>

Presence: [0..1]

Definition: Electronic address to which an agent is to send the remittance information.

Datatype: [Max2048Text on page 170](#)

2.1.16.5.3 PostalAddress <PstlAdr>

Presence: [0..1]

Definition: Postal address to which an agent is to send the remittance information.

PostalAddress <PstlAdr> contains the following **NameAndAddress16** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[1..1]	Text		116
		Address <Adr>	[1..1]	±		116

2.1.16.5.3.1 Name <Nm>

Presence: [1..1]

Definition: Name by which a party is known and is usually used to identify that party.

Datatype: [Max140Text on page 170](#)

2.1.16.5.3.2 Address <Adr>

Presence: [1..1]

Definition: Postal address of a party.

Address <Adr> contains the following elements (see [PostalAddress24](#) on page 86 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AddressType <AdrTp>	[0..1]			86
	{Or	Code <Cd>	[1..1]	CodeSet		87
	Or}	Proprietary <Prtry>	[1..1]	±		87
		Department <Dept>	[0..1]	Text		87
		SubDepartment <SubDept>	[0..1]	Text		87
		StreetName <StrtNm>	[0..1]	Text		88
		BuildingNumber <BldgNb>	[0..1]	Text		88
		BuildingName <BldgNm>	[0..1]	Text		88
		Floor <Flr>	[0..1]	Text		88
		PostBox <PstBx>	[0..1]	Text		88
		Room <Room>	[0..1]	Text		88
		PostCode <PstCd>	[0..1]	Text		88
		TownName <TwnNm>	[0..1]	Text		88
		TownLocationName <TwnLctnNm>	[0..1]	Text		89
		DistrictName <DstrctNm>	[0..1]	Text		89
		CountrySubDivision <CtrySubDvsn>	[0..1]	Text		89
		Country <Ctry>	[0..1]	CodeSet		89
		AddressLine <AdrLine>	[0..7]	Text		89

2.1.17 Settlement Instruction

2.1.17.1 SettlementInstruction7

Definition: Provides further details on the settlement of the instruction.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		SettlementMethod <SttlmMtd>	[1..1]	CodeSet		120
		SettlementAccount <SttlmAcct>	[0..1]	±		120
		ClearingSystem <ClrSys>	[0..1]			120
	{Or	Code <Cd>	[1..1]	CodeSet		121
	Or}	Proprietary <Prtry>	[1..1]	Text		121
		InstructingReimbursementAgent <InstgRmbrsmntAgt>	[0..1]	±		121
		InstructingReimbursementAgentAccount <InstgRmbrsmntAgtAcct>	[0..1]	±		121
		InstructedReimbursementAgent <InstdRmbrsmntAgt>	[0..1]	±		122
		InstructedReimbursementAgentAccount <InstdRmbrsmntAgtAcct>	[0..1]	±		122
		ThirdReimbursementAgent <ThrdRmbrsmntAgt>	[0..1]	±		123
		ThirdReimbursementAgentAccount <ThrdRmbrsmntAgtAcct>	[0..1]	±		123

Constraints

- **InstructedReimbursementAgentAccountRule**

If InstructedReimbursementAgentAccount is present, then InstructedReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00037
- *Error Text:* Invalid message content for instructed reimbursement agent account.

- **InstructingReimbursementAgentAccountRule**

If InstructingReimbursementAgentAccount is present, then InstructingReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00038
- *Error Text:* Invalid message content for instructing reimbursement agent account.

- **SettlementMethodAgentRule**

If SettlementMethod is equal to INDA or INGA, then ReimbursementAgent(s) and ClearingSystem are not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00018
- *Error Text:* Invalid message content for settlement method INGA or INDA.

- **SettlementMethodClearingRule**

If SettlementMethod is equal to CLRG, then SettlementAccount and ReimbursementAgent(s) are not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00019
- *Error Text:* Invalid message content for settlement method CLRG.

- **SettlementMethodCoverAgentRule**

If SettlementMethod is equal to COVE, then InstructedReimbursementAgent or InstructingReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00076
- *Error Text:* Invalid message content for cover settlement method and reimbursement agents.

- **SettlementMethodCoverRule**

If SettlementMethod is equal to COVE, then SettlementAccount and ClearingSystem are not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00075
- *Error Text:* Invalid message content for cover settlement method with settlement account and clearing system.

- **ThirdReimbursementAgentAccountRule**

If ThirdReimbursementAgentAccount is present, then ThirdReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00039
- *Error Text:* Invalid message content for third reimbursement agent account.

- **ThirdReimbursementAgentRule**

If ThirdReimbursementAgent is present, then InstructingReimbursementAgent and InstructedReimbursementAgent must both be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00040
- *Error Text:* Invalid message content for third reimbursement agent.

2.1.17.1.1 SettlementMethod <SttlmMtd>*Presence:* [1..1]*Definition:* Method used to settle the (batch of) payment instructions.*Datatype:* [SettlementMethod1Code](#) on page 162

CodeName	Name	Definition
INDA	InstructedAgent	Settlement is done by the agent instructed to execute a payment instruction.
INGA	InstructingAgent	Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.
COVE	CoverMethod	Settlement is done through a cover payment.
CLRG	ClearingSystem	Settlement is done through a payment clearing system.

2.1.17.1.2 SettlementAccount <SttlmAcct>*Presence:* [0..1]*Definition:* A specific purpose account used to post debit and credit entries as a result of the transaction.**SettlementAccount <SttlmAcct>** contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.17.1.3 ClearingSystem <ClrSys>*Presence:* [0..1]*Definition:* Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

ClearingSystem <ClrSys> contains one of the following **ClearingSystemIdentification3Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		121
	Or}	Proprietary <Prtry>	[1..1]	Text		121

2.1.17.1.3.1 Code <Cd>

Presence: [1..1]

Definition: Infrastructure through which the payment instruction is processed, as published in an external clearing system identification code list.

Datatype: ExternalCashClearingSystem1Code on page 147

2.1.17.1.3.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Clearing system identification in a proprietary form.

Datatype: Max35Text on page 171

2.1.17.1.4 InstructingReimbursementAgent <InstgRmbrsmntAgt>

Presence: [0..1]

Definition: Agent through which the instructing agent will reimburse the instructed agent.

Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used.

InstructingReimbursementAgent <InstgRmbrsmntAgt> contains the following elements (see **BranchAndFinancialInstitutionIdentification6** on page 36 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		36
		BranchIdentification <BrnchId>	[0..1]	±		37

2.1.17.1.5 InstructingReimbursementAgentAccount <InstgRmbrsmntAgtAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the instructing reimbursement agent account at its servicing agent in the payment chain.

InstructingReimbursementAgentAccount <InstgRmbrsmntAgtAcct> contains the following elements (see [CashAccount38 on page 24](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.17.1.6 InstructedReimbursementAgent <InstdRmbrsmntAgt>

Presence: [0..1]

Definition: Agent at which the instructed agent will be reimbursed.

Usage: If InstructedReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch.

Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used.

InstructedReimbursementAgent <InstdRmbrsmntAgt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6 on page 36](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		36
		BranchIdentification <BrnchId>	[0..1]	±		37

2.1.17.1.7 InstructedReimbursementAgentAccount <InstdRmbrsmntAgtAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the instructed reimbursement agent account at its servicing agent in the payment chain.

InstructedReimbursementAgentAccount <InstdRmbrsmntAgtAcct> contains the following elements (see [CashAccount38 on page 24](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.17.1.8 ThirdReimbursementAgent <ThrdRmbrsmntAgt>

Presence: [0..1]

Definition: Agent at which the instructed agent will be reimbursed.

Usage: If ThirdReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch.

ThirdReimbursementAgent <ThrdRmbrsmntAgt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 36 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		36
		BranchIdentification <BrnchId>	[0..1]	±		37

2.1.17.1.9 ThirdReimbursementAgentAccount <ThrdRmbrsmntAgtAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the third reimbursement agent account at its servicing agent in the payment chain.

ThirdReimbursementAgentAccount <ThrdRmbrsmntAgtAcct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.18 System Identification

2.1.18.1 ClearingSystemIdentification2Choice

Definition: Choice of a clearing system identifier.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		123
	Or}	Proprietary <Prtry>	[1..1]	Text		124

2.1.18.1.1 Code <Cd>

Presence: [1..1]

Definition: Identification of a clearing system, in a coded form as published in an external list.

Datatype: [ExternalClearingSystemIdentification1Code](#) on page 148

2.1.18.1.2 Proprietary <Prtry>*Presence:* [1..1]*Definition:* Identification code for a clearing system, that has not yet been identified in the list of clearing systems.*Datatype:* Max35Text on page 171**2.1.19 Tax****2.1.19.1 TaxParty2***Definition:* Details about the entity involved in the tax paid or to be paid.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TaxIdentification <TaxId>	[0..1]	Text		124
		RegistrationIdentification <RegnId>	[0..1]	Text		124
		TaxType <TaxTp>	[0..1]	Text		124
		Authorisation <Authstn>	[0..1]			124
		Title <Titl>	[0..1]	Text		125
		Name <Nm>	[0..1]	Text		125

2.1.19.1.1 TaxIdentification <TaxId>*Presence:* [0..1]*Definition:* Tax identification number of the debtor.*Datatype:* Max35Text on page 171**2.1.19.1.2 RegistrationIdentification <RegnId>***Presence:* [0..1]*Definition:* Unique identification, as assigned by an organisation, to unambiguously identify a party.*Datatype:* Max35Text on page 171**2.1.19.1.3 TaxType <TaxTp>***Presence:* [0..1]*Definition:* Type of tax payer.*Datatype:* Max35Text on page 171**2.1.19.1.4 Authorisation <Authstn>***Presence:* [0..1]*Definition:* Details of the authorised tax paying party.

Authorisation <Authstn> contains the following **TaxAuthorisation1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Title <Titl>	[0..1]	Text		125
		Name <Nm>	[0..1]	Text		125

2.1.19.1.4.1 Title <Titl>

Presence: [0..1]

Definition: Title or position of debtor or the debtor's authorised representative.

Datatype: [Max35Text on page 171](#)

2.1.19.1.4.2 Name <Nm>

Presence: [0..1]

Definition: Name of the debtor or the debtor's authorised representative.

Datatype: [Max140Text on page 170](#)

2.1.19.2 TaxInformation7

Definition: Details about tax paid, or to be paid, to the government in accordance with the law, including pre-defined parameters such as thresholds and type of account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Creditor <Cdtr>	[0..1]	±		125
		Debtor <Dbtr>	[0..1]	±		126
		UltimateDebtor <UltmtDbtr>	[0..1]	±		126
		AdministrationZone <AdmstnZone>	[0..1]	Text		126
		ReferenceNumber <RefNb>	[0..1]	Text		127
		Method <Mtd>	[0..1]	Text		127
		TotalTaxableBaseAmount <TtlTaxblBaseAmt>	[0..1]	Amount		127
		TotalTaxAmount <TtlTaxAmt>	[0..1]	Amount		127
		Date <Dt>	[0..1]	Date		127
		SequenceNumber <SeqNb>	[0..1]	Quantity		127
		Record <Rcrd>	[0..*]	±		127

2.1.19.2.1 Creditor <Cdtr>

Presence: [0..1]

Definition: Party on the credit side of the transaction to which the tax applies.

Creditor <Cdtr> contains the following elements (see [TaxParty1](#) on page 128 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TaxIdentification <TaxId>	[0..1]	Text		128
		RegistrationIdentification <RegnId>	[0..1]	Text		128
		TaxType <TaxTp>	[0..1]	Text		128

2.1.19.2.2 Debtor <Dbtr>

Presence: [0..1]

Definition: Identifies the party on the debit side of the transaction to which the tax applies.

Debtor <Dbtr> contains the following elements (see [TaxParty2](#) on page 124 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TaxIdentification <TaxId>	[0..1]	Text		124
		RegistrationIdentification <RegnId>	[0..1]	Text		124
		TaxType <TaxTp>	[0..1]	Text		124
		Authorisation <Authstn>	[0..1]			124
		Title <Titl>	[0..1]	Text		125
		Name <Nm>	[0..1]	Text		125

2.1.19.2.3 UltimateDebtor <UltmtDbtr>

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor, in this case, to the taxing authority.

UltimateDebtor <UltmtDbtr> contains the following elements (see [TaxParty2](#) on page 124 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TaxIdentification <TaxId>	[0..1]	Text		124
		RegistrationIdentification <RegnId>	[0..1]	Text		124
		TaxType <TaxTp>	[0..1]	Text		124
		Authorisation <Authstn>	[0..1]			124
		Title <Titl>	[0..1]	Text		125
		Name <Nm>	[0..1]	Text		125

2.1.19.2.4 AdministrationZone <AdmstnZone>

Presence: [0..1]

Definition: Territorial part of a country to which the tax payment is related.

Datatype: [Max35Text on page 171](#)

2.1.19.2.5 ReferenceNumber <RefNb>

Presence: [0..1]

Definition: Tax reference information that is specific to a taxing agency.

Datatype: [Max140Text on page 170](#)

2.1.19.2.6 Method <Mtd>

Presence: [0..1]

Definition: Method used to indicate the underlying business or how the tax is paid.

Datatype: [Max35Text on page 171](#)

2.1.19.2.7 TotalTaxableBaseAmount <TtlTaxblBaseAmt>

Presence: [0..1]

Definition: Total amount of money on which the tax is based.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 137](#)

2.1.19.2.8 TotalTaxAmount <TtlTaxAmt>

Presence: [0..1]

Definition: Total amount of money as result of the calculation of the tax.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 137](#)

2.1.19.2.9 Date <Dt>

Presence: [0..1]

Definition: Date by which tax is due.

Datatype: [ISODate on page 165](#)

2.1.19.2.10 SequenceNumber <SeqNb>

Presence: [0..1]

Definition: Sequential number of the tax report.

Datatype: [Number on page 168](#)

2.1.19.2.11 Record <Rcrd>

Presence: [0..*]

Definition: Record of tax details.

Record <Rcrd> contains the following elements (see [TaxRecord2](#) on page 132 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]	Text		133
		Category <Ctgy>	[0..1]	Text		133
		CategoryDetails <CtgyDtls>	[0..1]	Text		133
		DebtorStatus <DbtrSts>	[0..1]	Text		133
		CertificateIdentification <CertId>	[0..1]	Text		133
		FormsCode <FrmsCd>	[0..1]	Text		133
		Period <Prd>	[0..1]	±		133
		TaxAmount <TaxAmt>	[0..1]			134
		Rate <Rate>	[0..1]	Rate		134
		TaxableBaseAmount <TaxblBaseAmt>	[0..1]	Amount		134
		TotalAmount <TtlAmt>	[0..1]	Amount		134
		Details <Dtls>	[0..*]	±		134
		AdditionalInformation <AddtlInf>	[0..1]	Text		134

2.1.19.3 TaxParty1

Definition: Details about the entity involved in the tax paid or to be paid.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TaxIdentification <TaxId>	[0..1]	Text		128
		RegistrationIdentification <RegnId>	[0..1]	Text		128
		TaxType <TaxTp>	[0..1]	Text		128

2.1.19.3.1 TaxIdentification <TaxId>

Presence: [0..1]

Definition: Tax identification number of the creditor.

Datatype: [Max35Text](#) on page 171

2.1.19.3.2 RegistrationIdentification <RegnId>

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: [Max35Text](#) on page 171

2.1.19.3.3 TaxType <TaxTp>

Presence: [0..1]

Definition: Type of tax payer.

Datatype: [Max35Text on page 171](#)

2.1.19.4 TaxRecordDetails2

Definition: Provides information on the individual tax amount(s) per period of the tax record.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Period <Prd>	[0..1]	±		129
		Amount <Amt>	[1..1]	Amount		129

2.1.19.4.1 Period <Prd>

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

Period <Prd> contains the following elements (see [TaxPeriod2 on page 135](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Year <Yr>	[0..1]	Date		135
		Type <Tp>	[0..1]	CodeSet		135
		FromToDate <FrToDt>	[0..1]	±		136

2.1.19.4.2 Amount <Amt>

Presence: [1..1]

Definition: Underlying tax amount related to the specified period.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 137](#)

2.1.19.5 TaxInformation8

Definition: Details about tax paid, or to be paid, to the government in accordance with the law, including pre-defined parameters such as thresholds and type of account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Creditor <Cdtr>	[0..1]	±		130
		Debtor <Dbtr>	[0..1]	±		130
		AdministrationZone <AdmstnZone>	[0..1]	Text		131
		ReferenceNumber <RefNb>	[0..1]	Text		131
		Method <Mtd>	[0..1]	Text		131
		TotalTaxableBaseAmount <TtlTaxblBaseAmt>	[0..1]	Amount		131
		TotalTaxAmount <TtlTaxAmt>	[0..1]	Amount		131
		Date <Dt>	[0..1]	Date		131
		SequenceNumber <SeqNb>	[0..1]	Quantity		131
		Record <Rcrd>	[0..*]	±		131

2.1.19.5.1 Creditor <Cdtr>

Presence: [0..1]

Definition: Party on the credit side of the transaction to which the tax applies.

Creditor <Cdtr> contains the following elements (see [TaxParty1](#) on page 128 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TaxIdentification <TaxId>	[0..1]	Text		128
		RegistrationIdentification <RegnId>	[0..1]	Text		128
		TaxType <TaxTp>	[0..1]	Text		128

2.1.19.5.2 Debtor <Dbtr>

Presence: [0..1]

Definition: Party on the debit side of the transaction to which the tax applies.

Debtor <Dbtr> contains the following elements (see [TaxParty2](#) on page 124 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TaxIdentification <TaxId>	[0..1]	Text		124
		RegistrationIdentification <RegnId>	[0..1]	Text		124
		TaxType <TaxTp>	[0..1]	Text		124
		Authorisation <Authstn>	[0..1]			124
		Title <Titl>	[0..1]	Text		125
		Name <Nm>	[0..1]	Text		125

2.1.19.5.3 AdministrationZone <AdmstnZone>

Presence: [0..1]

Definition: Territorial part of a country to which the tax payment is related.

Datatype: Max35Text on page 171

2.1.19.5.4 ReferenceNumber <RefNb>

Presence: [0..1]

Definition: Tax reference information that is specific to a taxing agency.

Datatype: Max140Text on page 170

2.1.19.5.5 Method <Mtd>

Presence: [0..1]

Definition: Method used to indicate the underlying business or how the tax is paid.

Datatype: Max35Text on page 171

2.1.19.5.6 TotalTaxableBaseAmount <TtlTaxblBaseAmt>

Presence: [0..1]

Definition: Total amount of money on which the tax is based.

Datatype: ActiveOrHistoricCurrencyAndAmount on page 137

2.1.19.5.7 TotalTaxAmount <TtlTaxAmt>

Presence: [0..1]

Definition: Total amount of money as result of the calculation of the tax.

Datatype: ActiveOrHistoricCurrencyAndAmount on page 137

2.1.19.5.8 Date <Dt>

Presence: [0..1]

Definition: Date by which tax is due.

Datatype: ISODate on page 165

2.1.19.5.9 SequenceNumber <SeqNb>

Presence: [0..1]

Definition: Sequential number of the tax report.

Datatype: Number on page 168

2.1.19.5.10 Record <Rcrd>

Presence: [0..*]

Definition: Record of tax details.

Record <Rcrd> contains the following elements (see [TaxRecord2](#) on page 132 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]	Text		133
		Category <Ctgy>	[0..1]	Text		133
		CategoryDetails <CtgyDtls>	[0..1]	Text		133
		DebtorStatus <DbtrSts>	[0..1]	Text		133
		CertificateIdentification <CertId>	[0..1]	Text		133
		FormsCode <FrmsCd>	[0..1]	Text		133
		Period <Prd>	[0..1]	±		133
		TaxAmount <TaxAmt>	[0..1]			134
		Rate <Rate>	[0..1]	Rate		134
		TaxableBaseAmount <TaxblBaseAmt>	[0..1]	Amount		134
		TotalAmount <TtlAmt>	[0..1]	Amount		134
		Details <Dtls>	[0..*]	±		134
		AdditionalInformation <AddtlInf>	[0..1]	Text		134

2.1.19.6 TaxRecord2

Definition: Set of elements used to define the tax record.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]	Text		133
		Category <Ctgy>	[0..1]	Text		133
		CategoryDetails <CtgyDtls>	[0..1]	Text		133
		DebtorStatus <DbtrSts>	[0..1]	Text		133
		CertificateIdentification <CertId>	[0..1]	Text		133
		FormsCode <FrmsCd>	[0..1]	Text		133
		Period <Prd>	[0..1]	±		133
		TaxAmount <TaxAmt>	[0..1]			134
		Rate <Rate>	[0..1]	Rate		134
		TaxableBaseAmount <TaxblBaseAmt>	[0..1]	Amount		134
		TotalAmount <TtlAmt>	[0..1]	Amount		134
		Details <Dtls>	[0..*]	±		134
		AdditionalInformation <AddtlInf>	[0..1]	Text		134

2.1.19.6.1 Type <Tp>*Presence:* [0..1]*Definition:* High level code to identify the type of tax details.*Datatype:* [Max35Text on page 171](#)**2.1.19.6.2 Category <Ctgy>***Presence:* [0..1]*Definition:* Specifies the tax code as published by the tax authority.*Datatype:* [Max35Text on page 171](#)**2.1.19.6.3 CategoryDetails <CtgyDtls>***Presence:* [0..1]*Definition:* Provides further details of the category tax code.*Datatype:* [Max35Text on page 171](#)**2.1.19.6.4 DebtorStatus <DbtrSts>***Presence:* [0..1]*Definition:* Code provided by local authority to identify the status of the party that has drawn up the settlement document.*Datatype:* [Max35Text on page 171](#)**2.1.19.6.5 CertificateIdentification <CertId>***Presence:* [0..1]*Definition:* Identification number of the tax report as assigned by the taxing authority.*Datatype:* [Max35Text on page 171](#)**2.1.19.6.6 FormsCode <FrmsCd>***Presence:* [0..1]*Definition:* Identifies, in a coded form, on which template the tax report is to be provided.*Datatype:* [Max35Text on page 171](#)**2.1.19.6.7 Period <Prd>***Presence:* [0..1]*Definition:* Set of elements used to provide details on the period of time related to the tax payment.**Period <Prd>** contains the following elements (see [TaxPeriod2 on page 135](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Year <Yr>	[0..1]	Date		135
		Type <Tp>	[0..1]	CodeSet		135
		FromDate <FrToDt>	[0..1]	±		136

2.1.19.6.8 TaxAmount <TaxAmt>

Presence: [0..1]

Definition: Set of elements used to provide information on the amount of the tax record.

TaxAmount <TaxAmt> contains the following **TaxAmount2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Rate <Rate>	[0..1]	Rate		134
		TaxableBaseAmount <TaxblBaseAmt>	[0..1]	Amount		134
		TotalAmount <TtlAmt>	[0..1]	Amount		134
		Details <Dtls>	[0..*]	±		134

2.1.19.6.8.1 Rate <Rate>

Presence: [0..1]

Definition: Rate used to calculate the tax.

Datatype: [PercentageRate](#) on page 169

2.1.19.6.8.2 TaxableBaseAmount <TaxblBaseAmt>

Presence: [0..1]

Definition: Amount of money on which the tax is based.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 137

2.1.19.6.8.3 TotalAmount <TtlAmt>

Presence: [0..1]

Definition: Total amount that is the result of the calculation of the tax for the record.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 137

2.1.19.6.8.4 Details <Dtls>

Presence: [0..*]

Definition: Set of elements used to provide details on the tax period and amount.

Details <Dtls> contains the following elements (see [TaxRecordDetails2](#) on page 129 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Period <Prd>	[0..1]	±		129
		Amount <Amt>	[1..1]	Amount		129

2.1.19.6.9 AdditionalInformation <AddtlInf>

Presence: [0..1]

Definition: Further details of the tax record.

Datatype: [Max140Text](#) on page 170

2.1.19.7 TaxPeriod2

Definition: Period of time details related to the tax payment.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Year <Yr>	[0..1]	Date		135
		Type <Tp>	[0..1]	CodeSet		135
		FromDate <FrToDt>	[0..1]	±		136

2.1.19.7.1 Year <Yr>

Presence: [0..1]

Definition: Year related to the tax payment.

Datatype: [ISODate on page 165](#)

2.1.19.7.2 Type <Tp>

Presence: [0..1]

Definition: Identification of the period related to the tax payment.

Datatype: [TaxRecordPeriod1Code on page 163](#)

CodeName	Name	Definition
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.

CodeName	Name	Definition
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.

2.1.19.7.3 FromToDate <FrToDt>

Presence: [0..1]

Definition: Range of time between a start date and an end date for which the tax report is provided.

FromToDate <FrToDt> contains the following elements (see [DatePeriod2](#) on page 29 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FromDate <FrDt>	[1..1]	Date		29
		ToDate <ToDt>	[1..1]	Date		29

2.2 Message Datatypes

2.2.1 Amount

2.2.1.1 ActiveCurrencyAndAmount

Definition: A number of monetary units specified in an active currency where the unit of currency is explicit and compliant with ISO 4217.

Type: Amount

This data type contains the following XML attribute:

Name	Attribute XML Name	Datatype
Currency	Ccy	ActiveCurrencyCode on page 138

Format

minInclusive	0
totalDigits	18
fractionDigits	5

Constraints

- **ActiveCurrency**

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00005
- *Error Text:* Invalid currency code

- **CurrencyAmount**

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

2.2.1.2 ActiveOrHistoricCurrencyAndAmount

Definition: A number of monetary units specified in an active or a historic currency where the unit of currency is explicit and compliant with ISO 4217.

Type: Amount

This data type contains the following XML attribute:

Name	Attribute XML Name	Datatype
Currency	Ccy	ActiveOrHistoricCurrencyCode on page 139

Format

minInclusive	0
totalDigits	18
fractionDigits	5

Constraints

- **ActiveOrHistoricCurrency**

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

- **CurrencyAmount**

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

2.2.2 CodeSet

2.2.2.1 ActiveCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern [A-Z]{3,3}

Constraints

- **ActiveCurrency**

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00005
- *Error Text:* Invalid currency code

Restricts

ParentCurrencyCode on page 158

2.2.2.2 ActiveOrHistoricCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme, as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern [A-Z]{3,3}

Constraints

- **ActiveOrHistoricCurrency**

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

Restricts

[ParentCurrencyCode on page 158](#)

2.2.2.3 AddressType2Code

Definition: Specifies the type of address.

Type: CodeSet

CodeName	Name	Definition
ADDR	Postal	Address is the complete postal address.
PBOX	POBox	Address is a postal office (PO) box.
HOME	Residential	Address is the home address.
BIZZ	Business	Address is the business address.
MLTO	MailTo	Address is the address to which mail is sent.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.

Restricts

[AddressTypeCode on page 139](#)

2.2.2.4 AddressTypeCode

Definition: Specifies the type of address.

Type: CodeSet

CodeName	Name	Definition
HOME	Residential	Address is the home address.
BIZZ	Business	Address is the business address.
ADDR	Postal	Address is the complete postal address.
PBOX	POBox	Address is a postal office (PO) box.
MLTO	MailTo	Address is the address to which mail is sent.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.

Is restricted by

[AddressType2Code](#) on page 139

2.2.2.5 AmountDirectionCode

Definition: Specifies if an operation is an increase or a decrease or the result of a reversal operation.

Type: CodeSet

CodeName	Name	Definition
DBIT	Debit	Operation is a decrease.
CRDT	Credit	Operation is an increase.
RVDB	ReversalDebit	Credit entry used to reverse a previously booked debit entry.
RVCD	ReversalCredit	Debit entry used to reverse a previously booked credit entry.

Is restricted by

[CreditDebitCode](#) on page 142

2.2.2.6 ChargeBearerType1Code

Definition: Specifies which party(ies) will pay charges due for processing of the instruction.

Type: CodeSet

CodeName	Name	Definition
DEBT	BorneByDebtor	All transaction charges are to be borne by the debtor.
CRED	BorneByCreditor	All transaction charges are to be borne by the creditor.
SHAR	Shared	In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor,

CodeName	Name	Definition
		transaction charges on the receiver side are to be borne by the debtor.
SLEV	FollowingServiceLevel	Charges are to be applied following the rules agreed in the service level and/or scheme.

Restricts

[ChargeBearerTypeCode on page 141](#)

2.2.2.7 ChargeBearerTypeCode

Definition: Specifies which party(ies) will pay charges due for processing of the instruction.

Type: CodeSet

CodeName	Name	Definition
DEBT	BorneByDebtor	All transaction charges are to be borne by the debtor.
CRED	BorneByCreditor	All transaction charges are to be borne by the creditor.
SHAR	Shared	In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor.
SLEV	FollowingServiceLevel	Charges are to be applied following the rules agreed in the service level and/or scheme.

Is restricted by

[ChargeBearerType1Code on page 140](#)

2.2.2.8 ClearingChannel2Code

Definition: Specifies the clearing channel for the routing of the transaction, as part of the payment type identification.

Type: CodeSet

CodeName	Name	Definition
RTGS	RealTimeGrossSettlementSystem	Clearing channel is a real-time gross settlement system.
RTNS	RealTimeNetSettlementSystem	Clearing channel is a real-time net settlement system.
MPNS	MassPaymentNetSystem	Clearing channel is a mass payment net settlement system.
BOOK	BookTransfer	Payment through internal book transfer.

Restricts

[ClearingChannelCode on page 142](#)

2.2.2.9 ClearingChannelCode

Definition: Specifies the clearing channel for the routing of the transaction, as part of the payment type identification.

Type: CodeSet

CodeName	Name	Definition
RTGS	RealTimeGrossSettlementSystem	Clearing channel is a real-time gross settlement system.
RTNS	RealTimeNetSettlementSystem	Clearing channel is a real-time net settlement system.
MPNS	MassPaymentNetSystem	Clearing channel is a mass payment net settlement system.
BOOK	BookTransfer	Payment through internal book transfer.

Is restricted by

[ClearingChannel2Code on page 141](#)

2.2.2.10 CountryCode

Definition: Code to identify a country, a dependency, or another area of particular geopolitical interest, on the basis of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Type: CodeSet

Format

pattern [A-Z]{2,2}

Constraints

- **Country**

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

2.2.2.11 CreditDebitCode

Definition: Specifies if an operation is an increase or a decrease.

Type: CodeSet

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.

CodeName	Name	Definition
DBIT	Debit	Operation is a decrease.

Restricts

AmountDirectionCode on page 140

2.2.2.12 DocumentType3Code

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

CodeName	Name	Definition
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, for example, in a cover scenario.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
DISP	DispatchAdvice	Document is a dispatch advice.
PUOR	PurchaseOrder	Document is a purchase order.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.

Restricts

DocumentTypeCode on page 144

2.2.2.13 DocumentType6Code

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

CodeName	Name	Definition
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
CINV	CommercialInvoice	Document is an invoice.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.

CodeName	Name	Definition
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
DISP	DispatchAdvice	Document is a dispatch advice.
BOLD	BillOfLading	Document is a shipping notice.
VCHR	Voucher	Document is an electronic payment document.
AROJ	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
PUOR	PurchaseOrder	Document is a purchase order.

Restricts

DocumentTypeCode on page 144

2.2.2.14 DocumentTypeCode

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

CodeName	Name	Definition
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
CINV	CommercialInvoice	Document is an invoice.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.

CodeName	Name	Definition
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, for example, in a cover scenario.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
DISP	DispatchAdvice	Document is a dispatch advice.
PUOR	PurchaseOrder	Document is a purchase order.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.
BOLD	BillOfLading	Document is a shipping notice.
VCHR	Voucher	Document is an electronic payment document.
AROJ	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
HRCP	CashierReceipt	When the Sale system print the Cashier copy of the Payment receipt.
CRCP	CustomerReceipt	When the Sale System requires the POI system to print the Customer receipt.
JNRL	Journal	When the POI or the Sale System wants to store a message on the journal printer or electronic journal of the Sale Terminal (it is sometimes a Sale Logging/Journal Printer).
SRCP	SaleReceipt	When the Sale System requires the POI system to print the Sale receipt.

Is restricted by

[DocumentType3Code on page 143](#), [DocumentType6Code on page 143](#)

2.2.2.15 ExternalAccountIdentification1Code

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalAccountIdentificationCode on page 146](#)

2.2.2.16 ExternalAccountIdentificationCode

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalAccountIdentification1Code on page 145](#)

2.2.2.17 ExternalCashAccountType1Code

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalCashAccountTypeCode on page 147](#)

2.2.2.18 ExternalCashAccountTypeCode

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalCashAccountType1Code on page 146](#)

2.2.2.19 ExternalCashClearingSystem1Code

Definition: Specifies the cash clearing system, as published in an external cash clearing system code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	3

Restricts

[ExternalCashClearingSystemCode on page 147](#)

2.2.2.20 ExternalCashClearingSystemCode

Definition: Specifies the cash clearing system, as published in an external cash clearing system code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalCashClearingSystem1Code on page 147](#)

2.2.2.21 ExternalCategoryPurpose1Code

Definition: Specifies the category purpose, as published in an external category purpose code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalCategoryPurposeCode on page 148](#)

2.2.2.22 ExternalCategoryPurposeCode

Definition: Specifies the category purpose, as published in an external category purpose code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalCategoryPurpose1Code on page 148](#)

2.2.2.23 ExternalClearingSystemIdentification1Code

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	5

Restricts

[ExternalClearingSystemIdentificationCode on page 148](#)

2.2.2.24 ExternalClearingSystemIdentificationCode

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	5

Is restricted by

[ExternalClearingSystemIdentification1Code](#) on page 148

2.2.2.25 ExternalDiscountAmountType1Code

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalDiscountAmountTypeCode](#) on page 149

2.2.2.26 ExternalDiscountAmountTypeCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalDiscountAmountType1Code](#) on page 149

2.2.2.27 ExternalDocumentLineType1Code

Definition: Specifies the document line type as published in an external document type code list.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

ExternalDocumentLineTypeCode on page 150

2.2.2.28 ExternalDocumentLineTypeCode

Definition: Specifies the document line type as published in an external document type code list.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

ExternalDocumentLineType1Code on page 149

2.2.2.29 ExternalFinancialInstitutionIdentification1Code

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

ExternalFinancialInstitutionIdentificationCode on page 150

2.2.2.30 ExternalFinancialInstitutionIdentificationCode

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

ExternalFinancialInstitutionIdentification1Code on page 150

2.2.2.31 ExternalGarnishmentType1Code

Definition: Specifies the garnishment type as published in an external document type code list.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

ExternalGarnishmentTypeCode on page 151

2.2.2.32 ExternalGarnishmentTypeCode

Definition: Specifies the garnishment type as published in an external document type code list.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

ExternalGarnishmentType1Code on page 151

2.2.2.33 ExternalLocalInstrument1Code

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	35

Restricts

[ExternalLocalInstrumentCode on page 152](#)

2.2.2.34 ExternalLocalInstrumentCode

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	35

Is restricted by

[ExternalLocalInstrument1Code on page 151](#)

2.2.2.35 ExternalOrganisationIdentification1Code

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalOrganisationIdentificationCode on page 152](#)

2.2.2.36 ExternalOrganisationIdentificationCode

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalOrganisationIdentification1Code on page 152](#)

2.2.2.37 ExternalPersonIdentification1Code

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalPersonIdentificationCode on page 153](#)

2.2.2.38 ExternalPersonIdentificationCode

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalPersonIdentification1Code on page 153](#)

2.2.2.39 ExternalProxyAccountType1Code

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalProxyAccountTypeCode on page 154](#)

2.2.2.40 ExternalProxyAccountTypeCode

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalProxyAccountType1Code on page 153](#)

2.2.2.41 ExternalPurpose1Code

Definition: Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalPurposeCode on page 154](#)

2.2.2.42 ExternalPurposeCode

Definition: Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

ExternalPurpose1Code on page 154

2.2.2.43 ExternalServiceLevel1Code

Definition: Specifies the external service level code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

ExternalServiceLevelCode on page 155

2.2.2.44 ExternalServiceLevelCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

ExternalServiceLevel1Code on page 155

2.2.2.45 ExternalTaxAmountType1Code

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalTaxAmountTypeCode on page 156](#)

2.2.2.46 ExternalTaxAmountTypeCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalTaxAmountType1Code on page 155](#)

2.2.2.47 Instruction3Code

Definition: Specifies further instructions concerning the processing of a payment instruction, provided by the sending clearing agent to the next agent(s).

Type: CodeSet

CodeName	Name	Definition
CHQB	PayCreditorByCheque	(Ultimate) creditor must be paid by cheque.
HOLD	HoldCashForCreditor	Amount of money must be held for the (ultimate) creditor, who will call. Pay on identification.
PHOB	PhoneBeneficiary	Please advise/contact (ultimate) creditor/claimant by phone.
TELB	Telecom	Please advise/contact (ultimate) creditor/claimant by the most efficient means of telecommunication.

Restricts

[InstructionCode on page 157](#)

2.2.2.48 Instruction4Code

Definition: Specifies further instructions concerning the processing of a payment instruction, provided by the sending clearing agent to the next agent(s).

Type: CodeSet

CodeName	Name	Definition
PHOA	PhoneNextAgent	Please advise/contact next agent by phone.
TELA	TelecomNextAgent	Please advise/contact next agent by the most efficient means of telecommunication.

Restricts

InstructionCode on page 157

2.2.2.49 InstructionCode

Definition: Specifies further instructions concerning the processing of a payment instruction.

Type: CodeSet

CodeName	Name	Definition
PBEN	PayTheBeneficiary	(Ultimate) creditor to be paid only after verification of identity.
TTIL	TimeTill	Payment instruction is valid and eligible for execution until the date and time stipulated. Otherwise, the payment instruction will be rejected.
TFRO	TimeFrom	Payment instruction will be valid and eligible for execution from the date and time stipulated.
CHQB	PayCreditorByCheque	(Ultimate) creditor must be paid by cheque.
HOLD	HoldCashForCreditor	Amount of money must be held for the (ultimate) creditor, who will call. Pay on identification.
PHOB	PhoneBeneficiary	Please advise/contact (ultimate) creditor/claimant by phone.
TELB	Telecom	Please advise/contact (ultimate) creditor/claimant by the most efficient means of telecommunication.
PHOA	PhoneNextAgent	Please advise/contact next agent by phone.
TELA	TelecomNextAgent	Please advise/contact next agent by the most efficient means of telecommunication.

Is restricted by

Instruction3Code on page 156, Instruction4Code on page 157

2.2.2.50 NamePrefix2Code

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

CodeName	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).

Restricts

[NamePrefixCode on page 158](#)

2.2.2.51 NamePrefixCode

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

CodeName	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MIST	Mister	Title of the person is Mister or Mr.
MISS	Miss	Title of the person is Miss.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).

Is restricted by

[NamePrefix2Code on page 158](#)

2.2.2.52 ParentCurrencyCode

Definition: Code allocated to a currency, by a maintenance agency, under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds". Valid currency codes are registered with the ISO 4217 Maintenance Agency, and consist of three contiguous letters.

Type: CodeSet

Format

pattern [A-Z]{3,3}

Is restricted by

[ActiveCurrencyCode on page 138](#), [ActiveOrHistoricCurrencyCode on page 139](#)

2.2.2.53 PreferredContactMethod1Code

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

CodeName	Name	Definition
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.

Restricts

[PreferredContactMethodCode on page 159](#)

2.2.2.54 PreferredContactMethodCode

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

CodeName	Name	Definition
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
ONLI	Online	Preferred method used to reach the contact is online.

Is restricted by

[PreferredContactMethod1Code on page 159](#)

2.2.2.55 Priority2Code

Definition: Specifies the priority level of an event.

Type: CodeSet

CodeName	Name	Definition
HIGH	High	Priority level is high.

CodeName	Name	Definition
NORM	Normal	Priority level is normal.

Restricts

[PriorityCode on page 160](#)

2.2.2.56 Priority3Code

Definition: Specifies the priority level of an event.

Type: CodeSet

CodeName	Name	Definition
URGT	Urgent	Priority level is urgent (highest priority possible).
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

Restricts

[PriorityCode on page 160](#)

2.2.2.57 PriorityCode

Definition: Specifies the priority level of an event.

Type: CodeSet

CodeName	Name	Definition
URGT	Urgent	Priority level is urgent (highest priority possible).
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.
LOWW	Low	Priority level is low.

Is restricted by

[Priority2Code on page 159](#), [Priority3Code on page 160](#)

2.2.2.58 RegulatoryReportingType1Code

Definition: Identifies whether the regulatory reporting information applies to the debit side, to the credit side or to both debit and credit sides of the transaction.

Type: CodeSet

CodeName	Name	Definition
CRED	Credit	Regulatory information applies to the credit side.
DEBT	Debit	Regulatory information applies to the debit side.

CodeName	Name	Definition
BOTH	Both	Regulatory information applies to both credit and debit sides.

Restricts

[RegulatoryReportingTypeCode](#) on page 161

2.2.2.59 RegulatoryReportingTypeCode

Definition: Identifies whether the regulatory reporting information applies to the debit side, to the credit side or to both debit and credit sides of the transaction.

Type: CodeSet

CodeName	Name	Definition
CRED	Credit	Regulatory information applies to the credit side.
DEBT	Debit	Regulatory information applies to the debit side.
BOTH	Both	Regulatory information applies to both credit and debit sides.

Is restricted by

[RegulatoryReportingType1Code](#) on page 160

2.2.2.60 RemittanceLocationMethod2Code

Definition: Specifies the method used to deliver the remittance advice information.

Type: CodeSet

CodeName	Name	Definition
FAXI	Fax	Remittance advice information must be faxed.
EDIC	ElectronicDataInterchange	Remittance advice information must be sent through Electronic Data Interchange (EDI).
URID	UniformResourceIdentifier	Remittance advice information needs to be sent to a Uniform Resource Identifier (URI). URI is a compact string of characters that uniquely identify an abstract or physical resource. URI's are the super-set of identifiers, such as URLs, email addresses, ftp sites, etc, and as such, provide the syntax for all of the identification schemes.
EMAL	EMail	Remittance advice information must be sent through e-mail.
POST	Post	Remittance advice information must be sent through postal services.
SMSM	SMS	Remittance advice information must be sent through by phone as a short message service (SMS).

Restricts

[RemittanceLocationMethodCode on page 162](#)

2.2.2.61 RemittanceLocationMethodCode

Definition: Specifies the method used to deliver the remittance advice information.

Type: CodeSet

CodeName	Name	Definition
FAXI	Fax	Remittance advice information must be faxed.
EDIC	ElectronicDataInterchange	Remittance advice information must be sent through Electronic Data Interchange (EDI).
URID	UniformResourceIdentifier	Remittance advice information needs to be sent to a Uniform Resource Identifier (URI). URI is a compact string of characters that uniquely identify an abstract or physical resource. URI's are the super-set of identifiers, such as URLs, email addresses, ftp sites, etc, and as such, provide the syntax for all of the identification schemes.
EMAL	EMail	Remittance advice information must be sent through e-mail.
POST	Post	Remittance advice information must be sent through postal services.
SMSM	SMS	Remittance advice information must be sent through by phone as a short message service (SMS).

Is restricted by

[RemittanceLocationMethod2Code on page 161](#)

2.2.2.62 SettlementMethod1Code

Definition: Specifies the method used to settle the credit transfer instruction.

Type: CodeSet

CodeName	Name	Definition
INDA	InstructedAgent	Settlement is done by the agent instructed to execute a payment instruction.
INGA	InstructingAgent	Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.
COVE	CoverMethod	Settlement is done through a cover payment.
CLRG	ClearingSystem	Settlement is done through a payment clearing system.

Restricts

SettlementMethodCode on page 163

2.2.2.63 SettlementMethodCode

Definition: Specifies the method used to settle the payment instruction.

Type: CodeSet

CodeName	Name	Definition
INDA	InstructedAgent	Settlement is done by the agent instructed to execute a payment instruction.
INGA	InstructingAgent	Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.
COVE	CoverMethod	Settlement is done through a cover payment.
CLRG	ClearingSystem	Settlement is done through a payment clearing system.

Is restricted by

SettlementMethod1Code on page 162

2.2.2.64 TaxRecordPeriod1Code

Definition: Specifies the period related to the tax payment.

Type: CodeSet

CodeName	Name	Definition
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.

CodeName	Name	Definition
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.

Restricts

TaxRecordPeriodCode on page 164

2.2.2.65 TaxRecordPeriodCode

Definition: Specifies the period related to the tax payment.

Type: CodeSet

CodeName	Name	Definition
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.

CodeName	Name	Definition
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.

Is restricted by

[TaxRecordPeriod1Code on page 163](#)

2.2.3 Date

2.2.3.1 ISODate

Definition: A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Type: Date

2.2.4 DateTime

2.2.4.1 ISODateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: DateTime

2.2.5 IdentifierSet

2.2.5.1 AnyBICDec2014Identifier

Definition: Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Identification scheme: SWIFT; AnyBICIdentifier

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Constraints

- **AnyBIC**

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consists of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

2.2.5.2 BICFIDec2014Identifier

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Identification scheme: SWIFT; BICIdentifier

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Constraints

- **BICFI**

Valid BICs for financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consist of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid FI BIC.

2.2.5.3 IBAN2007Identifier

Definition: The International Bank Account Number is a code used internationally by financial institutions to uniquely identify the account of a customer at a financial institution as described in the 2007 edition of the ISO 13616 standard "Banking and related financial services - International Bank Account Number (IBAN)" and replaced by the more recent edition of the standard.

Type: IdentifierSet

Identification scheme: National Banking Association; International Bank Account Number (ISO 13616)

Format

pattern [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}

Constraints

- **IBAN**

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00003
- *Error Text:* Invalid IBAN format or invalid check digits.

2.2.5.4 LEIdentifier

Definition: Legal Entity Identifier is a code allocated to a party as described in ISO 17442 "Financial Services - Legal Entity Identifier (LEI)".

Type: IdentifierSet

Identification scheme: Global LEI System; LEIdentifier

Format

pattern [A-Z0-9]{18,18}[0-9]{2,2}

2.2.5.5 UUIDv4Identifier

Definition: Universally Unique Identifier (UUID) version 4, as described in IETF RFC 4122 "Universally Unique Identifier (UUID) URN Namespace".

Type: IdentifierSet

Identification scheme: RFC4122; UUIDv4

Format

pattern	[a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}
---------	---

2.2.6 Indicator

2.2.6.1 BatchBookingIndicator

Definition: Identifies whether the sending party requests a single debit or credit entry per individual transaction or a batch entry for the sum of the amounts of all transactions.

Type: Indicator

Meaning When True: Identifies that a batch entry for the sum of the amounts of all transactions in the batch or message is requested.

Meaning When False: Identifies that a single entry for each of the transactions in the batch or message is requested.

2.2.6.2 TrueFalseIndicator

Definition: A flag indicating a True or False value.

Type: Indicator

Meaning When True: True

Meaning When False: False

2.2.7 Quantity

2.2.7.1 DecimalNumber

Definition: Number of objects represented as a decimal number, for example 0.75 or 45.6.

Type: Quantity

Format

totalDigits	18
fractionDigits	17

2.2.7.2 Number

Definition: Number of objects represented as an integer.

Type: Quantity

Format

totalDigits	18
fractionDigits	0

2.2.8 Rate

2.2.8.1 BaseOneRate

Definition: Rate expressed as a decimal, for example, 0.7 is 7/10 and 70%.

Type: Rate

Format

totalDigits	11
fractionDigits	10
baseValue	1.0

2.2.8.2 PercentageRate

Definition: Rate expressed as a percentage, that is, in hundredths, for example, 0.7 is 7/10 of a percent, and 7.0 is 7%.

Type: Rate

Format

totalDigits	11
fractionDigits	10
baseValue	100.0

2.2.9 Text

2.2.9.1 Exact4AlphaNumericText

Definition: Specifies an alphanumeric string with a length of 4 characters.

Type: Text

Format

pattern	[a-zA-Z0-9]{4}
---------	----------------

2.2.9.2 Max10Text

Definition: Specifies a character string with a maximum length of 10 characters.

Type: Text

Format

minLength	1
maxLength	10

2.2.9.3 Max128Text

Definition: Specifies a character string with a maximum length of 128 characters.

Type: Text

Format

minLength	1
maxLength	128

2.2.9.4 Max140Text

Definition: Specifies a character string with a maximum length of 140 characters.

Type: Text

Format

minLength	1
maxLength	140

2.2.9.5 Max15NumericText

Definition: Specifies a numeric string with a maximum length of 15 digits.

Type: Text

Format

pattern	[0-9]{1,15}
---------	-------------

2.2.9.6 Max16Text

Definition: Specifies a character string with a maximum length of 16 characters.

Type: Text

Format

minLength	1
maxLength	16

2.2.9.7 Max2048Text

Definition: Specifies a character string with a maximum length of 2048 characters.

Type: Text

Format

minLength	1
maxLength	2048

2.2.9.8 Max34Text

Definition: Specifies a character string with a maximum length of 34 characters.

Type: Text

Format

minLength	1
maxLength	34

2.2.9.9 Max350Text

Definition: Specifies a character string with a maximum length of 350 characters.

Type: Text

Format

minLength	1
maxLength	350

2.2.9.10 Max35Text

Definition: Specifies a character string with a maximum length of 35 characters.

Type: Text

Format

minLength	1
maxLength	35

2.2.9.11 Max4Text

Definition: Specifies a character string with a maximum length of 4 characters.

Type: Text

Format

minLength	1
maxLength	4

2.2.9.12 Max70Text

Definition: Specifies a character string with a maximum length of 70characters.

Type: Text

Format

minLength	1
maxLength	70

2.2.9.13 PhoneNumber

Definition: The collection of information which identifies a specific phone or FAX number as defined by telecom services.

It consists of a "+" followed by the country code (from 1 to 3 characters) then a "-" and finally, any combination of numbers, "(", ")", "+" and "-" (up to 30 characters).

Type: Text

Format

pattern \+[0-9]{1,3}-[0-9()+\-]{1,30}

2.2.10 Time

2.2.10.1 ISOTime

Definition: A particular point in the progression of time in a calendar day expressed in either UTC time format (hh:mm:ss.sssZ), local time with UTC offset format (hh:mm:ss.sss+/-hh:mm), or local time format (hh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: Time

Legal Notices

Copyright

S.W.I.F.T. SC © 2026. All rights reserved.

You may copy this publication within your organisation. Any such copy must include these legal notices.

Confidentiality

This publication may contain Swift or third-party confidential information. Do not disclose this publication outside your organisation without the prior written consent of Swift.

Disclaimer

The information in this publication may change from time to time. You must always refer to the latest available version.

Swift Standards Intellectual Property Rights (IPR) Policy - End-User License Agreement

Swift Standards are licensed subject to the terms and conditions of the *Swift Standards IPR Policy - End-User License Agreement* available at www.swift.com > About Swift > Legal > Swift Standards IPR Policy.

Translations

The English version of Swift documentation is the only official version.

Trademarks and Patents

Swift is the trade name of S.W.I.F.T. SC. The following are registered trademarks of Swift: 3SKey, Innotribe, MyStandards, Sibos, Swift, SwiftNet, the Standards Forum logo, the Swift logo, Swift GPI with logo, the Swift GPI logo, and UETR. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.