

Standards

Standards MX

Message Reference Guide

FinancialInstitutionCreditTransferV08 (pacs.009.001.08)

This publication includes information exported from the MyStandards web platform.

For the official documentation of the messages included in this publication, see the relevant Standards MX Message Reference Guides available on swift.com > Support > Documentation

Table of Contents

1	MX pacs.009.001.08 FinancialInstitutionCreditTransferV08	3
1.1	MessageDefinition Functionality	3
1.2	Structure	4
1.3	Constraints	4
1.4	Message Building Blocks	17
2	Message Items Types	24
2.1	MessageComponents	24
2.2	Message Datatypes	141
	Legal Notices	175

1 MX pacs.009.001.08 FinancialInstitutionCreditTransferV08

1.1 MessageDefinition Functionality

Scope

The FinancialInstitutionCreditTransfer message is sent by a debtor financial institution to a creditor financial institution, directly or through other agents and/or a payment clearing and settlement system.

It is used to move funds from a debtor account to a creditor, where both debtor and creditor are financial institutions.

Usage

The FinancialInstitutionCreditTransfer message is exchanged between agents and can contain one or more credit transfer instructions where debtor and creditor are both financial institutions.

The FinancialInstitutionCreditTransfer message does not allow for grouping: a CreditTransferTransactionInformation block must be present for each credit transfer transaction.

The FinancialInstitutionCreditTransfer message can be used in domestic and cross-border scenarios.

Outline

The FinancialInstitutionCreditTransferV08 MessageDefinition is composed of 3 MessageBuildingBlocks:

A. GroupHeader

Set of characteristics shared by all individual transactions included in the message.

B. CreditTransferTransactionInformation

Set of elements providing information specific to the individual credit transfer(s).

C. SupplementaryData

Additional information that cannot be captured in the structured elements and/or any other specific block.

1.2 Structure

Index	Or	MessageElement/BuildingBlock<XML Tag>	Mult.	Type	Constr. No.	Page
		<i>Message root</i> <Document> <FICdtTrf>	[1..1]		✓C10, ✓C12, ✓C14, ✓C27, C44, C49, ✓C50, ✓C52	
		GroupHeader <GrpHdr>	[1..1]	±	✓C48	17
		CreditTransferTransactionInformation <CdtTrfTxInf>	[1..*]	±	✓C6, ✓C9, ✓C16, ✓C18, ✓C19, ✓C21, ✓C23, ✓C25, ✓C28, ✓C32, ✓C34, ✓C36, ✓C38, C30, C53, C55	17
		SupplementaryData <SplmtryData>	[0..*]	±	C45	23

1.3 Constraints

C1 ActiveCurrency ✓

(Rule)

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00005
- *Error Text:* Invalid currency code

C2 ActiveOrHistoricCurrency ✓

(Rule)

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

C3 AnyBIC ✓*(Rule)*

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consists of eight (8) or eleven (11) contiguous characters. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

C4 BICFI ✓*(Rule)*

Valid BICs for financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consist of eight (8) or eleven (11) contiguous characters. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid FI BIC.

C5 Country ✓*(Rule)*

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code). (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

C6 CreditorAgentAccountRule ✓*(Rule)*

If CreditorAgentAccount is present, then CreditorAgent must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00058
- *Error Text:* Invalid message content for creditor agent account.

C7 CurrencyAmount ✓*(Rule)*

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

C8 CurrencyAmount ✓*(Rule)*

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

C9 DebtorAgentAccountRule ✓*(Rule)*

If DebtorAgentAccount is present, then DebtorAgent must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00059
- *Error Text:* Invalid message content for debtor agent account.

C10 GroupHeaderInterbankSettlementDateRule ✓*(Rule)*

If GroupHeader/InterbankSettlementDate is present, then CreditTransferTransactionInformation/InterbankSettlementDate is not allowed. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00045
- *Error Text:* Invalid message content for interbank settlement date.

This constraint is defined at the MessageDefinition level.

C11 IBAN ✓

(Rule)

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN. (Algorithm)

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00003
- *Error Text:* Invalid IBAN format or invalid check digits.

C12 InstructedAgentRule ✓

(Rule)

If GroupHeader/InstructedAgent is present, then CreditTransferTransactionInformation/InstructedAgent is not allowed. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00008
- *Error Text:* Invalid message content for instructed agent.

This constraint is defined at the MessageDefinition level.

C13 InstructedReimbursementAgentAccountRule ✓

(Rule)

If InstructedReimbursementAgentAccount is present, then InstructedReimbursementAgent must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00037
- *Error Text:* Invalid message content for instructed reimbursement agent account.

C14 InstructingAgentRule ✓

(Rule)

If GroupHeader/InstructingAgent is present, then CreditTransferTransactionInformation/InstructingAgent is not allowed. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00007
- *Error Text:* Invalid message content for instructing agent.

This constraint is defined at the MessageDefinition level.

C15 InstructingReimbursementAgentAccountRule ✓

(Rule)

If InstructingReimbursementAgentAccount is present, then InstructingReimbursementAgent must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00038
- *Error Text:* Invalid message content for instructing reimbursement agent account.

C16 IntermediaryAgent1AccountRule ✓

(Rule)

If IntermediaryAgent1Account is present, then IntermediaryAgent1 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00052
- *Error Text:* Invalid message content for intermediary agent 1 account.

C17 IntermediaryAgent1AccountRule ✓

(Rule)

If IntermediaryAgent1Account is present, then IntermediaryAgent1 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00052
- *Error Text:* Invalid message content for intermediary agent 1 account.

C18 IntermediaryAgent1Rule ✓

(Rule)

If IntermediaryAgent1 is present, then CreditorAgent must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00060
- *Error Text:* Invalid message content for intermediary agent 1.

C19 IntermediaryAgent2AccountRule ✓*(Rule)*

If IntermediaryAgent2Account is present, then IntermediaryAgent2 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00053
- *Error Text:* Invalid message content for intermediary agent 2 account.

C20 IntermediaryAgent2AccountRule ✓*(Rule)*

If IntermediaryAgent2Account is present, then IntermediaryAgent2 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00053
- *Error Text:* Invalid message content for intermediary agent 2 account.

C21 IntermediaryAgent2Rule ✓*(Rule)*

If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00056
- *Error Text:* Invalid message content for intermediary agent 2.

C22 IntermediaryAgent2Rule ✓*(Rule)*

If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00056

- *Error Text:* Invalid message content for intermediary agent 2.

C23 IntermediaryAgent3AccountRule ✓

(Rule)

If IntermediaryAgent3Account is present, then IntermediaryAgent3 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00054
- *Error Text:* Invalid message content for intermediary agent 3 account.

C24 IntermediaryAgent3AccountRule ✓

(Rule)

If IntermediaryAgent3Account is present, then IntermediaryAgent3 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00054
- *Error Text:* Invalid message content for intermediary agent 3 account.

C25 IntermediaryAgent3Rule ✓

(Rule)

If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00057
- *Error Text:* Invalid message content for intermediary agent 3.

C26 IntermediaryAgent3Rule ✓

(Rule)

If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00057
- *Error Text:* Invalid message content for intermediary agent 3.

C27 PaymentTypeInfoInformationRule ✓

(Rule)

If GroupHeader/PaymentTypeInformation is present, then CreditTransferTransactionInformation/PaymentTypeInformation is not allowed. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00009
- *Error Text:* Invalid message content for payment type information.

This constraint is defined at the MessageDefinition level.

C28 PreviousInstructingAgent1AccountRule ✓

(Rule)

If PreviousInstructingAgent1Account is present, then PreviousInstructingAgent1 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00411
- *Error Text:* Invalid message content for previous instructing agent account.

C29 PreviousInstructingAgent1AccountRule ✓

(Rule)

If PreviousInstructingAgent1Account is present, then PreviousInstructingAgent1 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00411
- *Error Text:* Invalid message content for previous instructing agent account.

C30 PreviousInstructingAgent1Guideline

(Guideline)

It is recommended that, when present, PreviousInstructingAgent1 is the closest to the DebtorAgent in the payment chain.

C31 PreviousInstructingAgent1Guideline

(Guideline)

It is recommended that, when present, PreviousInstructingAgent1 is the closest to the DebtorAgent in the payment chain.

C32 PreviousInstructingAgent2AccountRule ✓

(Rule)

If PreviousInstructingAgent2Account is present, then PreviousInstructingAgent2 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00412
- *Error Text:* Invalid message content for previous instructing agent account.

C33 PreviousInstructingAgent2AccountRule ✓*(Rule)*

If PreviousInstructingAgent2Account is present, then PreviousInstructingAgent2 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00412
- *Error Text:* Invalid message content for previous instructing agent account.

C34 PreviousInstructingAgent3AccountRule ✓*(Rule)*

If PreviousInstructingAgent3Account is present, then PreviousInstructingAgent3 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00413
- *Error Text:* Invalid message content for previous instructing agent account.

C35 PreviousInstructingAgent3AccountRule ✓*(Rule)*

If PreviousInstructingAgent3Account is present, then PreviousInstructingAgent3 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00413
- *Error Text:* Invalid message content for previous instructing agent account.

C36 PreviousInstructionAgent2Rule ✓*(Rule)*

If PreviousInstructingAgent2 is present, then PreviousInstructingAgent1 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00415

- *Error Text:* Invalid message content for intermediary agent 1.

C37 PreviousInstructionAgent2Rule ✓

(Rule)

If PreviousInstructingAgent2 is present, then PreviousInstructingAgent1 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00415
- *Error Text:* Invalid message content for intermediary agent 1.

C38 PreviousInstructionAgent3Rule ✓

(Rule)

If PreviousInstructingAgent3 is present, then PreviousInstructingAgent2 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00416
- *Error Text:* Invalid message content for intermediary agent 1.

C39 PreviousInstructionAgent3Rule ✓

(Rule)

If PreviousInstructingAgent3 is present, then PreviousInstructingAgent2 must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00416
- *Error Text:* Invalid message content for intermediary agent 1.

C40 SettlementMethodAgentRule ✓

(Rule)

If SettlementMethod is equal to INDA or INGA, then ReimbursementAgent(s) and ClearingSystem are not allowed. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00018
- *Error Text:* Invalid message content for settlement method INGA or INDA.

C41 SettlementMethodClearingRule ✓

(Rule)

If SettlementMethod is equal to CLRG, then SettlementAccount and ReimbursementAgent(s) are not allowed. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00019
- *Error Text:* Invalid message content for settlement method CLRG.

C42 SettlementMethodCoverAgentRule ✓

(Rule)

If SettlementMethod is equal to COVE, then InstructedReimbursementAgent or InstructingReimbursementAgent must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00076
- *Error Text:* Invalid message content for cover settlement method and reimbursement agents.

C43 SettlementMethodCoverRule ✓

(Rule)

If SettlementMethod is equal to COVE, then SettlementAccount and ClearingSystem are not allowed. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00075
- *Error Text:* Invalid message content for cover settlement method with settlement account and clearing system.

C44 SupplementaryDataRule

(Rule)

The SupplementaryData building block at message level must not be used to provide additional information about a transaction. The SupplementaryData element at transaction level should be used for that purpose.

This constraint is defined at the MessageDefinition level.

C45 SupplementaryDataRule

(Rule)

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

C46 ThirdReimbursementAgentAccountRule ✓

(Rule)

If ThirdReimbursementAgentAccount is present, then ThirdReimbursementAgent must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00039
- *Error Text:* Invalid message content for third reimbursement agent account.

C47 ThirdReimbursementAgentRule ✓*(Rule)*

If ThirdReimbursementAgent is present, then InstructingReimbursementAgent and InstructedReimbursementAgent must both be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00040
- *Error Text:* Invalid message content for third reimbursement agent.

C48 TotalInterbankSettlementAmountAndDateRule ✓*(Rule)*

If TotalInterbankSettlementAmount is present, then InterbankSettlementDate must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00044
- *Error Text:* Invalid message content for group header interbank settlement date.

C49 TotalInterbankSettlementAmountAndSumRule*(Rule)*

If GroupHeader/TotalInterbankSettlementAmount is present, then it must equal the sum of all occurrences of CreditTransferTransactionInformation/InterbankSettlementAmount. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00043
- *Error Text:* Invalid message content for the total interbank settlement amount and sum of individual interbank settlement amounts.

This constraint is defined at the MessageDefinition level.

C50 TotalInterbankSettlementAmountRule ✓*(Rule)*

If GroupHeader/TotalInterbankSettlementAmount is present, then all occurrences of CreditTransferTransactionInformation/InterbankSettlementAmount must have the same currency as the currency of GroupHeader/TotalInterbankSettlementAmount. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00042
- *Error Text:* Invalid message content for the total interbank settlement amount and individual interbank settlement amount currencies.

This constraint is defined at the MessageDefinition level.

C51 TransactionIdentificationPresenceRule

(Rule)

TransactionIdentification or UETR must be present. Both may be present (CrossElementSimpleRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00420
- *Error Text:* No transaction identification is present

C52 TransactionInterbankSettlementDateRule ✓

(Rule)

If GroupHeader/InterbankSettlementDate is not present, then CreditTransferTransactionInformation/InterbankSettlementDate must be present. (CrossElementComplexRule)

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00290
- *Error Text:* Invalid message content for interbank settlement date.

This constraint is defined at the MessageDefinition level.

C53 UltimateCreditorGuideline

(Guideline)

UltimateCreditor may only be present if different from Creditor.

C54 UltimateCreditorGuideline

(Guideline)

UltimateCreditor may only be present if different from Creditor.

C55 UltimateDebtorGuideline

(Guideline)

UltimateDebtor may only be present if different from Debtor.

C56 UltimateDebtorGuideline

(Guideline)

UltimateDebtor may only be present if different from Debtor.

1.4 Message Building Blocks

This chapter describes the MessageBuildingBlocks of this MessageDefinition.

1.4.1 GroupHeader <GrpHdr>

Presence: [1..1]

Definition: Set of characteristics shared by all individual transactions included in the message.

Impacted by: ✓C48 TotalInterbankSettlementAmountAndDateRule ✓

GroupHeader <GrpHdr> contains the following elements (see [GroupHeader93](#) on page 43 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		MessageIdentification <MsgId>	[1..1]	Text		44
		CreationDateTime <CreDtTm>	[1..1]	DateTime		44
		BatchBooking <BtchBookg>	[0..1]	Indicator		44
		NumberOfTransactions <NbOfTx>	[1..1]	Text		45
		ControlSum <CtrlSum>	[0..1]	Quantity		45
		TotalInterbankSettlementAmount <TtlIntrBkSttlmAmt>	[0..1]	Amount		45
		InterbankSettlementDate <IntrBkSttlmDt>	[0..1]	Date		45
		SettlementInformation <SttlmInf>	[1..1]	±		45
		PaymentTypeInformation <PmtTpInf>	[0..1]	±		46
		InstructingAgent <InstgAgt>	[0..1]	±		47
		InstructedAgent <InstdAgt>	[0..1]	±		47

Constraints

- **TotalInterbankSettlementAmountAndDateRule**

If TotalInterbankSettlementAmount is present, then InterbankSettlementDate must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00044
- *Error Text:* Invalid message content for group header interbank settlement date.

1.4.2 CreditTransferTransactionInformation <CdtTrfTxInf>

Presence: [1..*]

Definition: Set of elements providing information specific to the individual credit transfer(s).

Impacted by: ✓C6 CreditorAgentAccountRule ✓, ✓C9 DebtorAgentAccountRule ✓,
✓C16 IntermediaryAgent1AccountRule ✓, ✓C18 IntermediaryAgent1Rule ✓,

✓C19 IntermediaryAgent2AccountRule ✓, ✓C21 IntermediaryAgent2Rule ✓,
✓C23 IntermediaryAgent3AccountRule ✓, ✓C25 IntermediaryAgent3Rule ✓, ✓C28
PreviousInstructingAgent1AccountRule ✓, ✓C32 PreviousInstructingAgent2AccountRule ✓,
✓C34 PreviousInstructingAgent3AccountRule ✓, ✓C36 PreviousInstructionAgent2Rule ✓,
✓C38 PreviousInstructionAgent3Rule ✓, C30 PreviousInstructingAgent1Guideline, C53
UltimateCreditorGuideline, C55 UltimateDebtorGuideline

CreditTransferTransactionInformation <CdtTrfTxInf> contains the following elements (see [CreditTransferTransaction36](#) on page 69 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PaymentIdentification <PmtId>	[1..1]	±		74
		PaymentTypeInfoInformation <PmtTpInf>	[0..1]	±		74
		InterbankSettlementAmount <IntrBkSttlmAmt>	[1..1]	Amount		74
		InterbankSettlementDate <IntrBkSttlmDt>	[0..1]	Date		75
		SettlementPriority <SttlmPrty>	[0..1]	CodeSet		75
		SettlementTimeIndication <SttlmTmIndctn>	[0..1]			75
		DebitDateTime <DbtDtTm>	[0..1]	DateTime		75
		CreditDateTime <CdtDtTm>	[0..1]	DateTime		75
		SettlementTimeRequest <SttlmTmReq>	[0..1]	±		76
		PreviousInstructingAgent1 <PrvsInstgAgt1>	[0..1]	±		76
		PreviousInstructingAgent1Account <PrvsInstgAgt1Acct>	[0..1]	±		76
		PreviousInstructingAgent2 <PrvsInstgAgt2>	[0..1]	±		76
		PreviousInstructingAgent2Account <PrvsInstgAgt2Acct>	[0..1]	±		77
		PreviousInstructingAgent3 <PrvsInstgAgt3>	[0..1]	±		77
		PreviousInstructingAgent3Account <PrvsInstgAgt3Acct>	[0..1]	±		77
		InstructingAgent <InstgAgt>	[0..1]	±		78
		InstructedAgent <InstdAgt>	[0..1]	±		78
		IntermediaryAgent1 <IntrmyAgt1>	[0..1]	±		78
		IntermediaryAgent1Account <IntrmyAgt1Acct>	[0..1]	±		79
		IntermediaryAgent2 <IntrmyAgt2>	[0..1]	±		79
		IntermediaryAgent2Account <IntrmyAgt2Acct>	[0..1]	±		79
		IntermediaryAgent3 <IntrmyAgt3>	[0..1]	±		80
		IntermediaryAgent3Account <IntrmyAgt3Acct>	[0..1]	±		80
		UltimateDebtor <UltmtDbtr>	[0..1]	±		80
		Debtor <Dbtr>	[1..1]	±		81
		DebtorAccount <DbtrAcct>	[0..1]	±		81
		DebtorAgent <DbtrAgt>	[0..1]	±		81
		DebtorAgentAccount <DbtrAgtAcct>	[0..1]	±		82
		CreditorAgent <CdtrAgt>	[0..1]	±		82

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CreditorAgentAccount <CdtrAgtAcct>	[0..1]	±		82
		Creditor <Cdtr>	[1..1]	±		83
		CreditorAccount <CdtrAcct>	[0..1]	±		83
		UltimateCreditor <UltmtCdtr>	[0..1]	±		83
		InstructionForCreditorAgent <InstrForCdtrAgt>	[0..*]	±		84
		InstructionForNextAgent <InstrForNxtAgt>	[0..*]			84
		Code <Cd>	[0..1]	CodeSet		84
		InstructionInformation <InstrInf>	[0..1]	Text		85
		Purpose <Purp>	[0..1]	±		85
		RemittanceInformation <RmtInf>	[0..1]	±		85
		UnderlyingCustomerCreditTransfer <UndrlygCstmrCdtTrf>	[0..1]	±		85
		SupplementaryData <SplmtryData>	[0..*]	±		87

Constraints

- **CreditorAgentAccountRule**

If CreditorAgentAccount is present, then CreditorAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00058
- *Error Text:* Invalid message content for creditor agent account.

- **DebtorAgentAccountRule**

If DebtorAgentAccount is present, then DebtorAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00059
- *Error Text:* Invalid message content for debtor agent account.

- **IntermediaryAgent1AccountRule**

If IntermediaryAgent1Account is present, then IntermediaryAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00052
- *Error Text:* Invalid message content for intermediary agent 1 account.

- **IntermediaryAgent1Rule**

If IntermediaryAgent1 is present, then CreditorAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00060
- *Error Text:* Invalid message content for intermediary agent 1.

- **IntermediaryAgent2AccountRule**

If IntermediaryAgent2Account is present, then IntermediaryAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00053
- *Error Text:* Invalid message content for intermediary agent 2 account.

- **IntermediaryAgent2Rule**

If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00056
- *Error Text:* Invalid message content for intermediary agent 2.

- **IntermediaryAgent3AccountRule**

If IntermediaryAgent3Account is present, then IntermediaryAgent3 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00054
- *Error Text:* Invalid message content for intermediary agent 3 account.

- **IntermediaryAgent3Rule**

If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00057
- *Error Text:* Invalid message content for intermediary agent 3.

- **PreviousInstructingAgent1AccountRule**

If PreviousInstructingAgent1Account is present, then PreviousInstructingAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00411
- *Error Text:* Invalid message content for previous instructing agent account.

- **PreviousInstructingAgent1Guideline**

It is recommended that, when present, PreviousInstructingAgent1 is the closest to the DebtorAgent in the payment chain.

- **PreviousInstructingAgent2AccountRule**

If PreviousInstructingAgent2Account is present, then PreviousInstructingAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00412
- *Error Text:* Invalid message content for previous instructing agent account.

- **PreviousInstructingAgent3AccountRule**

If PreviousInstructingAgent3Account is present, then PreviousInstructingAgent3 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00413
- *Error Text:* Invalid message content for previous instructing agent account.

- **PreviousInstructionAgent2Rule**

If PreviousInstructingAgent2 is present, then PreviousInstructingAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00415
- *Error Text:* Invalid message content for intermediary agent 1.

- **PreviousInstructionAgent3Rule**

If PreviousInstructingAgent3 is present, then PreviousInstructingAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00416
- *Error Text:* Invalid message content for intermediary agent 1.

- **UltimateCreditorGuideline**

UltimateCreditor may only be present if different from Creditor.

- **UltimateDebtorGuideline**

UltimateDebtor may only be present if different from Debtor.

1.4.3 SupplementaryData <SplmtryData>

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

Impacted by: [C45 SupplementaryDataRule](#)

SupplementaryData <SplmtryData> contains the following elements (see [SupplementaryData1](#) on page 47 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PlaceAndName <PlcAndNm>	[0..1]	Text		47
		Envelope <Envlp>	[1..1]	(External Schema)		48

Constraints

- **SupplementaryDataRule**

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

2 Message Items Types

2.1 MessageComponents

2.1.1 Account

2.1.1.1 CashAccount38

Definition: Provides the details to identify an account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.1.1.1 Identification <Id>

Presence: [1..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

Identification <Id> contains one of the following elements (see [AccountIdentification4Choice](#) on page 28 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	IBAN <IBAN>	[1..1]	IdentifierSet		28
	Or}	Other <Othr>	[1..1]	±		28

2.1.1.1.2 Type <Tp>

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

Type <Tp> contains one of the following elements (see [CashAccountType2Choice](#) on page 26 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		26
	Or}	Proprietary <Prtry>	[1..1]	Text		26

2.1.1.1.3 Currency <Ccy>

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: [ActiveOrHistoricCurrencyCode](#) on page 144

2.1.1.1.4 Name <Nm>

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: [Max70Text](#) on page 173

2.1.1.1.5 Proxy <Prxy>

Presence: [0..1]

Definition: Specifies an alternate assumed name for the identification of the account.

Proxy <Prxy> contains the following elements (see [ProxyAccountIdentification1](#) on page 25 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			25
	{Or	Code <Cd>	[1..1]	CodeSet		26
	Or}	Proprietary <Prtry>	[1..1]	Text		26
		Identification <Id>	[1..1]	Text		26

2.1.1.2 ProxyAccountIdentification1

Definition: Information related to a proxy identification of the account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			25
	{Or	Code <Cd>	[1..1]	CodeSet		26
	Or}	Proprietary <Prtry>	[1..1]	Text		26
		Identification <Id>	[1..1]	Text		26

2.1.1.2.1 Type <Tp>

Presence: [0..1]

Definition: Type of the proxy identification.

Type <Tp> contains one of the following **ProxyAccountType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		26
	Or}	Proprietary <Prtry>	[1..1]	Text		26

2.1.1.2.1.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: [ExternalProxyAccountType1Code on page 157](#)

2.1.1.2.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: [Max35Text on page 173](#)

2.1.1.2.2 Identification <Id>

Presence: [1..1]

Definition: Identification used to indicate the account identification under another specified name.

Datatype: [Max2048Text on page 172](#)

2.1.1.3 CashAccountType2Choice

Definition: Nature or use of the account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		26
	Or}	Proprietary <Prtry>	[1..1]	Text		26

2.1.1.3.1 Code <Cd>

Presence: [1..1]

Definition: Account type, in a coded form.

Datatype: [ExternalCashAccountType1Code on page 150](#)

2.1.1.3.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Nature or use of the account in a proprietary form.

Datatype: [Max35Text on page 173](#)

2.1.1.4 GenericAccountIdentification1

Definition: Information related to a generic account identification.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		27
		SchemeName <SchmeNm>	[0..1]			27
	{Or	Code <Cd>	[1..1]	CodeSet		27
	Or}	Proprietary <Prtry>	[1..1]	Text		27
		Issuer <Issr>	[0..1]	Text		27

2.1.1.4.1 Identification <Id>

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: [Max34Text on page 173](#)

2.1.1.4.2 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Name of the identification scheme.

SchemeName <SchmeNm> contains one of the following **AccountSchemeName1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		27
	Or}	Proprietary <Prtry>	[1..1]	Text		27

2.1.1.4.2.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: [ExternalAccountIdentification1Code on page 149](#)

2.1.1.4.2.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: [Max35Text on page 173](#)

2.1.1.4.3 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: [Max35Text on page 173](#)

2.1.2 Account Identification

2.1.2.1 AccountIdentification4Choice

Definition: Specifies the unique identification of an account as assigned by the account servicer.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	IBAN <IBAN>	[1..1]	IdentifierSet		28
	Or}	Other <Othr>	[1..1]	±		28

2.1.2.1.1 IBAN <IBAN>

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: [IBAN2007Identifier on page 169](#)

2.1.2.1.2 Other <Othr>

Presence: [1..1]

Definition: Unique identification of an account, as assigned by the account servicer, using an identification scheme.

Other <Othr> contains the following elements (see [GenericAccountIdentification1 on page 26](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		27
		SchemeName <SchmeNm>	[0..1]			27
	{Or	Code <Cd>	[1..1]	CodeSet		27
	Or}	Proprietary <Prtry>	[1..1]	Text		27
		Issuer <Issr>	[0..1]	Text		27

2.1.3 Date Period

2.1.3.1 DatePeriod2

Definition: Range of time defined by a start date and an end date.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FromDate <FrDt>	[1..1]	Date		29
		ToDate <ToDt>	[1..1]	Date		29

2.1.3.1.1 FromDate <FrDt>

Presence: [1..1]

Definition: Start date of the range.

Datatype: ISODate on page 168

2.1.3.1.2 ToDate <ToDt>

Presence: [1..1]

Definition: End date of the range.

Datatype: ISODate on page 168

2.1.4 Document

2.1.4.1 CreditorReferenceInformation2

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			29
		CodeOrProprietary <CdOrPrtry>	[1..1]			29
	{Or	Code <Cd>	[1..1]	CodeSet		30
	Or}	Proprietary <Prtry>	[1..1]	Text		30
		Issuer <Issr>	[0..1]	Text		30
		Reference <Ref>	[0..1]	Text		30

2.1.4.1.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of creditor reference.

Type <Tp> contains the following **CreditorReferenceType2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CodeOrProprietary <CdOrPrtry>	[1..1]			29
	{Or	Code <Cd>	[1..1]	CodeSet		30
	Or}	Proprietary <Prtry>	[1..1]	Text		30
		Issuer <Issr>	[0..1]	Text		30

2.1.4.1.1.1 CodeOrProprietary <CdOrPrtry>

Presence: [1..1]

Definition: Coded or proprietary format creditor reference type.

CodeOrProprietary <CdOrPrtry> contains one of the following **CreditorReferenceType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		30
	Or}	Proprietary <Prtry>	[1..1]	Text		30

2.1.4.1.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Type of creditor reference, in a coded form.

Datatype: [DocumentType3Code on page 147](#)

CodeName	Name	Definition
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, for example, in a cover scenario.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
DISP	DispatchAdvice	Document is a dispatch advice.
PUOR	PurchaseOrder	Document is a purchase order.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.

2.1.4.1.1.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Creditor reference type, in a proprietary form.

Datatype: [Max35Text on page 173](#)

2.1.4.1.1.2 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the credit reference type.

Datatype: [Max35Text on page 173](#)

2.1.4.1.2 Reference <Ref>

Presence: [0..1]

Definition: Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction.

Usage: If available, the initiating party should provide this reference in the structured remittance information, to enable reconciliation by the creditor upon receipt of the amount of money.

If the business context requires the use of a creditor reference or a payment remit identification, and only one identifier can be passed through the end-to-end chain, the creditor's reference or payment remittance identification should be quoted in the end-to-end transaction identification.

Datatype: [Max35Text](#) on page 173

2.1.5 Financial Institution Identification

2.1.5.1 FinancialInstitutionIdentification18

Definition: Specifies the details to identify a financial institution.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		BICFI <BICFI>	[0..1]	IdentifierSet		31
		ClearingSystemMemberIdentification <ClrSysMmbld>	[0..1]	±		31
		LEI <LEI>	[0..1]	IdentifierSet		31
		Name <Nm>	[0..1]	Text		32
		PostalAddress <PstlAdr>	[0..1]	±		32
		Other <Othr>	[0..1]	±		32

2.1.5.1.1 BICFI <BICFI>

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: [BICFIDec2014Identifier](#) on page 169

2.1.5.1.2 ClearingSystemMemberIdentification <ClrSysMmbld>

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

ClearingSystemMemberIdentification <ClrSysMmbld> contains the following elements (see [ClearingSystemMemberIdentification2](#) on page 36 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ClearingSystemIdentification <ClrSysId>	[0..1]	±		36
		MemberIdentification <Mmbld>	[1..1]	Text		37

2.1.5.1.3 LEI <LEI>

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: [LEIIdentifier](#) on page 170

2.1.5.1.4 Name <Nm>*Presence:* [0..1]*Definition:* Name by which an agent is known and which is usually used to identify that agent.*Datatype:* [Max140Text](#) on page 172**2.1.5.1.5 PostalAddress <PstlAdr>***Presence:* [0..1]*Definition:* Information that locates and identifies a specific address, as defined by postal services.**PostalAddress <PstlAdr>** contains the following elements (see [PostalAddress24](#) on page 96 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AddressType <AdrTp>	[0..1]			96
	{Or	Code <Cd>	[1..1]	CodeSet		97
	Or}	Proprietary <Prtry>	[1..1]	±		97
		Department <Dept>	[0..1]	Text		97
		SubDepartment <SubDept>	[0..1]	Text		97
		StreetName <StrtNm>	[0..1]	Text		98
		BuildingNumber <BldgNb>	[0..1]	Text		98
		BuildingName <BldgNm>	[0..1]	Text		98
		Floor <Flr>	[0..1]	Text		98
		PostBox <PstBx>	[0..1]	Text		98
		Room <Room>	[0..1]	Text		98
		PostCode <PstCd>	[0..1]	Text		98
		TownName <TwnNm>	[0..1]	Text		98
		TownLocationName <TwnLctnNm>	[0..1]	Text		99
		DistrictName <DstrctNm>	[0..1]	Text		99
		CountrySubDivision <CtrySubDvsn>	[0..1]	Text		99
		Country <Ctry>	[0..1]	CodeSet		99
		AddressLine <AdrLine>	[0..7]	Text		99

2.1.5.1.6 Other <Othr>*Presence:* [0..1]*Definition:* Unique identification of an agent, as assigned by an institution, using an identification scheme.

Other <Othr> contains the following elements (see [GenericFinancialIdentification1](#) on page 34 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		34
		SchemeName <SchmeNm>	[0..1]			35
	{Or	Code <Cd>	[1..1]	CodeSet		35
	Or}	Proprietary <Prtry>	[1..1]	Text		35
		Issuer <Issr>	[0..1]	Text		35

2.1.5.2 BranchData3

Definition: Information that locates and identifies a specific branch of a financial institution.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[0..1]	Text		33
		LEI <LEI>	[0..1]	IdentifierSet		33
		Name <Nm>	[0..1]	Text		33
		PostalAddress <PstlAdr>	[0..1]	±		33

2.1.5.2.1 Identification <Id>

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: [Max35Text](#) on page 173

2.1.5.2.2 LEI <LEI>

Presence: [0..1]

Definition: Legal entity identification for the branch of the financial institution.

Datatype: [LEIIdentifier](#) on page 170

2.1.5.2.3 Name <Nm>

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: [Max140Text](#) on page 172

2.1.5.2.4 PostalAddress <PstlAdr>

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

PostalAddress <PstlAdr> contains the following elements (see [PostalAddress24](#) on page 96 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AddressType <AdrTp>	[0..1]			96
	{Or	Code <Cd>	[1..1]	CodeSet		97
	Or}	Proprietary <Prtry>	[1..1]	±		97
		Department <Dept>	[0..1]	Text		97
		SubDepartment <SubDept>	[0..1]	Text		97
		StreetName <StrtNm>	[0..1]	Text		98
		BuildingNumber <BldgNb>	[0..1]	Text		98
		BuildingName <BldgNm>	[0..1]	Text		98
		Floor <Flr>	[0..1]	Text		98
		PostBox <PstBx>	[0..1]	Text		98
		Room <Room>	[0..1]	Text		98
		PostCode <PstCd>	[0..1]	Text		98
		TownName <TwnNm>	[0..1]	Text		98
		TownLocationName <TwnLctnNm>	[0..1]	Text		99
		DistrictName <DstrctNm>	[0..1]	Text		99
		CountrySubDivision <CtrySubDvsn>	[0..1]	Text		99
		Country <Ctry>	[0..1]	CodeSet		99
		AddressLine <AdrLine>	[0..7]	Text		99

2.1.5.3 GenericFinancialIdentification1

Definition: Information related to an identification of a financial institution.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		34
		SchemeName <SchmeNm>	[0..1]			35
	{Or	Code <Cd>	[1..1]	CodeSet		35
	Or}	Proprietary <Prtry>	[1..1]	Text		35
		Issuer <Issr>	[0..1]	Text		35

2.1.5.3.1 Identification <Id>

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: [Max35Text on page 173](#)

2.1.5.3.2 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Name of the identification scheme.

SchemeName <SchmeNm> contains one of the following **FinancialIdentificationSchemeName1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		35
	Or}	Proprietary <Prtry>	[1..1]	Text		35

2.1.5.3.2.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: [ExternalFinancialInstitutionIdentification1Code on page 154](#)

2.1.5.3.2.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: [Max35Text on page 173](#)

2.1.5.3.3 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: [Max35Text on page 173](#)

2.1.5.4 BranchAndFinancialInstitutionIdentification6

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.5.4.1 FinancialInstitutionIdentification <FinInstnId>

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

FinancialInstitutionIdentification <FinInstnId> contains the following elements (see [FinancialInstitutionIdentification18](#) on page 31 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		BICFI <BICFI>	[0..1]	IdentifierSet		31
		ClearingSystemMemberIdentification <ClrSysMmbld>	[0..1]	±		31
		LEI <LEI>	[0..1]	IdentifierSet		31
		Name <Nm>	[0..1]	Text		32
		PostalAddress <PstlAdr>	[0..1]	±		32
		Other <Othr>	[0..1]	±		32

2.1.5.4.2 BranchIdentification <BrnchId>

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

BranchIdentification <BrnchId> contains the following elements (see [BranchData3](#) on page 33 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[0..1]	Text		33
		LEI <LEI>	[0..1]	IdentifierSet		33
		Name <Nm>	[0..1]	Text		33
		PostalAddress <PstlAdr>	[0..1]	±		33

2.1.5.5 ClearingSystemMemberIdentification2

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ClearingSystemIdentification <ClrSysId>	[0..1]	±		36
		MemberIdentification <Mmbld>	[1..1]	Text		37

2.1.5.5.1 ClearingSystemIdentification <ClrSysId>

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

ClearingSystemIdentification <ClrSysId> contains one of the following elements (see [ClearingSystemIdentification2Choice on page 128](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		128
	Or}	Proprietary <Prtry>	[1..1]	Text		129

2.1.5.5.2 MemberIdentification <Mmbld>

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: [Max35Text on page 173](#)

2.1.6 Identification Information

2.1.6.1 GenericIdentification30

Definition: Information related to an identification, for example, party identification or account identification.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		37
		Issuer <Issr>	[1..1]	Text		37
		SchemeName <SchmeNm>	[0..1]	Text		37

2.1.6.1.1 Identification <Id>

Presence: [1..1]

Definition: Proprietary information, often a code, issued by the data source scheme issuer.

Datatype: [Exact4AlphaNumericText on page 171](#)

2.1.6.1.2 Issuer <Issr>

Presence: [1..1]

Definition: Entity that assigns the identification.

Datatype: [Max35Text on page 173](#)

2.1.6.1.3 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Short textual description of the scheme.

Datatype: [Max35Text on page 173](#)

2.1.6.2 PaymentIdentification7

Definition: Provides further means of referencing a payment transaction.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		InstructionIdentification <InstrId>	[0..1]	Text		38
		EndToEndIdentification <EndToEndId>	[1..1]	Text		38
		TransactionIdentification <TxId>	[0..1]	Text		38
		UETR <UETR>	[0..1]	IdentifierSet		39
		ClearingSystemReference <ClrSysRef>	[0..1]	Text		39

Constraints

- **TransactionIdentificationPresenceRule**

TransactionIdentification or UETR must be present. Both may be present

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00420
- *Error Text:* No transaction identification is present

2.1.6.2.1 InstructionIdentification <InstrId>

Presence: [0..1]

Definition: Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the instruction.

Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction.

Datatype: [Max35Text on page 173](#)

2.1.6.2.2 EndToEndIdentification <EndToEndId>

Presence: [1..1]

Definition: Unique identification, as assigned by the initiating party, to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.

Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction.

Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain.

Datatype: [Max35Text on page 173](#)

2.1.6.2.3 TransactionIdentification <TxId>

Presence: [0..1]

Definition: Unique identification, as assigned by the first instructing agent, to unambiguously identify the transaction that is passed on, unchanged, throughout the entire interbank chain.

Usage: The transaction identification can be used for reconciliation, tracking or to link tasks relating to the transaction on the interbank level.

Usage: The instructing agent has to make sure that the transaction identification is unique for a pre-agreed period.

Datatype: Max35Text on page 173

2.1.6.2.4 UETR <UETR>

Presence: [0..1]

Definition: Universally unique identifier to provide an end-to-end reference of a payment transaction.

Datatype: UUIDv4Identifier on page 170

2.1.6.2.5 ClearingSystemReference <ClrSysRef>

Presence: [0..1]

Definition: Unique reference, as assigned by a clearing system, to unambiguously identify the instruction.

Datatype: Max35Text on page 173

2.1.7 Miscellaneous

2.1.7.1 RemittanceAmount2

Definition: Nature of the amount and currency on a document referred to in the remittance section, typically either the original amount due/payable or the amount actually remitted for the referenced document.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DuePayableAmount <DuePyblAmt>	[0..1]	Amount		40
		DiscountAppliedAmount <DscntApldAmt>	[0..*]			40
		Type <Tp>	[0..1]			41
	{Or	Code <Cd>	[1..1]	CodeSet		41
	Or}	Proprietary <Prtry>	[1..1]	Text		41
		Amount <Amt>	[1..1]	Amount		41
		CreditNoteAmount <CdtNoteAmt>	[0..1]	Amount		41
		TaxAmount <TaxAmt>	[0..*]			41
		Type <Tp>	[0..1]			42
	{Or	Code <Cd>	[1..1]	CodeSet		42
	Or}	Proprietary <Prtry>	[1..1]	Text		42
		Amount <Amt>	[1..1]	Amount		42
		AdjustmentAmountAndReason <AdjstmntAmtAndRsn>	[0..*]			42
		Amount <Amt>	[1..1]	Amount		43
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		43
		Reason <Rsn>	[0..1]	Text		43
		AdditionalInformation <AddtlInf>	[0..1]	Text		43
		RemittedAmount <RmtdAmt>	[0..1]	Amount		43

2.1.7.1.1 DuePayableAmount <DuePyblAmt>

Presence: [0..1]

Definition: Amount specified is the exact amount due and payable to the creditor.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 142

2.1.7.1.2 DiscountAppliedAmount <DscntApldAmt>

Presence: [0..*]

Definition: Amount specified for the referred document is the amount of discount to be applied to the amount due and payable to the creditor.

DiscountAppliedAmount <DscntApldAmt> contains the following **DiscountAmountAndType1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			41
	{Or	Code <Cd>	[1..1]	CodeSet		41
	Or}	Proprietary <Prtry>	[1..1]	Text		41
		Amount <Amt>	[1..1]	Amount		41

2.1.7.1.2.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of the amount.

Type <Tp> contains one of the following **DiscountAmountType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		41
	Or}	Proprietary <Prtry>	[1..1]	Text		41

2.1.7.1.2.1.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: [ExternalDiscountAmountType1Code on page 153](#)

2.1.7.1.2.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: [Max35Text on page 173](#)

2.1.7.1.2.2 Amount <Amt>

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 142](#)

2.1.7.1.3 CreditNoteAmount <CdtNoteAmt>

Presence: [0..1]

Definition: Amount specified for the referred document is the amount of a credit note.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 142](#)

2.1.7.1.4 TaxAmount <TaxAmt>

Presence: [0..*]

Definition: Quantity of cash resulting from the calculation of the tax.

TaxAmount <TaxAmt> contains the following **TaxAmountAndType1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			42
	{Or	Code <Cd>	[1..1]	CodeSet		42
	Or}	Proprietary <Prtry>	[1..1]	Text		42
		Amount <Amt>	[1..1]	Amount		42

2.1.7.1.4.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of the amount.

Type <Tp> contains one of the following **TaxAmountType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		42
	Or}	Proprietary <Prtry>	[1..1]	Text		42

2.1.7.1.4.1.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: [ExternalTaxAmountType1Code](#) on page 159

2.1.7.1.4.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: [Max35Text](#) on page 173

2.1.7.1.4.2 Amount <Amt>

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 142

2.1.7.1.5 AdjustmentAmountAndReason <AdjstmntAmtAndRsn>

Presence: [0..*]

Definition: Specifies detailed information on the amount and reason of the document adjustment.

AdjustmentAmountAndReason <AdjstmntAmtAndRsn> contains the following **DocumentAdjustment1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Amount		43
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		43
		Reason <Rsn>	[0..1]	Text		43
		AdditionalInformation <AddtlInf>	[0..1]	Text		43

2.1.7.1.5.1 Amount <Amt>

Presence: [1..1]

Definition: Amount of money of the document adjustment.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 142](#)

2.1.7.1.5.2 CreditDebitIndicator <CdtDbtInd>

Presence: [0..1]

Definition: Specifies whether the adjustment must be subtracted or added to the total amount.

Datatype: [CreditDebitCode on page 146](#)

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

2.1.7.1.5.3 Reason <Rsn>

Presence: [0..1]

Definition: Specifies the reason for the adjustment.

Datatype: [Max4Text on page 173](#)

2.1.7.1.5.4 AdditionalInformation <AddtlInf>

Presence: [0..1]

Definition: Provides further details on the document adjustment.

Datatype: [Max140Text on page 172](#)

2.1.7.1.6 RemittedAmount <RmtdAmt>

Presence: [0..1]

Definition: Amount of money remitted for the referred document.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 142](#)

2.1.7.2 GroupHeader93

Definition: Set of characteristics shared by all individual transactions included in the message.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		MessageIdentification <MsgId>	[1..1]	Text		44
		CreationDateTime <CreDtTm>	[1..1]	DateTime		44
		BatchBooking <BtchBookg>	[0..1]	Indicator		44
		NumberOfTransactions <NbOfTx>	[1..1]	Text		45
		ControlSum <CtrlSum>	[0..1]	Quantity		45
		TotalInterbankSettlementAmount <TtlIntrBkSttlmAmt>	[0..1]	Amount		45
		InterbankSettlementDate <IntrBkSttlmDt>	[0..1]	Date		45
		SettlementInformation <SttlmInf>	[1..1]	±		45
		PaymentTypeInformation <PmtTpInf>	[0..1]	±		46
		InstructingAgent <InstgAgt>	[0..1]	±		47
		InstructedAgent <InstdAgt>	[0..1]	±		47

Constraints

- **TotalInterbankSettlementAmountAndDateRule**

If TotalInterbankSettlementAmount is present, then InterbankSettlementDate must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00044
- *Error Text:* Invalid message content for group header interbank settlement date.

2.1.7.2.1 MessageIdentification <MsgId>

Presence: [1..1]

Definition: Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message.

Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period.

Datatype: [Max35Text on page 173](#)

2.1.7.2.2 CreationDateTime <CreDtTm>

Presence: [1..1]

Definition: Date and time at which the message was created.

Datatype: [ISODatetime on page 168](#)

2.1.7.2.3 BatchBooking <BtchBookg>

Presence: [0..1]

Definition: Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested.

Usage: Batch booking is used to request and not order a possible batch booking.

Datatype: One of the following values must be used (see [BatchBookingIndicator](#) on page 170):

- *Meaning When True:* Identifies that a batch entry for the sum of the amounts of all transactions in the batch or message is requested.
- *Meaning When False:* Identifies that a single entry for each of the transactions in the batch or message is requested.

2.1.7.2.4 NumberOfTransactions <NbOfTx>

Presence: [1..1]

Definition: Number of individual transactions contained in the message.

Datatype: [Max15NumericText](#) on page 172

2.1.7.2.5 ControlSum <CtrlSum>

Presence: [0..1]

Definition: Total of all individual amounts included in the message, irrespective of currencies.

Datatype: [DecimalNumber](#) on page 171

2.1.7.2.6 TotalInterbankSettlementAmount <TtlIntrBkSttlmAmt>

Presence: [0..1]

Definition: Total amount of money moved between the instructing agent and the instructed agent.

Datatype: [ActiveCurrencyAndAmount](#) on page 141

2.1.7.2.7 InterbankSettlementDate <IntrBkSttlmDt>

Presence: [0..1]

Definition: Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.

Datatype: [ISODate](#) on page 168

2.1.7.2.8 SettlementInformation <SttlmInf>

Presence: [1..1]

Definition: Specifies the details on how the settlement of the transaction(s) between the instructing agent and the instructed agent is completed.

SettlementInformation <SttlmInf> contains the following elements (see [SettlementInstruction7](#) on page 122 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		SettlementMethod <SttlmMtd>	[1..1]	CodeSet		125
		SettlementAccount <SttlmAcct>	[0..1]	±		125
		ClearingSystem <ClrSys>	[0..1]			125
	{Or	Code <Cd>	[1..1]	CodeSet		126
	Or}	Proprietary <Prtry>	[1..1]	Text		126
		InstructingReimbursementAgent <InstgRmbrsmntAgt>	[0..1]	±		126
		InstructingReimbursementAgentAccount <InstgRmbrsmntAgtAcct>	[0..1]	±		126
		InstructedReimbursementAgent <InstdRmbrsmntAgt>	[0..1]	±		127
		InstructedReimbursementAgentAccount <InstdRmbrsmntAgtAcct>	[0..1]	±		127
		ThirdReimbursementAgent <ThrdRmbrsmntAgt>	[0..1]	±		128
		ThirdReimbursementAgentAccount <ThrdRmbrsmntAgtAcct>	[0..1]	±		128

2.1.7.2.9 PaymentTypeInformation <PmtTpInf>

Presence: [0..1]

Definition: Set of elements used to further specify the type of transaction.

PaymentTypeInformation <PmtTpInf> contains the following elements (see [PaymentTypeInformation28](#) on page 88 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		InstructionPriority <InstrPrty>	[0..1]	CodeSet		88
		ClearingChannel <ClrChanl>	[0..1]	CodeSet		88
		ServiceLevel <SvcLv>	[0..*]			89
	{Or	Code <Cd>	[1..1]	CodeSet		89
	Or}	Proprietary <Prtry>	[1..1]	Text		89
		LocalInstrument <LclInstrm>	[0..1]			89
	{Or	Code <Cd>	[1..1]	CodeSet		90
	Or}	Proprietary <Prtry>	[1..1]	Text		90
		CategoryPurpose <CtgyPurp>	[0..1]			90
	{Or	Code <Cd>	[1..1]	CodeSet		90
	Or}	Proprietary <Prtry>	[1..1]	Text		90

2.1.7.2.10 InstructingAgent <InstgAgt>

Presence: [0..1]

Definition: Agent that instructs the next party in the chain to carry out the (set of) instruction(s).

InstructingAgent <InstgAgt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 35 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.7.2.11 InstructedAgent <InstdAgt>

Presence: [0..1]

Definition: Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s).

InstructedAgent <InstdAgt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 35 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.7.3 SupplementaryData1

Definition: Additional information that can not be captured in the structured fields and/or any other specific block.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PlaceAndName <PlcAndNm>	[0..1]	Text		47
		Envelope <Envlp>	[1..1]	(External Schema)		48

Constraints

- **SupplementaryDataRule**

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

2.1.7.3.1 PlaceAndName <PlcAndNm>

Presence: [0..1]

Definition: Unambiguous reference to the location where the supplementary data must be inserted in the message instance.

In the case of XML, this is expressed by a valid XPath.

Datatype: [Max350Text](#) on page 173

2.1.7.3.2 Envelope <Envlp>

Presence: [1..1]

Definition: Technical element wrapping the supplementary data.

Type: (External Schema)

Technical component that contains the validated supplementary data information. This technical envelope allows to segregate the supplementary data information from any other information.

2.1.7.4 Purpose2Choice

Definition: Specifies the underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		48
	Or}	Proprietary <Prtry>	[1..1]	Text		48

2.1.7.4.1 Code <Cd>

Presence: [1..1]

Definition: Underlying reason for the payment transaction, as published in an external purpose code list.

Datatype: [ExternalPurpose1Code on page 158](#)

2.1.7.4.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Purpose, in a proprietary form.

Datatype: [Max35Text on page 173](#)

2.1.7.5 RemittanceInformation2

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Unstructured <Ustrd>	[0..*]	Text		48

2.1.7.5.1 Unstructured <Ustrd>

Presence: [0..*]

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, for example, commercial invoices in an accounts' receivable system in an unstructured form.

Datatype: [Max140Text on page 172](#)

2.1.8 Organisation Identification

2.1.8.1 OrganisationIdentification29

Definition: Unique and unambiguous way to identify an organisation.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AnyBIC <AnyBIC>	[0..1]	IdentifierSet		49
		LEI <LEI>	[0..1]	IdentifierSet		49
		Other <Othr>	[0..*]			49
		Identification <Id>	[1..1]	Text		50
		SchemeName <SchmeNm>	[0..1]			50
	{Or	Code <Cd>	[1..1]	CodeSet		50
	Or}	Proprietary <Prtry>	[1..1]	Text		50
		Issuer <Issr>	[0..1]	Text		50

2.1.8.1.1 AnyBIC <AnyBIC>

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: [AnyBICDec2014Identifier on page 168](#)

2.1.8.1.2 LEI <LEI>

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: [LEIIdentifier on page 170](#)

2.1.8.1.3 Other <Othr>

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

Other <Othr> contains the following **GenericOrganisationIdentification1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		50
		SchemeName <SchmeNm>	[0..1]			50
	{Or	Code <Cd>	[1..1]	CodeSet		50
	Or}	Proprietary <Prtry>	[1..1]	Text		50
		Issuer <Issr>	[0..1]	Text		50

2.1.8.1.3.1 Identification <Id>*Presence:* [1..1]*Definition:* Identification assigned by an institution.*Datatype:* [Max35Text on page 173](#)**2.1.8.1.3.2 SchemeName <SchmeNm>***Presence:* [0..1]*Definition:* Name of the identification scheme.

SchemeName <SchmeNm> contains one of the following
OrganisationIdentificationSchemeName1Choice elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		50
	Or}	Proprietary <Prtry>	[1..1]	Text		50

2.1.8.1.3.2.1 Code <Cd>*Presence:* [1..1]*Definition:* Name of the identification scheme, in a coded form as published in an external list.*Datatype:* [ExternalOrganisationIdentification1Code on page 156](#)**2.1.8.1.3.2.2 Proprietary <Prtry>***Presence:* [1..1]*Definition:* Name of the identification scheme, in a free text form.*Datatype:* [Max35Text on page 173](#)**2.1.8.1.3.3 Issuer <Issr>***Presence:* [0..1]*Definition:* Entity that assigns the identification.*Datatype:* [Max35Text on page 173](#)**2.1.9 Party Identification****2.1.9.1 Party38Choice***Definition:* Nature or use of the account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	OrganisationIdentification <OrgId>	[1..1]	±		50
	Or}	PrivateIdentification <PrvtId>	[1..1]	±		51

2.1.9.1.1 OrganisationIdentification <OrgId>*Presence:* [1..1]

Definition: Unique and unambiguous way to identify an organisation.

OrganisationIdentification <OrgId> contains the following elements (see [OrganisationIdentification29](#) on page 49 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AnyBIC <AnyBIC>	[0..1]	IdentifierSet		49
		LEI <LEI>	[0..1]	IdentifierSet		49
		Other <Othr>	[0..*]			49
		Identification <Id>	[1..1]	Text		50
		SchemeName <SchmeNm>	[0..1]			50
	{Or	Code <Cd>	[1..1]	CodeSet		50
	Or}	Proprietary <Prtry>	[1..1]	Text		50
		Issuer <Issr>	[0..1]	Text		50

2.1.9.1.2 PrivateIdentification <PrvtId>

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

PrivateIdentification <PrvtId> contains the following elements (see [PersonIdentification13](#) on page 90 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DateAndPlaceOfBirth <DtAndPlcOfBirth>	[0..1]			91
		BirthDate <BirthDt>	[1..1]	Date		91
		ProvinceOfBirth <PrvcOfBirth>	[0..1]	Text		91
		CityOfBirth <CityOfBirth>	[1..1]	Text		91
		CountryOfBirth <CtryOfBirth>	[1..1]	CodeSet		92
		Other <Othr>	[0..*]			92
		Identification <Id>	[1..1]	Text		92
		SchemeName <SchmeNm>	[0..1]			92
	{Or	Code <Cd>	[1..1]	CodeSet		92
	Or}	Proprietary <Prtry>	[1..1]	Text		93
		Issuer <Issr>	[0..1]	Text		93

2.1.9.2 PartyIdentification135

Definition: Specifies the identification of a person or an organisation.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		52
		PostalAddress <PstlAdr>	[0..1]	±		52
		Identification <Id>	[0..1]	±		53
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		53
		ContactDetails <CtctDtls>	[0..1]	±		54

2.1.9.2.1 Name <Nm>

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: Max140Text on page 172

2.1.9.2.2 PostalAddress <PstlAdr>

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

PostalAddress <PstlAdr> contains the following elements (see [PostalAddress24](#) on page 96 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AddressType <AdrTp>	[0..1]			96
	{Or	Code <Cd>	[1..1]	CodeSet		97
	Or}	Proprietary <Prtry>	[1..1]	±		97
		Department <Dept>	[0..1]	Text		97
		SubDepartment <SubDept>	[0..1]	Text		97
		StreetName <StrtNm>	[0..1]	Text		98
		BuildingNumber <BldgNb>	[0..1]	Text		98
		BuildingName <BldgNm>	[0..1]	Text		98
		Floor <Flr>	[0..1]	Text		98
		PostBox <PstBx>	[0..1]	Text		98
		Room <Room>	[0..1]	Text		98
		PostCode <PstCd>	[0..1]	Text		98
		TownName <TwnNm>	[0..1]	Text		98
		TownLocationName <TwnLctnNm>	[0..1]	Text		99
		DistrictName <DstrctNm>	[0..1]	Text		99
		CountrySubDivision <CtrySubDvsn>	[0..1]	Text		99
		Country <Ctry>	[0..1]	CodeSet		99
		AddressLine <AdrLine>	[0..7]	Text		99

2.1.9.2.3 Identification <Id>

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

Identification <Id> contains one of the following elements (see [Party38Choice](#) on page 50 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	OrganisationIdentification <OrgId>	[1..1]	±		50
	Or}	PrivateIdentification <PrvtId>	[1..1]	±		51

2.1.9.2.4 CountryOfResidence <CtryOfRes>

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: [CountryCode](#) on page 146

2.1.9.2.5 ContactDetails <CtctDtls>

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

ContactDetails <CtctDtls> contains the following elements (see [Contact4](#) on page 93 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		NamePrefix <NmPrfx>	[0..1]	CodeSet		93
		Name <Nm>	[0..1]	Text		94
		PhoneNumber <PhneNb>	[0..1]	Text		94
		MobileNumber <MobNb>	[0..1]	Text		94
		FaxNumber <FaxNb>	[0..1]	Text		94
		EmailAddress <EmailAdr>	[0..1]	Text		94
		EmailPurpose <EmailPurp>	[0..1]	Text		94
		JobTitle <JobTitl>	[0..1]	Text		94
		Responsibility <Rspnsblty>	[0..1]	Text		95
		Department <Dept>	[0..1]	Text		95
		Other <Othr>	[0..*]			95
		ChannelType <ChanlTp>	[1..1]	Text		95
		Identification <Id>	[0..1]	Text		95
		PreferredMethod <PrefrdMtd>	[0..1]	CodeSet		95

2.1.10 Payment

2.1.10.1 InstructionForCreditorAgent2

Definition: Further information related to the processing of the payment instruction that may need to be acted upon by the creditor's agent. The instruction may relate to a level of service, or may be an instruction that has to be executed by the creditor's agent, or may be information required by the creditor's agent.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Code <Cd>	[0..1]	CodeSet		54
		InstructionInformation <InstrInf>	[0..1]	Text		55

2.1.10.1.1 Code <Cd>

Presence: [0..1]

Definition: Coded information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor's agent.

Datatype: [Instruction5Code](#) on page 161

CodeName	Name	Definition
PHOB	PhoneBeneficiary	Please advise/contact (ultimate) creditor/claimant by phone.
TELB	Telecom	Please advise/contact (ultimate) creditor/claimant by the most efficient means of telecommunication.

2.1.10.1.2 InstructionInformation <InstrInf>

Presence: [0..1]

Definition: Further information complementing the coded instruction or instruction to the creditor's agent that is bilaterally agreed or specific to a user community.

Datatype: [Max140Text](#) on page 172

2.1.10.2 InstructionForCreditorAgent1

Definition: Further information related to the processing of the payment instruction that may need to be acted upon by the creditor's agent. The instruction may relate to a level of service, or may be an instruction that has to be executed by the creditor's agent, or may be information required by the creditor's agent.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Code <Cd>	[0..1]	CodeSet		55
		InstructionInformation <InstrInf>	[0..1]	Text		56

2.1.10.2.1 Code <Cd>

Presence: [0..1]

Definition: Coded information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor's agent.

Datatype: [Instruction3Code](#) on page 160

CodeName	Name	Definition
CHQB	PayCreditorByCheque	(Ultimate) creditor must be paid by cheque.
HOLD	HoldCashForCreditor	Amount of money must be held for the (ultimate) creditor, who will call. Pay on identification.
PHOB	PhoneBeneficiary	Please advise/contact (ultimate) creditor/claimant by phone.
TELB	Telecom	Please advise/contact (ultimate) creditor/claimant by the most efficient means of telecommunication.

2.1.10.2.2 InstructionInformation <InstrInf>

Presence: [0..1]

Definition: Further information complementing the coded instruction or instruction to the creditor's agent that is bilaterally agreed or specific to a user community.

Datatype: Max140Text on page 172

2.1.10.3 CreditTransferTransaction37

Definition: Provides further details specific to the individual transaction(s) included in the message.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		UltimateDebtor <UltmtDbtr>	[0..1]	±		60
		InitiatingParty <InitgPty>	[0..1]	±		60
		Debtor <Dbtr>	[1..1]	±		60
		DebtorAccount <DbtrAcct>	[0..1]	±		61
		DebtorAgent <DbtrAgt>	[1..1]	±		61
		DebtorAgentAccount <DbtrAgtAcct>	[0..1]	±		61
		PreviousInstructingAgent1 <PrvsInstgAgt1>	[0..1]	±		62
		PreviousInstructingAgent1Account <PrvsInstgAgt1Acct>	[0..1]	±		62
		PreviousInstructingAgent2 <PrvsInstgAgt2>	[0..1]	±		62
		PreviousInstructingAgent2Account <PrvsInstgAgt2Acct>	[0..1]	±		63
		PreviousInstructingAgent3 <PrvsInstgAgt3>	[0..1]	±		63
		PreviousInstructingAgent3Account <PrvsInstgAgt3Acct>	[0..1]	±		63
		IntermediaryAgent1 <IntrmyAgt1>	[0..1]	±		64
		IntermediaryAgent1Account <IntrmyAgt1Acct>	[0..1]	±		64
		IntermediaryAgent2 <IntrmyAgt2>	[0..1]	±		64
		IntermediaryAgent2Account <IntrmyAgt2Acct>	[0..1]	±		65
		IntermediaryAgent3 <IntrmyAgt3>	[0..1]	±		65
		IntermediaryAgent3Account <IntrmyAgt3Acct>	[0..1]	±		65
		CreditorAgent <CdtrAgt>	[1..1]	±		66
		CreditorAgentAccount <CdtrAgtAcct>	[0..1]	±		66
		Creditor <Cdtr>	[1..1]	±		66
		CreditorAccount <CdtrAcct>	[0..1]	±		67
		UltimateCreditor <UltmtCdtr>	[0..1]	±		67
		InstructionForCreditorAgent <InstrForCdtrAgt>	[0..*]	±		67
		InstructionForNextAgent <InstrForNxtAgt>	[0..*]			68
		Code <Cd>	[0..1]	CodeSet		68
		InstructionInformation <InstrInf>	[0..1]	Text		68
		Tax <Tax>	[0..1]	±		68
		RemittanceInformation <RmtInf>	[0..1]	±		69
		InstructedAmount <InstdAmt>	[0..1]	Amount		69

Constraints

- **IntermediaryAgent1AccountRule**

If IntermediaryAgent1Account is present, then IntermediaryAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00052
- *Error Text:* Invalid message content for intermediary agent 1 account.

- **IntermediaryAgent2AccountRule**

If IntermediaryAgent2Account is present, then IntermediaryAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00053
- *Error Text:* Invalid message content for intermediary agent 2 account.

- **IntermediaryAgent2Rule**

If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00056
- *Error Text:* Invalid message content for intermediary agent 2.

- **IntermediaryAgent3AccountRule**

If IntermediaryAgent3Account is present, then IntermediaryAgent3 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00054
- *Error Text:* Invalid message content for intermediary agent 3 account.

- **IntermediaryAgent3Rule**

If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00057
- *Error Text:* Invalid message content for intermediary agent 3.

- **PreviousInstructingAgent1AccountRule**

If PreviousInstructingAgent1Account is present, then PreviousInstructingAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00411
- *Error Text:* Invalid message content for previous instructing agent account.

- **PreviousInstructingAgent1Guideline**

It is recommended that, when present, PreviousInstructingAgent1 is the closest to the DebtorAgent in the payment chain.

- **PreviousInstructingAgent2AccountRule**

If PreviousInstructingAgent2Account is present, then PreviousInstructingAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00412
- *Error Text:* Invalid message content for previous instructing agent account.

- **PreviousInstructingAgent3AccountRule**

If PreviousInstructingAgent3Account is present, then PreviousInstructingAgent3 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00413
- *Error Text:* Invalid message content for previous instructing agent account.

- **PreviousInstructionAgent2Rule**

If PreviousInstructingAgent2 is present, then PreviousInstructingAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00415
- *Error Text:* Invalid message content for intermediary agent 1.

- **PreviousInstructionAgent3Rule**

If PreviousInstructingAgent3 is present, then PreviousInstructingAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00416
- *Error Text:* Invalid message content for intermediary agent 1.

- **UltimateCreditorGuideline**

UltimateCreditor may only be present if different from Creditor.

- **UltimateDebtorGuideline**

UltimateDebtor may only be present if different from Debtor.

2.1.10.3.1 UltimateDebtor <UltmtDbtr>

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor.

UltimateDebtor <UltmtDbtr> contains the following elements (see [PartyIdentification135](#) on page 51 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		52
		PostalAddress <PstlAdr>	[0..1]	±		52
		Identification <Id>	[0..1]	±		53
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		53
		ContactDetails <CtctDtls>	[0..1]	±		54

2.1.10.3.2 InitiatingParty <InitgPty>

Presence: [0..1]

Definition: Party that initiates the payment.

Usage: This can be either the debtor or a party that initiates the credit transfer on behalf of the debtor.

InitiatingParty <InitgPty> contains the following elements (see [PartyIdentification135](#) on page 51 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		52
		PostalAddress <PstlAdr>	[0..1]	±		52
		Identification <Id>	[0..1]	±		53
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		53
		ContactDetails <CtctDtls>	[0..1]	±		54

2.1.10.3.3 Debtor <Dbtr>

Presence: [1..1]

Definition: Party that owes an amount of money to the (ultimate) creditor.

Debtor <Dbtr> contains the following elements (see [PartyIdentification135](#) on page 51 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		52
		PostalAddress <PstlAdr>	[0..1]	±		52
		Identification <Id>	[0..1]	±		53
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		53
		ContactDetails <CtctDtls>	[0..1]	±		54

2.1.10.3.4 DebtorAccount <DbtrAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.

DebtorAccount <DbtrAcct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.10.3.5 DebtorAgent <DbtrAgt>

Presence: [1..1]

Definition: Financial institution servicing an account for the debtor.

DebtorAgent <DbtrAgt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 35 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.3.6 DebtorAgentAccount <DbtrAgtAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain.

DebtorAgentAccount <DbtrAgtAcct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.10.3.7 PreviousInstructingAgent1 <PrvsInstgAgt1>

Presence: [0..1]

Definition: Agent immediately prior to the instructing agent.

PreviousInstructingAgent1 <PrvsInstgAgt1> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 35 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.3.8 PreviousInstructingAgent1Account <PrvsInstgAgt1Acct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain.

PreviousInstructingAgent1Account <PrvsInstgAgt1Acct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.10.3.9 PreviousInstructingAgent2 <PrvsInstgAgt2>

Presence: [0..1]

Definition: Agent immediately prior to the instructing agent.

PreviousInstructingAgent2 <PrvsInstgAgt2> contains the following elements (see [BranchAndFinancialInstitutionIdentification6 on page 35](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.3.10 PreviousInstructingAgent2Account <PrvsInstgAgt2Acct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain.

PreviousInstructingAgent2Account <PrvsInstgAgt2Acct> contains the following elements (see [CashAccount38 on page 24](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.10.3.11 PreviousInstructingAgent3 <PrvsInstgAgt3>

Presence: [0..1]

Definition: Agent immediately prior to the instructing agent.

PreviousInstructingAgent3 <PrvsInstgAgt3> contains the following elements (see [BranchAndFinancialInstitutionIdentification6 on page 35](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.3.12 PreviousInstructingAgent3Account <PrvsInstgAgt3Acct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain.

PreviousInstructingAgent3Account <PrvsInstgAgt3Acct> contains the following elements (see [CashAccount38 on page 24](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.10.3.13 IntermediaryAgent1 <IntrmyAgt1>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than one intermediary agent is present, then IntermediaryAgent1 identifies the agent between the DebtorAgent and the IntermediaryAgent2.

IntermediaryAgent1 <IntrmyAgt1> contains the following elements (see [BranchAndFinancialInstitutionIdentification6 on page 35](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.3.14 IntermediaryAgent1Account <IntrmyAgt1Acct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 1 at its servicing agent in the payment chain.

IntermediaryAgent1Account <IntrmyAgt1Acct> contains the following elements (see [CashAccount38 on page 24](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.10.3.15 IntermediaryAgent2 <IntrmyAgt2>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than two intermediary agents are present, then IntermediaryAgent2 identifies the agent between the IntermediaryAgent1 and the IntermediaryAgent3.

IntermediaryAgent2 <IntrmyAgt2> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 35 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.3.16 IntermediaryAgent2Account <IntrmyAgt2Acct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 2 at its servicing agent in the payment chain.

IntermediaryAgent2Account <IntrmyAgt2Acct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.10.3.17 IntermediaryAgent3 <IntrmyAgt3>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If IntermediaryAgent3 is present, then it identifies the agent between the IntermediaryAgent 2 and the CreditorAgent.

IntermediaryAgent3 <IntrmyAgt3> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 35 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.3.18 IntermediaryAgent3Account <IntrmyAgt3Acct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 3 at its servicing agent in the payment chain.

IntermediaryAgent3Account <IntrmyAgt3Acct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.10.3.19 CreditorAgent <CdtrAgt>

Presence: [1..1]

Definition: Financial institution servicing an account for the creditor.

CreditorAgent <CdtrAgt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 35 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.3.20 CreditorAgentAccount <CdtrAgtAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction.

CreditorAgentAccount <CdtrAgtAcct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.10.3.21 Creditor <Cdtr>

Presence: [1..1]

Definition: Party to which an amount of money is due.

Creditor <Cdtr> contains the following elements (see [PartyIdentification135](#) on page 51 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		52
		PostalAddress <PstlAdr>	[0..1]	±		52
		Identification <Id>	[0..1]	±		53
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		53
		ContactDetails <CtctDtls>	[0..1]	±		54

2.1.10.3.22 CreditorAccount <CdtrAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.

CreditorAccount <CdtrAcct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.10.3.23 UltimateCreditor <UltmtCdtr>

Presence: [0..1]

Definition: Ultimate party to which an amount of money is due.

UltimateCreditor <UltmtCdtr> contains the following elements (see [PartyIdentification135](#) on page 51 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		52
		PostalAddress <PstlAdr>	[0..1]	±		52
		Identification <Id>	[0..1]	±		53
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		53
		ContactDetails <CtctDtls>	[0..1]	±		54

2.1.10.3.24 InstructionForCreditorAgent <InstrForCdtrAgt>

Presence: [0..*]

Definition: Further information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor agent.

InstructionForCreditorAgent <InstrForCdrAg> contains the following elements (see [InstructionForCreditorAgent1](#) on page 55 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Code <Cd>	[0..1]	CodeSet		55
		InstructionInformation <InstrInf>	[0..1]	Text		56

2.1.10.3.25 InstructionForNextAgent <InstrForNxtAg>

Presence: [0..*]

Definition: Further information related to the processing of the payment instruction that may need to be acted upon by the next agent.

InstructionForNextAgent <InstrForNxtAg> contains the following **InstructionForNextAgent1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Code <Cd>	[0..1]	CodeSet		68
		InstructionInformation <InstrInf>	[0..1]	Text		68

2.1.10.3.25.1 Code <Cd>

Presence: [0..1]

Definition: Coded information related to the processing of the payment instruction, provided by the initiating party, and intended for the next agent in the payment chain.

Datatype: [Instruction4Code](#) on page 161

CodeName	Name	Definition
PHOA	PhoneNextAgent	Please advise/contact next agent by phone.
TELA	TelecomNextAgent	Please advise/contact next agent by the most efficient means of telecommunication.

2.1.10.3.25.2 InstructionInformation <InstrInf>

Presence: [0..1]

Definition: Further information complementing the coded instruction or instruction to the next agent that is bilaterally agreed or specific to a user community.

Datatype: [Max140Text](#) on page 172

2.1.10.3.26 Tax <Tax>

Presence: [0..1]

Definition: Provides details on the tax.

Tax <Tax> contains the following elements (see [TaxInformation8](#) on page 134 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Creditor <Cdtr>	[0..1]	±		135
		Debtor <Dbtr>	[0..1]	±		135
		AdministrationZone <AdmstnZone>	[0..1]	Text		136
		ReferenceNumber <RefNb>	[0..1]	Text		136
		Method <Mtd>	[0..1]	Text		136
		TotalTaxableBaseAmount <TtlTaxblBaseAmt>	[0..1]	Amount		136
		TotalTaxAmount <TtlTaxAmt>	[0..1]	Amount		136
		Date <Dt>	[0..1]	Date		136
		SequenceNumber <SeqNb>	[0..1]	Quantity		136
		Record <Rcrd>	[0..*]	±		136

2.1.10.3.27 RemittanceInformation <RmtInf>

Presence: [0..1]

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.

RemittanceInformation <RmtInf> contains the following elements (see [RemittanceInformation16](#) on page 103 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Unstructured <Ustrd>	[0..*]	Text		103
		Structured <Strd>	[0..*]	±		103

2.1.10.3.28 InstructedAmount <InstdAmt>

Presence: [0..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

Usage: This amount has to be transported unchanged through the transaction chain.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 142

2.1.10.4 CreditTransferTransaction36

Definition: Provide further details specific to the individual transaction(s) included in the message.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PaymentIdentification <PmtId>	[1..1]	±		74
		PaymentTypeInfoInformation <PmtTplnf>	[0..1]	±		74
		InterbankSettlementAmount <IntrBkSttlmAmt>	[1..1]	Amount		74
		InterbankSettlementDate <IntrBkSttlmDt>	[0..1]	Date		75
		SettlementPriority <SttlmPrty>	[0..1]	CodeSet		75
		SettlementTimeIndication <SttlmTmIndctn>	[0..1]			75
		DebitDateTime <DbtDtTm>	[0..1]	DateTime		75
		CreditDateTime <CdtDtTm>	[0..1]	DateTime		75
		SettlementTimeRequest <SttlmTmReq>	[0..1]	±		76
		PreviousInstructingAgent1 <PrvsInstgAgt1>	[0..1]	±		76
		PreviousInstructingAgent1Account <PrvsInstgAgt1Acct>	[0..1]	±		76
		PreviousInstructingAgent2 <PrvsInstgAgt2>	[0..1]	±		76
		PreviousInstructingAgent2Account <PrvsInstgAgt2Acct>	[0..1]	±		77
		PreviousInstructingAgent3 <PrvsInstgAgt3>	[0..1]	±		77
		PreviousInstructingAgent3Account <PrvsInstgAgt3Acct>	[0..1]	±		77
		InstructingAgent <InstgAgt>	[0..1]	±		78
		InstructedAgent <InstdAgt>	[0..1]	±		78
		IntermediaryAgent1 <IntrmyAgt1>	[0..1]	±		78
		IntermediaryAgent1Account <IntrmyAgt1Acct>	[0..1]	±		79
		IntermediaryAgent2 <IntrmyAgt2>	[0..1]	±		79
		IntermediaryAgent2Account <IntrmyAgt2Acct>	[0..1]	±		79
		IntermediaryAgent3 <IntrmyAgt3>	[0..1]	±		80
		IntermediaryAgent3Account <IntrmyAgt3Acct>	[0..1]	±		80
		UltimateDebtor <UltmtDbtr>	[0..1]	±		80
		Debtor <Dbtr>	[1..1]	±		81
		DebtorAccount <DbtrAcct>	[0..1]	±		81
		DebtorAgent <DbtrAgt>	[0..1]	±		81
		DebtorAgentAccount <DbtrAgtAcct>	[0..1]	±		82
		CreditorAgent <CdtrAgt>	[0..1]	±		82
		CreditorAgentAccount <CdtrAgtAcct>	[0..1]	±		82

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Creditor <Cdtr>	[1..1]	±		83
		CreditorAccount <CdtrAcct>	[0..1]	±		83
		UltimateCreditor <UltmtCdtr>	[0..1]	±		83
		InstructionForCreditorAgent <InstrForCdtrAgt>	[0..*]	±		84
		InstructionForNextAgent <InstrForNxtAgt>	[0..*]			84
		Code <Cd>	[0..1]	CodeSet		84
		InstructionInformation <InstrInf>	[0..1]	Text		85
		Purpose <Purp>	[0..1]	±		85
		RemittanceInformation <RmtInf>	[0..1]	±		85
		UnderlyingCustomerCreditTransfer <UndrlygCstmrCdtTrf>	[0..1]	±		85
		SupplementaryData <SplmtryData>	[0..*]	±		87

Constraints

- **CreditorAgentAccountRule**

If CreditorAgentAccount is present, then CreditorAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00058
- *Error Text:* Invalid message content for creditor agent account.

- **DebtorAgentAccountRule**

If DebtorAgentAccount is present, then DebtorAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00059
- *Error Text:* Invalid message content for debtor agent account.

- **IntermediaryAgent1AccountRule**

If IntermediaryAgent1Account is present, then IntermediaryAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00052
- *Error Text:* Invalid message content for intermediary agent 1 account.

- **IntermediaryAgent1Rule**

If IntermediaryAgent1 is present, then CreditorAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00060
- *Error Text:* Invalid message content for intermediary agent 1.

- **IntermediaryAgent2AccountRule**

If IntermediaryAgent2Account is present, then IntermediaryAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00053
- *Error Text:* Invalid message content for intermediary agent 2 account.

- **IntermediaryAgent2Rule**

If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00056
- *Error Text:* Invalid message content for intermediary agent 2.

- **IntermediaryAgent3AccountRule**

If IntermediaryAgent3Account is present, then IntermediaryAgent3 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00054
- *Error Text:* Invalid message content for intermediary agent 3 account.

- **IntermediaryAgent3Rule**

If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00057
- *Error Text:* Invalid message content for intermediary agent 3.

- **PreviousInstructingAgent1AccountRule**

If PreviousInstructingAgent1Account is present, then PreviousInstructingAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00411
- *Error Text:* Invalid message content for previous instructing agent account.

- **PreviousInstructingAgent1Guideline**

It is recommended that, when present, PreviousInstructingAgent1 is the closest to the DebtorAgent in the payment chain.

- **PreviousInstructingAgent2AccountRule**

If PreviousInstructingAgent2Account is present, then PreviousInstructingAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00412
- *Error Text:* Invalid message content for previous instructing agent account.

- **PreviousInstructingAgent3AccountRule**

If PreviousInstructingAgent3Account is present, then PreviousInstructingAgent3 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00413
- *Error Text:* Invalid message content for previous instructing agent account.

- **PreviousInstructionAgent2Rule**

If PreviousInstructingAgent2 is present, then PreviousInstructingAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00415
- *Error Text:* Invalid message content for intermediary agent 1.

- **PreviousInstructionAgent3Rule**

If PreviousInstructingAgent3 is present, then PreviousInstructingAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00416
- *Error Text:* Invalid message content for intermediary agent 1.

- **UltimateCreditorGuideline**

UltimateCreditor may only be present if different from Creditor.

- **UltimateDebtorGuideline**

UltimateDebtor may only be present if different from Debtor.

2.1.10.4.1 PaymentIdentification <PmtId>

Presence: [1..1]

Definition: Set of elements used to reference a payment instruction.

PaymentIdentification <PmtId> contains the following elements (see [PaymentIdentification7](#) on page 37 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		InstructionIdentification <InstrId>	[0..1]	Text		38
		EndToEndIdentification <EndToEndId>	[1..1]	Text		38
		TransactionIdentification <TxId>	[0..1]	Text		38
		UETR <UETR>	[0..1]	IdentifierSet		39
		ClearingSystemReference <ClrSysRef>	[0..1]	Text		39

2.1.10.4.2 PaymentTypeInformation <PmtTpInf>

Presence: [0..1]

Definition: Set of elements used to further specify the type of transaction.

PaymentTypeInformation <PmtTpInf> contains the following elements (see [PaymentTypeInformation28](#) on page 88 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		InstructionPriority <InstrPrty>	[0..1]	CodeSet		88
		ClearingChannel <ClrChan>	[0..1]	CodeSet		88
		ServiceLevel <SvcLvl>	[0..*]			89
	{Or	Code <Cd>	[1..1]	CodeSet		89
	Or}	Proprietary <Prtry>	[1..1]	Text		89
		LocalInstrument <LclInstrm>	[0..1]			89
	{Or	Code <Cd>	[1..1]	CodeSet		90
	Or}	Proprietary <Prtry>	[1..1]	Text		90
		CategoryPurpose <CtgyPurp>	[0..1]			90
	{Or	Code <Cd>	[1..1]	CodeSet		90
	Or}	Proprietary <Prtry>	[1..1]	Text		90

2.1.10.4.3 InterbankSettlementAmount <IntrBkSttlmAmt>

Presence: [1..1]

Definition: Amount of money moved between the instructing agent and the instructed agent.

Datatype: [ActiveCurrencyAndAmount](#) on page 141

2.1.10.4.4 InterbankSettlementDate <IntrBkSttlmDt>

Presence: [0..1]

Definition: Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.

Datatype: [ISODate](#) on page 168

2.1.10.4.5 SettlementPriority <SttlmPrty>

Presence: [0..1]

Definition: Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the settlement instruction.

Datatype: [Priority3Code](#) on page 164

CodeName	Name	Definition
URGT	Urgent	Priority level is urgent (highest priority possible).
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

2.1.10.4.6 SettlementTimeIndication <SttlmTmIndctn>

Presence: [0..1]

Definition: Provides information on the occurred settlement time(s) of the payment transaction.

SettlementTimeIndication <SttlmTmIndctn> contains the following **SettlementDateTimeIndication1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DebitDateTime <DbtDtTm>	[0..1]	DateTime		75
		CreditDateTime <CdtDtTm>	[0..1]	DateTime		75

2.1.10.4.6.1 DebitDateTime <DbtDtTm>

Presence: [0..1]

Definition: Date and time at which a payment has been debited at the transaction administrator. In the case of TARGET, the date and time at which the payment has been debited at the central bank, expressed in Central European Time (CET).

Datatype: [ISODatetime](#) on page 168

2.1.10.4.6.2 CreditDateTime <CdtDtTm>

Presence: [0..1]

Definition: Date and time at which a payment has been credited at the transaction administrator. In the case of TARGET, the date and time at which the payment has been credited at the receiving central bank, expressed in Central European Time (CET).

Datatype: [ISODatetime](#) on page 168

2.1.10.4.7 SettlementTimeRequest <SttlmTmReq>*Presence:* [0..1]*Definition:* Provides information on the requested settlement time(s) of the payment instruction.**SettlementTimeRequest <SttlmTmReq>** contains the following elements (see [SettlementTimeRequest2](#) on page 87 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CLSTime <CLSTm>	[0..1]	Time		87
		TillTime <TillTm>	[0..1]	Time		87
		FromTime <FrTm>	[0..1]	Time		87
		RejectTime <RjctTm>	[0..1]	Time		88

2.1.10.4.8 PreviousInstructingAgent1 <PrvsInstgAgt1>*Presence:* [0..1]*Definition:* Agent immediately prior to the instructing agent.**PreviousInstructingAgent1 <PrvsInstgAgt1>** contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 35 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.4.9 PreviousInstructingAgent1Account <PrvsInstgAgt1Acct>*Presence:* [0..1]*Definition:* Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain.**PreviousInstructingAgent1Account <PrvsInstgAgt1Acct>** contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.10.4.10 PreviousInstructingAgent2 <PrvsInstgAgt2>*Presence:* [0..1]*Definition:* Agent immediately prior to the instructing agent.

PreviousInstructingAgent2 <PrvsInstgAgt2> contains the following elements (see [BranchAndFinancialInstitutionIdentification6 on page 35](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.4.11 PreviousInstructingAgent2Account <PrvsInstgAgt2Acct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain.

PreviousInstructingAgent2Account <PrvsInstgAgt2Acct> contains the following elements (see [CashAccount38 on page 24](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.10.4.12 PreviousInstructingAgent3 <PrvsInstgAgt3>

Presence: [0..1]

Definition: Agent immediately prior to the instructing agent.

PreviousInstructingAgent3 <PrvsInstgAgt3> contains the following elements (see [BranchAndFinancialInstitutionIdentification6 on page 35](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.4.13 PreviousInstructingAgent3Account <PrvsInstgAgt3Acct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain.

PreviousInstructingAgent3Account <PrvsInstgAgt3Acct> contains the following elements (see [CashAccount38 on page 24](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.10.4.14 InstructingAgent <InstgAgt>

Presence: [0..1]

Definition: Agent that instructs the next party in the chain to carry out the (set of) instruction(s).

InstructingAgent <InstgAgt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6 on page 35](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.4.15 InstructedAgent <InstdAgt>

Presence: [0..1]

Definition: Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s).

InstructedAgent <InstdAgt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6 on page 35](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.4.16 IntermediaryAgent1 <IntrmyAgt1>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than one intermediary agent is present, then IntermediaryAgent1 identifies the agent between the DebtorAgent and the IntermediaryAgent2.

IntermediaryAgent1 <IntrmyAgt1> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 35 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.4.17 IntermediaryAgent1Account <IntrmyAgt1Acct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 1 at its servicing agent in the payment chain.

IntermediaryAgent1Account <IntrmyAgt1Acct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.10.4.18 IntermediaryAgent2 <IntrmyAgt2>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than two intermediary agents are present, then IntermediaryAgent2 identifies the agent between the IntermediaryAgent1 and the IntermediaryAgent3.

IntermediaryAgent2 <IntrmyAgt2> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 35 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.4.19 IntermediaryAgent2Account <IntrmyAgt2Acct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 2 at its servicing agent in the payment chain.

IntermediaryAgent2Account <IntrmyAgt2Acct> contains the following elements (see [CashAccount38 on page 24](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.10.4.20 IntermediaryAgent3 <IntrmyAgt3>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If IntermediaryAgent3 is present, then it identifies the agent between the IntermediaryAgent 2 and the CreditorAgent.

IntermediaryAgent3 <IntrmyAgt3> contains the following elements (see [BranchAndFinancialInstitutionIdentification6 on page 35](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.4.21 IntermediaryAgent3Account <IntrmyAgt3Acct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 3 at its servicing agent in the payment chain.

IntermediaryAgent3Account <IntrmyAgt3Acct> contains the following elements (see [CashAccount38 on page 24](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.10.4.22 UltimateDebtor <UltmtDbtr>

Presence: [0..1]

Definition: Ultimate financial institution that owes an amount of money to the (ultimate) institutional creditor.

UltimateDebtor <UltmtDbtr> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 35 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.4.23 Debtor <Dbtr>

Presence: [1..1]

Definition: Financial institution that owes an amount of money to the (ultimate) financial institutional creditor.

Debtor <Dbtr> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 35 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.4.24 DebtorAccount <DbtrAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.

DebtorAccount <DbtrAcct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.10.4.25 DebtorAgent <DbtrAgt>

Presence: [0..1]

Definition: Financial institution servicing an account for the debtor.

DebtorAgent <DbtrAgt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 35 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.4.26 DebtorAgentAccount <DbtrAgtAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain.

DebtorAgentAccount <DbtrAgtAcct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.10.4.27 CreditorAgent <CdtrAgt>

Presence: [0..1]

Definition: Financial institution servicing an account for the creditor.

CreditorAgent <CdtrAgt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 35 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.4.28 CreditorAgentAccount <CdtrAgtAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction.

CreditorAgentAccount <CdtrAgtAcct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.10.4.29 Creditor <Cdtr>

Presence: [1..1]

Definition: Financial institution that receives an amount of money from the financial institutional debtor.

Creditor <Cdtr> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 35 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.4.30 CreditorAccount <CdtrAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.

CreditorAccount <CdtrAcct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.10.4.31 UltimateCreditor <UltmtCdtr>

Presence: [0..1]

Definition: Ultimate financial institution to which an amount of money is due.

UltimateCreditor <UltmtCdtr> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 35 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.10.4.32 InstructionForCreditorAgent <InstrForCdtrAg>

Presence: [0..*]

Definition: Further information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor agent.

InstructionForCreditorAgent <InstrForCdtrAg> contains the following elements (see [InstructionForCreditorAgent2](#) on page 54 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Code <Cd>	[0..1]	CodeSet		54
		InstructionInformation <InstrInf>	[0..1]	Text		55

2.1.10.4.33 InstructionForNextAgent <InstrForNxtAg>

Presence: [0..*]

Definition: Further information related to the processing of the payment instruction that may need to be acted upon by the next agent.

Usage: The next agent may not be the creditor agent.

The instruction can relate to a level of service, can be an instruction that has to be executed by the agent, or can be information required by the next agent.

InstructionForNextAgent <InstrForNxtAg> contains the following **InstructionForNextAgent1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Code <Cd>	[0..1]	CodeSet		84
		InstructionInformation <InstrInf>	[0..1]	Text		85

2.1.10.4.33.1 Code <Cd>

Presence: [0..1]

Definition: Coded information related to the processing of the payment instruction, provided by the initiating party, and intended for the next agent in the payment chain.

Datatype: [Instruction4Code](#) on page 161

CodeName	Name	Definition
PHOA	PhoneNextAgent	Please advise/contact next agent by phone.

CodeName	Name	Definition
TELA	TelecomNextAgent	Please advise/contact next agent by the most efficient means of telecommunication.

2.1.10.4.33.2 InstructionInformation <InstrInf>

Presence: [0..1]

Definition: Further information complementing the coded instruction or instruction to the next agent that is bilaterally agreed or specific to a user community.

Datatype: [Max140Text](#) on page 172

2.1.10.4.34 Purpose <Purp>

Presence: [0..1]

Definition: Underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

Purpose <Purp> contains one of the following elements (see [Purpose2Choice](#) on page 48 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		48
	Or}	Proprietary <Prtry>	[1..1]	Text		48

2.1.10.4.35 RemittanceInformation <RmtInf>

Presence: [0..1]

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.

RemittanceInformation <RmtInf> contains the following elements (see [RemittanceInformation2](#) on page 48 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Unstructured <Ustrd>	[0..*]	Text		48

2.1.10.4.36 UnderlyingCustomerCreditTransfer <UndrlygCstmrCdtTrf>

Presence: [0..1]

Definition: Provides information on the underlying customer credit transfer for which cover is provided.

UnderlyingCustomerCreditTransfer <UndrlygCstmrCdtTrf> contains the following elements (see [CreditTransferTransaction37](#) on page 56 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		UltimateDebtor <UltmtDbtr>	[0..1]	±		60
		InitiatingParty <InitgPty>	[0..1]	±		60
		Debtor <Dbtr>	[1..1]	±		60
		DebtorAccount <DbtrAcct>	[0..1]	±		61
		DebtorAgent <DbtrAgt>	[1..1]	±		61
		DebtorAgentAccount <DbtrAgtAcct>	[0..1]	±		61
		PreviousInstructingAgent1 <PrvsInstgAgt1>	[0..1]	±		62
		PreviousInstructingAgent1Account <PrvsInstgAgt1Acct>	[0..1]	±		62
		PreviousInstructingAgent2 <PrvsInstgAgt2>	[0..1]	±		62
		PreviousInstructingAgent2Account <PrvsInstgAgt2Acct>	[0..1]	±		63
		PreviousInstructingAgent3 <PrvsInstgAgt3>	[0..1]	±		63
		PreviousInstructingAgent3Account <PrvsInstgAgt3Acct>	[0..1]	±		63
		IntermediaryAgent1 <IntrmyAgt1>	[0..1]	±		64
		IntermediaryAgent1Account <IntrmyAgt1Acct>	[0..1]	±		64
		IntermediaryAgent2 <IntrmyAgt2>	[0..1]	±		64
		IntermediaryAgent2Account <IntrmyAgt2Acct>	[0..1]	±		65
		IntermediaryAgent3 <IntrmyAgt3>	[0..1]	±		65
		IntermediaryAgent3Account <IntrmyAgt3Acct>	[0..1]	±		65
		CreditorAgent <CdtrAgt>	[1..1]	±		66
		CreditorAgentAccount <CdtrAgtAcct>	[0..1]	±		66
		Creditor <Cdtr>	[1..1]	±		66
		CreditorAccount <CdtrAcct>	[0..1]	±		67
		UltimateCreditor <UltmtCdtr>	[0..1]	±		67
		InstructionForCreditorAgent <InstrForCdtrAgt>	[0..*]	±		67
		InstructionForNextAgent <InstrForNxtAgt>	[0..*]			68
		Code <Cd>	[0..1]	CodeSet		68
		InstructionInformation <InstrInf>	[0..1]	Text		68
		Tax <Tax>	[0..1]	±		68
		RemittanceInformation <RmtInf>	[0..1]	±		69

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		InstructedAmount <InstdAmt>	[0..1]	Amount		69

2.1.10.4.37 SupplementaryData <SplmtryData>

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

SupplementaryData <SplmtryData> contains the following elements (see [SupplementaryData1](#) on page 47 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		PlaceAndName <PlcAndNm>	[0..1]	Text		47
		Envelope <Envlp>	[1..1]	(External Schema)		48

2.1.10.5 SettlementTimeRequest2

Definition: Provides information on the requested settlement time(s) of the payment instruction.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CLSTime <CLSTm>	[0..1]	Time		87
		TillTime <TillTm>	[0..1]	Time		87
		FromTime <FrTm>	[0..1]	Time		87
		RejectTime <RjctTm>	[0..1]	Time		88

2.1.10.5.1 CLSTime <CLSTm>

Presence: [0..1]

Definition: Time by which the amount of money must be credited, with confirmation, to the CLS Bank's account at the central bank.

Usage: Time must be expressed in Central European Time (CET).

Datatype: [ISOTime](#) on page 174

2.1.10.5.2 TillTime <TillTm>

Presence: [0..1]

Definition: Time until when the payment may be settled.

Datatype: [ISOTime](#) on page 174

2.1.10.5.3 FromTime <FrTm>

Presence: [0..1]

Definition: Time as from when the payment may be settled.

Datatype: [ISOTime on page 174](#)

2.1.10.5.4 RejectTime <RjctTm>

Presence: [0..1]

Definition: Time by when the payment must be settled to avoid rejection.

Datatype: [ISOTime on page 174](#)

2.1.11 Payment Type

2.1.11.1 PaymentTypeInfo28

Definition: Provides further details of the type of payment.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		InstructionPriority <InstrPrty>	[0..1]	CodeSet		88
		ClearingChannel <ClrChanl>	[0..1]	CodeSet		88
		ServiceLevel <SvcLvl>	[0..*]			89
	{Or	Code <Cd>	[1..1]	CodeSet		89
	Or}	Proprietary <Prtry>	[1..1]	Text		89
		LocalInstrument <LclInstrm>	[0..1]			89
	{Or	Code <Cd>	[1..1]	CodeSet		90
	Or}	Proprietary <Prtry>	[1..1]	Text		90
		CategoryPurpose <CtgyPurp>	[0..1]			90
	{Or	Code <Cd>	[1..1]	CodeSet		90
	Or}	Proprietary <Prtry>	[1..1]	Text		90

2.1.11.1.1 InstructionPriority <InstrPrty>

Presence: [0..1]

Definition: Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction.

Datatype: [Priority2Code on page 164](#)

CodeName	Name	Definition
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

2.1.11.1.2 ClearingChannel <ClrChanl>

Presence: [0..1]

Definition: Specifies the clearing channel to be used to process the payment instruction.

Datatype: [ClearingChannel2Code on page 145](#)

CodeName	Name	Definition
RTGS	RealTimeGrossSettlementSystem	Clearing channel is a real-time gross settlement system.
RTNS	RealTimeNetSettlementSystem	Clearing channel is a real-time net settlement system.
MPNS	MassPaymentNetSystem	Clearing channel is a mass payment net settlement system.
BOOK	BookTransfer	Payment through internal book transfer.

2.1.11.1.3 ServiceLevel <SvcLvl>

Presence: [0..*]

Definition: Agreement under which or rules under which the transaction should be processed.

ServiceLevel <SvcLvl> contains one of the following **ServiceLevel8Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		89
	Or}	Proprietary <Prtry>	[1..1]	Text		89

2.1.11.1.3.1 Code <Cd>

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list.

Datatype: [ExternalServiceLevel1Code on page 159](#)

2.1.11.1.3.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as a proprietary code.

Datatype: [Max35Text on page 173](#)

2.1.11.1.4 LocalInstrument <LclInstrm>

Presence: [0..1]

Definition: User community specific instrument.

Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.

LocalInstrument <LclInstrm> contains one of the following **LocalInstrument2Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		90
	Or}	Proprietary <Prtry>	[1..1]	Text		90

2.1.11.1.4.1 Code <Cd>*Presence:* [1..1]*Definition:* Specifies the local instrument, as published in an external local instrument code list.*Datatype:* [ExternalLocalInstrument1Code on page 155](#)**2.1.11.1.4.2 Proprietary <Prtry>***Presence:* [1..1]*Definition:* Specifies the local instrument, as a proprietary code.*Datatype:* [Max35Text on page 173](#)**2.1.11.1.5 CategoryPurpose <CtgyPurp>***Presence:* [0..1]*Definition:* Specifies the high level purpose of the instruction based on a set of pre-defined categories.*Usage:* This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.**CategoryPurpose <CtgyPurp>** contains one of the following **CategoryPurpose1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		90
	Or}	Proprietary <Prtry>	[1..1]	Text		90

2.1.11.1.5.1 Code <Cd>*Presence:* [1..1]*Definition:* Category purpose, as published in an external category purpose code list.*Datatype:* [ExternalCategoryPurpose1Code on page 152](#)**2.1.11.1.5.2 Proprietary <Prtry>***Presence:* [1..1]*Definition:* Category purpose, in a proprietary form.*Datatype:* [Max35Text on page 173](#)**2.1.12 Person Identification****2.1.12.1 PersonIdentification13***Definition:* Unique and unambiguous way to identify a person.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DateAndPlaceOfBirth <DtAndPlcOfBirth>	[0..1]			91
		BirthDate <BirthDt>	[1..1]	Date		91
		ProvinceOfBirth <PrvcOfBirth>	[0..1]	Text		91
		CityOfBirth <CityOfBirth>	[1..1]	Text		91
		CountryOfBirth <CtryOfBirth>	[1..1]	CodeSet		92
		Other <Othr>	[0..*]			92
		Identification <Id>	[1..1]	Text		92
		SchemeName <SchmeNm>	[0..1]			92
	{Or	Code <Cd>	[1..1]	CodeSet		92
	Or}	Proprietary <Prtry>	[1..1]	Text		93
		Issuer <Issr>	[0..1]	Text		93

2.1.12.1.1 DateAndPlaceOfBirth <DtAndPlcOfBirth>

Presence: [0..1]

Definition: Date and place of birth of a person.

DateAndPlaceOfBirth <DtAndPlcOfBirth> contains the following **DateAndPlaceOfBirth1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		BirthDate <BirthDt>	[1..1]	Date		91
		ProvinceOfBirth <PrvcOfBirth>	[0..1]	Text		91
		CityOfBirth <CityOfBirth>	[1..1]	Text		91
		CountryOfBirth <CtryOfBirth>	[1..1]	CodeSet		92

2.1.12.1.1.1 BirthDate <BirthDt>

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: [ISODate](#) on page 168

2.1.12.1.1.2 ProvinceOfBirth <PrvcOfBirth>

Presence: [0..1]

Definition: Province where a person was born.

Datatype: [Max35Text](#) on page 173

2.1.12.1.1.3 CityOfBirth <CityOfBirth>

Presence: [1..1]

Definition: City where a person was born.

Datatype: [Max35Text on page 173](#)

2.1.12.1.1.4 CountryOfBirth <CtryOfBirth>

Presence: [1..1]

Definition: Country where a person was born.

Datatype: [CountryCode on page 146](#)

2.1.12.1.2 Other <Othr>

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

Other <Othr> contains the following **GenericPersonIdentification1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		92
		SchemeName <SchmeNm>	[0..1]			92
	{Or	Code <Cd>	[1..1]	CodeSet		92
	Or}	Proprietary <Prtry>	[1..1]	Text		93
		Issuer <Issr>	[0..1]	Text		93

2.1.12.1.2.1 Identification <Id>

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: [Max35Text on page 173](#)

2.1.12.1.2.2 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Name of the identification scheme.

SchemeName <SchmeNm> contains one of the following **PersonIdentificationSchemeName1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		92
	Or}	Proprietary <Prtry>	[1..1]	Text		93

2.1.12.1.2.2.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: [ExternalPersonIdentification1Code on page 157](#)

2.1.12.1.2.2.2 Proprietary <Prtry>*Presence:* [1..1]*Definition:* Name of the identification scheme, in a free text form.*Datatype:* [Max35Text on page 173](#)**2.1.12.1.2.3 Issuer <Issr>***Presence:* [0..1]*Definition:* Entity that assigns the identification.*Datatype:* [Max35Text on page 173](#)**2.1.12.2 Contact4***Definition:* Specifies the details of the contact person.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		NamePrefix <NmPrfx>	[0..1]	CodeSet		93
		Name <Nm>	[0..1]	Text		94
		PhoneNumber <PhneNb>	[0..1]	Text		94
		MobileNumber <MobNb>	[0..1]	Text		94
		FaxNumber <FaxNb>	[0..1]	Text		94
		EmailAddress <EmailAdr>	[0..1]	Text		94
		EmailPurpose <EmailPurp>	[0..1]	Text		94
		JobTitle <JobTitl>	[0..1]	Text		94
		Responsibility <Rspnsblty>	[0..1]	Text		95
		Department <Dept>	[0..1]	Text		95
		Other <Othr>	[0..*]			95
		ChannelType <ChanITp>	[1..1]	Text		95
		Identification <Id>	[0..1]	Text		95
		PreferredMethod <PrefrdMtd>	[0..1]	CodeSet		95

2.1.12.2.1 NamePrefix <NmPrfx>*Presence:* [0..1]*Definition:* Specifies the terms used to formally address a person.*Datatype:* [NamePrefix2Code on page 162](#)

CodeName	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MISS	Miss	Title of the person is Miss.

CodeName	Name	Definition
MIST	Mister	Title of the person is Mister or Mr.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).

2.1.12.2.2 Name <Nm>

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: [Max140Text on page 172](#)

2.1.12.2.3 PhoneNumber <PhneNb>

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: [PhoneNumber on page 174](#)

2.1.12.2.4 MobileNumber <MobNb>

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: [PhoneNumber on page 174](#)

2.1.12.2.5 FaxNumber <FaxNb>

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: [PhoneNumber on page 174](#)

2.1.12.2.6 EmailAddress <EmailAdr>

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: [Max2048Text on page 172](#)

2.1.12.2.7 EmailPurpose <EmailPurp>

Presence: [0..1]

Definition: Purpose for which an email address may be used.

Datatype: [Max35Text on page 173](#)

2.1.12.2.8 JobTitle <JobTitl>

Presence: [0..1]

Definition: Title of the function.

Datatype: [Max35Text on page 173](#)

2.1.12.2.9 Responsibility <Rspnsblty>

Presence: [0..1]

Definition: Role of a person in an organisation.

Datatype: [Max35Text on page 173](#)

2.1.12.2.10 Department <Dept>

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: [Max70Text on page 173](#)

2.1.12.2.11 Other <Othr>

Presence: [0..*]

Definition: Contact details in another form.

Other <Othr> contains the following **OtherContact1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ChannelType <ChanITp>	[1..1]	Text		95
		Identification <Id>	[0..1]	Text		95

2.1.12.2.11.1 ChannelType <ChanITp>

Presence: [1..1]

Definition: Method used to contact the financial institution's contact for the specific tax region.

Datatype: [Max4Text on page 173](#)

2.1.12.2.11.2 Identification <Id>

Presence: [0..1]

Definition: Communication value such as phone number or email address.

Datatype: [Max128Text on page 172](#)

2.1.12.2.12 PreferredMethod <PrefrdMtd>

Presence: [0..1]

Definition: Preferred method used to reach the contact.

Datatype: [PreferredContactMethod1Code on page 163](#)

CodeName	Name	Definition
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.

CodeName	Name	Definition
FAXX	Fax	Preferred method used to reach the contact is per fax.
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.

2.1.13 Postal Address

2.1.13.1 PostalAddress24

Definition: Information that locates and identifies a specific address, as defined by postal services.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AddressType <AdrTp>	[0..1]			96
	{Or	Code <Cd>	[1..1]	CodeSet		97
	Or}	Proprietary <Prtry>	[1..1]	±		97
		Department <Dept>	[0..1]	Text		97
		SubDepartment <SubDept>	[0..1]	Text		97
		StreetName <StrtNm>	[0..1]	Text		98
		BuildingNumber <BldgNb>	[0..1]	Text		98
		BuildingName <BldgNm>	[0..1]	Text		98
		Floor <Flr>	[0..1]	Text		98
		PostBox <PstBx>	[0..1]	Text		98
		Room <Room>	[0..1]	Text		98
		PostCode <PstCd>	[0..1]	Text		98
		TownName <TwnNm>	[0..1]	Text		98
		TownLocationName <TwnLctnNm>	[0..1]	Text		99
		DistrictName <DstrctNm>	[0..1]	Text		99
		CountrySubDivision <CtrySubDvsn>	[0..1]	Text		99
		Country <Ctry>	[0..1]	CodeSet		99
		AddressLine <AdrLine>	[0..7]	Text		99

2.1.13.1.1 AddressType <AdrTp>

Presence: [0..1]

Definition: Identifies the nature of the postal address.

AddressType <AdrTp> contains one of the following **AddressType3Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		97
	Or}	Proprietary <Prtry>	[1..1]	±		97

2.1.13.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Type of address expressed as a code.

Datatype: [AddressType2Code](#) on page 144

CodeName	Name	Definition
ADDR	Postal	Address is the complete postal address.
PBOX	POBox	Address is a postal office (PO) box.
HOME	Residential	Address is the home address.
BIZZ	Business	Address is the business address.
MLTO	MailTo	Address is the address to which mail is sent.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.

2.1.13.1.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Type of address expressed as a proprietary code.

Proprietary <Prtry> contains the following elements (see [GenericIdentification30](#) on page 37 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	Text		37
		Issuer <Issr>	[1..1]	Text		37
		SchemeName <SchmeNm>	[0..1]	Text		37

2.1.13.1.2 Department <Dept>

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: [Max70Text](#) on page 173

2.1.13.1.3 SubDepartment <SubDept>

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: [Max70Text](#) on page 173

2.1.13.1.4 StreetName <StrtNm>

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: [Max70Text on page 173](#)

2.1.13.1.5 BuildingNumber <BldgNb>

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: [Max16Text on page 172](#)

2.1.13.1.6 BuildingName <BldgNm>

Presence: [0..1]

Definition: Name of the building or house.

Datatype: [Max35Text on page 173](#)

2.1.13.1.7 Floor <Flr>

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: [Max70Text on page 173](#)

2.1.13.1.8 PostBox <PstBx>

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: [Max16Text on page 172](#)

2.1.13.1.9 Room <Room>

Presence: [0..1]

Definition: Building room number.

Datatype: [Max70Text on page 173](#)

2.1.13.1.10 PostCode <PstCd>

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: [Max16Text on page 172](#)

2.1.13.1.11 TownName <TwnNm>

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: [Max35Text on page 173](#)

2.1.13.1.12 TownLocationName <TwnLctnNm>

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: Max35Text on page 173

2.1.13.1.13 DistrictName <DstrctNm>

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: Max35Text on page 173

2.1.13.1.14 CountrySubDivision <CtrySubDvsn>

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: Max35Text on page 173

2.1.13.1.15 Country <Ctry>

Presence: [0..1]

Definition: Nation with its own government.

Datatype: CountryCode on page 146

2.1.13.1.16 AddressLine <AdrLine>

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: Max70Text on page 173

2.1.14 Remittance

2.1.14.1 Garnishment3

Definition: Provides remittance information about a payment for garnishment-related purposes.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[1..1]			100
		CodeOrProprietary <CdOrPrtry>	[1..1]			100
	{Or	Code <Cd>	[1..1]	CodeSet		100
	Or}	Proprietary <Prtry>	[1..1]	Text		101
		Issuer <Issr>	[0..1]	Text		101
		Garnishee <Grnshee>	[0..1]	±		101
		GarnishmentAdministrator <GrnshmtAdmstr>	[0..1]	±		101
		ReferenceNumber <RefNb>	[0..1]	Text		102
		Date <Dt>	[0..1]	Date		102
		RemittedAmount <RmtdAmt>	[0..1]	Amount		102
		FamilyMedicalInsuranceIndicator <FmlyMdclInsrncInd>	[0..1]	Indicator		102
		EmployeeTerminationIndicator <MplyeeTermntnInd>	[0..1]	Indicator		102

2.1.14.1.1 Type <Tp>

Presence: [1..1]

Definition: Specifies the type of garnishment.

Type <Tp> contains the following **GarnishmentType1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CodeOrProprietary <CdOrPrtry>	[1..1]			100
	{Or	Code <Cd>	[1..1]	CodeSet		100
	Or}	Proprietary <Prtry>	[1..1]	Text		101
		Issuer <Issr>	[0..1]	Text		101

2.1.14.1.1.1 CodeOrProprietary <CdOrPrtry>

Presence: [1..1]

Definition: Provides the type details of the garnishment.

CodeOrProprietary <CdOrPrtry> contains one of the following **GarnishmentType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		100
	Or}	Proprietary <Prtry>	[1..1]	Text		101

2.1.14.1.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Garnishment type in a coded form.

Would suggest this to be an External Code List to contain:

GNCS Garnishment from a third party payer for Child Support

GNDP Garnishment from a Direct Payer for Child Support

GTPP Garnishment from a third party payer to taxing agency.

Datatype: [ExternalGarnishmentType1Code on page 155](#)

2.1.14.1.1.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Proprietary identification of the type of garnishment.

Datatype: [Max35Text on page 173](#)

2.1.14.1.1.2 Issuer <Issr>

Presence: [0..1]

Definition: Identification of the issuer of the garnishment type.

Datatype: [Max35Text on page 173](#)

2.1.14.1.2 Garnishee <Grnshee>

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor, in this case, to the garnisher.

Garnishee <Grnshee> contains the following elements (see [PartyIdentification135 on page 51](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		52
		PostalAddress <PstlAdr>	[0..1]	±		52
		Identification <Id>	[0..1]	±		53
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		53
		ContactDetails <CtctDtls>	[0..1]	±		54

2.1.14.1.3 GarnishmentAdministrator <GrnshmtAdmstr>

Presence: [0..1]

Definition: Party on the credit side of the transaction who administers the garnishment on behalf of the ultimate beneficiary.

GarnishmentAdministrator <GrnshmtAdmstr> contains the following elements (see [PartyIdentification135](#) on page 51 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		52
		PostalAddress <PstlAdr>	[0..1]	±		52
		Identification <Id>	[0..1]	±		53
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		53
		ContactDetails <CtctDtls>	[0..1]	±		54

2.1.14.1.4 ReferenceNumber <RefNb>

Presence: [0..1]

Definition: Reference information that is specific to the agency receiving the garnishment.

Datatype: [Max140Text](#) on page 172

2.1.14.1.5 Date <Dt>

Presence: [0..1]

Definition: Date of payment which garnishment was taken from.

Datatype: [ISODate](#) on page 168

2.1.14.1.6 RemittedAmount <RmtdAmt>

Presence: [0..1]

Definition: Amount of money remitted for the referred document.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 142

2.1.14.1.7 FamilyMedicalInsuranceIndicator <FmlyMdclInsrncInd>

Presence: [0..1]

Definition: Indicates if the person to whom the garnishment applies (that is, the ultimate debtor) has family medical insurance coverage available.

Datatype: One of the following values must be used (see [TrueFalseIndicator](#) on page 170):

- *Meaning When True:* True
- *Meaning When False:* False

2.1.14.1.8 EmployeeTerminationIndicator <MplyeeTermntnInd>

Presence: [0..1]

Definition: Indicates if the employment of the person to whom the garnishment applies (that is, the ultimate debtor) has been terminated.

Datatype: One of the following values must be used (see [TrueFalseIndicator](#) on page 170):

- *Meaning When True:* True
- *Meaning When False:* False

2.1.14.2 RemittanceInformation16

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Unstructured <Ustrd>	[0..*]	Text		103
		Structured <Strd>	[0..*]	±		103

2.1.14.2.1 Unstructured <Ustrd>

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form.

Datatype: Max140Text on page 172

2.1.14.2.2 Structured <Strd>

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

Structured <Strd> contains the following elements (see [StructuredRemittanceInformation16](#) on page 105 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ReferredDocumentInformation <RfrdDocInf>	[0..*]			107
		Type <Tp>	[0..1]			109
		CodeOrProprietary <CdOrPrtry>	[1..1]			109
	{Or	Code <Cd>	[1..1]	CodeSet		109
	Or}	Proprietary <Prtry>	[1..1]	Text		110
		Issuer <Issr>	[0..1]	Text		110
		Number <Nb>	[0..1]	Text		110
		RelatedDate <RltdDt>	[0..1]	Date		111
		LineDetails <LineDtls>	[0..*]			111
		Identification <Id>	[1..*]			112
		Type <Tp>	[0..1]			113
		CodeOrProprietary <CdOrPrtry>	[1..1]			113
	{Or	Code <Cd>	[1..1]	CodeSet		113
	Or}	Proprietary <Prtry>	[1..1]	Text		114
		Issuer <Issr>	[0..1]	Text		114
		Number <Nb>	[0..1]	Text		114
		RelatedDate <RltdDt>	[0..1]	Date		114
		Description <Desc>	[0..1]	Text		114
		Amount <Amt>	[0..1]			114
		DuePayableAmount <DuePyblAmt>	[0..1]	Amount		115
		DiscountAppliedAmount <DscntApldAmt>	[0..*]			115
		Type <Tp>	[0..1]			116
	{Or	Code <Cd>	[1..1]	CodeSet		116
	Or}	Proprietary <Prtry>	[1..1]	Text		116
		Amount <Amt>	[1..1]	Amount		116
		CreditNoteAmount <CdtNoteAmt>	[0..1]	Amount		116
		TaxAmount <TaxAmt>	[0..*]			116
		Type <Tp>	[0..1]			117
	{Or	Code <Cd>	[1..1]	CodeSet		117
	Or}	Proprietary <Prtry>	[1..1]	Text		117

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Amount		117
		AdjustmentAmountAndReason <AdjstmntAmtAndRsn>	[0..*]			117
		Amount <Amt>	[1..1]	Amount		118
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		118
		Reason <Rsn>	[0..1]	Text		118
		AdditionalInformation <AddtlInf>	[0..1]	Text		118
		RemittedAmount <RmtdAmt>	[0..1]	Amount		118
		ReferredDocumentAmount <RfrdDocAmt>	[0..1]	±		118
		CreditorReferenceInformation <CdtrRefInf>	[0..1]	±		119
		Invoicer <Invcr>	[0..1]	±		120
		Invoicee <Invcee>	[0..1]	±		120
		TaxRemittance <TaxRmt>	[0..1]	±		121
		GarnishmentRemittance <GrnshmtRmt>	[0..1]	±		121
		AdditionalRemittanceInformation <AddtlRmtInf>	[0..3]	Text		122

2.1.14.3 StructuredRemittanceInformation16

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		ReferredDocumentInformation <RfrdDocInf>	[0..*]			107
		Type <Tp>	[0..1]			109
		CodeOrProprietary <CdOrPrtry>	[1..1]			109
	{Or	Code <Cd>	[1..1]	CodeSet		109
	Or}	Proprietary <Prtry>	[1..1]	Text		110
		Issuer <Issr>	[0..1]	Text		110
		Number <Nb>	[0..1]	Text		110
		RelatedDate <RltdDt>	[0..1]	Date		111
		LineDetails <LineDtls>	[0..*]			111
		Identification <Id>	[1..*]			112
		Type <Tp>	[0..1]			113
		CodeOrProprietary <CdOrPrtry>	[1..1]			113
	{Or	Code <Cd>	[1..1]	CodeSet		113
	Or}	Proprietary <Prtry>	[1..1]	Text		114
		Issuer <Issr>	[0..1]	Text		114
		Number <Nb>	[0..1]	Text		114
		RelatedDate <RltdDt>	[0..1]	Date		114
		Description <Desc>	[0..1]	Text		114
		Amount <Amt>	[0..1]			114
		DuePayableAmount <DuePyblAmt>	[0..1]	Amount		115
		DiscountAppliedAmount <DscntApldAmt>	[0..*]			115
		Type <Tp>	[0..1]			116
	{Or	Code <Cd>	[1..1]	CodeSet		116
	Or}	Proprietary <Prtry>	[1..1]	Text		116
		Amount <Amt>	[1..1]	Amount		116
		CreditNoteAmount <CdtNoteAmt>	[0..1]	Amount		116
		TaxAmount <TaxAmt>	[0..*]			116
		Type <Tp>	[0..1]			117
	{Or	Code <Cd>	[1..1]	CodeSet		117
	Or}	Proprietary <Prtry>	[1..1]	Text		117
		Amount <Amt>	[1..1]	Amount		117

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AdjustmentAmountAndReason <AdjstmntAmtAndRsn>	[0..*]			117
		Amount <Amt>	[1..1]	Amount		118
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		118
		Reason <Rsn>	[0..1]	Text		118
		AdditionalInformation <AddtlInf>	[0..1]	Text		118
		RemittedAmount <RmtdAmt>	[0..1]	Amount		118
		ReferredDocumentAmount <RfrdDocAmt>	[0..1]	±		118
		CreditorReferenceInformation <CdtrRefInf>	[0..1]	±		119
		Invoice <Invcr>	[0..1]	±		120
		Invoicee <Invcee>	[0..1]	±		120
		TaxRemittance <TaxRmt>	[0..1]	±		121
		GarnishmentRemittance <GrnshmtRmt>	[0..1]	±		121
		AdditionalRemittanceInformation <AddtlRmtInf>	[0..3]	Text		122

2.1.14.3.1 ReferredDocumentInformation <RfrdDocInf>

Presence: [0..*]

Definition: Provides the identification and the content of the referred document.

ReferredDocumentInformation <RfrdDocInf> contains the following **ReferredDocumentInformation7** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			109
		CodeOrProprietary <CdOrPrtry>	[1..1]			109
	{Or	Code <Cd>	[1..1]	CodeSet		109
	Or}	Proprietary <Prtry>	[1..1]	Text		110
		Issuer <Issr>	[0..1]	Text		110
		Number <Nb>	[0..1]	Text		110
		RelatedDate <RltdDt>	[0..1]	Date		111
		LineDetails <LineDtls>	[0..*]			111
		Identification <Id>	[1..*]			112
		Type <Tp>	[0..1]			113
		CodeOrProprietary <CdOrPrtry>	[1..1]			113
	{Or	Code <Cd>	[1..1]	CodeSet		113
	Or}	Proprietary <Prtry>	[1..1]	Text		114
		Issuer <Issr>	[0..1]	Text		114
		Number <Nb>	[0..1]	Text		114
		RelatedDate <RltdDt>	[0..1]	Date		114
		Description <Desc>	[0..1]	Text		114
		Amount <Amt>	[0..1]			114
		DuePayableAmount <DuePyblAmt>	[0..1]	Amount		115
		DiscountAppliedAmount <DscntApldAmt>	[0..*]			115
		Type <Tp>	[0..1]			116
	{Or	Code <Cd>	[1..1]	CodeSet		116
	Or}	Proprietary <Prtry>	[1..1]	Text		116
		Amount <Amt>	[1..1]	Amount		116
		CreditNoteAmount <CdtNoteAmt>	[0..1]	Amount		116
		TaxAmount <TaxAmt>	[0..*]			116
		Type <Tp>	[0..1]			117
	{Or	Code <Cd>	[1..1]	CodeSet		117
	Or}	Proprietary <Prtry>	[1..1]	Text		117
		Amount <Amt>	[1..1]	Amount		117

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		AdjustmentAmountAndReason <AdjstmntAmtAndRsn>	[0..*]			117
		Amount <Amt>	[1..1]	Amount		118
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		118
		Reason <Rsn>	[0..1]	Text		118
		AdditionalInformation <AddtlInf>	[0..1]	Text		118
		RemittedAmount <RmtdAmt>	[0..1]	Amount		118

2.1.14.3.1.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of referred document.

Type <Tp> contains the following **ReferredDocumentType4** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CodeOrProprietary <CdOrPrtry>	[1..1]			109
	{Or	Code <Cd>	[1..1]	CodeSet		109
	Or}	Proprietary <Prtry>	[1..1]	Text		110
		Issuer <Issr>	[0..1]	Text		110

2.1.14.3.1.1.1 CodeOrProprietary <CdOrPrtry>

Presence: [1..1]

Definition: Provides the type details of the referred document.

CodeOrProprietary <CdOrPrtry> contains one of the following **ReferredDocumentType3Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		109
	Or}	Proprietary <Prtry>	[1..1]	Text		110

2.1.14.3.1.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Document type in a coded form.

Datatype: [DocumentType6Code](#) on page 147

CodeName	Name	Definition
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.

CodeName	Name	Definition
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
CINV	CommercialInvoice	Document is an invoice.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
DISP	DispatchAdvice	Document is a dispatch advice.
BOLD	BillOfLading	Document is a shipping notice.
VCHR	Voucher	Document is an electronic payment document.
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
PUOR	PurchaseOrder	Document is a purchase order.

2.1.14.3.1.1.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Proprietary identification of the type of the remittance document.

Datatype: Max35Text on page 173

2.1.14.3.1.1.1.2 Issuer <Issr>

Presence: [0..1]

Definition: Identification of the issuer of the reference document type.

Datatype: Max35Text on page 173

2.1.14.3.1.1.1.2 Number <Nb>

Presence: [0..1]

Definition: Unique and unambiguous identification of the referred document.

Datatype: Max35Text on page 173

2.1.14.3.1.3 RelatedDate <RltdDt>

Presence: [0..1]

Definition: Date associated with the referred document.

Datatype: ISODate on page 168

2.1.14.3.1.4 LineDetails <LineDtls>

Presence: [0..*]

Definition: Set of elements used to provide the content of the referred document line.

LineDetails <LineDtls> contains the following **DocumentLineInformation1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..*]			112
		Type <Tp>	[0..1]			113
		CodeOrProprietary <CdOrPrtry>	[1..1]			113
	{Or	Code <Cd>	[1..1]	CodeSet		113
	Or}	Proprietary <Prtry>	[1..1]	Text		114
		Issuer <Issr>	[0..1]	Text		114
		Number <Nb>	[0..1]	Text		114
		RelatedDate <RltdDt>	[0..1]	Date		114
		Description <Desc>	[0..1]	Text		114
		Amount <Amt>	[0..1]			114
		DuePayableAmount <DuePyblAmt>	[0..1]	Amount		115
		DiscountAppliedAmount <DscntApldAmt>	[0..*]			115
		Type <Tp>	[0..1]			116
	{Or	Code <Cd>	[1..1]	CodeSet		116
	Or}	Proprietary <Prtry>	[1..1]	Text		116
		Amount <Amt>	[1..1]	Amount		116
		CreditNoteAmount <CdtNoteAmt>	[0..1]	Amount		116
		TaxAmount <TaxAmt>	[0..*]			116
		Type <Tp>	[0..1]			117
	{Or	Code <Cd>	[1..1]	CodeSet		117
	Or}	Proprietary <Prtry>	[1..1]	Text		117
		Amount <Amt>	[1..1]	Amount		117
		AdjustmentAmountAndReason <AdjstmntAmtAndRsn>	[0..*]			117
		Amount <Amt>	[1..1]	Amount		118
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		118
		Reason <Rsn>	[0..1]	Text		118
		AdditionalInformation <AddtlInf>	[0..1]	Text		118
		RemittedAmount <RmtdAmt>	[0..1]	Amount		118

2.1.14.3.1.4.1 Identification <Id>

Presence: [1..*]

Definition: Provides identification of the document line.

Identification <Id> contains the following **DocumentLineIdentification1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			113
		CodeOrProprietary <CdOrPrtry>	[1..1]			113
	{Or	Code <Cd>	[1..1]	CodeSet		113
	Or}	Proprietary <Prtry>	[1..1]	Text		114
		Issuer <Issr>	[0..1]	Text		114
		Number <Nb>	[0..1]	Text		114
		RelatedDate <RltdDt>	[0..1]	Date		114

2.1.14.3.1.4.1.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of referred document line identification.

Type <Tp> contains the following **DocumentLineType1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		CodeOrProprietary <CdOrPrtry>	[1..1]			113
	{Or	Code <Cd>	[1..1]	CodeSet		113
	Or}	Proprietary <Prtry>	[1..1]	Text		114
		Issuer <Issr>	[0..1]	Text		114

2.1.14.3.1.4.1.1.1 CodeOrProprietary <CdOrPrtry>

Presence: [1..1]

Definition: Provides the type details of the referred document line identification.

CodeOrProprietary <CdOrPrtry> contains one of the following **DocumentLineType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		113
	Or}	Proprietary <Prtry>	[1..1]	Text		114

2.1.14.3.1.4.1.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Line identification type in a coded form.

Datatype: [ExternalDocumentLineType1Code](#) on page 153

2.1.14.3.1.4.1.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Proprietary identification of the type of the remittance document.

Datatype: Max35Text on page 173

2.1.14.3.1.4.1.1.2 Issuer <Issr>

Presence: [0..1]

Definition: Identification of the issuer of the reference document line identificationtype.

Datatype: Max35Text on page 173

2.1.14.3.1.4.1.2 Number <Nb>

Presence: [0..1]

Definition: Identification of the type specified for the referred document line.

Datatype: Max35Text on page 173

2.1.14.3.1.4.1.3 RelatedDate <RltdDt>

Presence: [0..1]

Definition: Date associated with the referred document line.

Datatype: ISODate on page 168

2.1.14.3.1.4.2 Description <Desc>

Presence: [0..1]

Definition: Description associated with the document line.

Datatype: Max2048Text on page 172

2.1.14.3.1.4.3 Amount <Amt>

Presence: [0..1]

Definition: Provides details on the amounts of the document line.

Amount <Amt> contains the following **RemittanceAmount3** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DuePayableAmount <DuePyblAmt>	[0..1]	Amount		115
		DiscountAppliedAmount <DscntApldAmt>	[0..*]			115
		Type <Tp>	[0..1]			116
	{Or	Code <Cd>	[1..1]	CodeSet		116
	Or}	Proprietary <Prtry>	[1..1]	Text		116
		Amount <Amt>	[1..1]	Amount		116
		CreditNoteAmount <CdtNoteAmt>	[0..1]	Amount		116
		TaxAmount <TaxAmt>	[0..*]			116
		Type <Tp>	[0..1]			117
	{Or	Code <Cd>	[1..1]	CodeSet		117
	Or}	Proprietary <Prtry>	[1..1]	Text		117
		Amount <Amt>	[1..1]	Amount		117
		AdjustmentAmountAndReason <AdjstmntAmtAndRsn>	[0..*]			117
		Amount <Amt>	[1..1]	Amount		118
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		118
		Reason <Rsn>	[0..1]	Text		118
		AdditionalInformation <AddtlInf>	[0..1]	Text		118
		RemittedAmount <RmtdAmt>	[0..1]	Amount		118

2.1.14.3.1.4.3.1 DuePayableAmount <DuePyblAmt>

Presence: [0..1]

Definition: Amount specified is the exact amount due and payable to the creditor.

Datatype: ActiveOrHistoricCurrencyAndAmount on page 142

2.1.14.3.1.4.3.2 DiscountAppliedAmount <DscntApldAmt>

Presence: [0..*]

Definition: Amount of discount to be applied to the amount due and payable to the creditor.

DiscountAppliedAmount <DscntApldAmt> contains the following **DiscountAmountAndType1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			116
	{Or	Code <Cd>	[1..1]	CodeSet		116
	Or}	Proprietary <Prtry>	[1..1]	Text		116
		Amount <Amt>	[1..1]	Amount		116

2.1.14.3.1.4.3.2.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of the amount.

Type <Tp> contains one of the following **DiscountAmountType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		116
	Or}	Proprietary <Prtry>	[1..1]	Text		116

2.1.14.3.1.4.3.2.1.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: [ExternalDiscountAmountType1Code on page 153](#)

2.1.14.3.1.4.3.2.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: [Max35Text on page 173](#)

2.1.14.3.1.4.3.2.2 Amount <Amt>

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 142](#)

2.1.14.3.1.4.3.3 CreditNoteAmount <CdtNoteAmt>

Presence: [0..1]

Definition: Amount of a credit note.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 142](#)

2.1.14.3.1.4.3.4 TaxAmount <TaxAmt>

Presence: [0..*]

Definition: Amount of the tax.

TaxAmount <TaxAmt> contains the following **TaxAmountAndType1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			117
	{Or	Code <Cd>	[1..1]	CodeSet		117
	Or}	Proprietary <Prtry>	[1..1]	Text		117
		Amount <Amt>	[1..1]	Amount		117

2.1.14.3.1.4.3.4.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of the amount.

Type <Tp> contains one of the following **TaxAmountType1Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		117
	Or}	Proprietary <Prtry>	[1..1]	Text		117

2.1.14.3.1.4.3.4.1.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: [ExternalTaxAmountType1Code](#) on page 159

2.1.14.3.1.4.3.4.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: [Max35Text](#) on page 173

2.1.14.3.1.4.3.4.2 Amount <Amt>

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 142

2.1.14.3.1.4.3.5 AdjustmentAmountAndReason <AdjstmntAmtAndRsn>

Presence: [0..*]

Definition: Specifies detailed information on the amount and reason of the adjustment.

AdjustmentAmountAndReason <AdjstmntAmtAndRsn> contains the following **DocumentAdjustment1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Amount <Amt>	[1..1]	Amount		118
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		118
		Reason <Rsn>	[0..1]	Text		118
		AdditionalInformation <AddtlInf>	[0..1]	Text		118

2.1.14.3.1.4.3.5.1 Amount <Amt>

Presence: [1..1]

Definition: Amount of money of the document adjustment.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 142](#)

2.1.14.3.1.4.3.5.2 CreditDebitIndicator <CdtDbtInd>

Presence: [0..1]

Definition: Specifies whether the adjustment must be subtracted or added to the total amount.

Datatype: [CreditDebitCode on page 146](#)

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

2.1.14.3.1.4.3.5.3 Reason <Rsn>

Presence: [0..1]

Definition: Specifies the reason for the adjustment.

Datatype: [Max4Text on page 173](#)

2.1.14.3.1.4.3.5.4 AdditionalInformation <AddtlInf>

Presence: [0..1]

Definition: Provides further details on the document adjustment.

Datatype: [Max140Text on page 172](#)

2.1.14.3.1.4.3.6 RemittedAmount <RmtdAmt>

Presence: [0..1]

Definition: Amount of money remitted.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 142](#)

2.1.14.3.2 ReferredDocumentAmount <RfrdDocAmt>

Presence: [0..1]

Definition: Provides details on the amounts of the referred document.

ReferredDocumentAmount <RfrdDocAmt> contains the following elements (see [RemittanceAmount2](#) on page 39 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		DuePayableAmount <DuePyblAmt>	[0..1]	Amount		40
		DiscountAppliedAmount <DscntApldAmt>	[0..*]			40
		Type <Tp>	[0..1]			41
	{Or	Code <Cd>	[1..1]	CodeSet		41
	Or}	Proprietary <Prtry>	[1..1]	Text		41
		Amount <Amt>	[1..1]	Amount		41
		CreditNoteAmount <CdtNoteAmt>	[0..1]	Amount		41
		TaxAmount <TaxAmt>	[0..*]			41
		Type <Tp>	[0..1]			42
	{Or	Code <Cd>	[1..1]	CodeSet		42
	Or}	Proprietary <Prtry>	[1..1]	Text		42
		Amount <Amt>	[1..1]	Amount		42
		AdjustmentAmountAndReason <AdjstmntAmtAndRsn>	[0..*]			42
		Amount <Amt>	[1..1]	Amount		43
		CreditDebitIndicator <CdtDbtInd>	[0..1]	CodeSet		43
		Reason <Rsn>	[0..1]	Text		43
		AdditionalInformation <AddtlInf>	[0..1]	Text		43
		RemittedAmount <RmtdAmt>	[0..1]	Amount		43

2.1.14.3.3 CreditorReferenceInformation <CdtrRefInf>

Presence: [0..1]

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

CreditorReferenceInformation <CdtrRefInf> contains the following elements (see [CreditorReferenceInformation2](#) on page 29 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]			29
		CodeOrProprietary <CdOrPrtry>	[1..1]			29
	{Or	Code <Cd>	[1..1]	CodeSet		30
	Or}	Proprietary <Prtry>	[1..1]	Text		30
		Issuer <Issr>	[0..1]	Text		30
		Reference <Ref>	[0..1]	Text		30

2.1.14.3.4 Invoicer <Invcr>

Presence: [0..1]

Definition: Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor.

Invoicer <Invcr> contains the following elements (see [PartyIdentification135](#) on page 51 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		52
		PostalAddress <PstlAdr>	[0..1]	±		52
		Identification <Id>	[0..1]	±		53
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		53
		ContactDetails <CtctDtls>	[0..1]	±		54

2.1.14.3.5 Invoicee <Invcee>

Presence: [0..1]

Definition: Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor.

Invoicee <Invcee> contains the following elements (see [PartyIdentification135](#) on page 51 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Name <Nm>	[0..1]	Text		52
		PostalAddress <PstlAdr>	[0..1]	±		52
		Identification <Id>	[0..1]	±		53
		CountryOfResidence <CtryOfRes>	[0..1]	CodeSet		53
		ContactDetails <CtctDtls>	[0..1]	±		54

2.1.14.3.6 TaxRemittance <TaxRmt>

Presence: [0..1]

Definition: Provides remittance information about a payment made for tax-related purposes.

TaxRemittance <TaxRmt> contains the following elements (see [TaxInformation7](#) on page 130 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Creditor <Cdtr>	[0..1]	±		130
		Debtor <Dbtr>	[0..1]	±		131
		UltimateDebtor <UltmtDbtr>	[0..1]	±		131
		AdministrationZone <AdmstnZone>	[0..1]	Text		131
		ReferenceNumber <RefNb>	[0..1]	Text		132
		Method <Mtd>	[0..1]	Text		132
		TotalTaxableBaseAmount <TtlTaxblBaseAmt>	[0..1]	Amount		132
		TotalTaxAmount <TtlTaxAmt>	[0..1]	Amount		132
		Date <Dt>	[0..1]	Date		132
		SequenceNumber <SeqNb>	[0..1]	Quantity		132
		Record <Rcrd>	[0..*]	±		132

2.1.14.3.7 GarnishmentRemittance <GrnshmtRmt>

Presence: [0..1]

Definition: Provides remittance information about a payment for garnishment-related purposes.

GarnishmentRemittance <GrnshmtRmt> contains the following elements (see [Garnishment3](#) on page 99 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[1..1]			100
		CodeOrProprietary <CdOrPrtry>	[1..1]			100
	{Or	Code <Cd>	[1..1]	CodeSet		100
	Or}	Proprietary <Prtry>	[1..1]	Text		101
		Issuer <Issr>	[0..1]	Text		101
		Garnishee <Grnshee>	[0..1]	±		101
		GarnishmentAdministrator <GrnshmtAdmstr>	[0..1]	±		101
		ReferenceNumber <RefNb>	[0..1]	Text		102
		Date <Dt>	[0..1]	Date		102
		RemittedAmount <RmtdAmt>	[0..1]	Amount		102
		FamilyMedicalInsuranceIndicator <FmlyMdclInsrncInd>	[0..1]	Indicator		102
		EmployeeTerminationIndicator <MplyeeTermtnInd>	[0..1]	Indicator		102

2.1.14.3.8 AdditionalRemittanceInformation <AddtlRmtInf>

Presence: [0..3]

Definition: Additional information, in free text form, to complement the structured remittance information.

Datatype: [Max140Text](#) on page 172

2.1.15 Settlement Instruction

2.1.15.1 SettlementInstruction7

Definition: Provides further details on the settlement of the instruction.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		SettlementMethod <SttlmMtd>	[1..1]	CodeSet		125
		SettlementAccount <SttlmAcct>	[0..1]	±		125
		ClearingSystem <ClrSys>	[0..1]			125
	{Or	Code <Cd>	[1..1]	CodeSet		126
	Or}	Proprietary <Prtry>	[1..1]	Text		126
		InstructingReimbursementAgent <InstgRmbrsmntAgt>	[0..1]	±		126
		InstructingReimbursementAgentAccount <InstgRmbrsmntAgtAcct>	[0..1]	±		126
		InstructedReimbursementAgent <InstdRmbrsmntAgt>	[0..1]	±		127
		InstructedReimbursementAgentAccount <InstdRmbrsmntAgtAcct>	[0..1]	±		127
		ThirdReimbursementAgent <ThrdRmbrsmntAgt>	[0..1]	±		128
		ThirdReimbursementAgentAccount <ThrdRmbrsmntAgtAcct>	[0..1]	±		128

Constraints

- **InstructedReimbursementAgentAccountRule**

If InstructedReimbursementAgentAccount is present, then InstructedReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00037
- *Error Text:* Invalid message content for instructed reimbursement agent account.

- **InstructingReimbursementAgentAccountRule**

If InstructingReimbursementAgentAccount is present, then InstructingReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00038
- *Error Text:* Invalid message content for instructing reimbursement agent account.

- **SettlementMethodAgentRule**

If SettlementMethod is equal to INDA or INGA, then ReimbursementAgent(s) and ClearingSystem are not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00018
- *Error Text:* Invalid message content for settlement method INGA or INDA.

- **SettlementMethodClearingRule**

If SettlementMethod is equal to CLRG, then SettlementAccount and ReimbursementAgent(s) are not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00019
- *Error Text:* Invalid message content for settlement method CLRG.

- **SettlementMethodCoverAgentRule**

If SettlementMethod is equal to COVE, then InstructedReimbursementAgent or InstructingReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00076
- *Error Text:* Invalid message content for cover settlement method and reimbursement agents.

- **SettlementMethodCoverRule**

If SettlementMethod is equal to COVE, then SettlementAccount and ClearingSystem are not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00075
- *Error Text:* Invalid message content for cover settlement method with settlement account and clearing system.

- **ThirdReimbursementAgentAccountRule**

If ThirdReimbursementAgentAccount is present, then ThirdReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00039
- *Error Text:* Invalid message content for third reimbursement agent account.

- **ThirdReimbursementAgentRule**

If ThirdReimbursementAgent is present, then InstructingReimbursementAgent and InstructedReimbursementAgent must both be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00040
- *Error Text:* Invalid message content for third reimbursement agent.

2.1.15.1.1 SettlementMethod <SttlmMtd>*Presence:* [1..1]*Definition:* Method used to settle the (batch of) payment instructions.*Datatype:* [SettlementMethod1Code](#) on page 165

CodeName	Name	Definition
INDA	InstructedAgent	Settlement is done by the agent instructed to execute a payment instruction.
INGA	InstructingAgent	Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.
COVE	CoverMethod	Settlement is done through a cover payment.
CLRG	ClearingSystem	Settlement is done through a payment clearing system.

2.1.15.1.2 SettlementAccount <SttlmAcct>*Presence:* [0..1]*Definition:* A specific purpose account used to post debit and credit entries as a result of the transaction.

SettlementAccount <SttlmAcct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.15.1.3 ClearingSystem <ClrSys>*Presence:* [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

ClearingSystem <ClrSys> contains one of the following **ClearingSystemIdentification3Choice** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		126
	Or}	Proprietary <Prtry>	[1..1]	Text		126

2.1.15.1.3.1 Code <Cd>

Presence: [1..1]

Definition: Infrastructure through which the payment instruction is processed, as published in an external clearing system identification code list.

Datatype: ExternalCashClearingSystem1Code on page 151

2.1.15.1.3.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Clearing system identification in a proprietary form.

Datatype: Max35Text on page 173

2.1.15.1.4 InstructingReimbursementAgent <InstgRmbrsmntAgt>

Presence: [0..1]

Definition: Agent through which the instructing agent will reimburse the instructed agent.

Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used.

InstructingReimbursementAgent <InstgRmbrsmntAgt> contains the following elements (see BranchAndFinancialInstitutionIdentification6 on page 35 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.15.1.5 InstructingReimbursementAgentAccount <InstgRmbrsmntAgtAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the instructing reimbursement agent account at its servicing agent in the payment chain.

InstructingReimbursementAgentAccount <InstgRmbrsmntAgtAcct> contains the following elements (see [CashAccount38 on page 24](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.15.1.6 InstructedReimbursementAgent <InstdRmbrsmntAgt>

Presence: [0..1]

Definition: Agent at which the instructed agent will be reimbursed.

Usage: If InstructedReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch.

Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used.

InstructedReimbursementAgent <InstdRmbrsmntAgt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6 on page 35](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.15.1.7 InstructedReimbursementAgentAccount <InstdRmbrsmntAgtAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the instructed reimbursement agent account at its servicing agent in the payment chain.

InstructedReimbursementAgentAccount <InstdRmbrsmntAgtAcct> contains the following elements (see [CashAccount38 on page 24](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.15.1.8 ThirdReimbursementAgent <ThrdRmbrsmntAgt>

Presence: [0..1]

Definition: Agent at which the instructed agent will be reimbursed.

Usage: If ThirdReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch.

ThirdReimbursementAgent <ThrdRmbrsmntAgt> contains the following elements (see [BranchAndFinancialInstitutionIdentification6](#) on page 35 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FinancialInstitutionIdentification <FinInstnId>	[1..1]	±		35
		BranchIdentification <BrnchId>	[0..1]	±		36

2.1.15.1.9 ThirdReimbursementAgentAccount <ThrdRmbrsmntAgtAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the third reimbursement agent account at its servicing agent in the payment chain.

ThirdReimbursementAgentAccount <ThrdRmbrsmntAgtAcct> contains the following elements (see [CashAccount38](#) on page 24 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Identification <Id>	[1..1]	±		24
		Type <Tp>	[0..1]	±		24
		Currency <Ccy>	[0..1]	CodeSet		24
		Name <Nm>	[0..1]	Text		25
		Proxy <Prxy>	[0..1]	±		25

2.1.16 System Identification

2.1.16.1 ClearingSystemIdentification2Choice

Definition: Choice of a clearing system identifier.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
	{Or	Code <Cd>	[1..1]	CodeSet		128
	Or}	Proprietary <Prtry>	[1..1]	Text		129

2.1.16.1.1 Code <Cd>

Presence: [1..1]

Definition: Identification of a clearing system, in a coded form as published in an external list.

Datatype: [ExternalClearingSystemIdentification1Code](#) on page 152

2.1.16.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Identification code for a clearing system, that has not yet been identified in the list of clearing systems.

Datatype: [Max35Text on page 173](#)

2.1.17 Tax

2.1.17.1 TaxParty2

Definition: Details about the entity involved in the tax paid or to be paid.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TaxIdentification <TaxId>	[0..1]	Text		129
		RegistrationIdentification <RegnId>	[0..1]	Text		129
		TaxType <TaxTp>	[0..1]	Text		129
		Authorisation <Authstn>	[0..1]			129
		Title <Titl>	[0..1]	Text		130
		Name <Nm>	[0..1]	Text		130

2.1.17.1.1 TaxIdentification <TaxId>

Presence: [0..1]

Definition: Tax identification number of the debtor.

Datatype: [Max35Text on page 173](#)

2.1.17.1.2 RegistrationIdentification <RegnId>

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: [Max35Text on page 173](#)

2.1.17.1.3 TaxType <TaxTp>

Presence: [0..1]

Definition: Type of tax payer.

Datatype: [Max35Text on page 173](#)

2.1.17.1.4 Authorisation <Authstn>

Presence: [0..1]

Definition: Details of the authorised tax paying party.

Authorisation <Authstn> contains the following **TaxAuthorisation1** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Title <Titl>	[0..1]	Text		130
		Name <Nm>	[0..1]	Text		130

2.1.17.1.4.1 Title <Titl>

Presence: [0..1]

Definition: Title or position of debtor or the debtor's authorised representative.

Datatype: Max35Text on page 173

2.1.17.1.4.2 Name <Nm>

Presence: [0..1]

Definition: Name of the debtor or the debtor's authorised representative.

Datatype: Max140Text on page 172

2.1.17.2 TaxInformation7

Definition: Details about tax paid, or to be paid, to the government in accordance with the law, including pre-defined parameters such as thresholds and type of account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Creditor <Cdtr>	[0..1]	±		130
		Debtor <Dbtr>	[0..1]	±		131
		UltimateDebtor <UltmtDbtr>	[0..1]	±		131
		AdministrationZone <AdmstnZone>	[0..1]	Text		131
		ReferenceNumber <RefNb>	[0..1]	Text		132
		Method <Mtd>	[0..1]	Text		132
		TotalTaxableBaseAmount <TtlTaxblBaseAmt>	[0..1]	Amount		132
		TotalTaxAmount <TtlTaxAmt>	[0..1]	Amount		132
		Date <Dt>	[0..1]	Date		132
		SequenceNumber <SeqNb>	[0..1]	Quantity		132
		Record <Rcrd>	[0..*]	±		132

2.1.17.2.1 Creditor <Cdtr>

Presence: [0..1]

Definition: Party on the credit side of the transaction to which the tax applies.

Creditor <Cdtr> contains the following elements (see [TaxParty1](#) on page 133 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TaxIdentification <TaxId>	[0..1]	Text		133
		RegistrationIdentification <RegnId>	[0..1]	Text		133
		TaxType <TaxTp>	[0..1]	Text		133

2.1.17.2.2 Debtor <Dbtr>

Presence: [0..1]

Definition: Identifies the party on the debit side of the transaction to which the tax applies.

Debtor <Dbtr> contains the following elements (see [TaxParty2](#) on page 129 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TaxIdentification <TaxId>	[0..1]	Text		129
		RegistrationIdentification <RegnId>	[0..1]	Text		129
		TaxType <TaxTp>	[0..1]	Text		129
		Authorisation <Authstn>	[0..1]			129
		Title <Titl>	[0..1]	Text		130
		Name <Nm>	[0..1]	Text		130

2.1.17.2.3 UltimateDebtor <UltmtDbtr>

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor, in this case, to the taxing authority.

UltimateDebtor <UltmtDbtr> contains the following elements (see [TaxParty2](#) on page 129 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TaxIdentification <TaxId>	[0..1]	Text		129
		RegistrationIdentification <RegnId>	[0..1]	Text		129
		TaxType <TaxTp>	[0..1]	Text		129
		Authorisation <Authstn>	[0..1]			129
		Title <Titl>	[0..1]	Text		130
		Name <Nm>	[0..1]	Text		130

2.1.17.2.4 AdministrationZone <AdmstnZone>

Presence: [0..1]

Definition: Territorial part of a country to which the tax payment is related.

Datatype: [Max35Text on page 173](#)

2.1.17.2.5 ReferenceNumber <RefNb>

Presence: [0..1]

Definition: Tax reference information that is specific to a taxing agency.

Datatype: [Max140Text on page 172](#)

2.1.17.2.6 Method <Mtd>

Presence: [0..1]

Definition: Method used to indicate the underlying business or how the tax is paid.

Datatype: [Max35Text on page 173](#)

2.1.17.2.7 TotalTaxableBaseAmount <TtlTaxblBaseAmt>

Presence: [0..1]

Definition: Total amount of money on which the tax is based.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 142](#)

2.1.17.2.8 TotalTaxAmount <TtlTaxAmt>

Presence: [0..1]

Definition: Total amount of money as result of the calculation of the tax.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 142](#)

2.1.17.2.9 Date <Dt>

Presence: [0..1]

Definition: Date by which tax is due.

Datatype: [ISODate on page 168](#)

2.1.17.2.10 SequenceNumber <SeqNb>

Presence: [0..1]

Definition: Sequential number of the tax report.

Datatype: [Number on page 171](#)

2.1.17.2.11 Record <Rcrd>

Presence: [0..*]

Definition: Record of tax details.

Record <Rcrd> contains the following elements (see [TaxRecord2](#) on page 137 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]	Text		138
		Category <Ctgy>	[0..1]	Text		138
		CategoryDetails <CtgyDtls>	[0..1]	Text		138
		DebtorStatus <DbtrSts>	[0..1]	Text		138
		CertificateIdentification <CertId>	[0..1]	Text		138
		FormsCode <FrmsCd>	[0..1]	Text		138
		Period <Prd>	[0..1]	±		138
		TaxAmount <TaxAmt>	[0..1]			139
		Rate <Rate>	[0..1]	Rate		139
		TaxableBaseAmount <TaxblBaseAmt>	[0..1]	Amount		139
		TotalAmount <TtlAmt>	[0..1]	Amount		139
		Details <Dtls>	[0..*]	±		139
		AdditionalInformation <AddtlInf>	[0..1]	Text		139

2.1.17.3 TaxParty1

Definition: Details about the entity involved in the tax paid or to be paid.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TaxIdentification <TaxId>	[0..1]	Text		133
		RegistrationIdentification <RegnId>	[0..1]	Text		133
		TaxType <TaxTp>	[0..1]	Text		133

2.1.17.3.1 TaxIdentification <TaxId>

Presence: [0..1]

Definition: Tax identification number of the creditor.

Datatype: [Max35Text](#) on page 173

2.1.17.3.2 RegistrationIdentification <RegnId>

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: [Max35Text](#) on page 173

2.1.17.3.3 TaxType <TaxTp>

Presence: [0..1]

Definition: Type of tax payer.

Datatype: [Max35Text on page 173](#)

2.1.17.4 TaxRecordDetails2

Definition: Provides information on the individual tax amount(s) per period of the tax record.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Period <Prd>	[0..1]	±		134
		Amount <Amt>	[1..1]	Amount		134

2.1.17.4.1 Period <Prd>

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

Period <Prd> contains the following elements (see [TaxPeriod2 on page 140](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Year <Yr>	[0..1]	Date		140
		Type <Tp>	[0..1]	CodeSet		140
		FromToDate <FrToDt>	[0..1]	±		141

2.1.17.4.2 Amount <Amt>

Presence: [1..1]

Definition: Underlying tax amount related to the specified period.

Datatype: [ActiveOrHistoricCurrencyAndAmount on page 142](#)

2.1.17.5 TaxInformation8

Definition: Details about tax paid, or to be paid, to the government in accordance with the law, including pre-defined parameters such as thresholds and type of account.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Creditor <Cdtr>	[0..1]	±		135
		Debtor <Dbtr>	[0..1]	±		135
		AdministrationZone <AdmstnZone>	[0..1]	Text		136
		ReferenceNumber <RefNb>	[0..1]	Text		136
		Method <Mtd>	[0..1]	Text		136
		TotalTaxableBaseAmount <TtlTaxblBaseAmt>	[0..1]	Amount		136
		TotalTaxAmount <TtlTaxAmt>	[0..1]	Amount		136
		Date <Dt>	[0..1]	Date		136
		SequenceNumber <SeqNb>	[0..1]	Quantity		136
		Record <Rcrd>	[0..*]	±		136

2.1.17.5.1 Creditor <Cdtr>

Presence: [0..1]

Definition: Party on the credit side of the transaction to which the tax applies.

Creditor <Cdtr> contains the following elements (see [TaxParty1](#) on page 133 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TaxIdentification <TaxId>	[0..1]	Text		133
		RegistrationIdentification <RegnId>	[0..1]	Text		133
		TaxType <TaxTp>	[0..1]	Text		133

2.1.17.5.2 Debtor <Dbtr>

Presence: [0..1]

Definition: Party on the debit side of the transaction to which the tax applies.

Debtor <Dbtr> contains the following elements (see [TaxParty2](#) on page 129 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		TaxIdentification <TaxId>	[0..1]	Text		129
		RegistrationIdentification <RegnId>	[0..1]	Text		129
		TaxType <TaxTp>	[0..1]	Text		129
		Authorisation <Authstn>	[0..1]			129
		Title <Titl>	[0..1]	Text		130
		Name <Nm>	[0..1]	Text		130

2.1.17.5.3 AdministrationZone <AdmstnZone>

Presence: [0..1]

Definition: Territorial part of a country to which the tax payment is related.

Datatype: Max35Text on page 173

2.1.17.5.4 ReferenceNumber <RefNb>

Presence: [0..1]

Definition: Tax reference information that is specific to a taxing agency.

Datatype: Max140Text on page 172

2.1.17.5.5 Method <Mtd>

Presence: [0..1]

Definition: Method used to indicate the underlying business or how the tax is paid.

Datatype: Max35Text on page 173

2.1.17.5.6 TotalTaxableBaseAmount <TtlTaxblBaseAmt>

Presence: [0..1]

Definition: Total amount of money on which the tax is based.

Datatype: ActiveOrHistoricCurrencyAndAmount on page 142

2.1.17.5.7 TotalTaxAmount <TtlTaxAmt>

Presence: [0..1]

Definition: Total amount of money as result of the calculation of the tax.

Datatype: ActiveOrHistoricCurrencyAndAmount on page 142

2.1.17.5.8 Date <Dt>

Presence: [0..1]

Definition: Date by which tax is due.

Datatype: ISODate on page 168

2.1.17.5.9 SequenceNumber <SeqNb>

Presence: [0..1]

Definition: Sequential number of the tax report.

Datatype: Number on page 171

2.1.17.5.10 Record <Rcrd>

Presence: [0..*]

Definition: Record of tax details.

Record <Rcrd> contains the following elements (see [TaxRecord2](#) on page 137 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]	Text		138
		Category <Ctgy>	[0..1]	Text		138
		CategoryDetails <CtgyDtls>	[0..1]	Text		138
		DebtorStatus <DbtrSts>	[0..1]	Text		138
		CertificateIdentification <CertId>	[0..1]	Text		138
		FormsCode <FrmsCd>	[0..1]	Text		138
		Period <Prd>	[0..1]	±		138
		TaxAmount <TaxAmt>	[0..1]			139
		Rate <Rate>	[0..1]	Rate		139
		TaxableBaseAmount <TaxblBaseAmt>	[0..1]	Amount		139
		TotalAmount <TtlAmt>	[0..1]	Amount		139
		Details <Dtls>	[0..*]	±		139
		AdditionalInformation <AddtlInf>	[0..1]	Text		139

2.1.17.6 TaxRecord2

Definition: Set of elements used to define the tax record.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Type <Tp>	[0..1]	Text		138
		Category <Ctgy>	[0..1]	Text		138
		CategoryDetails <CtgyDtls>	[0..1]	Text		138
		DebtorStatus <DbtrSts>	[0..1]	Text		138
		CertificateIdentification <CertId>	[0..1]	Text		138
		FormsCode <FrmsCd>	[0..1]	Text		138
		Period <Prd>	[0..1]	±		138
		TaxAmount <TaxAmt>	[0..1]			139
		Rate <Rate>	[0..1]	Rate		139
		TaxableBaseAmount <TaxblBaseAmt>	[0..1]	Amount		139
		TotalAmount <TtlAmt>	[0..1]	Amount		139
		Details <Dtls>	[0..*]	±		139
		AdditionalInformation <AddtlInf>	[0..1]	Text		139

2.1.17.6.1 Type <Tp>*Presence:* [0..1]*Definition:* High level code to identify the type of tax details.*Datatype:* [Max35Text on page 173](#)**2.1.17.6.2 Category <Ctgy>***Presence:* [0..1]*Definition:* Specifies the tax code as published by the tax authority.*Datatype:* [Max35Text on page 173](#)**2.1.17.6.3 CategoryDetails <CtgyDtls>***Presence:* [0..1]*Definition:* Provides further details of the category tax code.*Datatype:* [Max35Text on page 173](#)**2.1.17.6.4 DebtorStatus <DbtrSts>***Presence:* [0..1]*Definition:* Code provided by local authority to identify the status of the party that has drawn up the settlement document.*Datatype:* [Max35Text on page 173](#)**2.1.17.6.5 CertificateIdentification <CertId>***Presence:* [0..1]*Definition:* Identification number of the tax report as assigned by the taxing authority.*Datatype:* [Max35Text on page 173](#)**2.1.17.6.6 FormsCode <FrmsCd>***Presence:* [0..1]*Definition:* Identifies, in a coded form, on which template the tax report is to be provided.*Datatype:* [Max35Text on page 173](#)**2.1.17.6.7 Period <Prd>***Presence:* [0..1]*Definition:* Set of elements used to provide details on the period of time related to the tax payment.**Period <Prd>** contains the following elements (see [TaxPeriod2 on page 140](#) for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Year <Yr>	[0..1]	Date		140
		Type <Tp>	[0..1]	CodeSet		140
		FromDate <FrToDt>	[0..1]	±		141

2.1.17.6.8 TaxAmount <TaxAmt>

Presence: [0..1]

Definition: Set of elements used to provide information on the amount of the tax record.

TaxAmount <TaxAmt> contains the following **TaxAmount2** elements

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Rate <Rate>	[0..1]	Rate		139
		TaxableBaseAmount <TaxblBaseAmt>	[0..1]	Amount		139
		TotalAmount <TtlAmt>	[0..1]	Amount		139
		Details <Dtls>	[0..*]	±		139

2.1.17.6.8.1 Rate <Rate>

Presence: [0..1]

Definition: Rate used to calculate the tax.

Datatype: [PercentageRate](#) on page 171

2.1.17.6.8.2 TaxableBaseAmount <TaxblBaseAmt>

Presence: [0..1]

Definition: Amount of money on which the tax is based.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 142

2.1.17.6.8.3 TotalAmount <TtlAmt>

Presence: [0..1]

Definition: Total amount that is the result of the calculation of the tax for the record.

Datatype: [ActiveOrHistoricCurrencyAndAmount](#) on page 142

2.1.17.6.8.4 Details <Dtls>

Presence: [0..*]

Definition: Set of elements used to provide details on the tax period and amount.

Details <Dtls> contains the following elements (see [TaxRecordDetails2](#) on page 134 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Period <Prd>	[0..1]	±		134
		Amount <Amt>	[1..1]	Amount		134

2.1.17.6.9 AdditionalInformation <AddtlInf>

Presence: [0..1]

Definition: Further details of the tax record.

Datatype: [Max140Text](#) on page 172

2.1.17.7 TaxPeriod2

Definition: Period of time details related to the tax payment.

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		Year <Yr>	[0..1]	Date		140
		Type <Tp>	[0..1]	CodeSet		140
		FromDate <FrToDt>	[0..1]	±		141

2.1.17.7.1 Year <Yr>

Presence: [0..1]

Definition: Year related to the tax payment.

Datatype: ISODate on page 168

2.1.17.7.2 Type <Tp>

Presence: [0..1]

Definition: Identification of the period related to the tax payment.

Datatype: TaxRecordPeriod1Code on page 165

CodeName	Name	Definition
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.

CodeName	Name	Definition
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.

2.1.17.7.3 FromToDate <FrToDt>

Presence: [0..1]

Definition: Range of time between a start date and an end date for which the tax report is provided.

FromToDate <FrToDt> contains the following elements (see [DatePeriod2](#) on page 28 for details)

Index	Or	MessageElement<XML Tag>	Mult.	Type	Constr. No.	Page
		FromDate <FrDt>	[1..1]	Date		29
		ToDate <ToDt>	[1..1]	Date		29

2.2 Message Datatypes

2.2.1 Amount

2.2.1.1 ActiveCurrencyAndAmount

Definition: A number of monetary units specified in an active currency where the unit of currency is explicit and compliant with ISO 4217.

Type: Amount

This data type contains the following XML attribute:

Name	Attribute XML Name	Datatype
Currency	Ccy	ActiveCurrencyCode on page 143

Format

minInclusive	0
totalDigits	18
fractionDigits	5

Constraints

- **ActiveCurrency**

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00005
- *Error Text:* Invalid currency code

- **CurrencyAmount**

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

2.2.1.2 ActiveOrHistoricCurrencyAndAmount

Definition: A number of monetary units specified in an active or a historic currency where the unit of currency is explicit and compliant with ISO 4217.

Type: Amount

This data type contains the following XML attribute:

Name	Attribute XML Name	Datatype
Currency	Ccy	ActiveOrHistoricCurrencyCode on page 144

Format

minInclusive	0
totalDigits	18
fractionDigits	5

Constraints

- **ActiveOrHistoricCurrency**

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

- **CurrencyAmount**

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

2.2.2 CodeSet

2.2.2.1 ActiveCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern [A-Z]{3,3}

Constraints

- **ActiveCurrency**

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00005
- *Error Text:* Invalid currency code

Restricts

ParentCurrencyCode on page 163

2.2.2.2 ActiveOrHistoricCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme, as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern [A-Z]{3,3}

Constraints

- **ActiveOrHistoricCurrency**

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

Restricts

[ParentCurrencyCode on page 163](#)

2.2.2.3 AddressType2Code

Definition: Specifies the type of address.

Type: CodeSet

CodeName	Name	Definition
ADDR	Postal	Address is the complete postal address.
PBOX	POBox	Address is a postal office (PO) box.
HOME	Residential	Address is the home address.
BIZZ	Business	Address is the business address.
MLTO	MailTo	Address is the address to which mail is sent.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.

Restricts

[AddressTypeCode on page 144](#)

2.2.2.4 AddressTypeCode

Definition: Specifies the type of address.

Type: CodeSet

CodeName	Name	Definition
HOME	Residential	Address is the home address.
BIZZ	Business	Address is the business address.
ADDR	Postal	Address is the complete postal address.
PBOX	POBox	Address is a postal office (PO) box.
MLTO	MailTo	Address is the address to which mail is sent.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.

Is restricted by

[AddressType2Code](#) on page 144

2.2.2.5 AmountDirectionCode

Definition: Specifies if an operation is an increase or a decrease or the result of a reversal operation.

Type: CodeSet

CodeName	Name	Definition
DBIT	Debit	Operation is a decrease.
CRDT	Credit	Operation is an increase.
RVDB	ReversalDebit	Credit entry used to reverse a previously booked debit entry.
RVCD	ReversalCredit	Debit entry used to reverse a previously booked credit entry.

Is restricted by

[CreditDebitCode](#) on page 146

2.2.2.6 ClearingChannel2Code

Definition: Specifies the clearing channel for the routing of the transaction, as part of the payment type identification.

Type: CodeSet

CodeName	Name	Definition
RTGS	RealTimeGrossSettlementSystem	Clearing channel is a real-time gross settlement system.
RTNS	RealTimeNetSettlementSystem	Clearing channel is a real-time net settlement system.
MPNS	MassPaymentNetSystem	Clearing channel is a mass payment net settlement system.
BOOK	BookTransfer	Payment through internal book transfer.

Restricts

[ClearingChannelCode on page 146](#)

2.2.2.7 ClearingChannelCode

Definition: Specifies the clearing channel for the routing of the transaction, as part of the payment type identification.

Type: CodeSet

CodeName	Name	Definition
RTGS	RealTimeGrossSettlementSystem	Clearing channel is a real-time gross settlement system.
RTNS	RealTimeNetSettlementSystem	Clearing channel is a real-time net settlement system.
MPNS	MassPaymentNetSystem	Clearing channel is a mass payment net settlement system.
BOOK	BookTransfer	Payment through internal book transfer.

Is restricted by

[ClearingChannel2Code on page 145](#)

2.2.2.8 CountryCode

Definition: Code to identify a country, a dependency, or another area of particular geopolitical interest, on the basis of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Type: CodeSet

Format

pattern [A-Z]{2,2}

Constraints

- **Country**

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

2.2.2.9 CreditDebitCode

Definition: Specifies if an operation is an increase or a decrease.

Type: CodeSet

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.

CodeName	Name	Definition
DBIT	Debit	Operation is a decrease.

Restricts

AmountDirectionCode on page 145

2.2.2.10 DocumentType3Code

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

CodeName	Name	Definition
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, for example, in a cover scenario.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
DISP	DispatchAdvice	Document is a dispatch advice.
PUOR	PurchaseOrder	Document is a purchase order.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.

Restricts

DocumentTypeCode on page 148

2.2.2.11 DocumentType6Code

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

CodeName	Name	Definition
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
CINV	CommercialInvoice	Document is an invoice.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.

CodeName	Name	Definition
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
DISP	DispatchAdvice	Document is a dispatch advice.
BOLD	BillOfLading	Document is a shipping notice.
VCHR	Voucher	Document is an electronic payment document.
AROJ	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
PUOR	PurchaseOrder	Document is a purchase order.

Restricts

DocumentTypeCode on page 148

2.2.2.12 DocumentTypeCode

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

CodeName	Name	Definition
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
CINV	CommercialInvoice	Document is an invoice.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.

CodeName	Name	Definition
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, for example, in a cover scenario.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
DISP	DispatchAdvice	Document is a dispatch advice.
PUOR	PurchaseOrder	Document is a purchase order.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.
BOLD	BillOfLading	Document is a shipping notice.
VCHR	Voucher	Document is an electronic payment document.
AROJ	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
HRCP	CashierReceipt	When the Sale system print the Cashier copy of the Payment receipt.
CRCP	CustomerReceipt	When the Sale System requires the POI system to print the Customer receipt.
JNRL	Journal	When the POI or the Sale System wants to store a message on the journal printer or electronic journal of the Sale Terminal (it is sometimes a Sale Logging/Journal Printer).
SRCP	SaleReceipt	When the Sale System requires the POI system to print the Sale receipt.

Is restricted by

[DocumentType3Code on page 147](#), [DocumentType6Code on page 147](#)

2.2.2.13 ExternalAccountIdentification1Code

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalAccountIdentificationCode on page 150](#)

2.2.2.14 ExternalAccountIdentificationCode

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalAccountIdentification1Code on page 149](#)

2.2.2.15 ExternalCashAccountType1Code

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalCashAccountTypeCode on page 151](#)

2.2.2.16 ExternalCashAccountTypeCode

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalCashAccountType1Code on page 150](#)

2.2.2.17 ExternalCashClearingSystem1Code

Definition: Specifies the cash clearing system, as published in an external cash clearing system code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	3

Restricts

[ExternalCashClearingSystemCode on page 151](#)

2.2.2.18 ExternalCashClearingSystemCode

Definition: Specifies the cash clearing system, as published in an external cash clearing system code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalCashClearingSystem1Code on page 151](#)

2.2.2.19 ExternalCategoryPurpose1Code

Definition: Specifies the category purpose, as published in an external category purpose code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalCategoryPurposeCode on page 152](#)

2.2.2.20 ExternalCategoryPurposeCode

Definition: Specifies the category purpose, as published in an external category purpose code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalCategoryPurpose1Code on page 152](#)

2.2.2.21 ExternalClearingSystemIdentification1Code

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	5

Restricts

[ExternalClearingSystemIdentificationCode on page 152](#)

2.2.2.22 ExternalClearingSystemIdentificationCode

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	5

Is restricted by

[ExternalClearingSystemIdentification1Code](#) on page 152

2.2.2.23 ExternalDiscountAmountType1Code

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalDiscountAmountTypeCode](#) on page 153

2.2.2.24 ExternalDiscountAmountTypeCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalDiscountAmountType1Code](#) on page 153

2.2.2.25 ExternalDocumentLineType1Code

Definition: Specifies the document line type as published in an external document type code list.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalDocumentLineTypeCode on page 154](#)

2.2.2.26 ExternalDocumentLineTypeCode

Definition: Specifies the document line type as published in an external document type code list.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalDocumentLineType1Code on page 153](#)

2.2.2.27 ExternalFinancialInstitutionIdentification1Code

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalFinancialInstitutionIdentificationCode on page 154](#)

2.2.2.28 ExternalFinancialInstitutionIdentificationCode

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

ExternalFinancialInstitutionIdentification1Code on page 154

2.2.2.29 ExternalGarnishmentType1Code

Definition: Specifies the garnishment type as published in an external document type code list.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

ExternalGarnishmentTypeCode on page 155

2.2.2.30 ExternalGarnishmentTypeCode

Definition: Specifies the garnishment type as published in an external document type code list.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

ExternalGarnishmentType1Code on page 155

2.2.2.31 ExternalLocalInstrument1Code

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	35

Restricts

[ExternalLocalInstrumentCode on page 156](#)

2.2.2.32 ExternalLocalInstrumentCode

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	35

Is restricted by

[ExternalLocalInstrument1Code on page 155](#)

2.2.2.33 ExternalOrganisationIdentification1Code

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalOrganisationIdentificationCode on page 156](#)

2.2.2.34 ExternalOrganisationIdentificationCode

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalOrganisationIdentification1Code on page 156](#)

2.2.2.35 ExternalPersonIdentification1Code

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalPersonIdentificationCode on page 157](#)

2.2.2.36 ExternalPersonIdentificationCode

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalPersonIdentification1Code on page 157](#)

2.2.2.37 ExternalProxyAccountType1Code

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalProxyAccountTypeCode on page 158](#)

2.2.2.38 ExternalProxyAccountTypeCode

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalProxyAccountType1Code on page 157](#)

2.2.2.39 ExternalPurpose1Code

Definition: Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalPurposeCode on page 158](#)

2.2.2.40 ExternalPurposeCode

Definition: Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

ExternalPurpose1Code on page 158

2.2.2.41 ExternalServiceLevel1Code

Definition: Specifies the external service level code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

ExternalServiceLevelCode on page 159

2.2.2.42 ExternalServiceLevelCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

ExternalServiceLevel1Code on page 159

2.2.2.43 ExternalTaxAmountType1Code

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Restricts

[ExternalTaxAmountTypeCode on page 160](#)

2.2.2.44 ExternalTaxAmountTypeCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

Is restricted by

[ExternalTaxAmountType1Code on page 159](#)

2.2.2.45 Instruction3Code

Definition: Specifies further instructions concerning the processing of a payment instruction, provided by the sending clearing agent to the next agent(s).

Type: CodeSet

CodeName	Name	Definition
CHQB	PayCreditorByCheque	(Ultimate) creditor must be paid by cheque.
HOLD	HoldCashForCreditor	Amount of money must be held for the (ultimate) creditor, who will call. Pay on identification.
PHOB	PhoneBeneficiary	Please advise/contact (ultimate) creditor/claimant by phone.
TELB	Telecom	Please advise/contact (ultimate) creditor/claimant by the most efficient means of telecommunication.

Restricts

[InstructionCode on page 161](#)

2.2.2.46 Instruction4Code

Definition: Specifies further instructions concerning the processing of a payment instruction, provided by the sending clearing agent to the next agent(s).

Type: CodeSet

CodeName	Name	Definition
PHOA	PhoneNextAgent	Please advise/contact next agent by phone.
TELA	TelecomNextAgent	Please advise/contact next agent by the most efficient means of telecommunication.

Restricts

[InstructionCode on page 161](#)

2.2.2.47 Instruction5Code

Definition: Specifies further instructions concerning the processing of a payment instruction, provided by the sending clearing agent to the next agent(s).

Type: CodeSet

CodeName	Name	Definition
PHOB	PhoneBeneficiary	Please advise/contact (ultimate) creditor/claimant by phone.
TELB	Telecom	Please advise/contact (ultimate) creditor/claimant by the most efficient means of telecommunication.

Restricts

[InstructionCode on page 161](#)

2.2.2.48 InstructionCode

Definition: Specifies further instructions concerning the processing of a payment instruction.

Type: CodeSet

CodeName	Name	Definition
PBEN	PayTheBeneficiary	(Ultimate) creditor to be paid only after verification of identity.
TTIL	TimeTill	Payment instruction is valid and eligible for execution until the date and time stipulated. Otherwise, the payment instruction will be rejected.
TFRO	TimeFrom	Payment instruction will be valid and eligible for execution from the date and time stipulated.
CHQB	PayCreditorByCheque	(Ultimate) creditor must be paid by cheque.

CodeName	Name	Definition
HOLD	HoldCashForCreditor	Amount of money must be held for the (ultimate) creditor, who will call. Pay on identification.
PHOB	PhoneBeneficiary	Please advise/contact (ultimate) creditor/claimant by phone.
TELB	Telecom	Please advise/contact (ultimate) creditor/claimant by the most efficient means of telecommunication.
PHOA	PhoneNextAgent	Please advise/contact next agent by phone.
TELA	TelecomNextAgent	Please advise/contact next agent by the most efficient means of telecommunication.

Is restricted by

[Instruction3Code on page 160](#), [Instruction4Code on page 161](#), [Instruction5Code on page 161](#)

2.2.2.49 NamePrefix2Code

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

CodeName	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).

Restricts

[NamePrefixCode on page 162](#)

2.2.2.50 NamePrefixCode

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

CodeName	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MIST	Mister	Title of the person is Mister or Mr.
MISS	Miss	Title of the person is Miss.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).

Is restricted by

[NamePrefix2Code](#) on page 162

2.2.2.51 ParentCurrencyCode

Definition: Code allocated to a currency, by a maintenance agency, under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds". Valid currency codes are registered with the ISO 4217 Maintenance Agency, and consist of three contiguous letters.

Type: CodeSet

Format

pattern [A-Z]{3,3}

Is restricted by

[ActiveCurrencyCode](#) on page 143, [ActiveOrHistoricCurrencyCode](#) on page 144

2.2.2.52 PreferredContactMethod1Code

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

CodeName	Name	Definition
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.

Restricts

[PreferredContactMethodCode](#) on page 163

2.2.2.53 PreferredContactMethodCode

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

CodeName	Name	Definition
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.

CodeName	Name	Definition
FAXX	Fax	Preferred method used to reach the contact is per fax.
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
ONLI	Online	Preferred method used to reach the contact is online.

Is restricted by

[PreferredContactMethod1Code on page 163](#)

2.2.2.54 Priority2Code

Definition: Specifies the priority level of an event.

Type: CodeSet

CodeName	Name	Definition
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

Restricts

[PriorityCode on page 164](#)

2.2.2.55 Priority3Code

Definition: Specifies the priority level of an event.

Type: CodeSet

CodeName	Name	Definition
URGT	Urgent	Priority level is urgent (highest priority possible).
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

Restricts

[PriorityCode on page 164](#)

2.2.2.56 PriorityCode

Definition: Specifies the priority level of an event.

Type: CodeSet

CodeName	Name	Definition
URGT	Urgent	Priority level is urgent (highest priority possible).
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

CodeName	Name	Definition
LOWW	Low	Priority level is low.

Is restricted by

[Priority2Code](#) on page 164, [Priority3Code](#) on page 164

2.2.2.57 SettlementMethod1Code

Definition: Specifies the method used to settle the credit transfer instruction.

Type: CodeSet

CodeName	Name	Definition
INDA	InstructedAgent	Settlement is done by the agent instructed to execute a payment instruction.
INGA	InstructingAgent	Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.
COVE	CoverMethod	Settlement is done through a cover payment.
CLRG	ClearingSystem	Settlement is done through a payment clearing system.

Restricts

[SettlementMethodCode](#) on page 165

2.2.2.58 SettlementMethodCode

Definition: Specifies the method used to settle the payment instruction.

Type: CodeSet

CodeName	Name	Definition
INDA	InstructedAgent	Settlement is done by the agent instructed to execute a payment instruction.
INGA	InstructingAgent	Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.
COVE	CoverMethod	Settlement is done through a cover payment.
CLRG	ClearingSystem	Settlement is done through a payment clearing system.

Is restricted by

[SettlementMethod1Code](#) on page 165

2.2.2.59 TaxRecordPeriod1Code

Definition: Specifies the period related to the tax payment.

Type: CodeSet

CodeName	Name	Definition
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.

Restricts

[TaxRecordPeriodCode](#) on page 166

2.2.2.60 TaxRecordPeriodCode

Definition: Specifies the period related to the tax payment.

Type: CodeSet

CodeName	Name	Definition
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.

Is restricted by

TaxRecordPeriod1Code on page 165

2.2.3 Date

2.2.3.1 ISODate

Definition: A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Type: Date

2.2.4 DateTime

2.2.4.1 ISODateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: DateTime

2.2.5 IdentifierSet

2.2.5.1 AnyBICDec2014Identifier

Definition: Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Identification scheme: SWIFT; AnyBICIdentifier

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Constraints

- **AnyBIC**

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consists of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

2.2.5.2 BICFIDec2014Identifier

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Identification scheme: SWIFT; BICIdentifier

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Constraints

- **BICFI**

Valid BICs for financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consist of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid FI BIC.

2.2.5.3 IBAN2007Identifier

Definition: The International Bank Account Number is a code used internationally by financial institutions to uniquely identify the account of a customer at a financial institution as described in the 2007 edition of the ISO 13616 standard "Banking and related financial services - International Bank Account Number (IBAN)" and replaced by the more recent edition of the standard.

Type: IdentifierSet

Identification scheme: National Banking Association; International Bank Account Number (ISO 13616)

Format

pattern [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}

Constraints**• IBAN**

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00003
- *Error Text:* Invalid IBAN format or invalid check digits.

2.2.5.4 LEIdentifier

Definition: Legal Entity Identifier is a code allocated to a party as described in ISO 17442 "Financial Services - Legal Entity Identifier (LEI)".

Type: IdentifierSet

Identification scheme: Global LEI System; LEIdentifier

Format

pattern [A-Z0-9]{18,18}[0-9]{2,2}

2.2.5.5 UUIDv4Identifier

Definition: Universally Unique Identifier (UUID) version 4, as described in IETF RFC 4122 "Universally Unique Identifier (UUID) URN Namespace".

Type: IdentifierSet

Identification scheme: RFC4122; UUIDv4

Format

pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}

2.2.6 Indicator**2.2.6.1 BatchBookingIndicator**

Definition: Identifies whether the sending party requests a single debit or credit entry per individual transaction or a batch entry for the sum of the amounts of all transactions.

Type: Indicator

Meaning When True: Identifies that a batch entry for the sum of the amounts of all transactions in the batch or message is requested.

Meaning When False: Identifies that a single entry for each of the transactions in the batch or message is requested.

2.2.6.2 TrueFalseIndicator

Definition: A flag indicating a True or False value.

Type: Indicator

Meaning When True: True

Meaning When False: False

2.2.7 Quantity

2.2.7.1 DecimalNumber

Definition: Number of objects represented as a decimal number, for example 0.75 or 45.6.

Type: Quantity

Format

totalDigits	18
fractionDigits	17

2.2.7.2 Number

Definition: Number of objects represented as an integer.

Type: Quantity

Format

totalDigits	18
fractionDigits	0

2.2.8 Rate

2.2.8.1 PercentageRate

Definition: Rate expressed as a percentage, that is, in hundredths, for example, 0.7 is 7/10 of a percent, and 7.0 is 7%.

Type: Rate

Format

totalDigits	11
fractionDigits	10
baseValue	100.0

2.2.9 Text

2.2.9.1 Exact4AlphaNumericText

Definition: Specifies an alphanumeric string with a length of 4 characters.

Type: Text

Format

pattern	[a-zA-Z0-9]{4}
---------	----------------

2.2.9.2 Max128Text

Definition: Specifies a character string with a maximum length of 128 characters.

Type: Text

Format

minLength	1
maxLength	128

2.2.9.3 Max140Text

Definition: Specifies a character string with a maximum length of 140 characters.

Type: Text

Format

minLength	1
maxLength	140

2.2.9.4 Max15NumericText

Definition: Specifies a numeric string with a maximum length of 15 digits.

Type: Text

Format

pattern	[0-9]{1,15}
---------	-------------

2.2.9.5 Max16Text

Definition: Specifies a character string with a maximum length of 16 characters.

Type: Text

Format

minLength	1
maxLength	16

2.2.9.6 Max2048Text

Definition: Specifies a character string with a maximum length of 2048 characters.

Type: Text

Format

minLength	1
maxLength	2048

2.2.9.7 Max34Text

Definition: Specifies a character string with a maximum length of 34 characters.

Type: Text

Format

minLength	1
maxLength	34

2.2.9.8 Max350Text

Definition: Specifies a character string with a maximum length of 350 characters.

Type: Text

Format

minLength	1
maxLength	350

2.2.9.9 Max35Text

Definition: Specifies a character string with a maximum length of 35 characters.

Type: Text

Format

minLength	1
maxLength	35

2.2.9.10 Max4Text

Definition: Specifies a character string with a maximum length of 4 characters.

Type: Text

Format

minLength	1
maxLength	4

2.2.9.11 Max70Text

Definition: Specifies a character string with a maximum length of 70characters.

Type: Text

Format

minLength	1
maxLength	70

2.2.9.12 PhoneNumber

Definition: The collection of information which identifies a specific phone or FAX number as defined by telecom services.

It consists of a "+" followed by the country code (from 1 to 3 characters) then a "-" and finally, any combination of numbers, "(", ")", "+", and "-" (up to 30 characters).

Type: Text

Format

pattern \+[0-9]{1,3}-[0-9()+\-]{1,30}

2.2.10 Time

2.2.10.1 ISOTime

Definition: A particular point in the progression of time in a calendar day expressed in either UTC time format (hh:mm:ss.sssZ), local time with UTC offset format (hh:mm:ss.sss+/-hh:mm), or local time format (hh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: Time

Legal Notices

Copyright

S.W.I.F.T. SC © 2026. All rights reserved.

You may copy this publication within your organisation. Any such copy must include these legal notices.

Confidentiality

This publication may contain Swift or third-party confidential information. Do not disclose this publication outside your organisation without the prior written consent of Swift.

Disclaimer

The information in this publication may change from time to time. You must always refer to the latest available version.

Swift Standards Intellectual Property Rights (IPR) Policy - End-User License Agreement

Swift Standards are licensed subject to the terms and conditions of the *Swift Standards IPR Policy - End-User License Agreement* available at www.swift.com > About Swift > Legal > Swift Standards IPR Policy.

Translations

The English version of Swift documentation is the only official version.

Trademarks and Patents

Swift is the trade name of S.W.I.F.T. SC. The following are registered trademarks of Swift: 3SKey, Innotribe, MyStandards, Sibos, Swift, SwiftNet, the Standards Forum logo, the Swift logo, Swift GPI with logo, the Swift GPI logo, and UETR. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.