




Broadcast Routing in Computer Networks

Concepts, Techniques, and Applications

Nikita Sudarshan

0133CS231215



What Is Broadcast Communication?

The Big Picture

Broadcast communication is a one-to-all transmission model — a single sender delivers the same packet to **every node** in the network simultaneously.

Think of it like a radio station: one transmitter, many receivers.

Why It Matters

- **Network discovery** — nodes announce their presence to all peers
- **Routing updates** — routers share topology changes network-wide
- **Efficiency** — one transmission replaces many individual sends
- **Protocols** — ARP, OSPF, and DHCP all rely on broadcast



Broadcast vs. Unicast vs. Multicast

Understanding the three fundamental communication models helps clarify when and why broadcast routing is needed.

Unicast

One-to-One communication. A single sender transmits data to a single, specific receiver. Example: loading a webpage or a video call.

Broadcast

One-to-All communication. A single sender transmits data to **every node** in the network. Example: ARP requests, DHCP discovery.

Multicast

One-to-Many communication. A sender transmits data to a **selected group** of receivers. Example: video conferencing, IPTV streaming.

Feature	Unicast	Broadcast	Multicast
Recipients	One	All Nodes	Selected Group
Bandwidth usage	Low	High	Moderate
Scalability	High	Low	Medium

Broadcast Address

A broadcast address is a special IP address used to send data to all devices in a network simultaneously.


Types of Broadcast Address

Limited Broadcast

- Address: 255.255.255.255
- Used to communicate with all devices in the local network

Directed Broadcast

- Example: 192.168.1.255
- Used to send broadcast packets to a specific network



Routers usually do not forward broadcast packets to avoid broadcast storms.

What Is Broadcast Routing?

Definition

Broadcast routing is the process by which a router or network layer algorithm delivers a single packet from one source to **all destinations** in the network — intelligently and without manual replication at the source.

Simple Broadcast vs. Broadcast Routing

Simple Broadcast

Source sends **N copies**
— one per destination.
Wastes bandwidth;
doesn't scale.

Broadcast Routing

Source sends **one packet**; routers forward intelligently using algorithms.

Why Do We Need Broadcast Routing?



Network Discovery

Devices use broadcast to announce themselves and locate services — essential during **ARP resolution** and DHCP setup.



Routing Updates

Protocols like **OSPF** and **RIP** broadcast topology changes so every router maintains a consistent network map.



Data Dissemination

Efficiently pushes **identical data** (firmware updates, alerts) to all nodes without redundant source transmissions.



Scalability

As networks grow, broadcast routing algorithms **scale gracefully** — far better than N individual unicast sends.

Core Concepts: One-to-All Communication

Key Challenges



A single source packet must reach every node — but the network topology can cause packets to loop or arrive multiple times.

Redundancy

Multiple paths between nodes can deliver the **same packet twice**, wasting bandwidth and processing.

Routing Loops

Without loop prevention, packets can **circulate indefinitely**, consuming resources and crashing nodes.

Scalability

Naive flooding generates **exponential traffic** as network size grows — algorithms are essential.

Broadcast Routing Techniques

Three core algorithms address the challenges of one-to-all delivery each with its own trade-offs in complexity, efficiency, and loop prevention.



Flooding

Forward every packet to **all neighbors** — simple but generates excessive traffic.




Reverse Path Forwarding

Only forward if packet arrived on the **shortest-path link** back to source.




Spanning Tree

Build a **loop-free tree** connecting all nodes — zero duplicate packets.



Technique 1: Flooding



How It Works

When a router receives a packet, it **forwards it out every interface** except the one it arrived on. Sequence numbers prevent infinite loops.

Sequence Number Control

To prevent infinite loops, each packet carries a **source address + sequence number**. If a node has already seen a packet with that sequence number, it discards the duplicate.

✓ Advantages

- Extremely **simple** to implement
- Guarantees delivery if path exists
- No topology knowledge needed

✗ Disadvantages

- Generates **massive duplicate** traffic
- Exponential packet explosion
- Poor scalability in large networks


Technique 2: Reverse Path Forwarding (RPF)

The Core Logic

RPF uses a simple but powerful check: a router forwards a broadcast packet **only if** it arrived on the interface that is on the shortest path back to the source.

Example

Router R receives a packet from source S. R checks: "Is this the link I'd use to reach S?" If **yes** → forward to all other neighbors. If **no** → drop the packet.



RPF dramatically reduces duplicates compared to flooding while requiring only standard **unicast routing table** knowledge.

Technique 3: Spanning Tree Broadcasting

What Is a Spanning Tree?

A **spanning tree** is a subset of the network graph that connects **all N nodes** using exactly **$N - 1$ edges**, with no cycles.


$$E = N - 1$$

Where **E** = edges in tree, **N** = total nodes. Once built, the source sends one packet — each router forwards it **exactly once** along the tree edges.

✅ **Result:** Zero duplicate packets. Every node receives exactly one copy.

Why No Duplication?

A tree has **no cycles by definition** — so there's no path for a packet to loop back or arrive twice at any node.



Comparison: Flooding vs. RPF vs. Spanning Tree

Criterion	Flooding	Reverse Path Forwarding	Spanning Tree
Efficiency	Low — exponential packet copies	Medium — some duplicates remain	High — each node gets exactly one copy
Complexity	Very Low	Medium — needs routing table	High — tree construction required
Duplicate Packets	Many	Few	None
Loop Prevention	Sequence numbers needed	Built-in via path check	Guaranteed by tree structure
Topology Knowledge	None required	Unicast table only	Full topology needed

PYQs

Explain the Flooding technique in broadcast routing. Discuss its advantages and disadvantages.

Give basic difference between broadcast and multicast routing.

What do you mean by Routing? Explain Hierarchical, Broadcast and Multicast routing