

UTL FILES PACKAGE:

WITH UTL FILE PACKAGE WE CAN WRITE DATA INTO AND READ DATA FROM FILES.

MEMBERS OF UTL FILE PACKAGE:

1.FILE_TYPE:

IT IS A TYPE USED TO DECLARE FILE VARIABLE.

SYNTAX:

<FILE VARIABLE NAME> UTL_FILE.FILE_TYPE;

2.FOPEN():

IT A FUNCTION USED TO OPEN FILE.

SYNTAX:

<FILE VARIABLE NAME>: = UTL_FILE.FOPEN(DIRECTORY NAME, <FILE NAME>, MODE);

HERE, MODE ARE WRITE (W), READ (R), APPEND(A).

3.PUT_LINE:

IT IS A PROCEDURE USED TO WRITE DATA INTO FILE.

SYNTAX:

UTL_FILE.PUT_LINE (<FILE VARIABLE NAME>, <TYPE DATA>);

4.GET_LINE:

IT IS A PROCEDURE USED TO READ DATA FROM FILE.

SYNTAX:

UTL_FILE.GET_LINE (<FILE VARIABLE NAME>, <STRING VARIABLE>);

5.FCLOSE:

IT IS PROCEDURE USED TO CLOSE FILE.

SYNTAX:

UTL_FILE.FCLOSE(<FILE VARIABLE NAME>);

EX:

SQL> CONN SYSTEM/MANAGER;

CONNECTED.

SQL> GRANT CREATE ANY DIRECTORY TO SCOTT;

GRANT SUCCEEDED.

SQL> CONN SCOTT/TIGER;

CONNECTED.

SQL> CREATE DIRECTORY XYZ AS 'E:\SUDHAKAR';

DIRECTORY CREATED.

SQL> CONN SYSTEM/MANAGER;

CONNECTED.

SQL> GRANT READ, WRITE ON DIRECTORY XYZ TO SCOTT;

GRANT SUCCEEDED.

EX1: PROGRAM TO WRITE DATA INTO TEXT FILE?

SQL> DECLARE

FV UTL_FILE.FILE_TYPE;

BEGIN

FV: =UTL_FILE.FOPEN('XYZ','FILE1.TXT','W');

UTL_FILE.PUT_LINE(FV,'HI SUDHAKAR HOW ARE YOU');

UTL_FILE.FCLOSE(FV);

END;

/

EX2: PROGRAM TO READ DATA FROM TEXT FILE?

SQL>DECLARE

```
FV UTL_FILE.FILE_TYPE;  
S VARCHAR2(1000);  
BEGIN  
FV: =UTL_FILE.FOPEN('XYZ','FILE1.TXT','R');  
LOOP  
UTL_FILE.GET_LINE (FV, S);  
DBMS_OUTPUT.PUT_LINE(S);  
END LOOP;  
EXCEPTION  
WHEN NO_DATA_FOUND THEN  
UTL_FILE.FCLOSE(FV);  
END;  
/
```

OUTPUT:

HI SUDHAKAR HOW ARE YOU

EX3: PROGRAM TO WRITE EMPLOYEE DATA INTO TEXT FILE?

DECLARE

```
F1 UTL_FILE.FILE_TYPE;  
TYPE EMP_ARRAY IS TABLE OF EMP%ROWTYPE;  
E EMP_ARRAY;  
BEGIN  
F1: =UTL_FILE.FOPEN('XYZ','EMP.TXT','W');  
SELECT * BULK COLLECT INTO E FROM EMP;  
FOR I IN E. FIRST..E.LAST  
LOOP  
UTL_FILE.PUT_LINE (F1, E(I). EMPNO||','||E(I). ENAME||','||E(I).  
SAL);  
END LOOP;
```

```
UTL_FILE.FCLOSE(F1);  
END;  
/
```

EX4: PROGRAM TO READ EMPLOYEE DATA FROM TEXT FILE:

```
DECLARE  
F1 UTL_FILE.FILE_TYPE;  
S VARCHAR2(1000);  
BEGIN  
F1: =UTL_FILE.FOPEN('XYZ','EMP.TXT','R');  
LOOP  
UTL_FILE.GET_LINE (F1, S);  
DBMS_OUTPUT.PUT_LINE(S);  
END LOOP;  
EXCEPTION  
WHEN NO_DATA_FOUND THEN  
UTL_FILE.FCLOSE(F1);  
END;  
/
```

EX5: Program to write employee data into excel file:

```
DECLARE  
F1 UTL_FILE.FILE_TYPE;  
TYPE EMP_ARRAY IS TABLE OF EMP%ROWTYPE;  
E EMP_ARRAY;  
BEGIN  
F1:= UTL_FILE.FOPEN('XYZ','EMP.csv','W');  
SELECT * BULK COLLECT INTO E FROM EMP;  
FOR i IN E.FIRST..E.LAST  
LOOP
```

```

UTL_FILE.PUT_LINE(F1,E(i).EMPNO||','||E(i).ENAME||','||E(i).SAL
);
END LOOP;
UTL_FILE.FCLOSE(F1);
END;
/

```

EX6: Program to read employee data from excel file:

```

DECLARE
F1 UTL_FILE.FILE_TYPE;
S VARCHAR2(1000);
BEGIN
F1:=UTL_FILE.FOPEN('XYZ','EMP.csv','R');
LOOP
UTL_FILE.GET_LINE(F1,S);
DBMS_OUTPUT.PUT_LINE(S);
END LOOP;
EXCEPTION
WHEN NO_DATA_FOUND THEN
UTL_FILE.FCLOSE(F1);
END;
/

```

NOTE:

TO VIEW DIRECTORY RELATED TO PHYSICAL PATH THEN USE THE FOLLOWING

DATADIRECTORY IS "ALL_DIRECTORIES ".

EX:

```
SQL> DESC ALL_DIRECTORIES;
```

```
SQL> SELECT DIRECTORY_NAME, DIRECTORY_PATH FROM
ALL_DIRECTORIES;
```

DIRECTORY_NAME

XYZ

DIRECTORY_PATH

E:\SUDHAKAR

SYNTAX TO DROP DIRECTORY:

SQL> DROP DIRECTORY <DIRECTORY NAME>;

EX:

SQL> DROP DIRECTORY XYZ;