

Design and Analysis of Algorithm

Tutorial-2

Satyam Kumar

Roll no. - 34

Sec - D.

Code is,

```
void fun(int n){  
    int j=1, i=0;  
    while (i<n){  
        i = i+j;  
        j++;  
    }
```

values of i

0
1
3
6
10
15
21
⋮
up to n.

$\Rightarrow i = 0, 1, 3, 6, 10, 15, 21, \dots, n$
K terms

Let the sum of these K terms be S_K

$$\Rightarrow S_K = 1 + 3 + 6 + 10 + 15 + 21 + \dots + T_K \quad \text{--- (1)}$$

$$S_{K-1} = 1 + 3 + 6 + 10 + 15 + 21 + \dots + T_{K-1} \quad \text{--- (2)}$$

Subtracting, (2) from (1),

$$\Rightarrow T_K = S_K - S_{K-1} = 1 + 2 + 3 + 4 + 5 + 6 + \dots + K$$

We have $T_K = n$.

$$\Rightarrow 1 + 2 + 3 + 4 + 5 + 6 + \dots + K = n$$

$$\Rightarrow \frac{K(K+1)}{2} = n$$

$$\Rightarrow K^2 + K - 2n = 0$$

$$\Rightarrow K = \frac{-1 \pm \sqrt{1 + 8n}}{2}, \text{ taking only positive value we}$$

get total ^{no.} times the loop runs for $i = K+1 = \frac{-1 + \sqrt{1 + 8n}}{2} + 1$

$$= 1 - \frac{1}{2} + \frac{\sqrt{8n+1}}{2}$$

$$= \frac{1 + \sqrt{8n+1}}{2}$$

⇒ Time complexity:-

$$T(n) = O\left(\frac{1 + \sqrt{8n+1}}{2}\right) = O(\sqrt{n}).$$

2.

pseudo Code:-

```

int fib(int n)
{
    if (n <= 1)      ——— O(1)
        return n;
    return fib(n-1) + fib(n-2); ——— T(n-1) + T(n-2)
}

```

⇒ • Time Complexity:-

$$T(n) = T(n-1) + T(n-2) + 1$$

when $n=0$ & $n=1$

$$\text{i.e., } T(0) = T(1) = 1.$$

$$\text{Here, } T(n-2) \approx T(n-1)$$

$$\Rightarrow T(n) = 2 * T(n-1) + 1 = 2T(n-1) + 1 \quad \text{--- (1)}$$

put $n = n-1$ in eqⁿ (1),

$$\Rightarrow T(n-1) = 2T(n-2) + 1$$

put in (1),

$$T(n) = 2 [2T(n-2) + 1] + 1 = 4T(n-2) + 2 + 1 \quad \text{--- (2)}$$

put $n = n-2$ in eqⁿ (1),

$$\Rightarrow T(n-2) = 2T(n-3) + 1$$

put in (2),

$$T(n) = 4 [2T(n-3) + 1] + 2 + 1 \quad \text{--- (3)}$$

$$T(n) = 8T(n-3) + 4 + 2 + 1$$

⇒ Generalised form:-

$$T(n) = \underbrace{2^k T(n-k) + 2^{k-1} + 2^{k-2} + \dots + 1}_{k+1 \text{ terms}}$$

put $n-k=0$

$$\begin{aligned} \Rightarrow T(n) &= 2^n T(0) + 2^{n-1} + 2^{n-2} + \dots + 1 \\ &= 2^n + 2^{n-1} + 2^{n-2} + \dots + 1 \\ &= \underbrace{1 + 2 + 4 + 8 + 16 + \dots + 2^n}_{k+1 \text{ terms.}} \end{aligned}$$

$$a=1, a_{k+1} = 2^n, r=2$$

$\Rightarrow (k+1)^{\text{th}}$ term: -

$$a_{k+1} = a r^{(k+1-1)}$$

$$2^n = 2^k$$

On comparing,
 $n=k$

$$\Rightarrow T.C. = O(k+1) = O(n+1) = O(n).$$

• Space Complexity: Here n is the no. of entries in a stack

and for each function call one.

So space complexity for each case (call) is 1, i.e., $O(1)$

& for n no. of cases, $\propto n$

\Rightarrow i.e., $O(n)$.

3.
for (int $i=0$; $i<n$; $i++$) {
 for (int $j=0$; $j<n$; $j=j+2$)
 {
 $O(1)$ // statements
 }
}

$$\Rightarrow O(n \log n)$$

```

for (int i=0; i<n; i++) {
  for (int j=0; j<n; j++) {
    for (int k=0; k<n; k++) {
      // O(1) - Statements
    }
  }
}

```

∴ $O(n^3)$.

```

for (int i=0; i<n; i++) {
  for (int i=0; i<n; i=i/2) {
    for (int j=0; j<n; j=j*2)
      {
        O(1) statements
      }
  }
}

```

$O(\log(\log n))$.

4.

$$T(n) = T(n/4) + T(n/2) + cn^2.$$

On removing $T(n/2)$ as smaller term,

$$T(n) = T(n/2) + cn^2.$$

Applying Master's Theorem,

$$a=0, b=2, K=2, P=0$$

$$\log_b a = \log_2 0 = 0.$$

$$0 < 2, \text{ i.e., } \log_b a < K, \text{ \& } P \geq 0.$$

$$\Rightarrow T(n) = \Theta(n^K \log^P n)$$

$$\Rightarrow T(n) = \Theta(n^2 \log^0 n)$$

$$= \Theta(n^2).$$

Ans 5

time complexity of the function $\text{fun}()$ is $O(n \log n)$.

⇒ for $i=1$, inner loop executed n times.

for $i=2$, inner loop executed $n/2$ times

for $i=3$, inner loop executed $n/3$ times

⋮

for $i=n$, inner loop executed $n/n=1$ time.

$$\Rightarrow n + \frac{n}{2} + \frac{n}{3} + \dots + \frac{n}{n}$$

$$n \left(1 + \frac{1}{2} + \frac{1}{3} + \dots + \frac{1}{n} \right)$$

⇒ particular term for time complexity is $(\log n)$.

So for, total times, the loop executed,

$$T(n) = O(n \log n).$$

Ans 6

for (int $i=2$; $i < n$; $i = \text{pow}(i, k)$) {

// $O(1)$ - Expressions.

}

i takes the values like, $2, 2^k, k^2, 2^{k^3} \dots 2^{k \log_k (\log n)}$,

last term must be less than or equal to n .

⇒

$$T(n) = O(\log_k (\log n)).$$

Ans 8

a)

$$100 < \log n < \log(n!) < \log(\log n) < n < n! < n \log n < \log^2 n < 2^n \\ < 4^n < 2^{(2^n)} < n^2.$$

b)

$$1 < \sqrt{\log n} < \log n < \log(n!) < \log(\log n) < \log(2n) < 2 \log(n) \\ < \log(n!) < n \log(n) < n < 2n < 4n < n! < 2^{6n}$$

c)

$$96 < \log_0(n) < \log_2(n) < \log(n!) < n! < n \log_6(n) < n \log_2(n) < 5n \\ < 8n^2 < 8^{2n} < 7n^3.$$

=