

ONNX Pre-processing WG

Monthly meeting - Jan 11, 2023

Agenda


- Status
- Resize - flip invariant
- Open floor

Status

- ResNet-50 <https://github.com/onnx/tutorials/pull/266>
 - Waiting for ONNX Runtime support for ONNX opset 18

Resize - flip-invariant properties


- ROI placement:
 - `data=[100, 200], scale=1.3`
 - Scaled data should be 2.6 long, but the actual output size is truncated to 2
 - Where do we sample the 2 locations from?
- "half_pixel" (current implementation)
 - `x_ori = (x + 0.5) / scale_factor - 0.5`
 - Biased towards the beginning of the input: `[100., 165.38]`



Resize - flip-invariant properties

"half_pixel"

```
data = (np.random.rand(4,4,3) * 255).astype('uint8')  
scales = np.array([1.0, 0.875, 1], dtype=np.float32)
```




```
flipped_then_resized = \  
    resize(data[:, ::-1, :], ...)
```




!=

```
resized_then_flipped = \  
    resize(data, ...)[ :, ::-1, :]
```



Resize - flip-invariant properties


- "half_pixel_symmetric" (proposal)
 - `adjustment = int(output_width) / output_width`
`center = input_width / 2`
`roi_start = -center * adjustment + center`
`x_ori = roi_start + (x + 0.5) / scale_factor - 0.5`
 - **Centered:** [111.54 188.46]




Resize - flip-invariant properties

"half_pixel_symmetric"

```
data = (np.random.rand(4,4,3) * 255).astype('uint8')  
scales = np.array([1.0, 0.875, 1], dtype=np.float32)
```



```
flipped_then_resized = \  
    resize(data[:, ::-1, :], ...)
```



=

```
resized_then_flipped = \  
    resize(data, ...)[ :, ::-1, :]
```



Open floor