Step 1 - Camera Calibration

In this step we will calibrate our camera. We capture a few photos of a known shape and find out how distorted the photos are.

In the [`camera_calibration`](camera_calibration) folder, run these commands:

Now edit [`camera_calibration/calibrate.py`](camera_calibration/calibrate.py), and change the `nx` and `ny` values to the number of inside corners in your image. For example, if your pattern is 9x6 squares, you should use `nx = 8` and `ny = 5`.

```
# Arrays to store object points and image points from all the images.
objpoints = [] # 3d points in real world space
imgpoints = [] # 2d points in image plane.

# Make a list of calibration images
images = glob.glob('calibration_wide/GO*.jpg')

# Step through the list and search for chessboard corners
for idx, fname in enumerate(images):
    img = cv2.imread(fname)
    gray = cv2.cvtColor(img, cv2.COLOR_BGR2GRAY)

    # Find the chessboard corners
    nx = 8 # the number of inside corners in x
    ny = 5 # the number of inside corners in y
    ret, corners = cv2.findChessboardCorners(gray, (nx, ny), None)

    # If found, add object points, image points
    if ret == True:
        objpoints.append(objp)
        imgpoints.append(corners)

        # Draw and display the corners
        cv2.drawChessboardCorners(img, (nx, ny), corners, ret)
        write_name = 'corners_found'+str(idx)+'.jpg'
        cv2.imwrite(write_name, img)
        cv2.imshow('img', img)
        cv2.waitKey(500)

cv2.destroyAllWindows()
```

Now run the calibration script:

Now run [`camera_calibration/undistort.py`](camera_calibration/undistort.py):

```
import cv2
import glob
import pickle
import numpy as np

# Read in the saved objpoints and imgpoints
dist_pickle = pickle.load( open( "wide_dist_pickle.p", "rb" ) )
objpoints = dist_pickle["objpoints"]
imgpoints = dist_pickle["imgpoints"]

# Read in an image
img = cv2.imread('test_image.jpg')
nx = 8 # the number of inside corners in x
ny = 5 # the number of inside corners in y

# Test undistortion on an image
img_size = (img.shape[1], img.shape[0])
ret, mtx, dist, rvecs, tvecs = cv2.calibrateCamera(objpoints, imgpoints, img_size,None,None)

dst = cv2.undistort(img, mtx, dist, None, mtx)
cv2.imwrite('test_undist.jpg',dst)

# Save the camera calibration result for later use (we won't worry about rvecs / tvecs)
dist_pickle = {}
dist_pickle["mtx"] = mtx
dist_pickle["dist"] = dist
pickle.dump( dist_pickle, open( "wide_dist_pickle.p", "wb" ) )

# Visualize undistortion
f, (ax1, ax2) = plt.subplots(1, 2, figsize=(20,10))
ax1.imshow(img)
ax1.set_title('Original Image', fontsize=30)
ax2.imshow(dst)
ax2.set_title('Undistorted Image', fontsize=30)
```