

Relational Database Schema

The Chen ER diagram above translates directly into the following relational schema, showing every table with its columns, data types, primary keys (PK) and foreign keys (FK), as actually implemented in FixHubDb.

Coupons	
CouponId	int, PK
Code	nvarchar(20), UQ
DiscountPercent	decimal(5,2)
ExpiryDate	date
UsageLimit	int
UsedCount	int
IsActive	bit

SuperAdmins	
SuperAdminId	int, PK
Username	nvarchar(50), UQ
PasswordHash	nvarchar(255)
CreatedAt	datetime

Payments	
PaymentId	int, PK
BookingId	int, FK
Amount	decimal(10,2)
CommissionAmount	decimal(10,2)
PaymentStatus	nvarchar(20)
PaymentMethod	nvarchar(20)
CreatedAt	datetime

Complaints	
ComplaintId	int, PK
BookingId	int, FK
Description	nvarchar(max)
Status	nvarchar(20)
ResolutionNotes	nvarchar(max)
ResolvedBySuperAdminId	int
ResolvedAt	datetime
CreatedAt	datetime

Bookings	
BookingId	int, PK
CustomerId	int, FK
AdminId	int, FK
ServiceName	nvarchar(150)
ScheduledDate	datetime
Address	nvarchar(500)
Status	nvarchar(20), CHECK
CreatedAt	datetime

Customers	
CustomerId	int, PK
Name	nvarchar(150)
Email	nvarchar(255), UQ
Phone	nvarchar(20)
Address	nvarchar(500)
PasswordHash	nvarchar(255)
CreatedAt	datetime

Reviews	
ReviewId	int, PK
BookingId	int, FK
CustomerId	int, FK
AdminId	int, FK
Rating	int, CHECK 1-5
Comment	nvarchar(500)
CreatedAt	datetime

Admins	
AdminId	int, PK
Name	nvarchar(150)
Email	nvarchar(255), UQ
Phone	nvarchar(20)
CategoryId	int, FK
Price	decimal(10,2)
Bio	nvarchar(max)
PasswordHash	nvarchar(255)
IsApproved	bit
IsSuspended	bit
IsAvailable	bit
Rating	decimal(3,2)
CreatedAt	datetime

ServiceCategories	
CategoryId	int, PK
CategoryName	nvarchar(100), UQ

Figure 2: FixHub Relational Database Schema