



GE23131-Programming Using C-2024

Status	Finished
Started	Monday, 13 January 2025, 8:32 PM
Completed	Monday, 13 January 2025, 8:51 PM
Duration	18 mins 59 secs

Question 1

Correct

Flag question

Given an array of numbers, find the index of the smallest array element (the pivot), for which the sums of all elements to the left and to the right are equal. The array may not be reordered.

Example

`arr=[1,2,3,4,6]`

- the sum of the first three elements, $1+2+3=6$.
The value of the last element is 6.
- Using zero based indexing, `arr[3]=4` is the pivot



between the two subarrays.

- The index of the pivot is 3.

Function Description

Complete the function `balancedSum` in the editor below.

`balancedSum` has the following parameter(s):

`int arr[n]`: an array of integers

Returns:

`int`: an integer representing the index of the pivot

Constraints

- $3 \leq n \leq 10^5$
- $1 \leq arr[i] \leq 2 \times 10^4$, where $0 \leq i < n$
- It is guaranteed that a solution always exists.

Input Format for Custom Testing

Input from stdin will be processed as follows and passed to the function.

The first Line contains an integer n , the size of the array `arr`.

Each of the next n Lines contains an integer, `arr[i]`, where $0 \leq i < n$.

Sample Case 0

Sample Input 0

STDIN Function Parameters

4 \rightarrow `arr[]` size $n = 4$

1 \rightarrow `arr = [1, 2, 3, 3]`

2

3

3

Sample Output 0

2

Explanation 0

- The sum of the first two elements, $1+2=3$. The value of the last element is 3.
- Using zero based indexing, `arr[2]=3` is the pivot between the two subarrays.
- The index of the pivot is 2.

Sample Case 1**Sample Input 1****STDIN Function Parameters**

3 → arr[] size n = 3

1 → arr = [1, 2, 1]

2

1

Sample Output 1

1

Explanation 1

- The first and Last elements are equal to 1.
- Using zero based indexing, arr[1]=2 is the pivot between the two subarrays.
- The index of the pivot is 1.

Answer: (penalty regime: 0 %)

Reset answer

1	/*
2	* Complete the 'balancedSum'
3	*
4	* The function is expected t

Answer: (penalty regime: 0 %)

Reset answer

```

1  /*
2  * Complete the 'balancedSum'
3  *
4  * The function is expected to
5  * The function accepts INTEGER
6  */
7
8  int balancedSum(int arr_count
9  {
10     int totalsum = 0;
11     for (int i=0;i<arr_count;
12         totalsum += arr[i];
13     }
14     int leftsum = 0;
15     for(int i =0;i<arr_count;
16         int rightsum = totalsum - leftsum;
17         if(leftsum==rightsum)
18             return i;
19     }
20     leftsum +=arr[i];
21 }
22 return 1;
23 }
24

```

	Test
✓	int arr[] = {1,2,3,3}; printf("%d", balancedSum(4, arr

Passed all tests! ✓

Question 2

Correct

 Flag question

Calculate the sum of an array of integers.

Example

`numbers = [3, 13, 4, 11, 9]`

The sum is $3 + 13 + 4 + 11 + 9 = 40$.

Function Description

Complete the function `arraySum` in the editor below.

`arraySum` has the following parameter(s):

`int numbers[n]`: an array of integers

Returns

`int`: integer sum of the numbers array

Constraints

$$1 \leq n \leq 10^4$$

$$1 \leq \text{numbers}[i] \leq 10^4$$

Input Format for Custom Testing

Input from stdin will be processed as follows and passed to the function.

The first line contains an integer n , the size of the array numbers.

Each of the next n lines contains an integer $\text{numbers}[i]$ where $0 \leq i < n$.

Sample Case 0

Sample Input 0

STDIN	Function
-------	----------

-----	-----
-------	-------

5	→ numbers[] size n = 5
---	------------------------

1	→ numbers = [1, 2, 3, 4, 5]
---	-----------------------------

2	
---	--

3	
---	--

4	
---	--

5	
---	--

Sample Output 0

15

Explanation 0

$$1 + 2 + 3 + 4 + 5 = 15.$$

Sample Case 1

Sample Input 1

STDIN	Function
-------	----------

-----	-----
-------	-------

2	→ numbers[] size n = 2
---	------------------------

12	→ numbers = [12, 12]
----	----------------------

12

Sample Output 1

24

Explanation 1

$$12 + 12 = 24.$$

Answer: (penalty regime: 0 %)

Reset answer


```
1  /*
2   * Complete the 'arraySum' fu
3   *
4   * The function is expected t
5   * The function accepts INTEG
6   */
7
8  int arraySum(int numbers_coun
9  {
10     int sum =0;
11     for(int i =0;i<numbers_cou
12         sum = sum+numbers[i];
13     }
14     return sum;
15 }
16
```

Test

```
int arr[] = {1,2,3,4,5};
printf("%d", arraySum(5, arr))
```

Passed all tests! ✓

Question 3

Correct

🚩 [Flag question](#)

Given an array of n integers, rearrange them so that the sum of the absolute differences of all adjacent elements is minimized. Then, compute the sum of those absolute differences. Example $n = 5$ $arr = [1, 3, 3, 2, 4]$ If the list is rearranged as $arr' = [1, 2, 3, 3, 4]$, the absolute differences are $|1 - 2| = 1$, $|2 - 3| = 1$, $|3 - 3| = 0$, $|3 - 4| = 1$. The sum of those differences is $1 + 1 + 0 + 1 = 3$.

Function Description Complete the function `minDiff` in the editor below. `minDiff` has the following parameter:

- `arr`: an integer array

Returns: `int`: the sum of the absolute differences of adjacent elements

Constraints $2 \leq n \leq 105$ $0 \leq arr[i] \leq 109$, where $0 \leq i < n$

Input Format For Custom Testing The first line of input contains an integer, n , the size of `arr`. Each of the following n lines contains an integer that describes `arr[i]` (where $0 \leq i < n$).

Sample Case 0

Sample Input For Custom Testing STDIN Function ----- 5
 $\rightarrow arr[]$ size $n = 5$ 5 $\rightarrow arr[] = [5, 1, 3, 7, 3]$ 1 3 7 3

Sample Output 6

Explanation $n = 5$ $arr = [5, 1, 3, 7, 3]$ If `arr` is rearranged as $arr' = [1, 3, 3, 5, 7]$, the differences are minimized. The final answer is $|1 - 3| + |3 - 3| + |3 - 5| + |5 - 7| = 6$.

Sample Case 1

Sample Input For Custom Testing STDIN Function ----- 2
 $\rightarrow arr[]$ size $n = 2$ 3 $\rightarrow arr[] = [3, 2]$ 2

Sample Output 1

Explanation $n = 2$ $arr = [3, 2]$ There is no need to rearrange because there are only two elements. The final answer is $|3 - 2| = 1$.

Answer: (penalty regime: 0 %)

Reset answer

```
1  /*
2  * Complete the 'minDiff' fun
3  *
```

Reset answer

```

1  /*
2   * Complete the 'minDiff' fun
3   *
4   * The function is expected t
5   * The function accepts INTEG
6   */
7  #include<stdio.h>
8  int compare(const void *a, con
9      return (*(int*)a) - (*(in
10 }
11 int minDiff(int arr_count, i
12 {
13     qsort(arr, arr_count, size
14     int totaldiff=0;
15     for(int i =1; i<arr_count
16         totaldiff += abs(arr
17     }
18     return totaldiff;
19 }
20

```

	Test	
✓	int arr[] = {5, 1, 3, 7, 3}; printf("%d", minDiff(5, arr))	6

Passed all tests! ✓

Finish review