

Homework 1 Solution

Aadarsha Gopala Reddy

September 8, 2022

Contents

1. Load Packages	1
2. Import Data	1
3. Filter Data	2
4. Create a New Variable	2
5. Transform the Dataset	3

1. Load Packages

In a chunk of code, load the tidyverse package and any other packages you will use in this document. `install.packages()` installs a package, if it exists. `library()` loads the package.

```
library("tidyverse")

## -- Attaching packages ----- tidyverse 1.3.2 --
## v ggplot2 3.3.6      v purrr  0.3.4
## v tibble  3.1.8      v dplyr  1.0.9
## v tidyr   1.2.0      v stringr 1.4.1
## v readr   2.1.2      v forcats 0.5.2
## -- Conflicts ----- tidyverse_conflicts() --
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()    masks stats::lag()
```

2. Import Data

Import *protest_data.csv* as an object in R. Print the first few rows of the dataset using the `head()` function.

```
protest_data <- read_csv("protest_data.csv")

## Rows: 21282 Columns: 11
## -- Column specification -----
## Delimiter: ","
## chr (7): event_date, event_type, sub_event_type, admin1, source, notes, loca...
## dbl (4): year, fatalities, latitude, longitude
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
```

```
head(protest_data)
```

```
## # A tibble: 6 x 11
##   event_date   year event~1 sub_e~2 admin1 source notes fatal~3 locat~4 latit~5
##   <chr>       <dbl> <chr>   <chr>   <chr> <chr> <chr>   <dbl> <chr>   <dbl>
## 1 12 August 2~ 2022 Protes~ Peacef~ Calif~ KTVU ~ On 1~      0 Martin~ 38.0
## 2 12 August 2~ 2022 Protes~ Peacef~ Texas News ~ On 1~      0 Midland 32.0
## 3 12 August 2~ 2022 Protes~ Peacef~ Calif~ NewsC~ On 1~      0 Palm S~ 33.8
## 4 12 August 2~ 2022 Protes~ Peacef~ Georg~ 11 Al~ On 1~      0 Atlanta 33.8
## 5 12 August 2~ 2022 Protes~ Peacef~ New Y~ 13WHA~ On 1~      0 Batavia 43.0
## 6 12 August 2~ 2022 Protes~ Peacef~ Delaw~ Fox29 On 1~      0 Wilmin~ 39.7
## # ... with 1 more variable: longitude <dbl>, and abbreviated variable names
## #   1: event_type, 2: sub_event_type, 3: fatalities, 4: location, 5: latitude
```

3. Filter Data

Subset the protest dataset to only the protests that occurred in the year 2022. Make sure to save your changes to the dataset.

```
protest_data <- filter(protest_data, year == 2022)
head(protest_data)
```

```
## # A tibble: 6 x 11
##   event_date   year event~1 sub_e~2 admin1 source notes fatal~3 locat~4 latit~5
##   <chr>       <dbl> <chr>   <chr>   <chr> <chr> <chr>   <dbl> <chr>   <dbl>
## 1 12 August 2~ 2022 Protes~ Peacef~ Calif~ KTVU ~ On 1~      0 Martin~ 38.0
## 2 12 August 2~ 2022 Protes~ Peacef~ Texas News ~ On 1~      0 Midland 32.0
## 3 12 August 2~ 2022 Protes~ Peacef~ Calif~ NewsC~ On 1~      0 Palm S~ 33.8
## 4 12 August 2~ 2022 Protes~ Peacef~ Georg~ 11 Al~ On 1~      0 Atlanta 33.8
## 5 12 August 2~ 2022 Protes~ Peacef~ New Y~ 13WHA~ On 1~      0 Batavia 43.0
## 6 12 August 2~ 2022 Protes~ Peacef~ Delaw~ Fox29 On 1~      0 Wilmin~ 39.7
## # ... with 1 more variable: longitude <dbl>, and abbreviated variable names
## #   1: event_type, 2: sub_event_type, 3: fatalities, 4: location, 5: latitude
```

```
protest_data %>% tally()
```

```
## # A tibble: 1 x 1
##       n
##   <int>
## 1  8305
```

How many protests occurred in the year 2022? **8305 protests.**

4. Create a New Variable

Create a new variable in the protest dataset called `cont_us`. This binary variable should measure whether the protest occurred in the contiguous United States. - Protests that occurred in Hawaii or Alaska should have a value of 0. - Protests that occurred in the other 48 states and Washington D.C. should have a value of 1.

```
protest_data$cont_us <- if_else(protest_data$admin1 %in% c("Hawaii", "Alaska"), 0, 1)
select(protest_data, 'admin1', 'cont_us')
```

```
## # A tibble: 8,305 x 2
##   admin1      cont_us
##   <chr>       <dbl>
```

```
## 1 California      1
## 2 Texas           1
## 3 California      1
## 4 Georgia         1
## 5 New York        1
## 6 Delaware        1
## 7 California      1
## 8 California      1
## 9 Michigan        1
## 10 Ohio           1
## # ... with 8,295 more rows
```

```
filter(protest_data, cont_us == 0) %>% tally()
```

```
## # A tibble: 1 x 1
##       n
##   <int>
## 1    66
```

How many protests occurred outside of the contiguous United States? **66 protests occurred outside the contiguous USA.**

5. Transform the Dataset

Transform the protest-level dataset into a state-level dataset and save it as a new object in R. In the new dataset, each observation should be a state or territory of the United States. It should contain the following variables:

- state: the name of the state.
- fatalities: the total number of fatalities at protests in that state in 2022.
- count: a count of the number of protests in that state in 2022.

Print the first few rows of the new dataset using the `head()` function.