

Debugging in Docker

Current Debugging Workflow

Current Debugging Workflow

1. Write code

Current Debugging Workflow

1. Write code
2. Compile

Current Debugging Workflow

1. Write code
2. Compile
3. Run in GDB/Valgrind

Current Debugging Workflow

1. Write code
2. Compile
3. Run in GDB/Valgrind

Issues?

Current Debugging Workflow

1. Write code
2. Compile
3. Run in GDB/Valgrind

Issues?

- Different version of g++/valgrind from CAEN

Current Debugging Workflow

1. Write code
2. Compile
3. Run in GDB/Valgrind

Issues?

- Different version of g++/valgrind from CAEN
- Can't use Valgrind/GDB if you're on mac/windows

Alternatives?

Alternatives?

- Go to a CAEN computer

Alternatives?

- Go to a CAEN computer
- SSH into CAEN

Alternatives?

- Go to a CAEN computer
- SSH into CAEN
- Virtual Machine

Alternatives?

- Go to a CAEN computer
- SSH into CAEN
- Virtual Machine

- **Docker!**

What is Docker?

What is Docker?

- A form of virtualisation

What is Docker?

- A form of virtualisation
- Containerise everything!

But That's Just a VM?

But That's Just a VM?

- It doesn't create the entire OS

But That's Just a VM?

- It doesn't create the entire OS
- All images used shared resources

Which is Better?

Docker

- Is much quicker to start
- *Hella fast*
- Open source :D
- Almost **0** overhead

VM's

- Full isolation
- You know how it works

Getting Started

Getting Started

- [Download Docker](#) (if you haven't already)

Getting Started

- [Download Docker](#) (if you haven't already)
- Start the Docker client

Getting Started

- [Download Docker](#) (if you haven't already)
- Start the Docker client
- `docker pull alpine`

Getting Started

- [Download Docker](#) (if you haven't already)
- Start the Docker client
- `docker pull alpine`
- `docker run alpine`

Getting Started

- [Download Docker](#) (if you haven't already)
- Start the Docker client
- `docker pull alpine`
- `docker run alpine`
- Why didn't that do anything?

Getting Started

- [Download Docker](#) (if you haven't already)
- Start the Docker client
- `docker pull alpine`
- `docker run alpine`
- Why didn't that do anything?
- You didn't give it any commands
- `docker run -it alpine` to open an interactive shell

What We Need

What We Need

- A linux image ([Ubuntu 17.10](#))

What We Need

- A linux image ([Ubuntu 17.10](#))
- Valgrind, GDB, etc.

Setting up an Image

Setting up an Image

- `docker pull ubuntu:artful`

Setting up an Image

- `docker pull ubuntu:artful`
- `docker run -it alpine`

Setting up an Image

- `docker pull ubuntu:artful`
- `docker run -it alpine`
- `apt-get update`

Setting up an Image

- `docker pull ubuntu:artful`
- `docker run -it alpine`
- `apt-get update`
- `apt-get install g++ valgrind make`

Building the Docker Way

- Use a Dockerfile
 - This contains all the commands a user would call on the command line to assemble an image
 - Makes it easy to share images, since you only need to share a simple text file

Building the Docker Way

- Use a Dockerfile
 - This contains all the commands a user would call on the command line to assemble an image
 - Makes it easy to share images, since you only need to share a simple text file

```
# Build a simple ubuntu image with vim installed
FROM ubuntu:artful
RUN apt-get update
RUN apt-get install -y vim
CMD ["bash"]
```

Building the Docker Way

- Use a Dockerfile
 - This contains all the commands a user would call on the command line to assemble an image
 - Makes it easy to share images, since you only need to share a simple text file

```
# Build a simple ubuntu image with vim installed
FROM ubuntu:artful
RUN apt-get update
RUN apt-get install -y vim
CMD ["bash"]
```

```
$ docker build .
```

Accessing Your Files

Accessing Your Files

- We can either:

Accessing Your Files

- We can either:
 - Copy over files
 - `ADD . /DOCKER/PATH`

Accessing Your Files

- We can either:
 - Copy over files
 - `ADD . /DOCKER/PATH`
 - Mount directory
 - `docker run -it -v "$(pwd):/DOCKER/PATH`

Time to Build a Debugging Container

The Dockerfile

The Dockerfile

Objective

- Build an image running ubuntu that has all the tools we need

The Dockerfile

The Dockerfile

Get the linux distro we want

The Dockerfile

Get the linux distro we want

```
# Using Ubuntu 17:01 (artful)  
FROM ubuntu:artful
```


The Dockerfile

The Dockerfile

Install everything we need

The Dockerfile

Install everything we need

```
RUN apt-get update
RUN apt-get install -y g++
RUN apt-get install -y gcc
RUN apt-get install -y make
RUN apt-get install -y valgrind
RUN apt-get install -y vim
```

The Dockerfile

The Dockerfile

Get it ready to be run

The Dockerfile

Get it ready to be run

```
# Set starting directory to /prog  
RUN mkdir /prog  
WORKDIR /prog
```

The Dockerfile

Get it ready to be run

```
# Set starting directory to /prog  
RUN mkdir /prog  
WORKDIR /prog
```

```
# Run bash  
CMD ["bash"]
```

The Dockerfile

The Dockerfile

```
# Using Ubuntu 17.10
FROM ubuntu:artful

RUN apt-get update
RUN apt-get install -y g++
RUN apt-get install -y gcc
RUN apt-get install -y make
RUN apt-get install -y valgrind
RUN apt-get install -y vim

# Set starting directory to home
RUN mkdir /prog
WORKDIR /prog

CMD ["bash"]
```

Build It

Build It

- If you're in the same directory as the Dockerfile

```
docker build -t docker-debugger .
```

Build It

- If you're in the same directory as the Dockerfile

```
docker build -t docker-debugger .
```

- If not

```
docker build -f /PATH/TO/Dockerfile -t docker-debugger
```

Running It

- Run the most recent 'docker-debugger' image

Running It

- Run the most recent 'docker-debugger' image

```
# Run it
# Mount the current directory to /prog
docker run -it --rm --privileged \
    -v "$(pwd):/prog" docker-debugger:latest
```

Running It

What are all those other flags??

Running It

What are all those other flags??

- `-it`: open an interactive shell

Running It

What are all those other flags??

- `-it`: open an interactive shell
- `--rm`: remove the container on exit

Running It

What are all those other flags??

- `-it`: open an interactive shell
- `--rm`: remove the container on exit
- `--privileged`: give it permissions required for gdb/valgrind

Running It

What are all those other flags??

- `-it`: open an interactive shell
- `--rm`: remove the container on exit
- `--privileged`: give it permissions required for gdb/valgrind
- `-v "LOCAL_PATH:CONTAINER_PATH"`: Mount `LOCAL_PATH` on your container at `CONTAINER_PATH`

Is That It?

Is That It?

- This is a really simple use case

Is That It?

- This is a really simple use case
- Deploy a website anywhere

Is That It?

- This is a really simple use case
- Deploy a website anywhere
 - Have loads of images + a load balancer!

Is That It?

Is That It?

Container Orchestration

Is That It?

Container Orchestration

- Managing loads and loads of running containers

Is That It?

Container Orchestration

- Managing loads and loads of running containers
- Scaling as appropriate by adding or removing containers

Is That It?

Container Orchestration

- Managing loads and loads of running containers
- Scaling as appropriate by adding or removing containers
- Distributing load between the containers

Is That It?

Container Orchestration

- Managing loads and loads of running containers
- Scaling as appropriate by adding or removing containers
- Distributing load between the containers
- Launching new containers on different machines if something fails