EXP7

19 August 2026

1 Fashion MNIST Image Classification using KNN

[ ]:
```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.neighbors import KNeighborsClassifier
from sklearn.metrics import classification_report, accuracy_score,␣
 ↪confusion_matrix
import time

# Load datasets
train_df = pd.read_csv('/content/drive/MyDrive/PCCSL508/EXP7/fashion-
mnist_train.csv')
test_df = pd.read_csv('/content/drive/MyDrive/PCCSL508/EXP7/fashion-mnist_test.
 ↪csv')

print(f"Training data shape: {train_df.shape}")
print(f"Testing data shape: {test_df.shape}")
display(train_df.head())
```

```
Training data shape: (60000, 785)
Testing data shape: (10000, 785)
```

	label	pixel1	pixel2	pixel3	pixel4	pixel5	pixel6	pixel7	pixel8	\
0	2	0	0	0	0	0	0	0	0	
1	9	0	0	0	0	0	0	0	0	
2	6	0	0	0	0	0	0	0	5	
3	0	0	0	0	1	2	0	0	0	
4	3	0	0	0	0	0	0	0	0	

	pixel9	…	pixel775	pixel776	pixel777	pixel778	pixel779	pixel780	\
0	0	…	0	0	0	0	0	0	
1	0	…	0	0	0	0	0	0	
2	0	…	0	0	0	30	43	0	
3	0	…	3	0	0	0	0	1	
4	0	…	0	0	0	0	0	0	

```
   pixel781  pixel782  pixel783  pixel784
0         0         0         0         0
1         0         0         0         0
2         0         0         0         0
3         0         0         0         0
4         0         0         0         0

[5 rows x 785 columns]
```

[ ]:
```python
# Preprocessing
# Separate features (pixels) and labels
X_train = train_df.iloc[:, 1:].values / 255.0
y_train = train_df.iloc[:, 0].values

X_test = test_df.iloc[:, 1:].values / 255.0
y_test = test_df.iloc[:, 0].values

# Define class names for Fashion MNIST
class_names = ['T-shirt/top', 'Trouser', 'Pullover', 'Dress', 'Coat',
               'Sandal', 'Shirt', 'Sneaker', 'Bag', 'Ankle boot']
```

1.0.1 Experimenting with different values of K

We will evaluate $K = [1, 3, 5, 7, 9, 11, 13, 15, 17, 19, 21, 100]$ to analyze the trade-off between accuracy and computational cost. Note: KNN can be slow on large datasets like this.

[ ]:
```python
k_values = [1, 3, 5, 7, 9, 11, 13, 15, 17, 19, 21, 100]
results = []

for k in k_values:
    start_time = time.time()
    knn = KNeighborsClassifier(n_neighbors=k)
    knn.fit(X_train, y_train)
    y_pred = knn.predict(X_test)
    end_time = time.time()

    acc = accuracy_score(y_test, y_pred)
    duration = end_time - start_time
    results.append({'K': k, 'Accuracy': acc, 'Time (s)': duration})
    print(f"K={k} | Accuracy: {acc:.4f} | Time: {duration:.2f}s")

results_df = pd.DataFrame(results)
display(results_df)
```

```
K=1 | Accuracy: 0.8567 | Time: 41.28s
K=3 | Accuracy: 0.8584 | Time: 36.44s
K=5 | Accuracy: 0.8589 | Time: 35.94s
K=7 | Accuracy: 0.8558 | Time: 36.17s
K=9 | Accuracy: 0.8561 | Time: 35.81s
```

```
K=11 | Accuracy: 0.8556 | Time: 37.73s
K=13 | Accuracy: 0.8543 | Time: 42.11s
K=15 | Accuracy: 0.8514 | Time: 37.96s
K=17 | Accuracy: 0.8505 | Time: 35.78s
K=19 | Accuracy: 0.8488 | Time: 38.04s
K=21 | Accuracy: 0.8462 | Time: 35.99s
K=100 | Accuracy: 0.8198 | Time: 38.26s
```


	K	Accuracy	Time (s)
0	1	0.8567	41.284203
1	3	0.8584	36.437742
2	5	0.8589	35.936902
3	7	0.8558	36.167361
4	9	0.8561	35.812597
5	11	0.8556	37.729565
6	13	0.8543	42.112188
7	15	0.8514	37.960819
8	17	0.8505	35.779838
9	19	0.8488	38.037757
10	21	0.8462	35.986986
11	100	0.8198	38.262727

[ ]:
```python
# Visualization of the impact of K
plt.figure(figsize=(10, 5))

plt.subplot(1, 2, 1)
plt.plot(results_df['K'], results_df['Accuracy'], marker='o', color='b')
plt.title('Accuracy vs K Value')
plt.xlabel('K')
plt.ylabel('Accuracy')

plt.subplot(1, 2, 2)
plt.plot(results_df['K'], results_df['Time (s)'], marker='o', color='r')
plt.title('Computation Time vs K Value')
plt.xlabel('K')
plt.ylabel('Time (seconds)')

plt.tight_layout()
plt.show()
```


Accuracy vs K Value
Accuracy
K
0.860
0.855
0.850
0.845
0.840
0.835
0.830
0.825
0.820
0
20
40
60
80
100
Computation Time vs K Value
Time (seconds)
K
42
41
40
39
38
37
36
0
20
40
60
80
100