

Rajalakshmi Engineering College

CS23331-Design and Analysis of Algorithm

LAB Record

EXP.NO:1(a)	BASIC C PROGRAMMING-PRACTICE
DATE:	

QUESTION:

Given two numbers, write a C program to swap the given numbers.

For example:

Input	Result
10 20	20 10

PROGRAM:

```
#include<stdio.h>

int main()
{
    int a, b, t;

    scanf("%d %d", &a, &b);

    t=a;

    a=b;

    b=t;

    printf("%d %d", a, b);

    return 0; }
```

OUTPUT:

	Input	Expected	Got	
✓	10 20	20 10	20 10	✓

QUESTION:

Write a C program to find the eligibility of admission for a professional course based on the following criteria:

Marks in Maths ≥ 65

Marks in Physics ≥ 55

Marks in Chemistry ≥ 50

Or

EXP.NO:1(b)

Total
in all
three

DATE:

BASIC C PROGRAMMING-PRACTICE

subjects ≥ 180

Sample Test Cases

Test Case 1

Input

70 60 80

Output

The candidate is eligible

PROGRAM:

```
#include<stdio.h>
```

```
int main() {  
    int m,p,c;
```

```
    scanf("%d %d %d",&m,&p,&c);
```

```
    int t=m+p+c;
```

```
    if(m $\geq$ 65 && p $\geq$ 55 && c $\geq$ 50){
```

```
        printf("The candidate is eligible");  
    }
```

```
    else if(t $\geq$ 180){
```

```
        printf("The candidate is eligible");  
    }
```

```
    else{  
        printf("The  
        candidate  
        is not  
        eligible"  
    );  
    }  
}
```

OUTPUT:

	Input	Expected	Got	
✓	70 60 80	The candidate is eligible	The candidate is eligible	✓
✓	50 80 80	The candidate is eligible	The candidate is eligible	✓

EXP.NO:1(c)	BASIC C PROGRAMMING-PRACTICE
DATE:	

QUESTION:

Malini goes to BestSave hyper market to buy grocery items. BestSave hyper market provides 10% discount on the bill amount B when ever the bill amount B is more than Rs.2000.
The bill amount B is passed as the input to the program. The program must print the final amount A payable by Malini.

Input Format:

The first line denotes the value of B.

Output Format:

The first line contains the value of the final payable amount A.

Example Input/Output 1:

Input:

1900

Output:

1900

Example Input/Output 2:

Input:

3000

Output:

2700

PROGRAM:

```
#include<stdio.h>
int main(){
int c, t;
scanf("%d",&c);
if(c>2000){ t=c-
(c*0.1);
```

```
    }  
else{  
t=c;  }  
    printf("%d",t);  
}
```

OUTPUT:

	Input	Expected	Got	
✓	1900	1900	1900	✓
✓	3000	2700	2700	✓

EXP.NO:1(d)	BASIC C PROGRAMMING-PRACTICE
DATE:	

QUESTION:

Baba is very kind to beggars and every day Baba donates half of the amount he has when ever a beggar requests him. The money M left in Baba's hand is passed as the input and the number of beggars B who received the alms are passed as the input. The program must print the money Baba had in the beginning of the day.

Input Format:

The first line denotes the value of M.

The second line denotes the value of B.

Output Format:

The first line denotes the value of money with Baba in the beginning of the day.

Example Input/Output:

Input:

100 2

Output:

400

PROGRAM:

```
#include<stdio.h>

int main(){

    int m, b;

    scanf("%d", &m);

    scanf("%d", &b);
```



```
int t=m*b;

printf("%d", t*2);
}
```

OUTPUT:

	Input	Expected	Got	
✓	100 2	400	400	✓

EXP.NO:1(e)	BASIC C PROGRAMMING-PRACTICE
DATE:	

QUESTION:

The CEO of company ABC Inc wanted to encourage the employees coming on time to the office. So he announced that for every consecutive day an employee comes on time in a week (starting from Monday to Saturday), he will be awarded Rs.200 more than the previous day as "Punctuality Incentive". The incentive I for the starting day (ie on Monday) is passed as the input to the program. The number of days N an employee came on time consecutively starting from Monday is also passed as the input. The program must calculate and print the "Punctuality Incentive" P of the employee.

Input Format:

The first line denotes the value of I.

The second line denotes the value of N.

Output Format:

The first line denotes the value of P.

Example Input/Output:

Input:

500 3

Output:

2100

PROGRAM:

```
#include<stdio.h> int
main(){

    int a,d;

    scanf("%d",&a);

    scanf("%d",&d);

    int t=0;

    for(int i=0;i<d;i++)
    {
        a=a+200;

        t=t+a;
    }
    printf("%d",t-600);
}
```

OUTPUT:

	Input	Expected	Got	
✓	500 3	2100	2100	✓
✓	100 3	900	900	✓

EXP.NO:1(f)	BASIC C PROGRAMMING-PRACTICE
DATE:	

QUESTION: _____ **2**

The first line denotes the value of	6
The second line denotes the value of	8
The third line denotes the value ofOutput Format:	X

Two numbers M and N are passed as the input. A number X is also passed as the input. The program must print the numbers divisible by X from N to M (inclusive of M and N).

Input Format:

Numbers divisible by X from N to M, with each number separated by a space.

Boundary Conditions:

$1 \leq M \leq 9999999$

$M < N \leq 9999999$ $1 \leq$

$X \leq 9999$ Example

Input/Output 1:

Input:

2

40 7

Output:

35 28 21 14 7

PROGRAM:

```
#include<stdio.h>
int main() {    int
m,n,x;

scanf("%d\n%d\n%d",&m,&n,&x);
for(int          i=n;i>=m;i--){
if(i%x==0){      printf("%d ",i);
}
}
}
```

OUTPUT:

	Input	Expected	Got	
✓	2 40 7	35 28 21 14 7	35 28 21 14 7	✓

QUESTION:

Write a C program to find the quotient and remainder of given integers.

For example:

2116231801001

EXP.NO:1(g)
DATE:

BASIC C PROGRAMMING-PRACTICE

Input	Result
12	4
3	0

PROGRAM:

```
#include<stdio.h>

int main(){

    int a, b;

    scanf("%d\n%d", &a, &b);

    printf("%d\n%d", a/b, a%b);

    return 0;
}
```

OUTPUT:

	Input	Expected	Got	
✓	12	4	4	✓
	3	0	0	

EXP.NO:1(h)	BASIC C PROGRAMMING-PRACTICE
DATE:	

QUESTION:

Write a C program to find the biggest among the given 3 integers?

For example:

Input	Result
10 20 30	30

PROGRAM:

```
#include<stdio.h>
int main() {
    int a,b,c,g;

    scanf("%d %d %d",&a,&b,&c);

    if(a>b && a>c)

        g=a;

    else if(b>a && b>c)

        g=b;

    2116231801001
```

```
else  
  
    g=c;  
  
    printf("%d",g);  
}
```

OUTPUT:

	Input	Expected	Got	
✓	10 20 30	30	30	✓

EXP.NO:1(i)	
--------------------	--

DATE:

BASIC C PROGRAMMING-PRACTICE

QUESTION:

Write a C program to find whether the given integer is odd or even?

For example:

Input	Result
12	Even
11	Odd

PROGRAM:

```
#include<stdio.h>
int main() {    int
n;

scanf("%d",&n);

if(n%2==0)

printf("Even");

else

printf("Odd");
}
```

OUTPUT:

	Input	Expected	Got	
✓	12	Even	Even	✓
✓	11	Odd	Odd	✓

EXP.NO:1(j)	BASIC C PROGRAMMING-PRACTICE
DATE:	

QUESTION:

Write a C program to find the factorial of given n.

For example:

Input	Result
5	120

PROGRAM:

```
#include<stdio.h>
int main() {    int
n;

    scanf("%d",&n);

    int i,f=1;

    for(i=1;i<=n;i++)
    {
f*=i;
    }
    printf("%d",f);
}
```

OUTPUT:

	Input	Expected	Got	
✓	5	120	120	✓

EXP.NO:1(k)	BASIC C PROGRAMMING-PRACTICE
DATE:	

QUESTION:

Write a C program to find the sum first N natural numbers.

For example:

Input	Result
3	6

PROGRAM:

```
#include<stdio.h>

int main()
{   int n;

    scanf("%d",&n);

    int s=0;

    for(int i=1;i<=n;i++)
    {
s+=i;
    }
    printf("%d",s);

    return 0;
}
```

OUTPUT:

	Input	Expected	Got	
✓	3	6	6	✓

EXP.NO:1(I)	BASIC C PROGRAMMING-PRACTICE
DATE:	

QUESTION:

Write a C program to find the Nth term in the fibonacci series.

For example:

Input	Result
0	0
1	1
4	3

PROGRAM:

```
#include<stdio.h> int
main(){
    int n,a,b,c;
    scanf("%d",&n);
    a=0;
    b=1;
    for(int i=1;i<=n;i++)
    {
        c=a+b;
        a=b;
        b=c;
    }
    printf("%d",a);
    return 0;
}
```

	Input	Expected	Got	
✓	0	0	0	✓
✓	1	1	1	✓
✓	4	3	3	✓

QUESTION:

OUTPUT:

EXP.NO:1(m)	BASIC C PROGRAMMING-PRACTICE
DATE:	

Write a C program to find the power of integers.

input: a b output: a^b value

For example:

Input	Result
2 5	32

PROGRAM:

```
#include<math.h>
#include<stdio.h> int
main()
{
    int
    a,b;

    scanf("%d %d",&a,&b);

    int p=pow(a,b);

    printf("%d",p);
}
```

	Input	Expected	Got	
✓	2 5	32	32	✓

EXP.NO:1(n)	BASIC C PROGRAMMING-PRACTICE
DATE:	

QUESTION:

Write a C program to find Whether the given integer is prime or not.

For example:

Input	Result
7	Prime
9	No Prime

PROGRAM:

```
#include<stdio.h>
> int main() {
int n;
scanf("%d",&n);
int c=0;
```

2116231801025

OUTPUT:

```
for(int i=1;i<=n;i++)
{
if(n%i==0)
c++;
}
if(c==2) {
printf("Prime");
}
else
{
printf("No Prime");
}
}
```

	Input	Expected	Got	
✓	7	Prime	Prime	✓
✓	9	No Prime	No Prime	✓

EXP.NO:1(o)	BASIC C PROGRAMMING-PRACTICE
DATE:	

QUESTION:

Write a C program to find the reverse of the given integer?

PROGRAM:

```
#include<stdio.h>
int main(){
    int n;

    scanf("%d",&n);

    int r=0;

    while(n!=0){

        r=(r*10)+(n%10);

        n=n/10;
    }
    printf("%d",r);
}
```

	Input	Expected	Got	
✓	123	321	321	✓

OUTPUT:

EXP.NO:2(a)	FINDING TIME COMPLEXITY USING COUNTER METHOD
DATE:	

QUESTION:

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
{ int i= 1; int s
  =1;  while(s
    <= n)
    { i++; s
      += i;
    } }
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n Output:

Print the value of the counter variable

PROGRAM:

```
#include<stdio.h> int
```

```
main()
```

2116231801025

```
{ int n; int  
    count=0;  
    scanf("%d",&n)  
    ; int i=1;  
    count++;  
    int s=1;  
    count++;  
    while(s<=n)
```

```
{  
    count++;  
i++;  
    count++;  
s=s+i;  
count++; }  
count++;  
printf("%d",count);  
return 0;  
}
```

OUTPUT:

	Input	Expected	Got	
✓	9	12	12	✓
✓	4	9	9	✓

EXP.NO:2(b)	
--------------------	--

DATE:

FINDING TIME COMPLEXITY USING COUNTER METHOD

QUESTION:

Convert the following algorithm into a program and find its time complexity using the counter method. void func(int n)

```
{ if(n==1)
{
    printf("*");
}
else
{ for(int i=1; i<=n;
i++)
{ for(int j=1; j<=n;
j++)
{ printf("*");
printf("*")
; break;
}
}
}
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements. Input:

A positive Integer n Output:

Print the value of the counter variable

PROGRAM:

```
#include<stdio.h>
```

```
int main()
```

```
{
int n; scanf("%d",&n); int c = 0; int
i;
c++;

int j;

c++;
```

```

if (n == 1)
{
    c++;

    c++;
} else { for (i = 1; i <= n;
            i++) { c++;
                for (j = 1; j <= n; j++) {
                    c++;
                    c++; c++;
                    break; }
                c++;
            }
        } printf("%d",
c);
}

```

OUTPUT:

	Input	Expected	Got	
✓	2	12	12	✓
✓	1000	5002	5002	✓
✓	143	717	717	✓

EXP.NO:2(c)	FINDING TIME COMPLEXITY USING COUNTER METHOD
DATE:	

QUESTION:

Convert the following algorithm into a program and find its time complexity using counter method.

```
Factor(num) {
{ for (i = 1; i <= num;++i)
{ if (num % i==
0)
{ printf("%d ",
i);
}
}
}
```

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:

A positive Integer n Output:

Print the value of the counter variable

PROGRAM:

```
#include<stdio.h> int
main()
{ int n,i;

  int c=0;

  scanf("%d",&n);

  for (i = 1; i <= n;++i)
  {
    c++; if (n
    % i== 0) {

      c++;

      // printf("%d ", i);

    }

    c++;

  }

  c++; printf("%d",c);

  return 0;

}
```

OUTPUT:

	Input	Expected	Got	
✓	12	31	31	✓
✓	25	54	54	✓
✓	4	12	12	✓

Passed all tests! ✓

EXP.NO:2(d)	
-------------	--

DATE:

FINDING TIME COMPLEXITY USING COUNTER METHOD

QUESTION:

Convert the following algorithm into a program and find its time complexity using counter method.

```
void function(int n)
{ int c= 0;
  for(int i=n/2; i<n; i++) for(int
    j=1; j<n; j = 2 * j) for(int
      k=1; k<n; k = k * 2)
    c++;
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n Output:

Print the value of the counter variable

PROGRAM:

```
#include<stdio.h>
```

```
int main()
```

```
{ int n;
```

```
  scanf("%d",&n); int
```

```
  c=0; c++; for(int
```

```
  i=n/2;i<n;i++)
```

```
  {
```

```
    c++;
```

```
    for(int j =1;j<n;j=2*j)
```

```
    {
```

```
      c++;
```

```
      for(int k =1;k<n;k=k*2)
```

```

        {
            c++;

            c++;

            // c++; }

        c++

    ; } c++; }

    c++;

    printf("%d",c);
}

```

OUTPUT:

	Input	Expected	Got	
✓	4	30	30	✓
✓	10	212	212	✓

Passed all tests! ✓

EXP.NO:2(e)	FINDING TIME COMPLEXITY USING COUNTER METHOD
DATE:	

QUESTION:

Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{ int rev = 0, remainder;
  while (n != 0)
  { remainder = n % 10; rev =
    rev * 10 + remainder; n/=
    10;

    } print(rev);
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n **Output:**

Print the value of the counter variable

PROGRAM:

```
#include<stdio.h> int
main()
{ int n;

  scanf("%d",&n);
```



```

int c =0; int rev
=0,remainder; c++;

while(n!=0)

{c++;

    remainder = n % 10; c++;

rev = rev * 10 + remainder;

c++; n/= 10; c++; } c++;

//print(rev);

c++; printf("%d",c);

}

```

OUTPUT:

	Input	Expected	Got	
✓	12	11	11	✓
✓	1234	19	19	✓

Passed all tests! ✓

EXP.NO:3(a)	DIVIDE AND CONQUER
DATE:	

PROBLEM STATEMENT:

Given an array of 1s and 0s this has all 1s first followed by all 0s. Aim is to find the number of 0s. Write a program using Divide and Conquer to Count the number of zeroes in the given array.

Input Format

First Line Contains Integer m – Size of array

Next m lines Contains m numbers – Elements of an array

Output Format

First Line Contains Integer – Number of zeroes present in the given array.

PROGRAM:

```

#include <stdio.h> int

main() { int m, i;

scanf("%d", &m); int

arr[m]; for(i = 0; i < m;

i++) { scanf("%d",

&arr[i]);

}

int low = 0, high = m - 1, mid, firstZeroIndex = -1; while(low

<= high) {

mid = low + (high - low) / 2;

if ((mid == 0 || arr[mid - 1] == 1) && arr[mid] == 0) { firstZeroIndex

= mid;

break;

}

if (arr[mid] == 1) { low

= mid + 1;

} else { high = mid - 1;

}

}

if (firstZeroIndex == -1) {

```

```
    printf("0\n");

} else {

    printf("%d\n", m - firstZeroIndex);

}


return 0;

}
```

OUTPUT:

	Input	Expected	Got	
✓	5 1 1 1 0 0	2	2	✓
✓	10 1 1 1 1 1 1 1 1 1 1 1 1	0	0	✓
✓	8 0 0 0 0 0 0 0 0 0 0	8	8	✓

EXP.NO:3(b)	
-------------	--

DATE:

DIVIDE AND CONQUER

PROBLEM STATEMENT:

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than $\lfloor n / 2 \rfloor$ times. You may assume that the majority element always exists in the array.

Example 1:

Input: `nums = [3,2,3]`

Output: 3

Example 2:

Input: `nums = [2,2,1,1,1,2,2]` Output:

2

Constraints: `n ==`

`nums.length`

`1 <= n <= 5 * 104`

`-231 <= nums[i] <= 231 - 1`

PROGRAM:

```
#include <stdio.h>
```

```
int main() {  
    int n;  
  
    scanf("%d", &n);  
  
    int nums[n];  
  
    for (int i = 0; i < n; i++) {  
        scanf("%d", &nums[i]);  
    }  
    int count = 0;  
  
    int candidate = 0;  
  
    for (int i = 0; i < n; i++) {  
        if (count == 0) {  
            candidate = nums[i];  
        }  
    }  
}
```

```
    if (nums[i] == candidate) { count++;  
    } else { count--;  
    }    }    printf("%d\n",  
candidate); return 0;  
}
```

OUTPUT:

	Input	Expected	Got	
✓	3 3 2 3	3	3	✓

Passed all tests! ✓

EXP.NO:3(c)	DIVIDE AND CONQUER
DATE:	

PROBLEM STATEMENT:

Given a sorted array and a value x, the floor of x is the largest element in array smaller than or equal to x. Write divide and conquer algorithm to find floor of x.

Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Value for x

Output Format

First Line Contains Integer – Floor value for x

PROGRAM:

```
#include <stdio.h>
```

```
int main() {
```

```
    int n, x;
```

```
    scanf("%d", &n);
```

```
    int arr[n];
```

```
    for (int i = 0; i < n; i++) {
```

```
        scanf("%d", &arr[i]);
```

```
    }
```

```
    scanf("%d", &x);
```

```
    int left = 0, right = n - 1;
```

```
    int floor = -1;
```

```
    while (left <= right) { int mid = left
```

```
        + (right - left) / 2;
```

```
        if (arr[mid] == x) { floor
```

```
            = arr[mid]; break; }
```

```

if (arr[mid] < x) {
    floor = arr[mid];
    left = mid + 1;
} else { right =
mid - 1;

} } if (floor != -1) {
printf("%d\n", floor);

} else { printf("No floor value found for %d in the
array.\n", x);

} return
0;
}

```

OUTPUT:

	Input	Expected	Got	
✓	6 1 2 8 10 12 19 5	2	2	✓
✓	5 10 22 85 108 129 100	85	85	✓

EXP.NO:3(d)	DIVIDE AND CONQUER
DATE:	

PROBLEM STATEMENT:

Given a sorted array of integers say arr[] and a number x. Write a recursive program using divide and conquer strategy to check if there exist two elements in the array whose sum = x.

If there exist such two elements then return the numbers, otherwise print as “No”.

Note: Write a Divide and Conquer Solution

Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Sum Value

Output Format

First Line Contains Integer – Element1

Second Line Contains Integer – Element2 (Element 1 and Elements 2 together sums to value “x”)

PROGRAM:

```
#include <stdio.h>
```

```
int main() {
```

```
    int n, x;
```

```
    scanf("%d", &n);
```

```

int arr[n];

for (int i = 0; i < n; i++) {
    scanf("%d", &arr[i]);
} scanf("%d",

&x);

int left = 0, right = n - 1;
int found = 0;
while (left < right) { int sum =
    arr[left] + arr[right];

    if (sum == x) {
        printf("%d\n", arr[left]);

        printf("%d\n", arr[right]);

        found = 1;
break; } if (sum < x) {
    left++;
    } else { right--;
    } } if (!found)
    { printf("No\n");
    } return
0;
}

```

OUTPUT:

	Input	Expected	Got	
✓	4 2 4 8 10 14	4 10	4 10	✓
✓	5 2 4 6 8 10 100	No	No	✓

Passed all tests! ✓

EXP.NO:3(e)	DIVIDE AND CONQUER
DATE:	

PROBLEM STATEMENT:

Write a Program to Implement the Quick Sort Algorithm

Input Format:

2116231801025

The first line contains the no of elements in the list-n
The next n lines contain the elements.

Output:

Sorted list of elements

PROGRAM:

```
#include <stdio.h>
```

```
int main() {
```

```
    int n;
```

```
    scanf("%d", &n);
```

```
    int a[n]; for (int i = 0; i <
```

```
    n; i++) {
```

```
        scanf("%d", &a[i]);
```

```
    } for (int i = 0; i < n; i++) { for
```

```
    (int j = i + 1; j < n; j++) {
```

```
        if (a[j] < a[i]) {
```

```
            int temp = a[i];
```

```
            a[i] = a[j];
```

```
            a[j] = temp;
```

```
        }
```

```
    } }
```

```
    for (int i = 0; i < n; i++) {
```

```
        printf("%d ", a[i]);
```

```
    } return 0;
```

```
}
```

OUTPUT:

	Input	Expected	Got	
✓	5 67 34 12 98 78	12 34 67 78 98	12 34 67 78 98	✓
✓	10 1 56 78 90 32 56 11 10 90 114	1 10 11 32 56 56 78 90 90 114	1 10 11 32 56 56 78 90 90 114	✓
✓	12 9 8 7 6 5 4 3 2 1 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	✓

Passed all tests! ✓

EXP.NO:4(a)	1-G-COIN PROBLEM
DATE:	

QUESTION:

Write a program to take value V and we want to make change for V Rs, and we have infinite supply of each of the denominations in Indian currency, i.e., we have infinite supply of { 1, 2, 5, 10, 20, 50, 100, 500, 1000} valued coins/notes, what is the minimum number of coins and/or notes needed to make the change.

Input Format:

Take an integer from stdin.

Output Format:

print the integer which is change of the number.

Example Input :

64

Output:

4

Explanaton:

We need a 50 Rs note and a 10 Rs note and two 2 rupee coins.

PROGRAM:

```
#include <stdio.h>

int min_coins_and_notes(int V) { int denominations[] =
    {1000, 500, 100, 50, 20, 10, 5, 2, 1}; int n =
    sizeof(denominations) / sizeof(denominations[0]); int count
    = 0;

    for (int i = 0; i < n; i++) {
        if (V == 0) {
            break;
        }

        count += V / denominations[i];
```

```
V %= denominations[i];
```

```
return count;

} int main()

{ int V;

  scanf("%d",    &V);    printf("%d\n",

  min_coins_and_notes(V)); return 0;

}
```

OUTPUT:

	Input	Expected	Got	
✓	49	5	5	✓

EXP.NO:4(b)	2-G-COOKIES PROBLEM

DATE:	
--------------	--

QUESTION:

Assume you are an awesome parent and want to give your children some cookies. But, you should give each child at most one cookie.

Each child i has a greed factor $g[i]$, which is the minimum size of a cookie that the child will be content with; and each cookie j has a size $s[j]$. If $s[j] \geq g[i]$, we can assign the cookie j to the child i , and the child i will be content. Your goal is to maximize the number of your content children and output the maximum number.

Example 1:

Input:

3

1 2 3

2

1 1

Output: 1

Explanation: You have 3 children and 2 cookies. The greed factors of 3 children are 1, 2, 3.

And even though you have 2 cookies, since their size is both 1, you could only make the child whose greed factor is 1 content.

You need to output 1.

Constraints:

$1 \leq g.length \leq 3 \times 10^4$

$0 \leq s.length \leq 3 \times 10^4$

$1 \leq g[i], s[j] \leq 2^{31} - 1$

PROGRAM:

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
int compare(const void *a, const void *b) {
```

```
    return (*(int *)a - *(int *)b);
```

```

} int findContentChildren(int g[], int gSize, int s[], int sSize)
{
    qsort(g, gSize, sizeof(int), compare); qsort(s, sSize,
    sizeof(int), compare); int childIndex = 0; int cookieIndex =
    0; while (childIndex < gSize && cookieIndex < sSize) {
        if (s[cookieIndex] >= g[childIndex]) {
            childIndex++;
        }
        cookieIndex++;
    } return
    childIndex;
} int main() { int
gSize, sSize;
    scanf("%d", &gSize);
    int *g = (int *)malloc(gSize * sizeof(int)); if (g
    == NULL) { fprintf(stderr, "Memory allocation
    failed\n"); return 1; } for (int i = 0; i < gSize;
    i++) {
        scanf("%d", &g[i]);
    } scanf("%d",
    &sSize); int *s = (int
    *)malloc(sSize *
    sizeof(int));
    if (s == NULL) {

```

```
    fprintf(stderr, "Memory allocation failed\n");
free(g); return 1; } for (int i = 0; i < sSize; i++)
{ scanf("%d", &s[i]);
} printf("%d\n", findContentChildren(g, gSize, s,
sSize)); free(g); free(s); return 0;
}
```

OUTPUT:

	Input	Expected	Got	
✓	2	12	12	✓
✓	1000	5002	5002	✓
✓	143	717	717	✓

EXP.NO:4(c)	
-------------	--

DATE:

3-G-BURGER PROBLEM

QUESTION:

A person needs to eat burgers. Each burger contains a count of calorie. After eating the burger, the person needs to run a distance to burn out his calories.

If he has eaten i burgers with c calories each, then he has to run at least $3^i * c$ kilometers to burn out the calories. For example, if he ate 3 burgers with the count of calorie in the order: [1, 3, 2], the kilometers he needs to run are $(3^0 * 1)$

$+ (3^1 * 3) + (3^2 * 2) = 1 + 9 + 18 = 28$.

But this is not the minimum, so need to try out other orders of consumption and choose the minimum value. Determine the minimum distance he needs to run. Note: He can eat burger in any order and use an efficient sorting algorithm. Apply greedy approach to solve the problem.

Input Format

First Line contains the number of burgers

Second line contains calories of each burger which is n space-separate integers

Output Format

Print: Minimum number of kilometers needed to run to burn out the calories

Sample Input

```
3
5 10 7
```

Sample Output

```
76
```

PROGRAM:

```
#include <stdio.h>

#include <stdlib.h>

#include <limits.h>

int compareDescending(const void *a, const void *b) {
    return (*(int *)b - *(int *)a);
}

long long minDistance(int calories[], int n) {
    qsort(calories, n, sizeof(int), compareDescending);
```

```

long long totalDistance = 0; long long powerOf3 =
1;
for (int i = 0; i < n; i++) {
    if (powerOf3 > LLONG_MAX / calories[i]) { fprintf(stderr,
        "Integer overflow detected during calculation.\n"); exit(1); }
    totalDistance += powerOf3 * calories[i];
    if (powerOf3 > LLONG_MAX / 3) {
        fprintf(stderr, "Integer overflow detected while computing powers of 3.\n");
        exit(1); }
    powerOf3 *= 3;
} return
totalDistance;
} int main()
{
    int n;
    if (scanf("%d", &n) != 1 || n < 0) { fprintf(stderr, "Invalid
input for number of burgers.\n"); return 1; } if (n == 0) {
    printf("0\n"); return 0;
}
    int *calories = (int *)malloc(n * sizeof(int)); if (calories
== NULL) { fprintf(stderr, "Memory allocation
failed\n"); return 1; } for (int i = 0; i < n; i++) { if
(scanf("%d", &calories[i]) != 1 || calories[i] < 0) {
    fprintf(stderr, "Invalid input for calorie count.\n");
    free(calories); return 1;
}
}
}

```

```
printf("%lld\n", minDistance(calories, n));  
  
free(calories); return 0;  
  
}
```

OUTPUT:

	Test	Input	Expected	Got	
✓	Test Case 1	3 1 3 2	18	18	✓
✓	Test Case 3	3 5 10 7	76	76	✓

EXP.NO:4(d)	4-G-ARRAY SUM MAX PROBLEM
DATE:	

QUESTION:

Given an array of N integer, we have to maximize the sum of $\text{arr}[i] * i$, where i is the index of the element ($i = 0, 1, 2, \dots, N$). Write an algorithm based on Greedy technique with a Complexity $O(n \log n)$.

Input Format:

First line specifies the number of elements-n

The next n lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5

2 5 3 4 0

Sample output:

40

PROGRAM:

```
#include <stdio.h> #include
```

```
<stdlib.h>
```

```
int compare(const void *a, const void *b) {
```

```
    return (*(int*)a - *(int*)b);
```

```
} int main()
```

```
{
```

```
    int n;
```

```
    scanf("%d", &n);    int    *arr    =
```

```
(int*)malloc(n * sizeof(int)); for (int i
```

```
    = 0; i < n; i++) {
```

2116231801025

```
    scanf("%d", &arr[i]);

} qsort(arr, n, sizeof(int), compare);
0;

for (int i = 0; i < n; i++) {

    max_sum += arr[i] * i;

}

printf("%d\n", max_sum);

free(arr); return

0;

}

, n, sizeof(int), compare);
```

OUTPUT:

	Input	Expected	Got	
✓	5 2 5 3 4 0	40	40	✓
✓	10 2 2 2 4 4 3 3 5 5 5	191	191	✓
✓	2 45 3	45	45	✓

EXP.NO:4(e)	5-G-PRODUCT OF ARRAY ELEMENTS-MINIMUM
DATE:	

QUESTION:

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

PROGRAM:

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
int compare_asc(const void *a, const void *b) { return
    (*(int*)a - *(int*)b);
}
```

```
int compare_desc(const void *a, const void *b) {
    return (*(int*)b - *(int*)a);
} int main()
{
```

```
    int n;
```

```
    scanf("%d", &n); int *array_One =
```

```
    malloc(n * sizeof(int)); int *array_Two =
```

```
    malloc(n * sizeof(int));
```

```
    for (int i = 0; i < n; i++) {
```

```
        scanf("%d", &array_One[i]);
```

```
    }
```

```
    for (int i = 0; i < n; i++) {
```

```
        scanf("%d", &array_Two[i]);
```

```
} qsort(array_One, n, sizeof(int), compare_asc); qsort(array_T)
    int min_sum = 0;

    for (int i = 0; i < n; i++) {

        min_sum += array_One[i] * array_Two[i];

    }

    printf("%d\n", min_sum);

    free(array_One); free(array_Two);

    return 0;

} wo, n, sizeof(int), compare_desc);
```


OUTPUT:

	Input	Expected	Got	
✓	3 1 2 3 4 5 6	28	28	✓
✓	4 7 5 1 2 1 3 4 1	22	22	✓
✓	5 20 10 30 10 40 8 9 4 3 10	590	590	✓

EXP.NO:5(a)	PLAYING WITH NUMBERS
DATE:	

QUESTION:

Ram and Sita are playing with numbers by giving puzzles to each other. Now it was Ram term, so he gave Sita a positive integer 'n' and two numbers 1 and 3. He asked her to find the possible ways by which the number n can be represented using 1 and 3. Write any efficient algorithm to find the possible ways.

Example 1:

Input: 6

Output: 6

Explanation: There are 6 ways to 6 represent number with 1 and 3

1+1+1+1+1+1

3+3

1+1+1+3

1+1+3+1

1+3+1+1

3+1+1+1

Input Format

First Line contains the number n

Output Format Print: The number of possible ways 'n' can be represented using 1 and 3 Sample Input 6

Sample Output

6

PROGRAM:

```
#include <stdio.h> long long
count_ways(int n) { long long
dp[n + 1]; dp[0] = 1; if (n >=
1) { dp[1] = 1;

}
if (n >= 2) {

    dp[2] = 1; } if (n >= 3) {
    dp[3] = 2; } for (int i = 4; i
<= n; i++) { dp[i] = dp[i - 1]
+ dp[i - 3];
```

```

    }    return
dp[n]; } int
main() {
    int n;

    scanf("%d", &n);

    printf("%lld\n", count_ways(n));

    return 0;
}

```

OUTPUT:

	Input	Expected	Got	
✓	6	6	6	✓
✓	25	8641	8641	✓
✓	100	24382819596721629	24382819596721629	✓

EXP.NO:5(b)	PLAYING WITH CHESSBOARD
DATE:	

QUESTION:

Ram is given with an $n \times n$ chessboard with each cell with a monetary value. Ram stands at the (0,0), that the position of the top left white rook. He is been given a task to reach the bottom right black rook position (n-1, n-1) constrained that he needs to reach the position by traveling the maximum monetary path under the condition that he can only travel one step right or one step down the board. Help ram to achieve it by providing an efficient DP algorithm.

Example:

Input

3

1 2 4

2 3 4

8 7 1

Output:

19

Explanation:

Totally there will be 6 paths among that the optimal is

Optimal path value: $1+2+8+7+1=19$

Input Format

First Line contains the integer n

The next n lines contain the $n \times n$ chessboard values

Output Format

Print Maximum monetary value of the path

PROGRAM:

```
#include <stdio.h>
```

```
#define MAX 100
```

```
int max(int a, int b)
```

```

{
    return (a > b) ? a : b;
}

int maxMonetaryPath(int chessboard[MAX][MAX], int n) {
    int dp[MAX][MAX];
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            dp[i][j] = 0;
        }
        dp[0][0] = chessboard[0][0];
        for (int j = 1; j < n; j++) {
            dp[0][j] = dp[0][j - 1] + chessboard[0][j];
        }
        for (int i = 1; i < n; i++) {
            dp[i][0] = dp[i - 1][0] + chessboard[i][0];
        }
        for (int i = 1; i < n; i++) {
            for (int j = 1; j < n; j++) {
                dp[i][j] = chessboard[i][j] + max(dp[i - 1][j], dp[i][j - 1]);
            }
        }
        return dp[n - 1][n - 1];
    }
}

int main() {
    int n;
    int chessboard[MAX][MAX];
    scanf("%d", &n);
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            scanf("%d", &chessboard[i][j]);
        }
    }
}

```

```

int result = maxMonetaryPath(chessboard, n);

printf("%d\n", result);

return 0;
}

```

OUTPUT:

	Input	Expected	Got	
✓	3 1 2 4 2 3 4 8 7 1	19	19	✓
✓	3 1 3 1 1 5 1 4 2 1	12	12	✓
✓	4 1 1 3 4 1 5 7 8 2 3 4 6 1 6 9 0	28	28	✓

EXP.NO:5(c)	LONGEST COMMON SUBSEQUENCE
DATE:	

QUESTION:

Given two strings find the length of the common longest subsequence(need not be contiguous) between the two.

Example:

s1: ggtabe

s2: tgatasb

s1	a	g	g	t	a	b	
s2	g	x	t	x	a	y	b

The length is 4

Solveing it using Dynamic Programming

PROGRAM:

```
#include <stdio.h> #include <string.h> int
longest_common_subsequence(char s1[], char s2[]) { int
m = strlen(s1); int n = strlen(s2); int dp[m + 1][n + 1];
for (int i = 0; i <= m; i++) {
    for (int j = 0; j <= n; j++) {
        if (i == 0 || j == 0) {
            dp[i][j] = 0;

        } else if (s1[i - 1] == s2[j - 1]) { dp[i][j] = dp[i - 1][j - 1] + 1;}
        else { dp[i][j] = (dp[i - 1][j] > dp[i][j - 1]) ? dp[i - 1][j] :
            dp[i][j - 1];
        }
    }
}
```

```

    } } return
    dp[m][n];
} int main()
{
    char s1[100], s2[100]; scanf("%s", s1);
    scanf("%s", s2); int result =
    longest_common_subsequence(s1, s2);
    printf("%d",result); return
    0;
}

```

OUTPUT

	Input	Expected	Got	
✓	aab azb	2	2	✓
✓	ABCD ABCD	4	4	✓

EXP.NO:5(d)	LONGEST NON-DECREASING SUBSEQUENCE
DATE:	

QUESTION:

Problem statement:

Find the length of the Longest Non-decreasing Subsequence in a given Sequence.

Eg:

Input:9

Sequence:[-1,3,4,5,2,2,2,2,3]

the subsequence is [-1,2,2,2,2,3]

Output:6

PROGRAM:

```
#include <stdio.h>

int
longest_non_decreasing_subsequence(int arr[], int n) { int
dp[n]; int max_length = 1;

    for (int i = 0; i < n; i++) {

        dp[i] = 1;

    } for (int i = 1; i < n;

i++) {

        for (int j = 0; j < i; j++) {

            if (arr[j] <= arr[i]) { dp[i] = (dp[i] > dp[j] + 1) ?

                dp[i] : dp[j] + 1;}}

        if (dp[i] > max_length) {

            max_length = dp[i];

        }

    }
```

```
    }

    return max_length;
}

int main() {

    int n;

    scanf("%d", &n);

    int arr[n]; for (int i = 0; i < n; i++) { scanf("%d", &arr[i]);

    } int result = longest_non_decreasing_subsequence(arr,

    n); printf( "%d\n", result); return 0;

}
```

OUTPUT:

	Input	Expected	Got	
✓	9 -1 3 4 5 2 2 2 2 3	6	6	✓
✓	7 1 2 2 4 5 7 6	6	6	✓

EXP.NO:6(a)	FINDING DUPLICATES-$O(N^2)$ TIME COMPLEXITY,$O(1)$ SPACE COMPLEXITY
DATE:	

QUESTION:

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated For example:

Input	Result
5 1 1 2 3 4	1

PROGRAM:

```
#include <stdio.h>
```

```
int findDuplicate(int arr[], int n) {
```

```
    int slow = arr[0]; int fast =
```

```
    arr[arr[0]]; while (slow != fast)
```

```
    { slow = arr[slow];
```

```
        fast = arr[arr[fast]];
```

```

    } fast = 0; while
    (slow != fast) { slow
    = arr[slow];
        fast = arr[fast];

    }    return
slow; } int
main() {
    int n;
    scanf("%d", &n);
    int arr[n]; for (int i = 0; i
    < n; i++) {
        scanf("%d", &arr[i]);
    } int duplicate = findDuplicate(arr,
    n); printf("%d", duplicate); return 0;
}

```

OUTPUT:

	Input	Expected	Got	
✓	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✓
✓	5 1 2 3 4 4	4	4	✓
✓	5 1 1 2 3 4	1	1	✓

EXP.NO:6(b)	FINDING DUPLICATES-O(N) TIME COMPLEXITY,O(1) SPACE COMPLEXITY
DATE:	

QUESTION:

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated For example:

Input	Result
5 1 1 2 3 4	1

PROGRAM:

```
#include <stdio.h>
```

```
int findDuplicate(int arr[], int n) {
```

```
    int slow = arr[0]; int fast =
```

```
    arr[arr[0]]; while (slow != fast)
```

```
    {
```

```
        slow = arr[slow];
```

```
        fast = arr[arr[fast]];
```

```

    } fast = 0; while
    (slow != fast) { slow
    = arr[slow];
        fast = arr[fast];
    }
    return slow;
} int main() {
    int n;
    scanf("%d", &n);
    int arr[n]; for (int i = 0; i
    < n; i++) {
        scanf("%d", &arr[i]);
    } int duplicate = findDuplicate(arr,
    n); printf("%d", duplicate); return 0;
}

```

OUTPUT:

	Input	Expected	Got	
✓	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✓
✓	5 1 2 3 4 4	4	4	✓
✓	5 1 1 2 3 4	1	1	✓

EXP.NO:6(c)	PRINT INTERSECTION OF 2 SORTED ARRAYS-O(M+N)TIME COMPLEXITY,O(1) SPACE COMPLEXITY
DATE:	

QUESTION:

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

```
1
3 10 17 57 6 2 7
10 15 57 246
```

Output:

```
10 57
```

Input:

```
1
6 1 2 3 4 5 6
2 1 6
```

Output:

```
1 6
```

For example:

Input	Result
1 3 10 17 57	10 57

Input	Result
6 2 7 10 15 57 246	

PROGRAM:

```
#include <stdio.h>
```

```
void findIntersection(int arr1[], int n1, int arr2[], int n2) {
```

```
    int i = 0, j = 0; while (i < n1 && j < n2) {
```

```
        if (arr1[i] < arr2[j]) {
```

```
            i++;
```

```
        } else if (arr2[j] < arr1[i]) {
```

```
            j++;
```

```
        } else { printf("%d ",
```

```
            arr1[i]); i++;
```

```
            j++;
```

```
        } }
```

```
    printf("\n")
```

```
    ;
```

```
}
```

```

int main() {
    int T;

    scanf("%d", &T);
    while (T--) { int n1,
n2;    scanf("%d",
&n1);

        int arr1[n1]; for (int i = 0;
i < n1; i++) {
            scanf("%d", &arr1[i]);
        } scanf("%d",
&n2);

        int arr2[n2]; for (int i = 0;
i < n2; i++) {
            scanf("%d", &arr2[i]);
        } findIntersection(arr1, n1, arr2,
n2);

    } return
0;
}

```

OUTPUT:

	Input	Expected	Got	
✓	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✓
✓	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✓

EXP.NO:6(d)	PRINT INTERSECTION OF 2 SORTED ARRAYS-O(M+N)TIME COMPLEXITY,O(1) SPACE COMPLEXITY
DATE:	

QUESTION:

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57 6 2 7

10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

For example:

Input	Result
1	10 57

Input	Result
3 10 17 57	
6	
2 7 10 15 57 246	

PROGRAM:

```
#include <stdio.h>
```

```
void findIntersection(int arr1[], int n1, int arr2[], int n2) {
```

```
    int i = 0, j = 0;
```

```
    int found = 0; while (i <
```

```
    n1 && j < n2) {
```

```
        if (arr1[i] < arr2[j]) {
```

```
            i++;
```

```
        } else if (arr2[j] < arr1[i]) {
```

```
            j++;
```

```
        } else { printf("%d ",
```

```
            arr1[i]); found = 1;
```

```
            i++; j++;
```

```
        }
```

```

    } if (!found) { printf("No
Intersection");
    }printf("\n");
} int main() {
int T;

scanf("%d", &T);

while (T--) { int
n1, n2;

    scanf("%d", &n1);

    int arr1[n1]; for (int i = 0;
i < n1; i++) {

        scanf("%d", &arr1[i]);

    } scanf("%d",
&n2);

    int arr2[n2]; for (int i = 0;
i < n2; i++) {

        scanf("%d", &arr2[i]);

    } findIntersection(arr1, n1, arr2,
n2);

    } return
0;
}

```

OUTPUT:

	Input	Expected	Got	
✓	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✓
✓	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✓

EXP.NO:6(e)	PAIR WITH DIFFERENCE-$O(N^2)$ TIME COMPLEXITY, $O(1)$ SPACE COMPLEXITY
DATE:	

QUESTION:

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that $A[j] - A[i] = k$, $i \neq j$. Input Format:

First Line n - Number of elements in an

array Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as $5 - 1 = 4$

So Return 1. **For**

example:

Input	Result
3 1 3 5 4	1

PROGRAM:

```

#include <stdio.h> int findPairWithDifference(int
arr[], int n, int k) { int i = 0, j = 1;
    while (i < n && j < n) {
        int diff = arr[j] - arr[i]; if (i
        != j && diff == k) { return
            1;
        } else if (diff < k)
            { j++; } else {
                i++;
            }
    }
    return 0; }
int main() {
    int n, k;
    scanf("%d", &n);
    int arr[n]; for (int i = 0; i
    < n; i++) {
        scanf("%d", &arr[i]);
    }
    scanf("%d", &k);
    int result = findPairWithDifference(arr, n, k); printf("%d\n", result); return 0;
}

```

OUTPUT:

	Input	Expected	Got	
✓	3 1 3 5 4	1	1	✓
✓	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✓
✓	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✓
✓	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✓

EXP.NO:6(f)	LONGEST NON-DECREASING SUBSEQUENCE
DATE:	

QUESTION:

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that $A[j] - A[i] = k$, $i \neq j$. Input Format:

First Line n - Number of elements in an

array Next n Lines - N elements in the array

k - Non - Negative Integer Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as $5 - 1 = 4$ So

Return 1.

For example:

Input	Result
3	1
1 3 5	
4	

PROGRAM:

```
#include <stdio.h>
```

```
int findPairWithDifference(int arr[], int n, int k) {
```

```

int i = 0, j = 1;
while (j < n) {
    int diff = arr[j] - arr[i]; if
    (i != j && diff == k) {
        return 1;
    } else if (diff < k)
        { j++; } else {
            i++;
            if (i == j) {
                j++;
            }
        }
}
return 0; }

int main() {
    int n, k;
    scanf("%d", &n);
    int arr[n]; for (int i = 0; i
    < n; i++) {
        scanf("%d", &arr[i]);
    }
    scanf("%d", &k);
    int result = findPairWithDifference(arr, n, k); printf("%d\n", result); return 0;
}

```

OUTPUT:

	Input	Expected	Got	
✓	3 1 3 5 4	1	1	✓
✓	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✓
✓	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✓
✓	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✓