



5CS037 - Concepts and Technologies of AI.

Week - 03 - Workshop - 03

Exploratory Data Analysis - Part-II.

Some Advance Operation with Pandas and Introduction to Matplotlib!!!

Siman Giri

Workshop - 03

November - 27 - 2024




Image by : J. Ferrer - 7 steps to mastering Data Analysis [KDruggets]

Outline

- 1 Some Advance Operation with Pandas.
- 2 Getting Started with Data Visualization.
- 3 Data Visualization with Pandas.
- 4 Data Visualization with Matplotlib.
- 5 Final Slide.

Advance Operation With Pandas.

1. Sorting and Susetting.

	Name	Height	Championships			Name	Height	Championships
0	Kobe Bryant	198	5	→	0	Kobe Bryant	198	5
1	LeBron James	206	4		2	Michael Jordan	198	6
2	Michael Jordan	198	6		1	LeBron James	206	4
3	Larry Bird	206	3		3	Larry Bird	206	3

Sort DataFrame



1.1 Sorting:

Sorting arranges data in a specific order (ascending or descending) based on values or indices for better organization and analysis.

- `sort_values()`: Sorts a DataFrame or Series by its values.
- `sort_index()`: Sorts a DataFrame or Series by its index.

```
1 # Syntax: Sorting by values
2 mydataframe.sort_values(by='column_name', ascending=True,
3                           inplace=False)
4
5 # Syntax: Sorting by index
6 mydataframe.sort_index(ascending=True, inplace=False)
```

1.1 Sorting - Code Example:

```
1 import pandas as pd
2 # Creating a sample DataFrame
3 data = {'Name': ['Alice', 'Bob', 'Charlie', 'David'],
4         'Age': [24, 19, 22, 25],
5         'Score': [88, 92, 85, 95]}
6 df = pd.DataFrame(data)
7 print(df.head())
8 # Example 1: Sort by 'Age' using sort_values()
9 sorted_by_age = df.sort_values(by='Age')
10 print(sorted_by_age.head())
11 # Example 2: Sort by index using sort_index()
12 sorted_by_index = df.sort_index()
13 print(sorted_by_index.head())
```

1.2 Subsetting by Indices:

When working with data, you may not need all of the variables in your dataset.

- Subsetting allows you to create a smaller, focused DataFrame by selecting specific rows or columns using indices (positional or labels) or directly by column names, tailoring the data for analysis.

Subsetting by indices uses `[]` which allows you to extract specific rows, columns, or values from a DataFrame for further analysis.

- `iloc[]`: Access rows and columns using integer indices.

```
dataframe.iloc[row_start:row_end, col_start:col_end]
```

- `loc[]`: Access rows and columns by labels and conditions.

```
dataframe.loc[condition, ['col1', 'col2']]
```

- `[]` (brackets): Used for selecting columns.

```
dataframe[['col1', 'col2']]
```

1.2.1 Subsetting By Indices: Examples

```

1 import pandas as pd
2 # Creating a sample DataFrame
3 data = {'Name': ['Alice', 'Bob', 'Charlie', 'David'],
4         'Age': [24, 19, 22, 25],
5         'Score': [88, 92, 85, 95]}
6 df = pd.DataFrame(data)
7 # 1.Using.iloc[:]:Accessing rows and columns by index
8 subset_iloc = df.iloc[1:3, 0:2]
9 print(subset_iloc)
10 # 2.Using.loc[:]:Accessing rows by condition and specific
    columns
11 subset_loc = df.loc[df['Age'] > 20, ['Name', 'Score']]
12 print(subset_loc)
13 # 3.Using [:]: Selecting specific columns
14 subset_brackets = df[['Name', 'Age']]
15 print(subset_brackets)

```


1.2.2 Subsetting by Values - Columns

Subsetting columns by values allows you to select specific columns directly using their names, either as a single column or multiple columns.

- Single Column: `dataframe['column_name']`
- Multiple Columns: `dataframe[['column_name1', 'column_name2']]`

```

1 import pandas as pd
2 # Creating a sample DataFrame
3 data = {'Name': ['Alice', 'Bob', 'Charlie', 'David'],
4         'Age': [24, 19, 22, 25],
5         'Score': [88, 92, 85, 95]}
6 df = pd.DataFrame(data)
7 # Subsetting a single column
8 name_column = df['Name']
9 print(name_column)
10 # Subsetting multiple columns
11 name_and_age = df[['Name', 'Age']]
12 print(name_and_age)

```

1.3 Subsetting by Rows (Filtering):

Subsetting by rows, also known as filtering, allows you to extract rows from a DataFrame that meet specific conditions.

- Filter with a Single Condition:
`dataframe[dataframe['column_name'] condition]`
- Filter with Multiple Conditions: You can filter for multiple conditions at once by using the bitwise "and" operator, \rightarrow `&`
`dataframe[(cond1) & (cond2)]`

```

1 import pandas as pd
2 # df: Dataframe from slide 09
3 # Filter rows with a single condition (Age > 20)
4 filtered_single = df[df['Age'] > 20]
5 print(filtered_single)
6 # Filter rows with multiple conditions (Age > 20 and Score >
   85)
7 filtered_multiple = df[(df['Age'] > 20) & (df['Score'] > 85)
   ]
8 print(filtered_multiple)

```

1.3.1 Filtering on Categorical Values

Filtering on categorical values allows you to subset rows based on column content.


- Single Category Filter: Extracts rows where a specific category matches
`dataframe[dataframe['categorical_col'] == 'category'].`
- Multiple Category Filter: Extracts rows where a column matches any value in a list,
`dataframe[dataframe['categorical_col'].isin(['cat1', 'cat2'])].`

1.3.2 Code Example: Filtering on Categorical Values

```
1 import pandas as pd
2 # Creating a sample DataFrame
3 data = {'Name': ['Alice', 'Bob', 'Charlie', 'David'],
4         'Department': ['HR', 'IT', 'Finance', 'HR'],
5         'Score': [88, 92, 85, 95]}
6 df = pd.DataFrame(data)
7 # Filter rows where 'Department' is 'HR'
8 filtered_single = df[df['Department'] == 'HR']
9 print(filtered_single)
10 # Filter rows where 'Department' is either 'HR' or 'IT'
11 filtered_multiple = df[df['Department'].isin(['HR', 'IT'])]
12 print(filtered_multiple)
```

Advance Operation With Pandas.

2. The Group By Method.




2.1 Group By Method - Introduction:

The Group By operation in pandas is a powerful tool for aggregating, transforming, or analyzing data. It follows the **Split-Apply-Combine** pattern:

1 Split:

- Divides data into groups based on values in one or more columns.
- Creates subgroups of the dataset where each subgroup has a common key or categor




```
result = data.groupby('col1')['col2'].sum()
```

2.2 Group By Method - Apply:

② Apply: Perform operations within each group. The Operation could be grouped to:

- Aggregation; Transformation and Filtration.



```
result = data.groupby('col1')['col2'].sum()
```

2.2.1 Group By Method - Apply - Aggregation:

② Apply: Perform operations within each group. The Operation could be grouped to:

(a) Aggregation: Aggregation computes summary statistics for each group.

- Purpose: Calculate metrics like mean, sum, max, etc., within each group.
- Syntax: `dataframe.groupby('column').agg(func)`

```
1 import pandas as pd
2 # Sample DataFrame
3 data = {'Category': ['A', 'B', 'A', 'B', 'A'],
4         'Value': [10, 20, 30, 40, 50]}
5 df = pd.DataFrame(data)
6 # Aggregation: Calculate mean for each group
7 grouped = df.groupby('Category')['Value'].mean()
8 print(grouped)
```


2.2.2 Group By Method - Apply - Transformation:

② Apply: Perform operations within each group. The Operation could be grouped to:

(b) Transformation: Transformation applies a function to transform data within each group.

- Purpose: Normalize or scale values within each group.
- Syntax: `dataframe.groupby('column').transform(func)`

```
1 import pandas as pd
2 # Sample DataFrame
3 data = {'Category': ['A', 'B', 'A', 'B', 'A'],
4         'Value': [10, 20, 30, 40, 50]}
5 df = pd.DataFrame(data)
6 # Transformation: Normalize values within each group
7 df['Normalized'] = df.groupby('Category')['Value'].
8     transform(lambda x: x / x.sum())
9 print(df)
```

2.2.3 Group By Method - Apply - Filtration:

② Apply: Perform operations within each group. The Operation could be grouped to:

(c) Filtration: Transformation applies a function to transform data within each group.

- Purpose: Exclude groups based on a condition.
- Syntax: `dataframe.groupby('column').filter(func)`

```

1 import pandas as pd
2 # Sample DataFrame
3 data = {'Category': ['A', 'B', 'A', 'B', 'A'],
4         'Value': [10, 20, 30, 40, 50]}
5 df = pd.DataFrame(data)
6 # Filtration: Keep groups where sum of values > 60
7 filtered = df.groupby('Category').filter(lambda x: x
8     ['Value'].sum() > 60)
9 print(filtered)


```

2.1 Group By Method - Introduction:

The Group By operation in pandas is a powerful tool for aggregating, transforming, or analyzing data. It follows the **Split-Apply-Combine** pattern:

3 Combine:

- Combines the results from each subgroup back into a single DataFrame or Series.
- Output can be a new DataFrame with group keys as the index or a modified dataset.



Getting Started with Data Visualizations.

3. What is Data Visualizations?




Image by : J. Ferrer – 7 steps to mastering Data Analysis [kDnuggets]

3.1 Data Visualization: Introduction

*The greatest value of a picture is when it forces
us to*

notice what we never expected to see.

— John Tukey

*Disclaimer: Data Visualization is not just about
the ability to create plots; it's about
understanding which plots to use and what insights
to draw from them.*

— Siman Giri

3.2 Data Visualization: Goals

- **Communicate(Explanatory)**

- Present data and ideas.
- Explain and inform.
- Provide evidence and support.
- Influence and persuade.

- **Analyze (Exploratory)**

- Explore the data.
- Assess a situation.
- Determine how to proceed.
- Decide what to do.

3.3 Effective Visualizations:

Followings are must for an effective visualizations:

- 1 Have a graphical integrity.
- 2 Keep it simple.
- 3 Use the right display.
- 4 Use color sensibly.

3.4 Tools for Visualizations:

Followings are must for an effective visualizations: Following three tools are the most popular tools used for **Data Visualizations and Exploration**. They are inter-mixable.

- Pandas Visualization module.
- Matplotlib
- Seaborn

```
1 import pandas as pd
2 import seaborn as sns
3 import matplotlib.pyplot as plt
4
```


Getting Started with Data Visualizations.

4. Pandas for Data Visualizations.




Image – R. Horvath – ReapPython.

4.1 Data Visualization with pandas

pandas offers built-in plotting capabilities powered by Matplotlib for quick and easy visualizations.

- Syntax: `dataframe.plot(kind='plot_type', ...)`
- Common plot types:
 - Line Plot
 - Bar Chart
 - Histogram
 - Scatter Plot
 - Box Plot

4.2 Line Plot Example

Line plots are useful for visualizing trends over time.


```
1 import pandas as pd
2 import matplotlib.pyplot as plt
3 # Sample Data
4 data = {'Month': ['Jan', 'Feb', 'Mar', 'Apr'],
5         'Sales': [200, 220, 250, 280]}
6 df = pd.DataFrame(data)
7 # Line Plot
8 df.plot(x='Month', y='Sales', kind='line', marker='o', title
9         ='Monthly Sales')
9 plt.show()
```



4.3 Barchart Example

Bar charts are effective for comparing categories.


```
1 # Sample Data
2 data = {'Category': ['A', 'B', 'C'],
3         'Values': [10, 20, 15]}
4 df = pd.DataFrame(data)
5 # Bar Chart
6 df.plot(x='Category', y='Values', kind='bar', title='
7         Category Comparison', color='skyblue')
8 plt.show()
```



4.4 Histogram Example

Histograms display the distribution of a single variable.


```
1 #import---
2 # Sample Data
3 data = {'Scores': [50, 60, 70, 75, 80, 85, 90, 95, 100]}
4 df = pd.DataFrame(data)
5 # Histogram
6 df['Scores'].plot(kind='hist', bins=5, title='Score
    Distribution', color='orange')
7 plt.show()
```



4.5 Scatter Plot Example

Scatter plots show relationships between two variables.


```
1 # Sample Data
2 data = {'Height': [150, 160, 170, 180],
3         'Weight': [50, 60, 70, 80]}
4 df = pd.DataFrame(data)
5 # Scatter Plot
6 df.plot(x='Height', y='Weight', kind='scatter', title='
7         Height vs Weight')
8 plt.show()
```



4.6 Box Plot Example

Box plots are used for visualizing the spread and outliers in data.

```
1 # Sample Data
2 data = {'Scores': [50, 60, 70, 75, 80, 85, 90, 95, 100,
3                  105]}
4 df = pd.DataFrame(data)
5 # Box Plot
6 df.boxplot(column='Scores')
7 plt.title('Score Distribution')
8 plt.show()
```



4.7 Comparison: Matplotlib vs. pandas

Feature	Matplotlib	pandas
Control	High (detailed customization)	Low to moderate (basic customization)
Ease of Use	More verbose and complex syntax	Simple and direct
Flexibility	Excellent for complex and multi-faceted plots	Good for straightforward plots
Customizable	Extensive, with access to every plot element	Limited to plot options in DataFrame


Table: Comparison of Matplotlib and pandas for Data Visualization

4.8 When to Use which?

- Use Matplotlib when you need precise control and complex customization for your plots.
- Use pandas for fast, simple plots when working directly with DataFrames, especially during initial data analysis.

Getting Started with Data Visualizations.

5. Matplotlib for Data Visualizations - A Revision.



5.1 Plotting Your First Figure

● Style:1

```
1 import matplotlib.pyplot as plt
2 days = ["Mon", "Tue", "Wed", "Thu", "Fri", "Sat", "Sun"]
3 steps_walked = [8934, 14902, 3409, 25672, 12300, 2023, 6890]
4 plt.plot(steps_walked)
5
```

● Style:2

```
1 import matplotlib.pyplot as plt
2 days = ["Mon", "Tue", "Wed", "Thu", "Fri", "Sat", "Sun"]
3 steps_walked = [8934, 14902, 3409, 25672, 12300, 2023,
4               6890]
5 plt.plot(days, steps_walked)
6 plt.show()
```

Observe the difference between above two outputs.

5.2 Anatomy of Matplotlib Figure.

- When working with data visualisation in Python, you'll want to have control over all aspects of your figure.
- In this section, you'll learn about the main components that make up a figure in Matplotlib.

Figure: Components of Matplotlib Figure



5.2.1 Anatomy of Matplotlib Figure.

Everything in Python is an object, and therefore, so is a Matplotlib figure. In fact, a Matplotlib figure is made up of several objects of different data types.

There are three main parts to a Matplotlib figure:

- **Figure:** This is the whole region of space that's created when you create any figure. The Figure object is the overall object that contains everything else.
- **Axes:** An Axes object is the object that contains the x-axis and y-axis for a 2D plot. Each Axes object corresponds to a plot or a graph. You can have more than one Axes object in a Figure, as you'll see later on in this Chapter.
- **Axis:** An Axis object contains one of the axes, the x-axis or the y-axis for a 2D plot.

5.3 Customising the plots

- Add a custom marker.

```

1 import matplotlib.pyplot as plt
2 days = ["Mon", "Tue", "Wed", "Thu", "Fri", "Sat", "Sun"]
3 steps_walked = [8934, 14902, 3409, 25672, 12300, 2023, 6890]
4 plt.plot(days, steps_walked, "o")
5 plt.show()
6

```

The third argument in `plot()` now indicates what marker you'd like to use. The string "o" represents filled circles.

Cautions: Please consult matplotlib documentation for updated version and type of marker available.

5.3.1 Customising the plots: Titles and labels

- Adding titles, labels and legends.

```

1 import matplotlib.pyplot as plt
2 days = ["Mon", "Tue", "Wed", "Thu", "Fri", "Sat", "Sun"]
3 steps_walked = [8934, 14902, 3409, 25672, 12300, 2023, 6890]
4 steps_last_week = [9788, 8710, 5308, 17630, 21309, 4002, 5223]
5 plt.plot(days, steps_walked, "o-g")
6 plt.plot(days, steps_last_week, "v--m")
7 plt.title("Step count | This week and last week")
8 plt.xlabel("Days of the week")
9 plt.ylabel("Steps walked")
10 plt.grid(True)
11 plt.legend(["This week", "Last week"])
12 plt.show()
13

```

Observe the output.

5.3.2 Creating Subplots

```
1 def f(t):  
2     return np.exp(-t) * np.cos(2*np.pi*t)  
3 t1 = np.arange(0.0, 5.0, 0.1)  
4 t2 = np.arange(0.0, 5.0, 0.02)  
5 plt.figure()  
6 plt.subplot(211)  
7 plt.plot(t1, f(t1), 'bo', t2, f(t2), 'k')  
8 plt.subplot(212)  
9 plt.plot(t2, np.cos(2*np.pi*t2), 'r--')  
10 plt.show()
```

Observe and find what are the arguments for `plt.subplot()`.

Towards Worksheet - 3.
Thank You.