HemaSmart: Integration of Dynamic Programming, Graph Theory, and Relational Databases in Modern Blood Supply Chain Management

A PROJECT REPORT

Submitted by

Aadi Jain [Reg.No:RA2411030030055]
Nandini Sharma [Reg.No:RA2411030030056]
Daksh Bansal [Reg.No:RA2411030030064]

Under the guidance of

Dr. Anirudha Gaikwad
(Assistant Professor, Department of Computer Science & Engineering)

In partial fulfillment for the award of the degree of

BACHELOR OF TECHNOLOGY

In

COMPUTER SCIENCE & ENGINEERING

Of

FACULTY OF ENGINEERING AND TECHNOLOGY

Delhi NCR Campus, Modinagar, Ghaziabad (U.P.)

APRIL 2026

SRM INSTITUTE OF SCIENCE &TECHNOLOGY

(Under Section 3 of UGC Act, 1956)

BONAFIDE CERTIFICATE

Certify that this project report titled "**HemaSmart: Integration of Dynamic Programming, Graph Theory, and Relational Databases in Modern Blood Supply Chain Management is the Bonafide work of (Aadi jain RA2411030030055), (Nandini Sharma RA2411030030056, (Daksh Bansal RA2411030030064)** , who has completed the project work under my supervision. Certified further, that apparently the work detailed thus shapes no other task report or paper based on which a degree or grant was given on a prior event on this or some other candidate.

SIGNATURE
(Dr. Anirudha Gaikwad)
GUIDE
Assistant Professor
Dept. of Computer Science & Engineering

SIGNATURE
(Dr. Neelam Singh)
HEAD OF THE DEPARTMENT
Associate Professor
B.Tech Computer Science & Engineering

ACKNOWLEDGEMENTS

We would like to thank our guide, Mr. Anirudha Gaikwad, for his valuable guidance, constant encouragement, personal caring, timely aid and offering timely assistance as well as providing us a wonderful environment in which to explore ourselves. Throughout the project, he has extended bright and agreeable assistance to us, despite his hectic schedule.

We would also want to express our gratitude to Dr. Neelam Singh, Professor and Head, Department of B.Tech Computer Science, SRM Institute of Science and Technology (Delhi-NCR Campus), for her helpful recommendations and support during the project's duration. We would like to express our gratitude to the personnel and students at the SRM Institute of Science and Technology's Computer Science and Engineering Department for their assistance during our investigation. Finally, we want to express our gratitude to our parents, family, and friends for their unwavering love, constant assistance, and unwavering support.

Table of Contents:

1. Title

2. Abstract

3. Introduction

4. Technical Specifications

- 4.1 Technology Stack Definition
- 4.2 Hardware and Environment Requirements
- 4.3 Step-by-Step Implementation Guide for Local Deployment
    - Step 1: Database Initialization and Schema Creation
    - Step 2: Backend Application Initialization (Node.js)
    - Step 3: Frontend Application Initialization (React.js)

5. Architecture Overview

- 5.1 Three-Tier Logical Architecture
- 5.2 Data Flow and Entity Interactions (DFD Analysis)
- 5.3 Implementation of Specialized Architectural Features

6. Operation and Working

- 6.1 Donor Screening and Eligibility Verification
- 6.2 Blood Collection, Testing, and Component Separation
- 6.3 Cold Chain Logistics and the Blood Expiry Tracker
- 6.4 Emergency Priority Queues and Smart Recommendation

7. Case Example: Algorithmic and Analytical Integration

- 7.1 Spatial Optimization: Dijkstra's Algorithm for Nearest Blood Bank Routing
- 7.2 Capacity Optimization: The 0/1 Knapsack Algorithm
- 7.3 Predictive Analytics: Demand Forecasting

8. Applications

9. Conclusion

10. References

Comprehensive Case Study: HemaSmart- An Intelligent Blood Bank Management System Integrating Dynamic Programming, Graph Theory, and Relational Databases

2. Abstract

The management of blood and its derivative components represents one of the most complex logistical and computational challenges in modern healthcare infrastructure. Blood is a highly perishable, life-saving biological resource that cannot be artificially synthesized, making the efficiency of its supply chain a matter of critical public health and emergency response. This comprehensive research report investigates the architectural, operational, and algorithmic paradigms underpinning modern, intelligent Blood Bank Management Systems (BBMS). Moving beyond traditional, digitized ledger systems, contemporary BBMS architectures integrate three-tier web frameworks with advanced operations research methodologies and Database Management System (DBMS) concepts to solve real-world spatiotemporal mismatches between blood supply and demand.

This report provides an exhaustive blueprint for constructing and deploying a scalable BBMS utilizing a modern technology stack combined with a MySQL relational database. It explicitly addresses the integration of ten advanced functional modules: Smart Donor Recommendation, Emergency Priority Queues, Nearest Blood Bank Routing, Expiry Tracking, Demand Prediction, Automated Notifications, Storage Optimization, Geospatial Heatmaps, Eligibility Verification, and Donor Gamification. Furthermore, the operational workflows—encompassing donor screening, component separation, cold chain logistics, and clinical crossmatching—are systematically evaluated. To demonstrate the integration of Design and Analysis of Algorithms (DAA) concepts within these systems, the report explores three primary algorithmic case examples in depth: the application of Dijkstra's Algorithm for emergency routing; the adaptation of the 0/1 Knapsack problem via Dynamic Programming for optimizing inventory capacity; and time-series forecasting to predict inventory requirements. By synthesizing software engineering, data structures, and clinical logistics, the analysis reveals how data-driven BBMS architectures fundamentally reduce component wastage, accelerate emergency response times, and ensure equitable access to life-saving transfusion therapies.

3. Introduction

Blood transfusion is an indispensable intervention in contemporary clinical medicine, essential for trauma resuscitation, complex surgical procedures, oncology treatments, and the management of chronic hematological disorders. Statistical analyses indicate a relentless, high-volume demand on global healthcare infrastructure; in the United States alone, a patient requires blood every two seconds. Despite significant advancements in medical technology, human blood remains a resource that is entirely dependent on the altruism of volunteer donors. Consequently, the blood supply chain is inherently fragile, characterized by stochastic supply patterns, highly variable clinical demand, and strict temporal constraints dictated by the perishability of biological tissues.

Historically, blood banks operated as decentralized, paper-based entities or relied on rudimentary, localized digital spreadsheets. These legacy systems suffered from severe operational bottlenecks, including manual data entry errors, lack of real-time inventory visibility, inability to rapidly trace donor-recipient pathogen transmission, and significant delays in cross-institutional blood sharing. Such inefficiencies inevitably led to high rates of component wastage—often due to expiration—while simultaneously experiencing acute shortages of rare blood types during emergencies.

The advent of the web-based Blood Bank Management System (BBMS) represents a paradigm shift from localized repositories to integrated, intelligent supply chain networks. A modern BBMS is engineered to coordinate the multifaceted processes of donor recruitment, serological testing, component fractionation, inventory tracking, and clinical distribution. However, the current frontier of BBMS development extends far beyond simple digitization. Intelligent systems now embed sophisticated mathematical models, dynamic data structures, and machine learning algorithms to achieve dynamic equilibrium within the supply chain.

This report outlines the architecture and implementation of a next-generation BBMS designed to overcome these historical limitations. The proposed system integrates ten core intelligent features:

1. **Smart Donor Recommendation System:** Algorithmic matching of patients to the most compatible and geographically proximate donors.
2. **Emergency Mode (Priority Queue):** Implementation of heap data structures to ensure critical trauma requests bypass standard queues.
3. **Nearest Blood Bank Finder:** Utilization of graph algorithms to locate alternative inventory when local supplies are depleted.
4. **Blood Expiry Tracker:** Automated monitoring of component shelf-life to enforce strict First-In-First-Out (FIFO) utilization.
5. **Demand Prediction:** Statistical analysis of historical data to anticipate seasonal supply deficits.
6. **Auto Notification to Donors:** Automated communication protocols triggered by minimum inventory thresholds.
7. **Blood Storage Optimization:** Application of combinatorial optimization logic (Knapsack) to maximize refrigerated transport efficiency.

8. **City-wise Donor Heatmap:** Geospatial visualization of donor density to target localized blood drives.
9. **Donor Eligibility Checker:** Enforcement of physiological and temporal constraints (e.g., the 90-day donation interval rule).
10. **Top Donors Leaderboard:** Gamification metrics tracking total donations to foster community engagement and retention.

The subsequent sections of this report provide a granular examination of the architecture, operational protocols, technical implementation steps, and computational algorithms required to build and deploy this state-of-the-art system on a local computing environment using DBMS and DAA principles.

4. Technical Specifications

The deployment of a robust, enterprise-grade BBMS necessitates a carefully engineered synthesis of hardware and software components. The system must guarantee high availability, strict data security protocols to protect patient confidentiality, and low-latency performance to facilitate real-time emergency requests.

4.1 Technology Stack Definition

To achieve the desired functionality, responsiveness, and scalability, a modern web technology stack paired with a robust relational database is required.

- **Frontend (Presentation Layer):** React.js (with HTML5, CSS3, and Tailwind CSS/Bootstrap). React's component-based architecture and virtual DOM ensure highly responsive user interfaces, crucial for rendering real-time elements like the City-wise Donor Heatmap and the Top Donors Leaderboard.
- **Backend (Application Layer):** Node.js utilizing the Express.js framework. Node.js provides a non-blocking, event-driven runtime environment ideal for handling concurrent asynchronous requests, such as dispatching automated SMS notifications to donors while simultaneously processing complex DAA routing algorithms.
- **Database (Data Layer):** MySQL. A relational DBMS is strictly required to manage the highly interconnected nature of blood banking data. MySQL enforces referential integrity across donors, donations, laboratory tests, and hospital requests, ensuring ACID (Atomicity, Consistency, Isolation, Durability) compliance which is non-negotiable in healthcare informatics.

4.2 Hardware and Environment Requirements

For local deployment, development, and testing, the following specifications are recommended to ensure optimal compilation and execution times :

- **Processor:** Minimum dual-core CPU (Intel Core i5 or equivalent), though a quad-core processor is recommended for executing intensive routing and optimization algorithms.
- **Memory:** Minimum 8 GB RAM (16 GB recommended to smoothly run the Node environment, React development server, and MySQL daemon simultaneously).
- **Storage:** 50 GB of available disk space, preferably SSD for faster database read/write I/O operations.
- **Software Dependencies:** Node.js (v16.x or higher), npm (Node Package Manager), MySQL Server (v8.0 or higher), and a database management tool such as MySQL Workbench or phpMyAdmin.

4.3 Step-by-Step Implementation Guide for Local Deployment

To instantiate the intelligent BBMS on a local machine, the following sequential implementation

protocol must be executed. This guide bridges theoretical architecture with practical deployment.

Step 1: Database Initialization and Schema Creation

The foundation of the system is the MySQL database. Based on optimal relational design principles and the specific entities required for this project , the schema must be meticulously constructed.
Launch MySQL Workbench, connect to the local instance, and execute the following Data Definition Language (DDL) scripts to establish the bloodbank_db schema:

```
CREATE DATABASE bloodbank_db;
USE bloodbank_db;

-- 1. City Table (For Geographic Heatmaps and Routing)
CREATE TABLE city (
    city_id INT AUTO_INCREMENT PRIMARY KEY,
    city_name VARCHAR(100) NOT NULL,
    latitude DECIMAL(10, 8),
    longitude DECIMAL(11, 8)
);

-- 2. Blood Bank Master Table
CREATE TABLE bloodbank (
    bank_id INT AUTO_INCREMENT PRIMARY KEY,
    bank_name VARCHAR(100) NOT NULL,
    address VARCHAR(200),
    contact VARCHAR(15),
    city_id INT,
    FOREIGN KEY (city_id) REFERENCES city(city_id)
);

-- 3. Hospital Table
CREATE TABLE hospital (
    hospital_id INT AUTO_INCREMENT PRIMARY KEY,
    hospital_name VARCHAR(100) NOT NULL,
    address VARCHAR(200),
    contact VARCHAR(15),
    city_id INT,
    total_blood_demand INT DEFAULT 0,
    FOREIGN KEY (city_id) REFERENCES city(city_id)
);

-- 4. User Table (Authentication and Role Management)
CREATE TABLE user (
    user_id INT AUTO_INCREMENT PRIMARY KEY,
    username VARCHAR(50) UNIQUE NOT NULL,
    password VARCHAR(255) NOT NULL,
    role ENUM('admin', 'donor', 'hospital') NOT NULL
```

```
);

-- 5. Donor Table (Includes Leaderboard and Eligibility Tracking)
CREATE TABLE donor (
    donor_id INT AUTO_INCREMENT PRIMARY KEY,
    user_id INT,
    name VARCHAR(100) NOT NULL,
    blood_group VARCHAR(5) NOT NULL,
    contact VARCHAR(15),
    email VARCHAR(100),
    last_donation_date DATE,
    city_id INT,
    total_donations_count INT DEFAULT 0,
    FOREIGN KEY (user_id) REFERENCES user(user_id),
    FOREIGN KEY (city_id) REFERENCES city(city_id)
);

-- 6. Blood Stock Table (For Expiry Tracking)
CREATE TABLE bloodstock (
    stock_id INT AUTO_INCREMENT PRIMARY KEY,
    bank_id INT,
    blood_group VARCHAR(5) NOT NULL,
    units_available INT DEFAULT 0,
    expiry_date DATE,
    FOREIGN KEY (bank_id) REFERENCES bloodbank(bank_id)
);

-- 7. Blood Request Table (For Emergency Priority Queue)
CREATE TABLE bloodrequest (
    request_id INT AUTO_INCREMENT PRIMARY KEY,
    patient_id INT,
    bank_id INT,
    blood_group VARCHAR(5) NOT NULL,
    units_required INT NOT NULL,
    request_date DATETIME DEFAULT CURRENT_TIMESTAMP,
    priority_level INT NOT NULL, -- 1=Routine, 2=Urgent, 3=Emergency
    status ENUM('Pending', 'Fulfilled', 'Rejected') DEFAULT 'Pending',
    FOREIGN KEY (bank_id) REFERENCES bloodbank(bank_id)
);

-- 8. Blood Compatibility Matrix Table
CREATE TABLE bloodcompatibility (
    compatibility_id INT AUTO_INCREMENT PRIMARY KEY,
    from_blood_group VARCHAR(5) NOT NULL,
    to_blood_group VARCHAR(5) NOT NULL
);
```

Step 2: Backend Application Initialization (Node.js)

Open a terminal interface and construct the backend directory structure. This layer will house the DAA logic and API endpoints.

```
mkdir bbms-backend
cd bbms-backend
npm init -y
npm install express mysql2 cors dotenv bcryptjs jsonwebtoken
```

Create an index.js file to establish the Express server and connect to the MySQL instance securely:

```
const express = require('express');
const mysql = require('mysql2/promise');
const cors = require('cors');
require('dotenv').config();

const app = express();
app.use(cors());
app.use(express.json());

// MySQL Connection Pool
const pool = mysql.createPool({
    host: 'localhost',
    user: 'root',
    password: 'your_mysql_password',
    database: 'bloodbank_db',
    waitForConnections: true,
    connectionLimit: 10,
    queueLimit: 0
});

// Health Check Endpoint
app.get('/api/health', async (req, res) => {
    try {
        const [rows] = await pool.query('SELECT 1');
        res.status(200).json({ status: 'Connected to MySQL DBMS
successfully' });
    } catch (error) {
        res.status(500).json({ error: 'Database connection failed' });
    }
});

const PORT = process.env.PORT |

| 5000;
app.listen(PORT, () => {
    console.log(`BBMS Backend Server executing on port ${PORT}`);
});
```

Step 3: Frontend Application Initialization (React.js)

In a separate terminal instance, generate the frontend architecture:

```
npx create-react-app bbms-frontend
cd bbms-frontend
npm install axios react-router-dom chart.js react-chartjs-2 leaflet
react-leaflet
npm start
```

The leaflet library will be explicitly used to render the City-wise Donor Heatmap, while chart.js will visualize the Demand Prediction graphs. By following these three initialization steps, the local development environment is fully operational, establishing the conduit between the user interface, the application logic, and the relational database.

5. Architecture Overview

The structural integrity of an intelligent BBMS relies on a highly modular design. By decoupling the user interface from the business logic and the data storage mechanisms, the system achieves maximum scalability, maintainability, and security.
!(https://via.placeholder.com/800x400.png?text=3-Tier+Architecture+Diagram+for+Intelligent+BBMS) *Illustration: The logical separation of concerns within the BBMS, depicting the flow of data from the client interface through the processing APIs to the persistent relational storage.*

5.1 Three-Tier Logical Architecture

The architecture maps directly to the technology stack defined previously, structured into three distinct tiers :

1. **Presentation Tier (Client/UI Layer):** This is the interactive interface accessed by disparate user roles.
    - *Donors* utilize this layer to view their donation history, check the Leaderboard, and update geographic data.
    - *Hospitals* interact with customized dashboards to submit bloodrequests and monitor real-time inventory indices.
    - *Administrators* access geospatial Heatmaps and statistical Demand Prediction graphs. The presentation layer performs initial input sanitization and utilizes RESTful API calls to communicate with the middle tier.
2. **Application Tier (Business Logic Layer):** Serving as the computational core, this layer executes the system's intelligence. It encompasses the DAA modules, running the Dijkstra algorithm for the Nearest Blood Bank Finder, executing the Knapsack algorithm for Storage Optimization, and managing the Priority Queue logic for emergency requests. Furthermore, it handles authentication, data validation, and the execution of automated triggers (such as the Auto Notification to Donors when stock dips below critical thresholds).
3. **Data Tier (Database Layer):** The persistent storage foundation. Utilizing MySQL, this tier relies on structured indexing to optimize query execution times. The database ensures that concurrent transactions—such as multiple hospitals requesting the same unit of rare AB-negative blood simultaneously—are handled via strict locking mechanisms to prevent double-booking and ensure data integrity.

5.2 Data Flow and Entity Interactions (DFD Analysis)

The movement of data through the BBMS is formally modeled using Data Flow Diagrams (DFDs), which illustrate how external entities interact with internal processes.

- **Level 0 Context Diagram:** The BBMS acts as a central processing node. The primary external entities are the *Donor*, the *Recipient/Hospital*, and the *Administrator*. Data flowing into the system includes registration details, blood requisition forms, and physical

component logs. Data flowing out encompasses SMS notifications, appointment confirmations, and analytical reports.

- **Level 1 DFD (Sub-system Breakdown):** The central node is deconstructed into specific functional modules: Donor Management, Inventory Management, Requisition Processing, and Analytical Reporting. For example, a hospital submits a request, which is passed to the Requisition Processing module. This module queries the Inventory Management data store. If a match is found, an issuance receipt is generated; if not, the query is passed to the Nearest Blood Bank routing module.

5.3 Implementation of Specialized Architectural Features

The architecture specifically accommodates the user's requested advanced features:

- **City-wise Donor Heatmap:** The Presentation tier utilizes geographic mapping libraries. It queries the Application tier, which executes a SELECT city_id, COUNT(*) FROM donor GROUP BY city_id statement against the Data tier. The application tier translates these IDs into latitudinal and longitudinal coordinates, passing them to the frontend to render thermal density overlays.
- **Top Donors Leaderboard:** A highly optimized view is generated by querying the total_donations_count attribute within the donor table. The application tier sorts this data in descending order (ORDER BY total_donations_count DESC LIMIT 10) and serves it to the frontend, gamifying the donation process and encouraging donor retention.

6. Operation and Working

The operation of a BBMS closely mirrors the physical lifecycle of a blood unit, transforming a biological donation into a standardized, tracked, and clinical-grade therapeutic product while enforcing rigorous medical protocols.
![(https://via.placeholder.com/800x400.png?text=Blood+Donation+Lifecycle+Process+Flow)
Illustration: The sequential transition of blood from donor screening through laboratory processing, storage optimization, and ultimate clinical transfusion.

6.1 Donor Screening and Eligibility Verification

The operational workflow commences when a prospective donor accesses the BBMS. Before an appointment is confirmed, the system invokes the **Donor Eligibility Checker**. According to physiological safety standards, whole blood donors must observe a minimum recovery interval to replenish iron stores and erythrocyte counts. The BBMS enforces the **90-day rule** (or 56 days depending on regional specificities) algorithmically.
When a user attempts to schedule a donation, the logic tier executes a date-difference calculation:

```
// Logic Tier: 90-Day Eligibility Rule Checker
const checkEligibility = (lastDonationDate) => {
    if (!lastDonationDate) return true; // First-time donor
    const msInDay = 24 * 60 * 60 * 1000;
    const daysSinceLast = Math.floor((new Date() - new
Date(lastDonationDate)) / msInDay);
    return daysSinceLast >= 90;
};
```

If the function evaluates to false, the system automatically defers the appointment and schedules an **Auto Notification** to email or SMS the donor once they become eligible, thereby maintaining high retention rates without manual administrative oversight.

6.2 Blood Collection, Testing, and Component Separation

Upon successful phlebotomy, a single unit of whole blood is collected. The physical bag and associated testing tubes are assigned a unique cryptographic barcode generated by the BBMS to maintain an unbroken Chain of Custody.
The blood undergoes stringent serological testing and Nucleic Acid Testing (NAT) for infectious diseases (e.g., HIV, Hepatitis B/C, Syphilis). Concurrently, the whole blood is placed in a centrifuge for fractionation, separating it into distinct therapeutic components to maximize utility.

6.3 Cold Chain Logistics and the Blood Expiry Tracker

Once deemed safe, the components are instantiated within the bloodstock table. Blood components exhibit extreme thermal sensitivity and drastically different lifespans, necessitating rigorous cold chain management.

Blood Component	Storage Temperature	Maximum Shelf Life	Clinical Utilization
Red Blood Cells (RBCs)	1°C to 6°C (Refrigerated)	35 to 42 Days	Trauma, surgery, acute anemia.
Platelets	20°C to 24°C (Continuous Agitation)	5 to 7 Days	Oncology, bleeding disorders.
Plasma / Cryoprecipitate	-18°C or colder (Frozen)	12 Months	Burn victims, shock, coagulation factors.

Table 1: Storage Parameters and Lifespans governed by the BBMS Expiry Tracker.

The **Blood Expiry Tracker** is implemented as a continuous daemon (cron job) running on the Node.js server. It perpetually scans the expiry_date column in the database. When components—particularly highly perishable platelets—approach within 48 hours of expiration, the system flags them in the administrative dashboard and prioritizes their issuance using strict First-In-First-Out (FIFO) rules, dramatically reducing biological wastage.

6.4 Emergency Priority Queues and Smart Recommendation

When a hospital registers a transfusion requirement, the request enters the system. To satisfy the **Emergency Mode** requirement, the Application Tier utilizes a Priority Queue (often implemented via a Max-Heap data structure). Requests flagged with priority_level = 3 (Emergency/Trauma) instantly bypass standard elective surgery requests (priority_level = 1), ensuring that computational resources and blood routing are dedicated to preserving life in critical moments.

Simultaneously, the **Smart Donor Recommendation System** analyzes the request. If the required blood type is entirely depleted across the network, the system queries the donor table. It utilizes the **Blood Compatibility Matrix** to identify not just exact matches, but universally compatible donors (e.g., O-negative donors for any recipient).

Patient Blood Type	Compatible RBC Donor Types	Compatible Plasma Donor Types
O (Universal Donor)	O	O, A, B, AB
A	A, O	A, AB
B	B, O	B, AB
AB (Universal Recipient)	AB, A, B, O	AB

Table 2: Clinical Crossmatch Matrix utilized by the Smart Recommendation Algorithm.

The system cross-references this matrix with the donor's city_id to locate eligible individuals within immediate geographical proximity, subsequently dispatching automated SMS alerts requesting an emergency donation.

7. Case Example: Algorithmic and Analytical Integration

The defining characteristic of an intelligent BBMS is its departure from basic CRUD (Create, Read, Update, Delete) operations, deeply incorporating Design and Analysis of Algorithms (DAA) concepts to optimize spatial routing, volumetric capacity, and temporal forecasting.

7.1 Spatial Optimization: Dijkstra's Algorithm for Nearest Blood Bank Routing

In critical trauma scenarios, the time required to transport a specific blood unit from a regional hub to a localized hospital directly determines patient survivability. The **Nearest Blood Bank Finder** module integrates Geospatial Information Systems (GIS) with Dijkstra's Algorithm to solve the Single-Source Shortest Path (SSSP) problem.

Mathematical Formulation: Consider a weighted directed graph G(V, E), where V represents a set of vertices (hospitals and regional blood centers) and E represents the road network connecting them. Each edge (u, v) \in E possesses a non-negative weight w(u, v) representing the real-world travel distance or dynamic travel time. The algorithm initializes the distance to the source node (the patient's hospital) as d(s) = 0 and all other nodes as d(v) = \infty. Through an iterative process of edge relaxation, the algorithm updates the shortest distance to each adjacent node:

Utilizing a min-priority queue, the algorithm efficiently resolves the shortest path with a worst-case time complexity of \Theta(|E| + |V| \log |V|).

Practical Case Study - Maharashtra Blood Logistics: Consider an emergency at a hospital in Pune requiring AB-negative blood, which is locally depleted. The system must locate the nearest hub containing the inventory. The graph maps real-world distances:

Source Node	Destination Node	Edge Weight (Distance)
Pune	Mumbai	145 km
Pune	Nashik	202 km
Pune	Aurangabad	214 km
Pune	Kolhapur	233 km

Table 3: Representative edge weights for a geographic blood routing graph in Maharashtra.

The Dijkstra module mathematically proves that Mumbai provides the optimal logistical route. Advanced implementations of this algorithm, such as Time-Based Dijkstra's Routing Algorithm (TDRA), further dynamically adjust edge weights based on live traffic congestion data, ensuring the transport vehicle avoids delays and preserves the cold chain integrity during transit.

7.2 Capacity Optimization: The 0/1 Knapsack Algorithm

The transportation of blood components from centralized processing hubs to local hospitals—particularly in mobile refrigerated vans or emerging drone delivery

payloads—presents a classic combinatorial resource allocation challenge. Capacity is strictly limited by volume or weight, yet the clinical urgency of differing components varies drastically. The **Blood Storage Optimization** module solves this utilizing the 0/1 Knapsack Algorithm via Dynamic Programming.

Algorithmic Logic: Let W be the total capacity of the refrigerated transport unit. We have n requested blood units available for transport. Each unit i has a physical volume w_i and a dynamically assigned clinical value v_i. The value v_i is computationally derived from a composite score: the rarity of the blood type, the priority level of the hospital request, and the inverse of its remaining shelf life (prioritizing the transport of platelets that will expire within 48 hours to prevent wastage). The objective is to maximize the total clinical value of the transported payload without exceeding the physical capacity limit.

The Application Tier resolves this NP-complete problem by constructing a 2D DP matrix where the state transition is defined as:

Implementation Code Snippet (Node.js/JavaScript):

```
// DAA Module: 0/1 Knapsack for Blood Storage Optimization
function optimizeBloodTransport(clinicalValues, volumes, maxCapacity)
{
    const n = clinicalValues.length;
    // Initialize 2D DP Array with zeros
    let dp = Array(n + 1).fill().map(() => Array(maxCapacity +
1).fill(0));

    for (let i = 1; i <= n; i++) {
        for (let w = 1; w <= maxCapacity; w++) {
            if (volumes[i - 1] <= w) {
                // Maximize utility by including or excluding the
current blood unit
                dp[i][w] = Math.max(
                    dp[i - 1][w],
                    clinicalValues[i - 1] + dp[i - 1][w - volumes[i -
1]]
                );
            } else {
                dp[i][w] = dp[i - 1][w];
            }
        }
    }
    return dp[n][maxCapacity]; // Returns maximized clinical value
payload
}

// Example Execution: Transporting 3 units with varying clinical
scores and volumes
const clinicalValues = ; // Priority score derived from BBMS logic
const volumes = ;          // Volumetric space required in cooler
const maxCapacity = 50;

console.log("Optimized Payload Value:",
```

```
optimizeBloodTransport(clinicalValues, volumes, maxCapacity));
```

By mathematically tying the perishable urgency of blood to volumetric constraints, this logic fundamentally shifts inventory logistics from basic sequential loading to active, algorithmic triage.

7.3 Predictive Analytics: Demand Forecasting

The disparity between blood supply and demand is notoriously exacerbated by seasonal trends. Supply routinely plummets during summer vacations, winter holidays, and severe weather events, while demand may spike concurrently. The **Demand Prediction** module employs statistical time-series forecasting, utilizing models such as the Seasonal Autoregressive Integrated Moving Average (SARIMA).
![(https://via.placeholder.com/800x400.png?text=Seasonal+Blood+Demand+and+Supply+Trends+Graph) *Graph Description: Time-series analysis illustrating cyclical deficits in blood supply during holiday months, contrasting with relatively stable baseline clinical demand.*
The SARIMA model, designated as (p, d, q) \times (P, D, Q)_s, accounts for autoregressive dynamics (p), differencing for data stationarity (d), moving averages (q), and the repeating seasonal cycle (s).
Quantitative Results: Analyses evaluating the integration of SARIMA into blood bank forecasting have demonstrated exceptional improvements over traditional rudimentary estimations. Comparative evaluations show significant reductions in the Mean Absolute Percentage Error (MAPE):

Forecasting Method	Average MAPE (Error Rate)	Suitability for BBMS
Simple Average	24.01%	Poor (Fails to capture seasonality)
Ratio-to-Trend	27.08%	Poor (Overestimates linear growth)
SARIMA Model	**18.59% (to <13%)**	**Excellent (Captures complex cyclical fluctuations)**

Table 4: Comparative error rates of forecasting models predicting blood component demand.
The operational implication of this enhanced accuracy is a measurable reduction in component wastage. Implementing these forecasts allows administrators to adjust Collection-to-Transfusion (C/T) ratios proactively. Case studies verify that forecasting-driven inventory management can reduce total monthly wastage rates by over 35%, ensuring a resilient healthcare supply chain even amidst systemic disruptions.

8. Applications

The integration of these ten intelligent features and advanced DAA algorithms within Blood Bank Management Systems has catalyzed transformative applications across the broader healthcare landscape:

1. **Disaster and Mass Casualty Management:** In the wake of natural disasters or systemic shocks (such as the COVID-19 pandemic), the sudden surge in blood demand typically overwhelms local infrastructure. A cloud-enabled BBMS utilizing dynamic Dijkstra routing and real-time inventory visibility allows for the immediate, coordinated redistribution of blood products from unaffected regional centers directly to the crisis zone.
2. **Eradication of Clinical Adverse Events:** The integration of automated barcode scanning, hardcoded ABO compatibility matrices, and strict algorithmic enforcement of shelf-life significantly diminishes the incidence of human transcription errors. By ensuring that the correct patient receives a thermally preserved, compatible product, the BBMS directly lowers the risk of fatal hemolytic transfusion reactions and bacterial sepsis.
3. **Equitable Rural Healthcare Logistics:** Utilizing algorithms like the 0/1 Knapsack in conjunction with emerging delivery vectors—such as drone technology—allows BBMS networks to autonomously configure optimal payloads for rapid delivery to remote, inaccessible clinics where maintaining a fully stocked local blood bank is economically unviable.
4. **Data-Driven Public Health Policy:** The aggregation of vast amounts of epidemiological data empowers national health ministries to conduct high-level audits. By analyzing forecasting trends and geographic Heatmaps, authorities can deploy highly targeted donor recruitment campaigns and optimize the allocation of financial resources toward blood bank infrastructure in empirically identified deficit zones.

9. Conclusion

The evolution of the Blood Bank Management System from a passive digital repository to an intelligent, predictive, and actively routing logistical platform represents a watershed achievement in healthcare informatics. The comprehensive architecture outlined in this report—spanning a secure, three-tier Node/React framework to a normalized MySQL relational database—provides the necessary foundation to manage the immense complexities of the blood supply chain seamlessly.

However, the true efficacy of this proposed system is realized through the integration of advanced DBMS and DAA concepts. The deployment of Dijkstra's Algorithm fundamentally reshapes emergency distribution, guaranteeing that physical transit times are minimized and cold chain integrity is protected during critical trauma scenarios. The mathematical precision of the 0/1 Knapsack algorithm provides an unparalleled solution to the persistent challenge of maximizing the clinical utility of perishable components within constrained mobile transportation networks. Furthermore, the application of sophisticated time-series forecasting, automated donor notification loops, and geographic heatmaps allows healthcare providers to transcend reactive crisis management.

By computationally harmonizing the altruistic availability of donors with the acute physiological demands of patients, the intelligent BBMS ensures that the critical pipeline of transfusion medicine remains unbroken, structurally equitable, and exceptionally efficient.

10. References

All empirical data, architectural models, operational workflows, algorithmic methodologies, and statistical forecasting metrics detailed within this report are synthesized from extensive peer-reviewed literature, systematic operational data, and systemic reviews. In accordance with the stylistic conventions of this analytical report, the primary references have been seamlessly integrated directly into the narrative prose and tabular data, cited inline utilizing their corresponding bracketed alphanumeric source identifiers (e.g.). This approach grounds the qualitative reasoning and mathematical models firmly in established clinical and software engineering research without necessitating a redundant concluding bibliography.

Works cited

1. Local Blood Supply Chain Optimization: A Case Study - Brieflands, https://brieflands.com/journals/amhsr/articles/102880 2. Design and Implementation of a Scalable, Real-Time, Web-Based Blood Bank Management System - ResearchGate, https://www.researchgate.net/publication/399814839_Design_and_Implementation_of_a_Scalable_Real-Time_Web-Based_Blood_Bank_Management_System_Architecture_Features_and_Performance_Analysis/fulltext/6969ee695cc49c35ce7e8c0f/Design-and-Implementation-of-a-Scalable-Real-Time-Web-Based-Blood-Bank-Management-System-Architecture-Features-and-Performance-Analysis.pdf?origin=scientificContributions 3. Blood Donation Cycle | Vitalant, https://www.vitalant.org/blog/blood-donation-basics/blood-donation-cycle 4. Saving Lives with Data: How Blood Supply Chain Optimization Reduces Shortages by 7% | Atlantis Press, https://www.atlantis-press.com/article/125987033.pdf 5. Blood Bank Inventory Management Analysis - Skemman, https://skemman.is/bitstream/1946/22336/1/ElisabetEdda.pdf 6. Blood Bank Management System - International Journal of Science Engineering and Technology, https://www.ijset.in/wp-content/uploads/IJSET_V9_issue3_260.pdf 7. Using Interactive Visual Analytics to Optimize Blood Products Inventory at a Blood Bank - DCSI, https://dcsi.cs.dal.ca/wp-content/uploads/2021/07/33.pdf 8. An AI-Driven Blood Bank Donation and Management System: An Integrated Framework for Matching, Prediction, Anomaly Detection, a, https://ijisrt.com/assets/upload/files/IJISRT25DEC1102.pdf 9. Inventory management practices in the blood bank of an institute of national importance in India - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC8884319/ 10. Blood Bank Management System - ER Publications, https://www.erpublications.com/uploaded_files/download/a-panhalkar-prof-s-shaikh-n-shriram-p-more-k-patil_IchUo.pdf 11. Full article: The Impact of Age Group in Hierarchical Forecasting of Monthly Blood Donations in Zimbabwe - Taylor & Francis, https://www.tandfonline.com/doi/full/10.2147/RMHP.S439699 12. A generic blood banking and transfusion process-oriented architecture for virtual organizations | PLOS One - Research journals, https://journals.plos.org/plosone/article?id=10.1371/journal.pone.0303970 13. Time series forecasting of red blood cell demand in hematology patients using SARIMA and exponential smoothing models: a retrospective analysis in a Chinese tertiary hospital - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC12682652/ 14. Blood Bank Information System Market Size, 2032 - Business Research Insights, https://www.businessresearchinsights.com/market-reports/blood-bank-information-system-mark

et-112435 15. HIPAA Compliance Checklist for Blood Banks: Requirements and Best Practices, https://www.accountablehq.com/post/hipaa-compliance-checklist-for-blood-banks-requirements-and-best-practices 16. Build a Full-Stack CRUD App with React, Node.js, and MySQL: The Complete Foundation Guide - EastWest Studios, https://lists.eastweststudios.com/lis/build-a-fullstack-crud-app-with-react-nodejs-and-mysql-the-complete-foundation-guide 17. Top Front-End & Back-End Tech for Healthcare Web Apps - eSEOspace, https://eseospace.com/blog/top-front-end-back-end/ 18. Blood Bank Management System SRS | PDF | Blood Donation | Login - Scribd, https://www.scribd.com/document/407694716/Blood-Software 19. A COMPREHENSIVE BLOOD BANK MANAGEMENT SYSTEM FOR EFFICIENT RESOURCE AND STAFF HANDLING IN SERVICE CENTERS - Granthaalayah Publications and Printers, https://www.granthaalayahpublication.org/journals/granthaalayah/article/download/6120/5932?inline=1 20. Understanding the architecture of a 3-tier application | by Imsagnik - Medium, https://medium.com/@imsagnik1729/understanding-the-architecture-of-a-3-tier-application-af840beb94c3 21. Building a Three-Tier Blood Bank Management System on Amazon Web Services | by Om Dnyaneshwar Bhamare | Mar, 2026 | Medium, https://medium.com/@ombhamare178/building-a-three-tier-blood-bank-management-system-on-amazon-web-services-ac71caae305e 22. Understanding the architecture of a 3-tier application - vFunction, https://vfunction.com/blog/3-tier-application/ 23. A COMPREHENSIVE BLOOD BANK MANAGEMENT SYSTEM FOR EFFICIENT RESOURCE AND STAFF HANDLING IN SERVICE CENTERS, https://www.granthaalayahpublication.org/journals/granthaalayah/article/download/6120/5931/34173 24. Blood Bank Management System DFD Levels | PDF | Information Science - Scribd, https://www.scribd.com/document/688309103/Blood-Bank-Management-System-DFD-Levels-0-1-2 25. Blood Bank Management System DFD | PDF - Scribd, https://www.scribd.com/document/977303637/Blood-Bank-Management-System-DFD 26. Blood Bank Management System Diagram | EdrawMax Templates, https://www.edrawmax.com/templates/1026883/ 27. online blood bank system design | DOCX - Slideshare, https://www.slideshare.net/slideshow/online-blood-bank-system-design/58901526 28. Assessment of Blood Donor Information Using Kernel Density Maps: A Case Study at Gangtok District, Sikkim and Modeling of a Web Application. | Semantic Scholar, https://www.semanticscholar.org/paper/Assessment-of-Blood-Donor-Information-Using-Kernel-Nirola-Gupta/bf59d2773099f9ae808748b2fc02bdb68fefaa41 29. Android-Based Geolocation Technology on a Blood Donation System (BDS) Using the Dijkstra Algorithm - ResearchGate, https://www.researchgate.net/publication/353188408_Android-Based_Geolocation_Technology_on_a_Blood_Donation_System_BDS_Using_the_Dijkstra_Algorithm 30. The Main Phases of the Life Cycle of a Blood Unit - ResearchGate, https://www.researchgate.net/figure/The-Main-Phases-of-the-Life-Cycle-of-a-Blood-Unit_fig1_360062021 31. The journey of a blood donation, https://www.blood.co.uk/the-donation-process/after-your-donation/the-journey-of-a-blood-donation/ 32. Donor Eligibility | ImpactLife, https://www.bloodcenter.org/donate/donor/requirements-faq/ 33. General donor assessment - Blood Donor Selection - NCBI Bookshelf - NIH, https://www.ncbi.nlm.nih.gov/books/NBK138219/ 34. BLOOD BANK MANAGEMENT SYSTEM - SciSpace, https://scispace.com/pdf/blood-bank-management-system-l2n0cg9d.pdf 35. A description of the steps involved in collecting, processing, and distributing volunteer blood donations. - OneBlood, https://www.oneblood.org/content/dam/oneblood/corporate/graphics/Description-of-Donation-St

eps.pdf 36. Venepuncture for blood donaton - WHO Guidelines on Drawing Blood - NCBI - NIH, https://www.ncbi.nlm.nih.gov/books/NBK138671/ 37. Blood Components - Red Cross Blood.