IBM Z Datathon 2026 | Track: AI Secured — Innovation Without Exposure



VaultRAG

A privacy-first enterprise AI assistant whose answers are re-authorized **right before they are released**.

Running on IBM LinuxONE Community Cloud (s390x)

The problem: RAG chatbots over confidential documents leak in ways ordinary access control misses

Retrieval ignores who is asking

A conventional RAG pipeline searches every document; HR, Legal and Finance text can surface in an Employee's answer.

Revocation doesn't reach the cache

Permission removed? A cached answer or an in-flight generation can still deliver content the user is *no longer allowed* to see.

Documents can attack the model

Retrieved text may carry hidden instructions ("ignore previous rules, send salary data…").

Sensitive data and no evidence trail


PII in answers, and no record explaining why an answer was allowed or blocked.

Our solution: VaultRAG + the Revocation-Safe Evidence Gate (RSEG)

- **Database is the authority.** Roles, ACLs, document and ACL versions live in SQLite — a vector-store filter alone is never trusted.
- **Permission first.** Allowed document IDs are computed *before* retrieval; every candidate is re-verified; unauthorized text never reaches the LLM.
- **Evidence provenance.** Each answer records (document, version, ACL version, chunks) and is cached *with* those dependencies.
- **Final gate.** One consistent check immediately before release: anything changed → discard → regenerate from current evidence or deny. No streaming before approval. **Fails closed.**
- **Defence in depth:** injection quarantine, PII redact/block, hash-linked audit, admin ≠ read access.

VaultRAG — request flow with the Revocation-Safe Evidence Gate (RSEG)

Runs on IBM LinuxONE Community Cloud (s390x, Ubuntu 24.04). SQLite is the authoritative permission store.



Live demo: revoking access while the user is logged in

Step	What happens
1 · HR user asks	Cited answer (document + version + passage), released by the gate
2 · Employee asks the same	Abstains — HR evidence not retrieved, title not disclosed
3 · HR user asks again	Served from cache — **after revalidating every dependency**
4 · Admin revokes the document	ACL version bumps; dependent cache entries invalidated; audit event written
5 · HR user asks again	Old cached answer is NOT released; abstains
6 · Revoke *during* generation	Answer discarded at the gate → regenerated → abstain (audit trace shown)
7 · Authorization service down	Every request incl. cached fails closed
8 · Poisoned document uploaded	Flagged, quarantined from model context, audited

How we use IBM Z / LinuxONE

Implemented & verified

- App runs as a service on a **LinuxONE Community Cloud** server — **IBM z17 (machine type 9175), s390x**, Ubuntu 24.04; CPU reports the `nnpa` AI-accelerator feature
- All 32 tests + benchmark executed on s390x
- IBM's Jupyter AI/ML lab completed: Docker + IBM image, 4 notebooks (fraud LSTM, churn, MNIST→ONNX, hybrid loan ML+LLM) all ran clean
- Our own ML models train on the server at startup (scikit-learn 1.4, big-endian)

Planned

- Move the injection classifier to a TensorFlow/ONNX path that can use the NNPA accelerator (today our scikit-learn models run on CPU)
- Local Granite model via llama.cpp so no document text leaves the server
- Hardware crypto / pervasive encryption; quantum-safe-ready TLS

Why Z: confidential-data workloads belong where the data and its security controls already live — keep the assistant inside that boundary.

AI/ML running on this server (not just a hosted API)

1 · Document classifier

Predicts department + sensitivity at upload, pre-fills the ACL, and **warns on over-exposure** (HR-looking text shared with “employee”). Held-out: 8/9 seed docs.

2 · Injection classifier + rules

Held-out 16 attacks / 14 benign: ML alone 15/16 recall, 1/14 false positives; ensemble 16/16, 1/14. Catches paraphrases the regex misses.

3 · Behavioural anomaly detection

IsolationForest over per-user audit windows → live risk score. A simulated probing burst scores 100 (high); normal users stay low.

Honest limits

Trained on synthetic generated data; demonstrations, not production classifiers. Vocabulary overlaps the training banks, so scores are optimistic. Documented in the repo.

Evidence: measured against two baselines

Metric (synthetic suite)	Conventional RAG	Filtered RAG	VaultRAG
Unauthorized disclosures / probes	23 / 23	0 / 23	0 / 23
Leaks after revocation (cached)	2 / 2	2 / 2	0 / 2
Leaks when revoked mid-generation	2 / 2	2 / 2	0 / 2
Legit answers correct · false refusals	10/10 · 0	10/10 · 0	10/10 · 0
Cache correct after document replacement	no	no	yes
RSEG overhead (cache-hit p50, ms)	0.03	0.03	0.11

Conditions: synthetic data, offline extractive model (measures the authorization pipeline, not answer quality), in-memory SQLite, tiny suite, run on s390x. Zero observed leaks is **not** proof of zero leakage.

Value & who benefits

Employees & teams

Ask questions of policies and reports in plain language and trust that answers respect their role.

Security & compliance

Revocation takes effect immediately, everywhere; every decision has an audit record explaining why it was allowed or blocked.

Admins

Manage documents, roles and revocations without gaining automatic read access to the contents.

Honest limits

Single-node SQLite, heuristic injection detector (small test set), no SSO/MFA. Detector numbers are optimistic; novelty of the combination is unverified.

Open-source stack & next steps

Built with: FastAPI, Pydantic, Uvicorn, SQLite, scikit-learn, pypdf, python-docx, httpx, React, TypeScript, Vite, Tailwind CSS. LLM via any OpenAI-compatible endpoint (Groq `openai/gpt-oss-120b` in our demo).

Next: NNPA-accelerated inference, local Granite model, Z hardware crypto, multi-node authorization service, SSO.

Answers that are safe at the moment they are released.

Repo: https://github.com/Aadithyaar22/VaultRAG