



Deadlock

Deadlocks



- Consider the partial schedule

T_3	T_4
lock-x (B)	
read (B)	
$B := B - 50$	
write (B)	
	lock-s (A)
	read (A)
	lock-s (B)
lock-x (A)	

- Neither T_3 nor T_4 can make progress — executing **lock-S(B)** causes T_4 to wait for T_3 to release its lock on B , while executing **lock-X(A)** causes T_3 to wait for T_4 to release its lock on A .
- Such a situation is called a **deadlock**.
 - To handle a deadlock one of T_3 or T_4 must be rolled back and its locks released.

Deadlock Handling



- System is deadlocked if there is a set of transactions such that every transaction in the set is waiting for another transaction in the set.
- Methods for deadlock handling:
 - Deadlock prevention
 - Deadlock detection and recovery.
- Both methods may result in transaction rollback.

Deadlock Prevention



- **Deadlock prevention** protocols ensure that the system will *never* enter into a deadlock state.
- Two approaches :
 - Ensure no cyclic waits occur
 - Require that each transaction locks all its data items before it begins execution (predeclaration).
 - Impose partial ordering of all data items and require that a transaction can lock data items only in the order specified by the partial order.
 - Preemption and transaction rollback

More Deadlock Prevention Strategies



- Following schemes use transaction timestamps for the sake of deadlock prevention alone.
- **wait-die** scheme — non-preemptive
 - older transaction may wait for younger one to release data item. (older means smaller timestamp) Younger transactions never wait for older ones; they are rolled back instead.
 - a transaction may die several times before acquiring needed data item
- **wound-wait** scheme — preemptive
 - older transaction forces rollback of younger transaction instead of waiting for it. Younger transactions may wait for older ones.
 - may be fewer rollbacks than *wait-die* scheme.

Deadlock prevention (Cont.)




- Both in *wait-die* and in *wound-wait* schemes, a rolled back transactions is restarted with its original timestamp. Older transactions thus have precedence over newer ones, and starvation is hence avoided.
- **Timeout-Based Schemes:**
 - a transaction waits for a lock only for a specified amount of time. If the lock has not been granted within that time, the transaction is rolled back and restarted,
 - Thus, deadlocks are not possible
 - simple to implement; but starvation is possible. Also difficult to determine good value of the timeout interval.

Deadlock Detection




- Deadlocks can be described as a *wait-for graph*, which consists of a pair $G = (V, E)$,
 - V is a set of vertices (all the transactions in the system)
 - E is a set of edges; each element is an ordered pair $T_i \rightarrow T_j$.
- If $T_i \rightarrow T_j$ is in E , then there is a directed edge from T_i to T_j , implying that T_i is waiting for T_j to release a data item.
- When T_i requests a data item currently being held by T_j , then the edge $T_i \rightarrow T_j$ is inserted in the wait-for graph. This edge is removed only when T_j is no longer holding a data item needed by T_i .
- The system is in a deadlock state if and only if the wait-for graph has a cycle. Must invoke a deadlock-detection algorithm periodically to look for cycles.

Deadlock Detection (Cont.)



Wait-for graph without a cycle



Wait-for graph with a cycle

Deadlock Recovery



- When deadlock is detected :
 - Some transaction will have to rolled back (made a victim) to break deadlock. Select that transaction as victim that will incur minimum cost.
 - Rollback -- determine how far to roll back transaction
 - Total rollback: Abort the transaction and then restart it.
 - Partial rollback: More effective to roll back transaction only as far as necessary to break deadlock.
 - Starvation happens if same transaction is always chosen as victim. Include the number of rollbacks in the cost factor to avoid starvation