

SUB QUERY

Nested Subqueries

- SQL provides a mechanism for the nesting of subqueries. A **subquery** is a **select-from-where** expression that is nested within another query.
- The nesting can be done in the following SQL query

```
select  $A_1, A_2, \dots, A_n$   
from  $r_1, r_2, \dots, r_m$   
where  $P$ 
```

as follows:

- A_i can be replaced by a subquery that generates a single value.
- r_i can be replaced by any valid subquery
- P can be replaced with an expression of the form:

$B <\text{operation}> (\text{subquery})$

Where B is an attribute and $<\text{operation}>$ to be defined later.



Subqueries in the Where Clause

- A common use of subqueries is to perform tests:
 - For set membership
 - For set comparisons
 - For set cardinality.

Set Membership

- Find courses offered in Fall 2009 and in Spring 2010

```
select distinct course_id
from section
where semester = 'Fall' and year= 2009 and
       course_id in (select course_id
                      from section
                      where semester = 'Spring' and year= 2010);
```



Set Membership

- Find courses offered in Fall 2009 but not in Spring 2010

```
select distinct course_id
from section
where semester = 'Fall' and year= 2009 and
       course_id not in (select course_id
                           from section
                           where semester = 'Spring' and year= 2010);
```



Set Comparison - “some” Clause

- Find names of instructors with salary greater than that of some (at least one) instructor in the Biology department.

```
select distinct T.name  
from instructor as T, instructor as S  
where T.salary > S.salary and S.dept name =  
'Biology';
```

- Same query using > **some** clause

```
select name  
from instructor  
where salary > some (select salary  
                        from instructor  
                        where dept name = 'Biology');
```



Set Comparison - “all” Clause

- Find the names of all instructors whose salary is greater than the salary of all instructors in the Biology department.

```
select name  
from instructor  
where salary > all (select salary  
                        from instructor  
                        where dept name =  
                        'Biology');
```



Use of “exists” Clause

- Yet another way of specifying the query “Find all courses taught in both the Fall 2009 semester and in the Spring 2010 semester”

```
select course_id
from section as S
where semester = 'Fall' and year = 2009 and
      exists (select *
              from section as T
              where semester = 'Spring' and year = 2010
                  and S.course_id = T.course_id);
```



Subqueries in the From Clause

Subqueries in the From Clause

- SQL allows a subquery expression to be used in the **from** clause
- Find the average instructors' salaries of those departments where the average salary is greater than \$42,000."

```
select dept_name, avg_salary
from (select dept_name, avg (salary) as avg_salary
      from instructor
      group by dept_name)
where avg_salary > 42000;
```

- Note that we do not need to use the **having** clause



Subqueries in the Select Clause

Scalar Subquery

- Scalar subquery is one which is used where a single value is expected
- List all departments along with the number of instructors in each department

```
select dept_name,  
        (select count(*)  
         from instructor  
         where department.dept_name = instructor.dept_name)  
        as num_instructors  
from department;
```



Modification of the Database

- Deletion of tuples from a given relation.
- Insertion of new tuples into a given relation
- Updating of values in some tuples in a given relation



Deletion

- Delete all instructors

```
delete from instructor
```

- Delete all instructors from the Finance department

```
delete from instructor  
where dept_name = 'Finance';
```

- Delete all tuples in the *instructor* relation for those instructors associated with a department located in the Watson building.

```
delete from instructor  
where dept name in (select dept name  
                     from department  
                     where building = 'Watson');
```



Insertion

- Add all instructors to the *student* relation with tot_creds set to 0

```
insert into student
  select ID, name, dept_name, 0
from instructor
```

- The **select from where** statement is evaluated fully before any of its results are inserted into the relation.



Updates

- Increase salaries of instructors whose salary is over \$100,000 by 3%, and all others by a 5%

- Write two **update** statements:

```
update instructor  
  set salary = salary * 1.03  
  where salary > 100000;  
update instructor  
  set salary = salary * 1.05  
  where salary <= 100000;
```

