Lab 1: Data Loading, Summary, and Visualisation

Type 'jupyter notebook' in terminal

A new browser window will be opened listing the directories and files of anaconda.

Choose a new Python 3 file.

1. Data Frame

A data frame is a 2-d data structure similar to matrix. However columns of the matrix can be of different types, Size is mutable, Rows and columns can be labelled. And Arithmetic operations can be performed on rows and columns.

Create a pandas data frame as follows.

```
import numpy
import pandas
myarray = numpy.array([[1,2,3],[4,5,6]])
rownames = ['a','b']
colnames=['f1','f2','f3']
mydataframe = pandas.DataFrame(myarray, index = rownames, columns=colnames)
print(mydataframe)
```

Change the type of data

```
import numpy
import pandas
myarray = numpy.array([['a','sandhya',9.6],[4,'shreya',6.5]])
rownames = ['r1','r2']
colnames=['f1','f2','f3']
mydataframe = pandas.DataFrame(myarray, index = rownames, columns=colnames)
print(mydataframe)
```

2. Load csv file using pandas from a specific path or url

Copy dataset given in https://www.kaggle.com/uciml/pima-indians-diabetes-database to your local folder. Then execute the following.

```
from pandas import read_csv

path='1_diabetes.csv'

data=read_csv(path)

print (data.shape) #to know size of the data
```

The file can be given column names as follows

```
from pandas import read_csv
url='1_diabetes.csv'
data=read_csv(url)
```

```
colnames=['Pregnancies','Glucose','BloodPressure','SkinThickness','Insulin','BMI','Diab etesPedigreeFunction','Age','Outcome'] print (data.shape)
```

3. To get statistical summary of the data

```
(a)
description = data.describe()
print(description)
```

This will give statistics of each column in the dataset.

Example

```
Pregnancies
             Glucose BloodPressure SkinThickness
                                                   Insulin \
count 768.000000 768.000000
                                           768.000000 768.000000
                              768.000000
       3.845052 120.894531
                                          20.536458 79.799479
mean
                              69.105469
      3.369578 31.972618
std
                            19.355807
                                        15.952218 115.244002
                                        0.000000 \quad 0.000000
min
      0.000000 0.000000
                             0.000000
25%
       1.000000 99.000000
                             62.000000
                                          0.000000 0.000000
50%
       3.000000 117.000000
                              72.000000
                                          23.000000 30.500000
                                          32.000000 127.250000
75%
       6.000000 140.250000
                              80.000000
max
      17.000000 199.000000
                             122.000000
                                           99.000000 846.000000
```

Here 25%, 50%, gives % of data that falls below a given corresponding value in each column.

(b) Size of matrix

```
print(data.shape)
```

(c) Peek at data

print(data.head(4))

(d) Group on the basis of a particular attribute

```
print(data.groupby('Outcome').size())
```

4. Data visualization

For plotting pairs of attributes as scattered plot, specify the attributes to be plotted explicitly

```
import matplotlib.pyplot as plt
import pandas
from pandas.plotting import scatter_matrix
scatter_matrix(data[['Pregnancies','Glucose']])
plt.show()
```

For plotting all pairs of attributes in data

```
import matplotlib.pyplot as plt
import pandas
from pandas.plotting import scatter_matrix
scatter_matrix(data) #scatter plot
plt.show()
data.hist() #histogram
plt.show()
```

5. Standardization of dataset

```
from sklearn.preprocessing import StandardScaler import pandas import numpy arr=data.values #convert data frame to array X=arr[:,0:8] #split columns Y=arr[:,8] scaler=StandardScaler().fit(X) #fit data for standardization rescaledX=scaler.transform(X) #convert the data as per (x-\mu)/\sigma numpy.set_printoptions(precision=3) print(rescaledX[0:2,:]) print(X[0:2,:])
```

6. Normalizing a column in pandas

plt.show()

Create a dataframe for a set of values in an array

```
myarray=numpy.array([1,3,-10,4,5,7,-4,-2,10])
mydataframe = pandas.DataFrame(myarray)
print(mydataframe)

plot the data

mydataframe.plot(kind='bar')
```

Plot normalized data

```
from sklearn import preprocessing
fl_x=mydataframe.values.astype(float)

#fl_x=mydataframe[['f1']].values.astype(float) #If specific feature name is to be converted

min_max_scaler=preprocessing.MinMaxScaler()

X_scaled=min_max_scaler.fit_transform(fl_x)

df_normalized=pandas.DataFrame(X_scaled)

print(df_normalized)

df_normalized.plot(kind='bar')

plt.show()
```

Question: Identify the difference in the standardization and normalization of data.

Repeat Q.1 to Q.6 with cancer dataset from https://www.kaggle.com/uciml/breast-cancer-wisconsindata