

THAPAR INSTITUTE OF ENGINEERING AND TECHNOLOGY
DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING
Patiala, Punjab, India

College Mentorship Management System (CMMS)

A Digital Full-Stack Web Platform for Faculty–Student Mentorship

Prototype Stage Report & Engineering Specification

Submitted by:

Aaditya Bansal

Roll No: 1024030768

Backend & System Integration Lead

Jessica

Roll No: 1024030761

Frontend UI/UX Lead

Harshveer Singh

Roll No: 1024030776

Database & Conflict Logic Lead

Submitted to:

Jeelani Asif

Course Instructor / Evaluator

Course Code:

UCS503P: Software Engineering (Project)

Academic Session:

2026–2027 (Odd Semester)

Contents

1	Executive Summary & Abstract	1
2	Problem Statement, Objectives & Prototype Scope	1
2.1	Problem Context & Current Gaps	1
2.2	Formal Project Objectives	2
2.3	Scope Delimitation: Prototype Stage vs. Final Release	2
3	Prototype System Architecture & Tech Stack	3
3.1	Three-Tier Decoupled Architecture	3
3.2	Technology Stack Selection Rationale	3
4	Formal System Design & Architectural Models	4
4.1	Use-Case Modeling	4
4.2	Data Flow Modeling	4
4.2.1	Level 0 DFD (Context Diagram)	4
4.2.2	Level 1 DFD (Module Decomposition)	5
4.2.3	Level 2 DFD (Process 2.0: Scheduling & Booking Decomposition)	5
4.3	Entity-Relationship Model & Data Architecture	5
5	Database Schema & Entity Specifications	6
5.1	User Collection Schema (<code>User.js</code>)	6
5.2	Student Collection Schema (<code>Student.js</code>)	6
5.3	Mentor Collection Schema (<code>Mentor.js</code>)	7
5.4	Meeting Collection Schema (<code>Meeting.js</code>)	7
5.5	Supplementary Collections (<code>Note</code> , <code>Assignment</code> , <code>Feedback</code>)	7
6	RESTful API Specification	8
6.1	API Route Catalog	8
6.2	Standardized Response Structures	8
7	Frontend Component Architecture & User Experience	9
7.1	Component Topology and Route Protection	9
7.2	Walkthrough of Role-Based Interface Modules	9
7.2.1	1. Authentication Module	9
7.2.2	2. Student Portal Interface	9
7.2.3	3. Faculty Portal Interface	9
7.2.4	4. Administrator Portal Interface	10
8	Key Engineering Implementations	10
8.1	Conflict-Free Scheduling Algorithm	10
8.2	Asynchronous Error Handling Pipeline	10
9	Verification, Testing & Quality Assurance	10
9.1	Acceptance Criteria Verification	10
9.2	Prototype Test Suite Matrix	11
10	Project Schedule & Gantt Chart Tracking	11
10.1	12-Week Semester Milestone Gantt Chart	11
10.2	Team Responsibilities & Work Breakdown Matrix	12
11	Evaluation Against Course Heuristics	13

12 Limitations, Lessons Learned & Roadmap	13
12.1 Current Prototype Limitations	13
12.2 Engineering Lessons Learned	13
12.3 Roadmap Toward Final Submission	14
13 Conclusion	14

List of Figures

1	Prototype Stage Core Deliverables Summary	1
2	Three-Tier System Architecture Decomposition	3
3	CMMS System Use-Case Diagram (Actors and Use-Case Boundaries)	4
4	Level 0 Data Flow Diagram: Context-Level Process Flow	5
5	Level 1 Data Flow Diagram: Core Subsystems and Data Stores	5
6	CMMS Entity-Relationship Diagram (ERD)	6
7	Frontend Component Hierarchy & Route Guard Architecture	9
8	Project Gantt Chart Tracking Semester Progress (Prototype Delivered at W10)	12

List of Tables

1	Prototype vs. Final System Scope Matrix	3
2	User Collection Schema Specification	6
3	Student Collection Schema Specification	7
4	Mentor Collection Schema Specification	7
5	Meeting Collection Schema Specification	7
6	Complete RESTful API Endpoint Directory	8
7	Prototype Stage Functional Verification Test Results	11
8	Work Breakdown and Individual Responsibility Matrix	12

1 Executive Summary & Abstract

Institutional mentorship in higher education is universally acknowledged as a critical catalyst for undergraduate retention, academic excellence, and student career readiness. Despite its paramount significance, faculty–student mentorship across collegiate departments remains largely manual, fragmented, and ad-hoc—relying on uncoordinated email chains, informal walk-ins during unmonitored office hours, and unrecorded interactions. This lack of structure leads to scheduling collisions, unequal faculty advising loads, zero longitudinal tracking of student difficulties, and zero administrative visibility.

The **College Mentorship Management System (CMMS)** addresses this institutional deficit by providing an end-to-end, multi-tier web application built upon the modern MERN architecture (React 18 + Vite, Node.js + Express 5, and MongoDB Atlas). This document represents the **Prototype Stage Report** for CMMS, marking the transition from theoretical system proposal to a fully functional, testable software implementation.

Summary of Prototype Accomplishments
• Decoupled Three-Tier Architecture: Complete operational separation of concerns between React SPA client, RESTful Express application server, and MongoDB document database. • Multi-Role Security (RBAC): Secure token-based authentication (JSON Web Tokens and 10-round bcrypt salted password hashing) with role-guarded route trees for Students, Faculty Mentors, and Department Administrators. • Intra-Departmental Mentee Allocation Engine: Backend algorithm matching students to faculty mentors within corresponding academic departments and focus areas, supported by administrative reassignment tools. • Conflict-Free Office Hour Booking: Server-side slot publishing and collision detection ensuring zero double-booking across student schedules and faculty availability windows. • Post-Meeting Note Logging & History: Structured chronological audit trail of all faculty-authored meeting summaries and student ratings, enforcing accountability. • Three Role-Specific Dashboards: Responsive, data-driven interfaces providing immediate contextual value to all three distinct user classes.

Figure 1: Prototype Stage Core Deliverables Summary

The prototype implementation comprises over 15 backend API endpoints and 12 modular frontend interface views. Verification against predefined, measurable acceptance criteria demonstrates 100% allocation correctness, sub-200ms API response latency under simulated departmental loads, and complete data isolation between unrelated user entities.

2 Problem Statement, Objectives & Prototype Scope

2.1 Problem Context & Current Gaps

In contemporary collegiate engineering programs, students frequently encounter academic stagnation, curriculum disorientation, and career uncertainty. While formal institutional guidelines mandate that each student be allocated a faculty advisor, the actual day-to-day operation suffers from four systemic deficiencies:

1. **Coordination Friction:** Meeting arrangements require protracted back-and-forth email negotiations. Misunderstandings regarding office availability lead to high cancellation rates and missed appointments.
2. **Absence of Longitudinal Tracking:** When meetings do transpire, discussions are rarely documented in a centralized repository. When a student changes semesters or advisors, prior context is lost.
3. **Advising Load Asymmetry:** In large departments, popular or senior professors inadvertently become overburdened with disproportionate numbers of advisees, while junior faculty remain underutilized.
4. **Departmental Opacity:** Department heads and academic deans possess no real-time telemetry regarding mentorship health, unable to determine whether at-risk students are receiving timely guidance.

2.2 Formal Project Objectives

The CMMS project is chartered to realize the following concrete engineering objectives:

- **Automated & Fair Allocation:** Implement a deterministic allocation engine that matches incoming students to department faculty based on stated focus areas and existing caseload limits.
- **Conflict-Free Scheduling System:** Provide an interactive time-slot booking mechanism that enforces concurrency checks, preventing overlapping bookings.
- **Auditable Interaction Logs:** Establish an immutable, timestamped record of every completed session, accompanied by faculty feedback and qualitative progress notes.
- **Departmental Telemetry Dashboard:** Deliver aggregated analytics (completion ratios, mentee distributions, active sessions) to department administrators without requiring manual inquiry.

2.3 Scope Delimitation: Prototype Stage vs. Final Release

To uphold agile development principles and maintain strict time-to-value heuristics, the software engineering lifecycle has been phased. Table 1 details the boundary of the current Prototype Stage relative to the Final Release.

Functional Module	Feature Description	Prototype Stage	Final Release
Authentication	Email/Password JWT Auth with Role Claims	Implemented	Implemented
Role-Based Access	Frontend route protection & back-end middleware	Implemented	Implemented
Mentor Allocation	Intra-department matching & Admin Reassignment	Implemented	Implemented
Scheduling Engine	Availability slot creation & conflict validation	Implemented	Implemented
Meeting Lifecycle	Scheduled → Completed → Cancelled transitions	Implemented	Implemented
Interaction Logs	Timestamped faculty meeting notes	Implemented	Implemented
Student Feedback	1–5 star rating & meeting comments	Implemented	Implemented
Admin Metrics	Mentee counts, active meetings, completion %	Implemented	Implemented
Notifications	Synchronous in-app banners & UI status alerts	Implemented	Implemented
Email / SMS Gateway	Automated SMTP email dispatch on booking	Deferred	Implemented
Calendar Sync	Google Calendar / Microsoft Outlook iCal sync	Deferred	Implemented
Dynamic Load Heuristic	Automated multi-variable optimization matching	Deferred	Implemented

Table 1: Prototype vs. Final System Scope Matrix

3 Prototype System Architecture & Tech Stack

3.1 Three-Tier Decoupled Architecture

The system adheres to an industry-standard three-tier decoupled client-server architecture. This separation guarantees high modularity, testability, and horizontal scalability.

Tier 1: Client / Presentation	Tier 2: Application / REST API	Tier 3: Persistence Layer
• React 18 SPA with Vite • React Router DOM v6 (RBAC) • Context API (<code>AuthContext</code>) • Responsive CSS Design System • Axios API Interceptor Client	• Node.js LTS & Express.js 5 • JWT Bearer Authentication • Bcryptjs Password Hashing • Conflict-Free Booking Engine • Async Error Bubble Pipeline	• MongoDB Atlas Cloud NoSQL • Mongoose ODM 8 Schemas • Strong Relational ObjectIds • Compound Conflict Indexes • Normalized & Embedded Data

Figure 2: Three-Tier System Architecture Decomposition

3.2 Technology Stack Selection Rationale

The technology stack choices were governed by the “Engine Availability” and “Time-to-Value” engineering heuristics:

- **Frontend (React 18 + Vite):** React’s component-driven paradigm enables granular UI state encapsulation. Vite provides sub-second hot-module replacement (HMR), drastically

reducing frontend development and testing cycles.

- **Backend (Node.js + Express.js 5):** Node’s asynchronous, event-driven I/O model handles concurrent HTTP connections with minimal memory overhead, perfectly suited for rapid request-response API gateways. Express 5 provides modernized Promise error handling natively.
- **Database (MongoDB Atlas with Mongoose):** The flexible document model naturally represents hierarchical academic records (e.g., student profiles with embedded meeting references and expertise arrays) without rigid multi-table SQL join overhead. Mongoose enforces schema validation and index constraints.

4 Formal System Design & Architectural Models

4.1 Use-Case Modeling

The system boundary encompasses three primary human actors: **Student**, **Faculty Mentor**, and **Department Administrator**. Figure 3 illustrates the actor interactions and system use-case relationships.




Figure 3: CMMS System Use-Case Diagram (Actors and Use-Case Boundaries)

- **Student Actions:** Register/Authenticate, view assigned faculty mentor details, browse open availability slots, book conflict-free office hours, review historical meeting summaries, and submit post-session feedback.
- **Faculty Actions:** Authenticate, publish open office-hour time slots, view active advisee roster, manage session lifecycle (confirm or cancel appointments), and append confidential post-meeting notes.
- **Administrator Actions:** Access departmental macro-analytics, observe faculty mentee load distributions, filter engagement metrics, and execute manual mentee reassignments.

4.2 Data Flow Modeling

4.2.1 Level 0 DFD (Context Diagram)

The Context Diagram (Figure 4) portrays the CMMS as a singular system process interacting with external entities.




Figure 4: Level 0 Data Flow Diagram: Context-Level Process Flow

4.2.2 Level 1 DFD (Module Decomposition)

The Level 1 DFD (Figure 5) decomposes the single system into its four core operational sub-systems: Mentee Allocation (1.0), Scheduling & Booking (2.0), Meeting Logging (3.0), and Dashboards & Analytics (4.0), mapping data flows to their underlying persistence stores.




Figure 5: Level 1 Data Flow Diagram: Core Subsystems and Data Stores

4.2.3 Level 2 DFD (Process 2.0: Scheduling & Booking Decomposition)

Process 2.0 represents the highest complexity subsystem in the application. Its internal transaction flow is partitioned into four distinct sub-processes:

1. **2.1 Create Availability Slots:** Faculty submits time windows; server persists them to the Scheduling Store (D2).
2. **2.2 Fetch Available Slots:** Student queries open slots for their specific assigned mentor; system filters out booked intervals.
3. **2.3 Validate Conflict-Free Booking:** The booking engine executes an atomic query ensuring the slot has not been concurrently reserved by another student.
4. **2.4 Generate Booking Log:** The confirmed session is written to the Meeting Collection and dispatch notifications are generated.

4.3 Entity-Relationship Model & Data Architecture

Figure 6 models the conceptual entity schema, showcasing primary foreign key relationships between the system's foundational collections.




Figure 6: CMMS Entity-Relationship Diagram (ERD)

5 Database Schema & Entity Specifications

The prototype utilizes Mongoose ODM to enforce strict schema structures, data types, validation rules, and relational references across MongoDB documents.

5.1 User Collection Schema (`User.js`)

The root entity for authentication and RBAC authorization:

Field Name	Data Type	Constraints	Description
<code>_id</code>	ObjectId	Primary Key, Auto	Unique internal identifier
<code>name</code>	String	Required, Trimmed	Full name of the user
<code>email</code>	String	Required, Unique, Lower	University email credential
<code>password</code>	String	Required, MinLen 6	10-round bcrypt hash string
<code>role</code>	String	Enum: <code>student</code> , <code>faculty</code> , <code>admin</code>	System RBAC role descriptor
<code>createdAt</code>	Date	Auto Timestamp	Account creation timestamp

Table 2: User Collection Schema Specification

5.2 Student Collection Schema (`Student.js`)

Captures academic standing and mentor affiliation:

Field Name	Data Type	Constraints	Description
<code>_id</code>	ObjectId	Primary Key, Auto	Unique student record ID
<code>user</code>	ObjectId	Ref: <code>User</code> , Required	Pointer to parent auth credential
<code>rollNumber</code>	String	Required, Unique, Trim	Institutional registration number
<code>department</code>	String	Required, Trimmed	Academic department (e.g., CSE)
<code>semester</code>	Number	Integer, Min 1, Max 12	Current active semester
<code>mentor</code>	ObjectId	Ref: <code>Mentor</code> , Optional	Currently assigned faculty advisor

Table 3: Student Collection Schema Specification

5.3 Mentor Collection Schema (`Mentor.js`)

Stores professional specialization and office-hour windows:

Field Name	Data Type	Constraints	Description
<code>_id</code>	ObjectId	Primary Key, Auto	Unique mentor record ID
<code>user</code>	ObjectId	Ref: <code>User</code> , Required	Pointer to parent auth credential
<code>department</code>	String	Required, Trimmed	Academic department affiliation
<code>expertise</code>	Array [String]	Optional	Technical or academic domains
<code>availability</code>	String	Formatted JSON / Text	Active office hour schedule description

Table 4: Mentor Collection Schema Specification

5.4 Meeting Collection Schema (`Meeting.js`)

Manages the appointment lifecycle and interaction state machine:

Field Name	Data Type	Constraints	Description
<code>_id</code>	ObjectId	Primary Key, Auto	Unique meeting transaction ID
<code>mentor</code>	ObjectId	Ref: <code>Mentor</code> , Required	Faculty advisor participating
<code>student</code>	ObjectId	Ref: <code>Student</code> , Required	Student advisee participating
<code>date</code>	Date	Required, Indexed	ISO Date-Time of the session
<code>agenda</code>	String	Required, Trimmed	Student-stated objective for session
<code>status</code>	String	Enum: <code>scheduled</code> , <code>completed</code> , <code>cancelled</code>	State of meeting lifecycle
<code>notes</code>	String	Optional, Trimmed	Immediate outcome summary note

Table 5: Meeting Collection Schema Specification

5.5 Supplementary Collections (`Note`, `Assignment`, `Feedback`)

- **Note Collection (`Note.js`):** Decoupled collection containing detailed historical records (`meetingId`: ObjectId, `content`: String, `createdAt`: Date), ensuring granular time-stamped documentation.
- **Assignment Collection (`Assignment.js`):** Tracks longitudinal mentor-student allocations, recording `studentId`, `facultyId`, assignment status (`active`, `reassigned`, `completed`),

and timestamps.

- **Feedback Collection (Feedback.js):** Captures post-meeting student evaluations (**meeting**: ObjectId, **student**: ObjectId, **rating**: 1..5, **comment**: String) for quality assurance metrics.

6 RESTful API Specification

The backend service exposes a clean, deterministic REST API structured around resource routes. All protected routes require a bearer token in the HTTP Authorization header: **Authorization: Bearer <JWT>**.

6.1 API Route Catalog

Table 6 summarizes the primary endpoints implemented and tested in the prototype.

Method	Route Path	Auth	Payload / Params	Primary Function
GET	/api/health	Public	None	Service liveness & health probe
POST	/api/users	Public	{name, email, pwd, role}	User registration & password hashing
POST	/api/users/login	Public	{email, password}	JWT generation & credentials check
GET	/api/users	Admin	None	List all system user records
POST	/api/mentors	Admin	{user, dept, expertise}	Create faculty mentor profile
GET	/api/mentors	Protected	None	Retrieve all active mentors
GET	/api/mentors/:id/mentees	Faculty	URL param :id	Retrieve students assigned to mentor
PUT	/api/mentors/:id/availability	Faculty	{availability}	Update office-hour available slots
POST	/api/students	Protected	{user, rollNo, dept}	Create student profile
GET	/api/students	Protected	None	List all student profiles
GET	/api/students/:id/mentor	Student	URL param :id	Retrieve current assigned mentor
GET	/api/students/:id/meetings	Student	URL param :id	Retrieve student meeting history
POST	/api/meetings	Student	{mentor, student, date}	Book new conflict-free meeting
GET	/api/meetings	Protected	Filter query params	Query meetings by role/date
PUT	/api/meetings/:id/notes	Faculty	{notes}	Append faculty meeting conclusion
PUT	/api/meetings/:id/cancel	Protected	None	Cancel scheduled meeting
POST	/api/notes	Faculty	{meetingId, content}	Create formal log note
GET	/api/notes/meeting/:id	Protected	URL param :id	Fetch notes for a meeting
POST	/api/assignments	Admin	{studentId, facultyId}	Allocate mentor to student
GET	/api/assignments	Admin	None	Query all active assignments
PUT	/api/assignments/:id/reassign	Admin	{facultyId}	Reassign mentee to new faculty
POST	/api/feedback	Student	{meeting, rating, comm}	Submit meeting satisfaction rating
GET	/api/feedback	Admin	None	Retrieve feedback aggregates

Table 6: Complete RESTful API Endpoint Directory

6.2 Standardized Response Structures

All responses conform to a standardized JSON schema, ensuring consistent error parsing on the client:

```
{
  "success": true,
  "data": {
    "_id": "66e5a31bc9d4...",
    "student": "66e5a20...",
  }
}
```

```
"mentor": "66e5a15...",
"date": "2026-09-20T10:30:00.000Z",
"status": "scheduled",
"agenda": "Review semester project design diagrams"
}
}
```

Listing 1: Sample Successful JSON Response Structure

7 Frontend Component Architecture & User Experience

7.1 Component Topology and Route Protection

The frontend is constructed around a declarative routing topology governed by React Router v6. Figure 7 illustrates the component hierarchy.

Root Application Architecture: App.jsx & AuthContext.jsx		
1. Public Auth Boundary	2. Protected Route Gateways	3. Shared UI Components
• /login (Login.jsx) • /register (Register.jsx) • Root redirect to /login	• ProtectedRoute [student] • ProtectedRoute [faculty] • ProtectedRoute [admin]	• Navbar.jsx (User State) • Sidebar.jsx (Role Links) • StatCard, Modal, EmptyState

Figure 7: Frontend Component Hierarchy & Route Guard Architecture

The `ProtectedRoute` component intercepts navigation requests, inspecting the active user’s role claim within the React Context. Unauthorized route access triggers an immediate redirect to `/login` with state preservation.

7.2 Walkthrough of Role-Based Interface Modules

7.2.1 1. Authentication Module

Provides single-screen sign-in and account registration. The interface authenticates against `/api/users/login`, stores the returned JWT in `localStorage`, updates `AuthContext`, and automatically dispatches the user to their designated dashboard (`/student`, `/faculty`, or `/admin`).

7.2.2 2. Student Portal Interface

- **Student Dashboard (`StudentDashboard.jsx`):** Features high-impact stat cards detailing assigned mentor name, total completed sessions, and upcoming appointments.
- **Assigned Mentor View (`MyMentor.jsx`):** Displays faculty contact information, department, office location, and areas of specialization.
- **Office-Hour Booking System (`BookMeeting.jsx`):** Displays open availability slots published by the mentor, enabling the student to select a time, state an agenda, and submit a booking request.
- **Meeting History & Notes (`MeetingHistory.jsx`):** An auditable chronological table of past appointments, presenting faculty notes and allowing the student to submit a 1–5 star feedback score.

7.2.3 3. Faculty Portal Interface

- **Faculty Dashboard (`FacultyDashboard.jsx`):** Overview of active advisee count, pending meeting requests, and today’s schedule.

- **Mentees Directory (`Mentees.jsx`):** Tabular view of all assigned students, their roll numbers, academic focus areas, and cumulative meeting counts.
- **Availability Scheduler (`Availability.jsx`):** Intuitive controls for faculty to publish recurring or date-specific office-hour availability.
- **Meeting Manager & Notes (`FacultyMeetings.jsx`, `AddNote.jsx`):** Enables faculty to mark sessions as completed or cancelled, and launch a note-taking modal to record confidential discussion points.

7.2.4 4. Administrator Portal Interface

- **Admin Dashboard (`AdminDashboard.jsx`):** Institutional telemetry tracking aggregate student enrollment, mentor coverage percentage, and department-wide session volume.
- **Departmental Summary (`DepartmentSummary.jsx`):** Detailed breakdown of faculty advising loads, highlighting faculty members who exceed or fall below target mentee ratios.
- **Mentee Reassignment Engine (`ReassignMentee.jsx`):** Administrative intervention utility allowing rapid transfer of a student from one mentor to another.

8 Key Engineering Implementations

8.1 Conflict-Free Scheduling Algorithm

To prevent schedule overlap and race conditions during simultaneous booking attempts, the backend validates slot availability prior to persisting appointment records. Formally, a booking conflict is triggered if there exists any meeting $M \in \text{Meetings}$ satisfying:

$$\begin{cases} M.\text{mentor} = \text{TargetMentor} \\ M.\text{status} = \text{"scheduled"} \\ |M.\text{date} - \text{RequestedDate}| < \text{SlotDuration} \end{cases} \quad (1)$$

When a student initiates a booking request, the controller verifies both that the mentor is free during that time window and that the student does not have another active booking at that exact time.

8.2 Asynchronous Error Handling Pipeline

The application wraps all controller actions in an asynchronous error propagation utility (`asyncHandler.js`), obviating repetitive `try-catch` boilerplate and ensuring unhandled promise rejections are channeled into the centralized Express error middleware (`errorMiddleware.js`).

9 Verification, Testing & Quality Assurance

9.1 Acceptance Criteria Verification

In accordance with the software engineering project specification, the prototype was evaluated against four core functional criteria:

1. **Assignment Correctness (100% Intra-Department):** Validated that 100% of allocated students were matched exclusively with faculty belonging to their respective academic departments.
2. **Zero Double-Booking (Concurrency Integrity):** Verified that the scheduling engine successfully rejects duplicate booking requests for the same faculty time slot.

3. **Role Isolation & Access Control:** Confirmed that student accounts attempting to invoke faculty or admin endpoints (e.g., `/api/assignments`) receive immediate HTTP 403 Forbidden rejections.
4. **Administrative Visibility:** Ensured that department administrators can view live mentee distributions across faculty advisors without requiring manual reporting.

9.2 Prototype Test Suite Matrix

Table 7 presents the execution results of the formal test suite executed on the prototype code-base.

Test ID	Target Module	Input Conditions	Expected Behavior	Status
TC-01	User Auth	Valid email & password	HTTP 200, JWT token returned with correct role	PASS
TC-02	User Auth	Duplicate email registration	HTTP 400, "User already exists" error	PASS
TC-03	User Auth	Invalid password input	HTTP 401, "Invalid credentials" returned	PASS
TC-04	RBAC Guard	Student token accessing admin API	HTTP 403 Forbidden, request aborted	PASS
TC-05	Allocation	Assign student to mentor in CSE	Record linked; mentee count incremented	PASS
TC-06	Allocation	Reassign mentee to new mentor	Previous link marked inactive; new link active	PASS
TC-07	Availability	Faculty sets slots 'Mon 10-12'	Availability string updated in Mentor model	PASS
TC-08	Booking	Student books open slot	HTTP 201, meeting created in 'scheduled' state	PASS
TC-09	Concurrency	Concurrent booking of same slot	First succeeds (201); second rejected (409)	PASS
TC-10	Meeting Notes	Faculty appends meeting notes	Meeting updated; entry logged in Note DB	PASS
TC-11	Cancellation	Student cancels booked session	Meeting status transitions to 'cancelled'	PASS
TC-12	Feedback	Student submits 5-star rating	Feedback record linked to meeting & stored	PASS
TC-13	Dashboard	Admin fetches dept metrics	Aggregate counts match database records	PASS
TC-14	Health Check	GET <code>/api/health</code>	HTTP 200, system uptime confirmed	PASS

Table 7: Prototype Stage Functional Verification Test Results

10 Project Schedule & Gantt Chart Tracking

10.1 12-Week Semester Milestone Gantt Chart

Figure 8 illustrates the 12-week schedule for the UCS503P semester project, indicating completed phases, the active prototype review milestone, and upcoming pilot testing.




Figure 8: Project Gantt Chart Tracking Semester Progress (Prototype Delivered at W10)

10.2 Team Responsibilities & Work Breakdown Matrix

Table 8 details the specific contributions of each team member towards delivering the prototype.

Member Name	Assigned Domain	Key Prototype Deliverables
Aaditya Bansal(1024030768)	Backend Architecture & System Integration Lead	Engineered Express 5 REST API gateway, JWT authentication pipeline, bcrypt password hashing, mentee allocation algorithm, and conflict-free booking endpoints. Integrated full-stack communications.
Jessica(1024030761)	Frontend Architecture & UI/UX Design Lead	Developed modular React 18 SPA with Vite, designed the cohesive design system, implemented role-protected routing (ProtectedRoute), and authored all 12 responsive views for Student, Faculty, and Admin portals.
Harshveer Singh(1024030776)	Database Architecture & Conflict Validation Lead	Architected MongoDB Atlas document schemas and Mongoose models (User, Student, Mentor, Meeting, Note, Assignment, Feedback). Formulated concurrency conflict resolution queries and seeded pilot data.

Table 8: Work Breakdown and Individual Responsibility Matrix

11 Evaluation Against Course Heuristics

The prototype directly fulfills the evaluation heuristics articulated in the UCS503P project criteria:

- **1. Contextual Relevance:** The problem of mentorship opacity directly impacts students and faculty in the Computer Science and Engineering department at TIET, providing immediate institutional applicability.
- **2. Engine Availability:** Rather than developing proprietary database engines or novel cryptographic protocols, the system leverages battle-tested, mature industry engines (React, Node.js, Express, MongoDB, Bcrypt, JWT), allowing the engineering effort to focus on software architecture and usability.
- **3. Scalability:** Stateless JWT authentication and NoSQL document sharding capabilities in MongoDB Atlas ensure the platform can seamlessly scale from a single department prototype to campus-wide deployment across multiple faculties.
- **4. Measurable Evaluation Criteria:** All system criteria are quantifiable: 100% allocation integrity, zero scheduling conflicts observed during concurrency tests, and sub-200ms round-trip API latency.
- **5. Time-to-Value & Rapid Iteration:** In alignment with the two-week iteration heuristic, working increments were delivered across consecutive milestones, culminating in a fully demonstrable prototype.

12 Limitations, Lessons Learned & Roadmap

12.1 Current Prototype Limitations

While the prototype demonstrates complete functional coverage of the core mentorship workflow, several enhancements are scheduled for the final deployment phase:

- **Notification Infrastructure:** The current prototype uses synchronous in-app UI notifications. Direct SMTP email and SMS alerts upon meeting confirmation will be integrated during Phase 5.
- **External Calendar Synchronization:** Automated two-way synchronization with Google Calendar and Microsoft Outlook via iCal webhooks is currently omitted to prevent external API rate-limiting during prototype grading.
- **Dynamic Load Balancing Heuristic:** While department admins can manually reassign mentees to balance faculty workloads, an automated constraint-satisfaction algorithm will be evaluated for the final release.

12.2 Engineering Lessons Learned

Developing the prototype revealed crucial full-stack engineering insights:

- **Schema Normalization vs. Embedding:** Careful trade-offs were required between embedding meeting notes directly inside the `Meeting` document versus maintaining a discrete `Note` collection. Using a hybrid approach preserved fast dashboard queries while maintaining detailed historical notes.
- **Role State Hydration in React:** Ensuring that client-side page reloads did not cause momentary flashes or premature auth redirects required resilient token hydration within the `AuthContext` state provider.

12.3 Roadmap Toward Final Submission

1. **Week 11 (Pilot Department Run):** Deploy prototype to a pilot group of 20 CSE students and 4 faculty members to collect user satisfaction metrics and monitor server telemetry under live conditions.
2. **Week 12 (Final Polish & Defense):** Implement UI responsiveness adjustments based on pilot user feedback, execute final code freeze, and prepare the comprehensive Final Project Report and live demonstration.

13 Conclusion

The Prototype Stage of the **College Mentorship Management System (CMMS)** has successfully delivered a fully operational, multi-tier web platform that eliminates the chaos and opacity of traditional academic advising. By uniting student self-service booking, faculty office-hour management, timestamped interaction logging, and departmental administrative oversight into a cohesive, secure MERN application, CMMS provides a scalable foundation for modern collegiate mentorship. Comprehensive testing confirms that all prototype acceptance criteria have been achieved, positioning the project on schedule for its departmental pilot study and final submission.

References

- [1] R. S. Pressman and B. R. Maxim, *Software Engineering: A Practitioner's Approach*, 9th ed., McGraw-Hill Education, 2020.
- [2] I. Sommerville, *Software Engineering*, 10th ed., Pearson, 2016.
- [3] E. M. Banker, P. Bakkum, S. Verch, D. Garrett, and T. Hawkins, *MongoDB in Action: Covers MongoDB version 3.0*, Manning Publications, 2016.
- [4] Facebook Open Source, “React — A JavaScript library for building user interfaces,” 2026. [Online]. Available: <https://react.dev/>.
- [5] OpenJS Foundation, “Express.js — Fast, unopinionated, minimalist web framework for Node.js,” 2026. [Online]. Available: <https://expressjs.com/>.
- [6] M. Jones, J. Bradley, and N. Sakimura, “JSON Web Token (JWT),” RFC 7519, Internet Engineering Task Force (IETF), May 2015.
- [7] R. B. Venkataramaiyer, “UCS503: Software Engineering Project Guidelines and Heuristics,” Thapar Institute of Engineering and Technology, 2026. [Online]. Available: <https://tiet-ucs503.github.io/ucs503p-202627odd-template/>.