

Ex No: 1b)

Date:

BASIC LINUX COMMANDS

1.1 GENERAL PURPOSE COMMANDS

1. The 'date' command:

The date command displays the current date with day of week, month, day, time (24 hours clock) and the year.

SYNTAX: \$ date

The date command can also be used with following format.

Format	Purpose	Example
+ %m	To display only month	\$ date + %m
+ %h	To display month name	\$ date + %h
+ %d	To display day of month	\$ date + %d
+ %y	To display last two digits of the year	\$ date + %y
+ %H	To display Hours	\$ date + %H
+ %M	To display Minutes	\$ date + %M
+ %S	To display Seconds	\$ date + %S

2. The 'echo' command:

The echo command is used to print the message on the screen.

SYNTAX: \$ echo

EXAMPLE: \$ echo "God is Great"

3. The 'cal' command:

The cal command displays the specified month or year calendar.

SYNTAX: \$ cal [month] [year]

EXAMPLE: \$ cal Jan 2012

4. The 'bc' command:

1.1 General purpose commands

1. \$ date

Output: SAT FEB 1 08:14:44 IST 2025

2. echo "God is great"

Output: God is great

3. cal Jan 2025

Output:

January 2025

SU	MO	TU	We	Th	Fr	Sa
			1	2	3	4
5	6	7	8	9	10	11
12	13	14	15	16	17	18
19	20	21	22	23	24	25
26	27	28	29	30	31	

4. 15

5. man

Output: what manual page do you want?

6. who

Output: root pts/0 2025-02-03 8:32 (0)
root pts/1 2025-02-03 8:40 (0)

7. who am i

Output: root pts/1 2025-02-03 8:40 (:0)

8. tty

Output: /dev/pts/1

9. ps

output :

PTD	TTY	TIMECMD
1560	PTS/1	00:00:00 barf
1589	PTS/1	00:00:00 PS
2 digits + 2s	To display only minute	MN ⁰ +
2 digits + 2s	To display only minute	MM ⁰ +
2 digits + 2s	To display only hour	HR ⁰ +
2 digits + 2s	To display last 10 digits of the year	YY ⁰ +
2 digits + 2s	To display Hours	1H ⁰ +
2 digits + 2s	To display Minutes	MN ⁰ +
2 digits + 2s	To display Seconds	SS ⁰ +

10. Name

Output: Linux

11. PWD

output : /root

Unix offers an online calculator and can be invoked by the command bc.

SYNTAX: \$ bc

EXAMPLE: bc -l

16/4

5/2

5. The 'who' command

The who command is used to display the data about all the users who are currently logged into the system.

SYNTAX: \$ who

6. The 'who am i' command

The who am i command displays data about login details of the user.

SYNTAX: \$ who am i

7. The 'id' command

The id command displays the numerical value corresponding to your login.

SYNTAX: \$ id

8. The 'tty' command

The tty (teletype) command is used to know the terminal name that we are using.

SYNTAX: \$ tty

9. The 'clear' command

The clear command is used to clear the screen of your terminal.

SYNTAX: \$ clear

10. The 'man' command

The man command gives you complete access to the Unix commands.

SYNTAX: \$ man [command]

11. The 'ps' command

The ps command is used to the process currently alive in the machine with the 'ps' (process status) command, which displays information about process that are alive when you run the command. 'ps;' produces a snapshot of machine activity.

SYNTAX: \$ ps

EXAMPLE: \$ ps

\$ ps -e

\$ps -aux

1.2 Directory commands

1. pwd → home / student
2. mkdir rec
3. rmdir rec
4. cd dirname
5. cd <filename> → cd rec
6. ls

output : anaconda - ks.cfg desktop documents downloads
initial - setup - ks.cfg music pictures public
templates videos.

12. The 'uname' command

The uname command is used to display relevant details about the operating system on the standard output.

- m -> Displays the machine id (i.e., name of the system hardware)
- n -> Displays the name of the network node. (host name)
- r -> Displays the release number of the operating system.
- s -> Displays the name of the operating system (i.e.. system name)
- v -> Displays the version of the operating system.
- a -> Displays the details of all the above five options.

SYNTAX: \$ uname [option]

EXAMPLE: \$ uname -a

1.2 DIRECTORY COMMANDS

1. The 'pwd' command:

The pwd (print working directory) command displays the current working directory.

SYNTAX: \$ pwd

2. The 'mkdir' command:

The mkdir is used to create an empty directory in a disk.

SYNTAX: \$ mkdir dirname

EXAMPLE: \$ mkdir receee

3. The 'rmdir' command:

The rmdir is used to remove a directory from the disk. Before removing a directory, the directory must be empty (no files and directories).

SYNTAX: \$ rmdir dirname

EXAMPLE: \$ rmdir receee

4. The 'cd' command:

The cd command is used to move from one directory to another.

SYNTAX: \$ cd dirname

EXAMPLE: \$ cd receee

5. The 'ls' command:

1.3 File Handling commands

1. cat > rec → hi there !! how are you ??
2. cp rec Aaditya → copy rec to Aaditya
3. rm rec → rec file removed
4. mv rec Aaditya
5. File Aaditya → Aaditya : ASCII // text
6. (piper) / who | wc -l → 2
7. tee sample | wc -l → 2
8. ls
9. chmod

The ls command displays the list of files in the current working directory.

SYNTAX: \$ ls

EXAMPLE: \$ ls

\$ ls -l

\$ ls -a

1.3 FILE HANDLING COMMANDS

1. The 'cat' command:

The cat command is used to create a file.

SYNTAX: \$ cat > filename

EXAMPLE: \$ cat > rec

2. The 'Display contents of a file' command:

The cat command is also used to view the contents of a specified file.

SYNTAX: \$ cat filename

3. The 'cp' command:

The cp command is used to copy the contents of one file to another and copies the file from one place to another.

SYNTAX: \$ cp oldfile newfile

EXAMPLE: \$ cp cse eee

4. The 'rm' command:

The rm command is used to remove or erase an existing file

SYNTAX: \$ rm filename

EXAMPLE: \$ rm rec

\$ rm -f rec

Use option -fr to delete recursively the contents of the directory and its subdirectories.

5. The 'mv' command:

The mv command is used to move a file from one place to another. It removes a specified file from its original location and places it in specified location.

SYNTAX: \$ mv oldfile newfile

EXAMPLE: \$ mv cse eee

6. The 'file' command:

The file command is used to determine the type of file.

SYNTAX: \$ file filename

EXAMPLE: \$ file receee

7. The 'wc' command:

The wc command is used to count the number of words, lines and characters in a file.

SYNTAX: \$ wc filename

EXAMPLE: \$ wc recccc

8. The 'Directing output to a file' command:

The ls command lists the files on the terminal (screen). Using the redirection operator '>' we can send the output to file instead of showing it on the screen.

SYNTAX: \$ ls > filename

EXAMPLE: \$ ls > cseeee

9. The 'pipes' command:

The Unix allows us to connect two commands together using these pipes. A pipe (|) is an mechanism by which the output of one command can be channeled into the input of another command.

SYNTAX: \$ command1 | command2

EXAMPLE: \$ who | wc -l

10. The 'tee' command:

While using pipes, we have not seen any output from a command that gets piped into another command. To save the output, which is produced in the middle of a pipe, the tee command is very useful.

SYNTAX: \$ command | tee filename

EXAMPLE: \$ who | tee sample | wc -l

11. The 'Metacharacters of unix' command:

Metacharacters are special characters that are at higher and abstract level compared to most of other characters in Unix. The shell understands and interprets these metacharacters in a special way.

* - Specifies number of characters

? - Specifies a single character

[] - used to match a whole set of file names at a command line.

! - Used to Specify Not

EXAMPLE:

\$ ls r** - Displays all the files whose name begins with 'r'

\$ ls ?kkk - Displays the files which are having 'kkk', from the second characters irrespective of the first character.

\$ ls [a-m] - Lists the files whose names begins alphabets from 'a' to 'm'

\$ ls [!a-m] - Lists all files other than files whose names begins alphabets from 'a' to 'm' 12.

The 'File permissions' command:

File permission is the way of controlling the accessibility of file for each of three users namely Users, Groups and Others.

There are three types of file permissions available, they are

r-read

w-write

x-execute

The permissions for each file can be divided into three parts of three bits each.

First three bits	Owner of the file
Next three bits	Group to which owner of the file belongs
Last three bits	Others

EXAMPLE: \$ ls college

-rwxr-xr-- 1 Lak std 1525 jan10 12:10 college

Where,

-rwx The file is readable, writable and executable by the owner of the file.

Lak Specifies Owner of the file.

r-x Indicates the absence of the write permission by the Group owner of the file. Std Is the Group Owner of the file.

r- Indicates read permissions for others.

13. The 'chmod' command:

The chmod command is used to set the read, write and execute permissions for all categories of users for file.

SYNTAX: \$ chmod category operation permission file

Category	Operation	permission
u-users	+ assign	r-read
g-group	-Remove	w-write
o-others	= assign absolutely	x-execute
a-all		

Grouping Commands

1.4

1. who ; date

O/P: root pts/0 2025-02-03 08:32 (:0)
root pts/1 2025-02-03 08:40 (:0)
Mon Feb 3 09:04:45 IST 2025

2. who & date

O/P: root pts/0 2025-02-03 08:32 (:0)
Mon Feb 3 09:04:45 IST 2025

3. who || date

O/P:
root pts/0 2025-02-03 08:32 (:0)
root pts/1 2025-02-03 08:40 (:0)

Filters

1. head <filename>
2. tail <filename>
3. sort <filename>
4. nl <filename>
5. cut -c <filename>

EXAMPLE:

\$ chmod u-wx college

Removes write & execute permission for users for 'college' file.

\$ chmod u+rwx, g+rw college

Assigns read & write permission for users and groups for 'college' file.

\$ chmod g=rxw college

Assigns absolute permission for groups of all read, write and execute permissions for 'college' file.

14. The 'Octal Notations' command:

The file permissions can be changed using octal notations also. The octal notations for file permission are

Read permission	4
Write permission	2

EXAMPLE:

\$ chmod 761 college

Execute permission	1
--------------------	---

Assigns all permission to the owner, read and write permissions to the group and only executable permission to the others for 'college' file.

1.4 GROUPING COMMANDS**1. The 'semicolon' command:**

The semicolon(;) command is used to separate multiple commands at the command line.

SYNTAX: \$ command1;command2;command3.....;commandn

EXAMPLE: \$ who;date

2. The '&&' operator:

The '&&' operator signifies the logical AND operation in between two or more valid Unix commands. It means that only if the first command is successfully executed, then the next command will be executed.

SYNTAX: \$ command1 && command && command3.....&& commandn

EXAMPLE: \$ who && date

3. The '||' operator:

The '||' operator signifies the logical OR operation in between two or more valid Unix commands. It means, that only if the first command will happen to be un successfully, it will continue to execute next commands.

SYNTAX: \$ command1 || command2 || command3.....||commandn

EXAMPLE: \$ who || date

1.5 FILTERS

1. The head filter

It displays the first ten lines of a file.

SYNTAX: \$ head filename

EXAMPLE: \$ head college Display the top ten lines.

\$ head -5 college Display the top five lines.

2. The tail filter

It displays ten lines of a file from the end of the file.

SYNTAX: \$ tail filename

EXAMPLE: \$ tail college Display the last ten lines.

\$tail -5 college Display the last five lines.

3. The more filter:

The pg command shows the file page by page.

SYNTAX: \$ ls -l | more

4. The 'grep' command:

This command is used to search for a particular pattern from a file or from the standard input and display those lines on the standard output. "Grep" stands for "global search for regular expression."

SYNTAX: \$ grep [pattern] [file_name]

EXAMPLE: \$ cat> student

Arun cse

Ram cce

Kani cse

\$ grep "cse" student

Arun cse

Kani cse

5. The 'sort' command:

The sort command is used to sort the contents of a file. The sort command reports only to the

screen, the actual file remains unchanged.

SYNTAX: \$ sort filename

EXAMPLE: \$ sort college

OPTIONS:

Command	Purpose
Sort -r college	Sorts and displays the file contents in reverse order
Sort -c college	Check if the file is sorted
Sort -n college	Sorts numerically
Sort -m college	Sorts numerically in reverse order

Sort -u college	Remove duplicate records
Sort -l college	Skip the column with +1 (one) option. Sorts according to second column

6. The 'nl' command:

The nl filter adds line numbers to a file and it displays the file and not provides access to edit but simply displays the contents on the screen.

SYNTAX: \$ nl filename

EXAMPLE: \$ nl college

7. The 'cut' command:

We can select specified fields from a line of text using cut command.

SYNTAX: \$ cut -c filename

EXAMPLE: \$ cut -c college

OPTION:

-c - Option cut on the specified character position from each line.

1.5) Other essential commands

- i) free
- ii) top
- iii) ps
- iv) vm stat
- v) df
- vi) ping
- vii) ifconfig
- viii) trace route

Function	Command
Show free memory info like count etc in memory	free -m
Copy file from one place to another	cp
Show current configuration	ifconfig
Show network routing	route
Show destination info in traceroute	traceroute

1. free -t

Total used free shared buffers / cache available

Mem:	1994332	738132	187920	106840	985400
swap:	2129916	0	2129996		
Total	2129248	738132	2317831		

2. top

2434 root 20 0 - - -

:

3. ps -e

1) 00:00:01 Systemd

:

1.5 OTHER ESSENTIAL COMMANDS

1. free

Display amount of free and used physical and swapped memory system.

synopsis- free [options]

example

```
[root@localhost ~]# free -t  
total used free shared buff/cache available Mem: 4044380 605464 2045080  
148820 1393836 3226708 Swap: 2621436 0 2621436  
Total: 6665816 605464 4666516
```

2. top

It provides a dynamic real-time view of processes in the system.

synopsis- top [options]

example

```
[root@localhost ~]# top  
top - 08:07:28 up 24 min, 2 users, load average: 0.01, 0.06, 0.23  
Tasks: 211 total, 1 running, 210 sleeping, 0 stopped, 0 zombie  
%Cpu(s): 0.8 us, 0.3 sy, 0.0 ni, 98.9 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st  
KiB Mem : 4044380 total, 2052960 free, 600452 used, 1390968 buff/cache KiB Swap:  
2621436 total, 2621436 free, 0 used. 3234820 avail Mem PID USER PR NI VIRT RES  
SHR S %CPU %MEM TIME+ COMMAND  
1105 root 20 0 175008 75700 51264 S 1.7 1.9 0:20.46 Xorg 2529 root 20 0 80444  
32640 24796 S 1.0 0.8 0:02.47 gnome-term 3. ps
```

It reports the snapshot of current processes
synopsis- ps [options]

example

```
[root@localhost ~]# ps -e
```

4. VM stat

r	b	swapd	free	buffer	cache	si	so	bi	bo	in	out
0	0	0	106008	6958	1000889	0	0	207124	208..		

5. df

device	172.16.4.0	0	172.16.4.0	0 % free	low
root	986180	0	986180	0	

6. ping 172.16.4.1

64 bytes from 172.16.4.1: icmp_seq=1668=64

time 0.193ms

PID TTY TIME CMD

1 ? 00:00:03 systemd
2 ? 00:00:00 kthreadd
3 ? 00:00:00 ksoftirqd/0

4. vmstat

It reports virtual memory statistics

Synopsis- vmstat [options]

example

```
[root@localhost ~]# vmstat
procs      memory      swap      io      system      cpu
- r b swpd free buff cache si so bi bo in cs us sy id wa st 0 0 0 1879368
1604 1487116 0 0 64 7 72 140 1 0 97 1 0
```

5. df

It displays the amount of disk space available in file-system.

Synopsis- df [options]

example

```
[root@localhost ~]# df
```

Filesystem 1K-blocks Used Available Use% Mounted on

```
devtmpfs 2010800 0 2010800 0% /dev tmpfs 2022188 148 2022040 1% /dev/shm
tmpfs 2022188 1404 2020784 1% /run /dev/sda6 487652 168276 289680 37% /boot
```

6. ping

It is used verify that a device can communicate with another on network. PING stands for Packet Internet Groper.

Synopsis- ping [options]

```
[root@localhost ~]# ping 172.16.4.1
```

```
PING 172.16.4.1 (172.16.4.1) 56(84) bytes of data.
64 bytes from 172.16.4.1: icmp_seq=1 ttl=64 time=0.328 ms
64 bytes from 172.16.4.1: icmp_seq=2 ttl=64 time=0.228 ms
```

7. /rajalakshmi.org (14.99.10.232) 0.155 ms 0.106 ms

```
64 bytes from 172.16.4.1: icmp_seq=3 ttl=64 time=0.264 ms
64 bytes from 172.16.4.1: icmp_seq=4 ttl=64 time=0.312 ms
^C
-- 172.16.4.1 ping statistics --
4 packets transmitted, 4 received, 0% packet loss, time 3000ms
rtt min/avg/max/mdev = 0.228/0.283/0.328/0.039 ms
```

7. ifconfig

It is used configure network interface.

synopsis- ifconfig [options]

example

```
[root@localhost ~]# ifconfig
```

```
enp2s0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu
1500 inet 172.16.6.102 netmask 255.255.252.0 broadcast 172.16.7.255 inet6
fe80::4a0f:cfff:fe6d:6057 prefixlen 64 scopeid 0x20<link>
ether 48:0f:cf:6d:60:57 txqueuelen 1000 (Ethernet)
```

```
RX packets 23216 bytes 2483338 (2.3 MiB)
RX errors 0 dropped 5 overruns 0 frame 0
TX packets 1077 bytes 107740 (105.2 KiB)
TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0 8.
```

traceroute

It tracks the route the packet takes to reach the destination.

synopsis- traceroute [options]

example

```
[root@localhost ~]# traceroute www.rajalakshmi.org
traceroute to www.rajalakshmi.org (220.227.30.51), 30 hops max, 60 byte
packets 1 gateway (172.16.4.1) 0.299 ms 0.297 ms 0.327 ms
2 220.225.219.38 (220.225.219.38) 6.185 ms 6.203 ms 6.189 ms
```

Result:

The above commands have been executed
successfully.

12/25