Parallel Finite Volume Simulation of 2D Heat Diffusion on Unstructured Triangular Meshes

Aadityanshu Abhinav (ME22B088) Anuj Sreenivasan (ME22B106)
Department of Mechanical Engineering, IIT Madras
ID5130: Parallel Scientific Computing

Abstract

*A cell-centred finite volume method (FVM) is applied to steady and unsteady 2D heat diffusion on a unit-square domain meshed with unstructured triangles generated by Gmsh [4]. Non-orthogonality of the mesh is handled through a primary/secondary gradient decomposition at each face [2]. The steady system is solved by graph-coloured Gauss–Seidel Successive Over Relaxation (GS-SOR) [3], while the unsteady system advances with explicit Euler. A serial implementation of the solvers, an **OpenMP** [6] shared-memory version, and an **MPI** [7] distributed-memory version are developed, all using the same graph colouring and relaxation factor $\omega = 1.5$, and all the three produce identical iteration counts and solutions. Strong-scaling experiments on a 4-core machine (2,744 elements, $\omega = 1.5$, 2,677 GS-SOR iterations) show MPI speedups of $S(2) = 1.40$ and $S(4) = 1.82$ for the steady solver, whereas OpenMP achieves no speedup, potentially due to a memory-bandwidth bottleneck inherent to the dense $N \times N$ matrix storage.*

Nomenclature

T	Temperature [°C]
k	Thermal conductivity [W/(m · K)]
p	Density [kg/m^3]
C_p	Specific heat [J/(kg · K)]
α	Thermal diffusivity [m^2/s]
S_T	Source term [W/m^3]
A_f	Outward face-area vector
$\hat{e}_g$	Unit vector between centroids (primary direction)
$\hat{e}_n$	Unit vector along face (tangent direction)
$\Delta\xi$	Centroid-to-centroid distance
$\Delta\eta$	Face edge length
V_i	Control volume area of element i
A	Global coefficient matrix
b	Right-hand side vector in $AT = b$
N	Number of elements in mesh
Δt	Time step [s]
w	Relaxation factor in GS-SOR
K	Number of colour groups in graph colouring
C_k	Set of elements belonging to colour group k
T_{bc}	Prescribed Dirichlet boundary temperature

1 Introduction

Heat conduction in complex geometries appears throughout engineering design: electronic cooling, additive manufacturing thermal history, and turbine-blade analysis all require solving the diffusion equation on domains not resolvable by structured grids. While unstructured triangular meshes offer geometric flexibility, the resulting non-orthogonal faces demand a correction to the standard FVM flux formula.

All thermophysical properties are set to unity ($\rho = k = C_p = 1$, $\alpha = 1$) and source terms are neglected for simplicity, reducing the governing equation to the Laplace equation in steady state and to $\partial T/\partial t = \nabla^2 T$ in the unsteady case.

This work follows two objectives: first, it validates a non-orthogonality-corrected FVM against the known analytical solution for 2D Laplace on the unit square with mixed Dirichlet boundary conditions; second, it parallelises the solver with both OpenMP [6] and MPI [7] using graph coloring, benchmarks both against a serial reference using the same algorithm, then characterizes strong and weak scaling on a shared 4-core machine.

2 Mathematical Formulation

2.1 Governing equations

The general differential equation governing the diffusion of heat in a solid is as follows:

$$\rho C_p \frac{\partial T}{\partial t} = k\nabla^2 T + S_T \tag{1}$$

where S_T is the source term. On applying the assumptions stated above, the equation is reduced to the following forms.

The *steady* problem is the 2D Laplace equation on $\Omega = [0,1]^2$:

$$\nabla^2 T = 0, \qquad (x,y) \in \Omega, \tag{2}$$

with Dirichlet boundary conditions

$$\begin{aligned} T\big|_{x=0} = 50, \quad T\big|_{x=1} = 200, \\ T\big|_{y=1} = 100, \quad T\big|_{y=0} = 300\ [^\circ\mathrm{C}]. \end{aligned} \tag{3}$$

The *unsteady* problem adds a time derivative ($\alpha = 1$):

$$\frac{\partial T}{\partial t} = \nabla^2 T, \qquad T(x, y, 0) = 100\ ^\circ\mathrm{C}, \tag{4}$$

with the same spatial boundary conditions (3).

2.2 Analytical solutions

Steady. By superposition of four sub-problems (each side driven, others homogeneous), the steady solution is [1]

$$\begin{aligned} T_s = \sum_{n\,\mathrm{odd}} \frac{4}{n\pi} \Big[& T_L\, s(y,n)\, \tfrac{\sinh n\pi(1-x)}{\sinh n\pi} \\ & + T_R\, s(y,n)\, \tfrac{\sinh n\pi x}{\sinh n\pi} \\ & + T_B\, s(x,n)\, \tfrac{\sinh n\pi(1-y)}{\sinh n\pi} \\ & + T_T\, s(x,n)\, \tfrac{\sinh n\pi y}{\sinh n\pi} \Big], \end{aligned} \tag{5}$$

where $s(z, n) = \sin(n\pi z)$. The series converges rapidly; 50 odd terms are used in practice.

Unsteady. The full solution is the steady part plus an eigenfunction expansion:

$$\begin{aligned} T(x, y, t) = {} & T_s(x, y) \\ & + \sum_{m=1}^{N} \sum_{n=1}^{N} \frac{16}{mn\pi^2} \sin(m\pi x) \sin(n\pi y) \\ & \times e^{-(m^2+n^2)\pi^2 t}, \end{aligned} \tag{6}$$

where the initial condition $T = 100$ has been decomposed in the sine basis on $[0, 1]^2$. As $t \to \infty$ the transient decays and $T \to T_s$.

3 FVM Discretisation

3.1 Mesh and cell-centred layout

Gmsh [4] generates an unstructured triangular mesh of Ω with target edge length l_c. Each triangle Ω_i is a control volume; the unknown T_i is located at its centroid. Integration of Eq. (2) over Ω_i and the divergence theorem give [3]

$$\oint_{\partial\Omega_i} \nabla T \cdot \mathbf{n}\, \mathrm{d}S = 0, \tag{7}$$

where the contour consists of up to three faces: interior faces and boundary faces.

3.2 Non-orthogonality correction



Figure 1: Face geometry for two adjacent triangular cells. a and b are the face endpoint nodes; c_0, c_1 are the cell centroids; $\hat{e}_\xi$ is the centroid-to-centroid unit vector; $\hat{e}_\eta$ runs along the face from a to b; $\mathbf{A}_f$ is the outward face-area vector, perpendicular to the face.

For an interior face f shared by cells i ($\equiv c_0$) and j ($\equiv c_1$), with endpoint nodes a and b (Fig. 1), define [2]

- $\hat{e}_\xi$ = unit vector from centroid c_0 to centroid c_1 (primary direction),
- $\hat{e}_\eta$ = unit vector along the face from node a to node b (tangent direction),
- $\Delta\xi = |\mathbf{c}_1 - \mathbf{c}_0|$, $\quad \Delta\eta$ = face edge length $|b - a|$,
- $\mathbf{A}_f$ = outward face-area vector, perpendicular to the face ($A_f^x = \Delta\eta\, e_{\eta,y},\ A_f^y = -\Delta\eta\, e_{\eta,x}$).

The face gradient is decomposed as

$$\nabla T \cdot \mathbf{A}_f \approx \underbrace{\frac{|\mathbf{A}_f|^2}{(\mathbf{A}_f \cdot \hat{e}_\xi)\,\Delta\xi}}_{\text{PGcoeff}} (T_j - T_i) + \underbrace{-\frac{|\mathbf{A}_f|^2\,(\hat{e}_\eta \cdot \hat{e}_\xi)}{(\mathbf{A}_f \cdot \hat{e}_\xi)\,\Delta\eta}}_{\text{SGcoeff}} \overline{\Delta T}_\eta, \tag{8}$$

where PGcoeff drives the primary (normal) gradient between centroids and SGcoeff corrects for the skew between $\mathbf{A}_f$ and $\hat{e}_\xi$.

The secondary gradient $\overline{\Delta T}_\eta$ is the difference of node-averaged temperatures at the two face endpoints a and b:

$$\overline{\Delta T}_\eta = \bar{T}_a - \bar{T}_b, \qquad \bar{T}_n = \frac{1}{|S_n|} \sum_{k \in S_n} T_k, \tag{9}$$

where S_n is the set of elements sharing node n. Since T is defined only at element centroids, this arithmetic mean is an approximation of the true nodal temperature. Boundary nodes take their prescribed Dirichlet value exactly.

Both PGcoeff and SGcoeff contributions are assembled directly into the global matrix $\mathbf{A}$: PGcoeff connects only face-neighbouring elements (the primary $\hat{e}_\xi$ stencil), while SGcoeff creates additional off-diagonal entries connecting all elements that share an endpoint node of the face. Assembling all interior and boundary faces yields the linear system $\mathbf{AT} = \mathbf{B}$, where $\mathbf{A} \in \mathbb{R}^{N\times N}$ is stored *densely*.

Algorithm 1 Assembly of $\mathbf{A}$ and $\mathbf{b}$ for steady diffusion

Require: Mesh data, connectivity, geometry; N elements
$\mathbf{A}[N][N] \leftarrow 0$; $\mathbf{b}[N] \leftarrow 0$
for each element $i = 0, \ldots, N-1$ **do**
  for each face $j = 0, 1, 2$ **do**
    nbTag $\leftarrow$ (neighbour element tag)
    if nbTag $\neq 0$ **then** ▷ interior face
      Compute PGcoeff, SGcoeff
      $A[i,i] \mathrel{-}= \mathrm{PGcoeff}$; $A[i,\mathrm{nb}] \mathrel{+}= \mathrm{PGcoeff}$
      for node $n_k \in \{n_a, n_b\}$, sign $s_k \in \{-1, +1\}$ **do**
        if n_k on boundary **then**
          $b[i] \mathrel{+}= s_k \cdot \mathrm{SGcoeff} \cdot T_{\mathrm{bc}}$
        else
          for each $\ell \in$ `nodeToElems`$[n_k]$ **do**
            $A[i,\ell] \mathrel{-}= s_k \cdot \mathrm{SGcoeff}/|\mathrm{elems}|$
          end for
        end if
      end for
    else if face is boundary **then**
      Compute PGcoeff
      $A[i,i] \mathrel{-}= \mathrm{PGcoeff}$; $b[i] \mathrel{-}= \mathrm{PGcoeff} \cdot T_{\mathrm{bc}}$
    end if
  end for
end for

The unsteady solver stores only two vectors T^n and T^{n+1} (no matrix assembly). The time step $\Delta t = l_c^2/20$ satisfies the explicit stability limit; the initial condition is $T(x, y, 0) = 100\,^\circ\mathrm{C}$ everywhere.

Algorithm 2 Explicit unsteady update

Require: Mesh, connectivity, geometry; N, Δt
$T^n[N] \leftarrow 100$; $T^{n+1}[N] \leftarrow 0$
for each time step **do**
  for each element i **do**
    $F_i \leftarrow 0$
    for each face j **do**
      if interior face **then**
        $F_i \mathrel{+}= \mathrm{PGcoeff}\big(T^n[\mathrm{nb}] - T^n[i]\big)$
          + SGcoeff via node averages of T^n
      else if boundary face **then**
        $F_i \mathrel{+}= \mathrm{PGcoeff}\big(T_{\mathrm{bc}} - T^n[i]\big)$
      end if
    end for
    $T^{n+1}[i] \leftarrow T^n[i] + (\Delta t/V_i)\, F_i$
  end for
  Swap $T^n \leftrightarrow T^{n+1}$
end for

4 Parallelisation

4.1 Graph colouring

The GS-SOR update of element i reads the current value of every neighbour connected through an $\mathbf{A}$ matrix entry. Two elements that share a node contribute to each other's rows, so simultaneous updates create a data race.

A *graph colouring* of the element adjacency graph (edges connect elements that share at least one node) partitions elements into colour groups such that no two same-coloured elements share a node. Elements within a colour group can therefore be updated in any order (or in parallel) without conflict. Greedy colouring applied to the Gmsh mesh typically yields 9–10 colours for the triangulations used here.

Algorithm 3 Greedy graph colouring

Require: Element adjacency via `nodeToElems`; N elements
color$[i] \leftarrow -1$ for all i
for $i = 0, \ldots, N-1$ **do**
  used $\leftarrow \{\mathrm{color}[j] : j \in \mathrm{neighbors}(i),\ \mathrm{color}[j] \geq 0\}$
  color$[i] \leftarrow \min\{c \geq 0 : c \notin \mathrm{used}\}$
end for
$K \leftarrow \max_i \mathrm{color}[i] + 1$
Partition elements into $\mathcal{C}_1, \ldots, \mathcal{C}_K$ by colour index

where $\mathrm{neighbors}(i)$ denotes all elements sharing at least one node with element i (obtained via `nodeToElems`).

4.2 GS-SOR with graph colouring

Let $\mathcal{C}_1, \ldots, \mathcal{C}_K$ be the colour groups. One GS-SOR iteration proceeds as: for $k = 1, \ldots, K$, update all $i \in \mathcal{C}_k$ in parallel,

$$T_i \leftarrow (1-\omega)T_i + \omega\,\frac{B_i - \sum_{j\neq i} A_{ij}T_j}{A_{ii}}, \tag{10}$$

making each update visible to subsequent colour groups. Convergence is checked as $\max_i |T_i^{\mathrm{new}} - T_i| < 10^{-10}$.

4.3 OpenMP implementation

The outer loop over colours is sequential. Inside each colour group, a `#pragma omp parallel for` [6] distributes elements across threads:

```
for (int c = 0; c < K; c++) {
  #pragma omp parallel for reduction(max:err)
  for (int ci = 0; ci < Nc; ci++)
    sor_update(color[c][ci]);
}
```

No synchronisation beyond the implicit barrier at the colour-group boundary is required.

4.4 MPI implementation

Each rank r owns a contiguous slice of rows $[\ell_r, u_r)$ of $\mathbf{A}$ and $\mathbf{B}$. The global temperature vector $\mathbf{T}$ is replicated on every rank. Within each colour group, rank r updates only those elements of $\mathcal{C}_k$ that fall in its slice, then an `MPI_Allgatherv` [7] assembles the updated entries on all ranks before the next colour group begins:

```
for each color C_k:
  for i in C_k, i in [local_s, local_e):
    sor_update(i)
  MPI_Allgatherv(MPI_IN_PLACE, T, ...)
MPI_Allreduce(&lMax, &gMax, MPI_MAX)
```

The per-colour synchronisation produces the *identical* update order as the serial version, because elements in $\mathcal{C}_k$ share no nodes globally, guaranteeing the same iteration count and solution across all three paradigms.

4.5 Unsteady parallelisation

The explicit Euler step reads $\mathbf{T}^n$ (frozen, read-only) and writes $\mathbf{T}^{n+1}_{\text{buf}}$; each T_i^{n+1} depends only on previous-step values and no two elements write to the same location, so every update is unconditionally independent. For OpenMP, a single `#pragma omp parallel for` over all elements suffices (no colouring needed). For MPI, each rank computes its local slice of $\mathbf{T}_{\text{buf}}$ and one `MPI_Allgatherv` per step synchronises all ranks.

5 Results

All experiments use $l_c = 0.03$ (strong scaling, $N = 2{,}744$ elements) and $l_c = 0.15/\sqrt{p}$ (weak scaling), with $\omega = 1.5$ and convergence tolerance 10^{-10}. The machine is a 4-core AMD host running Ubuntu; all timings are wall-clock seconds via `omp_get_wtime()` / `MPI_Wtime()`.

5.1 Steady-state solution accuracy



(a) Analytical $T_s(x, y)$ **(b)** FVM solution

Figure 2: Steady temperature field: analytical (left) vs. FVM at $l_c = 0.03$, $N = 2{,}744$ (right). The serial, OMP, and MPI solvers all produce the same field to floating-point precision.



Figure 3: Pointwise error $|T_{\text{FVM}} - T_{\text{exact}}|$ at $l_c = 0.03$ (linear colourscale). Peak error $\approx 2.0\,^\circ$C near corners arises from the slow Fourier convergence of the analytical series, not the FVM truncation error.

Table 1 summarises convergence and peak error across mesh sizes.

Table 1: Steady solver convergence ($\omega = 1.5$, all paradigms).

l_c	N	Iterations	$\max\lvert T_{\text{FVM}} - T_{\text{exact}}\rvert$
0.15	118	109	2.43
0.07	544	552	2.34
0.03	2744	2677	2.02

Figure 4 verifies that both parallel solvers reproduce the serial solution to floating-point precision.



(a) Serial vs. OMP **(b)** Serial vs. MPI

Figure 4: $|T_{\text{serial}} - T_{\text{parallel}}|$ at $l_c = 0.03$. The field is identically zero to floating-point tolerance ($\max|\Delta T| < 10^{-10}\,^\circ$C) for both paradigms, confirming correctness of the graph-coloured update scheme.

5.2 Unsteady evolution

The unsteady solver uses $\Delta t = l_c^2/20$ from uniform initial temperature $T_0 = 100\,^\circ$C. Figure 5 shows snapshots from a 10,000-step visualisation run at $l_c = 0.15$ ($\Delta t \approx 1.1 \times 10^{-3}$,

$t_{\max} \approx 11.2$); the timing benchmarks in Table 3 use 1,000 steps at $l_c = 0.03$. The MPI solution at every snapshot is precisely identical to the OMP solution.

5.3 Strong scaling

Strong scaling fixes the problem size ($l_c = 0.03$, $N = 2{,}744$) and increases the number of processes/threads.

Table 2: Strong scaling: steady solver ($N = 2{,}744$, 2,677 GS-SOR iterations, $\omega = 1.5$).

Paradigm	p	T_{solve} (s)	$S(p)$	$E(p)$
OMP	1	20.87	1.00	100%
	2	21.00	0.99	50%
	4	21.36	0.98	24%
MPI	1	21.46	1.00	100%
	2	15.27	**1.40**	**70%**
	4	11.81	**1.82**	**46%**

Table 3: Strong scaling: unsteady solver ($N = 2{,}744$, 1,000 steps).

Paradigm	p	T_{solve} (s)	$S(p)$	$E(p)$
OMP	1	1.462	1.00	100%
	2	1.486	0.98	49%
	4	1.447	1.01	25%
MPI	1	1.385	1.00	100%
	2	0.993	**1.39**	**70%**
	4	0.861	**1.61**	**40%**

5.4 Weak scaling

Weak scaling keeps the work per process roughly constant by setting $l_c(p) = 0.15/\sqrt{p}$, so the element count grows as $N \propto p$.

Table 4: Weak scaling efficiency $E_w(p) = T(1)/T(p)$.

Solver	Paradigm	$p = 1$	$p = 2$	$p = 4$
Steady	OMP	100%	11.7%	1.8%
	MPI	100%	15.4%	2.5%
Unsteady	OMP	100%	46.3%	25.3%
	MPI	100%	69.5%	37.3%

5.5 Discussion

MPI outperforms OMP for the steady solver. The full dense matrix occupies $N^2 \times 8\,\text{B} \approx 60\,\text{MB}$ at $N = 2{,}744$, far exceeding the L3 cache. Since all OpenMP threads share the same memory bus, the solver is potentially memory-bandwidth-bound, which would explain the flat OMP scaling regardless of thread count. MPI processes each hold an independent memory slice (N/p rows), avoiding shared-bus contention and yielding meaningful speedup.

Why MPI scaling is sub-linear. Each GS-SOR iteration requires $K \approx 10$ `MPI_Allgatherv` calls plus one `MPI_Allreduce`; at 2,677 iterations this totals ∼26,800 collective operations [5]. Communication latency caps efficiency at $\approx 46\%$ at $p = 4$.

Unsteady OMP. The explicit Euler kernel is element-wise independent, yet OMP achieves $S \approx 1$ because writing `Usteady.txt` at every time step (∼137 MB for 1,000 steps) dominates wall time and serialises the run.

Weak scaling. The dense-matrix GS-SOR has $O(N)$ work per element, so increasing both N and p proportionally still doubles per-element work, causing the steep steady-solver degradation ($< 3\%$ at $p = 4$). The unsteady $O(1)$ stencil is more resilient ($\sim 37\%$ at $p = 4$ for MPI).

6 Conclusions

A graph-coloured GS-SOR FVM solver for 2D heat diffusion was implemented and parallelised with both OpenMP and MPI on an unstructured triangular mesh. Key findings are:

1. **Correctness.** The serial, OpenMP, and MPI solvers all use graph-coloured GS-SOR with $\omega = 1.5$. Because the graph colouring and update order are identical across all three, they converge in the same number of iterations (2,677 at $l_c = 0.03$) and produce the same solution, verified against the analytical Fourier series ($\max |T_{\text{FVM}} - T_{\text{exact}}| = 2.02\,°\text{C}$).
2. **MPI strong scaling (steady):** $S(4) = 1.82$**.** Distributed-memory processes avoid shared memory-bus contention and achieve meaningful speedup despite collective communication overhead.
3. **OMP shows no speedup for the steady solver.** The dense $N \times N$ matrix ($\approx 60\,\text{MB}$ at $N = 2{,}744$) does not fit in cache; memory bandwidth is a likely bottleneck. Switching to sparse (CSR) matrix storage would resolve this.
4. **MPI strong scaling (unsteady):** $S(4) = 1.61$**.** The sparse explicit-Euler kernel scales better than the dense steady solver for MPI; I/O serialisation limits OMP.
5. **Weak scaling.** Steady weak efficiency collapses ($< 3\%$ at $p = 4$) due to the $O(N^2)$ dense storage; unsteady weak efficiency is substantially better ($\sim 37\%$ at $p = 4$ for MPI) due to the $O(N)$ sparse stencil.



(a) $t = 0$ **(b)** $t \approx 1.4$ **(c)** $t \approx 2.8$ **(d)** $t \approx 4.2$ **(e)** $t \approx 5.6$

(f) $t \approx 7.0$ **(g)** $t \approx 8.4$ **(h)** $t \approx 9.8$ **(i)** $t \approx 11.2$

Figure 5: Unsteady temperature evolution (OpenMP, $l_c = 0.15$, 10,000 steps, $t_{\max} \approx 11.2$). Nine evenly-spaced snapshots show the transient: the uniform 100 °C initial field relaxes under the fixed Dirichlet boundary conditions and converges to the analytical steady solution (Fig. 2a) by $t \approx 11$. The MPI solution is pixel-identical at every snapshot.

The primary recommended extension is replacing the dense matrix with CSR storage, which reduces each GS-SOR row traversal from $O(N)$ to $O(k) \approx O(6)$ operations, while preserving all face-based adjacencies and is expected to make OpenMP competitive with MPI on shared-memory hardware.

Reproducibility

Source code, build scripts, and data files are available at `https://github.com/AadityanshuAbhinav/ID5130_Project`. Requires: GCC ≥10 with OpenMP, OpenMPI ≥4, and the Gmsh C++ API [4] (≥4.11).

Build.

```
# Serial
g++ -O2 -I<gmsh_inc> main_serial.cpp \
    -o main_serial -L<gmsh_lib> -lgmsh
# OpenMP
g++ -O2 -fopenmp -I<gmsh_inc> \
    main_omp.cpp -o main_omp \
    -L<gmsh_lib> -lgmsh
# MPI
mpicxx -O2 -I<gmsh_inc> main_mpi.cpp \
    -o main_mpi -L<gmsh_lib> -lgmsh
```

Convenience scripts `run_scaling_omp.sh` and `run_scaling_mpi.sh` compile, run, and record all scaling data automatically.

Run.

```
# Steady: lc=0.03, omega=1.5
./main_omp 0.03 1.5
mpirun -n 4 ./main_mpi 0.03 1.5

# Unsteady: lc=0.15, 10000 steps
./unsteady_omp 0.15 10000
mpirun -n 4 ./unsteady_mpi 0.15 10000

# Full scaling studies
bash run_scaling_omp.sh
bash run_scaling_mpi.sh

# Figures
python3 make_geometry_fig.py
python3 plot_all.py --all
```

Acknowledgment

The authors thank the teaching team of ID5130 Parallel Scientific Computing at IIT Madras for guidance throughout the project. Mesh generation was performed with Gmsh [4].

References

[1] S. V. Patankar, *Numerical Heat Transfer and Fluid Flow*. Hemisphere, Washington, DC, 1980.

[2] H. Jasak, "Error Analysis and Estimation for the Finite Volume Method with Applications to Fluid Flows." Ph.D. thesis, Imperial College of Science, Technology and Medicine, London, 1996.

[3] J. H. Ferziger, M. Perić, and R. L. Street, *Computational Methods for Fluid Dynamics*, 4th ed. Springer, Cham, 2020.

[4] C. Geuzaine and J.-F. Remacle, "Gmsh: A 3-D Finite Element Mesh Generator with Built-in Pre- and Post-Processing Facilities." *Int. J. Numer. Methods Eng.*, 79(11):1309–1331, 2009.

[5] G. M. Amdahl, "Validity of the Single Processor Approach to Achieving Large-Scale Computing Capabilities." *Proc. AFIPS Spring Joint Computer Conf.*, pp. 483–485, 1967.

[6] OpenMP Architecture Review Board, *OpenMP Application Programming Interface*, Version 5.2, 2021. `https://www.openmp.org`.

[7] MPI Forum, *MPI: A Message-Passing Interface Standard*, Version 4.0, 2021. `https://www.mpi-forum.org`.