



# Chapter 7: Query Processing

**Database System Concepts, 5th Ed.**

©Silberschatz, Korth and Sudarshan

See [www.db-book.com](http://www.db-book.com) for conditions on re-use





# Chapter 13: Query Processing


- Overview
- Measures of Query Cost
- Evaluation of Expressions





# Basic Steps in Query Processing

1. Parsing and translation
2. Optimization
3. Evaluation





# Basic Steps in Query Processing (Cont.)

- Parsing and translation
  - translate the query into its internal form. This is then translated into relational algebra.
  - Parser checks syntax, verifies relations
- Evaluation
  - The query-execution engine takes a query-evaluation plan, executes that plan, and returns the answers to the query.





# Basic Steps in Query Processing : Optimization

- A relational algebra expression may have many equivalent expressions
  - E.g.,  $\sigma_{balance < 2500}(\Pi_{balance}(account))$  is equivalent to  $\Pi_{balance}(\sigma_{balance < 2500}(account))$
- Each relational algebra operation can be evaluated using one of several different algorithms
  - Correspondingly, a relational-algebra expression can be evaluated in many ways.
- Annotated expression specifying detailed evaluation strategy is called an **evaluation-plan**.
  - E.g., can use an index on *balance* to find accounts with balance < 2500,
  - or can perform complete relation scan and discard accounts with balance  $\geq$  2500

The Query executive engine takes a query-evaluation plan, executes that plan, and returns the answers to the query..





# Basic Steps: Optimization (Cont.)

- **Query Optimization:** Amongst all equivalent evaluation plans choose the one with lowest cost.
  - Cost is estimated using statistical information from the database catalog
    - ▶ e.g. number of tuples in each relation, size of tuples, etc.
- In this chapter we study
  - How to measure query costs
- In Chapter Query Optimization
  - We study how to optimize queries, that is, how to find an evaluation plan with lowest estimated cost





# Measures of Query Cost

- Cost is generally measured as total elapsed time for answering query
  - Many factors contribute to time cost
    - ▶ *disk accesses, CPU, or even network communication*
- Typically disk access is the predominant cost, and is also relatively easy to estimate. Measured by taking into account
  - Number of seeks \* average-seek-cost
  - + Number of blocks read \* average-block-read-cost
  - + Number of blocks written \* average-block-write-cost
    - ▶ Cost to write a block is greater than cost to read a block
      - data is read back after being written to ensure that the write was successful
  - Assumption: single disk
    - ▶ Can modify formulae for multiple disks/RAID arrays
    - ▶ Or just use single-disk formulae, but interpret them as measuring **resource consumption** instead of time





# Measures of Query Cost (Cont.)

- For simplicity we just use the number of block transfers from disk and the number of seeks as the cost measures
  - $t_T$  – time to transfer one block
  - $t_S$  – time for one seek
  - Cost for b block transfers plus S seeks
$$b * t_T + S * t_S$$
- We ignore CPU costs for simplicity
  - Real systems do take CPU cost into account
- We do not include cost to writing output to disk in our cost formulae
- Several algorithms can reduce disk IO by using extra buffer space
  - Amount of real memory available to buffer depends on other concurrent queries and OS processes, known only during execution
    - ▶ We often use worst case estimates, assuming only the minimum amount of memory needed for the operation is available
- Required data may be buffer resident already, avoiding disk I/O
  - But hard to take into account for cost estimation







## Figure 13.2

