



Top 50 Data Structures Interview Questions

1) What is data structure?

Data structures refers to the way data is organized and manipulated. It seeks to find ways to make data access more efficient. When dealing with data structure, we not only focus on one piece of data, but rather different set of data and how they can relate to one another in an organized manner.

2) Differentiate file structure from storage structure.

Basically, the key difference is the memory area that is being accessed. When dealing with the structure that resides the main memory of the computer system, this is referred to as storage structure. When dealing with an auxiliary structure, we refer to it as file structures.

3) When is a binary search best applied?

A binary search is an algorithm that is best applied to search a list when the elements are already in order or sorted. The list is search starting in the middle, such that if that middle value is not the target search key, it will check to see if it will continue the search on the lower half of the list or the higher half. The split and search will then continue in the same manner.

4) What is a linked list?

A linked list is a sequence of nodes in which each node is connected to the node following it. This forms a chain-like link of data storage.

5) How do you reference all the elements in a one-dimension array?

To do this, an indexed loop is used, such that the counter runs from 0 to the array size minus one. In this manner, we are able to reference all the elements in sequence by using the loop counter as the array subscript.

6) In what areas do data structures applied?

Data structures is important in almost every aspect where data is involved. In general, algorithms that involve efficient data structure is applied in the following areas: numerical

analysis, operating system, A.I., compiler design, database management, graphics, and statistical analysis, to name a few.

7) What is LIFO?

LIFO is short for Last In First Out, and refers to how data is accessed, stored and retrieved. Using this scheme, data that was stored last, should be the one to be extracted first. This also means that in order to gain access to the first data, all the other data that was stored before this first data must first be retrieved and extracted.

8) What is a queue?

A queue is a data structures that can simulates a list or stream of data. In this structure, new elements are inserted at one end and existing elements are removed from the other end.

9) What are binary trees?

A binary tree is one type of data structure that has two nodes, a left node and a right node. In programming, binary trees are actually an extension of the linked list structures.

10) Which data structures is applied when dealing with a recursive function?

Recursion, which is basically a function that calls itself based on a terminating condition, makes use of the stack. Using LIFO, a call to a recursive function saves the return address so that it knows how to return to the calling function after the call terminates.

11) What is a stack?

A stack is a data structure in which only the top element can be accessed. As data is stored in the stack, each data is pushed downward, leaving the most recently added data on top.

12) Explain Binary Search Tree

A binary search tree stores data in such a way that they can be retrieved very efficiently. The left subtree contains nodes whose keys are less than the node's key value, while the right subtree contains nodes whose keys are greater than or equal to the node's key value. Moreover, both subtrees are also binary search trees.

13) What are multidimensional arrays?

Multidimensional arrays make use of multiple indexes to store data. It is useful when storing data that cannot be represented using a single dimensional indexing, such as data representation in a board game, tables with data stored in more than one column.

14) Are linked lists considered linear or non-linear data structures?

It actually depends on where you intend to apply linked lists. If you based it on storage, a linked list is considered non-linear. On the other hand, if you based it on access strategies, then a linked list is considered linear.

15) How does dynamic memory allocation help in managing data?

Aside from being able to store simple structured data types, dynamic memory allocation can combine separately allocated structured blocks to form composite structures that expand and contract as needed.

16) What is FIFO?

FIFO is short for First-in, First-out, and is used to represent how data is accessed in a queue. Data has been inserted into the queue list the longest is the one that is removed first.

17) What is an ordered list?

An ordered list is a list in which each node's position in the list is determined by the value of its key component, so that the key values form an increasing sequence, as the list is traversed.

18) What is merge sort?

Merge sort takes a divide-and-conquer approach to sorting data. In a sequence of data, adjacent ones are merged and sorted to create bigger sorted lists. These sorted lists are then merged again to form an even bigger sorted list, which continues until you have one single sorted list.

19) Differentiate NULL and VOID.

Null is actually a value, whereas Void is a data type identifier. A variable that is given a Null value simply indicates an empty value. Void is used to identify pointers as having no initial size.

20) What is the primary advantage of a linked list?

A linked list is a very ideal data structure because it can be modified easily. This means that modifying a linked list works regardless of how many elements are in the list.

21) What is the difference between a PUSH and a POP?

Pushing and popping applies to the way data is stored and retrieved in a stack. A push denotes data being added to it, meaning data is being "pushed" into the stack. On the other hand, a pop denotes data retrieval, and in particular refers to the topmost data being accessed.

22) What is a linear search?

A linear search refers to the way a target key is being searched in a sequential data structure.

Using this method, each element in the list is checked and compared against the target key, and is repeated until found or if the end of the list has been reached.

23) How does variable declaration affect memory allocation?

The amount of memory to be allocated or reserved would depend on the data type of the variable being declared. For example, if a variable is declared to be of integer type, then 32 bits of memory storage will be reserved for that variable.

24) What is the advantage of the heap over a stack?

Basically, the heap is more flexible than the stack. That's because memory space for the heap can be dynamically allocated and de-allocated as needed. However, memory of the heap can at times be slower when compared to that stack.

25) What is a postfix expression?

A postfix expression is an expression in which each operator follows its operands. The advantage of this form is that there is no need to group sub-expressions in parentheses or to consider operator precedence.

26) What is Data abstraction?

Data abstraction is a powerful tool for breaking down complex data problems into manageable chunks. This is applied by initially specifying the data objects involved and the operations to be performed on these data objects without being overly concerned with how the data objects will be represented and stored in memory.

27) How do you insert a new item in a binary search tree?

Assuming that the data to be inserted is a unique value (that is, not an existing entry in the tree), check first if the tree is empty. If it's empty, just insert the new item in the root node. If it's not empty, refer to the new item's key. If it's smaller than the root's key, insert it into the root's left subtree, otherwise, insert it into the root's right subtree.

28) How does a selection sort work for an array?

The selection sort is a fairly intuitive sorting algorithm,, though not necessarily efficient. To perform this, the smallest element is first located and switched with the element at subscript zero, thereby placing the smallest element in the first position. The smallest element remaining in the subarray is then located next with subscripts 1 through n-1 and switched with the element at subscript 1, thereby placing the second smallest element in the second position. The steps are repeated in the same manner till the last element.

29) How do signed and unsigned numbers affect memory?

In the case of signed numbers, the first bit is used to indicate whether positive or negative, which leaves you with one bit short. With unsigned numbers, you have all bits available for that number. The effect is best seen in the number range (unsigned 8 bit number has a range 0-255, while 8-bit signed number has a range -128 to +127).

30) What is the minimum number of nodes that a binary tree can have?

A binary tree can have a minimum of zero nodes, which occurs when the nodes have NULL values. Furthermore, a binary tree can also have 1 or 2 nodes.

31) What are dynamic data structures?

Dynamic data structures are structures that expand and contract as a program runs. It provides a flexible means of manipulating data because it can adjust according to the size of the data.

32) In what data structures are pointers applied?

Pointers that are used in linked list have various applications in data structure. Data structures that make use of this concept include the Stack, Queue, Linked List and Binary Tree.

33) Do all declaration statements result in a fixed reservation in memory?

Most declarations do, with the exemption of pointers. Pointer declaration does not allocate memory for data, but for the address of the pointer variable. Actual memory allocation for the data comes during run-time.

34) What are ARRAYS?

When dealing with arrays, data is stored and retrieved using an index that actually refers to the element number in the data sequence. This means that data can be accessed in any order. In programming, an array is declared as a variable having a number of indexed elements.

35) What is the minimum number of queues needed when implementing a priority queue?

The minimum number of queues needed in this case is two. One queue is intended for sorting priorities while the other queue is intended for actual storage of data.

36) Which sorting algorithm is considered the fastest?

There are many types of sorting algorithms: quick sort, bubble sort, balloon sort, radix sort, merge sort, etc. Not one can be considered the fastest because each algorithm is designed for a particular data structure and data set. It would depend on the data set that you would want to sort.

37) Differentiate STACK from ARRAY.

Data that is stored in a stack follows a LIFO pattern. This means that data access follows a sequence wherein the last data to be stored will be the first one to be extracted. Arrays, on the other hand, do not follow a particular order and instead can be accessed by referring to the indexed element within the array.

38) Give a basic algorithm for searching a binary search tree.

1. if the tree is empty, then the target is not in the tree, end search
2. if the tree is not empty, the target is in the tree
3. check if the target is in the root item
4. if target is not in the root item, check if target is smaller than the root's value
5. if target is smaller than the root's value, search the left subtree
6. else, search the right subtree

39) What is a dequeue?

A dequeue is a double-ended queue. This is a structure wherein elements can be inserted or removed from either end.

40) What is a bubble sort and how do you perform it?

A bubble sort is one sorting technique that can be applied to data structures such as an array. It works by comparing adjacent elements and exchanges their values if they are out of order. This method lets the smaller values “bubble” to the top of the list, while the larger value sinks to the bottom.

41) What are the parts of a linked list?

A linked list typically has two parts: the head and the tail. Between the head and tail lie the actual nodes, with each node being linked in a sequential manner.

42) How does selection sort work?

Selection sort works by picking the smallest number from the list and placing it at the front. This process is repeated for the second position towards the end of the list. It is the simplest sort algorithm.

43) What is a graph?

A graph is one type of data structure that contains a set of ordered pairs. These ordered pairs are also referred to as edges or arcs, and are used to connect nodes where data can be stored and retrieved.

44) Differentiate linear from non linear data structure.

Linear data structure is a structure wherein data elements are adjacent to each other. Examples

of linear data structure include arrays, linked lists, stacks and queues. On the other hand, non-linear data structure is a structure wherein each data element can connect to more than two adjacent data elements. Examples of non linear data structure include trees and graphs.

45) What is an AVL tree?

An AVL tree is a type of binary search tree that is always in a state of partially balanced. The balance is measured as a difference between the heights of the subtrees from the root. This self-balancing tree was known to be the first data structure to be designed as such.

46) What are doubly linked lists?

Doubly linked lists are a special type of linked list wherein traversal across the data elements can be done in both directions. This is made possible by having two links in every node, one that links to the next node and other one that links to the previous node.

47) What is Huffman's algorithm?

Huffman's algorithm is associated in creating extended binary trees that has minimum weighted path lengths from the given weights. It makes use of a table that contains frequency of occurrence for each data element.

48) What is Fibonacci search?

Fibonacci search is a search algorithm that applies to a sorted array. It makes use of a divide-and-conquer approach that can greatly reduce the time needed in order to reach the target element.

49) Briefly explain recursive algorithm.

Recursive algorithm targets a problem by dividing it into smaller, manageable sub-problems. The output of one recursion after processing one sub-problem becomes the input to the next recursive process.

50) How do you search for a target key in a linked list?

To find the target key in a linked list, you have to apply sequential search. Each node is traversed and compared with the target key, and if it is different, then it follows the link to the next node. This traversal continues until either the target key is found or if the last node is reached.

Java	MIS	MongoDB	BigData	Cassandra
Web Services	SQLite	JSP	Informatica	Accounting
SAP Training	Python	Excel	ASP Net	HBase
Project Management	Test Management	Business Analyst	Ethical Hacking	PMP
Live Project	SoapUI	Photoshop	Manual Testing	Mobile Testing
Selenium	CCNA	AngularJS	NodeJS	PLSQL

**Stay updated with new
courses at Guru99
Join our Newsletter**