

# # Coin Change Problem

if arr = 

1	2	3
0	1	2

 target = 5

you have to find minimum no. of element  $\rightarrow$  to reach the target sum.

$\{1, 1, 1, 1, 1\} \rightarrow 5$   
 $\{1, 2, 1, 1\} \rightarrow 4$

$\{2, 2, 1\} \rightarrow 3$


$\{3, 1, 1\} \rightarrow 3$

$\{3, 2\} \rightarrow 2$   $\rightarrow$  minimum no. of element to reach target sum.

Note Target Reach krne ke we have 2 way

- 1) target  $\rightarrow 0$  (if target  $= 0$ ) means reach target
- 2)  $0 \rightarrow 5$  (target)  $\rightarrow$  target reach hojaga, but here use Additional variable, joki 5 ko store krega, jisse hum 0 me up date krke 5 ko reach krve.
- original value ko decrease krega 0 le janne ke lie
- original ko store krke comparison

Extra variable lekr usko update krenge upto 5 Kyuki last me check bhi to krna pdega, na ki kya jo variable lie hai wo target ke barabar hai ki nhi



PAGE No.			
DATE			




Sun	Mon	Tue	Wed	Thu	Fri	Sat
1	2	3	4	5	6	7
8	9	10	11	12	13	14
15	16	17	18	19	20	21
22	23	24	25	26	27	28
29	30	31				

if both equal means, we reach target

target = 5

1, 2  
0, 1

Ex -



Wednesday



21

Thursday

Sun	Mon	Tue	Wed	Thu	Fri	Sat
6	7	8	9	10	11	12
13	14	15	16	17	18	19
20	21	22	23	24	25	26
27	28	29	30	31		

```


int solve(arr, target)
{
}

```

give min. no. of coins required to reach the target sum

arr = [1, 2, 5] target = 11

min. no. of coins to reach 11




ge sb hure function de rha hai

22


Friday

min. of coins to reach 10









So Our final ans = 2

-ve value ko ignore krna hai is line

```

if (target < 0)
{
    mini = INTMAX
}

```

bcz 0 Barane ko lie mujhe  
 0 coin chahiye but  
 0 tk ans ke lie main  
 ek 3 ka coin bhi  
 to use krna hua  
 that's way it  
 return  $ans + 1$

DATE \_\_\_\_\_  
 PAGE \_\_\_\_\_

## Cut into segments

ip  $\rightarrow$   $N$  - odd length.

Maximum no of segments but only with  $x, y, z$ .

eg.  $N = 7$   
 $x = 5$   
 $y = 2$   
 $z = 2$

```
int main() {
    int n = 7;
    int x = 5;
    int y = 2;
    int z = 2;
```

```
    int ans = solve(n, x, y, z);
    cout << "Ans is " << ans << endl;
    return 0;
}
```

```
int solve(int n, int x, int y, int z) {
    if (n == 0) {
        return 0;
    }
    ? int ans = 0;
    if (n - x >= 0) {
        ans = solve(n - x, x, y, z) + 1;
    }
    int b = 0;
    if (n - y >= 0) {
        b = solve(n - y, x, y, z) + 1;
    }
}
```

if (ans < 0)  
 ans = 0;




```

int c=0;
if (n-2 >= 0) {
    c = solve(n-2, x, y, 2) + 1;
}
int ans = max(a, max(b, c));
return ans;


```

Ex-2)




eg.

$n=2$   
 $x=5$   
 $y=2$   
 $z=2$







Reason of  $1 + ans$

3) Maximum sum of non adjacent elements

i/p: 

2	1	4	9
---	---	---	---

Returns the max sum of subsequence in which no two elements are adjacent

$$\left. \begin{array}{l} 2+4=6 \\ 1+9=10 \\ 2+9=11 \end{array} \right\}$$

$i=0$

2	4	4	9
---	---	---	---

inc  
 $i=i+2$

exc  
 $i$

2	1	4	9
---	---	---	---

2	1	4	9
---	---	---	---

inc

exc

2	1	4	9	$i$
---	---	---	---	-----

2	1	4	9
---	---	---	---

$\downarrow$   
B.C.

Question me Sub sequence ki bt kia hai mtlb sub sequence me element ka preset or absent hota hai

means Use Include / Exclude Technique