

Configuration

With a basic knowledge of Qt, you could change the configuration of the default Kvantum theme. That configuration can be easily copied by using **Kvantum Manager** (click *Save* button on its third page) or, manually, by following these steps:

- (1) Create the folder “`~/.config/Kvantum/`” (~ is your home);
- (2) Create the file “`kvantum.kvconfig`” in the above folder with this line in it:

theme=***DefaultCopy***

Here, ***DefaultCopy*** could be any name you choose for the new configuration;

- (3) Create the folder “`~/.config/Kvantum/DefaultCopy/`” and the file “`DefaultCopy.kvconfig`” in it;
- (4) Copy/paste the contents of “`style/themeconfig/default.kvconfig`” (from the source) to the file “`DefaultCopy.kvconfig`”.

Now, you can change the values of variables (keys). Please note that deleting a variable often means that its value will be taken from the default configuration, so that you could keep only those sections or variables you want to change. See [below](#) for a more accurate explanation.

There are many sections (groups) and variables (keys) in the config file. That's intentional: unlike most theme engines, Kvantum is supposed to be able to control virtually all aspects of widgets. Here are the meanings of various sections:

Sections Table

| Section (Group) | Meaning |
|----------------------|--|
| [%General] | General info on the theme and some general variables. |
| [GeneralColors] | The most important colors used by the theme. |
| [Hacks] | Hacks for specific apps or widgets. |
| [PanelButtonCommand] | Panel for a button used to initiate an action, for example, a push button. |
| [PanelButtonTool] | Panel for a tool button. |

| | |
|-----------------------|---|
| [Dock] | A dock widget. |
| [DockTitle] | The title of a dock widget. |
| [IndicatorSpinBox] | Indicators of a spin widget. |
| [RadioButton] | A radio button. |
| [CheckBox] | A check box. |
| [Focus] | Generic focus frame. |
| [GenericFrame] | Generic frame. |
| [LineEdit] | A line edit (one-line text editor). |
| [DropDownButton] | Indicator for a drop down button, for example, a tool button that displays a menu. |
| [ToolboxTab] | Just text colors for tab labels of a toolbox. |
| [Tab] | The tab shape within a tab bar. Also the tear indicator of a tab bar and the close button of a tab. |
| [TabFrame] | The frame for tab widgets. |
| [TabBarFrame] | The frame that is drawn for a tab bar, ususally for a tab bar that isn't part of a tab widget. |
| [TreeExpander] | Indicators used to represent the branch of a tree in a tree view. |
| [HeaderSection] | A header section. Also its label and arrow. |
| [SizeGrip] | Window resize handle if it exists. |
| [Toolbar] | A toolbar. Also its handle and separator. |
| [Scrollbar] | Scrollbar increase/decrease indicators (arrows). |
| [ScrollbarGroove] | The groove of a scrollbar. |
| [ScrollbarSlider] | A scrollbar slider. |
| [Slider] | A slider (a classic widget for controlling a bounded value). |
| [SliderCursor] | The handle of a slider. |
| [Progressbar] | The groove and label of a progressbar. |
| [ProgressbarContents] | The progress indicator. |
| [ItemView] | An item in an item view. |
| [Splitter] | A splitter handle. |
| [Menu] | The panel and frame of a menu. Also its frame shadow. |
| [MenuItem] | A menu item in a menu. Also the tear-off section of a menu. |
| [MenuBar] | The empty area of a menu bar. |
| [MenuBarItem] | A menu bar item, like the buttons in a menubar. |
| [TitleBar] | A title bar, like those used in QMdiSubWindow. |
| [ComboBox] | A combo box and its label. |

| | |
|---------------------|---|
| [GroupBox] | A group box and the frame around it. |
| [ToolTip] | The panel for a tooltip label. |
| [Window] | A window or dialog. |
| [WindowTranslucent] | This is used when a distinction is needed to be made between opaque and translucent windows. If it is omitted, the above section is used for all windows. |

The following table shows the variables (keys) you could change to configure the current theme – without necessarily making a new one. These are the rules for the value inheritance:

(1) If a section (group) is not present in your configuration, its variables and their values will be taken from the default config file.

(2) If a variable is not present in a section of your configuration:

(2a) First the “*inherits*” section will be searched for it and then, if nothing is found,

(2b) its value will be taken from the same section of the default config file.

There are three exceptions to these rules:

Exception No.1: The “*inherits*” variable will not be taken from the default config file if it is not present in a section.

Exception No.2: If colors are omitted or not valid or if a section they could belong to is not present, they will be taken from the currently used color scheme. Also font boldness/italicity will be ignored if omitted.

Exception No.3: Any variable related to compositing or hacking will be ignored if omitted.

Variables Table

| Variable (Key) | Value | Meaning |
|-----------------------------------|------------|---|
| <i>The General Section</i> | | |
| author | string | Obvious. |
| comment | string | Obvious. |
| x11drag | true/false | Drag windows from anywhere possible? |
| alt_mnemonic | true/false | Show underlines only when Alt is pressed? |

| | | |
|--------------------------|------------|--|
| double_click | true/false | Activate view items on double clicking? They are activated on single clicking by default but the KDE setting has priority over the default. |
| vertical_spin_indicators | true/false | Draw spin indicators vertically and inside the spin line-edit? By default, they are drawn on adjacent buttons. |
| left_tabs | true/false | Align tabs to the left edge? Tabs are centered by default. |
| joined_tabs | true/false | Join tabs together? They are detached by default. |
| attach_active_tab | true/false | Attach the active tab to the tab widget? It is detached by default. |
| mirror_doc_tabs | true/false | In the document mode, mirror the top/left tab shape to draw the bottom/right tab? True by default, which means that the bottom and right tab shapes are always the mirror images of the top and left ones, respectively. Setting this key to false will change this behavior <i>only if the tab widget is in the document mode</i> , so that the top/right and bottom/left tab shapes will be identical. |
| group_toolbar_buttons | true/false | Raise and group neighbor toolbar buttons? By default, they are not raised. |
| center_toolbar_handle | true/false | If true, the SVG element for the toolbar handle will be centered and its size will be that of the toolbar indicator. Otherwise, it will be scaled vertically with an 8-px width. False by default. |
| slim_toolbars | true/false | When true, the size of toolbar icons will be 16px if it is not set in the app. If false, the size will be determined by the DE or the app. True by default. |
| toolbutton_style | integer | Sets the toolbutton style when it is not set by the app. 0: follow, 1: icon only, 2: text only, 3: text beside icon, and 4: text under icon. The toolbutton style is 0 by default. |
| spread_progressbar | true/false | Spread progressbar's indicator across its whole groove and not just its interior? By default, the indicator is drawn inside progressbar's frame. |
| textless_progressbar | true/false | No percentage label for progressbars? They have percentage labels by default – unless the labels do not fit into the bars because of a small value for the following key. |

| | | |
|----------------------------|-------------|---|
| progressbar_thickness | integer | If positive, it sets the (maximum) progressbar thickness. It is zero by default, which means there is no limit to progressbar thickness. |
| menubar_mouse_tracking | true/false | Enable mouse tracking in menubars? It is enabled by default. |
| merge_menubar_with_toolbar | true/false | Draw adjacent menu and tool bars as a whole? If true, the toolbar SVG interior and frame will be used for drawing them. |
| composite | true/false | Use compositing to have translucent menus or tooltips? It is automatically set to false if no compositing is available. Its absence also means false. |
| menu_shadow_depth | integer | The depth of the shadow menus cast. A value of zero, its absence or a false value for <i>composite</i> means no shadow. |
| tooltip_shadow_depth | integer | The depth of the shadow tooltips cast. A value of zero, its absence or a false value for <i>composite</i> means no shadow. |
| translucent_windows | true/false | Translucent windows and dialogs? This requires a translucent SVG element too. A false value, its absence or a false value for <i>composite</i> means no translucency. |
| opaque | String list | A comma-separated list of executables, whose apps should not have window translucency. It has meaning only if <i>translucent_windows</i> is set to true. |
| blurring | true/false | Blur the screen area behind translucent windows in KDE? This needs KDE blur effect and also a graphic card that supports it. It has no effect when <i>composite</i> or <i>translucent_windows</i> is false. |
| popup_blurring | true/false | Blur the regions behind translucent menus and tooltips? This needs KDE blur effect and a graphic card that supports it. It will automatically be set to true if blurring is true. |
| splitter_width | integer | The width of splitter handles. 7Px by default. |
| scroll_width | integer | The width of scrollbars. The default value is 12px. |
| scroll_arrows | true/false | Draw scrollbar add-line and sub-line arrows? True by default. If set to false, it will remove scroll arrows as far as possible but some apps might still force scroll arrows. |
| slider_width | integer | The width of sliders. The default value is 8px. |

| | | |
|---|------------|---|
| slider_handle_width slider_handle_length | integer | The width or height of slider handles. The default values are 16px. |
| check_size | integer | The width and height of checkboxes and radio buttons. The default value is 13px. |
| small_icon_size large_icon_size button_icon_size toolbar_icon_size | integer | These affect menu-items/headers, icon-views, buttons/tabbars/listviews, and toolbars respectively. KDE setting will have priority over these values if it exists. |
| fill_rubberband | true/false | Always fill the rubber-band rectangle with the highlight color? By default, drop rectangles for movable toolbars and dock widgets are hollow. |

The GeneralColors Section

| | | |
|--------------------------|---------------------|---|
| window.color | String (#RRGGBB) | A general background color as #RRGGBB or with a valid name like white, black, red, etc. |
| base.color | String (#RRGGBB) | Used mostly as the background color for text entry widgets. |
| alt.base.color | String (#RRGGBB) | Used as the alternate background color in views with alternating row colors. |
| button.color | String (#RRGGBB) | The general button background color. |
| light.color | String (#RRGGBB) | Lighter than <i>button.color</i> (used mostly for 3D bevels). |
| mid.light.color | String (#RRGGBB) | Between <i>button.color</i> and <i>light.color</i> (used mostly for 3D bevels). |
| dark.color | String (#RRGGBB) | Darker than <i>button.color</i> (used mostly for 3D bevels). |
| mid.color | String (#RRGGBB) | Between <i>button.color</i> and <i>dark.color</i> (used mostly for 3D bevels). |
| shadow.color | String (#RRGGBB) | A very dark color. By default, it is black. (used mostly for 3D bevels). |
| highlight.color | String (#RRGGBB) | A color for text selection. |
| inactive.highlight.color | String (#RRGGBB) | Like <i>highlight.color</i> but when the text widget does not have focus. |
| tooltip.base.color | String (#RRGGBB) | Tooltip background color (used in "WhatsThis" tooltips). |

| | | |
|-------------------------------|---------------------|---|
| text.color | String (#RRGGBB) | The foreground color used with <i>base.color</i> . |
| window.text.color | String (#RRGGBB) | A general foreground color. |
| button.text.color | String (#RRGGBB) | Obvious. |
| disabled.text.color | String (#RRGGBB) | Obvious. |
| tooltip.text.color | String (#RRGGBB) | Obvious. |
| highlight.text.color | String (#RRGGBB) | The color of selected text. |
| link.color | String (#RRGGBB) | Obvious. |
| link.visited.color | String (#RRGGBB) | Obvious. |
| progress.indicator.text.color | String (#RRGGBB) | The color of that part of the progress text, which is inside the progress indicator. Useful when the progress text does not have enough contrast with the progress indicator. |

The Hacks Section

| | | |
|-----------------------------|------------|---|
| transparent_dolphin_view | true/false | No background or frame for Dolphin's view (Dolphin is the file manager of KDE)? |
| blur_konsole | true/false | Blur the region behind Konsole's transparent background if possible? |
| transparent_ktitle_label | true/false | No background for the label of KtitleWidget (a KDE widget with a heading label)? |
| transparent_menutitle | true/false | No background for (KDE) menu titles? |
| kcapacitybar_as_progressbar | true/false | Draw KCapacityBar as progressbar? KCapacityBar has its hard-coded style by default. |
| respect_darkness | true/false | Some apps don't respect dark themes. Fix that as far as possible? |
| force_size_grip | true/false | Show the size grips of dialogs and statusbars as far as possible? |

| <i>Other Sections</i> | | |
|--|---------------------|--|
| inherits | string | The name of a section (in the same config file and without brackets) whose configuration is also used for this one. |
| frame | true/false | Draw a frame around the widget? |
| frame.top frame.bottom frame.left frame.right | integer | The height or width of the corresponding frame part. |
| frame.expansion | integer | A positive value will expand the frames until the corner frames meet each other either vertically or horizontally, <i>provided that at least the height or the width of the widget is not greater than it</i> . With appropriate SVG images, this key can be used for making corners completely rounded. Its value is zero by default. Read the file <i>Theme-Making.pdf</i> for an explanation. |
| interior | true/false | Draw an interior for the widget? |
| interior.x.patternsize interior.y.patternsize | integer | The interior pattern sizes. Used for tiling the interior of a widget with a pattern. A value of zero means no tiling in the corresponding direction. Their absence also means no pattern. <i>Some widget types may never accept patterns.</i> |
| indicator.size | integer | Some widgets, like scrollbar arrows, have indicators. This is their size. |
| text.margin | true/false | Put a margin around the text? |
| text.margin.top text.margin.bottom text.margin.left text.margin.right | integer | The sizes of the text margins if there is any. |
| text.normal.color | String (#RRGGBB) | <p>The color of the normal text as #RRGGBB or with a valid name like white, black, red, etc. It may override the text colors defined under the GeneralColors section.</p> <p>Note: State-specific text colors do not have meaning for <i>Window</i>, <i>Dock</i>, <i>LineEdit</i> and frame widgets (namely <i>GenericFrame</i>, <i>TabFrame</i> and <i>TabBarFrame</i>).</p> |

| | | |
|--|---------------------|---|
| text.focus.color | String (#RRGGBB) | The color of the focused (hover) text. |
| text.press.color | String (#RRGGBB) | The color of the pressed text. |
| text.toggle.color | String (#RRGGBB) | The color of the toggled text. |
| text.bold | true/false | Bold font for text? The font is not bold by default. |
| text.italic | true/false | Italic font for text? The font is not italic by default. |
| text.shadow | true/false | Draw a shadow for the text? |
| text.shadow.xshift text.shadow.yshift | integer | The vertical/horizontal shifts of the text shadow if it exists. |
| text.shadow.color | string (#RRGGBB) | The color of the text shadow as #RRGGBB or with a valid name like white, black, red, etc. |
| text.shadow.alpha | integer (0-255) | The opacity of the text shadow. 255 means completely opaque. |
| text.shadow.depth | integer | The text shadow depth. |
| size.minwidth size.minheight | integer | Minimum/fixed width or height of a menu/menuitem, for example. |

If you want to make your own theme (see the file "Theme-Making"), you'll also need to know the meanings of these variables:

Elements Table

| Variable (Key) | Value | Meaning |
|-------------------|--------|---|
| interior.element | string | The SVG element to be used for drawing the interior of a widget. |
| frame.element | string | The SVG element to be used for drawing the frame of a widget. |
| indicator.element | string | The SVG element to be used for drawing the indicator of a widget. |

Some Examples

If you don't want menus and tooltips to be translucent or cast shadow and want the color scheme to be used for all texts, you could use a blank configuration or a very basic one with just this in it:

[%General]

You could also be more explicit:

```
[%General]  
composite=false  
  
[PanelButtonCommand]  
text.normal.color=none  
text.focus.color=none  
text.press.color=none  
text.toggle.color=none
```

Here “none” is not a valid color, so text colors will be taken from the currently used color scheme.

If you want to have bigger buttons without increasing your font sizes, you could use this:

```
[%General]  
composite=true  
menu_shadow_depth=6  
tooltip_shadow_depth=6  
  
[PanelButtonCommand]  
text.normal.color=white  
text.focus.color=#80C0FF  
text.press.color=white  
text.toggle.color=white  
text.margin.top=4  
text.margin.bottom=4  
text.margin.left=5  
text.margin.right=5  
  
[PanelButtonTool]  
inherits=PanelButtonCommand
```

To have black text shadows with light green focused text, use this (black text shadows are already defined but disabled in the default config file):

```
[%General]  
composite=true  
menu_shadow_depth=6  
tooltip_shadow_depth=6
```

```
[PanelButtonCommand]  
text.normal.color=white  
text.focus.color=lightgreen  
text.press.color=white  
text.toggle.color=white  
text.shadow=true
```

Note that, in the two examples above, the compositing values and normal/focused/pressed text colors are also added because otherwise, they would be disabled ([see the exceptions above](#)). In the previous example, customized text colors were disabled for all widgets other than push-buttons because there were no sections for them. If you want them back, you could add sections like these:

```
[PanelButtonTool]  
inherits=PanelButtonCommand  
[Tab]  
inherits=PanelButtonCommand  
[MenuItem]  
inherits=PanelButtonCommand
```

And so on.