

AIM

To understand the concept of classes and objects in Kotlin by creating a class with properties and methods, and accessing them using an object in an Android application.

Procedure

1. Open Android Studio and your project.
2. Open activity_main.xml and add a **TextView** and **Button**.
3. Create a new Kotlin class named Student.
4. Define properties and a method inside the class.
5. Open MainActivity.kt.
6. Create an object of the class inside onCreate().
7. Call the class method using the object.
8. Display the result in the TextView.
9. Run the app and observe output.

Code**Student.kt**

```
package com.example.kotlinbasics

class Student(val name: String, val rollNo: Int) {

    fun displayDetails(): String {
        return "Name: $name\nRoll No: $rollNo"
    }
}
```

activity_main.xml

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:gravity="center"
    android:orientation="vertical">

    <Button
        android:id="@+id/btnShow"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Show Details"/>

    <TextView
```

```
        android:id="@+id/txtOutput"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:textSize="18sp"/>
</LinearLayout>
```

MainActivity.kt

```
package com.example.kotlinbasics
```

```
import android.os.Bundle
import android.widget.Button
import android.widget.TextView
import androidx.appcompat.app.AppCompatActivity
```

```
class MainActivity : AppCompatActivity() {

    override fun onCreate(savedInstanceState: Bundle?) {
        super.onCreate(savedInstanceState)
        setContentView(R.layout.activity_main)

        val btn = findViewById<Button>(R.id.btnShow)
        val txt = findViewById<TextView>(R.id.txtOutput)

        btn.setOnClickListener {

            // Creating object
            val student = Student("Ravi", 101)

            // Display output
            txt.text = student.displayDetails()
        }
    }
}
```

Result

The application successfully demonstrates classes and objects by displaying:

