

# GE23131-Programming Using C-2024

Quiz navigation

1

2

3

Show one page at a time

Finish review

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Saturday, 14 December 2024, 2:54 PM
Duration	9 days 2 hours

Question 1

Correct

Marked out of 3.00

Flag question

Some data sets specify dates using the year and day of year rather than the year, month, and day of month. The day of year (DOY) is the sequential day number starting with day 1 on January 1st.

There are two calendars - one for normal years with 365 days, and one for leap years with 366 days. Leap years are divisible by 4. Centuries, like 1900, are not leap years unless they are divisible by 400. So, 2000 was a leap year.

To find the day of year number for a standard date, scan down the Jan column to find the day of month, then scan across to the appropriate month column and read the day of year number. Reverse the process to find the standard date for a given day of year.

Write a program to print the Day of Year of a given date, month and year.

Sample Input 1

## Sample Output 1

170

**Answer:** (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int d,m,y,feb;
5      scanf("%d%d%d",&d,&m,&y);
6      if((y%100==0&& y%400) || (y%4==0))
7          feb=29;
8      else
9          feb=28;
10     switch(m)
11     {
12         case 1:
13             printf("%d",d);
14             break;
15         case 2:
16             printf("%d",31+d);
17             break;
18         case 3:
19             printf("%d",31+feb+d);
20             break;
21         case 4:
22             printf("%d",31+feb+31+d);
23             break;
24         case 5:
25             printf("%d",31+feb+31+30+d);
26             break;
27         case 6:
28             printf("%d",31+feb+31+30+31+d);
29             break;
```

```
32     break;
33     case 8:
34         printf("%d", 31+feb+31+30+31+30+31+d);
35         break;
36     case 9:
37         printf("%d", 31+feb+31+30+31+30+31+31+d);
38         break;
39     case 10:
40         printf("%d", 31+feb+31+30+31+30+31+31+30+d);
41         break;
42     case 11:
43         printf("%d", 31+feb+31+30+31+30+31+31+30+31+d);
44         break;
45     case 12:
46         printf("%d", 31+feb+31+30+31+30+31+31+30+31+30+d);
47         break;
48     }
49 }
50
```

	Input	Expected	Got	
✓	18	170	170	✓
	6			
	2020			

Passed all tests! ✓

Question **2**

Correct

Marked out of  
5.00

Suppandi is trying to take part in the local village math quiz. In the first round, he is asked about shapes and areas. Suppandi, is confused, he was never any good at math.

- When he says rectangle he is actually referring to a square.
- When he says square, he is actually referring to a triangle.
- When he says triangle he is referring to a rectangle
- And when he is confused, he just says something random. At this point, all you can do is say 0.

Help Suppandi by printing the correct answer in an integer.

Input Format

- Name of shape (always in upper case R à Rectangle, S à Square, T à Triangle)
- Length of 1 side
- Length of other side

Note: In case of triangle, you can consider the sides as height and length of base

Output Format

- Print the area of the shape.

Sample Input 1

T  
10

Sample Output 1

200

Sample Input 2

S

30

40

Sample Output 2

600

Sample Input 3

R

10

10

Sample Output 3

100

G

8

8

Sample Output 4

0

Sample Input

C

9

10

Sample Output 4

0

Explanation:

- First is output of area of rectangle
- Then, output of area of triangle
- Then output of area square

**Answer:** (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b;
5     char c;
6     scanf("%c%d%d",&c,&a,&b);
7     switch(c)
8     {
9         case 'R':
10            printf("%d",a*b);
11            break;
12         case 'S':
13            printf("%.0f",(0.5)*a*b);
14            break;
15         case 'T':
16            printf("%d",a*b);
17            break;
18         default:
19            printf("0");
20     }
21 }
22
```

	Input	Expected	Got	
✓	T 10 20	200	200	✓
✓	S 30 40	600	600	✓

	11			
✓	R	300	300	✓
	10			
	30			
✓	S	1000	1000	✓
	40			
	50			

Passed all tests! ✓

Question **3**

Correct

Marked out of  
7.00

🚩 [Flag question](#)

Superman is planning a journey to his home planet. It is very important for him to know which day he arrives there. They don't follow the 7-day week like us. Instead, they follow a 10-day week with the following days: Day Number Name of Day 1 Sunday 2 Monday 3 Tuesday 4 Wednesday 5 Thursday 6 Friday 7 Saturday 8 Kryptonday 9 Coluday 10 Daxamday Here are the rules of the calendar: • The calendar starts with Sunday always. • It has only 296 days. After the 296th day, it goes back to Sunday. You begin your journey on a Sunday and will reach after n. You have to tell on which day you will arrive when you reach there.

Input format: •

Contain a number n ( $0 < n$ )

Output format: Print the name of the day you are arriving on

Example Input

7

Example Output

Kryptonday

Example Input

1



**Answer:** (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n,day;
5     scanf("%d",&n);
6     if(n<296)
7         day=n;
8     else
9         day=n-296;
10    day%=10;
11    day=day+1;
12    day%=10;
13    switch(day)
14    {
15        case 1:
16            printf("Sunday");
17            break;
18        case 2:
19            printf("Monday");
20            break;
21        case 3:
22            printf("Tuesday");
23            break;
24        case 4:
25            printf("Wednesday");
26            break;
27        case 5:
28            printf("Thursday");
29            break;
30        case 6:
31            printf("Friday");
32            break;
33        case 7:
34            printf("Saturday");
35            break;
36        case 8:
37            printf("Kryptonday");
38            break;
39        case 9:
40            printf("Clouday");
41            break;
42    }
```

```
44 |         break;
45 |     }
46 | }
```

	Input	Expected	Got	
✓	7	Kryptonday	Kryptonday	✓
✓	1	Monday	Monday	✓

Passed all tests! ✓

Finish review