Study Project on

Simpson's Integration Approach for Geometric Nonlinear Sensitivity

Conducted by

Aakash Ravichandran

MSc Student

Supervised by

Philipp Jakobs

Research Associate

Contents

- Introduction
- Nonlinear Strain Energy
- Simpson-Based Formulation
- Results
- Inferences

Contents

- **Introduction**
  - Structural Optimization
  - Geometric Linear Objective
  - Geometric Non-Linear Objective

- Nonlinear Strain Energy
- Simpson-Based Formulation
- Results
- Inferences

Introduction

Structural Optimization

- Objective: Increase stiffness → Minimise strain energy
- Geometric Linear
- Geometric Non-Linear

Introduction

Geometric Linear Objective

- Objective function: $\frac{1}{2}$ KU^2
- Linear Sensitivity Formulation: $\frac{1}{2}\ \mathrm{U}^{\mathrm{T}} \frac{\partial \mathrm{K}}{\partial s} \mathrm{U}$
- U – Displacement Vector, S - Design Variable
- Optimized Structures may be prone to buckling



Introduction

Geometric Non-Linear Objective

- Optimization considering geometric nonlinear behaviour
- Flexible structures
- Objective formulations - **Exact Nonlinear**

  - Linearized End compliance



Introduction

Geometric Non-Linear Objective

- Optimization considering geometric nonlinear behaviour
- Flexible structures
- Objective formulations - Exact Nonlinear

  - **Linearized End compliance**
- Load-displacement history is neglected
- Structure Optimized for the specific selected load
- Results in adverse optimized shape for structures dominated by snap-through buckling



Contents

- Introduction
- **Nonlinear Strain Energy**
  - Trapezoidal approach
  - Proposal - Simpsons integration approach

- Simpson-Based Formulation
- Results
- Inferences

Nonlinear Strain Energy

Trapezoidal approach



- Advantage: Excat Nonlinear representation of structure in the objective function

- Drawback: Time-consuming - number of computations of displacement per optimization iteration increases

Nonlinear Strain Energy

Proposal - Simpsons integration approach



Area = $\frac{1}{6} * x * (4y_1 + y_2)$

- Advantage: 1. Excat up to 3rd degree polynomial

  2. Nonlinear computations per iteration is reduced

- Drawback: 1. Inaccurate for degree greater than 3

Contents

- Introduction
- Nonlinear Strain Energy
- **Simpson-Based Formulation**
  - Methodology
  - Objective Formulation
  - Adjoint Sensitivity Formulation
  - Implementation

- Results
- Inferences

Simpson-Based Formulation

Methodology

- Objective function formulation for Simpson’s approach
- Analytical adjoint sensitivity derivation
- Comparison of Finite Difference (FD) sensitivity of Simpson’s with the Trapezoidal approach
- Verify analytical sensitivity of Simpson’s by comparing against its FD values

Simpson-Based Formulation

Objective Formulation

Area under a quadratic curve by Simpsons = $\frac{1}{6}$ * x * ($4y_1 + y_2$), assuming start point (0,0)

Condition: y_1 must be found at $X_1 = \frac{X_2}{2}$.

For our problem, y is load, F

x is displacement, u

But here, x is taken as the load(F)

y is taken as the displacement(u)

Complementary Strain Energy



Reason: Implemented software capability - Load control only

Potential Issue: Find **[F]** which satisfies **[U_1] =** $\frac{[U_2]}{2}$ for all u values and **[F_n]= λ[F]**

Simpson-Based Formulation

Objective Formulation

Then,

$$\text{Area} = \frac{1}{6} * F_2 * (4U_1 + U_2) \longrightarrow \text{Complimentary Strain Energy}$$

U_2 is the nonlinear displacement for force F_2

U_1 is the nonlinear displacement for force $F_1 = \frac{F_2}{2}$.



$$\text{Strain Energy} = F_2 U_2 - \frac{1}{6} * F_2 * (4U_1 + U_2)$$

$$= [F_2]^T[U_2] - \frac{1}{6} * [F_2]^T * (4[U_1] + [U_2])$$

Simpson-Based Formulation

Adjoint Sensitivity Formulation

Then,

Complimentary $\frac{dJ}{dS} = \left[\frac{4}{6} * F_2^T * K_1^{-1} * \frac{dK_1}{dS} * U_1\right] + \left[\frac{1}{6} * F_2^T * K_2^{-1} * \frac{dK_2}{dS} * U_2\right]$

Adjoint analytical sensitivity equation,

Complimentary $\frac{dJ}{dS} = \left[\frac{4}{6} * (K_1^{-1}F_2)^T * \frac{dK_1}{dS} * U_1\right] + \left[\frac{1}{6} * (K_2^{-1}F_2)^T * \frac{dK_2}{dS} * U_2\right]$



$$\frac{dJ}{dS} = \left[U_2^T * \frac{dK_2}{dS} * U_2\right] - \left[\left[\frac{4}{6} * (K_1^{-1}F_2)^T * \frac{dK_1}{dS} * U_1\right] + \left[\frac{1}{6} * (K_2^{-1}F_2)^T * \frac{dK_2}{dS} * U_2\right]\right]$$

K_1^{-1} and K_2^{-1} - Two inverse computations

Simpson-Based Formulation

Adjoint Sensitivity Formulation

Then,

Complimentary $\frac{dJ}{dS} = \left[\frac{4}{6} * F_2^T * K_1^{-1} * \frac{dK_1}{dS} * U_1\right] + \left[\frac{1}{6} * F_2^T * K_2^{-1} * \frac{dK_2}{dS} * U_2\right]$

Adjoint analytical sensitivity equation,

Complimentary $\frac{dJ}{dS} = \left[\frac{4}{6} * (K_1^{-1}F_2)^T * \frac{dK_1}{dS} * U_1\right] + \left[\frac{1}{6} * (K_2^{-1}F_2)^T * \frac{dK_2}{dS} * U_2\right]$



$$\boldsymbol{\frac{dJ}{dS} = \left[U_2^T * \frac{dK_2}{dS} * U_2\right] - \left[\left[\frac{4}{6} * (K_1^{-1}F_2)^T * \frac{dK_1}{dS} * U_1\right] + \left[\frac{1}{6} * (U_2)^T * \frac{dK_2}{dS} * U_2\right]\right]}$$

K_1^{-1} and K_2^{-1} - **Two inverse** computations

Simpson-Based Formulation

Implementation

- Implemented in self-developed software
- Capabilities
  1. 2D - 1st and 2nd order Structural Analysis
  2. Dynamic Modal Analysis
  3. Linearized Buckling analysis
- Available as
  1. Website
  2. PyPi module
- Programming language – Python
- Element – 2nd order Bernoulli beam element



Simpson-Based Formulation

Implementation

- Implemented in self-developed software
- Capabilities
  1. 2D - 1st and 2nd order Structural Analysis
  2. Dynamic Modal Analysis
  3. Linearized Buckling analysis
- Available as
  1. Website
  2. PyPi module
- Programming language – Python
- Element – 2nd order Bernoulli beam element



Simpson-Based Formulation

Implementation

- Implemented in self-developed software
- Capabilities
  1. 2D - 1st and 2nd order Structural Analysis
  2. Dynamic Modal Analysis
  3. Linearized Buckling analysis
- Available as
  1. Website
  2. PyPi module
- Programming language – Python
- Element – **2nd order Bernoulli beam element**



Contents

- Introduction
- Nonlinear Strain Energy
- Simpson-Based Formulation
- **Results**
  - Models
  - Load Displacement Curve
  - FD Sensitivity - Trapezoidal - Reference
  - FD Sensitivity - Linearized End Compliance
  - Simpsons - Adjoint vs FD Sensitivity
- Inferences

Results

Models

Model 1



Support condition: Both Fixed

Design variable : Moment of inertia

Discretization : 7 elements per beam

Area : 0.09

Moment of inertia: 0.000675

Model 2



Support condition: Fixed and Hinged

Design variable : Moment of inertia

Discretization : 7 elements per beam

Area : 0.09

Moment of inertia: 0.000675

Results

Models

Model 1



Support condition: Both Fixed

Design variable : Moment of inertia

Discretization : 7 elements per beam

Area : 0.09

Moment of inertia: 0.000675

Model 2



Support condition: Fixed and Hinged

Design variable : Moment of inertia

Discretization : 7 elements per beam

Area : 0.09

Moment of inertia: 0.000675

Results

Models

Model 1



Support condition: Both Fixed

Design variable : Moment of inertia

Discretization : 7 elements per beam

Area : 0.09

Moment of inertia: 0.000675

Model 2



Support condition: Fixed and Hinged

Design variable : Moment of inertia

Discretization : 7 elements per beam

Area : 0.09

Moment of inertia: 0.000675

Results

Load Displacement Curve

Model 1



Support condition: Both Fixed

Design variable : Moment of inertia

Discretization : 7 elements per beam

Area : 0.09

Moment of inertia: 0.000675

Model 2



Support condition: Fixed and Hinged

Design variable : Moment of inertia

Discretization : 7 elements per beam

Area : 0.09

Moment of inertia: 0.000675

Results

FD Sensitivity - Trapezoidal Approach - Reference

Model 1



Objective: Green region

Divisions: 10

Model 2



Objective: Green region

Divisions: 10

Results

FD Sensitivity - Linearized End Compliance

Model 1



Objective: Green region

Divisions: 1

Average Error in sensitivity: 43.11 %

Model 2



Objective: Green region

Divisions: 1

Average Error in sensitivity: 54.96 %

Results

FD Sensitivity - Simpson's Approach

Model 1



Objective: Green region

Divisions: 2

Average Error in sensitivity: 9.78 %

Model 2



Objective: Green region

Divisions: 2

Average Error in sensitivity: 9.03 %

Results

Simpsons - Adjoint vs FD Sensitivity

Element	Analytical Simpsons	Numerical Simpsons	Relative Error (%)
1	-6.85E-05	-6.85E-05	0
2	-1.64E-05	-1.64E-05	0.03
3	-6.44E-06	-6.44E-06	0.04
4	-5.05E-05	-5.05E-05	0.01
5	-9.71E-05	-9.71E-05	0.01
6	-9.08E-05	-9.08E-05	0
7	-3.68E-05	-3.68E-05	0.01
8	-2.16E-06	-2.16E-06	0.08
9	-5.53E-05	-5.53E-05	0
10	-1.75E-04	-1.75E-04	0.01
11	-2.40E-04	-2.40E-04	0
12	-5.42E-05	-5.42E-05	0.01
13	-3.38E-05	-3.38E-05	0
14	-2.47E-04	-2.47E-04	0

$$\frac{dJ}{dS} = \left[U_2^T * \frac{dK_2}{dS} * U_2\right] - \left[\left[\frac{4}{6} * (K_1^{-1}F_2)^T * \frac{dK_1}{dS} * U_1\right] + \left[\frac{1}{6} * (K_2^{-1}F_2)^T * \frac{dK_2}{dS} * U_2\right]\right]$$

- Model - 1 Avg error - 0.01%
- Model - 2 Avg error - 0.08%

Contents

- Introduction
- Nonlinear Strain Energy
- Simpson-Based Formulation
- Results
- **Inferences**

Inference

1. Simpson's approach is efficient than the trapezoidal approach.

2. With twice the increase in computational cost, the error can be decreased up to 50 percent.

3. Complimentary strain energy-based formulation - Not applicable to snap-through problems

Thank You