


Module 2 – Syntax Analysis

Bottom Up Parsing

Parsing Methods



Handle & Handle pruning

- **Handle:** A “handle” of a string is a substring of the string that matches the right side of a production, and whose reduction to the non terminal of the production is one step along the **reverse of rightmost derivation**.
- **Handle pruning:** The process of discovering a handle and **reducing it to appropriate left hand side non terminal** is known as handle pruning.

$E \rightarrow E + E$

$E \rightarrow E * E$ String: id1+id2*id3

$E \rightarrow id$

Rightmost Derivation

E

E+E

E+E*E

E+E*id3

E+id2*id3

id1+id2*id3

Right sentential form	Handle	Production
id1+id2*id3		

Shift reduce parser

- The shift reduce parser performs following basic operations:

1. **Shift:** Moving of the symbols from **input buffer onto the stack**, this action is called shift.
2. **Reduce:** If handle appears on the top of the stack then **reduction of it by appropriate rule** is done. This action is called reduce action.
3. **Accept:** If **stack contains start symbol only and input buffer is empty** at the same time then that action is called accept.
4. **Error:** A situation in which parser **cannot either shift or reduce** the symbols, it cannot even perform accept action then it is called error action.

Example: Shift reduce parser

Grammar:

$E \rightarrow E + T \mid T$

$T \rightarrow T * F \mid F$

$F \rightarrow \text{id}$

String: $\text{id} + \text{id} * \text{id}$

Consider the following grammar-

$$S \rightarrow T L ;$$
$$T \rightarrow \text{int} \mid \text{float}$$
$$L \rightarrow L , \text{id} \mid \text{id}$$

Parse the input string `int id , id ;` using a shift-reduce parser.

Operator precedence parsing

- **Operator Grammar:** A Grammar in which there is no ϵ in RHS of any production or no adjacent non terminals is called operator grammar.
- Example: $E \rightarrow \textcolor{red}{EAE} \mid (E) \mid \text{id}$
 $A \rightarrow + \mid * \mid -$
- Above **grammar is not operator grammar** because right side **EAE** has consecutive non terminals.
- In operator precedence parsing we define following disjoint relations:

Relation	Meaning
$a < \cdot b$	a “yields precedence to” b
$a = b$	a “has the same precedence as” b
$a \cdot > b$	a “takes precedence over” b

Precedence & associativity of operators

Operator	Precedence	Associative
\uparrow	1	right
$*, /$	2	left
$+, -$	3	left

Steps of operator precedence parsing

1. Find Leading and trailing of non terminal
2. Establish relation
3. Creation of table
4. Parse the string

Leading & Trailing

Leading:- Leading of a non terminal is the **first terminal or operator** in production of that non terminal.

Trailing:- Trailing of a non terminal is the **last terminal or operator** in production of that non terminal.

Example: $E \rightarrow E + T \mid T$

$T \rightarrow T * F \mid F$

$F \rightarrow \text{id}$

Non terminal	Leading	Trailing
E		
T		
F		

Rules to establish a relation

1. For $a = b$, $\Rightarrow aAb$, where A is ϵ or a single non terminal [e.g : (E)]
2. $a < \cdot b \Rightarrow Op . NT$ then $Op < . Leading(NT)$ [e.g : +T]
3. $a \cdot > b \Rightarrow NT . Op$ then $(Trailing(NT)) \cdot > Op$ [e.g : E+]
4. $\$ < \cdot$ Leading (start symbol)
5. Trailing (start symbol) $\cdot > \$$

Example: Operator precedence parsing

Step 1: Find Leading & Trailing of NT

Nonterminal	Leading	Trailing
E	{+,*,id}	{+,*,id}
T	{*,id}	{*,id}
F	{id}	{id}

$E \rightarrow E+T \mid T$
 $T \rightarrow T * F \mid F$
 $F \rightarrow id$

Step 2: Establish Relation

$a < \cdot b$

$Op \cdot NT \mid Op < \cdot Leading(NT)$

$+T \mid + < \cdot \{*, id\}$

$*F \mid * < \cdot \{id\}$

Step3: Creation of Table

	+	*	id	\$
+				
*				
id				
\$				

Example: Operator precedence parsing

Step 1: Find Leading & Trailing of NT

Nonterminal	Leading	Trailing
E	{+,*,id}	{+,*,id}
T	{*,id}	{*,id}
F	{id}	{id}

$E \rightarrow E + T \mid T$
 $T \rightarrow T * F \mid F$
 $F \rightarrow id$

Step2: Establish Relation

$a \cdot > b$

$NT \cdot Op \mid (Trailing(NT)) \cdot > Op$

$E + \mid \{+, *, id\} \cdot > +$

$T * \mid \{*, id\} \cdot > *$

Step3: Creation of Table

	+	*	id	\$
+		$< \cdot$	$< \cdot$	
*			$< \cdot$	
id				
\$				

Example: Operator precedence parsing

Step 1: Find Leading & Trailing of NT

Nonterminal	Leading	Trailing
E	{+,*,id}	{+,*,id}
T	{*,id}	{*,id}
F	{id}	{id}

$E \rightarrow E + T \mid T$
 $T \rightarrow T * F \mid F$
 $F \rightarrow id$

Step 2: Establish Relation

$\$ < \cdot$ Leading (start symbol)

$\$ < \cdot \{+, *, id\}$

Trailing (start symbol) $\cdot > \$$

$\{+, *, id\} \cdot > \$$

Step 3: Creation of Table


	+	*	id	\$
+	$\cdot >$	$< \cdot$	$< \cdot$	
*	$\cdot >$	$\cdot >$	$< \cdot$	
id	$\cdot >$	$\cdot >$		
\$				

Operator precedence function

1. Create functions f_a and g_a for each a that is terminal or \$.

$E \rightarrow E+T \mid T$
 $T \rightarrow T * F \mid F$
 $F \rightarrow id$

$a = \{+, *, id\} \text{ or } \$$



Operator precedence function

- Partition the symbols in as many as groups possible, in such a way that f_a and g_b are in the same group if $a = b$.

g_{id}

f_{id}

f_*

g_*

g_+

f_+


$f_\$$

$g_\$$

	+	*	id	\$
+	$\cdot >$	$< \cdot$	$< \cdot$	$\cdot >$
*	$\cdot >$	$\cdot >$	$< \cdot$	$\cdot >$
id	$\cdot >$	$\cdot >$		$\cdot >$
\$	$< \cdot$	$< \cdot$	$< \cdot$	

Operator precedence function

- if $a < \cdot b$, place an edge from the group of g_b to the group of f_a
- if $a \cdot > b$, place an edge from the group of f_a to the group of g_b




<i>g</i>					
<i>f</i>		+	*	id	\$
	+	·>	<·	<·	·>
	*	·>	·>	<·	·>
	id	·>	·>		·>
	\$	<·	<·	<·	

$$\begin{array}{ll}
 f_+ \cdot > g_+ & f_+ \rightarrow g_+ \\
 f_* \cdot > g_+ & f_* \rightarrow g_+ \\
 f_{id} \cdot > g_+ & f_{id} \rightarrow g_+ \\
 f_\$ < \cdot g_+ & f_\$ \leftarrow g_+
 \end{array}$$

Operator precedence function

- if $a < \cdot b$, place an edge from the group of g_b to the group of f_a
- if $a \cdot > b$, place an edge from the group of f_a to the group of g_b




<i>g</i>					
<i>f</i>		+	*	id	\$
	+	·>	<·	<·	·>
	*	·>	·>	<·	·>
	id	·>	·>		·>
	\$	<·	<·	<·	

$$\begin{array}{ll}
 f_+ < \cdot g_* & f_+ \leftarrow g_* \\
 f_* \cdot > g_* & f_* \rightarrow g_* \\
 f_{id} \cdot > g_* & f_{id} \rightarrow g_* \\
 f_\$ < \cdot g_* & f_\$ \leftarrow g_*
 \end{array}$$

Operator precedence function

- if $a < \cdot b$, place an edge from the group of g_b to the group of f_a
- if $a \cdot > b$, place an edge from the group of f_a to the group of g_b




<i>g</i>					
		+	*	id	\$
<i>f</i>	+	$\cdot >$	$< \cdot$	$< \cdot$	$\cdot >$
	*	$\cdot >$	$\cdot >$	$< \cdot$	$\cdot >$
	id	$\cdot >$	$\cdot >$		$\cdot >$
	\$	$< \cdot$	$< \cdot$	$< \cdot$	

$$\begin{array}{ll}
 f_+ < \cdot g_{id} & f_+ \leftarrow g_{id} \\
 f_* < \cdot g_{id} & f_* \leftarrow g_{id} \\
 f_{\$} < \cdot g_{id} & f_{\$} \leftarrow g_{id}
 \end{array}$$

Operator precedence function

3. if $a < \cdot b$, place an edge from the group of g_b to the group of f_a
 if $a \cdot > b$, place an edge from the group of f_a to the group of g_b




<i>g</i>					
<i>f</i>		+	*	id	\$
	+	·>	<·	<·	·>
	*	·>	·>	<·	·>
	id	·>	·>		·>
	\$	<·	<·	<·	

$$\begin{array}{ll}
 f_+ < \cdot g_\$ & f_+ \rightarrow g_\$ \\
 f_* < \cdot g_\$ & f_* \rightarrow g_\$ \\
 f_{id} < \cdot g_\$ & f_{id} \rightarrow g_\$
 \end{array}$$


Operator precedence function

	+	*	id	\$
f				
g				




4. If the constructed graph has a cycle then no precedence functions exist. When there are no cycles collect the length of the longest paths from the groups of f_a and g_b respectively.

Operator precedence function




	+	*	id	\$
<i>f</i>	2			
<i>g</i>				

Operator precedence function



	+	*	id	\$
<i>f</i>	2			
<i>g</i>	1			


Operator precedence function



	+	*	id	\$
<i>f</i>	2	4		
<i>g</i>	1			


Operator precedence function

	+	*	id	\$
<i>f</i>	2	4		
<i>g</i>	1	3		




Operator precedence function

	+	*	id	\$
<i>f</i>	2	4	4	
<i>g</i>	1	3		



Operator precedence function



	+	*	id	\$
<i>f</i>	2	4	4	
<i>g</i>	1	3	5	