

```

# package to handle thread-base parallelism
import threading
# package to handle time related functions
import time

print("imported some packages")

    imported some packages

# represents a distributed database system
class DatabaseNode:
    # initialization method
    def __init__(self, node_id):
        # unique identifier for each node
        self.node_id = node_id
        # data stored locally within the node
        self.data = {}
        #list of replica nodes
        self.replica_nodes = []


    # stimulates a write operation on the database node
    def write_data(self, key, value):
        print(f"Node {self.node_id}: Write Operation - Key: {key}, Value: {value}")
        self.data[key] = value

        # iterates over each replica node to replicate the write operation
        for replica_node in self.replica_nodes:
            replica_node.receive_replication(key, value)

    # receive replicated data from other nodes:
    def receive_replication(self, key, value):
        print(f"Node {self.node_id}: Replication - Key: {key}, Value: {value}")
        self.data[key] = value

    # simulates a read operation on the database node
    def read_data(self, key):
        print(f"Node {self.node_id}: Read Operation - Key: {key}, Value: {self.data.get(key, 'Not found')}")

print("created the node that represents the distributed database system")

 created the node that represents the distributed database system

# simulates a continuous stream of write operations on a database node
def simulate_writes(node):
    # used to generate unique keys for write operation
    i = 0
    # continuous loop
    while True:
        node.write_data(f" k - {i}", f" v - {i}")
        # ensure unique key-value pair
        i += 1
        # pause execution for 2 seconds before the next iteration
        time.sleep(2)

print("defined the methods to handle simulating a continuous stream of write operations")

    defined the methods to handle simulating a continuous stream of write operations

# create two node instances
#node1 = DatabaseNode(1)
#node2 = DatabaseNode(2)

# set up replication between the two nodes
#node1.replica_nodes.append(node2)
#node2.replica_nodes.append(node1)

print("initialized the node instances and setup node replication")

    initialized the node instances and setup node replication

# start write operations for node1 in a separate thread
#threading.Thread(target=simulate_writes, args=(node1,)).start()

```

```
# initiates a read operation on node1
#node1.read_data("key0")
#pause 5 seconds to all write operations to be replicated between the nodes before reading again
time.sleep(5)
# performs a similar read operation on node2, allow for replication of write operations between the nodes
#node2.read_data("key0")
```