

## CSS Cheat sheet

# for id

. for accessing class

> for accessing child

tagName[attribute='value']

```
...
::before
▼ <form id="searchbox" method="get" action="http://automationpractice.com/index.php?controller=search" == $0
  <input type="hidden" name="controller" value="search">
  <input type="hidden" name="orderby" value="position">
  <input type="hidden" name="orderby" value="position">
  ...
```

form#searchbox

```
...
::before
▼ <form id="searchbox" method="get" action="http://automationpractice.com/index.php?controller=search">
  <input type="hidden" name="controller" value="search">
  ...
```

form#searchbox>input

```
...
Search value autocomplete="off" >
▼ <button type="submit" name="submit_search" class="btn btn-default button-search" == $0
  ::before
  <span>Search</span>
  </button>
  </form>
  ::after
</div>
html #index #page div #header div div.container div.row div#search_block_top.col-sm-4.clearfix form#searchbox button.btn.btn-default.button-search
button[class='btn btn-default button-search'] Copy (Ctrl+C) 1 of 1
```

button[class='btn btn-default button-search']

```
...
Search value autocomplete="off" >
▼ <button type="submit" name="submit_search" class="btn btn-default button-search" == $0
  ::before
  <span>Search</span>
  </button>
  </form>
  ::after
</div>
html #index #page div #header div div.container div.row div#search_block_top.col-sm-4.clearfix form#searchbox button.btn.btn-default.button-search
button.btn.btn-default.button-search 1 of 1
```

button.btn.btn-default.button-search

.btn.btn-default.button-search

```
▼<div align="center">
```

```
<input type="image" name="login" value="Login" src="/images/btn_signin.gif" width="58" height="17"  
alt="Sign-In" border="0"> == $0
```

```
</div>
```

```
input[name='login']
```

```
input[name='login'],input[alt='Sign-In'] //or
```

```
input[name='login'][alt='Sign-In']
```

```
input[src*='signin'] //Contains
```

```
input[src^='/images'] //Starts-with
```

```
input[src$='.gif'] //Ends-with
```