

Naseeb ulah

Chem 18/11/13

Chemical engineering

27-11-2020

①

Q No: 3

$$T_1 = 10.0 \text{ kg}$$

$$P_1 = 20 \text{ bar}$$

$$V_1 = 1.0 \text{ m}^3$$

$$P_2 = 100 \text{ bar}$$

$$P V^{1.5} \text{ relation} = P V^{1.5} = \text{constant}$$

a) $\hat{w} = ?$

$$P = \frac{100 \text{ bar} / 100 \text{ KPa}}{1 \text{ bar}} = 10 \text{ Mpa}$$

$$\hat{V}_2 = ?$$

$$P_1 V_1^{1.5} = P_2 V_2^{1.5} \Rightarrow \hat{V}_2 = \frac{P_1 V_1^{1.5}}{P_2}$$

$$\hat{V}_2 = \left[\frac{2 \text{ Mpa} (1.0 \text{ m}^3)^{1.5}}{10 \text{ Mpa}} \right]^{1/1.5} \Rightarrow \hat{V}_2 = (0.2 \times 1.0^{1.5})^{1/1.5} \text{ m}^3/\text{kg}$$

$$= (0.2 \times 0.0316)^{1/1.5} = (0.2 \times 0.0316)^{0.663}$$

$$\hat{V}_2 = 0.0342 \text{ m}^3/\text{kg}$$

$$\hat{w} = \int_{0.1}^{0.0342} P_2 \cdot d\hat{V} = - \int_{0.1}^{0.0342} P \cdot d\hat{V}$$

2

$$P v^{1.5} = P_1 v_1^{1.5} \Rightarrow P = \frac{P_1 v_1^{1.5}}{v^{1.5}}$$

$$P = \frac{2 \text{ MPa}}{\left(\frac{0.1 \text{ m}^3}{\text{kg}} \right)^{1.5}} \left(\frac{1 \text{ kg}}{0.1 \text{ m}^3} \right)^{1.5}$$

$$P = \frac{0.0632}{v^{1.5}} \text{ MPa}$$

$$w = \int_{0.1}^{0.0342} \frac{0.0632}{v^{1.5}} dv$$

$$= \left[\frac{-0.0632}{-0.5} \frac{1}{v^{0.5}} \right]_{0.1}^{0.0342}$$

$$= \frac{-0.0632}{-0.5} \left[\frac{1}{0.0342^{0.5}} - \frac{1}{0.1^{0.5}} \right]$$

$$= \frac{0.2838 \text{ MPa} \cdot \text{m}^3}{\text{kg}} \left| \frac{1000 \text{ kPa}}{1 \text{ MPa}} \right| \left| \frac{1 \text{ kJ}}{1 \text{ kPa} \cdot \text{m}^3} \right|$$

$$w = 283.8 \text{ kJ/kg}$$

b) $q = ?$

$$\Delta u = q + w$$

At state 1, $P_1 = 2 \text{ MPa}$, $T_1 = 213.6^\circ \text{C}$

$u_1 = ?$

$u_1 = (\text{kJ/kg})$
2600.3
u_1
2628.3

$T(^{\circ}\text{C})$
212.4
213.6
225

Naseeb ulah
 Chem 8/10/13
 Chemical engineering
 27-11-2020

①

Q No: 3

$$T_1 = 10.0 \text{ kg}$$

$$P_1 = 20 \text{ bar}$$

$$V_1 = 1.0 \text{ m}^3$$

$$P_2 = 100 \text{ bar}$$

$$P V^{1.5} = \text{constant}$$

a) $\hat{w} = ?$

$$P = \frac{100 \text{ bar} / 100 \text{ kPa}}{1 \text{ bar}} = 10 \text{ MPa}$$

$$\hat{V}_2 = ?$$

$$P_1 V_1^{1.5} = P_2 V_2^{1.5} \Rightarrow \hat{V}_2 = \frac{P_1 V_1^{1.5}}{P_2}$$

$$\hat{V}_2 = \left[\frac{2 \text{ MPa} (1.0 \text{ m}^3)^{1.5}}{10 \text{ MPa}} \right]^{1/1.5} \Rightarrow \hat{V}_2 = (0.2 \times 1.0^{1.5})^{1/1.5} \text{ m}^3/\text{kg}$$

$$= (0.2 \times 0.0316)^{1/1.5} = (0.2 \times 0.0316)^{0.663}$$

$$\hat{V}_2 = 0.0342 \text{ m}^3/\text{kg}$$

$$\hat{w} = \int_{0.1}^{0.0342} P_2 d\hat{V} = - \int_{0.1}^{0.0342} P d\hat{V}$$

2

$$P v^{1.5} = P_1 v_1^{1.5} \Rightarrow P = \frac{P_1 v_1^{1.5}}{v^{1.5}}$$

$$P = \frac{2 \text{ MPa}}{\left(\frac{\text{kg}}{\text{m}^3} \right)^{1.5}} \left(\frac{\text{kg}}{\text{m}^3} \right)^{1.5}$$

$$P = \frac{0.0632}{v^{1.5}} \text{ MPa}$$

$$w^u = \int_{0.1}^{0.0342} \frac{0.0632}{v^{1.5}} dv$$

$$= \left[\frac{-0.0632}{-0.5} v^{-0.5} \right]_{0.1}^{0.0342}$$

$$= \frac{-0.0632}{-0.5} \left[\frac{1}{0.0342^{0.5}} - \frac{1}{0.1^{0.5}} \right]$$

$$= \frac{0.2838 \text{ MPa} \cdot \text{m}^3}{\text{kg}} \left| \frac{1000 \text{ kPa}}{1 \text{ MPa}} \right| \frac{1 \text{ kJ}}{1 \text{ kPa} \cdot \text{m}^3}$$

$$w^u = 283.8 \text{ kJ/kg}$$

b) $q = ?$

$$\Delta u = q^v + w^u$$

At state 1, $P_1 = 2 \text{ MPa}$, $T_1 = 213.6^\circ \text{C}$

$u_1 = ?$

$u_1 = (\text{kJ/kg})$
2600.3
u_1
2628.3

$T(^{\circ}\text{C})$
212.4
213.6
225

$$u_1 = 2602.96 \text{ kJ/kg}$$

$$v_2 = 0.0342 \text{ m}^3/\text{kg}$$

At state 2, $P_2 = 10 \text{ MPa}$

$$\frac{\hat{u}_2 \text{ (kJ/kg)}}{u_2}$$

$$3045.8$$

$$\hat{u}_2$$

$$3144.5$$

$$\frac{\hat{v}_2 \text{ (m}^3/\text{kg)}}{v_2}$$

$$0.0328$$

$$0.0342$$

$$0.0356$$

$$\hat{u}_2 = 3095.15 \text{ kJ/kg}$$

$$\Rightarrow \Delta \hat{u} = \hat{u}_2 - \hat{u}_1$$

$$= (3095.15 - 2602.97) \frac{\text{kJ}}{\text{kg}}$$

$$\Delta \hat{u} = 492.18 \text{ kJ/kg}$$

$$\Delta \hat{u} = q + \hat{w}$$

$$\hat{q} = \Delta \hat{u} + \hat{w}$$

$$\hat{q} = (492.18 - 283.8) \text{ kJ/kg}$$

$$\hat{q} = 492.38 \frac{\text{kJ}}{\text{kg}}$$

$$\hat{q}_1 = 208.38 \text{ kJ/kg}$$

Q. No. 2

(4)

$$p = 7 \text{ bar}$$

$$h = 2600 \text{ kJ/kg}$$

$$v = ?$$

$$\hat{v} = ?$$

$$u = ?$$

Sol

$$\textcircled{1} \quad \hat{h} = hf + u \cdot hf_g$$
$$2600 = 697.1 + u(2064.9)$$
$$2600 - 697.1 = u(2064.9)$$

$$\frac{1902.9}{2064.9} = u$$

$$u = 0.921$$

$$\textcircled{2} \quad \hat{v} = v_f + u \cdot vfg$$
$$= 0.001108 + (0.921)(0.0273 - 0.001108)$$
$$= 0.001108 + (0.921)(0.271892)$$
$$= 0.001108 + 0.25041$$
$$= 0.2515 \text{ m}^3/\text{kg}$$

$$\textcircled{3} \quad \hat{u} = uf + u \cdot uf_g$$
$$= 696.3 + (0.921)(2571.1 - 696.3)$$
$$= 696.3 + (0.921)(1874.8)$$
$$= 696.3 + 1726.6908$$
$$= 2420 \text{ kJ/kg}$$

$$\textcircled{4} \quad \text{So,} \quad \hat{v} = 0.2515 \text{ m}^3/\text{kg}$$


$$\hat{u} = 2420 \text{ kJ/kg}$$

Q. No. 1

(5)

1) System

System refers to the subject matter of analysis. Thermodynamic system or system refers to definite quantity of matter, enclosed by a boundary, on which we focus our attention for thermodynamic analysis.



2) Surroundings

This part of the universe other than the system is called surroundings. As shown Fig 0.1.

3) Adiabatic process

No heat transfer

through boundaries of the system.

4) Isolated process

No mass or heat energy

transfer with environment.

5) Extensive property

Depend upon the mass of

System e.g. mass, volume, internal energy
Enthalpy, Entropy.