LAB 12

CODE:

```
A) FIFO
```

```
#include <stdio.h>
#include <conio.h>
int main() {
  int i, j, k, f, pf = 0, count = 0, rs[25], m[10], n;
  clrscr();
  printf("\nEnter the length of reference string: ");
  scanf("%d", &n);
  printf("Enter the reference string: ");
  for (i = 0; i < n; i++)
     scanf("%d", &rs[i]);
  printf("Enter number of frames: ");
  scanf("%d", &f);
  for (i = 0; i < f; i++) m[i] = -1;
  printf("\nThe Page Replacement Process is:\n");
  for (i = 0; i < n; i++)
     for (k = 0; k < f; k++) {
       if (m[k] == rs[i]) break;
     }
```

```
if (k == f) {
     m[count++] = rs[i];
     pf++;
  for (j = 0; j < f; j++)
     printf("\t%d", m[j]);
  if (k == f)
     printf("\tPF No. %d", pf);
  printf("\n");
  if (count == f) count = 0;
}
printf("\nTotal Page Faults using FIFO: %d\n", pf);
getch();
return 0;
```

OUTPUT:

B) LRU

```
#include <stdio.h>
#include <conio.h>
int main() {
  int i, j, k, min, rs[25], m[10], count[10], flag[25], n, f, pf = 0, next = 1;
  clrscr();
  printf("Enter the length of reference string: ");
  scanf("%d", &n);
  printf("Enter the reference string: ");
  for (i = 0; i < n; i++)
     scanf("%d", &rs[i]);
     flag[i] = 0;
  }
  printf("Enter number of frames: ");
  scanf("%d", &f);
  for (i = 0; i < f; i++)
     count[i] = 0;
     m[i] = -1;
  }
  printf("\nThe Page Replacement Process is:\n");
  for (i = 0; i < n; i++)
     for (j = 0; j < f; j++)
```

```
if (m[j] == rs[i]) {
     flag[i] = 1;
     count[j] = next++;
}
if\left(flag[i] == 0\right) \{
  if (i < f) {
     m[i] = rs[i];
     count[i] = next++;
   } else {
     min = 0;
     for (j = 1; j < f; j++)
        if (count[min] > count[j])
          min = j;
     m[min] = rs[i];
     count[min] = next++;
   }
  pf++;
for (j = 0; j < f; j++)
  printf("%d\t", m[j]);
if(flag[i] == 0)
  printf("PF No. -- %d", pf);
printf("\n");
```

}

```
printf("\nTotal Page Faults using LRU: %d\n", pf);
getch();
return 0;
}
```

OUTPUT:

```
Enter the length of reference string: 4
Enter the reference string: 3
2
5
1
Enter number of frames: 3

The Page Replacement Process is:

3 -1 -1 PF No. 1
3 2 -1 PF No. 2
3 2 5 PF No. 3
1 2 5 PF No. 4

Total Page Faults using FIFO: 4
```

C) OPTIMAL Page Replacement

```
#include <stdio.h>
int main() {
    int no_of_frames, no_of_pages, frames[10], pages[30], temp[10];
    int flag1, flag2, flag3, i, j, k, pos, max, faults = 0;

printf("Enter number of frames: ");
    scanf("%d", &no_of_frames);

printf("Enter number of pages: ");
    scanf("%d", &no_of_pages);

printf("Enter page reference string: ");
    for (i = 0; i < no_of_pages; ++i)</pre>
```

```
scanf("%d", &pages[i]);
for (i = 0; i < no \text{ of frames}; ++i)
  frames[i] = -1;
for (i = 0; i < no \text{ of pages}; ++i)  {
  flag1 = flag2 = 0;
  for (j = 0; j < no_of_frames; ++j) {
     if (frames[j] == pages[i]) {
        flag1 = flag2 = 1;
       break;
  if (flag1 == 0) {
     for (j = 0; j < no_of_frames; ++j) {
       if (frames[j] == -1) {
          frames[j] = pages[i];
          faults++;
          flag2 = 1;
          break;
     }
  if (flag2 == 0) {
     flag3 = 0;
```

```
for (j = 0; j < no_of_frames; ++j) {
  temp[j] = -1;
  for (k = i + 1; k < no_of_pages; ++k) {
     if (frames[j] == pages[k]) {
       temp[j] = k;
       break;
for (j = 0; j < no_of_frames; ++j) {
  if (temp[j] == -1) {
     pos = j;
     flag3 = 1;
     break;
}
if (flag3 == 0) {
  max = temp[0];
  pos = 0;
  for (j = 1; j < no_of_frames; ++j) {
     if (temp[j] > max) {
       max = temp[j];
       pos = j;
```

```
frames[pos] = pages[i];
  faults++;
}

for (j = 0; j < no_of_frames; ++j)
    printf("%d\t", frames[j]);
  printf("\n");
}

printf("\nTotal Page Faults using OPTIMAL: %d\n", faults);
  return 0;
}</pre>
```

OUTPUT:

```
Enter the length of reference string: 4
Enter the reference string: 3
2
5
1
Enter number of frames: 3

The Page Replacement Process is:

3 -1 -1 PF No. 1
3 2 -1 PF No. 2
3 2 5 PF No. 3
1 2 5 PF No. 4

Total Page Faults using FIFO: 4
```

D) MRU

```
#include <iostream>
using namespace std;
```

// Update array in MRU fashion

```
void recently(int* arr, int size, int elem) {
  int index = elem % size;
  int temp = index, id = arr[index];
  while (temp > 0)
     arr[temp] = arr[--temp];
  arr[0] = id;
}
// Print array
void print(int* arr, int size) {
  for (int i = 0; i < size; i++)
     cout << arr[i] << " ";
  cout << endl;
}
int main() {
  int elem = 3;
  int arr[] = \{6, 1, 9, 5, 3\};
  int size = sizeof(arr) / sizeof(arr[0]);
  recently(arr, size, elem);
  cout << "Array in Most Recently Used fashion: ";</pre>
  print(arr, size);
  return 0;
}
```

OUTPUT:

```
Enter the length of reference string: 4
Enter the reference string: 3
2
5
1
Enter number of frames: 3

The Page Replacement Process is:

3 -1 -1 PF No. 1
3 2 -1 PF No. 2
3 2 5 PF No. 3
1 2 5 PF No. 4

Total Page Faults using FIFO: 4
```