# Lab Exercise 5- Building a Docker Image for an HTML App Using Nginx

Name - Sujal Bhandari

SAP\_ID - 500106865

Roll\_No - R2142220181

#### 1. Setup

You will need:

- Docker installed on your machine.
- A simple HTML file for the app.

# 2. Step 1: Create the HTML File

Create a directory for your HTML app and place an index.html file in it.

```
mkdir nginx-html-app

cd nginx-html-app
```

Inside the nginx-html-app directory, create the HTML file.

touch index.html

```
sujal@HP-Victus MINGW64 ~/OneDri
$ cd nginx-html-app/
sujal@HP-Victus MINGW64 ~/OneDri
$ touch index.html
```

Edit the index.html file with the following content (or any custom HTML content you want):

```
<!DOCTYPE html>
<html>
<head>
<title>Welcome to My Nginx HTML App</title>
```

```
</head>
<body>
<h1>Hello, Nginx Docker!</h1>
This is a simple HTML app served by Nginx in a Docker container.
</body>
</html>
```

# 3. Step 2: Create a Dockerfile

In the same directory, create a Dockerfile. This file will define how to build the Docker image using Nginx as the base image.

touch Dockerfile

```
sujal@HP-Victus MINGW64 ~/
$ touch Dockerfile
sujal@HP-Victus MINGW64 ~/
$ nano Dockerfile
```

Edit the Dockerfile and add the following content:

```
FROM nginx:latest

COPY index.html /usr/share/nginx/html/

EXPOSE 80
```

```
MINGW64:/c/Users/sujal/OneDrive/Desktop/Sem_5
GNU nano 7.1
FROM nginx:latest
COPY index.html /usr/share/nginx/html/
EXPOSE 80
```

#### 4. Step 3: Build the Docker Image

Now that you have the Dockerfile and index.html, it's time to build the Docker image. Run the following command to build the image, giving it a tag (e.g., nginx-html-app):

docker build -t nginx-html-app.

Docker will use the Nginx base image, copy your index.html into the appropriate directory, and build the image.

#### 5. Step 4: Run the Docker Container

After building the image, you can run the container with the following command:


docker run -d -p 8080:80 nginx-html-app

```
sujal@HP-Victus MINGW64 ~/OneDrive/Desktop/Sem_5/CnD_Security_Lab/Exp
$ docker run -d -p 8080:80 nginx-html-app
416596fa46a6e23d09c29cf7421fa277cfe353f10c8bb97670605f2f2b2bd716
```

This command runs the container in detached mode (-d) and maps port 8080 on your host machine to port 80 inside the container, where Nginx is serving your HTML app.

### 6. Step 5: Verify

Open a browser and go to http://localhost:8080. You should see your HTML page with the message "Hello, Nginx Docker!".



# Hello, Nginx Docker!

This is a simple HTML app served by Nginx in a Docker container.

## 7. Step 6: Stop and Remove the Container

Once you're done, you can stop and remove the container:

```
docker ps # to see running containers

docker stop <container-id>

docker rm <container-id>
```

sujal@HP-Victus MINGW64 ~/C
\$ docker ps -a
CONTAINER ID IMAGE
416596fa46a6 nginx-html-a
sujal@HP-Victus MINGW64 ~/C
\$ docker stop 41659
41659
sujal@HP-Victus MINGW64 ~/C
\$ docker rm 41659
41659